

# Package ‘concordexR’

April 15, 2025

**Title** Identify Spatial Homogeneous Regions with concordex

**Version** 1.8.0

**Description** Spatial homogeneous regions (SHRs) in tissues are domains that are homogenous with respect to cell type composition. We present a method for identifying SHRs using spatial transcriptomics data, and demonstrate that it is efficient and effective at finding SHRs for a wide variety of tissue types. concordex relies on analysis of k-nearest-neighbor (kNN) graphs. The tool is also useful for analysis of non-spatial transcriptomics data, and can elucidate the extent of concordance between partitions of cells derived from clustering algorithms, and transcriptomic similarity as represented in kNN graphs.

**License** Artistic-2.0

**URL** <https://github.com/pachterlab/concordexR>,  
<https://pachterlab.github.io/concordexR/>

**BugReports** <https://github.com/pachterlab/concordexR/issues>

**Depends** R (>= 4.4.0)

**Imports** BiocGenerics, BiocNeighbors, BiocParallel, bluster, cli,  
DelayedArray, Matrix, methods, purrr, rlang,  
SingleCellExperiment, sparseMatrixStats, SpatialExperiment,  
SummarizedExperiment

**Suggests** BiocManager, BiocStyle, ggplot2, glue, knitr, mbkmeans,  
patchwork, rmarkdown, scater, SFEData,  
SpatialFeatureExperiment, TENxPBMCDData, testthat (>= 3.0.0)

**VignetteBuilder** knitr

**biocViews** SingleCell, Clustering, Spatial, Transcriptomics

**Config/testthat/edition** 3

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**git\_url** <https://git.bioconductor.org/packages/concordexR>

**git\_branch** RELEASE\_3\_21

**git\_last\_commit** 0f8144d

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.21

**Date/Publication** 2025-04-15

**Author** Kayla Jackson [aut, cre] (ORCID:

<<https://orcid.org/0000-0001-6483-0108>>),

A. Sina Boeshaghi [aut] (ORCID:

<<https://orcid.org/0000-0002-6442-4502>>),

Angel Galvez-Merchan [aut] (ORCID:

<<https://orcid.org/0000-0001-7420-8697>>),

Lambda Moses [aut] (ORCID: <<https://orcid.org/0000-0002-7092-9427>>),

Alexandra Kim [ctb],

Laura Luebbert [ctb] (ORCID: <<https://orcid.org/0000-0003-1379-2927>>),

Lior Pachter [aut, rev, ths] (ORCID:

<<https://orcid.org/0000-0002-9164-6231>>)

**Maintainer** Kayla Jackson <kaylajac@caltech.edu>

## Contents

|                              |          |
|------------------------------|----------|
| calculateConcordex . . . . . | 2        |
| <b>Index</b>                 | <b>5</b> |

---

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| calculateConcordex | <i>Identify Spatially Homogeneous Regions with concordex</i> |
|--------------------|--------------------------------------------------------------|

---

## Description

Compute the neighborhood consolidation matrix and identify spatial homogeneous regions.

## Usage

```
calculateConcordex(x, ...)
```

```
runConcordex(x, ...)
```

```
## S4 method for signature 'ANY'
```

```
calculateConcordex(
  x,
  labels,
  ...,
  n_neighbors = 30,
  compute_similarity = FALSE,
```

```

    BLUSPARAM,
    BNINDEX,
    BNPARAM = KmknnParam(),
    BPPARAM = SerialParam()
)

## S4 method for signature 'SummarizedExperiment'
calculateConcordex(x, labels, ..., assay.type = "logcounts")

## S4 method for signature 'SingleCellExperiment'
calculateConcordex(x, labels, ..., use.dimred = NULL)

## S4 method for signature 'SpatialExperiment'
calculateConcordex(x, labels, ..., use.spatial = TRUE)

## S4 method for signature 'SpatialExperiment'
runConcordex(x, labels, ..., name = "NBC")

## S4 method for signature 'SingleCellExperiment'
runConcordex(x, labels, ..., name = "NBC")

```

## Arguments

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                  | <p>A <a href="#">SpatialExperiment</a>, <a href="#">SpatialFeatureExperiment</a>, <a href="#">SingleCellExperiment</a>, or <a href="#">SummarizedExperiment</a> object containing a count matrix.</p> <p>Otherwise, a numeric matrix-like object containing counts for observations (e.g. cells/spots) on the rows and features on the columns.</p>                                                                                                                                                                                                                                                                                                                                                        |
| ...                | Other parameters passed to default method                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| labels             | <p>Observation labels used to compute the neighborhood consolidation matrix. Continuous or discrete labels are allowed, and typically, integer labels are assumed to be discrete.</p> <p>Labels can be specified as follows:</p> <ul style="list-style-type: none"> <li>• A vector or matrix-like object with one entry per observation. If a matrix, the observations should be on the rows and the label identifiers on the columns.</li> <li>• If x inherits from <a href="#">SummarizedExperiment-class</a>, a string or character vector specifying the names of columns in <code>colData(x)</code> or the name of a dimensionality reduction result (see <a href="#">reducedDimNames</a>)</li> </ul> |
| n_neighbors        | Number of neighbors to expect for each observation. Defaults to 30.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| compute_similarity | Logical. Whether to return the label similarity matrix. Only useful if discrete labels are provided.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| BLUSPARAM          | A <a href="#">BlusterParam-class</a> object specifying the clustering algorithm to use to identify spatial homogeneous regions. If this parameter is not specified, then regions are not returned. By default, this parameter is missing.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| BNINDEX            | A <a href="#">BiocNeighborIndex</a> object containing the precomputed index information, see <a href="#">findKNN</a> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|             |                                                                                                                                                                                                                                            |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BNPARAM     | A <a href="#">BiocNeighborParam</a> object specifying the algorithm to use. This can be missing if BNINDEX is supplied, see <a href="#">findKNN</a> .                                                                                      |
| BPPARAM     | A <a href="#">BiocParallelParam</a> object specifying whether and how computing the metric for numerous observations shall be parallelized (see <a href="#">bpparam</a> ).                                                                 |
| assay.type  | String or integer scalar indicating the assay of x containing the counts.                                                                                                                                                                  |
| use.dimred  | Integer or string specifying the reduced dimensions to use for construction of the k-nearest neighbor graph. Note that if this is not NULL, reduced dimensions can not be used as labels to compute the neighborhood consolidation matrix. |
| use.spatial | Logical, should the spatial coordinates be used to compute the k-nearest neighbor graph?                                                                                                                                                   |
| name        | String specifying the name to be used to store the result in the <a href="#">reducedDims</a> of the output.                                                                                                                                |

## Value

A sparse matrix

## Examples

```
example(read10xVisium, "SpatialExperiment")
library(bluster)

## Setting BLUSPARAM clusters the consolidation
## matrix into SHRs
cdx <- calculateConcordex(
  spe, "in_tissue",
  n_neighbors=10,
  BLUSPARAM=KmeansParam(3)
)

## SHRs are an attribute of the result
shr <- attr(cdx, "shr")

## The label similarity matrix can be computed
## with `compute_similarity=TRUE`
cdx <- calculateConcordex(
  spe, "in_tissue",
  n_neighbors=10,
  compute_similarity=TRUE,
  BLUSPARAM=KmeansParam(3)
)
```

# Index

BiocNeighborIndex, [3](#)  
BiocNeighborParam, [4](#)  
BiocParallelParam, [4](#)  
bpparam, [4](#)  
  
calculateConcordex, [2](#)  
calculateConcordex, ANY-method  
    (calculateConcordex), [2](#)  
calculateConcordex, SingleCellExperiment-method  
    (calculateConcordex), [2](#)  
calculateConcordex, SpatialExperiment-method  
    (calculateConcordex), [2](#)  
calculateConcordex, SummarizedExperiment-method  
    (calculateConcordex), [2](#)  
  
findKNN, [3](#), [4](#)  
  
reducedDimNames, [3](#)  
reducedDims, [4](#)  
runConcordex (calculateConcordex), [2](#)  
runConcordex, SingleCellExperiment-method  
    (calculateConcordex), [2](#)  
runConcordex, SpatialExperiment-method  
    (calculateConcordex), [2](#)  
  
SingleCellExperiment, [3](#)  
SpatialExperiment, [3](#)  
SummarizedExperiment, [3](#)