

Package ‘epivizrStandalone’

October 12, 2016

Title Run Epivizr Interactive Genomic Data Visualization App within R

Version 1.0.4

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

Author Hector Corrada Bravo, Jayaram Kancherla

Description This package imports the epivizr visualization JavaScript app for genomic data interactive visualization. The 'epivizrServer' package is used to provide a web server running completely within R. This standalone version allows to browse arbitrary genomes through genome annotations provided by Bioconductor packages.

Depends R (>= 3.2.3), epivizr (>= 1.99.5), methods

License MIT + file LICENSE

LazyData true

Imports git2r, epivizrServer, GenomeInfoDb, BiocGenerics, GenomicFeatures, S4Vectors

Suggests testthat, knitr, rmarkdown, OrganismDbi (>= 1.13.9), Mus.musculus, Biobase

RoxygenNote 5.0.1

VignetteBuilder knitr

biocViews Visualization, Infrastructure, GUI

NeedsCompilation no

R topics documented:

setStandalone	2
startStandalone	2

Index	4
--------------	----------

setStandalone *Set settings for epiviz standalone repository.*

Description

The epiviz app run by function [startStandalone](#) in this package is cloned as a git repository. This function initializes the settings specifying which git repository is used. It can be either a github repository (the usual case), or local repository containing the epiviz JS app (used for testing and development).

Usage

```
setStandalone(url = "https://github.com/epiviz/epiviz.git", branch = "min",
  local_path = NULL, non_interactive = FALSE)
```

Arguments

url (character) github url to use. defaults to ("<https://github.com/epiviz/epiviz.git>").

branch (character) branch on the github repository. defaults to (master).

local_path (character) if you already have a local instance of epiviz and would like to run standalone use this.

non_interactive (logical) don't download repo, used for testing purposes.

Value

path to the epiviz app git repository

Examples

```
# argument non_interactive here to avoid downloading when testing
# package. Remove non_interactive argument when you try it out.
setStandalone(url="https://github.com/epiviz/epiviz.git", branch="master", non_interactive=TRUE)
```

startStandalone *Start a standalone epivizr session.*

Description

Uses the local repository of epiviz JS app to start a standalone epivizr session through the [startEpiviz](#) function. The epiviz app requires a list of sequence names and lengths (e.g., chromosome names and lengths) to setup genome browsing. These can be passed in the seqinfo argument or derived from the gene_track argument. The gene_track argument can be used to pass a genome annotation and add a gene track to the epiviz browser. See package vignette for further detail.

Usage

```
startStandalone(gene_track = NULL, seqinfo = NULL, keep_seqlevels = NULL,  
  chr = NULL, start = NULL, end = NULL, non_interactive = FALSE,  
  register_function = epivizr:::register_all_the_epiviz_things, ...)
```

Arguments

gene_track (OrganismDb) an object of type [OrganismDb](#) or [TxDb](#)

seqinfo (Seqinfo) an object of type [Seqinfo](#) from which sequence names and lengths are obtained

keep_seqlevels (character) vector of sequence names to include in the standalone app

chr (character) chromosome to browse to on app startup.

start (integer) start location to browse to on app startup.

end (integer) end location to browse to on app startup.

non_interactive (logical) run server in non-interactive mode. Used for testing and development.

register_function (function) function used to initialize actions in epiviz app. Used for testing and development.

... additional arguments passed to [startEpiviz](#).

Value

An object of class [EpivizApp](#)

Examples

```
# see package vignete for example usage  
seqinfo <- GenomeInfoDb::Seqinfo(c("chr1", "chr2"), c(10, 20))  
app <- startStandalone(seqinfo=seqinfo, non_interactive=TRUE)  
app$stop_app()
```

Index

EpivizApp, [3](#)

OrganismDb, [3](#)

Seqinfo, [3](#)

setStandalone, [2](#)

startEpiviz, [2](#), [3](#)

startStandalone, [2](#), [2](#)

TxDB, [3](#)