

Package ‘Polytect’

April 8, 2025

Title An R package for digital data clustering

Version 0.99.5

Description Polytect is an advanced computational tool designed for the analysis of multi-color digital PCR data. It provides automatic clustering and labeling of partitions into distinct groups based on clusters first identified by the flowPeaks algorithm. Polytect is particularly useful for researchers in molecular biology and bioinformatics, enabling them to gain deeper insights into their experimental results through precise partition classification and data visualization.

biocViews ddPCR, Clustering, MultiChannel, Classification

License Artistic-2.0

URL <https://github.com/emmachenlingo/Polytect>

BugReports <https://github.com/emmachenlingo/Polytect/issues>

Encoding UTF-8

LazyData false

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Depends R (>= 4.4.0)

Imports stats, utils, grDevices, mvtnorm, sn, dplyr, flowPeaks, ggplot2, tidyverse, cowplot, mlrMBO, DiceKriging, smooof, ParamHelpers, lhs, rgenoud, BiocManager

Suggests testthat (>= 3.0.0), knitr, rmarkdown, ddPCRclust

VignetteBuilder knitr

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/Polytect>

git_branch devel

git_last_commit ff9290d

git_last_commit_date 2024-12-27

Repository Bioconductor 3.21

Date/Publication 2025-04-07

Author Yao Chen [aut, cre] (ORCID: <<https://orcid.org/0000-0001-8172-3996>>)

Maintainer Yao Chen <emmachentar@live.com>

Contents

| | |
|------------------------------|-----------|
| approxSilhouette | 2 |
| BPV | 3 |
| CA | 4 |
| cluster_selection | 4 |
| CNV5plex | 5 |
| CNV6plex | 5 |
| combined_vectors | 6 |
| compute_tmp_matrix | 7 |
| conc_cal | 7 |
| estep | 8 |
| fp_search | 9 |
| GMM_init | 9 |
| HIV | 10 |
| HMM_merge | 10 |
| HR | 11 |
| LR | 12 |
| MM | 12 |
| mstep_cov | 13 |
| mstep_mu | 13 |
| polytect_clust | 15 |
| polytect_merge | 16 |
| polytect_plot | 17 |
| polytect_summary | 17 |
| silhouette_coef | 18 |
| sil_plot | 19 |
| Index | 20 |

| | |
|------------------|----------------------------|
| approxSilhouette | <i>Internal Function 2</i> |
|------------------|----------------------------|

Description

This function outputs silhouette coefficients.

Usage

```
approxSilhouette(x, clusters)
```

Arguments

| | |
|-----------------------|--|
| <code>x</code> | A matrix of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. |
| <code>clusters</code> | cluster labels |

Value

A data frame of silhouette coefficients for each partition.

BPV

BPV data

Description

A 3-color dPCR data of bovine papilloma virus assay

Usage

```
data(BPV)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

channel3 fluorescence intensities of color 3

Examples

```
data(BPV)  
head(BPV)
```

CA *CA data*

Description

2-color competitive assay of competition BRAF V600E assay with 1% mutant

Usage

```
data(CA)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. data is not orthogonal.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

Examples

```
data(CA)  
head(CA)
```

cluster_selection *Internal Function 11*

Description

This function outputs all combinations of primary targets

Usage

```
cluster_selection(cluster_num)
```

Arguments

cluster_num The expected maximum number of clusters

Value

A matrix of all combinations of primary targets

`CNV5plex`*CNV 5-plex data*

Description

CNV 5-plex universal probes

Usage

```
data(CNV5plex)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

channel3 fluorescence intensities of color 3

channel4 fluorescence intensities of color 4

channel5 fluorescence intensities of color 5

Examples

```
data(CNV5plex)
head(CNV5plex)
```

`CNV6plex`*CNV 6-plex data*

Description

CNV 6-plex universal probes

Usage

```
data(CNV6plex)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

channel3 fluorescence intensities of color 3

channel4 fluorescence intensities of color 4

channel5 fluorescence intensities of color 5

channel6 fluorescence intensities of color 6

Examples

```
data(CNV6plex)
head(CNV6plex)
```

combined_vectors

Internal Function 4

Description

This function outputs vectors and weights that will be used in EM algorithm

Usage

```
combined_vectors(coefs, mus, cluster_num, dim_data)
```

Arguments

| | |
|-------------|--|
| coefs | coefs The coefficients to adjust for the expected cluster centers. The default is 1 which can be used for common assay designs and has to be modified for special assays such as competing assays. |
| mus | The cluster centers of primary targets |
| cluster_num | The expected maximum number of clusters. |
| dim_data | dimension of the dataset |

Value

A list of vectors and weights

compute_tmp_matrix *Internal Function 6*

Description

This function compute the necessary elements for estep function

Usage

```
compute_tmp_matrix(g, k, cluster_num, mg, log_pih, mug_t, muh_t, covh, covg)
```

Arguments

| | |
|-------------|---|
| g | cluster index |
| k | cluster index |
| cluster_num | The expected maximum number of clusters |
| mg | cluster sizes of base clustering result |
| log_pih | log pih (the probability of cluster g belonging at level l+1 to cluster h at level l) |
| mug_t | the transposed matrix of cluster centers at level l+1 |
| muh_t | the transposed matrix of cluster centers at level l |
| covh | the covariance matrix of clusters at level l |
| covg | the covariance matrix of clusters at level l+1 |

Value

A vector of intermediate values for zi calculation in estep function

conc_cal *concentration calculation function*

Description

This function takes a data frame of fluorescence intensities and partition clusters as input. It can be results from polytect_clust or polytect_merge. It will give the target concentration as output.

Usage

```
conc_cal(df_data, cluster_num, sampvol = 0.91, volmix = 20, voltemp = 20)
```

Arguments

| | |
|--------------------------|---|
| <code>df_data</code> | A data frame containing partition fluorescence intensities and corresponding cluster label. This can be the output of <code>polytect_merge</code> or any data frame containing the above information. |
| <code>cluster_num</code> | the expected number of clusters |
| <code>sampvol</code> | The sample volume in microliters (μL) |
| <code>volmix</code> | The volume of the mixture |
| <code>voltemp</code> | The volume of the template |

Value

a data frame of target concentration.

Examples

```
data(HR)
df_data<-polytect_clust(HR,4)
conc_cal(df_data,4)
```

 estep

Internal Function 7

Description

This function calculates z_i in E-step of EM algorithm

Usage

```
estep(g_clusternum, cluster_num, pih, muh, covh, mg, mug, covg)
```

Arguments

| | |
|---------------------------|---|
| <code>g_clusternum</code> | cluster labels from base clustering |
| <code>cluster_num</code> | The expected maximum number of clusters |
| <code>pih</code> | the probability of cluster g belonging at level $l+1$ to cluster h at level l |
| <code>muh</code> | the matrix of cluster centers at level l |
| <code>covh</code> | the covariance matrix of clusters at level l |
| <code>mg</code> | cluster sizes of base clustering result |
| <code>mug</code> | the matrix of cluster centers at level $l+1$ |
| <code>covg</code> | the covariance matrix of clusters at level $l+1$ |

Value

z_i for estep in EM algorithm

fp_search *Internal Function 3*

Description

This function optimizes parameters of flowPeaks

Usage

```
fp_search(data, cluster_num = 16)
```

Arguments

| | |
|-------------|--|
| data | A matrix of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. |
| cluster_num | The expected maximum number of clusters |

Value

A vector containing the optimal parameters found by the algorithm

GMM_init *Internal Function 5*

Description

This function initialize the parameters for the main clustering function

Usage

```
GMM_init(data, cluster_num, base_clust, coefs)
```

Arguments

| | |
|-------------|--|
| data | A matrix or data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. |
| cluster_num | The expected maximum number of clusters |
| base_clust | The results of base clustering |
| coefs | The coefficients to adjust for the expected cluster centers. The default is 1 which can be used for common assay designs and has to be modified for special assays such as competing assays. |

Value

A list of initial parameters for the EM algorithm

HIV

HIV data

Description

A 4-color dPCR data of intact HIV-1 proviruses

Usage

```
data(HIV)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

channel3 fluorescence intensities of color 3

channel4 fluorescence intensities of color 4

Source

<https://www.biorxiv.org/content/10.1101/2023.08.18.553846v1>

Examples

```
data(HIV)
head(HIV)
```

HMM_merge

Internal Function 10

Description

This function merges the excess clusters given by the base clustering

Usage

```
HMM_merge(  
  data,  
  cluster_num,  
  base_clust,  
  eps = 10-10,  
  max_iter = 1000,  
  lambdas = rep(2, 2),  
  coefs = rep(1, 2)  
)
```

Arguments

| | |
|--------------------------|--|
| <code>data</code> | A matrix or data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. |
| <code>cluster_num</code> | The expected maximum number of clusters |
| <code>base_clust</code> | base clustering results before merging |
| <code>eps</code> | the convergence threshold |
| <code>max_iter</code> | maximum number of iterations |
| <code>lambdas</code> | The penalty terms for the deviation from the expected cluster centers. Higher lambdas penalizes the deviation more. |
| <code>coefs</code> | The coefficients to adjust for the expected cluster centers. The default is 1 which can be used for common assay designs and has to be modified for special assays such as competing assays. |

Value

A list of membership probability, cluster center, merging probability

| | |
|----|----------------|
| HR | <i>HR data</i> |
|----|----------------|

Description

A high-resolution 2-color dPCR data of RPP30 genomic DNA assay

Usage

```
data(HR)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. good separation but some crosstalk.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

Source

<https://pubmed.ncbi.nlm.nih.gov/33992770/>

Examples

```
data(HR)
head(HR)
```

LR *LR data*

Description

A low-resolution 2-color dPCR data of development of genotyping assays for plants various

Usage

```
data(LR)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. barely separable on x-axis.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

Examples

```
data(LR)
head(LR)
```

MM *MM data*

Description

A multi-mode 2-color dPCR data of HIV gBlock sequences

Usage

```
data(MM)
```

Format

A data frame of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. obvious multimodality.

channel1 fluorescence intensities of color 1

channel2 fluorescence intensities of color 2

Source

<https://pubmed.ncbi.nlm.nih.gov/37827643/>

Examples

```
data(MM)
head(MM)
```

mstep_cov

Internal Function 9

Description

This function calculates mu in M-step of EM algorithm

Usage

```
mstep_cov(cluster_num, dim_data, g_clusternum, zi, mg, covg, mug, muh)
```

Arguments

| | |
|--------------|---|
| cluster_num | The expected maximum number of clusters |
| dim_data | the dimension of the dataset |
| g_clusternum | cluster labels from base clustering |
| zi | the expected log-likelihood found on the E step |
| mg | cluster sizes of base clustering result |
| covg | the covariance matrix of clusters at level l+1 |
| mug | the matrix of cluster centers at level l+1 |
| muh | the matrix of cluster centers at level l |

Value

covh the covariance matrix of clusters at level l in the EM algorithm

mstep_mu

Internal Function 8

Description

This function calculates mu in M-step of EM algorithm

Usage

```
mstep_mu(
  zi,
  g_clusternum,
  dim_data,
  cluster_num,
  weights,
  muh,
  covh,
  mg,
  mug,
  neg_assum,
  lambdas,
  coefs
)
```

Arguments

| | |
|--------------|--|
| zi | the expected log-likelihood found on the E step |
| g_clusternum | cluster labels from base clustering |
| dim_data | the dimension of the dataset |
| cluster_num | The expected maximum number of clusters |
| weights | combinations of coefficients of the cluster centers |
| muh | the matrix of cluster centers at level l |
| covh | the covariance matrix of clusters at level l |
| mg | cluster sizes of base clustering result |
| mug | the matrix of cluster centers at level l+1 |
| neg_assum | the estimated cluster center of negative population |
| lambdas | The penalty terms for the deviation from the expected cluster centers. Higher lambdas penalizes the deviation more. |
| coefs | The coefficients to adjust for the expected cluster centers. The default is 1 which can be used for common assay designs and has to be modified for special assays such as competing assays. |

Value

muh the cluster centers at level l in the EM algorithm

| | |
|----------------|-------------------------------------|
| polytect_clust | <i>Main function for clustering</i> |
|----------------|-------------------------------------|

Description

This is the main function for clustering. The function will start with flowPeaks, then merge the excess clusters. It will return a data frame of fluorescence intensities and partition labels.

Usage

```
polytect_clust(  
  data,  
  cluster_num,  
  fp_par = "default",  
  fp_optim = c(0.1, 1, 1.5),  
  lambdas = rep(2, 64 - log2(64)),  
  coefs = rep(1, 6)  
)
```

Arguments

| | |
|-------------|--|
| data | A matrix of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. |
| cluster_num | The expected maximum number of clusters. |
| fp_par | The parameters for flowPeaks. fp_par=c("default","manual","auto"). When "default" is chosen, the default parameters of flowPeaks will be used. With "manual", you have to fill in fp_optim. |
| fp_optim | The paramters for flowPeaks that users have to fill in manually when fp_par is set at "manual". |
| lambdas | The penalty terms for the deviation from the expected cluster centers. Higher lambdas penalizes the deviation more. |
| coefs | The coefficients to adjust for the expected cluster centers. The default is 1 which can be used for common assay designs and has to be modified for special assays such as competing assays. |

Value

A data frame containing the original fluorescence intensity and the cluster labels.

Examples

```
data(HR)  
head(polytect_clust(HR, 4))
```

| | |
|----------------|-----------------------------|
| polytect_merge | <i>Function for merging</i> |
|----------------|-----------------------------|

Description

This function takes the clustering result as input. Users can first perform any clustering algorithm, then use this function. It will return a data frame of fluorescence intensities and partition labels.

Usage

```
polytect_merge(  
  data,  
  cluster_num,  
  base_clust,  
  lambdas = rep(2, 64 - log2(64)),  
  coefs = rep(1, 6)  
)
```

Arguments

| | |
|-------------|--|
| data | A matrix of fluorescence intensities in each channel. Each row represents each partitions, and each column each channel. |
| cluster_num | The expected maximum number of clusters. |
| base_clust | A list that contains partition labels given by initial clustering. |
| lambdas | The penalty terms for the deviation from the expected cluster centers. Higher lambdas penalizes the deviation more. |
| coefs | The coefficients to adjust for the expected cluster centers. The default is 1 which can be used for common assay designs and has to be modified for special assays such as competing assays. |

Value

A data frame containing the original fluorescence intensity and the cluster labels.

Examples

```
data(HR)  
dist_matrix <- dist(HR)  
hc <- hclust(dist_matrix, method = "ward.D2")  
hc_clusters <- cutree(hc, k = 6)  
base_clust <- list()  
base_clust$cluster <- hc_clusters  
head(polytect_merge(HR, 4, base_clust))
```

| | |
|---------------|---|
| polytect_plot | <i>Plotting function for clustering results</i> |
|---------------|---|

Description

This function takes results from `polytect_clust` and `polytect_merge`, or a data frame containing fluorescence intensities and partition labels. It will output all combination of 2-color plots.

Usage

```
polytect_plot(df_data, cluster_num, cluster_selected = TRUE)
```

Arguments

| | |
|-------------------------------|---|
| <code>df_data</code> | A data frame containing partition fluorescence intensities and corresponding cluster label. This can be the output of <code>polytect_clust</code> and <code>polytect_merge</code> or any data frame containing the above information. |
| <code>cluster_num</code> | the expected number of clusters |
| <code>cluster_selected</code> | Indicator of whether all the clusters are present in the plots. If TRUE, then only selected ones (the ones only positive in the selected 2 dimensions) are shown. The default value is "TRUE". |

Value

2-color plots.

Examples

```
data(HR)
df_data<-polytect_clust(HR,4)
polytect_plot(df_data,4)
```

| | |
|------------------|-------------------------|
| polytect_summary | <i>Summary function</i> |
|------------------|-------------------------|

Description

This function takes results from `polytect_clust` and `polytect_merge`, or a data frame containing fluorescence intensities and partition labels. It will summarise cluster centers, cluster sizes and cluster silhouette coefficients.

Usage

```
polytect_summary(df_data)
```

Arguments

`df_data` A data frame containing partition fluorescence intensities and corresponding cluster label. This can be the output of `polytect_clust` and `polytect_merge` or any data frame containing the above information.

Value

a data frame of the summary of cluster centers, cluster sizes and cluster silhouette coefficients.

Examples

```
data(HR)
df_data<-polytect_clust(HR,4)
polytect_summary(df_data)
```

`silhouette_coef`*Internal Function 1*

Description

This function outputs silhouette coefficients.

Usage

```
silhouette_coef(data, clustering, plot = FALSE)
```

Arguments

`data` A data frame containing standardized partition fluorescence intensities and corresponding cluster label.

`clustering` cluster labels

`plot` TRUE or FALSE, whether a plot should be shown. The default value is "FALSE".

Value

A list of silhouette coefficients for each partition and the mean silhouette coefficients for each cluster.

`sil_plot`*Plotting function for silhouette coefficients*

Description

This function takes results from `polytect_clust` and `polytect_merge`, or a data frame containing fluorescence intensities and partition labels. It will output the silhouette coefficients of each cluster.

Usage

```
sil_plot(df_data)
```

Arguments

`df_data` A data frame containing partition fluorescence intensities and corresponding cluster label. This can be the output of `polytect_clust` and `polytect_merge` or any data frame containing the above information.

Value

plot of silhouette coefficients for each cluster.

Examples

```
data(HR)
df_data<-polytect_clust(HR,4)
sil_plot(df_data)
```

Index

* datasets

BPV, [3](#)
CA, [4](#)
CNV5plex, [5](#)
CNV6plex, [5](#)
HIV, [10](#)
HR, [11](#)
LR, [12](#)
MM, [12](#)

* internal

approxSilhouette, [2](#)
cluster_selection, [4](#)
combined_vectors, [6](#)
compute_tmp_matrix, [7](#)
estep, [8](#)
fp_search, [9](#)
GMM_init, [9](#)
HMM_merge, [10](#)
mstep_cov, [13](#)
mstep_mu, [13](#)
silhouette_coef, [18](#)

HMM_merge, [10](#)

HR, [11](#)

LR, [12](#)

MM, [12](#)

mstep_cov, [13](#)

mstep_mu, [13](#)

polytect_clust, [15](#)

polytect_merge, [16](#)

polytect_plot, [17](#)

polytect_summary, [17](#)

sil_plot, [19](#)

silhouette_coef, [18](#)

approxSilhouette, [2](#)

BPV, [3](#)

CA, [4](#)

cluster_selection, [4](#)

CNV5plex, [5](#)

CNV6plex, [5](#)

combined_vectors, [6](#)

compute_tmp_matrix, [7](#)

conc_cal, [7](#)

estep, [8](#)

fp_search, [9](#)

GMM_init, [9](#)

HIV, [10](#)