

BSgenome.Mfascicularis.NCBI.5.0

April 16, 2025

BSgenome.Mfascicularis.NCBI.5.0

*Full genome sequences for Macaca fascicularis
(Macaca_fascicularis_5.0)*

Description

Full genome sequences for *Macaca fascicularis* (long-tailed macaque) as provided by NCBI (Macaca_fascicularis_5.0, 2013-06-12) and stored in Biostrings objects.

Note

This BSgenome data package was made from the following source data files:

GCF_000364345.1_Macaca_fascicularis_5.0_genomic.fna.gz from ftp://ftp.ncbi.nlm.nih.gov/genomes/all/GCF_000364345.1_Macaca_fascicularis_5.0_genomic.fna.gz

See [?BSgenomeForge](#) and the BSgenomeForge vignette (vignette("BSgenomeForge")) in the **BSgenome** software package for how to make a BSgenome data package.

Author(s)

The Bioconductor Dev Team

See Also

- [BSgenome](#) objects and the [available.genomes](#) function in the **BSgenome** software package.
- [DNASTring](#) objects in the **Biostrings** package.
- The BSgenomeForge vignette (vignette("BSgenomeForge")) in the **BSgenome** software package for how to make a BSgenome data package.

Examples

```

BSgenome.Mfascicularis.NCBI.5.0
genome <- BSgenome.Mfascicularis.NCBI.5.0
head(seqlengths(genome))
genome$MFA1 # same as genome[["MFA1"]]

## -----
## About the ordering of the sequences
## -----
## The sequences in BSgenome object 'genome' are ordered like in the
## assembly report at the following URL
url <- "ftp://ftp.ncbi.nlm.nih.gov/genomes/ASSEMBLY_REPORTS/All/GCF_000364345.1.assembly.txt"
## except that the MT sequence was moved from the last position to the
## position between the chromosomes (MFA* sequences) and the scaffolds
## (Scaffold* sequences):
SequenceName <- read.table(url, sep="\t", stringsAsFactors=FALSE)[[1]]
target_seqlevels <- SequenceName[c(1:21, 7601, 22:7600)]
stopifnot(identical(seqlevels(genome), target_seqlevels))

## -----
## Genome-wide motif searching
## -----
## See the GenomeSearching vignette in the BSgenome software
## package for some examples of genome-wide motif searching using
## Biostrings and the BSgenome data packages:
if (interactive())
  vignette("GenomeSearching", package="BSgenome")

```

Index

* **data**

BSgenome.Mfascicularis.NCBI.5.0, [1](#)

* **package**

BSgenome.Mfascicularis.NCBI.5.0, [1](#)

available.genomes, [1](#)

BSgenome, [1](#)

BSgenome.Mfascicularis.NCBI.5.0, [1](#)

BSgenome.Mfascicularis.NCBI.5.0-package
(BSgenome.Mfascicularis.NCBI.5.0),
[1](#)

BSgenomeForge, [1](#)

DNAString, [1](#)

Mfascicularis

(BSgenome.Mfascicularis.NCBI.5.0),
[1](#)