

Package ‘ROC’

September 24, 2012

Version 1.32.0

Title utilities for ROC, with uarray focus

Author Vince Carey <stvjc@channing.harvard.edu>, Henning Redestig for
C++ language enhancements

Maintainer Vince Carey <stvjc@channing.harvard.edu>

Description utilities for ROC, with uarray focus

biocViews Bioinformatics, DifferentialExpression

Depends R (>= 1.9.0), utils, methods

Suggests Biobase

License Artistic-2.0

URL <http://www.bioconductor.org>

LazyLoad Yes

R topics documented:

AUC	2
plot-methods	3
rocc-class	3
rocdemo.sca	4
trapezint	6
Index	7

AUC *functionals of ROC curve*

Description

various functionals of ROC (Receiver Operating Characteristic) curves

Usage

```
AUC(rocobj)
AUCi(rocobj)
pAUC(rocobj, t0)
pAUCi(rocobj, t0)
```

Arguments

rocobj	element of class rocc
t0	FPR point at which TPR is evaluated or limit in (0,1) to integrate to

Details

AUC, pAUC, AUCi and pAUCi compute the Area Under the Curve.

AUC and pAUC employ the trapezoidal rule. AUCi and pAUCi use `integrate()`.

AUC and AUCi compute the area under the curve from 0 to 1 on the x-axis (i.e., the 1 - specificity axis).

pAUC and pAUCi compute the area under the curve from 0 to argument t0 on the x-axis (i.e., the 1 - specificity axis).

Elements of class rocc can be created by `rocdemo.sca()` or other constructors you might make using the code of `rocdemo.sca()` as a template.

Author(s)

Vince Carey (stvjc@channing.harvard.edu)

References

Rosner, B., 2000, *Fundamentals of Biostatistics, 5th Ed.*, pp. 63–65

Duda, R. O., Hart, P. E., Stork, D. G., 2001 *Pattern Classification, 2nd Ed.*, p. 49

See Also

`rocdemo.sca`

Examples

```
set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
print(AUC(R1))
print(pAUC(R1,.3))
print(pAUCi(R1,.3))
print(ROC(R1,.3))
```

plot-methods

plot method for ROC curves

Description

plot method for ROC curves

Methods

`x = rocc` plots an ROC curve object, with additional parameters available:

show.thresh (logical): should marker threshold values be plotted?

jit (logical): should plotted points be jittered?

add (logical): increment to current plot?

line (logical): plot points or lines?

threshCex (numeric): if showing threshold values, set character expansion in text call to this value

threshYsh (numeric): if showing threshold values, add this quantity to y coordinate of curve to plot the threshold value (should be negative for printing below point)

threshDig (numeric): if showing threshold values, use this as the digits parameter to round to display the threshold

... extra parameters passed to base plot, lines or points as needed

Examples

```
set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
plot(R1, line=TRUE, show.thresh=TRUE, lwd=2, threshDig=2)
R2 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
plot(R2, line=TRUE, add=TRUE, col="green", lwd=2 )
R3 <- rocdemo.sca( rbinom(40,1,.4), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
points(R3, col="red", pch=19)
```

rocc-class

Class rocc, ROC curve representation

Description

object representing ROC curve, typically created using `rocdemo.sca`

Creating Objects

```

new('rocc',
  sens      = ..., # Object of class numeric
  spec      = ..., # Object of class numeric
  rule      = ..., # Object of class function
  cuts      = ..., # Object of class numeric
  markerLabel = ..., # Object of class character
  caseLabel  = ..., # Object of class character
)

```

Slots

sens: Object of class "numeric" sensitivity values
spec: Object of class "numeric" specificity values
rule: Object of class "function" rule to classify objects
cuts: Object of class "numeric" thresholds defining curve
markerLabel: Object of class "character" name of measured marker
caseLabel: Object of class "character" name of condition

Methods

plot (rocc, missing): a plotting function with some additional parameters

Examples

```

set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), dxrule.sca,
  caseLabel="new case", markerLabel="demo Marker" )
plot( R1, show.thresh=TRUE )

```

rocdemo.sca

function to build objects of class 'rocc'

Description

rocdemo.sca – demonstrate 'rocc' class construction using a scalar marker and simple functional rule

Usage

```

rocdemo.sca(truth, data, rule=NULL,
  cutpts=NA,
  markerLabel="unnamed marker", caseLabel="unnamed diagnosis")

```

Arguments

truth	true classification of objects. Must take values 0 or 1.
data	quantitative markers used to classify
rule	rule: a function with arguments (x, thresh) returning 0 or 1. If no rule is provided or the standard rule dxrule.sca is passed, a faster C-based implementation is used to compute sensitivity and specificity.
cutpts	values of thresholds
markerLabel	textual label describing marker
caseLabel	textual label describing classification

Details

dxrule.sca is function (x, thresh) ifelse(x > thresh, 1, 0)

The default value of argument cutpts is a point less than min(data), points separating the unique values of data and a point greater than max(data).

Value

an object of S4 class rocc

Author(s)

Vince Carey (stvjc@channing.harvard.edu)

See Also

AUC

Examples

```
set.seed(123)
R1 <- rocdemo.sca( rbinom(40,1,.3), rnorm(40), caseLabel="new case", markerLabel="demo Marker" )
plot(R1, line=TRUE, show.thresh=TRUE)

truth <- c(0, 1, 0, 1, 1, 0, 1, 1)
data <- c(2, 3, 4, 4, 5, 6, 7, 8)
R2 <- rocdemo.sca(truth, data, dxrule.sca)
plot(R2, line=TRUE, show.thresh=TRUE)
R3 <- rocdemo.sca(truth, data, function(x, thresh) 1 - dxrule.sca(x, thresh))
if (AUC(R2) + AUC(R3) != 1) stop('Sum of AUCs should be 1.')
#
# more involved
#
set.seed(1234)
x = runif(1000)
w = runif(1000)
z = rbinom(1000, 1, plogis(-2.7+6.2*x + .3*w))
m1 = glm(z~x, fam=binomial)
demorule.glm.clo = function(model) function(w,thresh)
  ifelse(predict(model, newdata=list(x=w), type="response")>thresh, 1, 0)
demorule.glm = demorule.glm.clo(m1)
R4 = rocdemo.sca(z, x, demorule.glm )
plot(R4)
```

trapezint

trapezoidal rule for AUC

Description

trapezoidal rule for AUC

Usage`trapezint(x, y, a, b)`**Arguments**

<code>x</code>	x - abscissae
<code>y</code>	y - ordinates
<code>a</code>	a - lower limit of integration
<code>b</code>	b - upper limit of integration

Detailsuses `approx`**Value**

estimated AUC

Examples

```
x <- sort(runif(30))
y <- sin(x)
print(trapezint(x,y,0,1))
```

Index

*Topic **methods**

plot-methods, 3

rocc-class, 3

*Topic **models**

AUC, 2

rocdemo.sca, 4

trapezint, 6

.initClasses (rocc-class), 3

AUC, 2

AUCi (AUC), 2

dxrule.sca (rocdemo.sca), 4

lines, rocc-method (plot-methods), 3

pAUC (AUC), 2

pAUCi (AUC), 2

plot, rocc-method (plot-methods), 3

plot-methods, 3

points, rocc-method (plot-methods), 3

ROC (AUC), 2

rocc-class, 3

rocdemo.sca, 4

trapezint, 6