

# Package ‘flowCore’

April 5, 2014

**Title** flowCore: Basic structures for flow cytometry data

**Version** 1.28.24

**Author** B. Ellis, P. Haaland, F. Hahne, N. Le Meur, N. Gopalakrishnan, J. Spidlen

**Description** Provides S4 data structures and basic functions to deal with flow cytometry data.

**Maintainer** M.Jiang <wjjiang2@fhcrc.org>

**Depends** R (>= 2.10.0)

**Imports** Biobase, BiocGenerics (>= 0.1.14), feature, graph, graphics,grDevices, MASS, methods, rrcov, stats, utils, stats4, corpcor

**Suggests** Rgraphviz, flowViz, ncdf

**Collate** AllGenerics.R AllClasses.R flowFrame-accessors.R  
flowSet-accessors.R Rm-methods.R actionItem-accessors.R  
coerce.R logicalFilterResult-accessors.R summarizeFilter-methods.R filterSummary-accessors.R  
fcReference-accessors.R manyFilterResult-accessors.R  
summary-methods.R multipleFilterResult-accessors.R on-methods.R  
transformList-accessors.R identifier-methods.R  
parameters-methods.R view-accessors.R initialize-methods.R  
filterResult-accessors.R in-methods.R rectangleGate-accessors.R  
workFlow-accessors.R filterResultList-accessors.R IO.R  
show-methods.R length-methods.R names-methods.R  
filterSet-accessors.R split-methods.R eval-methods.R gatingML.R  
FCSTransTransform.R median-logicle-transform.R

**License** Artistic-2.0

**biocViews** Infrastructure, FlowCytometry, CellBasedAssays

## R topics documented:

flowCore-package . . . . .	4
actionItem-class . . . . .	5
arcsinhTransform . . . . .	6

asinhT-class . . . . .	7
asinhTgml2-class . . . . .	8
biexponentialTransform . . . . .	9
boundaryFilter-class . . . . .	10
characterOrTransformation-class . . . . .	13
coerce . . . . .	13
compensateActionItem-class . . . . .	14
compensatedParameter-class . . . . .	16
compensateView-class . . . . .	17
compensation-class . . . . .	18
concreteFilter-class . . . . .	21
curv1Filter-class . . . . .	22
curv2Filter-class . . . . .	24
dg1polynomial-class . . . . .	26
each_col . . . . .	28
EHtrans-class . . . . .	28
ellipsoidGate-class . . . . .	30
exponential-class . . . . .	32
expressionFilter-class . . . . .	33
fcReference-class . . . . .	35
FCSTransTransform . . . . .	39
filter . . . . .	40
filter-and-methods . . . . .	42
filter-class . . . . .	42
filter-in-methods . . . . .	43
filterDetails-methods . . . . .	44
filterList-class . . . . .	44
filterReference-class . . . . .	45
filterResult-class . . . . .	46
filterResultList-class . . . . .	47
filters-class . . . . .	48
filterSet-class . . . . .	49
filterSummary-class . . . . .	51
filterSummaryList-class . . . . .	53
flowFrame-class . . . . .	54
flowSet-class . . . . .	61
fsApply . . . . .	66
gateActionItem-class . . . . .	67
gateView-class . . . . .	69
getIndexSort . . . . .	71
GvHD . . . . .	72
hyperlog-class . . . . .	73
hyperlogtGml2-class . . . . .	74
identifer . . . . .	76
inverseLogicleTransform . . . . .	77
invplitscale-class . . . . .	78
keyword-methods . . . . .	80
kmeansFilter-class . . . . .	82

linearTransform . . . . .	84
lintGml2-class . . . . .	85
lnTransform . . . . .	86
logarithm-class . . . . .	87
logicalFilterResult-class . . . . .	89
logicletGml2-class . . . . .	89
logicletTransform . . . . .	92
logtGml2-class . . . . .	93
logTransform . . . . .	95
manyFilterResult-class . . . . .	96
multipleFilterResult-class . . . . .	97
norm2Filter-class . . . . .	98
normalization-class . . . . .	100
normalizeActionItem-class . . . . .	102
normalizeView-class . . . . .	103
parameterFilter-class . . . . .	105
parameters . . . . .	105
parameters-class . . . . .	106
parameterTransform-class . . . . .	107
polygonGate-class . . . . .	108
polytopeGate-class . . . . .	110
quadGate-class . . . . .	111
quadratic-class . . . . .	113
quadraticTransform . . . . .	114
randomFilterResult-class . . . . .	115
ratio-class . . . . .	116
ratiotGml2-class . . . . .	117
read.FCS . . . . .	118
read.FCSheader . . . . .	121
read.flowSet . . . . .	122
rectangleGate-class . . . . .	123
sampleFilter-class . . . . .	126
scaleTransform . . . . .	128
setOperationFilter-class . . . . .	129
singleParameterTransform-class . . . . .	129
sinht-class . . . . .	130
spillover . . . . .	131
split-methods . . . . .	133
splitscale-class . . . . .	135
splitScaleTransform . . . . .	137
squareroot-class . . . . .	138
Subset . . . . .	139
subsetting-class . . . . .	140
subsettingActionItem-class . . . . .	141
subsettingView-class . . . . .	143
summarizeFilter-methods . . . . .	144
timeFilter-class . . . . .	145
transform-class . . . . .	147

transformActionItem-class . . . . .	148
transformation-class . . . . .	150
transformFilter-class . . . . .	151
transformList-class . . . . .	152
transformMap-class . . . . .	153
transformReference-class . . . . .	154
transformView-class . . . . .	154
truncateTransform . . . . .	156
unitytransform-class . . . . .	157
view-class . . . . .	158
workFlow-class . . . . .	160
write.FCS . . . . .	163
write.flowSet . . . . .	164
%on% . . . . .	165

**Index** **166**

---

flowCore-package	<i>Provides S4 data structures and basic infrastructure and functions to deal with flow cytometry data.</i>
------------------	---

---

**Description**

Define important flow cytometry data classes: [flowFrame](#), [flowSet](#) and their accessors.

Provide important transformation, filter, gating, workflow, and summary functions for flow cytometry data analysis.

Most of flow cytometry related Bioconductor packages (such as [flowStats](#), [flowFP](#), [flowQ](#), [flowViz](#), [flowMerge](#), [flowClust](#)) are heavily depended on this package.

**Details**

Package:	flowCore
Type:	Package
Version:	1.11.20
Date:	2009-09-16
License:	Artistic-2.0

**Author(s)**

Maintainer: Florian Hahne <[fhahne@fhcrc.org](mailto:fhahne@fhcrc.org)>

Authors: B. Ellis, P. Haaland, F. Hahne, N. Le Meur, N. Gopalakrishnan

---

actionItem-class	Class "actionItem"
------------------	--------------------

---

## Description

Class and method to capture standard operations in a flow cytometry workflow.

## Details

actionItems provide a means to bind standard operations on flow cytometry data in a workflow. Usually, the user doesn't have to create these objects, instead they will be automatically created when applying one of the standard operations (gating, transformation, compensation) to a `workFlow` object. Each `actionItem` creates one or several new `views`, which again can be the basis to apply further operations. One can conceptualize `actionItems` being the edges in the workflow tree connecting `views`, which are the nodes of the tree. There are more specific subclasses for the three possible types of operation: `gateActionItem` for gating operations, `transformActionItem` for transformations, and `compensateActionItem` for compensation operations. See their documentation for details.

## Objects from the Class

A virtual Class: No objects may be created from it.

## Slots

**ID:** Object of class "character". A unique identifier for the `actionItem`.

**name:** Object of class "character". A more human-readable name

**parentView:** Object of class "fcViewReference". A reference to the parent `view` the `actionItem` is applied on.

**alias:** Object of class "fcAliasReference". A reference to the alias table.

**env:** Object of class "environment". The evaluation environment in the `workFlow`.

## Methods

**identifier** signature(object = "actionItem"): Accessor for the ID slot.

**names** signature(x = "actionItem"): Accessor for the name slot.

**parent** signature(object = "actionItem"): Accessor for the parentView slot. Note that the reference is resolved, i.e., the `view` object is returned.

**alias** signature(object = "actionItem"): Get the alias table from a `actionItem`.

**Rm** signature(symbol = "actionItem", envir = "workFlow", subSymbol = "character"): Remove a `actionItem` from a `workFlow`. This method is recursive and will also remove all dependent `views` and `actionItems`.

## Author(s)

Florian Hahne

**See Also**

[workFlow](#), [gateActionItem](#), [transformActionItem](#), [compensateActionItem](#), [view](#)

**Examples**

```
showClass("view")
```

---

arcsinhTransform	<i>Create the definition of an arcsinh transformation function (base specified by user) to be applied on a data set</i>
------------------	---

---

**Description**

Create the definition of the arcsinh Transformation that will be applied on some parameter via the transform method. The definition of this function is currently  $x \leftarrow \text{asinh}(a+b*x)+c$ . The transformation would normally be used to convert to a linear valued parameter to the natural logarithm scale. By default a and b are both equal to 1 and c to 0.

**Usage**

```
arcsinhTransform(transformationId="defaultArcsinhTransform", a=1, b=1, c=0)
```

**Arguments**

transformationId	character string to identify the transformation
a	positive double that corresponds to the base of the logarithm.
b	positive double that corresponds to a scale factor.
c	positive double that corresponds to a scale factor

**Value**

Returns an object of class transform.

**Author(s)**

B. Ellis

**See Also**

[transform-class](#), [transform](#), [asinh](#)

**Examples**

```
samp <- read.FCS(system.file("extdata",
  "0877408774.B08", package="flowCore"))
asinhTrans <- arcsinhTransform(transformationId="ln-transformation", a=1, b=1, c=1)
dataTransform <- transform(samp,FSC-H=asinhTrans(FSC-H))
```

---

asinh-class	Class "asinh"
-------------	---------------

---

### Description

Inverse hyperbolic sin transformation is defined by the function

$$f(\text{parameter}, a, b) = \sinh^{-1}(a * \text{parameter}) * b$$

### Objects from the Class

Objects can be created by calls to the constructor `asinh(parameter, a, b, transformationId)`

### Slots

.Data: Object of class "function" ~~

a: Object of class "numeric" -non zero constant

b: Object of class "numeric" -non zero constant

parameters: Object of class "transformation" -flow parameter to be transformed

transformationId: Object of class "character" -unique ID to reference the transformation

### Extends

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

### Methods

No methods defined with class "asinh" in the signature.

### Note

The inverse hyperbolic sin transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

### Author(s)

Gopalakrishnan N, F.Hahne

### References

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

### See Also

`sinht`

**Examples**

```
dat <- read.FCS(system.file("extdata","0877408774.B08", package="flowCore"))
asinht1<-asinht(parameters="FSC-H",a=2,b=1,transformationId="asinH1")
transOut<-eval(asinh1)(exprs(dat))
```

---

asinhtGml2-class	Class <i>asinhtGml2</i>
------------------	-------------------------

---

**Description**

Inverse hyperbolic sin transformation as parameterized in Gating-ML 2.0 is defined by the following function:

$$f(\text{parameter}, T, M, A) = (\text{asinh}(\text{parameter} * \sinh(M * \ln(10)) / T) + A * \ln(10)) / ((M + A) * \ln(10))$$

This transformation is equivalent to Logicle(T, 0, M, A) (i.e., with W=0). It provides an inverse hyperbolic sine transformation that maps a data value onto the interval [0,1] such that:

- The top of scale value (i.e., T) is mapped to 1.
- Large data values are mapped to locations similar to an (M + A)-decade logarithmic scale.
- A decades of negative data are brought on scale.

**Objects from the Class**

Objects can be created by calls to the constructor

```
asinhtGml2(parameter, T, M, A, transformationId)
```

**Slots**

**.Data:** Object of class function ~~

**T:** Object of class numeric -positive constant (top of scale value)

**M:** Object of class numeric -positive constant (desired number of decades)

**A:** Object of class numeric -non-negative constant that is less than or equal to M (desired number of additional negative decades)

**parameters:** Object of class "transformation" -flow parameter to be transformed

**transformationId:** Object of class "character" -unique ID to reference the transformation

**Extends**

Class [singleParameterTransform](#), directly. Class [transform](#), by class [singleParameterTransform](#), distance 2. Class [transformation](#), by class [singleParameterTransform](#), distance 3. Class [characterOrTransformation](#), by class [singleParameterTransform](#), distance 4.

**Methods**

No methods defined with class `asinhtGml2` in the signature.



**Note**

The inverse hyperbolic sine transformation object can be evaluated using the eval method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Spidlen, J.

**References**

Gating-ML 2.0: International Society for Advancement of Cytometry (ISAC) standard for representing gating descriptions in flow cytometry. <http://flowcyt.sourceforge.net/gating/20130122.pdf>

**See Also**

[asinht](#), [transform-class](#), [transform](#)

**Examples**

```
myDataIn <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
myASinH1 <- asinhtGml2(parameters = "FSC-H", T = 1000, M = 4.5,
  A = 0, transformationId="myASinH1")
transOut <- eval(myASinH1)(exprs(myDataIn))
```

---

biexponentialTransform

*Compute a transform using the 'biexponential' function*

---

**Description**

The 'biexponential' is an over-parameterized inverse of the hyperbolic sine. The function to be inverted takes the form  $\text{biexp}(x) = a \cdot \exp(b \cdot (x-w)) - c \cdot \exp(-d \cdot (x-w)) + f$  with default parameters selected to correspond to the hyperbolic sine.

**Usage**

```
biexponentialTransform(transformationId="defaultBiexponentialTransform", a = 0.5, b = 1, c = 0.5, d = 1)
```

**Arguments**

**transformationId**  
A name to assign to the transformation. Used by the transform/filter integration routines.

**a**  
See the function description above. Defaults to 0.5

b	See the function description above. Defaults to 1.0
c	See the function description above. Defaults to 0.5 (the same as a)
d	See the function description above. Defaults to 1 (the same as b)
f	A constant bias for the intercept. Defaults to 0.
w	A constant bias for the 0 point of the data. Defaults to 0.
tol	A tolerance to pass to the inversion routine ( <code>uniroot</code> usually)
maxit	A maximum number of iterations to use, also passed to <code>uniroot</code>

### Value

Returns values giving the inverse of the biexponential within a certain tolerance. This function should be used with care as numerical inversion routines often have problems with the inversion process due to the large range of values that are essentially 0. Do not be surprised if you end up with population splitting about `w` and other odd artifacts.

### Author(s)

B. Ellis, N Gopalakrishnan

### See Also

[transform](#)

### Examples

```
# Construct some "flow-like" data which tends to be heteroscedastic.
data(GvHD)
biexp <- biexponentialTransform("myTransform")
after.1 <- transform(GvHD, FSC-H= biexp(FSC-H))

biexp <- biexponentialTransform("myTransform",w=10)
after.2 <- transform(GvHD, FSC-H= biexp(FSC-H))

opar = par(mfcol=c(3, 1))
plot(density(exprs(GvHD[[1]])[, 1]), main="Original")
plot(density(exprs(after.1[[1]])[, 1]), main="Standard Transform")
plot(density(exprs(after.2[[1]])[, 1]), main="Shifted Zero Point")
```

---

boundaryFilter-class *Class "boundaryFilter"*

---

### Description

Class and constructor for data-driven [filter](#) objects that discard margin events.

**Usage**

```
boundaryFilter(x, tolerance=.Machine$double.eps, side=c("both", "lower",
"upper"), filterId="defaultBoundaryFilter")
```

**Arguments**

x	Character giving the name(s) of the measurement parameter(s) on which the filter is supposed to work. Note that all events on the margins of any of the channels provided by x will be discarded, which is often not desired. Such events may not convey much information in the particular channel on which their value falls on the margin, however they may well be informative in other channels.
tolerance	Numeric vector, used to set the tolerance slot of the object. Can be set separately for each element in x. R's recycling rules apply.
side	Character vector, used to set the side slot of the object. Can be set separately for each element in x. R's recycling rules apply.
filterId	An optional parameter that sets the filterId slot of this filter. The object can later be identified by this name.

**Details**

Flow cytometry instruments usually operate on a given data range, and the limits of this range are stored as keywords in the FSC files. Depending on the amplification settings and the dynamic range of the measured signal, values can occur that are outside of the measurement range, and most instruments will simply pile those values at the minimum or maximum range limit. The `boundaryFilter` removes these values, either for a single parameter, or for a combination of parameters. Note that it is often desirable to treat boundary events on a per-parameter basis, since their values might be uninformative for one particular channel, but still be useful in all of the other channels.

The constructor `boundaryFilter` is a convenience function for object instantiation. Evaluating a `boundaryFilter` results in a single sub-population, and hence in an object of class `filterResult`.

**Value**

Returns a `boundaryFilter` object for use in filtering `flowFrames` or other flow cytometry objects.

**Extends**

Class "`parameterFilter`", directly.

Class "`concreteFilter`", by class `parameterFilter`, distance 2.

Class "`filter`", by class `parameterFilter`, distance 3.

**Slots**

**tolerance:** Object of class "numeric". The machine tolerance used to decide whether an event is on the measurement boundary. Essentially, this is done by evaluating  $x > \text{minRange} + \text{tolerance}$  &  $x < \text{maxRange} - \text{tolerance}$ .

**side:** Object of class "character". The margin on which to evaluate the filter. Either upper for the upper margin or lower for the lower margin or both for both margins.

### Objects from the Class

Objects can be created by calls of the form `new("boundaryFilter", ...)` or using the constructor `boundaryFilter`. Using the constructor is the recommended way of object instantiation:

### Methods

**%in%** signature(`x = "flowFrame"`, `table = "boundaryFilter"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the `filter` methods.

**show** signature(`object = "boundaryFilter"`): Print information about the filter.

### Author(s)

Florian Hahne

### See Also

`flowFrame`, `flowSet`, `filter` for evaluation of boundaryFilters and `Subset` for subsetting of flow cytometry data sets based on that.

### Examples

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Create directly. Most likely from a command line
boundaryFilter("FSC-H", filterId="myBoundaryFilter")

## To facilitate programmatic construction we also have the following
bf <- boundaryFilter(filterId="myBoundaryFilter", x=c("FSC-H"))

## Filtering using boundaryFilter
fres <- filter(dat, bf)
fres
summary(fres)

## We can subset the data with the result from the filtering operation.
Subset(dat, fres)

## A boundaryFilter on the lower margins of several channels
bf2 <- boundaryFilter(x=c("FSC-H", "SSC-H"), side="lower")
```

---

```
characterOrTransformation-class
      Class "characterOrTransformation"
```

---

**Description**

~~ A concise (1-5 lines) description of what the class is. ~~

**Objects from the Class**

A virtual Class: No objects may be created from it.

**Methods**

No methods defined with class "characterOrTransformation" in the signature.

**References**

~put references to the literature/web site here ~

**Examples**

```
showClass("characterOrTransformation")
```

---

```
coerce          Convert an object to another class
```

---

**Description**

These functions manage the relations that allow coercing an object to a given class.

**Arguments**

from, to      The classes between which def performs coercion. (In the case of the coerce function, these are objects from the classes, not the names of the classes, but you're not expected to call coerce directly.)

**Details**

The function supplied as the third argument is to be called to implement as(x, to) when x has class from. Need we add that the function should return a suitable object with class to.

**Author(s)**

F. Hahne, B. Ellis

## Examples

```
samp1 <- read.FCS(system.file("extdata", "0877408774.E07", package="flowCore"))
samp2 <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
samples <- list("sample1"=samp1, "sample2"=samp2)
experiment <- as(samples, "flowSet")
```

---

compensateActionItem-class

*Class "compensateActionItem"*

---

## Description

Class and method to capture compensation operations in a flow cytometry workflow.

## Usage

```
compensateActionItem(ID = paste("compActionRef", guid(), sep = "_"),
  name = paste("action", identifier(get(compensate)), sep = "_"),
  parentView, compensate, workflow)
```

## Arguments

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal <code>guid</code> function.
name	A more human-readable name of the view.
parentView, compensate	References to the parent <a href="#">view</a> and <a href="#">compensation</a> objects, respectively.

## Details

`compensateActionItems` provide a means to bind compensation operations in a workflow. Each `compensateActionItem` represents a single [compensation](#).

## Value

A reference to the `compensateActionItem` that is created inside the [workFlow](#) environment as a side effect of calling the `add` method.

A `compensateActionItem` object for the constructor.

## Objects from the Class

Objects should be created using the `add` method, which creates a `compensateActionItem` from a `compensation` object and directly assigns it to a `workFlow`. Alternatively, one can use the `compensateActionItem` constructor function for more programmatic access.

## Slots

`compensate`: Object of class `"fcCompensateReference"`. A reference to the `compensation` object that is used for the compensation operation.

`ID`: Object of class `"character"`. A unique identifier for the `actionItem`.

`name`: Object of class `"character"`. A more human-readable name

`parentView`: Object of class `"fcViewReference"`. A reference to the parent `view` the `compensateActionItem` is applied on.

`env`: Object of class `"environment"`. The evaluation environment in the `workFlow`.

## Extends

Class `"actionItem"`, directly.

## Methods

**print** signature(`x = "compensateActionItem"`): Print details about the object.

**Rm** signature(`symbol = "compensateActionItem"`, `envir = "workFlow"`, `subSymbol = "character"`): Remove a `compensateActionItem` from a `workFlow`. This method is recursive and will also remove all dependent views and `actionItems`.

**show** signature(`object = "compensateActionItem"`): Print details about the object.

## Author(s)

Florian Hahne

## See Also

`workFlow`, `actionItem`, `gateActionItem`, `transformActionItem`, `view`

## Examples

```
showClass("view")
```

---

 compensatedParameter-class

*Class "compensatedParameter"*


---

### Description

Emission spectral overlap can be corrected by subtracting the the amount of spectral overlap from the total detected signals. This compensation process can be described by using spillover matrices.

compensatedParameter objects allow for compensation of specific parameters the user is interested in by creating compensatedParameter objects and evaluating them. This allows for use of compensatedParameter in gate definitions.

### Objects from the Class

Objects can be created by calls of the form `compensatedParameter(parameters, spillRefId, transformationId, searchEnv)`

### Slots

`.Data`: Object of class "function" ~~

`parameters`: Object of class "character" -flow parameters to be compensated

`spillRefId`: Object of class "character" -name of the compensation object (The compensation object contains the spillover Matrix)

`searchEnv`: Object of class "environment" -environment in which the compensation object is defined

`transformationId`: Object of class "character" -unique Id to reference the compensatedParameter object

### Extends

Class "`transform`", directly. Class "`transformation`", by class "`transform`", distance 2. Class "`characterOrTransformation`", by class "`transform`", distance 3.

### Methods

No methods defined with class "compensatedParameter" in the signature.

### Note

The transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

### Author(s)

Gopalakrishnan N,F.Hahne



**References**

~~

**See Also**

compensation

**Examples**

```
samp <- read.flowSet(path=system.file("extdata", "compdata", "data", package="flowCore"))
cfile <- system.file("extdata","compdata","compmatrix", package="flowCore")
comp.mat <- read.table(cfile, header=TRUE, skip=2, check.names = FALSE)
comp.mat

## create a compensation object
comp <- compensation(comp.mat,compensationId="comp1")
## create a compensated parameter object
cPar1<-compensatedParameter(c("FL1-H", "FL3-H"), "comp", searchEnv=.GlobalEnv)
compOut<-eval(cPar1)(exprs(samp[[1]]))
```

---

compensateView-class    *Class "compensateView"*

---

**Description**

Class and method to capture the result of compensation operations in a flow cytometry workflow.

**Usage**

```
compensateView(workflow, ID=paste("compViewRef", guid(), sep="_"),
               name="default", action, data)
```

**Arguments**

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal <code>guid</code> function.
name	A more human-readable name of the view.
data, action	References to the data and <a href="#">actionItem</a> objects, respectively.

**Value**

A reference to the `compensateView` that is created inside the `workFlow` environment as a side effect of calling the `add` method.

A `compensateView` object for the constructor.

### Objects from the Class

Objects should be created using the add method, which creates a compensateView from a [compensation](#) object and directly assigns it to a [workFlow](#). Alternatively, one can use the compensateView constructor function for more programmatic access.

### Slots

ID: Object of class "character". A unique identifier for the view.

name: Object of class "character". A more human-readable name

action: Object of class "fcActionReference". A reference to the [actionItem](#) that generated the view.

env: Object of class "environment". The evaluation environment in the [workFlow](#).

data: Object of class "fcDataReference" A reference to the data that is associated to the view.

### Extends

Class "[view](#)", directly.

### Methods

**Rm** signature(symbol = "compensateView", envir = "workFlow", subSymbol = "character"): Remove a compensateView from a [workFlow](#). This method is recursive and will also remove all dependent views and [actionItems](#).

### Author(s)

Florian Hahne

### See Also

[workFlow](#), [view](#), [gateView](#), [transformView](#), [normalizeView](#), [actionItem](#)

### Examples

```
showClass("view")
```

---

compensation-class      *Class "compensation"*

---

### Description

Class and methods to compensate for spillover between channels by applying a spillover matrix to a flowSet or a flowFrame assuming a simple linear combination of values.

**Usage**

```
compensation(..., spillover,
             compensationId="defaultCompensation")
```

```
compensate(x, spillover, ...)
```

**Arguments**

`spillover`        The spillover or compensation matrix.

`compensationId` The identifier for the compensation object.

`x`                An object of class `flowFrame` or `flowSet`.

`...`             Further arguments.

The constructor is designed to be useful in both programmatic and interactive settings, and `...` serves as a container for possible arguments. The following combinations of values are allowed:

Elements in `...` are character scalars of parameter names or `transform` objects and the colnames in `spillover` match to these parameter names.

The first element in `...` is a character vector of parameter names or a list of character scalars or `transform` objects and the colnames in `spillover` match to these parameter names.

Argument `spillover` is missing and the first element in `...` is a matrix, in which case it is assumed to be the spillover matrix.

`...` is missing, in which case all parameter names are taken from the colnames of `spillover`.

**Details**

The essential premise of compensation is that some fluorochromes may register signals in detectors that do not correspond to their primary detector (usually a photomultiplier tube). To compensate for this fact, some sort of standard is used to obtain the background signal (no dye) and the amount of signal on secondary channels for each fluorochrome relative to the signal on their primary channel.

To calculate the spillover percentage we use either the mean or the median (more often the latter) of the secondary signal minus the background signal for each dye to obtain  $n$  by  $n$  matrix,  $S$ , of so-called spillover values, expressed as a percentage of the primary channel. The observed values are then considered to be a linear combination of the true fluorescence and the spillover from each other channel so we can obtain the true values by simply multiplying by the inverse of the spillover matrix.

The spillover matrix can be obtained through several means. Some flow cytometers provide a spillover matrix calculated during acquisition, possibly by the operator, that is made available in the metadata of the `flowFrame`. While there is a theoretical standard keyword `$SPILL` it can also be found in the `SPILLOVER` or `SPIILL` keyword depending on the cytometry. More commonly the spillover matrix is calculated using a series of compensation cells or beads collected before the experiment. If you have set of FCS files with one file per fluorochrome as well as an unstained FCS file you can use the `spillover` method for `flowSets` to automatically calculate a spillover matrix.

The compensation class is essentially a wrapper around a matrix that allows for transformed parameters and method dispatch.

### Value

A compensation object for the constructor.

A `flowFrame` or `flowSet` for the compensate methods.

### Objects from the Class

Objects should be created using the constructor `compensation()`. See the Usage and Arguments sections for details.

### Slots

`spillover`: Object of class `matrix`; the spillover matrix.

`compensationId`: Object of class `character`. An identifier for the object.

`parameters`: Object of class `parameters`. The flow parameters for which the compensation is defined. This can also be objects of class `transform`, in which case the compensation is performed on the compensated parameters.

### Methods

**compensate** signature(`x = "flowFrame"`, `spillover = "compensation"`): Apply the compensation defined in a compensation object on a `flowFrame`. This returns a compensated `flowFrame`.

*Usage:*

```
compensate(flowFrame, compensation)
```

**compensate** signature(`x = "flowFrame"`, `spillover = "matrix"`): Apply a compensation matrix to a `flowFrame`. This returns a compensated `flowFrame`.

*Usage:*

```
compensate(flowFrame, matrix)
```

**compensate** signature(`x = "flowFrame"`, `spillover = "data.frame"`): Try to coerce the `data.frame` to a matrix and apply that to a `flowFrame`. This returns a compensated `flowFrame`.

*Usage:*

```
compensate(flowFrame, data.frame)
```

**identifier, identifier<-** signature(`object = "compensation"`): Accessor and replacement methods for the `compensationId` slot.

*Usage:*

```
identifier(compensation)
identifier(compensation) <- value
```

**parameters** signature(`object = "compensation"`): Get the parameter names of the compensation object. This method also tries to resolve all `transforms` and `transformReferences` before returning the parameters as character vectors. Unresolvable references return NA.

*Usage:*

```
parameters(compensation)
```

**show** signature(object = "compensation"): Print details about the object.

*Usage:*

This method is automatically called when the object is printed on the screen.

### Author(s)

F.Hahne, B. Ellis, N. Le Meur

### See Also

[spillover](#)

### Examples

```
## Read sample data and a sample spillover matrix
samp <- read.flowSet(path=system.file("extdata", "compdata", "data",
  package="flowCore"))
cfile <- system.file("extdata", "compdata", "compmatrix", package="flowCore")
comp.mat <- read.table(cfile, header=TRUE, skip=2, check.names = FALSE)
comp.mat

## compensate using the spillover matrix directly
summary(samp)
samp <- compensate(samp, comp.mat)
summary(samp)

## create a compensation object and compensate using that
comp <- compensation(comp.mat)
compensate(samp, comp)
```

---

concreteFilter-class *Class "concreteFilter"*

---

### Description

The concreteFilter serves as a base class for all filters that actually implement a filtering process. At the moment this includes all filters except [filterReference](#), the only non-concrete filter at present.

### Objects from the Class

Objects of this class should never be created directly. It serves only as a point of inheritance.

### Slots

filterId: The identifier associated with this class.

**Extends**

Class "[filter](#)", directly.

**Author(s)**

B. Ellis

**See Also**

[parameterFilter](#)

---

curv1Filter-class      *Class "curv1Filter"*

---

**Description**

Class and constructor for data-driven [filter](#) objects that selects high-density regions in one dimension.

**Usage**

```
curv1Filter(x, bwFac=1.2, gridsize=rep(401, 2),
  filterId="defaultCurv1Filter")
```

**Arguments**

x	Character giving the name of the measurement parameter on which the filter is supposed to work on. This can also be a list containing a single character scalar for programmatic access.
filterId	An optional parameter that sets the filterId slot of this filter. The object can later be identified by this name.
bwFac, gridsize	Numerics of length 1 and 2, respectively, used to set the bwFac and gridsize slots of the object.

**Details**

Areas of high local density in one dimensions are identified by detecting significant curvature regions. See *Duong, T. and Cowling, A. and Koch, I. and Wand, M.P., Computational Statistics and Data Analysis 52/9, 2008* for details. The constructor `curv1Filter` is a convenience function for object instantiation. Evaluating a `curv1Filter` results in potentially multiple sub-populations, an hence in an object of class [multipleFilterResult](#). Accordingly, `curv1Filters` can be used to split flow cytometry data sets.

**Value**

Returns a curv1Filter object for use in filtering [flowFrames](#) or other flow cytometry objects.

**Extends**

Class "[parameterFilter](#)", directly.

Class "[concreteFilter](#)", by class parameterFilter, distance 2.

Class "[filter](#)", by class parameterFilter, distance 3.

**Slots**

**bwFac:** Object of class "numeric". The bandwidth factor used for smoothing of the density estimate.

**gridsize:** Object of class "numeric". The size of the bins used for density estimation.

**parameters:** Object of class "character", describing the parameter used to filter the flowFrame.

**filterId:** Object of class "character", referencing the filter.

**Objects from the Class**

Objects can be created by calls of the form `new("curvFilter", ...)` or using the constructor `curv1Filter`. Using the constructor is the recommended way of object instantiation:

**Methods**

**%in%** signature(`x = "flowFrame"`, `table = "curv1Filter"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the [filter](#) methods.

**show** signature(`object = "curv1Filter"`): Print information about the filter.

**Note**

See the documentation in the [flowViz](#) package for plotting of curv1Filters.

**Author(s)**

Florian Hahne

**See Also**

[curv2Filter](#), [flowFrame](#), [flowSet](#), [filter](#) for evaluation of curv1Filters and [split](#) for splitting of flow cytometry data sets based on that.

## Examples

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Create directly. Most likely from a command line
curv1Filter("FSC-H", filterId="myCurv1Filter", bwFac=2)

## To facilitate programmatic construction we also have the following
c1f <- curv1Filter(filterId="myCurv1Filter", x=list("FSC-H"), bwFac=2)

## Filtering using curv1Filter
fres <- filter(dat, c1f)
fres
summary(fres)
names(fres)

## The result of curv1 filtering are multiple sub-populations
## and we can split our data set accordingly
split(dat, fres)

## We can limit the splitting to one or several sub-populations
split(dat, fres, population="rest")
split(dat, fres, population=list(keep=c("peak 2", "peak 3")))
```

---

curv2Filter-class	Class "curv2Filter"
-------------------	---------------------

---

## Description

Class and constructor for data-driven `filter` objects that selects high-density regions in two dimensions.

## Usage

```
curv2Filter(x, y, filterId="defaultCurv2Filter", bwFac=1.2,
gridsize=rep(151, 2))
```

## Arguments

<code>x, y</code>	Characters giving the names of the measurement parameter on which the filter is supposed to work on. <code>y</code> can be missing in which case <code>x</code> is expected to be a character vector of length 2 or a list of characters.
-------------------	---



filterId	An optional parameter that sets the filterId slot of this filter. The object can later be identified by this name.
bwFac, gridsize	Numerics of length 1 and 2, respectively, used to set the bwFac and gridsize slots of the object.

### Details

Areas of high local density in two dimensions are identified by detecting significant curvature regions. See *Duong, T. and Cowling, A. and Koch, I. and Wand, M.P., Computational Statistics and Data Analysis 52/9, 2008* for details. The constructor `curv2Filter` is a convenience function for object instantiation. Evaluating a `curv2Filter` results in potentially multiple sub-populations, and hence in an object of class `multipleFilterResult`. Accordingly, `curv2Filters` can be used to split flow cytometry data sets.

### Value

Returns a `curv2Filter` object for use in filtering `flowFrames` or other flow cytometry objects.

### Extends

Class `"parameterFilter"`, directly.

Class `"concreteFilter"`, by class `parameterFilter`, distance 2.

Class `"filter"`, by class `parameterFilter`, distance 3.

### Slots

`bwFac`: Object of class `"numeric"`. The bandwidth factor used for smoothing of the density estimate.

`gridsize`: Object of class `"numeric"`. The size of the bins used for density estimation.

`parameters`: Object of class `"character"`, describing the parameters used to filter the `flowFrame`.

`filterId`: Object of class `"character"`, referencing the filter.

### Objects from the Class

Objects can be created by calls of the form `new("curv2Filter", ...)` or using the constructor `curv2Filter`. The constructor is the recommended way of object instantiation:

### Methods

`%in%` signature(`x = "flowFrame"`, `table = "curv2Filter"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the `filter` methods.

`show` signature(`object = "curv2Filter"`): Print information about the filter.

### Note

See the documentation in the `flowViz` package for plotting of `curv2Filters`.

**Author(s)**

Florian Hahne

**See Also**

[curv1Filter](#), [flowFrame](#), [flowSet](#), [filter](#) for evaluation of curv2Filters and [split](#) for splitting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Create directly. Most likely from a command line
curv2Filter("FSC-H", "SSC-H", filterId="myCurv2Filter")

## To facilitate programmatic construction we also have the following
c2f <- curv2Filter(filterId="myCurv2Filter", x=list("FSC-H", "SSC-H"),
bwFac=2)
c2f <- curv2Filter(filterId="myCurv2Filter", x=c("FSC-H", "SSC-H"),
bwFac=2)

## Filtering using curv2Filter
fres <- filter(dat, c2f)
fres
summary(fres)
names(fres)

## The result of curv2 filtering are multiple sub-populations
## and we can split our data set accordingly
split(dat, fres)

## We can limit the splitting to one or several sub-populations
split(dat, fres, population="rest")
split(dat, fres, population=list(keep=c("area 2", "area 3")))

curv2Filter("FSC-H", "SSC-H", filterId="test filter")
```

---

dg1polynomial-class    *Class "dg1polynomial"*

---

**Description**

dg1polynomial allows for scaling, linear combination and translation within a single transformation defined by the function

$$f(\text{parameter}_1, \dots, \text{parameter}_n, a_1, \dots, a_n, b) = b + \sum_{i=1}^n a_i * \text{parameter}_i$$

### Objects from the Class

Objects can be created by using the constructor `dg1polynomial(parameter, a, b, transformationId)`.

### Slots

`.Data`: Object of class "function" ~~

`parameters`: Object of class "parameters" -the flow parameters that are to be transformed

`a`: Object of class "numeric" - coefficients of length equal to the number of flow parameters

`b`: Object of class "numeric" - coefficient of length 1 that performs the translation

`transformationId`: Object of class "character" unique ID to reference the transformation

### Extends

Class "[transform](#)", directly. Class "[transformation](#)", by class "transform", distance 2. Class "[characterOrTransformation](#)", by class "transform", distance 3.

### Methods

No methods defined with class "dg1polynomial" in the signature.

### Note

The transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

### Author(s)

Gopalakrishnan N, F.Hahne

### References

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

### See Also

`ratio`, `quadratic`, `squareroot`

### Examples

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))
dg1 <- dg1polynomial(c("FSC-H", "SSC-H"), a=c(1,2), b=1, transformationId="dg1")
transOut <- eval(dg1)(exprs(dat))
```

---

each_col	<i>Method to apply functions over flowFrame margins</i>
----------	---

---

**Description**

Returns a vector or array of values obtained by applying a function to the margins of a flowFrame. This is equivalent of running [apply](#) on the output of `exprs(flowFrame)`.

**Usage**

```
each_col(x, FUN, ...)
each_row(x, FUN, ...)
```

**Arguments**

x	Object of class <a href="#">flowFrame</a> .
FUN	the function to be applied. In the case of functions like '+', '%*%', etc., the function name must be backquoted or quoted.
...	optional arguments to 'FUN'.

**Author(s)**

B. Ellis, N. LeMeur, F. Hahne

**See Also**

[apply](#)

**Examples**

```
samp <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"),
transformation="linearize")
each_col(samp, summary)
```

---

EHtrans-class	<i>Class "EHtrans"</i>
---------------	------------------------

---

**Description**

EH transformation of a parameter is defined by the function

$$EH(\text{parameter}, a, b) = 10^{\left(\frac{\text{parameter}}{a}\right)} + \frac{b * \text{parameter}}{a} - 1 \quad \text{parameter} \geq 0$$

$$-10^{\left(\frac{-\text{parameter}}{a}\right)} + \frac{b * \text{parameter}}{a} + 1 \quad \text{parameter} < 0$$

## Objects from the Class

Objects can be created by calls to the constructor `EHtrans(parameters, a, b, transformationId)`

## Slots

`.Data`: Object of class "function" ~~

`a`: Object of class "numeric" -numeric constant greater than zero

`b`: Object of class "numeric" -numeric constant greater than zero

`parameters`: Object of class "transformation" - flow parameter to be transformed

`transformationId`: Object of class "character"- unique ID to reference the transformation

## Extends

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

## Methods

No methods defined with class "EHtrans" in the signature.

## Note

The transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

## Author(s)

Gopalakrishnan N, F.Hahne

## References

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

## See Also

[hyperlog](#)

## Examples

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
eh1<-EHtrans("FSC-H", a=1250, b=4, transformationId="eh1")
transOut<-eval(eh1)(exprs(dat))
```

---

ellipsoidGate-class    *Class "ellipsoidGate"*

---

### Description

Class and constructor for n-dimensional ellipsoidal [filter](#) objects.

### Usage

```
ellipsoidGate(..., .gate, mean, distance=1, filterId="defaultEllipsoidGate")
```

### Arguments

<code>filterId</code>	An optional parameter that sets the <code>filterId</code> of this gate.
<code>.gate</code>	A definition of the gate via a covariance matrix.
<code>mean</code>	Numeric vector of equal length as dimensions in <code>.gate</code> .
<code>distance</code>	Numeric scalar giving the Mahalanobis distance defining the size of the ellipse. This mostly exists for compliance reasons to the gatingML standard as mean and gate should already uniquely define the ellipse. Essentially, distance is merely a factor that gets applied to the values in the covariance matrix.
<code>...</code>	You can also directly describe the covariance matrix through named arguments, as described below.

### Details

A convenience method to facilitate the construction of a ellipsoid [filter](#) objects. Ellipsoid gates in n dimensions ( $n \geq 2$ ) are specified by a a covarinace matrix and a vector of mean values giving the center of the ellipse.

This function is designed to be useful in both direct and programmatic usage. In the first case, simply describe the covariance matrix through named arguments. To use this function programmatically, you may pass a covariance matrix and a mean vector directly, in which case the parameter names are the colnames of the matrix.

### Value

Returns a [ellipsoidGate](#) object for use in filtering [flowFrames](#) or other flow cytometry objects.

### Extends

Class "[parameterFilter](#)", directly.

Class "[concreteFilter](#)", by class [parameterFilter](#), distance 2.

Class "[filter](#)", by class [parameterFilter](#), distance 3.

**Slots**

**mean:** Objects of class "numeric". Vector giving the location of the center of the ellipse in n dimensions.

**cov:** Objects of class "matrix". The covariance matrix defining the shape of the ellipse.

**distance:** Objects of class "numeric". The Mahalanobis distance defining the size of the ellipse.

**parameters:** Object of class "character", describing the parameter used to filter the flowFrame.

**filterId:** Object of class "character", referencing the filter.

**Objects from the Class**

Objects can be created by calls of the form `new("ellipsoidGate", ...)` or by using the constructor `ellipsoidGate`. Using the constructor is the recommended way of object instantiation:

**Methods**

**%in%** signature(`x = "flowFrame"`, `table = "ellipsoidGate"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the `filter` methods.

**show** signature(`object = "ellipsoidGate"`): Print information about the filter.

**Note**

See the documentation in the `flowViz` package for plotting of ellipsoidGates.

**Author(s)**

F.Hahne, B. Ellis, N. LeMeur

**See Also**

`flowFrame`, `polygonGate`, `rectangleGate`, `polytopeGate`, `filter` for evaluation of rectangleGates and `split` and `Subset` for splitting and subsetting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Defining the gate
cov <- matrix(c(6879, 3612, 3612, 5215), ncol=2,
dimnames=list(c("FSC-H", "SSC-H"), c("FSC-H", "SSC-H")))
mean <- c("FSC-H"=430, "SSC-H"=175)
eg <- ellipsoidGate(filterId= "myEllipsoidGate", .gate=cov, mean=mean)

## Filtering using ellipsoidGates
fres <- filter(dat, eg)
fres
```

```
summary(fres)

## The result of ellipsoid filtering is a logical subset
Subset(dat, fres)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
split(dat, fres)
```

---

exponential-class      *Class "exponential"*

---

### Description

Exponential transform class defines a transformation given by the function

$$f(\text{parameter}, a, b) = e^{\text{parameter}/b} * \frac{1}{a}$$

### Objects from the Class

Objects can be created by calls to the constructor `exponential(parameters, a, b)`.

### Slots

.Data: Object of class "function" ~~  
a: Object of class "numeric"- non zero constant  
b: Object of class "numeric"- non zero constant  
parameters: Object of class "transformation"- flow parameter to be transformed  
transformationId: Object of class "character" -unique ID to reference the transformation

### Extends

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

### Methods

No methods defined with class "exponential" in the signature.

### Note

The exponential transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column



**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

**See Also**

logarithm

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
exp1<-exponential(parameters="FSC-H", a=1, b=37, transformationId="exp1")
transOut<-eval(exp1)(exprs(dat))
```

---

expressionFilter-class

*Class "expressionFilter"*

---

**Description**

A [filter](#) holding an expression that can be evaluated to a logical vector or a vector of factors.

**Usage**

```
expressionFilter(expr, ..., filterId="defaultExpressionFilter")
char2ExpressionFilter(expr, ..., filterId="defaultExpressionFilter")
```

**Arguments**

filterId	An optional parameter that sets the filterId of this <a href="#">filter</a> . The object can later be identified by this name.
expr	A valid R expression or a character vector that can be parsed into an expression.
...	Additional arguments that are passed to the evaluation environment of the expression.

**Details**

The expression is evaluated in the environment of the flow cytometry values, hence the parameters of a [flowFrame](#) can be accessed through regular R symbols. The convenience function `char2ExpressionFilter` exists to programmatically construct expressions.

**Value**

Returns a expressionFilter object for use in filtering [flowFrames](#) or other flow cytometry objects.

**Extends**

Class "[concreteFilter](#)", directly.

Class "[filter](#)", by class concreteFilter, distance 2.

**Slots**

**expr**: The expression that will be evaluated in the context of the flow cytometry values.

**args**: An environment providing additional parameters.

**deparse**: A character scalar of the deparsed expression.

**filterId**: The identifier of the filter

**Objects from the Class**

Objects can be created by calls of the form `new("expressionFilter", ...)`, using the [expressionFilter](#) constructor or, programmatically, from a character string using the `char2ExpressionFilter` function.

**Methods**

**%in%** signature(`x = "flowFrame"`, `table = "expressionFilter"`): The workhorse used to evaluate the gate on data. This is usually not called directly by the user, but internally by calls to the [filter](#) methods.

**show** signature(`object = "expressionFilter"`): Print information about the gate.

**Author(s)**

F. Hahne, B. Ellis

**See Also**

[flowFrame](#), [filter](#) for evaluation of sampleFilters and [split](#) and [Subset](#) for splitting and sub-setting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

#Create the filter
ef <- expressionFilter(FSC-H > 200, filterId="myExpressionFilter")
ef
```

```

## Filtering using sampeFilters
fres <- filter(dat, ef)
fres
summary(fres)

## The result of sample filtering is a logical subset
newDat <- Subset(dat, fres)
all(exprs(newDat)[,"FSC-H"] > 200)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
split(dat, fres)

## Programmatically construct an expression
dat <- dat[,-8]
r <- range(dat)
cn <- paste("", colnames(dat), "", sep="")
exp <- paste(cn, ">", r[1,], "&", cn, "<", r[2,], collapse=" & ")
ef2 <- char2ExpressionFilter(exp, filterId="myExpressionFilter")
ef2
fres2 <- filter(dat, ef2)
fres2
summary(fres2)

```

---

fcReference-class      *Class "fcReference" and its subclasses*

---

## Description

Classes and methods to provide reference-based semantics for flow cytometry workflows.

## Usage

```

fcReference(ID=paste("genericRef", guid(), sep="_"), env=new.env(parent=emptyenv()))
fcTreeReference(ID=paste("treeRef", guid(), sep="_"), env=new.env(parent=emptyenv()))
fcAliasReference(ID=paste("aliasRef", guid(), sep="_"), env=new.env(parent=emptyenv()))
fcDataReference(ID=paste("dataRef", guid(), sep="_"), env=new.env(parent=emptyenv()))
fcActionReference(ID=paste("actionRef", guid(), sep="_"), env=new.env(parent=emptyenv()))
fcViewReference(ID=paste("viewRef", guid(), sep="_"), env=new.env(parent=emptyenv()))
fcFilterResultReference(ID=paste("fresRef", guid(), sep="_"), env=new.env(parent=emptyenv()))

```

```

fcFilterReference(ID=paste("filterRef", guid(), sep="_"), env=new.env(parent=emptyenv()))

fcCompensateReference(ID=paste("compRef",
                               guid(), sep="_"),
                      env=new.env(parent=emptyenv()))

fcNormalizationReference(ID=paste("normRef",
                                   guid(), sep="_"),
                          env=new.env(parent=emptyenv()))

fcSubsettingReference(ID=paste("subRef",
                                guid(), sep="_"),
                       env=new.env(parent=emptyenv()))

fcTransformReference(ID=paste("transRef",
                               guid(), sep="_"),
                      env=new.env(parent=emptyenv()))

fcNullReference(...)

assign(x, value, pos = -1, envir = as.environment(pos), inherits = FALSE,
       immediate = TRUE)

## S4 method for signature fcReference,missing,missing
get(x, pos = -1, envir = as.environment(pos), mode = "any",
    inherits = TRUE)

isNull(f)

Rm(symbol, envir, subSymbol, ...)

```

### Arguments

<code>x, f, symbol</code>	An object of class or inheriting from class <code>fcReference</code> .
<code>ID</code>	The reference identifier.
<code>value</code>	An arbitrary R object which is supposed to be assigned to the environment in the <code>workFlow</code> object and to which a reference is returned.
<code>env</code>	An environment, usually within a <code>workFlow</code> object.
<code>pos, envir</code>	Objects of class <code>workFlow</code> .
<code>inherits, immediate, mode, subSymbol, ...</code>	Further arguments from the generics that are not used in this context.

### Details

These classes provide references to objects within an R environment and allow for method dispatch based on the nature of the referenced object. The parent `fcReference` class is used for references to

all R objects, unless there exists a more specific subclass. `fcTreeReference`, `fcViewReference`, and `fcActionReference` are used to reference to `graphNEL`, `view`, and `actionItem` objects, respectively. `fcDataReference` should be used for `flowFrame` or `flowSet` objects, whereas `fcFilterResultReference`, `fcFilterReference`, `fcTransformReference`, `fcCompensateReference`, and `fcNormalizationReference` link to `filterResult`, `filter`, `transform` and `compensation` objects. `fsStructureReference` only exists to jointly dispatch on certain subgroups of references.

### Value

An object of class `fcReference` or one of its subclasses for the `assign` constructor.

The object referenced to for the `get` method.

A character string of the object symbol for the `identifier` method.

A logical scalar for the `isNull` method.

### Extends

`fcStructureReference`:

Class "`fcReference`", directly.

`fcTreeReference`:

Class "`fcStructureReference`", directly. Class "`fcReference`", by class "`fcStructureReference`", distance 2.

`fcAliasReference`:

Class "`fcStructureReference`", directly. Class "`fcReference`", by class "`fcStructureReference`", distance 2.

`fcDataReference`:

Class "`fcReference`", directly.

`fcActionReference`:

Class "`fcStructureReference`", directly. Class "`fcReference`", by class "`fcStructureReference`", distance 2.

`fcViewReference`:

Class "`fcStructureReference`", directly. Class "`fcReference`", by class "`fcStructureReference`", distance 2.

`fcFilterResultReference`:

Class "`fcReference`", directly.

`fcFilterReference`:

Class "`fcReference`", directly.

`fcCompensateReference`:

Class "`fcReference`", directly.

`fcTransformReference`:

Class "`fcReference`", directly.

`fcNormalizationReference`:

Class "fcReference", directly.

fcNullReference:

Class "fcDataReference", directly. Class "fcActionReference", directly. Class "fcViewReference", directly. Class "fcFilterResultReference", directly. Class "fcFilterReference", directly. Class "fcCompensateReference", directly. Class "fcTransformReference", directly. Class "fcNormalizationReference", directly. Class "fcTreeReference", directly. Class "fcAliasReference", directly. Class "fcReference", by class "fcDataReference", distance2. Class "fcStructureReference", by class "fcActionReference", distance 2. Class "fcReference", by class "fcActionReference", distance 3. Class "fcStructureReference", by class "fcViewReference", distance 2. Class "fcReference", by class "fcViewReference", distance3. Class "fcReference", by class "fcFilterResultReference", distance 2. Class "fcReference", by class "fcFilterReference", distance 2. Class "fcReference", by class "fcCompensateReference", distance 2. Class "fcReference", by class "fcTransformReference", distance 2. Class "fcStructureReference", by class "fcTreeReference", distance 2. Class "fcReference", by class "fcTreeReference", distance 3.

### Objects from the Class

Objects should be created via the assign constructor. Whenever an object is assigned to a `workFlow` using the assign method, an appropriate instance of class `fcReference` or one of its subclasses is returned. In addition, there are the usual constructor functions of same names as the classes that can be used for object instantiation without assignment. Note that this might lead to unresolvable references unless the object referenced to is available in the environment.

### Slots

**ID:** Object of class "character" The name of the object in env referenced to.

**env:** Object of class "environment" An environment that contains the referenced objects. Usually, this will be the environment that's part of a `workFlow` object.

### Methods

**get** signature(x = "fcReference", pos = "missing", envir = "missing", mode = "missing", inherits = "missing")  
Resolve the reference, i.e., get the object from the environment.

**get** signature(x = "fcNullReference", pos = "missing", envir = "missing", mode = "missing", inherits = "missing")  
Resolve the reference. This always returns NULL.

**identifier** signature(object = "fcReference"): Return a character string of the object name.

**isNull** signature(f = "fcReference"): Check whether a `fcReference` is a NULL reference. Note that this is different from an unresolvable reference.

**Rm** signature(symbol = "fcReference", envir = "missing", subSymbol = "character"): Remove the object referenced to by a `fcReference` from its environment. The argument `subSymbol` will be automatically set by the generic and should never be provided by the user.

**Rm** signature(symbol = "fcReference", envir = "workFlow", subSymbol = "character"): Remove the object referenced to by a `fcReference` from a `workFlow`. The argument `subSymbol` will be automatically set by the generic and should never be provided by the user.

**Rm** signature(symbol = "fcNullReference", envir = "missing", subSymbol = "character"): Essentially, this doesn't do anything since there is no object referenced to.

**show** signature(object = "fcReference"): Print details about the object.

**show** signature(object = "fcNullReference"): Print details about the object.

### Author(s)

Florian Hahne

### See Also

[workFlow](#)

### Examples

```
showClass("fcReference")
```

---

FCSTransTransform	<i>Computes a transform using the 'iplogicle' function</i>
-------------------	--

---

### Description

Transforms FCS data using the iplogicle function from FCSTrans by Quian et al. The core functionality of FCSTrans has been imported to produce transformed FCS data rescaled and truncated as produced by FCSTrans. The w parameter is estimated by iplogicle automatically, then makes a call to iplogicle which in turn uses the logicle transform code of Wayne Moore.

For the details of the FCSTrans transformation, we recommend the excellent Supplementary File that accompanies Quian et al. (2012): <http://onlinelibrary.wiley.com/doi/10.1002/cyto.a.22037/suppinfo>

### Usage

```
FCSTransTransform(transformationId = "defaultFCSTransTransform", channelrange = 2^18, channeldecade =
```

### Arguments

transformationId	A name to assign to the transformation. Used by the transform/filter routines.
channelrange	is the range of the data. By default, $2^{18} = 262144$ .
channeldecade	is the number of logarithmic decades. By default, it is set to 4.5.
range	the target resolution. The default value is $2^{12} = 4096$ .
cutoff	a threshold below which the logicle transformation maps values to 0.
w	the logicle width. This is estimated by iplogicle by default. Details can be found in the Supplementary File from Quian et al.
rescale	logical parameter whether or not the data should be rescaled to the number of channels specified in range. By default, the value is TRUE but can be set to FALSE if you want to work on the transformed scale.

**Author(s)**

Wayne Moore, N Gopalakrishnan

**References**

Y Quian, Y Liu, J Campbell, E Thompson, YM Kong, RH Scheuermann; FCSTrans: An open source software system for FCS file conversion and data transformation. Cytometry A, 2012

**See Also**

[inverseLogicleTransform](#), [estimateLogicle](#) , [logicleTransform](#)

**Examples**

```
data(GvHD)
samp <- GvHD[[1]]
## User defined logicle function
lgcl <- FCSTransTransform()
after <- transform(samp, FL1-H = lgcl(FL1-H), FL2-H = lgcl(FL2-H))
```

---

filter

*Filter FCS files*

---

**Description**

These methods link filter descriptions to a particular set of flow cytometry data allowing for the lightweight calculation of summary statistics common to flow cytometry analysis.

**Usage**

```
filter(x, filter, method = c("convolution", "recursive"),
       sides = 2L, circular = FALSE, init = NULL)
```

**Arguments**

**x** Object of class [flowFrame](#) or [flowSet](#).

**filter** An object of class [filter](#) or a named list filters.

**method, sides, circular, init** These arguments are not used.



## Details

The `filter` method conceptually links a filter description, represented by a `filter` object, to a particular `flowFrame`. This is accomplished via the `filterResult` object, which tracks the linked frame as well as caching the results of the filtering operation itself, allowing for fast calculation of certain summary statistics such as the percentage of events accepted by the filter. This method exists chiefly to allow the calculation of these statistics without the need to first `Subset` a `flowFrame`, which can be quite large.

When applying on a `flowSet`, the `filter` argument can either be a single filter object, in which case it is recycled for all frames in the set, or a named list of filter objects. The names are supposed to match the frame identifiers (i.e., the output of `sampleNames(x)` of the `flowSet`). If some frames identifiers are missing, the particular frames are skipped during filtering. Accordingly, all filters in the filter list that can't be mapped to the `flowSet` are ignored. Note that all filter objects in the list must be of the same type, e.g. `rectangleGates`.

## Value

A `filterResult` object or a `filterResultList` object if `x` is a `flowSet`. Note that `filterResult` objects are themselves filters, allowing them to be used in filter expressions or `Subset` operations.

## Author(s)

F Hahne, B. Ellis, N. Le Meur

## See Also

[Subset](#), [filterResult](#)

## Examples

```
## Filtering a flowFrame
samp <- read.FCS(system.file("extdata","0877408774.B08", package="flowCore"))
rectGate <- rectangleGate(filterId="nonDebris", "FSC-H"=c(200,Inf))
fr <- filter(samp,rectGate)
class(fr)
summary(fr)

## filtering a flowSet
data(GvHD)
foo <- GvHD[1:3]
fr2 <- filter(foo, rectGate)
class(fr2)
summary(fr2)

## filtering a flowSet using different filters for each frame
rg2 <- rectangleGate(filterId="nonDebris", "FSC-H"=c(300,Inf))
rg3 <- rectangleGate(filterId="nonDebris", "FSC-H"=c(400,Inf))
flist <- list(rectGate, rg2, rg3)
names(flist) <- sampleNames(foo)
fr3 <- filter(foo, flist)
```

---

filter-and-methods      *Take the intersection of two filters*

---

### Description

There are two notions of intersection in flowCore. First, there is the usual intersection boolean operator & that has been overridden to allow the intersection of two filters or of a filter and a list for convenience. There is also the %% or %subset% operator that takes an intersection, but with subset semantics rather than simple intersection semantics. In other words, when taking a subset, calculations from [summary](#) and other methods are taken with respect to the right hand filter. This primarily affects calculations, which are ordinarily calculated with respect to the entire population as well as data-driven gating procedures which will operate only on elements contained by the right hand filter. This becomes especially important when using filters such as [norm2Filter](#)

### Author(s)

B. Ellis

---

filter-class      *A class for representing filtering operations to be applied to flow data.*

---

### Description

The filter class is the virtual base class for all filter/gating objects in flowCore. In general you will want to subclass or create a more specific filter.

### Slots

**filterId:** A character vector that identifies this filter. This is typically user specified but can be automatically deduced by certain filter operations, particularly boolean and set operations.

### Objects from the Class

All [filter](#) objects in flowCore should be instantiated through their constructors. These are functions that share the same name with the respective filter classes. E.g., [rectangleGate\(\)](#) is the constructor function for rectangular gates, and [kmeansFilter\(\)](#) creates objects of class [kmeansFilter](#). Usually these constructors can deal with various different inputs, allowing to utilize the same function in different programmatic or interactive settings. For all filters that operate on specific flow parameters (i.e., those inheriting from [parameterFilter](#)), the parameters need to be passed to the constructor, either as names or colnames of additional input arguments or explicitly as separate arguments. See the documentation of the respective filter classes for details. If parameters are explicitly defined as separate arguments, they may be of class character, in which case they will be evaluated literally as colnames in a [flowFrame](#), or of class [transform](#), in which case the filtering is performed on a temporarily transformed copy of the input data. See [here](#) for details.

## Methods

`%in%` Used in the usual way this returns a vector of values that identify which events were accepted by the filter. A single filter may encode several populations so this can return either a logical vector, a factor vector or a numeric vector of probabilities that the event is accepted by the filter. Minimally, you must implement this method when creating a new type of filter

`&`, `|`, `!` Two filters can be composed using the usual boolean operations returning a filter class of a type appropriate for handling the operation. These methods attempt to guess an appropriate `filterId` for the new filter

`%subset%, %%%` Defines a filter as being a subset of another filter. For deterministic filters the results will typically be equivalent to using an `&` operation to compose the two filters, though summary methods will use subset semantics when calculating proportions. Additionally, when the filter is data driven, such as `norm2Filter`, the subset semantics are applied to the data used to fit the filter possibly resulting in quite different, and usually more desirable, results.

`%on%` Used in conjunction with a `transformList` to create a `transformFilter`. This filter is similar to the subset filter in that the filtering operation takes place on transformed values rather than the original values.

`filter` A more formal version of `%in%`, this method returns a `filterResult` object that can be used in subsequent filter operations as well as providing more metadata about the results of the filtering operation

`summarizeFilter` When implementing a new filter this method is used to update the `filterDetails` slot of a `filterResult`. It is optional and typically only needs to be implemented for data-driven filters.

## Author(s)

B. Ellis, P.D. Haaland and N. LeMeur

## See Also

[transform](#), [filter](#)

---

filter-in-methods

*Filter-specific membership methods*

---

## Description

Membership methods must be defined for every object of type `filter` with respect to a `flowFrame` object. The operation is considered to be general and may return a logical, numeric or factor vector that will be handled appropriately. The ability to handle logical matrices as well as vectors is also planned but not yet implemented.

## Author(s)

F.Hahne, B. Ellis

---

filterDetails-methods *Obtain details about a filter operation*

---

### Description

A filtering operation captures details about its metadata and stores it in a `filterDetails` slot that is accessed using the `filterDetails` method. Each set of metadata is indexed by the `filterId` of the filter allowing for all the metadata in a complex filtering operation to be recovered after the final filtering.

### Methods

**result = "filterResult", filterId = "missing"** When no particular `filterId` is specified all the details are returned

**result = "filterResult", filterId = "ANY"** You can also obtain a particular subset of details

### Author(s)

B. Ellis, P.D. Haaland and N. LeMeur

---

filterList-class *Class "filterList"*

---

### Description

Container for a list of `filter` objects. The class mainly exists for method dispatch.

### Usage

```
filterList(x, filterId=identifier(x[[1]]))
```

### Arguments

<code>x</code>	A list of <code>filter</code> objects.
<code>filterId</code>	The global identifier of the filter list. As default, we take the <code>filterId</code> of the first <code>filter</code> object in <code>x</code> .

### Value

A `filterList` object for the constructor

### Objects from the Class

Objects are created from regular lists using the constructor `filterList`.

**Slots**

**.Data:** Object of class "list". The class directly extends list, and this slot holds the list data.  
**filterId:** Object of class "character". The identifier for the object.

**Extends**

Class "[list](#)", from data part.

**Methods**

**show** signature(object = "filterList"): Print details about the object.  
**identifier, identifier<-** signature(object = "filterList"): Accessor and replacement method for the object's filterId slot.

**Author(s)**

Florian Hahne

**See Also**

[filter](#),

**Examples**

```
f1 <- rectangleGate(FSC=c(100,200), filterId="testFilter")
f2 <- rectangleGate(FSC=c(200,400))
f1 <- filterList(list(a=f1, b=f2))
f1
identifier(f1)
```

---

filterReference-class *Class filterReference*

---

**Description**

A reference to another filter inside a reference. Users should generally not be aware that they are using this class, but it is used heavily by "[filterSet](#)" classes.

**Objects from the Class**

Objects are generally not created by users so there is no constructor function.

**Slots**

**name:** The R name of the referenced filter

**env:** The environment where the filter must live

**filterId:** The filterId, not really used since you always resolve

**Extends**

Class "[filter](#)", directly.

**Author(s)**

B. Ellis

**See Also**

["filterSet"](#)

---

filterResult-class	<i>Class "filterResult"</i>
--------------------	-----------------------------

---

**Description**

Container to store the result of applying a filter on a flowFrame object

**Slots**

**frameId:** Object of class "character" referencing the flowFrame object filtered. Used for sanity checking.

**filterDetails:** Object of class "list" describing the filter applied

**filterId:** Object of class "character" referencing the filter applied

**Extends**

Class "[filter](#)", directly.

**Methods**

**==** test equality

**Author(s)**

B. Ellis, N. LeMeur

**See Also**

[filter](#), ["logicalFilterResult"](#), ["multipleFilterResult"](#), ["randomFilterResult"](#)

**Examples**

```
showClass("filterResult")
```

---

```
filterResultList-class
```

```
Class "filterResultList"
```

---

**Description**

Container to store the result of applying a filter on a flowSet object

**Objects from the Class**

Objects are created by applying a [filter](#) on a [flowSet](#). The user doesn't have to deal with manual object instantiation.

**Slots**

**.Data:** Object of class "list". The class directly extends list, and this slot holds the list data.

**frameId:** Object of class "character" The IDs of the [flowFrames](#) in the filtered [flowSet](#).

**filterDetails:** Object of class "list". Since filterResultList inherits from [filterResult](#), this slot has to be set. It contains only the input filter.

**filterId:** Object of class "character". The identifier for the object.

**Extends**

Class "[list](#)", from data part. Class "[filterResult](#)", directly. Class "[concreteFilter](#)", by class "[filterResult](#)", distance 2. Class "[filter](#)", by class "[filterResult](#)", distance 3.

**Methods**

[ signature(x = "filterResultList", i = "ANY"): Subset to filterResultList.

[[ signature(x = "filterResultList", i = "ANY"): Subset to individual [filterResult](#).

**names** signature(x = "filterResultList"): Accessor to the frameId slot.

**parameters** signature(object = "filterResultList"): Return parameters on which data has been filtered.

**show** signature(object = "filterResultList"): Print details about the object.

**split** signature(x = "flowSet", f = "filterResultList"): Split a [flowSet](#) based on the results in the filterResultList. See [split](#) for details.

**summary** signature(object = "filterResultList"): Summarize the filtering operation. This creates a [filterSummaryList](#) object.

**Author(s)**

Florian Hahne

**See Also**

[filter](#), [filterResult](#), [logicalFilterResult](#), [multipleFilterResult](#), [randomFilterResult](#)

**Examples**

```
## Loading example data and creating a curv1Filter
data(GvHD)
dat <- GvHD[1:3]
c1f <- curv1Filter(filterId="myCurv1Filter", x=list("FSC-H"), bwFac=2)

## applying the filter
fres <- filter(dat, c1f)
fres

## subsetting the list
fres[[1]]
fres[1:2]

## details about the object
parameters(fres)
names(fres)
summary(fres)

## splitting based on the filterResults
split(dat, fres)
```

---

filters-class

*Class "filters" and "filtersList"*

---

**Description**

The filters class is the container for a list of [filter](#) objects. The class mainly exists for displaying multiple filters/gates on one single panel(flowFrame) of [xyplot](#). Note that it is different from [filerList](#) class which is to be applied to a flowSet. In other words, filter objects of a fliterList are to be applied to different flowFrames. However,all of filter objects of a filters are for one single flowFrame, more specifically for one pair of projections(parameters).So these filters should share the common parameters.

And filtersList is a list of filters objects,which are to be applied to a flowSet.

**Usage**

```
filters(x)
filtersList(x)
```

**Arguments**

x                    A list of filter or filters objects.



**Value**

A filters or filtersList object for the constructor

**Slots**

.Data: Object of class "list". The class directly extends list, and this slot holds the list data.

**Extends**

Class "list", from data part.

**Objects from the Class**

Objects are created from regular lists using the constructors filters and filtersList.

**Author(s)**

Mike Jiang

**See Also**

[filter](#), [filterList](#)

---

filterSet-class

*Class filterSet*

---

**Description**

A container for a collection of related filters.

**Objects from the Class**

There are several ways to create a filterSet object. There is the [filterSet](#) constructor, which creates an empty filterSet object (see the details section for more information). filterSet objects can also be coerced to and from list objects using the as function.

**Slots**

env: The environment that actually holds the filters

name: A more descriptive name of the set.

## Methods

- names** An unsorted list of the names of the filters contained within the set.
- sort** Returns a topological sort of the names of the filters contained within the set. Primarily used by internal functions (such as `filter`), this method is also useful for planning gating strategy layouts and the like.
- filterReference** Retrieves references to a filter inside a filterSet
- [ Returns the filter reference used inside the filter. See Details.
  - [[ Retrieves the actual filters from a filterSet. Note that composed filters can still contain references.
  - [[<- Put a filter into a filterSet. As a convenience, assigning to the "" or NULL name will use the filter's name for assignment. Composed filters can be added easily using formulas rather than attempting to construct filters the long way. The formula interface is also lazy, allowing you to add filters in any order.

## Details

`filterSet` objects are intended to provide a convenient grouping mechanism for a particular gating strategy. To accomplish this, much like the `flowSet` object, the `filterSet` object introduces reference semantics through the use of an environment, allowing users to change an upstream filter via the usual assignment mechanism and have that change reflected in all dependent filters. We do this by actually creating two filters for each filter in the `filterSet`. The first is the actual concrete filter, which is assigned to a variable of the form `.name` where `name` is the original filter name. A second `filterReference` filter is the created with the original name to point to the internal name. The allows us to evaluate a formula in the environment without creating a copy of the original filter.

## Author(s)

B. Ellis

## See Also

`filterSet`

## Examples

```
fs = new("filterSet")

## Simple assignment. Note that the filterId slot for the rectangle gate
## is changed.
fs[["filter1"]] = rectangleGate("FSC-H"=c(.2,.8),"SSC-H"=c(0,.8))

## Convenience assignment using the filterId slot.
fs[[""]] = norm2Filter("FSC-H","SSC-H",scale.factor=2,filterId="Live Cells")

## We also support formula interfaces. These two statements are equivalent.
fs[["Combined"]] = ~ filter1 %subset% Live Cells
fs[[""]] = Combined ~ filter1 %subset% Live Cells
fs
as(fs,"list")
```

```
as(as(fs,"list"),"filterSet")
```

---

```
filterSummary-class    Class "filterSummary"
```

---

### Description

Class and methods to handle the summary information of a gating operation.

### Usage

```
## S4 method for signature filterResult
summary(object, ...)
```

### Arguments

object	An object inheriting from class <code>filterResult</code> which is to be summarized.
...	Further arguments that are passed to the generic.

### Details

Calling `summary` on a `filterResult` object prints summary information on the screen, but also creates objects of class `filterSummary` for computational access.

### Value

An object of class `filterSummary` for the summary constructor, a named list for the subsetting operators. The `$` operator returns a named vector of the respective value, where each named element corresponds to one sub-population.

### Objects from the Class

Objects are created by calling `summary` on a `link{filterResult}` object. The user doesn't have to deal with manual object instantiation.

### Slots

**name:** Object of class "character". The name(s) of the populations created in the filtering operation. For a `logicalFilterResult` this is just a single value; the name of the `link{filter}`.

**true:** Object of class "numeric". The number of events within the population(s).

**count:** Object of class "numeric". The total number of events in the gated `flowFrame`.

**p:** Object of class "numeric". The percentage of cells in the population(s).

**Methods**

**[[** signature(x = "filterSummary", i = "numeric"): Subset the filterSummary to a single population. This only makes sense for [multipleFilterResults](#). The output is a list of summary statistics.

**[[** signature(x = "filterSummary", i = "character"): see above

**\\$** signature(x = "filterSummary", name = "ANY"): A list-like accessor to the slots and more. Valid values are n and count (those are identical), true and in (identical), false and out (identical), name, p and q (1-p).

**coerce** signature(from = "filterSummary", to = "data.frame"): Coerce object to data.frame.

**length** signature(x = "filterSummary"): The number of populations in the filterSummary.

**names** signature(x = "filterSummary"): The names of the populations in the filterSummary.

**print** signature(x = "filterSummary"): Print details about the object.

**show** signature(object = "filterSummary"): Print details about the object.

**toTable** signature(x = "filterSummary"): Coerce object to data.frame.

**Author(s)**

Florian Hahne, Byron Ellis

**See Also**

[filterResult](#), [logicalFilterResult](#), [multipleFilterResult](#), [flowFrame](#) [filterSummaryList](#)

**Examples**

```
## Loading example data, creating and applying a curv1Filter
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))
c1f <- curv1Filter(filterId="myCurv1Filter", x=list("FSC-H"), bwFac=2)
fres <- filter(dat, c1f)

## creating and showing the summary
summary(fres)
s <- summary(fres)

## subsetting
s[[1]]
s[["peak 2"]]

##accessing details
s$true
s$n
toTable(s)
```

---

filterSummaryList-class

*Class "filterSummaryList"*

---

### Description

Class and methods to handle summary statistics for from filtering operations on whole [flowSets](#).

### Arguments

object            An object of class [filterResultList](#) which is to be summarized.  
...                Further arguments that are passed to the generic.

### Details

Calling `summary` on a [filterResult](#) object prints summary information on the screen, but also creates objects of class `filterSummary` for computational access.

### Value

An object of class `filterSummaryList`.

### Objects from the Class

Objects are created by calling `summary` on a `link{filterResultList}` object. The user doesn't have to deal with manual object instantiation.

### Slots

`.Data`: Object of class "list". The class directly extends `list`, and this slot holds the list data.

### Extends

Class "[list](#)", from data part.

### Usage

```
summary(object, ...)
```

### Methods

**toTable** signature(`x = "filterSummaryList"`): Coerce object to `data.frame`. Additional factors are added to indicate list items in the original object.

### Author(s)

Florian Hahne

**See Also**

[filterResult](#), [filterResultList](#), [logicalFilterResult](#), [multipleFilterResult](#), [flowFrame](#)  
[filterSummary](#)

**Examples**

```
## Loading example data, creating and applying a curv1Filter
data(GvHD)
dat <- GvHD[1:3]
c1f <- curv1Filter(filterId="myCurv1Filter", x=list("FSC-H"), bwFac=2)
fres <- filter(dat, c1f)

## creating and showing the summary
summary(fres)
s <- summary(fres)

## subsetting
s[[1]]

##accessing details
toTable(s)
```

---

flowFrame-class	<i>'flowFrame': a class for storing observed quantitative properties for a population of cells from a FACS run</i>
-----------------	--

---

**Description**

This class represents the data contained in a FCS file or similar data structure. There are three parts of the data:

1. a numeric matrix of the raw measurement values with rows=events and columns=parameters
2. annotation for the parameters (e.g., the measurement channels, stains, dynamic range)
3. additional annotation provided through keywords in the FCS file

**Details**

Objects of class `flowFrame` can be used to hold arbitrary data of cell populations, acquired in flow-cytometry.

FCS is the Data File Standard for Flow Cytometry, the current version is FCS 3.0. See the vignette of this package for additional information on using the object system for handling of flow-cytometry data.

## Creating Objects

Objects can be created using

```
new("flowFrame",
  exprs      = ..., Object of class matrix
  parameters = ..., Object of class AnnotatedDataFrame
  description = ..., Object of class list
)
```

or the constructor `flowFrame`, with mandatory arguments `exprs` and optional arguments `parameters` and `description`.

```
flowFrame(exprs, parameters, description=list())
```

To create a `flowFrame` directly from an FCS file, use function `read.FCS`. This is the recommended and safest way of object creation, since `read.FCS` will perform basic data quality checks upon import. Unless you know exactly what you are doing, creating objects using `new` or the constructor is discouraged.

## Slots

**exprs:** Object of class `matrix` containing the measured intensities. Rows correspond to cells, columns to the different measurement channels. The `colnames` attribute of the matrix is supposed to hold the names or identifiers for the channels. The `rownames` attribute would usually not be set.

**parameters:** An `AnnotatedDataFrame` containing information about each column of the `flowFrame`. This will generally be filled in by `read.FCS` or similar functions using data from the FCS keywords describing the parameters.

**description:** A list containing the meta data included in the FCS file.

## Methods

There are separate documentation pages for most of the methods listed here which should be consulted for more details.

**Subsetting.** Returns an object of class `flowFrame`. The subsetting is applied to the `exprs` slot, while the `description` slot is unchanged. The syntax for subsetting is similar to that of `data.frames`. In addition to the usual index vectors (integer and logical by position, character by parameter names), `flowFrames` can be subset via `filterResult` and `filter` objects.

*Usage:*

```
flowFrame[i,j]
flowFrame[filter,]
flowFrame[filterResult,]
```

Note that the value of argument `drop` is ignored when subsetting `flowFrames`.

**\\$** **Subsetting by channel name.** This is similar to subsetting of columns of `data.frames`, i.e., `frame$FSC.H` is equivalent to `frame[, "FSC.H"]`. Note that column names may have to be quoted if they are no valid R symbols (e.g. `frame$"FSC-H"`).

**exprs, exprs<-** Extract or replace the raw data intensities. The replacement value must be a numeric matrix with `colnames` matching the parameter definitions. Implicit subsetting is allowed

(i.e. less columns in the replacement value compared to the original flowFrame, but all have to be defined there).

*Usage:*

```
exprs(flowFrame)
exprs(flowFrame) <- value
```

**head, tail** Show first/last elements of the raw data matrix

*Usage:*

```
head(flowFrame)
tail(flowFrame)
```

**description, description<-** Extract or replace the whole list of annotation keywords. Usually one would only be interested in a subset of keywords, in which case the keyword method is more appropriate. The optional hideInternal parameter can be used to exclude internal FCS parameters starting with\$.

*Usage:*

```
description(flowFrame)
description(flowFrame) <- value
```

**keyword, keyword<-** Extract or replace one or more entries from the description slot by keyword. Methods are defined for character vectors (select a keyword by name), functions (select a keyword by evaluating a function on their content) and for lists (a combination of the above). See [keyword](#) for details.

*Usage:*

```
keyword(flowFrame)
keyword(flowFrame, character)
keyword(flowFrame, list)
keyword(flowFrame) <- list(value)
```

**parameters, parameters<-** Extract parameters and return an object of class [AnnotatedDataFrame](#), or replace such an object. To access the actual parameter annotation, use `pData(parameters(frame))`. Replacement is only valid with [AnnotatedDataFrames](#) containing all varLabels name, desc, range, minRange and maxRange, and matching entries in the name column to the colnames of the exprs matrix. See [parameters](#) for more details.

*Usage:*

```
parameters(flowFrame)
parameters(flowFrame) <- value
```

**show** Display details about the flowFrame object.

**summary** Return descriptive statistical summary (min, max, mean and quantile) for each channel

*Usage:*

```
summary(flowFrame)
```

**plot** Basic plots for flowFrame objects. If the object has only a single parameter this produces a [histogram](#). For exactly two parameters we plot a bivariate density map (see [smoothScatter](#) and for more than two parameters we produce a simple [splom](#) plot. To select specific parameters from a flowFrame for plotting, either subset the object or specify the parameters as a character vector in the second argument to plot. The smooth parameters lets you toggle between density-type [smoothScatter](#) plots and regular scatterplots. For far more sophisticated plotting of flow cytometry data, see the [flowViz](#) package.



*Usage:*

```
plot(flowFrame, ...)
plot(flowFrame, character, ...)
plot(flowFrame, smooth=FALSE, ...)
```

**ncol, nrow, dim** Extract the dimensions of the data matrix.

*Usage:*

```
ncol(flowFrame)
nrow(flowFrame)
dim(flowFrame)
```

**featureNames, colnames, colnames<-** Extract parameter names (i.e., the colnames of the data matrix). colnames and featureNames are synonyms. For colnames there is also a replacement method. This will update the name column in the parameters slot as well.

*Usage:*

```
featureNames(flowFrame)
colnames(flowFrame)
colnames(flowFrame) <- value
```

**names** Extract pretty formatted names of the parameters including parameter descriptions.

*Usage:*

```
names(flowFrame)
```

**identifier** Extract GUID of a flowFrame. Returns the file name if no GUID is available. See [identifier](#) for details.

*Usage:*

```
identifier(flowFrame)
```

**range** Get dynamic range of the flowFrame. Note that this is not necessarily the range of the actual data values, but the theoretical range of values the measurement instrument was able to capture. The values of the dynamic range will be transformed when using the transformation methods for flowFrames. Additional character arguments are evaluated as parameter names for which to return the dynamic range.

*Usage:*

```
range(flowFrame, ...)
```

**each\_row, each\_col** Apply functions over rows or columns of the data matrix. These are convenience methods. See [each\\_col](#) for details.

*Usage:*

```
each_row(flowFrame, function, ...)
each_col(flowFrame, function, ...)
```

**transform** Apply a transformation function on a flowFrame object. This uses R's [transform](#) function by treating the flowFrame like a regular data.frame. flowCore provides an additional inline mechanism for transformations (see [%on%](#)) which is strictly more limited than the out-of-line transformation described here.

*Usage:*

```
transform(flowFrame, ...)
```

**filter** Apply a [filter](#) object on a flowFrame object. This returns an object of class [filterResult](#), which could then be used for subsetting of the data or to calculate summary statistics. See [filter](#) for details.

*Usage:*

```
filter(flowFrame, filter)
```

**split** Split flowFrame object according to a [filter](#), a [filterResult](#) or a factor. For most types of filters, an optional flowSet=TRUE parameter will create a [flowSet](#) rather than a simple list. See [split](#) for details.

*Usage:*

```
split(flowFrame, filter, flowSet=FALSE, ...)
split(flowFrame, filterResult, flowSet=FALSE, ...)
split(flowFrame, factor, flowSet=FALSE, ...)
```

**Subset** Subset a flowFrame according to a filter or a logical vector. The same can be done using the standard subsetting operator with a filter, filterResult, or a logical vector as first argument.

*Usage:*

```
Subset(flowFrame, filter)
Subset(flowFrame, logical)
```

**cbind2** Expand a flowFrame by the data in a numeric matrix of the same length. The matrix must have column names different from those of the flowFrame. The additional method for numerics only raises a useful error message.

*Usage:*

```
cbind2(flowFrame, matrix)
cbind2(flowFrame, numeric)
```

**compensate** Apply a compensation matrix (or a [compensation](#) object) on a flowFrame object. This returns a compensated flowFrame.

*Usage:*

```
compensate(flowFrame, matrix)    compensate(flowFrame, data.frame)
```

**spillover** Extract spillover matrix from description slot if present.

*Usage:*

```
spillover(flowFrame, matrix)
```

**==** Test equality between two flowFrames

**<, >, <=, >=** These operators basically treat the flowFrame as a numeric matrix.

**initialize(flowFrame):** Object instantiation, used by new; not to be called directly by the user.

### Author(s)

F. Hahne, B. Ellis, P. Haaland and N. Le Meur

### See Also

[flowSet](#), [read.FCS](#)

**Examples**

```
## load example data
data(GvHD)
frame <- GvHD[[1]]

## subsetting
frame[1:4,]
frame[,3]
frame[,"FSC-H"]
frame$"SSC-H"

## accessing and replacing raw values
head(exprs(frame))
exprs(frame) <- exprs(frame)[1:3000,]
frame
exprs(frame) <- exprs(frame)[,1:6]
frame

## access FCS keywords
head(description(frame))
keyword(frame, c("FILENAME", "$FIL"))

## parameter annotation
parameters(frame)
pData(parameters(frame))

## summarize frame data
summary(frame)

## plotting
plot(frame)
if(require(flowViz)){
  plot(frame)
  plot(frame, c("FSC-H", "SSC-H"))
  plot(frame[,1])
  plot(frame, c("FSC-H", "SSC-H"), smooth=FALSE)
}

## frame dimensions
ncol(frame)
nrow(frame)
dim(frame)

## accessing and replacing parameter names
featureNames(frame)
all(featureNames(frame) == colnames(frame))
colnames(frame) <- make.names(colnames(frame))
colnames(frame)
parameters(frame)$name
names(frame)
```

```
## accessing a GUID
identifier(frame)
identifier(frame) <- "test"

## dynamic range of a frame
range(frame)
range(frame, "FSC.H", "FL1.H")
range(frame)$FSC.H

## iterators
head(each_row(frame, mean))
head(each_col(frame, mean))

## transformation
opar <- par(mfcol=c(1:2))
if(require(flowViz))
plot(frame, c("FL1.H", "FL2.H"))
frame <- transform(frame, FL1.H=log(FL1.H), FL2.H=log(FL2.H))
if(require(flowViz))
plot(frame, c("FL1.H", "FL2.H"))
par(opar)
range(frame)

## filtering of flowFrames
rectGate <- rectangleGate(filterId="nonDebris", "FSC.H"=c(200,Inf))
fres <- filter(frame, rectGate)
summary(fres)

## splitting of flowFrames
split(frame, rectGate)
split(frame, rectGate, flowSet=TRUE)
split(frame, fres)
f <- cut(exprs(frame)$FSC.H, 3)
split(frame, f)

## subsetting according to filters and filter results
Subset(frame, rectGate)
Subset(frame, fres)
Subset(frame, as.logical(exprs(frame)$FSC.H < 300))
frame[rectGate,]
frame[fres,]

## accessing the spillover matrix
try(spillover(frame))

## check equality
frame2 <- frame
frame == frame2
exprs(frame2) <- exprs(frame)*2
frame == frame2
```

---

flowSet-class	<i>'flowSet': a class for storing flow cytometry raw data from quantitative cell-based assays</i>
---------------	---

---

## Description

This class is a container for a set of [flowFrame](#) objects

## Creating Objects

Objects can be created using

```
new(flowSet,
    frames = ..., # environment with flowFrames
    phenoData = ... # object of class AnnotatedDataFrame
    colnames = ... # object of class character
)
```

or via the constructor `flowSet`, which takes arbitrary numbers of `flowFrames`, either as a list or directly as arguments, along with an optional [AnnotatedDataFrame](#) for the `phenoData` slot and a character scalar for the name by which the object can be referenced.

```
flowSet(..., phenoData)
```

Alternatively, `flowSets` can be coerced from list and environment objects.

```
as(list("A"=frameA,"B"=frameB),"flowSet")
```

The safest and easiest way to create `flowSets` directly from FCS files is via the [read.flowSet](#) function, and there are alternative ways to specify the files to read. See the separate documentation for details.

## Slots

`frames`: An [environment](#) containing one or more [flowFrame](#) objects.

`phenoData`: A [AnnotatedDataFrame](#) containing the phenotypic data for the whole data set. Each row corresponds to one of the [flowFrames](#) in the `frames` slot. The `sampleNames` of `phenoData` (see below) must match the names of the [flowFrame](#) in the `frames` environment.

`colnames`: A character object with the (common) column names of all the data matrices in the [flowFrames](#).

## Methods

`[, [` Subsetting. `x[i]` where `i` is a scalar, returns a `flowSet` object, and `x[[i]]` a [flowFrame](#) object. In this respect the semantics are similar to the behavior of the subsetting operators for lists. `x[i, j]` returns a `flowSet` for which the parameters of each [flowFrame](#) have been subset according to `j`, `x[[i, j]]` returns the subset of a single [flowFrame](#) for all parameters in `j`. Similar to data frames, valid values for `i` and `j` are logicals, integers and characters.

*Usage:*

```
flowSet[i]
```

```
flowSet[i, j]
flowSet[[i]]
```

**\\$** Subsetting by frame name. This will return a single [flowFrame](#) object. Note that names may have to be quoted if they are no valid R symbols (e.g. `flowSet$"sample 1"`)

**colnames, colnames<-** Extract or replace the `colnames` slot.

*Usage:*

```
colnames(flowSet)
colnames(flowSet) <- value
```

**identifier, identifier<-** Extract or replace the name item from the environment.

*Usage:*

```
identifier(flowSet)
identifier(flowSet) <- value
```

**phenoData, phenoData<-** Extract or replace the [AnnotatedDataFrame](#) from the `phenoData` slot.

*Usage:*

```
phenoData(flowSet)
phenoData(flowSet) <- value
```

**pData, pData<-** Extract or replace the data frame (or columns thereof) containing actual phenotypic information from the `phenoData` slot.

*Usage:*

```
pData(flowSet)
pData(flowSet)$someColumn <- value
```

**varLabels, varLabels<-** Extract and set `varLabels` in the [AnnotatedDataFrame](#) of the `phenoData` slot.

*Usage:*

```
varLabels(flowSet)
varLabels(flowSet) <- value
```

**sampleNames** Extract and replace sample names from the `phenoData` object. Sample names correspond to frame identifiers, and replacing them will also replace the `GUID` slot for each frame. Note that `sampleName` need to be unique.

*Usage:*

```
sampleNames(flowSet)
sampleNames(flowSet) <- value
```

**keyword** Extract or replace keywords specified in a character vector or a list from the `description` slot of each frame. See [keyword](#) for details.

*Usage:*

```
keyword(flowSet, list(keywords))
keyword(flowSet, keywords)
keyword(flowSet) <- list(foo="bar")
```

**length** number of [flowFrame](#) objects in the set.

*Usage:*

```
length(flowSet)
```

**show** display object summary.

**summary** Return descriptive statistical summary (min, max, mean and quantile) for each channel of each `flowFrame`

*Usage:*

```
summary(flowSet)
```

**fsApply** Apply a function on all frames in a `flowSet` object. Similar to `sapply`, but with additional parameters. See separate documentation for details.

*Usage:*

```
fsApply(flowSet, function, ...)
fsApply(flowSet, function, use.exprs=TRUE, ...)
```

**compensate** Apply a compensation matrix on all frames in a `flowSet` object. See separate documentation for details.

*Usage:*

```
compensate(flowSet, matrix)
```

**transform** Apply a transformation function on all frames of a `flowSet` object. See separate documentation for details.

*Usage:*

```
transform(flowSet, ...)
```

**filter** Apply a filter object on a `flowSet` object. There are methods for `filters`, `filterSets` and lists of filters. The latter has to be a named list, where names of the list items are matching sampleNames of the `flowSet`. See `filter` for details.

*Usage:*

```
filter(flowSet, filter)
filter(flowSet, list(filters))
```

**split** Split all `flowSet` objects according to a `filter`, `filterResult` or a list of such objects, where the length of the list has to be the same as the length of the `flowSet`. This returns a list of `flowFrames` or an object of class `flowSet` if the `flowSet` argument is set to `TRUE`. Alternatively, a `flowSet` can be split into separate subsets according to a factor (or any vector that can be coerced into factors), similar to the behaviour of `split` for lists. This will return a list of `flowSets`. See `split` for details.

*Usage:*

```
split(flowSet, filter)
split(flowSet, filterResult)
split(flowSet, list(filters))
split(flowSet, factor)
```

**Subset** Returns a `flowSet` of `flowFrames` that have been subset according to a `filter` or `filterResult`, or according to a list of such items of equal length as the `flowSet`.

*Usage:*

```
Subset(flowSet, filter)
Subset(flowSet, filterResult)
Subset(flowSet, list(filters))
```

**rbind2** Combine two `flowSet` objects, or one `flowSet` and one `flowFrame` object.

*Usage:*

```
rbind2(flowSet, flowSet)
rbind2(flowSet, flowFrame)
```

**spillover** Compute spillover matrix from a compensation set. See separate documentation for details.

### Important note on storage and performance

The bulk of the data in a `flowSet` object is stored in an `environment`, and is therefore not automatically copied when the `flowSet` object is copied. If `x` is an object of class `flowSet`, then the code

```
y <- x
```

will create an object `y` that contains copies of the `phenoData` and administrative data in `x`, but refers to the *same* environment with the actual fluorescence data. See below for how to create proper copies.

The reason for this is performance. The pass-by-value semantics of function calls in R can result in numerous copies of the same data object being made in the course of a series of nested function calls. If the data object is large, this can result in considerable cost of memory and performance. `flowSet` objects are intended to contain experimental data in the order of hundreds of Megabytes, which can effectively be treated as read-only: typical tasks are the extraction of subsets and the calculation of summary statistics. This is afforded by the design of the `flowSet` class: an object of that class contains a `phenoData` slot, some administrative information, and a *reference* to an environment with the fluorescence data; when it is copied, only the reference is copied, but not the potentially large set of fluorescence data themselves.

However, note that subsetting operations, such as `y <- x[i]` do create proper copies, including a copy of the appropriate part of the fluorescence data, as it should be expected. Thus, to make a proper copy of a `flowSet` `x`, use `y <- x[seq(along=x)]`

### Author(s)

F. Hahne, B. Ellis, P. Haaland and N. Le Meur

### See Also

[flowFrame](#), [read.flowSet](#)

### Examples

```
## load example data and object creation
data(GvHD)

## subsetting to flowSet
set <- GvHD[1:4]
GvHD[1:4, 1:2]
sel <- sampleNames(GvHD)[1:2]
GvHD[sel, "FSC-H"]
GvHD[sampleNames(GvHD) == sel[1], colnames(GvHD[1]) == "SSC-H"]

## subsetting to flowFrame
GvHD[[1]]
```



```

GvHD[[1, 1:3]]
GvHD[[1, "FSC-H"]]
GvHD[[1, colnames(GvHD[1]) == "SSC-H"]]
GvHD$s5a02

## constructor
flowSet(GvHD[[1]], GvHD[[2]])
pd <- phenoData(GvHD)[1:2,]
flowSet(s5a01=GvHD[[1]], s5a02=GvHD[[2]],phenoData=pd)

## colnames
colnames(set)
colnames(set) <- make.names(colnames(set))

## object name
identifier(set)
identifier(set) <- "test"

## phenoData
pd <- phenoData(set)
pd
pd$test <- "test"
phenoData(set) <- pd
pData(set)
varLabels(set)
varLabels(set)[6] <- "Foo"
varLabels(set)

## sampleNames
sampleNames(set)
sampleNames(set) <- LETTERS[1:length(set)]
sampleNames(set)

## keywords
keyword(set, list("transformation"))

## length
length(set)

## compensation
samp <- read.flowSet(path=system.file("extdata","compdata","data",
package="flowCore"))
cfile <- system.file("extdata","compdata","compmatrix", package="flowCore")
comp.mat <- read.table(cfile, header=TRUE, skip=2, check.names = FALSE)
comp.mat
summary(samp[[1]])
samp <- compensate(samp, as.matrix(comp.mat))
summary(samp[[1]])

## transformation
opar <- par(mfcol=c(1:2))
plot(set[[1]], c("FL1.H", "FL2.H"))
set <- transform(set, FL1.H=log(FL1.H), FL2.H=log(FL2.H))

```

```

plot(set[[1]], c("FL1.H", "FL2.H"))
par(opar)

## filtering of flowSets
rectGate <- rectangleGate(filterId="nonDebris", FSC.H=c(200,Inf))
fres <- filter(set, rectGate)
class(fres)
summary(fres[[1]])
rectGate2 <- rectangleGate(filterId="nonDebris2", SSC.H=c(300,Inf))
fres2 <- filter(set, list(A=rectGate, B=rectGate2, C=rectGate, D=rectGate2))

## Splitting frames of a flowSet
split(set, rectGate)
split(set[1:2], rectGate, populatiuon="nonDebris2+")
split(set, c(1,1,2,2))

## subsetting according to filters and filter results
Subset(set, rectGate)
Subset(set, filter(set, rectGate))
Subset(set, list(A=rectGate, B=rectGate2, C=rectGate, D=rectGate2))

## combining flowSets
rbind2(set[1:2], set[3:4])
rbind2(set[1:3], set[[4]])
rbind2(set[[4]], set[1:2])

```

---

fsApply

*Apply a Function over values in a flowSet*


---

## Description

fsApply like many of the apply-style functions in R acts as an iterator for flowSet objects, allowing the application of a function to either the flowFrame or the data matrix itself. The output can be reconstructed as either a flowSet, a list or a matrix depending on options and the type of objects returned.

## Usage

```
fsApply(x, FUN, ..., simplify=TRUE, use.exprs=FALSE)
```

## Arguments

x	flowSet to be used
FUN	the function to be applied to each element of x
simplify	logical (default: TRUE); if all true and all objects are flowFrame objects, a flowSet object will be constructed. If all of the values are of the same type there will be an attempt to construct a vector or matrix of the appropriate type (e.g. all numeric results will return a matrix).

use.exprs      logical (default: FALSE); should the FUN be applied on the [flowFrame](#) object or the expression values.

...            optional arguments to FUN.

**Author(s)**

B. Ellis

**See Also**

[apply](#), [sapply](#)

**Examples**

```
fcs.loc <- system.file("extdata",package="flowCore")
file.location <- paste(fcs.loc, dir(fcs.loc), sep="/")
samp <- read.flowSet(file.location[1:3])

#Get summary information about each sample.
fsApply(samp,summary)

#Obtain the median of each parameter in each frame.
fsApply(samp,each_col,median)
```

---

gateActionItem-class    *Class "gateActionItem"*

---

**Description**

Class and method to capture gating operations in a flow cytometry workflow.

**Usage**

```
gateActionItem(ID = paste("gateActionRef", guid(), sep = "_"), name =
paste("action", identifier(get(gate)), sep = "_"), parentView, gate,
filterResult, workflow)
```

**Arguments**

workflow      An object of class [workFlow](#) for which a view is to be created.

ID            A unique identifier of the view, most likely created by using the internal guid function.

name          A more human-readable name of the view.

parentView, gate, filterResult      References to the parent [view](#), [filter](#), and [filterResult](#) objects, respectively.

## Details

gateActionItems provide a means to bind gating operations in a workflow. Each gateActionItem represents a single [filter](#).

## Value

A reference to the gateActionItem that is created inside the [workFlow](#) environment as a side effect of calling the add method.

A gateActionItem object for the constructor.

## Objects from the Class

Objects should be created using the add method, which creates a gateActionItem from a [filter](#) object and directly assigns it to a [workFlow](#). Alternatively, one can use the gateActionItem constructor function for more programmatic access.

## Slots

**gate:** Object of class "fcFilterReference". A reference to the [filter](#) that is used for the gating operation.

**filterResult:** Object of class "fcFilterResultReference". A reference to the [filterResult](#) produced by the gating operation.

**ID:** Object of class "character". A unique identifier for the actionItem.

**name:** Object of class "character". A more human-readable name

**parentView:** Object of class "fcViewReference". A reference to the parent [view](#) the gateActionItem is applied on.

**env:** Object of class "environment". The evaluation environment in the [workFlow](#).

## Extends

Class "[actionItem](#)", directly.

## Methods

**gate** signature(object = "gateActionItem"): Accessor to the gate slot. Note that this resolved the reference, i.e., the [filter](#) object is returned.

**print** signature(x = "gateActionItem"): Print details about the object.

**Rm** signature(symbol = "gateActionItem", envir = "workFlow", subSymbol = "character"): Remove a gateActionItem from a [workFlow](#). This method is recursive and will also remove all dependent views and [actionItems](#).

**show** signature(object = "gateActionItem"): Print details about the object.

**summary** signature(object = "gateActionItem"): Summarize the gating operation and return the appropriate [filterSummary](#) object.

## Author(s)

Florian Hahne

**See Also**

[workFlow](#), [actionItem](#), [transformActionItem](#), [compensateActionItem](#), [view](#)

**Examples**

```
showClass("view")
```

---

gateView-class	<i>Class "gateView"</i>
----------------	-------------------------

---

**Description**

Class and method to capture the result of gating operations in a flow cytometry workflow.

**Usage**

```
gateView(workflow, ID=paste("gateViewRef", guid(), sep="_"),
         name="default", action, data, indices,
         filterResult, frEntry)
```

**Arguments**

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal guid function.
name	A more human-readable name of the view.
data, action, filterResult	References to the data, <a href="#">filterResult</a> , and <a href="#">actionItem</a> objects, respectively.
indices	A logical vector of indices in the parent data.
frEntry	A character vector indicating the name of the population in the <a href="#">filterResult</a> .

**Details**

gateViews provide a means to bind the results of gating operations in a workflow. Each gateView represents one of the populations that arise from the gating. [logicalFilterResults](#) create two gateViews (events in the gate and events not in the gate), [multipleFilterResults](#) one view for each population. See the documentation of the parent class [view](#) for more details.

**Value**

A reference to the gateView that is created inside the [workFlow](#) environment as a side effect of calling the add method.

A gateView object for the constructor.

## Objects from the Class

Objects should be created using the add method, which creates a `gateView` from a `filter` object and directly assigns it to a `workFlow`. Alternatively, one can use the `gateView` constructor function for more programmatic access.

## Slots

`indices`: Object of class "logical". The indices in the parent data for events that are within the filter.

`filterResult`: Object of class "fcFilterResultReference". A reference to the outcome of the filtering operation.

`frEntry`: Object of class "character" The population in the `filterResult` that corresponds to the current view. See details for further explanation.

`ID`: Object of class "character". A unique identifier for the view.

`name`: Object of class "character". A more human-readable name

`action`: Object of class "fcActionReference". A reference to the `actionItem` that generated the view.

`env`: Object of class "environment". The evaluation environment in the `workFlow`.

`data`: Object of class "fcDataReference" A reference to the data that is associated to the view. Subsets of the data are only generated when a further action is invoked on a particular `gateView`. Summary statistics about the view can be acquired through the usual process of summarizing `filterResults`.

## Extends

Class "`view`", directly.

## Methods

**Rm** signature(symbol = "gateView", envir = "workFlow", subSymbol = "character"): Remove a `gateView` from a `workFlow`. This method is recursive and will also remove all dependent views and `actionItems`.

**summary** signature(x = "formula", data = "gateView"): Summarize the gating operation.

**xyplot** signature(x = "formula", data = "gateView"): Plot the data of the `gateView` along with the gate.

## Author(s)

Florian Hahne

## See Also

`workFlow`, `view`, `transformView`, `compensateView`, `actionItem`

## Examples

```
showClass("view")
```

---

`getIndexSort`*Extract Index Sorted Data from an FCS File*

---

### Description

Retrieve a data frame of index sorted data and sort indices from an FCS file.

### Details

The input FCS file should already be compensated. Index sorting permits association of cell-level fluorescence intensities with downstream data collection on the sorted cells. Cells are sorted into a plate with X, Y coordinates, and those coordinates are stored in the FCS file.

This function will extract the data frame of flow data and the X, Y coordinates for the cell-level data, which can be written to a text file, or concatenated with sample-level information and analyzed in R. The coordinates are names 'XLoc', 'YLoc', and a 'name' column is also prepended with the FCS file name.

### Value

Matrix of fluorescence intensities and sort indices for plate location. When no index sorting data is available, invisibly returns 0. Test for 0 to check success.

### Methods

**x = "flowFrame"** Return a matrix of fluorescence intensities and indices into the sorting plate for each cell.

### Author(s)

G. Finak

### Examples

```
samp <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
# This will return a message that no index sorting data is available
getIndexSort(samp)
```

---

GvHD

*Extract of a Graft versus Host Disease monitoring experiment  
(Rizzieri et al., 2007)*

---

### Description

A flow cytometry high throughput screening was used to identify biomarkers that would predict the development of GvHD. The GvHD dataset is an extract of a collection of weekly peripheral blood samples obtained from patients following allogenic blood and marrow transplant. Samples were taken at various time points before and after graft.

### Usage

```
data(GvHD)
```

### Format

The format is an object of class `flowSet` composed of 35 `flowFrames`. Each `flowFrame` corresponds to one sample at one time point. The phenodata lists:

**Patient** The patient Id code

**Visit** The number of visits to the hospital

**Days** The number of days since the graft. Negative values correspond to days before the graft.

**Grade** Grade of the cancer

### Details

This GvHD dataset represents the measurements of one biomarker (leukocyte) for 5 patients over 7 visits (7 time points). The blood samples were labeled with four different fluorescent probes to identify the biomarker and the fluorescent intensity was determined for at least ten thousand cells per sample.

### Source

Complete dataset available at [http://www.ficcs.org/software.html#Data\\_Files](http://www.ficcs.org/software.html#Data_Files), the Flow Informatics and Computational Cytometry Society website (FICCS)

### References

Rizzieri DA et al. J Clin Oncol. 2007 Jan 16; [Epub ahead of print] PMID: 17228020



---

hyperlog-class	Class "hyperlog"
----------------	------------------

---

### Description

Hyperlog transformation of a parameter is defined by the function

$$f(\text{parameter}, a, b) = \text{rootEH}(y, a, b) - \text{parameter}$$

where EH is a function defined by

$$EH(y, a, b) = 10^{(\frac{y}{a})} + \frac{b * y}{a} - 1 \quad y \geq 0$$

$$-10^{(\frac{-y}{a})} + \frac{b * y}{a} + 1 \quad y < 0$$

### Objects from the Class

Objects can be created by calls to the constructor `hyperlog(parameter, a, b, transformationId)`

### Slots

`.Data`: Object of class "function" ~~

`a`: Object of class "numeric" - numeric constant greater than zero

`b`: Object of class "numeric" numeric constant greater than zero

`parameters`: Object of class "transformation" -flow parameter to be transformed

`transformationId`: Object of class "character" - unique ID to reference the transformation

### Extends

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

### Methods

No methods defined with class "hyperlog" in the signature.

### Note

The transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

**See Also**

EHtrans

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))
hlog1<-hyperlog("FSC-H",a=1,b=1,transformationId="hlog1")
transOut<-eval(hlog1)(exprs(dat))
```

---

hyperlogtGml2-class    *Class hyperlogtGml2*

---

**Description**

Hyperlog transformation parameterized according to Gating-ML 2.0 is defined by the following function:

$$\text{hyperlog}(x, T, W, M, A) = \text{root}(EH(y, T, W, M, A) - x)$$

and  $EH$  is defined as:

$$EH(y, T, W, M, A) = ae^{by} + cy - f$$

where

- $x$  is the value that is being transformed (an FCS dimension value). Typically,  $x$  is less than or equal to  $T$ , although the transformation function is also defined for  $x$  greater than  $T$ .
- $y$  is the result of the transformation.
- $T$  is greater than zero and represents the top of scale value.
- $M$  is greater than zero and represents the number of decades that the true logarithmic scale approached at the high end of the Hyperlog scale would cover in the plot range.
- $W$  is positive and not greater than half of  $M$  and represents the number of such decades in the approximately linear region.
- $A$  is the number of additional decades of negative data values to be included.  $A$  shall be greater than or equal to  $-W$ , and less than or equal to  $M - 2W$
- $\text{root}$  is a standard root finding algorithm (e.g., Newton's method) that finds  $y$  such as  $B(y, T, W, M, A) = x$ .

and  $a$ ,  $b$ ,  $c$  and  $f$  are defined by means of  $T$ ,  $W$ ,  $M$ ,  $A$ ,  $w$ ,  $x_0$ ,  $x_1$ ,  $x_2$ ,  $e_0$ ,  $ca$  and  $fa$  as:

$$\begin{aligned}w &= W/(M + A) \\x_2 &= A/(M + A) \\x_1 &= x_2 + w \\x_0 &= x_2 + 2 * w \\b &= (M + A) * \ln(10) \\e_0 &= e^{b*x_0} \\ca &= e_0/w \\fa &= e^{b*x_1} + ca * x_1 \\a &= T/(e^b + ca - fa) \\c &= ca * a \\f &= fa * a\end{aligned}$$

### Objects from the Class

Objects can be created by calls to the constructor

`hyperlogtGml2(parameter, T, M, W, A, transformationId)`

### Slots

**.Data:** Object of class `function` ~~

**T:** Object of class `numeric` -positive constant (top of scale value)

**M:** Object of class `numeric` -positive constant (desired number of decades)

**W:** Object of class `numeric` -positive constant that is not greater than half of M (the number of such decades in the approximately linear region)

**A:** Object of class `numeric` -a constant that is greater than or equal to -W, and also less than or equal to M-2W. (A represents the number of additional decades of negative data values to be included.)

**parameters:** Object of class `"transformation"` -flow parameter to be transformed

**transformationId:** Object of class `"character"` -unique ID to reference the transformation

### Extends

Class `singleParameterTransform`, directly. Class `transform`, by class `singleParameterTransform`, distance 2. Class `transformation`, by class `singleParameterTransform`, distance 3. Class `characterOrTransformation`, by class `singleParameterTransform`, distance 4.

### Methods

No methods defined with class `hyperlogtGml2` in the signature.

**Note**

That `hyperlogtGm12` transformation brings "reasonable" data values to the scale of  $[0, 1]$ . The transformation is somewhat similar to `logicletGm12`. (See Gating-ML 2.0 for detailed comparison)

The hyperlog transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Spidlen, J., Moore, W.

**References**

Gating-ML 2.0: International Society for Advancement of Cytometry (ISAC) standard for representing gating descriptions in flow cytometry. <http://flowcyt.sourceforge.net/gating/20130122.pdf>

**See Also**

[hyperlog](#), [logicletTransform](#), [transform-class](#), [transform](#)

**Examples**

```
myDataIn <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
myHyperLg <- hyperlogtGm12(parameters = "FSC-H", T = 1023, M = 4.5,
  W = 0.5, A = 0, transformationId="myHyperLg")
transOut <- eval(myHyperLg)(exprs(myDataIn))
```

---

identifier

*Retrieve the GUID of flowCore objects*

---

**Description**

Retrieve the GUID (globally unique identifier) of a `flowFrame` that was generated by the cytometer or the identifier of a `filter` or `filterResult` given by the analyst.

**Usage**

```
identifier(object)
```

**Arguments**

`object` Object of class `flowFrame`, `filter` or `filterResult`.

## Details

GUID or Globally Unique Identifier is a pseudo-random number used in software applications. While each generated GUID is not guaranteed to be unique, the total number of unique keys ( $2^{128}$ ) is so large that the probability of the same number being generated twice is very small.

Note that if no GUID has been recorded along with the FCS file, the name of the file is returned.

## Value

Character vector representing the GUID or the name of the file.

## Methods

**object = "filter"** Return identifier of a `filter` object.

**object = "filterReference"** Return identifier of a `filterReference` object.

**object = "filterResult"** Return identifier of a `filterResult` object.

**object = "transform"** Return identifier of a `transform` object.

**object = "flowFrame"** Return GUID from the description slot of a `flowFrame` object or, alternatively, the name of the input FCS file in case none can be found. For `flowFrame` objects there also exists a replacement method.

## Author(s)

N. LeMeur

## Examples

```
samp <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
identifier(samp)
```

---

inverseLogicleTransform

*Computes the inverse of the transform defined by the 'logicleTransform' function*

---

## Description

`inverseLogicleTransform` can be used to compute the inverse of the Logicle transformation. The parameters `w`, `t`, `m`, `a` for calculating the inverse are obtained from the `'trans'` input passed to the `'inverseLogicleTransform'` function. (The `inverseLogicleTransform` method makes use of the C++ implementation of the inverse logicle transform contributed by Wayne Moore et al.)

## Usage

```
inverseLogicleTransform(transformationId, trans)
```

**Arguments**

transformationId	A name to assigned to the inverse transformation. Used by the transform routines.
trans	An object of class 'transform' created using the 'logicleTransform' function. The parameters w, t, m, a for calculating the inverse are obtained from the 'trans' input passed to the 'inverseLogicleTransform' function.

**Author(s)**

Wayne Moore, N. Gopalakrishnan

**References**

Parks D.R., Roederer M., Moore W.A.(2006) A new "logicle" display method avoids deceptive effects of logarithmic scaling for low signals and compensated data. *CytometryA*, 96(6):541-51.

**See Also**

[logicleTransform](#)

**Examples**

```
data(GvHD)
samp <- GvHD[[1]]
logicle <- logicleTransform(t = 10000, w = 0.5, m = 4.5 , a =0 ,"logicle")
## transform FL1-H parameter using logicle transformation
after <- transform(samp, FL1-H = logicle(FL1-H))

## Inverse transform the logicle transformed data to retrieve the original data
invLogicle <- inverseLogicleTransform(trans = logicle)
before <- transform (after, FL1-H= invLogicle(FL1-H))
```

---

invsplitscale-class    *Class "invsplitscale"*

---

**Description**

The inverse split scale transformation is defined by the function

$$f(\text{parameter}, r, \text{maxValue}, \text{transitionChannel}) = \frac{(\text{parameter} - b)}{a} \quad \text{parameter} \leq t * a + b$$

$$\frac{10^{\text{parameter} * \frac{d}{r}}}{c} \quad \text{parameter} > t * a + b$$

where,

$$b = \frac{\text{transitionChannel}}{2}$$

$$d = \frac{2 * \log_{10}(e) * r}{\text{transitionChannel}} + \log_{10}(\text{maxValue})$$

$$t = 10^{\log_{10} t}$$

$$a = \frac{\text{transitionChannel}}{2 * t}$$

$$\log_{10} ct = \frac{(a * t + b) * d}{r}$$

$$c = 10^{\log_{10} ct}$$

### Objects from the Class

Objects can be created by calls to the constructor `invsplitscale(parameters, r, maxValue, transitionChannel, transformationId)`

### Slots

`.Data`: Object of class "function" ~~

`r`: Object of class "numeric" -a positive value indicating the range of the logarithmic part of the display

`maxValue`: Object of class "numeric" -a positive value indicating the maximum value the transformation is applied to

`transitionChannel`: Object of class "numeric" -non negative value that indicates where to split the linear vs. logarithmic transformation

`parameters`: Object of class "transformation" - flow parameter to be transformed

`transformationId`: Object of class "character" -unique ID to reference the transformation

### Extends

Class "`singleParameterTransform`", directly. Class "`transform`", by class "singleParameterTransform", distance 2. Class "`transformation`", by class "singleParameterTransform", distance 3. Class "`characterOrTransformation`", by class "singleParameterTransform", distance 4.

### Methods

No methods defined with class "invsplitscale" in the signature.

### Note

The transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

### Author(s)

Gopalakrishnan N,F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry

**See Also**

splitscale

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
sp1<-invsplitscale("FSC-H", r=512, maxValue=2000, transitionChannel=512)
transOut<-eval(sp1)(exprs(dat))
```

---

keyword-methods

*Methods to retrieve keywords of a flowFrame*

---

**Description**

Accessor and replacement methods for items in the description slot (usually read in from a FCS file header). It lists the keywords and its values for a flowFrame specified by a character vector. Additional methods for function and lists exists for more programmatic access to the keywords.

**Usage**

```
keyword(object, keyword)
```

**Arguments**

object	Object of class <code>flowFrame</code> .
keyword	Character vector or list of potential keywords or function. If missing all keywords are returned.

**Details**

The keyword methods allow access to the keywords stored in the FCS files, either for a flowFrame or for a list of frames in a flowSet. The most simple use case is to provide a character vector or a list of character strings of keyword names. A more sophisticated version is to provide a function which has to take one mandatory argument, the value of this is the flowFrame. This can be used to query arbitrary information from the flowFrames description slot or even the raw data. The function has to return a single character string. The list methods allow to combine functional and direct keyword access. The replacement method takes a named character vector or a named list as input. R's usual recycling rules apply when replacing keywords for a whole flowSet



## Methods

**object = "flowFrame", keyword = "character"** Return values for all keywords from the description slot in object that match the character vector keyword.

**object = "flowFrame", keyword = "function"** Apply the function in keyword on the `flowFrame` object. The function needs to be able to cope with a single argument and it needs to return a single character string. A typical use case is for instance to paste together values from several different keywords or to compute some statistic on the `flowFrame` and combine it with one or several other keywords.

**object = "flowFrame", keyword = "list"** Combine characters and functions in a list to select keyword values.

**object = "flowFrame", keyword = "missing"** This is essentially an alias for `description` and returns all keyword-value pairs.

**object = "flowSet", keyword = "list"** This is a wrapper around `fsApply(object, keyword, keyword)` which essentially iterates over the frames in the `flowSet`.

**object = "flowSet", keyword = "ANY"** This first coerces the keyword (mostly a character vector) to a list and then calls the next applicable method.

## Author(s)

N LeMeur, F Hahne, B Ellis

## See Also

[description](#)

## Examples

```
samp <- read.FCS(system.file("extdata","0877408774.B08", package="flowCore"))
keyword(samp)

keyword(samp, "FCSversion")

keyword(samp, function(x,...) paste(keyword(x, "SAMPLE ID"), keyword(x,
"GUID"), sep="_"))

keyword(samp) <- list(foo="bar")

data(GvHD)
keyword(GvHD, list("GUID", cellnumber=function(x) nrow(x)))

keyword(GvHD) <- list(sample=sampleNames(GvHD))
```

---

kmeansFilter-class      *Class "kmeansFilter"*

---

### Description

A filter that performs one-dimensional k-means (Lloyd-Max) clustering on a single flow parameter.

### Usage

```
kmeansFilter(..., filterId="defaultKmeansFilter")
```

### Arguments

...      kmeansFilter are defined by a single flow parameter and an associated list of k population names. They can be given as a character vector via a named argument, or as a list with a single named argument. In both cases the name will be used as the flow parameter and the content of the list or of the argument will be used as population names, after coercing to character. For example

```
kmeansFilter(FSC=c("a", "b", "c"))
```

or

```
kmeansFilter(list(SSC=1:3))
```

If the parameter is not fully realized, but instead is the result of a [transformation](#) operation, two arguments need to be passed to the constructor: the first one being the [transform](#) object and the second being a vector of population names which can be coerced to a character. For example

```
kmeansFilter(tf, c("D", "E"))
```

filterId      An optional parameter that sets the filterId of the object. The filter can later be identified by this name.

### Details

The one-dimensional k-means filter is a multiple population filter capable of operating on a single flow parameter. It takes a parameter argument associated with two or more populations and results in the generation of an object of class [multipleFilterResult](#). Populations are considered to be ordered such that the population with the smallest mean intensity will be the first population in the list and the population with the highest mean intensity will be the last population listed.

### Value

Returns a kmeansFilter object for use in filtering [flowFrames](#) or other flow cytometry objects.

## Extends

Class [parameterFilter](#), directly.

Class [concreteFilter](#), by class [parameterFilter](#), distance 2.

Class [filter](#), by class [parameterFilter](#), distance 3.

## Slots

**populations:** Object of class character. The names of the k populations (or clusters) that will be created by the [kmeansFilter](#). These names will later be used for the respective subpopulations in [split](#) operations and for the summary of the [filterResult](#).

**parameters:** Object of class [parameters](#), defining a single parameter for which the data in the [flowFrame](#) is to be clustered. This may also be a [transformation](#) object.

**filterId:** Object of class character, an identifier or name to reference the [kmeansFilter](#) object later on.

## Objects from the Class

Like all other [filter](#) objects in [flowCore](#), [kmeansFilter](#) objects should be instantiated through their constructor [kmeansFilter\(\)](#). See the Usage section for details.

## Methods

**%in%** signature(x = "flowFrame", table = "kmeansFilter"): The workhorse used to evaluate the filter on data.

*Usage:*

This is usually not called directly by the user, but internally by the [filter](#) methods.

**show** signature(object = "kmeansFilter"): Print information about the filter.

*Usage:*

The method is called automatically whenever the object is printed on the screen.

## Note

See the documentation in the [flowViz](#) package for plotting of [kmeansFilters](#).

## Author(s)

F. Hahne, B. Ellis, N. LeMeur

## See Also

[flowFrame](#), [flowSet](#), [filter](#) for evaluation of [kmeansFilters](#) and [split](#) for splitting of flow cytometry data sets based on the result of the filtering operation.

**Examples**

```

## Loading example data
dat <- read.FCS(system.file("extdata","0877408774.B08",
package="flowCore"))

## Create the filter
kf <- kmeansFilter("FSC-H"=c("Pop1","Pop2","Pop3"), filterId="myKmFilter")

## Filtering using kmeansFilters
fres <- filter(dat, kf)
fres
summary(fres)
names(fres)

## The result of quadGate filtering are multiple sub-populations
## and we can split our data set accordingly
split(dat, fres)

## We can limit the splitting to one or several sub-populations
split(dat, fres, population="Pop1")
split(dat, fres, population=list(keep=c("Pop1","Pop2")))

```

---

linearTransform	<i>Create the definition of a linear transformation function to be applied on a data set</i>
-----------------	--

---

**Description**

Create the definition of the linear Transformation that will be applied on some parameter via the transform method. The definition of this function is currently  $x \leftarrow a*x+b$

**Usage**

```
linearTransform(transformationId="defaultLinearTransform", a = 1, b = 0)
```

**Arguments**

transformationId	character string to identify the transformation
a	double that corresponds to the multiplicative factor in the equation
b	double that corresponds to the additive factor in the equation

**Value**

Returns an object of class transform.

**Author(s)**

N. LeMeur

**See Also**[transform-class](#), [transform](#)**Examples**

```
samp <- read.FCS(system.file("extdata",
  "0877408774.B08", package="flowCore"))
linearTrans <- linearTransform(transformationId="Linear-transformation", a=2, b=0)
dataTransform <- transform(samp,FSC-H=linearTrans(FSC-H))
```

---

 lintGml2-class

 Class *lintGml2*


---

**Description**

Linear transformation as parameterized in Gating-ML 2.0 is defined by the following function:

$$f(\text{parameter}, T, A) = (\text{parameter} + A) / (T + A)$$

This transformation provides a linear display that maps scale values from the  $[-A, T]$  interval to the  $[0, 1]$  interval. However, it is defined for all  $x \in R$  including outside of the  $[-A, T]$  interval.

**Objects from the Class**

Objects can be created by calls to the constructor

```
lintGml2(parameter, T, A, transformationId)
```

**Slots**

**.Data:** Object of class `function` ~~

**T:** Object of class `numeric` -positive constant (top of scale value)

**A:** Object of class `numeric` -non-negative constant that is less than or equal to T; it is determining the bottom end of the transformation

**parameters:** Object of class `"transformation"` -flow parameter to be transformed

**transformationId:** Object of class `"character"` -unique ID to reference the transformation

**Extends**

Class [singleParameterTransform](#), directly. Class [transform](#), by class `singleParameterTransform`, distance 2. Class [transformation](#), by class `singleParameterTransform`, distance 3. Class [characterOrTransformation](#), by class `singleParameterTransform`, distance 4.

## Methods

No methods defined with class `lintGml2` in the signature.

## Note

The linear transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

## Author(s)

Spidlen, J.

## References

Gating-ML 2.0: International Society for Advancement of Cytometry (ISAC) standard for representing gating descriptions in flow cytometry. <http://flowcyt.sourceforge.net/gating/20130122.pdf>

## See Also

[linearTransform](#), [transform-class](#), [transform](#)

## Examples

```
myDataIn <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
myLinTr1 <- lintGml2(parameters = "FSC-H", T = 1000, A = 0,
  transformationId="myLinTr1")
transOut <- eval(myLinTr1)(exprs(myDataIn))
```

---

lnTransform

*Create the definition of a ln transformation function (natural logarithm) to be applied on a data set*

---

## Description

Create the definition of the ln Transformation that will be applied on some parameter via the `transform` method. The definition of this function is currently  $x \leftarrow \log(x) * (r/d)$ . The transformation would normally be used to convert to a linear valued parameter to the natural logarithm scale. Typically  $r$  and  $d$  are both equal to 1.0. Both must be positive.

## Usage

```
lnTransform(transformationId="defaultLnTransform", r=1, d=1)
```

**Arguments**

transformationId  
character string to identify the transformation

r  
positive double that corresponds to a scale factor.

d  
positive double that corresponds to a scale factor

**Value**

Returns an object of class transform.

**Author(s)**

B. Ellis and N. LeMeur

**See Also**

[transform-class](#), [transform](#)

**Examples**

```
data(GvHD)
lnTrans <- lnTransform(transformationId="ln-transformation", r=1, d=1)
ln1 <- transform(GvHD, FSC-H=lnTrans(FSC-H))

opar = par(mfcol=c(2, 1))
plot(density(exprs(GvHD[[1]])[ ,1]), main="Original")
plot(density(exprs(ln1[[1]])[ ,1]), main="Ln Transform")
```

---

logarithm-class	Class "logarithm"
-----------------	-------------------

---

**Description**

Logarithmic transformation of an argument is a transformation defined by the function

$$f(\text{parameter}, a, b) = \ln(a * \text{parameter}) * b \quad a * \text{parameter} > 0$$

$$0 \quad a * \text{parameter} \leq 0$$

**Objects from the Class**

Objects can be created by calls to the constructor `logarithm(parameters, a, b, transformationId)`

**Slots**

.Data: Object of class "function" ~~

a: Object of class "numeric" -non zero multiplicative constant

b: Object of class "numeric" -non zero multiplicative constant

parameters: Object of class "transformation"-flow parameters to be transformed

transformationId: Object of class "character"-unique ID to reference the transformation

**Extends**

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

**Methods**

No methods defined with class "logarithm" in the signature.

**Note**

The logarithm transformation object can be evaluated using the eval method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

**See Also**

exponential,quadratic

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
lg1<-logarithm(parameters="FSC-H", a=2, b=1, transformationId="lg1")
transOut<-eval(lg1)(exprs(dat))
```



---

logicalFilterResult-class  
*Class "logicalFilterResult"*

---

**Description**

Container to store the result of applying a filter on a flowFrame object

**Slots**

subSet: Object of class "numeric"

frameId: Object of class "character" referencing the flowFrame object filtered. Used for sanity checking.

filterDetails: Object of class "list" describing the filter applied

filterId: Object of class "character" referencing the filter applied

**Extends**

Class "[filterResult](#)", directly. Class "[filter](#)", by class "filterResult", distance 2.

**Author(s)**

B. Ellis

**See Also**

[filter](#)

**Examples**

```
showClass("logicalFilterResult")
```

---

logicletGml2-class      *Class logicletGml2*

---

**Description**

Logicle transformation as published by Moore and Parks is defined by the following function:

$$\text{logiclet}(x, T, W, M, A) = \text{root}(B(y, T, W, M, A) - x)$$

and  $B$  is a modified biexponential function:

$$B(y, T, W, M, A) = ae^{by} - ce^{-dy} - f$$

where

- $x$  is the value that is being transformed (an FCS dimension value). Typically,  $x$  is less than or equal to  $T$ , although the transformation function is also defined for  $x$  greater than  $T$ .
- $y$  is the result of the transformation.
- $T$  is greater than zero and represents the top of scale value.
- $M$  is greater than zero and represents the number of decades that the true logarithmic scale approached at the high end of the Logicle scale would cover in the plot range.
- $W$  is non-negative and not greater than half of  $M$  and represents the number of such decades in the approximately linear region. The choice of  $W = M/2$  specifies a scale that is essentially linear over the whole range except for a small region of large data values. For situations in which values of  $W$  approaching  $M/2$  might be chosen, ordinary linear display scales will usually be more appropriate. The choice of  $W = 0$  gives essentially the hyperbolic sine function.
- $A$  is the number of additional decades of negative data values to be included.  $A$  shall be greater than or equal to  $-W$ , and less than or equal to  $M - 2W$
- root is a standard root finding algorithm (e.g., Newton's method) that finds  $y$  such as  $B(y, T, W, M, A) = x$ .

and  $a, b, c, d$  and  $f$  are defined by means of  $T, W, M, A, w, x_0, x_1, x_2, ca$  and  $fa$  as:

$$w = W/(M + A)$$

$$x_2 = A/(M + A)$$

$$x_1 = x_2 + w$$

$$x_0 = x_2 + 2 * w$$

$$b = (M + A) * \ln(10)$$

and  $d$  is a constant so that

$$2 * (\ln(d) - \ln(b)) + w * (d + b) = 0$$

given  $b$  and  $w$ , and

$$ca = e^{x_0 * (b+d)}$$

$$fa = e^{b * x_1} - (ca / (e^{d * x_1}))$$

$$a = T / (e^b - fa - (ca / e^d))$$

$$c = ca * a$$

$$f = fa * a$$

The Logicle scale is the inverse of a modified biexponential function. It provides a Logicle display that maps scale values onto the  $[0, 1]$  interval such that the data value  $T$  is mapped to 1, large data values are mapped to locations similar to an  $(M + A)$ -decade logarithmic scale, and  $A$  decades of negative data are brought on scale. For implementation purposes, it is recommended to follow guidance in Moore and Parks publication.

### Objects from the Class

Objects can be created by calls to the constructor

```
logicletGml2(parameter, T, M, W, A, transformationId)
```

**Slots**

**.Data:** Object of class function ~-

**T:** Object of class numeric -positive constant (top of scale value)

**M:** Object of class numeric -positive constant (desired number of decades)

**W:** Object of class numeric -non-negative constant that is not greater than half of M (the number of such decades in the approximately linear region)

**A:** Object of class numeric -a constant that is greater than or equal to -W, and also less than or equal to M-2W. (A represents the number of additional decades of negative data values to be included.)

**parameters:** Object of class "transformation" -flow parameter to be transformed

**transformationId:** Object of class "character" -unique ID to reference the transformation

**Extends**

Class `singleParameterTransform`, directly. Class `transform`, by class `singleParameterTransform`, distance 2. Class `transformation`, by class `singleParameterTransform`, distance 3. Class `characterOrTransformation`, by class `singleParameterTransform`, distance 4.

**Methods**

No methods defined with class `logicletGml2` in the signature.

**Note**

Please note that `logicletGml2` and `logicletTransform` are similar transformations; however, the Gating-ML 2.0 compliant `logicletGml2` brings "reasonable" data values to the scale of  $[0, 1]$  while the `logicletTransform` scales these values to  $[0, M]$ .

The `logiclet` transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Spidlen, J., Moore, W.

**References**

Gating-ML 2.0: International Society for Advancement of Cytometry (ISAC) standard for representing gating descriptions in flow cytometry. <http://flowcyt.sourceforge.net/gating/20130122.pdf>

Moore, WA and Parks, DR. Update for the `logiclet` data scale including operational code implementations. *Cytometry A.*, 2012;81A(4):273-277.

Parks, DR and Roederer, M and Moore, WA. A new "Logiclet" display method avoids deceptive effects of logarithmic scaling for low signals and compensated data. *Cytometry A.*, 2006;69(6):541-551.

**See Also**

[logicleTransform](#), [transform-class](#), [transform](#)

**Examples**

```
myDataIn <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
myLogicle <- logicletGml2(parameters = "FSC-H", T = 1023, M = 4.5,
  W = 0.5, A = 0, transformationId="myLogicle")
transOut <- eval(myLogicle)(exprs(myDataIn))
```

---

<code>logicleTransform</code>	<i>Computes a transform using the 'logicle_transform' function</i>
-------------------------------	--

---

**Description**

Logicle transformation creates a subset of [biexponentialTransform](#) hyperbolic sine transformation functions that provides several advantages over linear/log transformations for display of flow cytometry data. (The `logicleTransform` method makes use of the C++ implementation of the logicle transform contributed by Wayne Moore et al.)

**Usage**

```
logicleTransform(transformationId="defaultLogicleTransform", w = 0.5, t = 262144,
  m = 4.5, a = 0)
estimateLogicle(x, channels,...)
```

**Arguments**

<code>transformationId</code>	A name to assign to the transformation. Used by the transform/filter routines.
<code>w</code>	<code>w</code> is the linearization width in asymptotic decades. <code>w</code> should be $> 0$ and determines the slope of transformation at zero. <code>w</code> can be estimated using the equation $w=(m-\log_{10}(t/abs(r)))/2$ , where <code>r</code> is the most negative value to be included in the display
<code>t</code>	Top of the scale data value, e.g, 10000 for common 4 decade data or 262144 for a 18 bit data range. <code>t</code> should be greater than zero
<code>m</code>	<code>m</code> is the full width of the transformed display in asymptotic decades. <code>m</code> should be greater than zero
<code>a</code>	Additional negative range to be included in the display in asymptotic decades. Positive values of the argument brings additional negative input values into the transformed display viewing area. Default value is zero corresponding to a Standard logicle function.
<code>x</code>	Input flow frame for which the logicle transformations are to be estimated.
<code>channels</code>	Flourescence channels for which the logicle transformation is to be estimated.
<code>...</code>	other arguments: <code>q</code> : a numeric type specifying quantile value, default is 0.05

**Author(s)**

Wayne Moore, N Gopalakrishnan

**References**

Parks D.R., Roederer M., Moore W.A.(2006) A new "logicle" display method avoids deceptive effects of logarithmic scaling for low signals and compensated data. *CytometryA*, 96(6):541-51.

**See Also**

[inverseLogicleTransform](#), [estimateLogicle](#)

**Examples**

```
data(GvHD)
samp <- GvHD[[1]]
## User defined logicle function
lgcl <- logicleTransform( w = 0.5, t= 10000, m =4.5)
after <- transform(samp, FL1-H = lgcl(FL1-H), FL2-H = lgcl(FL2-H))
invLgcl <- inverseLogicleTransform(trans = lgcl)
before <- transform (after, FL1-H= invLgcl(FL1-H), FL2-H = invLgcl(FL2-H))

## Automatically estimate the logicle transformation based on the data
lgcl <- estimateLogicle(samp, channels = c("FL1-H", "FL2-H", "FL3-H", "FL2-A", "FL4-H"))
## transform parameters using the estimated logicle transformation
after <- transform(samp, lgcl)
```

---

logtGml2-class

*Class logtGml2*


---

**Description**

Log transformation as parameterized in Gating-ML 2.0 is defined by the following function:

$$f(\text{parameter}, T, M) = (1/M) * \log_{10}(x/T) + 1$$

This transformation provides a logarithmic display that maps scale values from the  $(0, T]$  interval to the  $(-\text{Inf}, 1]$  interval such that the data value T is mapped to 1 and M decades of data are mapped into the interval. Also, the limit for x going to 0 is -Inf.

**Objects from the Class**

Objects can be created by calls to the constructor

```
logtGml2(parameter, T, M, transformationId)
```

**Slots**

.Data: Object of class function ~~  
T: Object of class numeric -positive constant (top of scale value)  
M: Object of class numeric -positive constant (number of decades)  
parameters: Object of class "transformation" -flow parameter to be transformed  
transformationId: Object of class "character" -unique ID to reference the transformation

**Extends**

Class `singleParameterTransform`, directly. Class `transform`, by class `singleParameterTransform`, distance 2. Class `transformation`, by class `singleParameterTransform`, distance 3. Class `characterOrTransformation`, by class `singleParameterTransform`, distance 4.

**Methods**

No methods defined with class `logtGml2` in the signature.

**Note**

The log transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Spidlen, J.

**References**

Gating-ML 2.0: International Society for Advancement of Cytometry (ISAC) standard for representing gating descriptions in flow cytometry. <http://flowcyt.sourceforge.net/gating/20130122.pdf>

**See Also**

[logTransform](#), [transform-class](#), [transform](#)

**Examples**

```
myDataIn <- read.FCS(system.file("extdata", "0877408774.B08",  
  package="flowCore"))  
myLogTr1 <- logtGml2(parameters = "FSC-H", T = 1023, M = 4.5,  
  transformationId="myLogTr1")  
transOut <- eval(myLogTr1)(exprs(myDataIn))
```

---

logTransform	<i>Create the definition of a log transformation function (base specified by user) to be applied on a data set</i>
--------------	--

---

### Description

Create the definition of the log Transformation that will be applied on some parameter via the transform method. The definition of this function is currently  $x \leftarrow \log(x, \text{logbase})^{*(r/d)}$ . The transformation would normally be used to convert to a linear valued parameter to the natural logarithm scale. Typically r and d are both equal to 1.0. Both must be positive. logbase = 10 corresponds to base 10 logarithm.

### Usage

```
logTransform(transformationId="defaultLogTransform", logbase=10, r=1, d=1)
```

### Arguments

transformationId	character string to identify the transformation
logbase	positive double that corresponds to the base of the logarithm.
r	positive double that corresponds to a scale factor.
d	positive double that corresponds to a scale factor

### Value

Returns an object of class transform.

### Author(s)

B. Ellis, N. LeMeur

### See Also

[transform-class](#), [transform](#)

### Examples

```
samp <- read.FCS(system.file("extdata",  
  "0877408774.B08", package="flowCore"))  
logTrans <- logTransform(transformationId="log10-transformation", logbase=10, r=1, d=1)  
dataTransform <- transform(samp, FSC-H=logTrans(FSC-H))
```

---

manyFilterResult-class

*Class "manyFilterResult"*

---

### Description

The result of a several related, but possibly overlapping filter results. The usual creator of this object will usually be a [filter](#) operation of [filterSet](#) object on a [flowFrame](#) object.

### Slots

**subSet:** Object of class "matrix"

**frameId:** Object of class "character" referencing the flowFrame object filtered. Used for sanity checking.

**filterDetails:** Object of class "list" describing the filter applied

**filterId:** Object of class "character" referencing the filter applied

**dependency:** Any dependencies between the filters. Currently not used.

### Extends

Class "[filterResult](#)", directly. Class "[filter](#)", by class "filterResult", distance 2.

### Methods

**[, [[** subsetting. If x is manyFilterResult, then x[[i]] a filterResult object. The semantics is similar to the behavior of the subsetting operators for lists.

**length** number of filterResult objects in the set.

**names** names of the filterResult objects in the set.

**summary** summary filterResult objects in the set.

### Author(s)

B. Ellis

### See Also

[filterResult](#)

### Examples

```
showClass("manyFilterResult")
```



---

multipleFilterResult-class  
Class "multipleFilterResult"

---

### Description

Container to store the result of applying filter on set of flowFrame objects

### Slots

subSet: Object of class "factor"

frameId: Object of class "character" referencing the flowFrame object filtered. Used for sanity checking.

filterDetails: Object of class "list" describing the filter applied

filterId: Object of class "character" referencing the filter applied

### Extends

Class "[filterResult](#)", directly. Class "[filter](#)", by class "filterResult", distance 2.

### Methods

[, [[ subsetting. If x is multipleFilterResult, then x[[i]] a FilterResult object. The semantics is similar to the behavior of the subsetting operators for lists.

**length** number of FilterResult objects in the set.

**names** names of the FilterResult objects in the set.

**summary** summary FilterResult objects in the set.

### Author(s)

B. Ellis

### See Also

[filterResult](#)

### Examples

```
showClass("multipleFilterResult")
```

---

norm2Filter-class      *Class "norm2Filter"*

---

### Description

Class and constructors for a [filter](#) that fits a bivariate normal distribution to a data set of paired values and selects data points according to their standard deviation from the fitted distribution.

### Usage

```
norm2Filter(x, y, method="covMcd", scale.factor=1, n=50000,
  filterId="defaultNorm2Filter")
```

### Arguments

<code>x,y</code>	Characters giving the names of the measurement parameter on which the filter is supposed to work on. <code>y</code> can be missing in which case <code>x</code> is expected to be a character vector of length 2 or a list of characters.
<code>filterId</code>	An optional parameter that sets the <code>filterId</code> slot of this filter. The object can later be identified by this name.
<code>scale.factor, n</code>	Numerics of length 1, used to set the <code>scale.factor</code> and <code>n</code> slots of the object.
<code>method</code>	Character in <code>covMcd</code> or <code>cov.rob</code> , used to set the <code>method</code> slot of the object.

### Details

The filter fits a bivariate normal distribution to the data and selects all events within the Mahalanobis distance multiplied by the `scale.factor` argument. The constructor `norm2Filter` is a convenience function for object instantiation. Evaluating a `curv2Filter` results in an object of class [logicalFilterResult](#). Accordingly, `norm2Filters` can be used to subset and to split flow cytometry data sets.

### Value

Returns a `norm2Filter` object for use in filtering `flowFrames` or other flow cytometry objects.

### Extends

Class "[parameterFilter](#)", directly.  
 Class "[concreteFilter](#)", by class `parameterFilter`, distance 2.  
 Class "[filter](#)", by class `parameterFilter`, distance 3.

**Slots**

method: One of covMcd or cov.rob defining method used for computation of covariance matrix.

scale.factor: Numeric vector giving factor of standard deviations used for data selection (all points within scalefac standard deviations are selected).

n: Object of class "numeric", the number of events used to compute the covariance matrix of the bivariate distribution.

filterId: Object of class "character" referencing the filter.

parameters: Object of class "ANY" describing the parameters used to filter the [flowFrame](#) or [flowSet](#).

**Objects from the Class**

Objects can be created by calls of the form `new("norm2Filter", ...)` or using the constructor `norm2Filter`. The constructor is the recommended way of object instantiation:

**Methods**

**%in%** signature(x = "flowFrame", table = "norm2Filter"): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the [filter](#) methods.

**show** signature(object = "norm2Filter"): Print information about the filter.

**Note**

See the documentation in the [flowViz](#) package for plotting of norm2Filters.

**Author(s)**

F. Hahne

**See Also**

[cov.rob](#), [CovMcd](#), [filter](#) for evaluation of norm2Filters and [split](#) and [Subset](#) for splitting and subsetting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Create directly. Most likely from a command line
norm2Filter("FSC-H", "SSC-H", filterId="myCurv2Filter")

## To facilitate programmatic construction we also have the following
n2f <- norm2Filter(filterId="myNorm2Filter", x=list("FSC-H", "SSC-H"),
scale.factor=2)
n2f <- norm2Filter(filterId="myNorm2Filter", x=c("FSC-H", "SSC-H"),
```

```

scale.factor=2)

## Filtering using norm2Filter
fres <- filter(dat, n2f)
fres
summary(fres)

## The result of norm2 filtering is a logical subset
Subset(dat, fres)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
split(dat, fres)

```

---

```
normalization-class    Class "normalization"
```

---

## Description

Class and methods to normalize a a flowSet using a potentially complex normalization function.

## Usage

```

normalization(parameters, normalizationId="defaultNormalization",
normFunction, arguments=list())

normalize(data, x,...)

```

## Arguments

parameters	Character vector of parameter names.
normalizationId	The identifier for the normalization object.
x	An object of class <a href="#">flowSet</a> .
normFunction	The normalization function
arguments	The list of additional arguments to normFunction
data	The flowSet to normalize.
...	other arguments: see <a href="#">normalize-methods</a> for details.

## Details

Data normalization of a `flowSet` is a rather fuzzy concept and the class mainly exists for method dispatch in the workflow tools. The idea is to have a rather general function that takes a `flowSet` and a list of parameter names as input and applies any kind of normalization to the respective data columns. The output of the function has to be a `flowSet` again. Although we don't formally check for it, the dimensions of the input and of the output set should remain the same. Additional arguments may be passed to the normalization function via the `arguments` list. Internally we evaluate the function using `do.call` and one should check its documentation for details.

Currently, the most prominent example for a normalization function is warping, as provided by the `flowStats` package.

## Value

A normalization object for the constructor.

A `flowSet` for the `normalize` methods.

## Objects from the Class

Objects should be created using the constructor `normalization()`. See the Usage and Arguments sections for details.

## Slots

**parameters:** Object of class "character". The flow parameters that are supposed to be normalized by the normalization function.

**normalizationId:** Object of class "character". An identifier for the object.

**normFunction:** Object of class "function" The normalization function. It has to take two mandatory arguments: `x`, the `flowSet`, and `parameters`, a character of parameter names that are to be normalized by the function. Additional arguments have to be passed in via `arguments`.

**arguments:** Object of class "list" A names list of additional arguments. Can be NULL.

## Methods

**add** signature(`wf` = "workFlow", `action` = "normalization"): The constructor for the workFlow.

**identifier<-** signature(`object` = "normalization", `value` = "character"): Set method for the identifier slot.

**identifier** signature(`object` = "normalization"): Get method for the identifier slot.

**normalize** signature(`data` = "flowSet", `x` = "normalization"): Apply a normalization to a `flowSet`.

**parameters** signature(`object` = "normalization"): The more generic constructor.

## Author(s)

F. Hahne

---

normalizeActionItem-class

*Class "normalizeActionItem"*

---

## Description

Class and method to capture normalization operations in a flow cytometry workflow.

## Usage

```
normalizeActionItem(ID = paste("normActionRef", guid(), sep = "_"),
name = paste("action", identifier(get(normalization)), sep = "_"),
parentView, normalization, workflow)
```

## Arguments

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal guid function.
name	A more human-readable name of the view.
parentView, normalization	References to the parent <a href="#">view</a> and <a href="#">normalization</a> objects, respectively.

## Details

`normalizeActionItems` provide a means to bind normalization operations like warping in a workflow. Each `normalizeActionItem` represents a single [normalization](#).

## Value

A reference to the `normalizeActionItem` that is created inside the [workFlow](#) environment as a side effect of calling the `add` method.

A `normalizeActionItem` object for the constructor.

## Objects from the Class

Objects should be created using the `add` method, which creates a `normalizeActionItem` from a [normalization](#) object and directly assigns it to a [workFlow](#). Alternatively, one can use the `normalizeActionItem` constructor function for more programmatic access.

**Slots**

**normalization:** Object of class "fcNormalizationReference". A reference to the [normalization](#) object that is used for the compensation operation.

**ID:** Object of class "character". A unique identifier for the actionItem.

**name:** Object of class "character". A more human-readable name

**parentView:** Object of class "fcViewReference". A reference to the parent [view](#) the normalizeActionItem is applied on.

**env:** Object of class "environment". The evaluation environment in the [workFlow](#).

**Extends**

Class "[actionItem](#)", directly.

**Methods**

**print** signature(x = "normalizeActionItem"): Print details about the object.

**Rm** signature(symbol = "normalizeActionItem", envir = "workFlow", subSymbol = "character"): Remove a normalizeActionItem from a [workFlow](#). This method is recursive and will also remove all dependent views and [actionItems](#).

**show** signature(object = "normalizeActionItem"): Print details about the object.

**Author(s)**

Florian Hahne

**See Also**

[workFlow](#), [actionItem](#), [gateActionItem](#), [transformActionItem](#), [compensateActionItem](#), [view](#)

**Examples**

```
showClass("view")
```

---

normalizeView-class    *Class "normalizeView"*

---

**Description**

Class and method to capture the result of normalization operations in a flow cytometry workflow.

**Usage**

```
normalizeView(workflow, ID=paste("normViewRef", guid(), sep="_"),
              name="default", action, data)
```

**Arguments**

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal guid function.
name	A more human-readable name of the view.
data, action	References to the data and <a href="#">actionItem</a> objects, respectively.

**Value**

A reference to the `normalizeView` that is created inside the `workFlow` environment as a side effect of calling the `add` method.

A `normalizeView` object for the constructor.

**Objects from the Class**

Objects should be created using the `add` method, which creates a `normalizeView` from a [normalization](#) object and directly assigns it to a `workFlow`. Alternatively, one can use the `normalizeView` constructor function for more programmatic access.

**Slots**

**ID:** Object of class "character". A unique identifier for the view.

**name:** Object of class "character". A more human-readable name

**action:** Object of class "fcActionReference". A reference to the [actionItem](#) that generated the view.

**env:** Object of class "environment". The evaluation environment in the `workFlow`.

**data:** Object of class "fcDataReference" A reference to the data that is associated to the view.

**Extends**

Class "[view](#)", directly.

**Methods**

**Rm** `signature(symbol = "normalizeView", envir = "workFlow", subSymbol = "character"):`  
Remove a `normalizeView` from a `workFlow`. This method is recursive and will also remove all dependent views and [actionItems](#).

**Author(s)**

Florian Hahne

**See Also**

[workFlow](#), [view](#), [gateView](#), [transformView](#), [compensateView](#), [actionItem](#)



**Examples**

```
showClass("view")
```

---

```
parameterFilter-class  Class "parameterFilter"
```

---

**Description**

A concrete filter that acts on a set of parameters.

**Objects from the Class**

parameterFilter objects are never created directly. This class serves as an inheritance point for filters that depends on particular parameters.

**Slots**

parameters: The names of the parameters employed by this filter

filterId: The filter identifier

**Extends**

Class "[concreteFilter](#)", directly. Class "[filter](#)", by class "concreteFilter", distance 2.

**Methods**

No methods defined with class "parameterFilter" in the signature.

**Author(s)**

B. Ellis

---

parameters	<i>Obtain information about parameters for flow cytometry objects.</i>
------------	--

---

**Description**

Many different objects in flowCore are associated with one or more parameters. This includes [filter](#), [flowFrame](#) and [parameterFilter](#) objects that all either describe or use parameters.

**Usage**

```
parameters(object, ...)
```

**Arguments**

`object`            Object of class `filter`, `flowFrame` or `parameterFilter`.  
`...`              Further arguments that get passed on to the methods.

**Value**

When applied to a `flowFrame` object, the result is an `AnnotatedDataFrame` describing the parameters recorded by the cytometer. For other objects it will usually return a vector of names used by the object for its calculations.

**Methods**

**object = "filter"** Returns for all objects that inherit from `filter` a vector of parameters on which a gate is defined.  
**object = "parameterFilter"** see above  
**object = "setOperationFilter"** see above  
**object = "filterReference"** see above  
**object = "flowFrame"** Returns an `AnnotatedDataFrame` containing detailed descriptions about the measurement parameters of the `flowFrame`. For `flowFrame` objects there also exists a replacement method.

**Author(s)**

B. Ellis, N. Le Meur, F. Hahne

**Examples**

```
samp <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
parameters(samp)
print(samp@parameters@data)
```

---

parameters-class            *Class "parameters"*

---

**Description**

A representation of flow parameters that allows for referencing.

**Objects from the Class**

Objects will be created internally whenever necessary and this should not be of any concern to the user.

**Slots**

`.Data`: A list of the individual parameters

**Extends**

Class "[list](#)", from data part. Class "[vector](#)", by class "list", distance 2.

**Methods**

No methods defined with class "parameters" in the signature.

**Author(s)**

Nishant Gopalakrishnan

---

parameterTransform-class

*Class "parameterTransform"*

---

**Description**

Link a transformation to particular flow parameters

**Objects from the Class**

Objects are created by using the %on% operator and are usually not directly instantiated by the user.

**Slots**

**.Data:** Object of class "function", the transformation function.

**parameters:** Object of class "character" The parameters the transformation is applied to.

**transformationId:** Object of class "character". The identifier for the object.

**Extends**

Class "[transform](#)", directly. Class "[function](#)", by class "transform", distance 2.

**Methods**

**%on%** signature(e1 = "filter", e2 = "parameterTransform"): Apply the transformation.

**%on%** signature(e1 = "parameterTransform", e2 = "flowFrame"): see above

**parameters** signature(object = "parameterTransform"): Accessor to the parameters slot

**Author(s)**

Byron Ellis

---

polygonGate-class      *Class "polygonGate"*

---

### Description

Class and constructor for 2-dimensional polygonal [filter](#) objects.

### Usage

```
polygonGate(..., .gate, boundaries, filterId="defaultPolygonGate")
```

### Arguments

<code>filterId</code>	An optional parameter that sets the <code>filterId</code> of this gate.
<code>.gate, boundaries</code>	A definition of the gate. This can be either a list or a named matrix as described below. Note the argument <code>boundaries</code> is deprecated and will go away in the next release.
<code>...</code>	You can also directly describe a gate without wrapping it in a list or matrix, as described below.

### Details

Polygons are specified by the coordinates of their vertices in two dimensions. The constructor is designed to be useful in both direct and programmatic usage. It takes either a list or a named matrix with 2 columns and at least 3 rows containing these coordinates. Alternatively, vertices can be given as named arguments, in which case the function tries to convert the values into a matrix.

### Value

Returns a [polygonGate](#) object for use in filtering [flowFrames](#) or other flow cytometry objects.

### Extends

Class "[parameterFilter](#)", directly.  
 Class "[concreteFilter](#)", by class `parameterFilter`, distance 2.  
 Class "[filter](#)", by class `parameterFilter`, distance 3.

### Slots

`boundaries`: Object of class "`matrix`". The vertices of the polygon in two dimensions. There need to be at least 3 vertices specified for a valid polygon.  
`parameters`: Object of class "`character`", describing the parameter used to filter the `flowFrame`.  
`filterId`: Object of class "`character`", referencing the filter.

## Objects from the Class

Objects can be created by calls of the form `new("polygonGate", ...)` or by using the constructor `polygonGate`. Using the constructor is the recommended way of object instantiation:

## Methods

**%in%** signature(`x = "flowFrame"`, `table = "polygonGate"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the `filter` methods.

**show** signature(`object = "polygonGate"`): Print information about the filter.

## Note

See the documentation in the `flowViz` package for plotting of `polygonGates`.

## Author(s)

F.Hahne, B. Ellis N. Le Meur

## See Also

`flowFrame`, `rectangleGate`, `ellipsoidGate`, `polytopeGate`, `filter` for evaluation of `rectangleGates` and `split` and `Subset` for splitting and subsetting of flow cytometry data sets based on that.

## Examples

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Defining the gate
sqrcut <- matrix(c(300,300,600,600,50,300,300,50), ncol=2, nrow=4)
colnames(sqrcut) <- c("FSC-H", "SSC-H")
pg <- polygonGate(filterId="nonDebris", boundaries= sqrcut)
pg

## Filtering using polygonGates
fres <- filter(dat, pg)
fres
summary(fres)

## The result of polygon filtering is a logical subset
Subset(dat, fres)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
split(dat, fres)
```

---

polytopeGate-class     *Define filter boundaries*

---

### Description

Convenience methods to facilitate the construction of [filter](#) objects

### Usage

```
polytopeGate(..., .gate, b, filterId="defaultPolytopeGate")
```

### Arguments

filterId	An optional parameter that sets the filterId of this gate.
.gate	A definition of the gate. This can be either a list, vector or matrix, described below.
b	Need documentation
...	You can also directly describe a gate without wrapping it in a list or matrix, as described below.

### Details

These functions are designed to be useful in both direct and programmatic usage.

For rectangle gate in  $n$  dimensions, if  $n=1$  the gate correspond to a range gate. If  $n=2$ , the gate is a rectangle gate. To use this function programmatically, you may either construct a list or you may construct a matrix with  $n$  columns and 2 rows. The first row corresponds to the minimal value for each parameter while the second row corresponds to the maximal value for each parameter. The names of the parameters are taken from the column names as in the third example.

Rectangle gate objects can also be multiplied together using the `*` operator, provided that both gate have orthogonal axes.

For polygon gate, the boundaries are specified as vertices in 2 dimensions, for polytope gate objects as vertices in  $n$  dimensions.

For quadrant gates, the boundaries are specified as a named list or vector of length two.

### Value

Returns a [rectangleGate](#) or [polygonGate](#) object for use in filtering [flowFrames](#) or other flow cytometry objects.

### Author(s)

F.Hahne, B. Ellis N. Le Meur

**See Also**

[flowFrame](#), [filter](#)

---

quadGate-class	Class "quadGate"
----------------	------------------

---

**Description**

Class and constructors for quadrant-type [filter](#) objects.

**Usage**

```
quadGate(..., .gate, filterId="defaultQuadGate")
```

**Arguments**

<code>filterId</code>	An optional parameter that sets the <code>filterId</code> of this <a href="#">filter</a> . The object can later be identified by this name.
<code>.gate</code>	A definition of the gate for programmatic access. This can be either a named list or a named numeric vector, as described below.
<code>...</code>	The parameters of <code>quadGates</code> can also be directly described using named function arguments, as described below.

**Details**

`quadGates` are defined by two parameters, which specify a separation of a two-dimensional parameter space into four quadrants. The `quadGate` function is designed to be useful in both direct and programmatic usage:

For the interactive use, these parameters can be given as additional named function arguments, where the names correspond to valid parameter names in a [flowFrame](#) or [flowSet](#). For a more programmatic approach, a named list or numeric vector of the gate boundaries can be passed on to the function as argument `.gate`.

Evaluating a `quadGate` results in four sub-populations, and hence in an object of class [multipleFilterResult](#). Accordingly, `quadGates` can be used to split flow cytometry data sets.

**Value**

Returns a `quadGate` object for use in filtering [flowFrames](#) or other flow cytometry objects.

**Extends**

Class "[parameterFilter](#)", directly.

Class "[concreteFilter](#)", by class `parameterFilter`, distance 2.

Class "[filter](#)", by class `parameterFilter`, distance 3.

**Slots**

**boundary:** Object of class "numeric", length 2. The boundaries of the quadrant regions.  
**parameters:** Object of class "character", describing the parameter used to filter the flowFrame.  
**filterId:** Object of class "character", referencing the gate.

**Objects from the Class**

Objects can be created by calls of the form `new("quadGate", ...)` or using the constructor `quadGate`. The latter is the recommended way of object instantiation:

**Methods**

**%in%** signature(`x = "flowFrame"`, `table = "quadGate"`): The workhorse used to evaluate the gate on data. This is usually not called directly by the user, but internally by calls to the `filter` methods.

**show** signature(`object = "quadGate"`): Print information about the gate.

**Note**

See the documentation in the `flowViz` package for plotting of quadGates.

**Author(s)**

F.Hahne, B. Ellis N. Le Meur

**See Also**

`flowFrame`, `flowSet`, `filter` for evaluation of quadGates and `split` for splitting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

## Create directly. Most likely from a command line
quadGate(filterId="myQuadGate1", "FSC-H"=100, "SSC-H"=400)

## To facilitate programmatic construction we also have the following
quadGate(filterId="myQuadGate2", list("FSC-H"=100, "SSC-H"=400))
## FIXME: Do we want this?
##quadGate(filterId="myQuadGate3", .gate=c("FSC-H"=100, "SSC-H"=400))

## Filtering using quadGates
qg <- quadGate(filterId="quad", "FSC-H"=600, "SSC-H"=400)
fres <- filter(dat, qg)
fres
summary(fres)
```



```

names(fres)

## The result of quadGate filtering are multiple sub-populations
## and we can split our data set accordingly
split(dat, fres)

## We can limit the splitting to one or several sub-populations
split(dat, fres, population="FSC-H-SSC-H-")
split(dat, fres, population=list(keep=c("FSC-H-SSC-H-",
"FSC-H-SSC-H+")))

```

---

quadratic-class	Class "quadratic"
-----------------	-------------------

---

### Description

Quadratic transform class defines a transformation defined by the function

$$f(\text{parameter}, a) = a * \text{parameter}^2$$

### Objects from the Class

Objects can be created by calls to the constructor `quadratic(parameters, a, transformationId)`

### Slots

`.Data`: Object of class "function" ~~

`a`: Object of class "numeric"-non zero multiplicative constant

`parameters`: Object of class "transformation"-flow parameter to be transformed

`transformationId`: Object of class "character"-unique ID to reference the transformation

### Extends

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "[singleParameterTransform](#)", distance 2. Class "[transformation](#)", by class "[singleParameterTransform](#)", distance 3. Class "[characterOrTransformation](#)", by class "[singleParameterTransform](#)", distance 4.

### Methods

No methods defined with class "quadratic" in the signature.

### Note

The quadratic transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a column vector. (See example below)

**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

**See Also**

dg1polynomial, ratio, squareroot

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))
quad1<-quadratic(parameters="FSC-H", a=2, transformationId="quad1")
transOut<-eval(quad1)(exprs(dat))
```

---

quadraticTransform	<i>Create the definition of a quadratic transformation function to be applied on a data set</i>
--------------------	---

---

**Description**

Create the definition of the quadratic Transformation that will be applied on some parameter via the transform method. The definition of this function is currently  $x \leftarrow a*x^2 + b*x + c$

**Usage**

```
quadraticTransform(transformationId="defaultQuadraticTransform", a = 1, b = 1, c = 0)
```

**Arguments**

transformationId	character string to identify the transformation
a	double that corresponds to the quadratic coefficient in the equation
b	double that corresponds to the linear coefficient in the equation
c	double that corresponds to the intercept in the equation

**Value**

Returns an object of class transform.

**Author(s)**

N. Le Meur

**See Also**

[transform-class](#), [transform](#)

**Examples**

```
samp <- read.FCS(system.file("extdata",
  "0877408774.B08", package="flowCore"))
quadTrans <- quadraticTransform(transformationId="Quadratic-transformation", a=1, b=1, c=0)
dataTransform <- transform(samp, FSC-H=quadTrans(FSC-H))
```

---

randomFilterResult-class

*Class "randomFilterResult"*

---

**Description**

Container to store the result of applying a filter on a flowFrame object

**Slots**

subSet: Object of class "numeric"

frameId: Object of class "character" referencing the flowFrame object filtered. Used for sanity checking.

filterDetails: Object of class "list" describing the filter applied

filterId: Object of class "character" referencing the filter applied

**Extends**

Class "[filterResult](#)", directly. Class "[filter](#)", by class "filterResult", distance 2.

**Author(s)**

B. Ellis

**See Also**

[filter](#)

ratio-class

Class "ratio"

**Description**

ratio transform calculates the ratio of two parameters defined by the function

$$f(\text{parameter}_1, \text{parameter}_2) = \frac{\text{parameter}_1}{\text{parameter}_2}$$

**Objects from the Class**

Objects can be created by calls to the constructor `ratio(parameter1, parameter2, transformationId)`

**Slots**

`.Data`: Object of class "function" ~~

`numerator`: Object of class "transformation" -flow parameter to be transformed

`denominator`: Object of class "transformation" -flow parameter to be transformed

`transformationId`: Object of class "character" unique ID to reference the transformation

**Extends**

Class "`transform`", directly. Class "`transformation`", by class "`transform`", distance 2. Class "`characterOrTransformation`", by class "`transform`", distance 3.

**Methods**

No methods defined with class "ratio" in the signature.

**Note**

The ratio transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as matrix with one column. (See example below)

**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

**See Also**

`dg1polynomial`, `quadratic`, `squareeroot`

**Examples**

```
dat <- read.FCS(system.file("extdata","0877408774.B08",
package="flowCore"))
rat1<-ratio("FSC-H","SSC-H",transformationId="rat1")
transOut<-eval(rat1)(exprs(dat))
```

---

ratiotGml2-class	Class "ratiotGml2"
------------------	--------------------

---

**Description**

Ratio transformation as parameterized in Gating-ML 2.0 is defined by the following function:

$$f(p1, p2, A, B, C) = A * (p1 - B) / (p2 - C)$$

**Objects from the Class**

Objects can be created by calls to the constructor

```
ratiotGml2(p1, p2, A, B, C, transformationId)
```

**Slots**

.Data: Object of class function ~~

numerator: Object of class "transformation" -flow parameter to be used as numerator in the transformation function

denominator: Object of class "transformation" -flow parameter to be used as denominator in the transformation function

pA: Object of class numeric constant A

pB: Object of class numeric constant B

pC: Object of class numeric constant C

transformationId: Object of class "character" -unique ID to reference the transformation

**Extends**

Class "transform", directly. Class "transformation", by class "transform", distance 2. Class "characterOrTransformation", by class "transform", distance 3.

**Methods**

No methods defined with class "ratiotGml2" in the signature.

**Note**

The ratiotGml2 transformation object can be evaluated using the eval method by passing the data frame as an argument. The transformed parameters are returned as matrix with one column. (See example below)

**Author(s)**

Spidlen, J.

**References**

Gating-ML 2.0: International Society for Advancement of Cytometry (ISAC) standard for representing gating descriptions in flow cytometry. <http://flowcyt.sourceforge.net/gating/20130122.pdf>

**See Also**

[ratio](#), [transform-class](#), [transform](#)

**Examples**

```
myDataIn <- read.FCS(system.file("extdata", "0877408774.B08",
  package="flowCore"))
myRatioT <- ratiotGml2("FSC-H", "SSC-H", pA = 2, pB = 3,
  pC = -10, transformationId = "myRatioT")
transOut <- eval(myRatioT)(exprs(myDataIn))
```

---

read.FCS

*Read an FCS file*

---

**Description**

Check validity and Read Data File Standard for Flow Cytometry

**Usage**

```
isFCSfile(files)

read.FCS(filename, transformation="linearize", which.lines=NULL,
  alter.names=FALSE, column.pattern=NULL, invert.pattern = FALSE,
  decades=0, ncdf = FALSE, min.limit=NULL, dataset=NULL, emptyValue=TRUE)

cleanup()
```

**Arguments**

files	A vector of filenames
filename	Character of length 1: filename

transformation	An character string that defines the type of transformation. Valid values are linearize (default), linearize-with-PnG-scaling, or scale. The linearize transformation applies the appropriate power transform to the data. The linearize-with-PnG-scaling transformation applies the appropriate power transform for parameters stored on log scale, and also a linear scaling transformation based on the 'gain' (FCS $\backslash$ PnG keywords) for parameters stored on a linear scale. The scale transformation scales all columns to $\$[0,10^{\text{decades}}]\$$ , defaulting to decades=0 as in the FCS4 specification. A logical can also be used: TRUE is equal to linearize and FALSE(or NULL) corresponds to no transformation. Also when the transformation keyword of the FCS header is set to "custom" or "applied", no transformation will be used.
which.lines	Numeric vector to specify the indices of the lines to be read. If NULL all the records are read, if of length 1, a random sample of the size indicated by which.lines is read in.
alter.names	boolean indicating whether or not we should rename the columns to valid R names using <code>make.names</code> . The default is FALSE.
column.pattern	An optional regular expression defining parameters we should keep when loading the file. The default is NULL.
invert.pattern	logical. By default, FALSE. If TRUE, inverts the regular expression specified in column.pattern. This is useful for indicating the channel names that we do not want to read. If column.pattern is set to NULL, this argument is ignored.
decades	When scaling is activated, the number of decades to use for the output.
ncdf	Instead of reading all data into memory, this switches to file-based data storage. A netCDF file is creates for each <code>flowFrame</code> in the <code>.flowCoreNcdf</code> subdirectory. For large data sets this significantly reduces the memory profile of the R session, to the cost of speed and disk space. The <code>exprs</code> and <code>exprs&lt;-</code> methods make sure that the user always gets a matrix of data values. Please note that currently all operations that call <code>exprs&lt;-</code> , either explicitly or implicitly, will result in the creation of a new netCDF file. This behaviour may change in the future. Currently the software does not remove any of the netCDF files and it is up to the user to do clean up. The easiest way to do that is to delete the whole netCDF directory. To this end, one can invoke the <code>cleanup</code> function.
min.limit	The minimum value in the data range that is allowed. Some instruments produce extreme artifactual values. The positive data range for each parameter is completely defined by the measurement range of the instrument and all larger values are set to this threshold. The lower data boundary is not that well defined, since compensation might shift some values below the original measurement range of the instrument. The default value of -111 copies the behavior of <code>flowJo</code> . It can be set to an arbitrary number or to NULL, in which case the original values are kept.
dataset	The FCS file specification allows for multiple data segments in a single file. Since the output of <code>read.FCS</code> is a single <code>flowFrame</code> we can't automatically read in all available sets. This parameter allows to chose one of the subsets for import. Its value is supposed to be an integer in the range of available data sets. This argument is ignored if there is only a single data segment in the FCS file.

`emptyValue` boolean indicating whether or not we allow empty value for keyword values in TEXT segment. It affects how the double delimiters are treated. IF TRUE, The double delimiters are parsed as a pair of start and end single delimiter for an empty value. Otherwise, double delimiters are parsed one part of string as the keyword value. default is TRUE.

### Details

The function `isFCSfile` determines whether its arguments are valid FCS files.

The function `read.FCS` works with the output of the FACS machine software from a number of vendors (FCS 2.0, FCS 3.0 and List Mode Data LMD). However, the FCS 3.0 standard includes some options that are not yet implemented in this function. If you need extensions, please let me know. The output of the function is an object of class `flowFrame`.

For specifications of FCS 3.0 see <http://www.isac-net.org> and the file `../doc/fcs3.html` in the doc directory of the package.

The `which.lines` arguments allow you to read a subset of the record as you might not want to read the thousands of events recorded in the FCS file.

### Value

`isFCSfile` returns a logical vector.

`read.FCS` returns an object of class `flowFrame` that contains the data in the `exprs` slot, the parameters monitored in the `parameters` slot and the keywords and value saved in the header of the FCS file.

### Author(s)

F. Hahne, N.Le Meur

### See Also

[read.flowSet](#)

### Examples

```
## a sample file
fcsFile <- system.file("extdata", "0877408774.B08", package="flowCore")

## read file and linearize values
samp <- read.FCS(fcsFile, transformation="linearize")
exprs(samp[1:3,])
description(samp)[3:6]
class(samp)

## Only read in lines 2 to 5
subset <- read.FCS(fcsFile, which.lines=2:5, transformation="linearize")
exprs(subset)

## Read in a random sample of 100 lines
subset <- read.FCS(fcsFile, which.lines=100, transformation="linearize")
```



```
nrow(subset)
```

---

read.FCSheader	<i>Read the TEXT section of a FCS file</i>
----------------	--

---

### Description

Read (part of) the TEXT section of a Data File Standard for Flow Cytometry that contains FACS keywords.

### Usage

```
read.FCSheader(files, path=".", keyword=NULL)
```

### Arguments

files	Character vector of filenames.
path	Directory where to look for the files.
keyword	An optional character vector that specifies the FCS keyword to read.

### Details

The function `read.FCSheader` works with the output of the FACS machine software from a number of vendors (FCS 2.0, FCS 3.0 and List Mode Data LMD). The output of the function is the TEXT section of the FCS files. The user can specify some keywords to limit the output to the information of interest.

### Value

A list of character vector. Each element of the list correspond to one FCS file.

### Author(s)

N.Le Meur

### See Also

```
link[flowCore]{read.flowSet}, link[flowCore]{read.FCS}
```

### Examples

```
samp <- read.FCSheader(system.file("extdata",
  "0877408774.B08", package="flowCore"))
samp
```

```
samp <- read.FCSheader(system.file("extdata",
  "0877408774.B08", package="flowCore"), keyword=c("$DATE", "$FIL"))
samp
```

---

read.flowSet                      *Read a set of FCS files*

---

### Description

Read one or several FCS files: Data File Standard for Flow Cytometry

### Usage

```
read.flowSet(files=NULL, path=".", pattern=NULL, phenoData,
             descriptions,name.keyword, alter.names=FALSE,
             transformation = "linearize", which.lines=NULL,
             column.pattern = NULL, invert.pattern = FALSE, decades=0, sep="\t",
             as.is=TRUE, name, ncdf=FALSE, dataset=NULL, min.limit=NULL,
             emptyValue=TRUE, ...)
```

### Arguments

files	Optional character vector with filenames.
path	Directory where to look for the files.
pattern	This argument is passed on to <a href="#">dir</a> , see details.
phenoData	An object of class <a href="#">AnnotatedDataFrame</a> , character or a list of values to be extracted from the <a href="#">flowFrame</a> object, see details.
descriptions	Character vector to annotate the object of class <a href="#">flowSet</a> .
name.keyword	An optional character vector that specifies which FCS keyword to use as the sample names. If this is not set, the GUID of the FCS file is used for sample-Names, and if that is not present (or not unique), then the file names are used.
alter.names	see <a href="#">read.FCS</a> for details.
transformation	see <a href="#">read.FCS</a> for details.
which.lines	see <a href="#">read.FCS</a> for details.
column.pattern	see <a href="#">read.FCS</a> for details.
invert.pattern	see <a href="#">read.FCS</a> for details.
decades	see <a href="#">read.FCS</a> for details.
sep	Separator character that gets passed on to <a href="#">read.AnnotatedDataFrame</a> .
as.is	Logical that gets passed on to <a href="#">read.AnnotatedDataFrame</a> . This controls the automatic coercion of characters to factors in the phenoData slot.
name	An optional character scalar used as name of the object.
ncdf	Instead of reading all data into memory, this switches to file-based data storage. See <a href="#">read.FCS</a> for details.
dataset	see <a href="#">read.FCS</a> for details.

<code>min.limit</code>	see <a href="#">read.FCS</a> for details.
<code>emptyValue</code>	see <a href="#">read.FCS</a> for details.
<code>...</code>	Further arguments that get passed on to <a href="#">read.AnnotatedDataFrame</a> , see details.

## Details

There are four different ways to specify the file from which data is to be imported:

First, if the argument `phenoData` is present and is of class [AnnotatedDataFrame](#), then the file names are obtained from its sample names (i.e. column name). The column is mandatory, and an error will be generated if it is not there. Alternatively, the argument `phenoData` can be of class character, in which case this function tries to read a [AnnotatedDataFrame](#) object from the file with that name by calling `read.AnnotatedDataFrame(file.path(path, phenoData), ...)`.

In some cases the file names are not a reasonable selection criterion and the user might want to import files based on some keywords within the file. One or several keyword value pairs can be given as the `phenoData` argument in form of a named list.

Third, if the argument `phenoData` is not present and the argument `files` is not NULL, then `files` is expected to be a character vector with the file names.

Fourth, if neither the argument `phenoData` is present nor `files` is not NULL, then the file names are obtained by calling `dir(path, pattern)`.

## Value

An object of class [flowSet](#).

## Author(s)

F. Hahne, N.Le Meur, B. Ellis

## Examples

```
fcs.loc <- system.file("extdata", package="flowCore")
file.location <- paste(fcs.loc, dir(fcs.loc), sep="/")

samp <- read.flowSet(file.location[1:3])
```

---

`rectangleGate-class`    *Class "rectangleGate"*

---

## Description

Class and constructor for n-dimensional rectangular [filter](#) objects.

**Usage**

```
rectangleGate(..., .gate, filterId="defaultRectangleGate")
```

**Arguments**

<code>filterId</code>	An optional parameter that sets the <code>filterId</code> of this gate. The object can later be identified by this name.
<code>.gate</code>	A definition of the gate. This can be either a list, or a matrix, as described below.
<code>...</code>	You can also directly provide the boundaries of a <code>rectangleGate</code> as additional named arguments, as described below.

**Details**

This class describes a rectangular region in  $n$  dimensions, which is a Cartesian product of  $n$  orthogonal intervals in these dimensions.  $n=1$  corresponds to a range gate,  $n=2$  to a rectangle gate,  $n=3$  corresponds to a box region and  $n>3$  to a hyper-rectangular regions. Intervals may be open on one side, in which case the value for the boundary is supposed to be `Inf` or `-Inf`, respectively. `rectangleGates` are inclusive, that means that events on the boundaries are considered to be in the gate.

The constructor is designed to be useful in both direct and programmatic usage. To use it programmatically, you may either construct a named list or you may construct a matrix with  $n$  columns and 2 rows. The first row corresponds to the minimal value for each parameter while the second row corresponds to the maximal value for each parameter. The names of the parameters are taken from the column names or from the list names, respectively. Alternatively, the boundaries of the `rectangleGate` can be given as additional named arguments, where each of these arguments should be a numeric vector of length 2; the function tries to collapse these boundary values into a matrix.

Note that boundaries of `rectangleGates` where `min > max` are syntactically valid, however when evaluated they will always be empty.

`rectangleGate` objects can also be multiplied using the `*` operator, provided that both gates have orthogonal axes. This results in higher-dimensional `rectangleGates`. The inverse operation of subsetting by parameter name(s) is also available.

Evaluating a `rectangleGate` generates an object of class `logicalFilterResult`. Accordingly, `rectangleGates` can be used to subset and to split flow cytometry data sets.

**Value**

Returns a `rectangleGate` object for use in filtering `flowFrames` or other flow cytometry objects.

**Extends**

Class `"parameterFilter"`, directly.

Class `"concreteFilter"`, by class `parameterFilter`, distance 2.

Class `"filter"`, by class `parameterFilter`, distance 3.

**Slots**

**min,max:** Objects of class "numeric". The minimum and maximum values of the n-dimensional rectangular region.

**parameters:** Object of class "character", indicating the parameters for which the rectangleGate is defined.

**filterId:** Object of class "character", referencing the filter.

**Objects from the Class**

Objects can be created by calls of the form `new("rectangleGate", ...)`, by using the constructor `rectangleGate` or by combining existing `rectangleGates` using the `*` method. Using the constructor is the recommended way of object instantiation:

**Methods**

**%in%** signature(`x = "flowFrame"`, `table = "rectangleGate"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user, but internally by calls to the `filter` methods.

**show** signature(`object = "rectangleGate"`): Print information about the filter.

**\*** signature(`e1 = "rectangleGate"`, `e2 = "rectangleGate"`): combining two `rectangleGates` into one higher dimensional representation.

**[** signature(`x = "rectangleGate"`, `i = "character"`): Subsetting of a `rectangleGate` by parameter name(s). This is essentially the inverse to `*`.

**Note**

See the documentation in the `flowViz` package for details on plotting of `rectangleGates`.

**Author(s)**

F.Hahne, B. Ellis N. Le Meur

**See Also**

`flowFrame`, `polygonGate`, `ellipsoidGate`, `polytopeGate`, `filter` for evaluation of `rectangleGates` and `split` and `Subset` for splitting and subsetting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

#Create directly. Most likely from a command line
rectangleGate(filterId="myRectGate", "FSC-H"=c(200, 600), "SSC-H"=c(0, 400))

#To facilitate programmatic construction we also have the following
```

```

rg <- rectangleGate(filterId="myRectGate", list("FSC-H"=c(200, 600),
"SSC-H"=c(0, 400)))
mat <- matrix(c(200, 600, 0, 400), ncol=2, dimnames=list(c("min", "max"),
c("FSC-H", "SSC-H")))
rg <- rectangleGate(filterId="myRectGate", .gate=mat)

## Filtering using rectangleGates
fres <- filter(dat, rg)
fres
summary(fres)

## The result of rectangle filtering is a logical subset
Subset(dat, fres)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
split(dat, fres)

## Multiply rectangle gates
rg1 <- rectangleGate(filterId="FSC-", "FSC-H"=c(-Inf, 50))
rg2 <- rectangleGate(filterId="SSC+", "SSC-H"=c(50, Inf))
rg1 * rg2

## Subset rectangle gates
rg["FSC-H"]

```

---

sampleFilter-class      *Class "sampleFilter"*

---

## Description

This non-parameter filter selects a number of events from the primary [flowFrame](#).

## Usage

```
sampleFilter(size, filterId="defaultSampleFilter")
```

## Arguments

filterId	An optional parameter that sets the filterId of this <a href="#">filter</a> . The object can later be identified by this name.
size	The number of events to select.

## Details

Selects a number of events without replacement from a [flowFrame](#).

**Value**

Returns a sampleFilter object for use in filtering [flowFrames](#) or other flow cytometry objects.

**Extends**

Class "[concreteFilter](#)", directly.

Class "[filter](#)", by class [concreteFilter](#), distance 2.

**Slots**

**size:** Object of class "numeric". Then number of events that are to be selected.

**filterId:** A character vector that identifies this filter.

**Objects from the Class**

Objects can be created by calls of the form `new("sampleFilter", ...)` or using the constructor `sampleFilter`. The latter is the recommended way of object instantiation:

**Methods**

**%in%** signature(x = "flowFrame", table = "sampleFilter"): The workhorse used to evaluate the gate on data. This is usually not called directly by the user, but internally by calls to the [filter](#) methods.

**show** signature(object = "sampleFilter"): Print information about the gate.

**Author(s)**

B. Ellis, F.Hahne

**See Also**

[flowFrame](#), [filter](#) for evaluation of sampleFilters and [split](#) and [Subset](#) for splitting and sub-setting of flow cytometry data sets based on that.

**Examples**

```
## Loading example data
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))

#Create the filter
sf <- sampleFilter(filterId="mySampleFilter", size=500)
sf

## Filtering using sampeFilters
fres <- filter(dat, sf)
fres
summary(fres)
```

```
## The result of sample filtering is a logical subset
Subset(dat, fres)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
split(dat, fres)
```

---

scaleTransform	<i>Create the definition of a scale transformation function to be applied on a data set</i>
----------------	---

---

### Description

Create the definition of the scale Transformation that will be applied on some parameter via the transform method. The definition of this function is currently  $x = (x-a)/(b-a)$ . The transformation would normally be used to convert to a 0-1 scale. In this case, b would be the maximum possible value and a would be the minimum possible value.

### Usage

```
scaleTransform(transformationId="defaultScaleTransform", a, b)
```

### Arguments

transformationId	character string to identify the transformation
a	double that corresponds to the value that will be transformed to 0
b	double that corresponds to the value that will be transformed to 1

### Value

Returns an object of class transform.

### Author(s)

P. Haaland

### See Also

[transform-class](#), [transform](#)

### Examples

```
samp <- read.FCS(system.file("extdata",
  "0877408774.B08", package="flowCore"))
scaleTrans <- scaleTransform(transformationId="Truncate-transformation", a=1, b=10^4)
dataTransform <- transform(samp,FSC-H=scaleTrans(FSC-H))
```



---

setOperationFilter-class

*Class "setOperationFilter"*

---

### Description

Description goes here

### Slots

filters: Object of class "list"

filterId: Object of class "character" referencing the filter applied

### Extends

Class "[filter](#)", directly.

### Author(s)

B. Ellis

### See Also

[filter](#)

---

singleParameterTransform-class

*Class "singleParameterTransform"*

---

### Description

A transformation that operates on a single parameter

### Objects from the Class

Objects can be created by calls of the form `new("singleParameterTransform", ...)`.

### Slots

.Data: Object of class "function". The transformation.

parameters: Object of class "transformation". The parameter to transform. Can be a derived parameter from another transformation.

transformationId: Object of class "character". An identifier for the object.

**Extends**

Class "[transform](#)", directly. Class "[transformation](#)", by class "transform", distance 2. Class "[characterOrTransformation](#)", by class "transform", distance 3.

**Methods**

No methods defined with class "singleParameterTransform" in the signature.

**Author(s)**

F Hahne

**Examples**

```
showClass("singleParameterTransform")
```

---

sinht-class

*Class "sinht"*

---

**Description**

~~ A concise (1-5 lines) description of what the class is. ~~

**Objects from the Class**

Objects can be created by calls of the form `new("sinht", parameters, ...)`. ~~ describe objects here ~~

**Slots**

.Data: Object of class "function" ~~

a: Object of class "numeric"- non zero constant

b: Object of class "numeric"- non zero constant

parameters: Object of class "transformation" -flow parameters to be transformed

transformationId: Object of class "character" -unique ID to reference the transformation

**Extends**

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

**Methods**

No methods defined with class "sinht" in the signature.

**Note**

The transformation object can be evaluated using the eval method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry V 1.5

**See Also**

asinht

**Examples**

```
dat <- read.FCS(system.file("extdata","0877408774.B08", package="flowCore"))
sinh1<-sinht(parameters="FSC-H",a=1,b=2000,transformationId="sinH1")
transOut<-eval(sinh1)(exprs(dat))
```

---

spillover

*Compute a spillover matrix from a flowSet*

---

**Description**

Spillover information for a particular experiment is often obtained by running several tubes of beads or cells stained with a single color that can then be used to determine a spillover matrix for use with [compensate](#).

When matching stain channels in `x` with the compensation controls, we provide a few options. If ordered, we assume the ordering of the channels in the flowSet object is the same as the ordering of the compensation-control samples. IF `regexpr`, we use a regular expression to match the channel names with the filenames of the compensation controls. By default, we must "guess" based on the largest statistic for the compensation control (i.e., the row).

**Usage**

```
## S4 method for signature flowSet
spillover(x, unstained = NULL, patt = NULL, fsc = "FSC-A",
          ssc = "SSC-A", method = "median", stain_match = c("intensity", "ordered", "regexpr"),
          useNormFilt=FALSE, pregate = FALSE, plot = FALSE, ...)
```

**Arguments**

x	A flowSet of compensation beads or cells
unstained	The name of index of the unstained negative control
patt	An optional regular expression defining which parameters should be considered.
fsc	The name or index of the forward scatter parameter
ssc	The name or index of the side scatter parameter
method	The statistic to use for calculation. Traditionally, this has been the median so it is the default. The mean is sometimes more stable.
stain_match	Determines how the stain channels are matched with the compensation controls. See details.
useNormFilt	Logical Indicating whether to apply a <a href="#">norm2Filter</a> first before computing the spillover
pregate	logical. Should we pregate each channel before computing the spillover matrix? By default, no.
plot	logical. Plots the kernel density for each channel when pregating. Displays the gate used. If pregate is set to FALSE, this argument is ignored.
...	Additional arguments passed to <a href="#">rangeGate</a> .

**Details**

The algorithm used is fairly simple. First, using the scatter parameters, we restrict ourselves to the most closely clustered population to reduce the amount of debris. The selected statistic is then calculated on all appropriate parameters and the unstained values swept out of the matrix. Every sample is then normalized to [0,1] with respect to the maximum value of the sample, giving the spillover in terms of a proportion of the primary channel intensity.

**Value**

A matrix for each of the parameters

**Author(s)**

B. Ellis

**References**

C. B. Bagwell & E. G. Adams (1993). Fluorescence spectral overlap compensation for any number of flow cytometry parameters. in: *Annals of the New York Academy of Sciences*, 677:167-184.

**See Also**

[compensate](#)

## Description

Divide a flow cytometry data set into several subset according to the results of a filtering operation. There are also methods available to split according to a factor variable.

## Details

The splitting operation in the context of `flowFrames` and `flowSets` is the logical extension of subsetting. While the latter only returns the events contained within a gate, the former splits the data into the groups of events contained within and those not contained within a particular gate. This concept is extremely useful in applications where gates describe the distinction between positivity and negativity for a particular marker.

The flow data structures in `flowCore` can be split into subsets on various levels:

`flowFrame`: row-wise splitting of the raw data. In most cases, this will be done according to the outcome of a filtering operation, either using a filter that identifies more than one sub-population or by a logical filter, in which case the data is split into two populations: "in the filter" and "not in the filter". In addition, the data can be split according to a factor (or a numeric or character vector that can be coerced into a factor).

`flowSet`: can be either split into subsets of `flowFrames` according to a factor or a vector that can be coerced into a factor, or each individual `flowFrame` into subpopulations based on the `filters` or `filterResults` provided as a list of equal length.

Splitting has a special meaning for filters that result in `multipleFilterResults` or `manyFilterResults`, in which case simple subsetting doesn't make much sense (there are multiple populations that are defined by the gate and it is not clear which of those should be used for the subsetting operation). Accordingly, splitting of `multipleFilterResults` creates multiple subsets. The argument `population` can be used to limit the output to only one or some of the resulting subsets. It takes as values a character vector of names of the populations of interest. See the documentation of the different filter classes on how population names can be defined and the respective default values. For splitting of `logicalFilterResults`, the `population` argument can be used to set the population names since there is no reasonable default other than the name of the gate. The content of the argument `prefix` will be prepended to the population names and '+' or '-' are finally appended allowing for more flexible naming schemes.

The default return value for any of the `split` methods is a list, but the optional logical argument `filterSet` can be used to return a `flowSet` instead. This only applies when splitting `flowFrames`, splitting of `flowSets` always results in lists of `flowSet` objects.

## Methods

`flowFrame` methods:

`x = "flowFrame", f = "ANY", drop = "ANY"` Catch all input and cast an error if there is no method for `f` to dispatch to.

- x = "flowFrame", f = "factor", drop = "ANY"** Split a `flowFrame` by a factor variable. Length of `f` should be the same as `nrow(x)`, otherwise it will be recycled, possibly leading to undesired outcomes. The optional argument `drop` works in the usual way, in that it removes empty levels from the factor before splitting.
- x = "flowFrame", f = "character", drop = "ANY"** Coerce `f` to a factor and split on that.
- x = "flowFrame", f = "numeric", drop = "ANY"** Coerce `f` to a factor and split on that.
- x = "flowFrame", f = "filter", drop = "ANY"** First applies the `filter` to the `flowFrame` and then splits on the resulting `filterResult` object.
- x = "flowFrame", f = "filterSet", drop = "ANY"** First applies the `filterSet` to the `flowFrame` and then splits on the resulting final `filterResult` object.
- x = "flowFrame", f = "logicalFilterResult", drop = "ANY"** Split into the two subpopulations (in and out of the gate). The optional argument `population` can be used to control the names of the results.
- x = "flowFrame", f = "manyFilterResult", drop = "ANY"** Split into the several subpopulations identified by the filtering operation. Instead of returning a list, the additional logical argument `codeflowSet` makes the method return an object of class `flowSet`. The optional `population` argument takes a character vector indicating the subpopulations to use for splitting (as identified by the population name in the `filterDetails` slot).
- x = "flowFrame", f = "multipleFilterResult", drop = "ANY"** Split into the several subpopulations identified by the filtering operation. Instead of returning a list, the additional logical argument `codeflowSet` makes the method return an object of class `flowSet`. The optional `population` argument takes a character vector indicating the subpopulations to use for splitting (as identified by the population name in the `filterDetails` slot). Alternatively, this can be a list of characters, in which case the populations for each list item are collapsed into one `flowFrame`.

`flowSet` methods:

- x = "flowSet", f = "ANY", drop = "ANY"** Catch all input and cast an error if there is no method for `f` to dispatch to.
- x = "flowSet", f = "factor", drop = "ANY"** Split a `flowSet` by a factor variable. Length of `f` needs to be the same as `length(x)`. The optional argument `drop` works in the usual way, in that it removes empty levels from the factor before splitting.
- x = "flowSet", f = "character", drop = "ANY"** Coerce `f` to a factor and split on that.
- x = "flowSet", f = "numeric", drop = "ANY"** Coerce `f` to a factor and split on that.
- x = "flowSet", f = "list", drop = "ANY"** Split a `flowSet` by a list of `filterResults` (as typically returned by filtering operations on a `flowSet`). The length of the list has to be equal to the length of the `flowSet` and every list item needs to be a `filterResult` of equal class with the same parameters. Instead of returning a list, the additional logical argument `codeflowSet` makes the method return an object of class `flowSet`. The optional `population` argument takes a character vector indicating the subpopulations to use for splitting (as identified by the population name in the `filterDetails` slot). Alternatively, this can be a list of characters, in which case the populations for each list item are collapsed into one `flowFrame`. Note that using the `population` argument implies common population names for all `filterResults` in the list and there will be an error if this is not the case.

**Author(s)**

F Hahne, B. Ellis, N. Le Meur

**Examples**

```

data(GvHD)
qGate <- quadGate(filterId="qg", "FSC-H"=200, "SSC-H"=400)

## split a flowFrame by a filter that creates
## a multipleFilterResult
samp <- GvHD[[1]]
fres <- filter(samp, qGate)
split(samp, qGate)

## return a flowSet rather than a list
split(samp, fres, flowSet=TRUE)

## only keep one population
names(fres)
##split(samp, fres, population="FSC-Height+SSC-Height+")

## split the whole set, only keep two populations
##split(GvHD, qGate, population=c("FSC-Height+SSC-Height+",
##"FSC-Height-SSC-Height+"))

## now split the flowSet according to a factor
split(GvHD, pData(GvHD)$Patient)

```

---

splitscale-class      *Class "splitscale"*


---

**Description**

The split scale transformation class defines a transformation that has a logarithmic scale at high values and a linear scale at low values. The transition points are chosen so that the slope of the transformation is continuous at the transition points.

The split scale transformation is defined by the function

$$f(\text{parameter}, r, \text{maxValue}, \text{transitionChannel}) = a * \text{parameter} + b \quad \text{parameter} \leq t$$

$$\log_{10}(c * \text{parameter}) * \frac{r}{d} \quad \text{parameter} > t$$

where,

$$b = \frac{\text{transitionChannel}}{2}$$

$$d = \frac{2 * \log_{10}(e) * r}{transitionChannel} + \log_{10}(maxValue)$$

$$t = 10^{\log_{10}t}$$

$$a = \frac{transitionChannel}{2 * t}$$

$$\log_{10}ct = \frac{(a * t + b) * d}{r}$$

$$c = 10^{\log_{10}ct}$$

### Objects from the Class

Objects can be created by calls to the constructor `splitscale(parameters, r, maxValue, transitionChannel, transformationId)`.

### Slots

`.Data`: Object of class "function" ~~

`r`: Object of class "numeric"-a positive value indicating the range of the logarithmic part of the display

`maxValue`: Object of class "numeric" -a positive value indicating the maximum value the transformation is applied to

`transitionChannel`: Object of class "numeric" -non negative value that indicates where to split the linear vs. logarithmic transformation

`parameters`: Object of class "transformation" - flow parameter to be transformed

`transformationId`: Object of class "character"-unique ID to reference the transformation

### Extends

Class "[singleParameterTransform](#)", directly. Class "[transform](#)", by class "singleParameterTransform", distance 2. Class "[transformation](#)", by class "singleParameterTransform", distance 3. Class "[characterOrTransformation](#)", by class "singleParameterTransform", distance 4.

### Methods

No methods defined with class "splitscale" in the signature.

### Note

The transformation object can be evaluated using the `eval` method by passing the data frame as an argument. The transformed parameters are returned as a matrix with a single column. (See example below)

### Author(s)

Gopalakrishnan N, F.Hahne

### References

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry



**See Also**

invsplitscale

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
sp1<-splitscale("FSC-H", r=768, maxValue=10000, transitionChannel=256)
transOut<-eval(sp1)(exprs(dat))
```

---

splitScaleTransform     *Compute the split-scale transformation describe by FL. Battye*

---

**Description**

The split scale transformation described by Francis L. Battye [B15] (Figure 13) consists of a logarithmic scale at high values and a linear scale at low values with a fixed transition point chosen so that the slope (first derivative) of the transform is continuous at that point. The scale extends to the negative of the transition value that is reached at the bottom of the display.

**Usage**

```
splitScaleTransform(transformationId="defaultSplitscaleTransform", maxValue=1023, transitionChannel=
```

**Arguments**

transformationId	A name to assign to the transformation. Used by the transform/filter integration routines.
maxValue	Maximum value the transformation is applied to, e.g., 1023
transitionChannel	Where to split the linear versus the logarithmic transformation, e.g., 64
r	Range of the logarithm part of the display, ie. it may be expressed as the maxChannel - transitionChannel considering the maxChannel as the maximum value to be obtained after the transformation.

**Value**

Returns values giving the inverse of the biexponential within a certain tolerance. This function should be used with care as numerical inversion routines often have problems with the inversion process due to the large range of values that are essentially 0. Do not be surprised if you end up with population splitting about w and other odd artifacts.

**Author(s)**

N. LeMeur

**References**

Battye F.L. A Mathematically Simple Alternative to the Logarithmic Transform for Flow Cytometric Fluorescence Data Displays. <http://www.wehi.edu.au/cytometry/Abstracts/AFCG05B.html>.

**See Also**

[transform](#)

**Examples**

```
data(GvHD)
ssTransform <- splitScaleTransform("mySplitTransform")
after.1 <- transform(GvHD, FSC-H= ssTransform(FSC-H))

opar = par(mfcol=c(2, 1))
plot(density(exprs(GvHD[[1]]), 1]), main="Original")
plot(density(exprs(after.1[[1]]), 1), main="Split-scale Transform")
```

---

squareroot-class      *Class "squareroot"*

---

**Description**

Square root transform class defines a transformation defined by the function

$$f(\text{parameter}, a) = \sqrt{\left| \frac{\text{parameter}}{a} \right|}$$

**Objects from the Class**

Objects can be created by calls to the constructor `squareroot(parameters, a, transformationId)`

**Slots**

`.Data`: Object of class "function" ~~

`a`: Object of class "numeric" -non zero multiplicative constant

`parameters`: Object of class "transformation"-flow parameter to be transformed

`transformationId`: Object of class "character" -unique ID to reference the transformation

**Extends**

Class "`singleParameterTransform`", directly. Class "`transform`", by class "`singleParameterTransform`", distance 2. Class "`transformation`", by class "`singleParameterTransform`", distance 3. Class "`characterOrTransformation`", by class "`singleParameterTransform`", distance 4.

**Methods**

No methods defined with class "squareroot" in the signature.

**Note**

The squareroot transformation object can be evaluated using the eval method by passing the data frame as an argument. The transformed parameters are returned as a column vector. (See example below)

**Author(s)**

Gopalakrishnan N, F.Hahne

**References**

Gating-ML Candidate Recommendation for Gating Description in Flow Cytometry

**See Also**

dg1polynomial, ratio,quadratic

**Examples**

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))
sqrt1<-squareroot(parameters="FSC-H",a=2,transformationId="sqrt1")
transOut<-eval(sqrt1)(exprs(dat))
```

---

Subset

*Subset a flowFrame or a flowSet*

---

**Description**

An equivalent of a [subset](#) function for [flowFrame](#) or a [flowSet](#) object. Alternatively, the regular subsetting operators can be used for most of the topics documented here.

**Usage**

```
Subset(x, subset, ...)
```

**Arguments**

x	The flow object, frame or set, to subset.
subset	A filter object or, in the case of flowSet subsetting, a named list of filters.
...	Like the original <a href="#">subset</a> function, you can also select columns.

## Details

The Subset method is the recommended method for obtaining a `flowFrame` that only contains events consistent with a particular filter. It is functionally equivalent to `frame[as(filter(frame, subset), "logical"), ]` when used in the `flowFrame` context. Used in the `flowSet` context, it is equivalent to using `fsApply` to apply the filtering operation to each `flowFrame`.

Additionally, using Subset on a `flowSet` can also take a named list as the subset. In this case, the names of the list object should correspond to the `sampleNames` of the `flowSet`, allowing a different filter to be applied to each frame. If not all of the names are used or excess names are present, a warning will be generated but the valid filters will be applied for the rare instances where this is the intended operation. Note that a `filter` operation will generate a list of `filterResult` objects that can be used directly with Subset in this manner.

## Value

Depending on the original context, either a `flowFrame` or a `flowSet`.

## Author(s)

B. Ellis

## See Also

[split](#), [subset](#)

## Examples

```
sample <- read.flowSet(path=system.file("extdata", package="flowCore"),
  pattern="0877408774")
result <- filter(sample, rectangleGate("FSC-H"=c(-Inf, 1024)))
result
Subset(sample, result)
```

---

subsetting-class      *Class "subsetting"*

---

## Description

Class and methods to subset a `flowSet`. This is only needed for method dispatch in the `workFlow` framework.

## Usage

```
subsetting(indices, subsettingId="defaultSubsetting")
```

**Arguments**

`indices` Character or numeric vector of sample names.  
`subsettingId` The identifier for the subsetting object.

**Details**

The class mainly existst for method dispatch in the workflow tools.

**Value**

A subsetting object.

**Objects from the Class**

Objects should be created using the constructor `subsetting()`. See the Usage and Arguments sections for details.

**Slots**

`subsettingId`: Object of class "character". An identifier for the object.  
`indices`: Object of class "numericOrCharacter". Indices into a flowSet.

**Methods**

**add** signature(wf = "workFlow", action = "subsetting"): The constructor for the work-Flow.  
**identifier<-** signature(object = "subsetting", value = "character"): Set method for the identifier slot.  
**identifier** signature(object = "subsetting"): Get method for the identifier slot.  
**show** signature(object = "subsetting"): Show details about the object.

**Author(s)**

F. Hahne

---

subsettingActionItem-class

*Class "subsettingActionItem"*

---

**Description**

Class and method to capture subsetting operations in a flow cytometry workflow.

**Usage**

```
subsettingActionItem(ID = paste("subActionRef", guid(), sep = "_"),
  name = paste("action", identifier(get(subsetting)), sep = "_"),
  parentView, subsetting, workflow)
```

**Arguments**

workflow	An object of class <code>workFlow</code> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal <code>guid</code> function.
name	A more human-readable name of the view.
parentView, subsetting	References to the parent <code>view</code> and <code>subsetting</code> objects, respectively.

**Details**

`subsettingActionItems` provide a means to bind subsetting operations in a workflow. Each `subsettingActionItem` represents a single `subsetting`.

**Value**

A reference to the `subsettingActionItem` that is created inside the `workFlow` environment as a side effect of calling the `add` method.

A `subsettingActionItem` object for the constructor.

**Objects from the Class**

Objects should be created using the `add` method, which creates a `subsettingActionItem` from a `normalization` object and directly assigns it to a `workFlow`. Alternatively, one can use the `subsettingActionItem` constructor function for more programmatic access.

**Slots**

**subsetting:** Object of class `"fcSubsettingReference"`. A reference to the `subsetting` object that is used for the operation.

**ID:** Object of class `"character"`. A unique identifier for the `actionItem`.

**name:** Object of class `"character"`. A more human-readable name

**parentView:** Object of class `"fcViewReference"`. A reference to the parent `view` the `subsettingActionItem` is applied on.

**env:** Object of class `"environment"`. The evaluation environment in the `workFlow`.

**Extends**

Class `"actionItem"`, directly.

**Methods**

**print** signature(x = "subsettingActionItem"): Print details about the object.

**Rm** signature(symbol = "subsettingActionItem", envir = "workFlow", subSymbol = "character"): Remove a subsettingActionItem from a [workFlow](#). This method is recursive and will also remove all dependent views and [actionItems](#).

**show** signature(object = "subsettingActionItem"): Print details about the object.

**Author(s)**

Florian Hahne

**See Also**

[workFlow](#), [actionItem](#), [gateActionItem](#), [transformActionItem](#), [compensateActionItem](#), [view](#)

**Examples**

```
showClass("view")
```

---

```
subsettingView-class  Class "subsettingView"
```

---

**Description**

Class and method to capture the result of subsetting operations in a flow cytometry workflow.

**Usage**

```
subsettingView(workflow, ID=paste("subViewRef", guid(), sep="_"),
               name="default", action, data)
```

**Arguments**

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal <code>guid</code> function.
name	A more human-readable name of the view.
data, action	References to the data and <a href="#">actionItem</a> objects, respectively.

**Value**

A reference to the `subsettingView` that is created inside the [workFlow](#) environment as a side effect of calling the `add` method.

A `subsettingView` object for the constructor.

### Objects from the Class

Objects should be created using the add method, which creates a `subsettingView` from a `subsetting` object and directly assigns it to a `workFlow`. Alternatively, one can use the `subsettingView` constructor function for more programmatic access.

### Slots

**ID:** Object of class "character". A unique identifier for the view.

**name:** Object of class "character". A more human-readable name

**action:** Object of class "fcActionReference". A reference to the `actionItem` that generated the view.

**env:** Object of class "environment". The evaluation environment in the `workFlow`.

**data:** Object of class "fcDataReference" A reference to the data that is associated to the view.

### Extends

Class "`view`", directly.

### Methods

**Rm** signature(symbol = "subsettingView", envir = "workFlow", subSymbol = "character"):  
Remove a `subsettingView` from a `workFlow`. This method is recursive and will also remove all dependent views and `actionItems`.

### Author(s)

Florian Hahne

### See Also

`workFlow`, `view`, `gateView`, `transformView`, `compensateView`, `actionItem`

### Examples

```
showClass("view")
```

---

summarizeFilter-methods

*Methods for function summarizeFilter*

---

### Description

Internal methods to populate the `filterDetails` slot of a `filterResult` object.



## Methods

**result = "filterResult", filter = "filter"** summarizeFilter methods are called during the process of filtering. Their output is a list, and it can be arbitrary data that should be stored along with the results of a filtering operation.

**result = "filterResult", filter = "filterReference"** see above

**result = "filterResult", filter = "parameterFilter"** see above

**result = "filterResult", filter = "subsetFilter"** see above

**result = "logicalFilterResult", filter = "norm2Filter"** see above

**result = "logicalFilterResult", filter = "parameterFilter"** see above

**result = "multipleFilterResult", filter = "curv1Filter"** see above

**result = "multipleFilterResult", filter = "curv2Filter"** see above

**result = "multipleFilterResult", filter = "parameterFilter"** see above

---

timeFilter-class      *Class "timeFilter"*

---

## Description

Define a **filter** that removes stretches of unusual data distribution within a single parameter over time. This can be used to correct for problems during data acquisition like air bubbles or clods.

## Usage

```
timeFilter(..., bandwidth=0.75, binSize, timeParameter,
filterId="defaultTimeFilter")
```

## Arguments

**...**            The names of the parameters on which the filter is supposed to work on. Names can either be given as individual arguments, or as a list or a character vector.

**filterId**        An optional parameter that sets the filterId slot of this gate. The object can later be identified by this name.

**bandwidth, binSize**      Numerics used to set the bandwidth and binSize slots of the object.

**timeParameter**    Character used to set the timeParameter slot of the object.

## Details

Clods and disturbances in the laminar flow of a FACS instrument can cause temporal aberrations in the data acquisition that lead to artifactual values. **timeFilters** try to identify such stretches of disturbance by computing local variance and location estimates and to remove them from the data.

**Value**

Returns a [timeFilter](#) object for use in filtering [flowFrames](#) or other flow cytometry objects.

**Extends**

Class "[parameterFilter](#)", directly.

Class "[concreteFilter](#)", by class [parameterFilter](#), distance 2.

Class "[filter](#)", by class [parameterFilter](#), distance 3.

**Slots**

**bandwidth:** Object of class "numeric". The sensitivity of the filter, i.e., the amount of local variance of the signal we want to allow.

**binSize:** Object of class "numeric". The size of the bins used for the local variance and location estimation. If NULL, a reasonable default is used when evaluating the filter.

**timeParameter:** Object of class "character", used to define the time domain parameter. If NULL, the filter tries to guess the time domain from the [flowFrame](#).

**parameters:** Object of class "character", describing the parameters used to filter the [flowFrame](#).

**filterId:** Object of class "character", referencing the filter.

**Objects from the Class**

Objects can be created by calls of the form `new("timeFilter", ...)` or using the constructor `timeFilter`. Using the constructor is the recommended way of object instantiation:

**Methods**

**%in%** signature(`x = "flowFrame"`, `table = "timeFilter"`): The workhorse used to evaluate the filter on data. This is usually not called directly by the user.

**show** signature(`object = "timeFilter"`): Print information about the filter.

**Note**

See the documentation of [timeLinePlot](#) in the [flowViz](#) package for details on visualizing temporal problems in flow cytometry data.

**Author(s)**

Florian Hahne

**See Also**

[flowFrame](#), [filter](#) for evaluation of [timeFilters](#) and [split](#) and [Subset](#) for splitting and subsetting of flow cytometry data sets based on that.

## Examples

```
## Loading example data
data(GvHD)
dat <- GvHD[1:10]

## create the filter
tf <- timeFilter("SSC-H", bandwidth=1, filterId="myTimeFilter")
tf

## Visualize problems
## Not run:
library(flowViz)
timelikePlot(dat, "SSC-H")

## End(Not run)

## Filtering using timeFilters
fres <- filter(dat, tf)
fres[[1]]
summary(fres[[1]])
summary(fres[[7]])

## The result of rectangle filtering is a logical subset
cleanDat <- Subset(dat, fres)

## Visualizing after cleaning up
## Not run:
timelikePlot(cleanDat, "SSC-H")

## End(Not run)

## We can also split, in which case we get those events in and those
## not in the gate as separate populations
allDat <- split(dat[[7]], fres[[7]])

par(mfcol=c(1,3))
plot(exprs(dat[[7]])[, "SSC-H"], pch=".")
plot(exprs(cleanDat[[7]])[, "SSC-H"], pch=".")
plot(exprs(allDat[[2]])[, "SSC-H"], pch=".")
```

---

transform-class	<i>'transform': a class for transforming flow-cytometry data by applying scale factors.</i>
-----------------	---

---

## Description

Transform objects are simply functions that have been extended to allow for specialized dispatch. All of the "...Transform" constructors return functions of this type for use in one of the transformation modalities.

**Slots**

.Data: Object of class "function"  
 transformationId: A name for the transformation object

**Methods**

summary Return the parameters

**Author(s)**

N LeMeur

**See Also**

[linearTransform](#), [lnTransform](#), [logicleTransform](#), [biexponentialTransform](#), [arcsinhTransform](#),  
[quadraticTransform](#), [logTransform](#)

**Examples**

```
cosTransform <- function(transformId, a=1, b=1){
  t = new("transform", .Data = function(x) cos(a*x+b))
  t@transformationId = transformId
  t
}

cosT <- cosTransform(transformId="CosT", a=2, b=1)

summary(cosT)
```

---

transformActionItem-class

*Class "transformActionItem"*

---

**Description**

Class and method to capture transformation operations in a flow cytometry workflow.

**Usage**

```
transformActionItem(ID = paste("transActionRef", guid(), sep = "_"),
  name=paste("action", identifier(get(transform)), sep =
    "_"), parentView, transform, workflow)
```

**Arguments**

workflow	An object of class <code>workFlow</code> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal <code>guid</code> function.
name	A more human-readable name of the view.
parentView, transform	References to the parent <code>view</code> and <code>transform</code> objects, respectively.

**Details**

`transformActionItems` provide a means to bind transformation operations in a workflow. Each `transformActionItem` represents a single `transform`.

**Value**

A reference to the `transformActionItem` that is created inside the `workFlow` environment as a side effect of calling the `add` method.

A `transformActionItem` object for the constructor.

**Objects from the Class**

Objects should be created using the `add` method, which creates a `transformActionItem` from a `transform` object and directly assigns it to a `workFlow`. Alternatively, one can use the `transformActionItem` constructor function for more programmatic access.

**Slots**

**transform:** Object of class `"fcTransformReference"`. A reference to the `transform` object that is used for the transformation operation.

**ID:** Object of class `"character"`. A unique identifier for the `actionItem`.

**name:** Object of class `"character"`. A more human-readable name

**parentView:** Object of class `"fcViewReference"`. A reference to the parent `view` the `transformActionItem` is applied on.

**env:** Object of class `"environment"`. The evaluation environment in the `workFlow`.

**Extends**

Class `"actionItem"`, directly.

**Methods**

**print** signature(`x = "transformActionItem"`): Print details about the object.

**Rm** signature(`symbol = "transformActionItem"`, `envir = "workFlow"`, `subSymbol = "character"`): Remove a `transformActionItem` from a `workFlow`. This method is recursive and will also remove all dependent views and `actionItems`.

**show** signature(`object = "transformActionItem"`): Print details about the object.

**Author(s)**

Florian Hahne

**See Also**

[workFlow](#), [actionItem](#), [gateActionItem](#), [compensateActionItem](#), [view](#)

**Examples**

```
showClass("view")
```

---

transformation-class    *Class "transformation"*

---

**Description**

A virtual class to abstract transformations.

**Objects from the Class**

A virtual Class: No objects may be created from it.

**Extends**

Class "[characterOrTransformation](#)", directly.

**Methods**

No methods defined with class "transformation" in the signature.

**Author(s)**

N. Gopalakrishnan

---

transformFilter-class *A class for encapsulating a filter to be performed on transformed parameters*

---

## Description

The transformFilter class is a mechanism for including one or more variable transformations into the filtering process. Using a special case of `transform` we can introduce transformations inline with the filtering process eliminating the need to process `flowFrame` objects before applying a filter.

## Objects from the Class

Objects of this type are not generally created “by hand”. They are a side effect of the use of the `%on%` method with a `filter` object on the left hand side and a `transformList` on the right hand side.

## Slots

`transforms`: A list of transforms to perform on the target `flowFrame`

`filter`: The filter to be applied to the transformed frame

`filterId`: The name of the filter (chosen automatically)

## Extends

Class “`filter`”, directly.

## Author(s)

B. Ellis

## See Also

“`filter`”, “`transform`”, `transform`

## Examples

```
samp <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))

## Gate this object after log transforming the forward and side
## scatter variables
filter(samp, norm2Filter("FSC-H", "SSC-H", scale.factor=2)
      %on% transform("FSC-H"=log,"SSC-H"=log))
```

---

transformList-class    *Class "transformList"*

---

### Description

Class "transformList"

### Usage

```
transformList(from, tfun, to=from, transformationId =
              "defaultTransformation")
```

### Arguments

from, to	Characters giving the names of the measurement parameter on which to transform on and into which the result is supposed to be stored. If both are equal, the existing parameters will be overwritten.
tfun	A list of functions or a character vector of the names of the functions used to transform the data. R's recycling rules apply, so a single function can be given to be used on all parameters.
transformationId	The identifier for the object.

### Objects from the Class

Objects can be created by calls of the form `new("transformList", ...)`, by calling the `transform` method with key-value pair arguments of the form `key equals character` and `value equals function`, or by using the constructor `transformList`. See below for details

### Slots

**transforms:** Object of class "list", where each list item is of class `transformMap`.  
**transformationId:** Object of class "character", the identifier for the object.

### Methods

**colnames** signature(`x = "transformList"`): This returns the names of the parameters that are to be transformed.

**c** signature(`x = "transformList"`): Concatenate `transformLists` or regular lists and `transformLists`.

**%on%** signature(`e1 = "transformList"`, `e2 = "flowFrame"`): Perform a transformation using the `transformList` on a `flowFrame` or `flowSet`.

### Author(s)

B. Ellis, F. Hahne



**See Also**

[transform](#), [transformMap](#)

**Examples**

```
t1 <- transformList(c("FSC-H", "SSC-H"), list(log, asinh))
colnames(t1)
c(t1, transformList("FL1-H", "linearTransform"))
data(GvHD)
transform(GvHD[[1]], t1)
```

---

transformMap-class      *A class for mapping transforms between parameters*

---

**Description**

This class provides a mapping between parameters and transformed parameters via a function.

**Objects from the Class**

Objects of this type are not usually created by the user, except perhaps in special circumstances. They are generally automatically created by the inline [transform](#) process during the creation of a [transformFilter](#), or by a call to the [transformList](#) constructor.

**Slots**

output: Name of the transformed parameter  
input: Name of the parameter to transform  
f: Function used to accomplish the transform

**Methods**

**show** signature(object = "transformList"): Print details about the object.

**Author(s)**

B. Ellis, F. Hahne

**See Also**

[transform](#), [transformList](#)

**Examples**

```
new("transformMap", input="FSC-H", output="FSC-H", f=log)
```

---

transformReference-class      *Class "transformReference"*

---

**Description**

Class allowing to reference transforms, for instance as parameters.

**Objects from the Class**

Objects will be created internally whenever necessary and this should not be of any concern to the user.

**Slots**

.Data: The list of references

searchEnv: The environment into which the reference points.

transformationId: The name of the transformation

**Extends**

Class "[transform](#)", directly. Class "[transformation](#)", by class "[transform](#)", distance 2. Class "[characterOrTransformation](#)", by class "[transform](#)", distance 3.

**Methods**

No methods defined with class "transformReference" in the signature.

**Author(s)**

N. Gopalakrishnan

---

transformView-class      *Class "transformView"*

---

**Description**

Class and method to capture the result of transformation operations in a flow cytometry workflow.

**Usage**

```
transformView(workflow, ID=paste("transViewRef", guid(), sep="_"),
              name="default", action, data)
```

**Arguments**

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
ID	A unique identifier of the view, most likely created by using the internal guid function.
name	A more human-readable name of the view.
data, action	References to the data and <a href="#">actionItem</a> objects, respectively.

**Value**

A reference to the transformView that is created inside the [workFlow](#) environment as a side effect of calling the add method.

A transformView object for the constructor.

**Objects from the Class**

Objects should be created using the add method, which creates a transformView from a [transform](#) object and directly assigns it to a [workFlow](#). Alternatively, one can use the transformView constructor function for more programmatic access.

**Slots**

ID: Object of class "character". A unique identifier for the view.

name: Object of class "character". A more human-readable name

action: Object of class "fcActionReference". A reference to the [actionItem](#) that generated the view.

env: Object of class "environment". The evaluation environment in the [workFlow](#).

data: Object of class "fcDataReference" A reference to the data that is associated to the view.

**Extends**

Class "[view](#)", directly.

**Methods**

**Rm** signature(symbol = "transformView", envir = "workFlow", subSymbol = "character"):  
Remove a transformView from a [workFlow](#). This method is recursive and will also remove all dependent views and [actionItems](#).

**Author(s)**

Florian Hahne

**See Also**

[workFlow](#), [view](#), [gateView](#), [compensateView](#), [actionItem](#)

**Examples**

```
showClass("view")
```

---

truncateTransform	<i>Create the definition of a truncate transformation function to be applied on a data set</i>
-------------------	--

---

**Description**

Create the definition of the truncate Transformation that will be applied on some parameter via the transform method. The definition of this function is currently  $x[x < a] <- a$ . Hence, all values less than a are replaced by a. The typical use would be to replace all values less than 1 by 1.

**Usage**

```
truncateTransform(transformationId="defaultTruncateTransform", a=1)
```

**Arguments**

transformationId	character string to identify the transformation
a	double that corresponds to the value at which to truncate

**Value**

Returns an object of class transform.

**Author(s)**

P. Haaland

**See Also**

[transform-class](#), [transform](#)

**Examples**

```
samp <- read.FCS(system.file("extdata",  
  "0877408774.B08", package="flowCore"))  
truncateTrans <- truncateTransform(transformationId="Truncate-transformation", a=5)  
dataTransform <- transform(samp, FSC-H=truncateTrans(FSC-H))
```

---

unitytransform-class    *Class "unitytransform"*

---

### Description

Unity transform class transforms parameters names provided as characters into unity transform objects which can be evaluated to retrieve the corresponding columns from the data frame

### Objects from the Class

Objects can be created by calls to the constructor `unitytransform(parameters, transformationId)`.

### Slots

`.Data`: Object of class "function" ~~

`parameters`: Object of class "character" -flow parameters to be transformed

`transformationId`: Object of class "character"-unique ID to reference the transformation

### Extends

Class "`transform`", directly. Class "`transformation`", by class "`transform`", distance 2. Class "`characterOrTransformation`", by class "`transform`", distance 3.

### Methods

No methods defined with class "unitytransform" in the signature.

### Author(s)

Gopalakrishnan N, F.Hahne

### See Also

`dg1polynomial`, `ratio`

### Examples

```
dat <- read.FCS(system.file("extdata", "0877408774.B08",
package="flowCore"))
un1<-unitytransform(c("FSC-H", "SSC-H"),transformationId="un1")
transOut<-eval(un1)(exprs(dat))
```

---

view-class	<i>Class "view"</i>
------------	---------------------

---

### Description

Class and method to capture the results of standard operations (called "views" here) in a flow cytometry workflow.

### Usage

```
view(workflow, ID=paste("viewRef", guid(), sep="_"),
      name="default", data, action)
```

```
parent(object)
```

```
Data(object)
```

```
action(object)
```

```
alias(object, ...)
```

### Arguments

workflow	An object of class <a href="#">workFlow</a> for which a view is to be created.
object	An object of class <a href="#">view</a> or one of its subclasses.
ID	A unique identifier of the view, most likely created by using the internal <code>guid</code> function.
name	A more human-readable name of the view.
data, action	References to the data and <a href="#">actionItem</a> objects, respectively.
...	Further arguments that get passed to the generic.

### Details

Views provide a means to bind the results of standard operations on flow cytometry data in a workflow. Each view can be considered the outcome of one operation. There are more specific subclasses for the three possible types of operation: [gateView](#) for gating operations, [transformView](#) for transformations, and [compensateView](#) for compensation operations. See their documentation for details.

### Value

A reference to the view that is created inside the [workFlow](#) environment as a side effect of calling the constructor.

The parent view (i.e., the view based on which the current view was created) for the `parent` method.

## Objects from the Class

Objects should be created using the constructor `view`, which also assigns the view to a `workFlow` object.

## Slots

**ID:** Object of class "character". A unique identifier for the view.

**name:** Object of class "character". A more human-readable name

**action:** Object of class "fcActionReference". A reference to the `actionItem` that generated the view.

**env:** Object of class "environment". The evaluation environment in the `workFlow`.

**alias:** Object of class "fcAliasReference". A reference to the alias table.

**data:** Object of class "fcDataReference" A reference to the data that is associated to the view. See `gateView` for details on copying and subsetting of the raw data in the context of gating.

## Methods

**action** signature(object = "view"): Accessor for the action slot. Note that this returns the actual `actionItem` object, i.e., the reference gets resolved.

**Data** signature(object = "view"): Accessor for the data slot. Note that this returns the actual data object, i.e., the reference gets resolved.

**names** signature(x = "view"): Accessor to the name slot.

**alias** signature(object = "view"): Get the alias table from a view.

**parent** signature(object = "view"): The parent view, i.e., the view based on which the current view was created.

**print** signature(x = "view"): Print details about the object.

**Rm** signature(symbol = "view", envir = "workFlow", subSymbol = "character"): Remove a view from a `workFlow`. This method is recursive and will also remove all dependent views and `actionItems`.

**show** signature(object = "view"): Print details about the object.

**xyplot** signature(x = "formula", data = "view"): Plot the data underlying the view.

**xyplot** signature(x = "view", data = "missing"): Plot the data underlying the view.

## Author(s)

Florian Hahne

## See Also

`workFlow`, `gateView`, `transformView`, `compensateView`, `actionItem`

## Examples

```
showClass("view")
```

---

workFlow-class	<i>Class "workFlow"</i>
----------------	-------------------------

---

### Description

Class and methods to organize standard flow cytometry data analysis operation in a concise workflow.

### Usage

```
workFlow(data, name = "default", env = new.env(parent = emptyenv()))
```

```
undo(wf, n=1)
```

### Arguments

data	An object of class <a href="#">flowFrame</a> or <a href="#">flowSet</a> for which a basic <a href="#">view</a> is created.
name	A more human-readable name of the view.
env	Object of class environment. The evaluation environment used for the <a href="#">workFlow</a> .
wf	Object of class <a href="#">workFlow</a> .
n	The number of operations to undo.

### Details

[workFlow](#) objects organize standard flow data analysis operations like gating, compensation and transformation in one single object. The user can interact with a [workFlow](#) object (e.g. adding operations, removing them, summarizing the results) without having to keep track of intermediate objects and names.

The integral part of a [workFlow](#) is an evaluation environment which holds all objects that are created during the analysis. The structure of the whole workflow is a tree, where nodes represent [link{view}s](#) (or results of an operation) and edges represent [actionItems](#) (or the operations themselves).

### Value

A [workFlow](#) object for the constructor

Both [applyParentFilter](#) and [undo](#) are called for their side-effects.

### Objects from the Class

Objects should be created using the constructor [workFlow](#), which takes a [flowFrame](#) or [flowSet](#) as only mandatory input and creates a basic view for that.



**Slots**

- name:** Object of class "character". The name of the workFlow object.
- tree:** Object of class "fcTreeReference". A reference to the [graphNEL](#) objects representing the view structure of the workflow.
- alias:** Object of class "fcAliasReference". A reference to the alias table.
- journal:** Object of class "fcJournalReference". A reference to the journal.
- env:** Object of class "environment". The evaluation environment for the workflow in which all objects will be stored.

**Methods**

- add** signature(wf = "workFlow", action = "concreteFilter"): Create a new [gateActionItem](#) and [gateView](#) from a [filter](#) and assign those to the workflow.
- add** signature(wf = "workFlow", action = "filterList"): Create a new [gateActionItem](#) and [gateView](#) from a [filterList](#) and assign those to the workflow.
- add** signature(wf = "workFlow", action = "transformList"): Create a new [transformActionItem](#) and [transformView](#) from a [transform](#) and assign those to the workflow.
- add** signature(wf = "workFlow", action = "compensation"): Create a new [compensateActionItem](#) and [compensateView](#) from a [compensation](#) and assign those to the workflow.
- assign** signature(x = "ANY", value = "ANY", pos = "missing", envir = "workFlow", inherits = "missing", imm = "missing"): Assign an object to the environment in the workFlow object and return a [fcReference](#) to it. The symbol for the object is created as a unique identifier.
- assign** signature(x = "missing", value = "ANY", pos = "workFlow", envir = "missing", inherits = "missing", imm = "missing"): see above
- assign** signature(x = "missing", value = "ANY", pos = "missing", envir = "workFlow", inherits = "missing", imm = "missing"): same as above, but provide custom symbol for the assignment.
- assign** signature(x = "character", value = "ANY", pos = "workFlow", envir = "missing", inherits = "missing", imm = "missing"): see above
- assign** signature(x = "fcReference", value = "ANY", pos = "workFlow", envir = "missing", inherits = "missing", imm = "missing"): same as above, but assign object using an existing [fcReference](#). Note that assigning NULL essentially removes the original object.
- [ signature(x = "workFlow", i = "ANY"): Cast a useful error message.
- [[ signature(x = "workFlow", i = "ANY"): Treat the workFlow object as a regular environment. Essentially, this is equivalent to `get(x, i)`.
- \\$ signature(x = "workFlow", name = "character"): Allow for list-like access. Note that completion is only available for [views](#) since all other objects in the environment are considered to be internal.
- get** signature(x = "character", pos = "workFlow", envir = "missing", mode = "missing", inherits = "missing", imm = "missing"): Get an object identified by symbol x from the environment in the workFlow.
- get** signature(x = "character", pos = "missing", envir = "workFlow", mode = "missing", inherits = "missing", imm = "missing"): see above
- ls** signature(name = "workFlow", pos = "missing", envir = "missing", all.names = "missing", pattern = "missing"): List the content of the environment in the workFlow.

- ls** signature(name = "workFlow", pos = "missing", envir = "missing", all.names = "missing", pattern = "character"): see above
- mget** signature(x = "character", envir = "workFlow", mode = "missing", ifnotfound = "missing", inherits = "missing"): Get multiple objects identified by the symbols in x from the environment in the workFlow.
- names** signature(x = "workFlow"): List the identifiers for all [views](#) and [actionItems](#) in the workFlow.
- plot** signature(x = "workFlow", y = "missing"): Plot the structure of the workFlow tree.
- Rm** signature(symbol = "character", envir = "workFlow", subSymbol = "character"): Remove the object identified by the symbol symbol from the workFlow.
- undo** signature(wf = "workFlow", n = "numeric"): Undo the last n operations on the workFlow.
- show** signature(object = "workFlow"): Print details about the object.
- summary** signature(object = "workFlow"): Summarize a view in the workFlow.
- nodes** signature(object = "workFlow"): Return a named vector of node ids where the names are the human readable names stored in the alias table.
- actions** signature(x = "workFlow"): List the names of the [actionItems](#) in the workFlow.
- views** signature(x = "workFlow"): List the names of only the [views](#) in the workFlow.
- alias** signature(object = "workFlow"): Return the alias table for the workFlow.
- alias** signature(object = "environment"): Return the alias table from a generic environment. The method tries to find 'fcAliasRef' among the object symbols in the environment.
- journal** signature(object = "workFlow"): Return the journal for the workFlow.
- journal** signature(object = "environment"): Return the journal from a generic environment. The method tries to find 'fcJournalRef' among the object symbols in the environment.
- tree** signature(object = "workFlow"): Return the tree of the workFlow.
- journal** signature(object = "environment"): Return the tree from a generic environment. The method tries to find 'fcTreeRef' among the object symbols in the environment.

**Author(s)**

Florian Hahne

**See Also**

["view"](#), ["actionItem"](#)

**Examples**

```
showClass("view")
```

---

write.FCS	<i>Write an FCS file</i>
-----------	--------------------------

---

**Description**

Write FCS file from a flowFrame

**Usage**

```
write.FCS(x, filename, what="numeric")
```

**Arguments**

x	A <a href="#">flowFrame</a> .
filename	A character scalar giving the output file name.
what	A character scalar defining the output data type. One in integer, numeric, double. Note that forcing the data type to integer may result in considerable loss of precision if the data has been transformed. We recommend using the default data type unless disc space is an issue.

**Details**

The function `write.FCS` creates FCS 3.0 standard file from an object of class `flowFrame`.

For specifications of FCS 3.0 see <http://www.isac-net.org> and the file `../doc/fcs3.html` in the doc directory of the package.

**Value**

A character of the file name.

**Author(s)**

F. Hahne

**See Also**

```
link[flowCore]{write.flowSet}
```

**Examples**

```
## a sample file
inFile <- system.file("extdata", "0877408774.B08", package="flowCore")
foo <- read.FCS(inFile, transform=FALSE)
outFile <- file.path(tempdir(), "foo.fcs")

## now write out into a file
write.FCS(foo, outFile)
bar <- read.FCS(outFile, transform=FALSE)
```

```
all(exprs(foo) == exprs(bar))
```

---

write.flowSet	<i>Write an FCS file</i>
---------------	--------------------------

---

### Description

Write FCS file for each flowFrame in a flowSet

### Usage

```
write.flowSet(x, outdir=identifier(x), filename, ...)
```

### Arguments

x	A <a href="#">flowSet</a> .
filename	A character scalar or vector giving the output file names. By default, the function will use the identifiers of the individual flowFrames as the file name, potentially adding the .fcs suffix unless a file extension is already present. Alternatively, one can supply either a character scalar, in which case the prefix i_ is appended (i being an integer in seq_len(length(x))), or a character vector of the same length as the flowSet x.
outdir	A character scalar giving the output directory. As the default, the output of identifier(x) is used.
...	Further arguments that are passed on to <a href="#">write.FCS</a> .

### Details

The function write.flowSet creates FCS 3.0 standard file for all flowFrames in an object of class flowSet. In addition, it will write the content of the phenoData slot in the ASCII file "annotation.txt". This file can subsequently be used to reconstruct the whole flowSet using the [read.flowSet](#) function, e.g.:

```
read.flowSet(path=outdir, phenoData="annotation.txt")
```

The function uses [write.FCS](#) for the actual writing of the FCS files.

### Value

A character of the output directory.

### Author(s)

F. Hahne

### See Also

[link\[flowCore\]{write.FCS}](#)

**Examples**

```
## sample data
data(GvHD)
foo <- GvHD[1:5]
outDir <- file.path(tempdir(), "foo")

## now write out into files
write.flowSet(foo, outDir)
dir(outDir)

## and read back in
bar <- read.flowSet(path=outDir, phenoData="annotation.txt")
```

**Description**

This operator is used to construct a `transformFilter` that first applies a `transformList` to the data before applying the filter operation. You may also apply the operator to a `flowFrame` or `flowSet` to obtain transformed values specified in the list.

**Author(s)**

B. Ellis

**Examples**

```
samp <- read.FCS(system.file("extdata", "0877408774.B08", package="flowCore"))
plot(transform("FSC-H"=log, "SSC-H"=log) %on% samp)

rectangle <- rectangleGate(filterId="rectangleGateI", "FSC-H"=c(4.5, 5.5))
sampFiltered <- filter(samp, rectangle %on% transform("FSC-H"=log, "SSC-H"=log))
res <- Subset(samp, sampFiltered)

plot(transform("FSC-H"=log, "SSC-H"=log) %on% res)
```

# Index

!, filter-method (filter-class), 42

## \*Topic **IO**

read.FCS, 118  
read.FCSheader, 121  
read.flowSet, 122  
write.FCS, 163  
write.flowSet, 164

## \*Topic **classes**

actionItem-class, 5  
asinh-class, 7  
asinhGml2-class, 8  
boundaryFilter-class, 10  
characterOrTransformation-class,  
13  
compensateActionItem-class, 14  
compensatedParameter-class, 16  
compensateView-class, 17  
compensation-class, 18  
concreteFilter-class, 21  
curv1Filter-class, 22  
curv2Filter-class, 24  
dg1polynomial-class, 26  
EHtrans-class, 28  
exponential-class, 32  
expressionFilter-class, 33  
fcReference-class, 35  
filter-class, 42  
filterList-class, 44  
filterReference-class, 45  
filterResult-class, 46  
filterResultList-class, 47  
filters-class, 48  
filterSet-class, 49  
filterSummary-class, 51  
filterSummaryList-class, 53  
flowFrame-class, 54  
flowSet-class, 61  
gateActionItem-class, 67  
gateView-class, 69

hyperlog-class, 73  
hyperlogGml2-class, 74  
invsplitscale-class, 78  
kmeansFilter-class, 82  
lintGml2-class, 85  
logarithm-class, 87  
logicalFilterResult-class, 89  
logicletGml2-class, 89  
logtGml2-class, 93  
manyFilterResult-class, 96  
multipleFilterResult-class, 97  
norm2Filter-class, 98  
normalization-class, 100  
normalizeActionItem-class, 102  
normalizeView-class, 103  
parameterFilter-class, 105  
parameters-class, 106  
parameterTransform-class, 107  
quadGate-class, 111  
quadratic-class, 113  
randomFilterResult-class, 115  
ratio-class, 116  
ratiotGml2-class, 117  
rectangleGate-class, 123  
sampleFilter-class, 126  
setOperationFilter-class, 129  
singleParameterTransform-class,  
129  
sinh-class, 130  
splitscale-class, 135  
squareroot-class, 138  
subsetting-class, 140  
subsettingActionItem-class, 141  
subsettingView-class, 143  
timeFilter-class, 145  
transform-class, 147  
transformActionItem-class, 148  
transformation-class, 150  
transformFilter-class, 151

- transformList-class, 152
- transformMap-class, 153
- transformReference-class, 154
- transformView-class, 154
- unitytransform-class, 157
- view-class, 158
- workFlow-class, 160
- \*Topic **datasets**
  - GvHD, 72
- \*Topic **iteration**
  - fsApply, 66
- \*Topic **manip**
  - Subset, 139
- \*Topic **methods**
  - %on%, 165
  - arcsinhTransform, 6
  - biexponentialTransform, 9
  - boundaryFilter-class, 10
  - coerce, 13
  - compensation-class, 18
  - curv1Filter-class, 22
  - curv2Filter-class, 24
  - each\_col, 28
  - ellipsoidGate-class, 30
  - expressionFilter-class, 33
  - FCSTransTransform, 39
  - filter, 40
  - filter-and-methods, 42
  - filter-in-methods, 43
  - filterDetails-methods, 44
  - getIndexSort, 71
  - identifier, 76
  - inverseLogicleTransform, 77
  - keyword-methods, 80
  - kmeansFilter-class, 82
  - linearTransform, 84
  - lnTransform, 86
  - logicleTransform, 92
  - logTransform, 95
  - norm2Filter-class, 98
  - normalization-class, 100
  - parameters, 105
  - polygonGate-class, 108
  - polytopeGate-class, 110
  - quadGate-class, 111
  - quadraticTransform, 114
  - rectangleGate-class, 123
  - sampleFilter-class, 126
  - scaleTransform, 128
  - spillover, 131
  - split-methods, 133
  - splitScaleTransform, 137
  - subsetting-class, 140
  - summarizeFilter-methods, 144
  - timeFilter-class, 145
  - truncateTransform, 156
- \*Topic **package**
  - flowCore-package, 4
- \*, rectangleGate, rectangleGate-method (rectangleGate-class), 123
- <, flowFrame, ANY-method (flowFrame-class), 54
- <=, flowFrame, ANY-method (flowFrame-class), 54
- ==, filterResult, flowFrame-method (filterResult-class), 46
- ==, flowFrame, filterResult-method (flowFrame-class), 54
- ==, flowFrame, flowFrame-method (flowFrame-class), 54
- >, flowFrame, ANY-method (flowFrame-class), 54
- >=, flowFrame, ANY-method (flowFrame-class), 54
- [, filterResultList, ANY-method (filterResultList-class), 47
- [, filterSet, character-method (filterSet-class), 49
- [, flowFrame, ANY-method (flowFrame-class), 54
- [, flowFrame, filter-method (flowFrame-class), 54
- [, flowFrame, filterResult-method (flowFrame-class), 54
- [, flowSet, ANY-method (flowSet-class), 61
- [, flowSet-method (flowSet-class), 61
- [, multipleFilterResult, ANY-method (multipleFilterResult-class), 97
- [, rectangleGate, ANY-method (rectangleGate-class), 123
- [, rectangleGate, character-method (rectangleGate-class), 123
- [, workFlow, ANY-method (workFlow-class), 160
- [[, filterResult, ANY-method

- (filterResult-class), 46
- [[, filterResultList, ANY-method (filterResultList-class), 47
- [[, filterSet, character-method (filterSet-class), 49
- [[, filterSummary, character-method (filterSummary-class), 51
- [[, filterSummary, numeric-method (filterSummary-class), 51
- [[, flowSet, ANY-method (flowSet-class), 61
- [[, flowSet-method (flowSet-class), 61
- [[, logicalFilterResult, ANY-method (logicalFilterResult-class), 89
- [[, manyFilterResult, ANY-method (manyFilterResult-class), 96
- [[, manyFilterResult-method (manyFilterResult-class), 96
- [[, multipleFilterResult, ANY-method (multipleFilterResult-class), 97
- [[, multipleFilterResult-method (multipleFilterResult-class), 97
- [[, workflow, ANY-method (workflow-class), 160
- [[<-, filterSet, ANY, ANY, filterReference-method (filterSet-class), 49
- [[<-, filterSet, NULL, ANY, filter-method (filterSet-class), 49
- [[<-, filterSet, NULL, ANY, formula-method (filterSet-class), 49
- [[<-, filterSet, character, ANY, filter-method (filterSet-class), 49
- [[<-, filterSet, character, ANY, formula-method (filterSet-class), 49
- [[<-, filterSet, missing, ANY, filter (filterSet-class), 49
- [[<-, filterSet, missing, ANY, filter-method (filterSet-class), 49
- [[<-, flowFrame-method (flowSet-class), 61
- [[<-, flowSet, ANY, ANY, flowFrame-method (flowSet-class), 61
- [[<-, flowSet-method (flowSet-class), 61
- \$.filterSummary-method (filterSummary-class), 51
- \$.flowSet-method (flowSet-class), 61
- \$.workflow-method (workflow-class), 160
- \$.flowFrame (flowFrame-class), 54
- %% (filter-and-methods), 42
- %%, ANY-method (filter-and-methods), 42
- %%, filter, filter-method (filter-and-methods), 42
- %%-methods (filter-and-methods), 42
- %in (filter-in-methods), 43
- %in, ANY, filterReference-method (filter-in-methods), 43
- %in, ANY, filterResult-method (filter-in-methods), 43
- %in, ANY, manyFilterResult-method (filter-in-methods), 43
- %in, ANY, multipleFilterResult-method (filter-in-methods), 43
- %in, flowFrame, boundaryFilter-method (filter-in-methods), 43
- %in, flowFrame, complementFilter-method (filter-in-methods), 43
- %in, flowFrame, curv1Filter-method (filter-in-methods), 43
- %in, flowFrame, curv2Filter-method (filter-in-methods), 43
- %in, flowFrame, ellipsoidGate-method (filter-in-methods), 43
- %in, flowFrame, expressionFilter-method (filter-in-methods), 43
- %in, flowFrame, filterResult-method (filter-in-methods), 43
- %in, flowFrame, intersectFilter-method (filter-in-methods), 43
- %in, flowFrame, kmeansFilter-method (filter-in-methods), 43
- %in, flowFrame, norm2Filter-method (filter-in-methods), 43
- %in, flowFrame, polygonGate-method (filter-in-methods), 43
- %in, flowFrame, polytopeGate-method (filter-in-methods), 43
- %in, flowFrame, quadGate-method (filter-in-methods), 43
- %in, flowFrame, rectangleGate-method (filter-in-methods), 43
- %in, flowFrame, sampleFilter-method (filter-in-methods), 43
- %in, flowFrame, subsetFilter-method (filter-in-methods), 43



- `%in%`, `flowFrame`, `timeFilter`-method  
(`filter-in-methods`), 43
- `%in%`, `flowFrame`, `transformFilter`-method  
(`filter-in-methods`), 43
- `%in%`, `flowFrame`, `unionFilter`-method  
(`filter-in-methods`), 43
- `%in%`-methods (`filter-in-methods`), 43
- `%on%`, ANY, `flowSet`-method (`%on%`), 165
- `%on%`, `filter`, `parameterTransform`-method  
(`%on%`), 165
- `%on%`, `filter`, `transform`-method (`%on%`), 165
- `%on%`, `filter`, `transformList`-method  
(`%on%`), 165
- `%on%`, `parameterTransform`, `flowFrame`-method  
(`%on%`), 165
- `%on%`, `transform`, `flowFrame`-method (`%on%`),  
165
- `%on%`, `transformList`, `flowFrame`-method  
(`%on%`), 165
- `%on%`, `transformList`, `flowSet`-method  
(`%on%`), 165
- `%on%`-methods (`%on%`), 165
- `%subset%` (`filter-and-methods`), 42
- `%subset%`, ANY-method  
(`filter-and-methods`), 42
- `%subset%`, `filter`, `filter`-method  
(`filter-and-methods`), 42
- `%subset%`, `filterSet`, `filter`-method  
(`filterSet-class`), 49
- `%subset%`, `list`, `filter`-method  
(`filter-and-methods`), 42
- `&`, `filter`, `filter`-method  
(`filter-and-methods`), 42
- `&`, `filter`, `list`-method  
(`filter-and-methods`), 42
- `&`, `list`, `filter`-method  
(`filter-and-methods`), 42
- `%on%`, 57, 151, 165
  
- `action` (`view-class`), 158
- `action`, `view`-method (`view-class`), 158
- `actionItem`, 15, 17, 18, 37, 68–70, 103, 104,  
142–144, 149, 150, 155, 158, 159,  
162
- `actionItem`-class, 5
- `actionItems`, 15, 103, 143, 149, 155, 159,  
160, 162
- `actions` (`workFlow-class`), 160
- `actions`, `workFlow`-method  
(`workFlow-class`), 160
- `add` (`workFlow-class`), 160
- `add`, `workFlow`, `character`-method  
(`subsetting-class`), 140
- `add`, `workFlow`, `compensation`-method  
(`workFlow-class`), 160
- `add`, `workFlow`, `concreteFilter`-method  
(`workFlow-class`), 160
- `add`, `workFlow`, `filterList`-method  
(`workFlow-class`), 160
- `add`, `workFlow`, `logical`-method  
(`subsetting-class`), 140
- `add`, `workFlow`, `normalization`-method  
(`normalization-class`), 100
- `add`, `workFlow`, `numeric`-method  
(`subsetting-class`), 140
- `add`, `workFlow`, `subsetting`-method  
(`subsetting-class`), 140
- `add`, `workFlow`, `transformList`-method  
(`workFlow-class`), 160
- `alias` (`view-class`), 158
- `alias`, `actionItem`-method  
(`actionItem-class`), 5
- `alias`, `environment`-method  
(`workFlow-class`), 160
- `alias`, `view`-method (`view-class`), 158
- `alias`, `workFlow`-method (`workFlow-class`),  
160
- `AnnotatedDataFrame`, 55, 56, 61, 62, 106, 123
- `AnnotatedDataFrames`, 56
- `apply`, 28, 67
- `arcsinhTransform`, 6, 148
- `as.data.frame.manyFilterResult`  
(`manyFilterResult-class`), 96
- `asinht`, 9
- `asinht` (`asinht-class`), 7
- `asinht`-class, 7
- `asinhtGml2` (`asinhtGml2-class`), 8
- `asinhtGml2`-class, 8
- `assign` (`fcReference-class`), 35
- `assign`, ANY, ANY, missing, `workFlow`, missing, missing-method  
(`workFlow-class`), 160
- `assign`, `character`, ANY, `workFlow`, missing, missing, missing-method  
(`workFlow-class`), 160
- `assign`, `fcReference`, ANY, `workFlow`, missing, missing, missing-method  
(`workFlow-class`), 160
- `assign`, missing, ANY, missing, `workFlow`, missing, missing-method

- (workFlow-class), 160
- assign,missing,ANY,workFlow,missing,missing,missing-method (coerce), 13
- (workFlow-class), 160
- biexponentialTransform, 9, 92, 148
- booleanGate, filter-class
  - (filter-class), 42
- boundaryFilter (boundaryFilter-class), 10
- boundaryFilter-class, 10
- c, transformList-method
  - (transformList-class), 152
- call, filter-method (filter), 40
- cbind2, flowFrame, matrix-method
  - (flowFrame-class), 54
- cbind2, flowFrame, numeric-method
  - (flowFrame-class), 54
- char2ExpressionFilter
  - (expressionFilter-class), 33
- character, filter-method (filter), 40
- characterOrTransformation, 7, 8, 16, 27, 29, 32, 73, 75, 79, 85, 88, 91, 94, 113, 116, 117, 130, 136, 138, 150, 154, 157
- characterOrTransformation-class, 13
- cleanup (read.FCS), 118
- coerce, 13
- coerce, call, filter-method (coerce), 13
- coerce, character, filter-method
  - (coerce), 13
- coerce, complementFilter, call-method
  - (coerce), 13
- coerce, complementFilter, logical-method
  - (coerce), 13
- coerce, ellipsoidGate, polygonGate-method
  - (coerce), 13
- coerce, environment, flowSet-method
  - (coerce), 13
- coerce, factor, filterResult-method
  - (coerce), 13
- coerce, filter, call-method (coerce), 13
- coerce, filter, logical-method (coerce), 13
- coerce, filterReference, call-method
  - (coerce), 13
- coerce, filterReference, concreteFilter-method
  - (coerce), 13
- coerce, filterResult, logical-method
  - (coerce), 13
- coerce, filterResultList, list-method
  - (coerce), 13
- coerce, filterSet, list-method (coerce), 13
- coerce, filterSummary, data.frame-method
  - (filterSummary-class), 51
- coerce, flowFrame, filterSet-method
  - (coerce), 13
- coerce, flowFrame, flowSet-method
  - (coerce), 13
- coerce, flowSet, flowFrame-method
  - (coerce), 13
- coerce, flowSet, list-method (coerce), 13
- coerce, formula, filter-method (coerce), 13
- coerce, gateView, filterResult-method
  - (coerce), 13
- coerce, intersectFilter, call-method
  - (coerce), 13
- coerce, intersectFilter, call-method
  - (filter-and-methods), 42
- coerce, intersectFilter, logical-method
  - (coerce), 13
- coerce, list, filterResultList-method
  - (coerce), 13
- coerce, list, filterSet-method (coerce), 13
- coerce, list, flowSet-method (coerce), 13
- coerce, list, transformList-method
  - (coerce), 13
- coerce, logical, filterResult-method
  - (coerce), 13
- coerce, logicalFilterResult, logical-method
  - (coerce), 13
- coerce, matrix, filterResult-method
  - (coerce), 13
- coerce, name, filter-method (coerce), 13
- coerce, nullParameter, character-method
  - (coerce), 13
- coerce, numeric, filterResult-method
  - (coerce), 13
- coerce, parameters, character-method
  - (coerce), 13
- coerce, randomFilterResult, logical-method
  - (coerce), 13
- coerce, ratio, character-method (coerce),

- 13
- coerce, rectangleGate, polygonGate-method  
(coerce), 13
- coerce, subsetFilter, call-method  
(coerce), 13
- coerce, subsetFilter, logical-method  
(coerce), 13
- coerce, transform, character-method  
(coerce), 13
- coerce, unionFilter, call-method  
(coerce), 13
- coerce, unionFilter, logical-method  
(coerce), 13
- coerce, unitytransform, character-method  
(coerce), 13
- colnames, flowFrame-method  
(flowFrame-class), 54
- colnames, flowSet-method  
(flowSet-class), 61
- colnames, transformList-method  
(transformList-class), 152
- colnames<- (flowFrame-class), 54
- colnames<-, flowFrame-method  
(flowFrame-class), 54
- colnames<-, flowSet-method  
(flowSet-class), 61
- compensate, 131, 132
- compensate (compensation-class), 18
- compensate, flowFrame, compensation-method  
(flowFrame-class), 54
- compensate, flowFrame, data.frame-method  
(flowFrame-class), 54
- compensate, flowFrame, matrix-method  
(flowFrame-class), 54
- compensate, flowSet, ANY-method  
(flowSet-class), 61
- compensate, flowSet, matrix-method  
(flowSet-class), 61
- compensateActionItem, 5, 6, 69, 103, 143,  
150, 161
- compensateActionItem  
(compensateActionItem-class),  
14
- compensateActionItem-class, 14
- compensatedParameter  
(compensatedParameter-class),  
16
- compensatedParameter-class, 16
- compensateView, 70, 104, 144, 155, 158, 159,  
161
- compensateView (compensateView-class),  
17
- compensateView-class, 17
- compensation, 14, 15, 18, 37, 58, 161
- compensation (compensation-class), 18
- compensation-class, 18
- complementFilter-class  
(setOperationFilter-class), 129
- concreteFilter, 11, 23, 25, 30, 34, 47, 83,  
98, 105, 108, 111, 124, 127, 146
- concreteFilter-class, 21
- cov.rob, 99
- CovMcd, 99
- curv1Filter, 26
- curv1Filter (curv1Filter-class), 22
- curv1Filter-class, 22
- curv2Filter, 23, 25
- curv2Filter (curv2Filter-class), 24
- curv2Filter-class, 24
- Data (view-class), 158
- Data, view-method (view-class), 158
- data.frames, 55
- decisionTreeGate, filter-class  
(filter-class), 42
- description, 81
- description (flowFrame-class), 54
- description, flowFrame-method  
(flowFrame-class), 54
- description<-, flowFrame, ANY-method  
(flowFrame-class), 54
- description<-, flowFrame, list-method  
(flowFrame-class), 54
- dg1polynomial (dg1polynomial-class), 26
- dg1polynomial-class, 26
- dim (flowFrame-class), 54
- dim, flowFrame-method (flowFrame-class),  
54
- dir, 122
- do.call, 101
- each\_col, 28, 57
- each\_col, flowFrame-method (each\_col), 28
- each\_col-methods (each\_col), 28
- each\_row (each\_col), 28
- each\_row, flowFrame-method (each\_col), 28
- each\_row-methods (each\_col), 28

- EHtrans (EHtrans-class), 28
- EHtrans-class, 28
- ellipsoidGate, 30, 109, 125
- ellipsoidGate (ellipsoidGate-class), 30
- ellipsoidGate, filter-class
  - (filter-class), 42
- ellipsoidGate-class, 30
- environment, 61, 64
- estimateLogicle, 40, 93
- estimateLogicle (logicleTransform), 92
- eval, asinht, missing-method
  - (asinht-class), 7
- eval, asinhtGml2, missing-method
  - (asinhtGml2-class), 8
- eval, compensatedParameter, missing-method
  - (compensatedParameter-class), 16
- eval, dg1polynomial, missing-method
  - (dg1polynomial-class), 26
- eval, EHtrans, missing-method
  - (EHtrans-class), 28
- eval, exponential, missing-method
  - (exponential-class), 32
- eval, filterReference, missing-method
  - (filterReference-class), 45
- eval, hyperlog, missing-method
  - (hyperlog-class), 73
- eval, hyperlogtGml2, missing-method
  - (hyperlogtGml2-class), 74
- eval, invsplitscale, missing-method
  - (invsplitscale-class), 78
- eval, lintGml2, missing-method
  - (lintGml2-class), 85
- eval, logarithm, missing-method
  - (logarithm-class), 87
- eval, logicletGml2, missing-method
  - (logicletGml2-class), 89
- eval, logtGml2, missing-method
  - (logtGml2-class), 93
- eval, quadratic, missing-method
  - (quadratic-class), 113
- eval, ratio, missing-method
  - (ratio-class), 116
- eval, ratiotGml2, missing-method
  - (ratiotGml2-class), 117
- eval, sinht, missing-method
  - (sinht-class), 130
- eval, splitscale, missing-method
  - (splitscale-class), 135
- eval, squareroot, missing-method
  - (squareroot-class), 138
- eval, transformReference, missing-method
  - (transformReference-class), 154
- eval, unitytransform, missing-method
  - (unitytransform-class), 157
- exponential (exponential-class), 32
- exponential-class, 32
- expressionFilter, 34
- expressionFilter
  - (expressionFilter-class), 33
- expressionFilter-class, 33
- exprs, 119
- exprs (flowFrame-class), 54
- exprs, flowFrame-method
  - (flowFrame-class), 54
- exprs<- (flowFrame-class), 54
- exprs<-, flowFrame, ANY-method
  - (flowFrame-class), 54
- exprs<-, flowFrame, matrix-method
  - (flowFrame-class), 54
- fcActionReference, 38
- fcActionReference (fcReference-class), 35
- fcActionReference-class
  - (fcReference-class), 35
- fcAliasReference, 38
- fcAliasReference (fcReference-class), 35
- fcAliasReference-class
  - (fcReference-class), 35
- fcCompensateReference, 38
- fcCompensateReference
  - (fcReference-class), 35
- fcCompensateReference-class
  - (fcReference-class), 35
- fcDataReference, 38
- fcDataReference (fcReference-class), 35
- fcDataReference-class
  - (fcReference-class), 35
- fcFilterReference, 38
- fcFilterReference (fcReference-class), 35
- fcFilterReference-class
  - (fcReference-class), 35
- fcFilterResultReference, 38
- fcFilterResultReference
  - (fcReference-class), 35

- fcFilterResultReference-class  
(fcReference-class), 35
- fcNormalizationReference, 38
- fcNormalizationReference  
(fcReference-class), 35
- fcNormalizationReference-class  
(fcReference-class), 35
- fcNullReference (fcReference-class), 35
- fcNullReference-class  
(fcReference-class), 35
- fcReference, 37, 38, 161
- fcReference (fcReference-class), 35
- fcReference-class, 35
- FCSTransTransform, 39
- fcStructureReference, 37, 38
- fcStructureReference-class  
(fcReference-class), 35
- fcSubsettingReference  
(fcReference-class), 35
- fcSubsettingReference-class  
(fcReference-class), 35
- fcTransformReference, 38
- fcTransformReference  
(fcReference-class), 35
- fcTransformReference-class  
(fcReference-class), 35
- fcTreeReference, 38
- fcTreeReference (fcReference-class), 35
- fcTreeReference-class  
(fcReference-class), 35
- fcViewReference, 38
- fcViewReference (fcReference-class), 35
- fcViewReference-class  
(fcReference-class), 35
- featureNames (flowFrame-class), 54
- featureNames, flowFrame-method  
(flowFrame-class), 54
- filerList, 48
- filter, 10–12, 22–26, 30, 31, 33, 34, 37, 40,  
40–50, 55, 58, 63, 67, 68, 70, 76, 77,  
83, 89, 96–99, 105, 106, 108–112,  
115, 123–127, 129, 133, 134, 140,  
145, 146, 151, 161
- filter, filter-method (filter-class), 42
- filter, flowFrame, filter-method  
(filter), 40
- filter, flowFrame, filterSet-method  
(filter), 40
- filter, flowFrame, norm2Filter (filter),  
40
- filter, flowFrame, polygonGate (filter),  
40
- filter, flowFrame, rectangleGate  
(filter), 40
- filter, flowFrame-method (filter), 40
- filter, flowSet, filter-method (filter),  
40
- filter, flowSet, filterList-method  
(filter), 40
- filter, flowSet, filterSet-method  
(filter), 40
- filter, flowSet, list-method (filter), 40
- filter-and-methods, 42
- filter-class, 42
- filter-in-methods, 43
- filter-on-methods (%on%), 165
- filterDetails (filterDetails-methods),  
44
- filterDetails, filterResult, ANY-method  
(filterDetails-methods), 44
- filterDetails, filterResult, missing-method  
(filterDetails-methods), 44
- filterDetails-methods, 44
- filterDetails<-  
(filterDetails-methods), 44
- filterDetails<-, filterResult, character, ANY-method  
(filterDetails-methods), 44
- filterDetails<-, filterResult, character, filter-method  
(filterDetails-methods), 44
- filterDetails<-, filterResult, character, setOperationFilter-  
(filterDetails-methods), 44
- filtergate, filter-class (filter-class),  
42
- filterList, 49, 161
- filterList (filterList-class), 44
- filterList-class, 44
- filterReference, 21, 77
- filterReference  
(filterReference-class), 45
- filterReference, environment, character-method  
(filterReference-class), 45
- filterReference, filterSet, character-method  
(filterSet-class), 49
- filterReference-class, 45
- filterResult, 11, 37, 41, 43, 47, 48, 51–55,  
58, 63, 67–70, 76, 77, 83, 89, 96, 97,

- 115, 133, 134, 140, 144
- filterResult (filterResult-class), 46
- filterResult-class, 46
- filterResultList, 41, 53, 54
- filterResultList
  - (filterResultList-class), 47
- filterResultList-class, 47
- filterResults, 70
- filters (filters-class), 48
- filters-class, 48
- filterSet, 45, 46, 49, 50, 63, 96, 134
- filterSet (filterSet-class), 49
- filterSet-class, 49
- filtersList (filters-class), 48
- filtersList-class (filters-class), 48
- filterSummary, 54, 68
- filterSummary (filterSummary-class), 51
- filterSummary-class, 51
- filterSummaryList, 47, 52
- filterSummaryList
  - (filterSummaryList-class), 53
- filterSummaryList-class, 53
- flowCore (flowCore-package), 4
- flowCore-package, 4
- flowFrame, 4, 11, 12, 19, 20, 23, 25, 26, 28,
  - 30, 31, 33, 34, 37, 40–42, 51, 52, 54,
  - 61–64, 67, 76, 77, 80, 81, 83, 96, 98,
  - 99, 105, 106, 108–112, 119, 120,
  - 122, 124–127, 133, 134, 139, 140,
  - 146, 151, 152, 160, 163
- flowFrame (flowFrame-class), 54
- flowFrame-class, 54
- flowFrames, 47, 82
- flowSet, 4, 12, 19, 20, 23, 26, 37, 40, 41, 47,
  - 58, 66, 81, 83, 99–101, 111, 112,
  - 122, 123, 133, 134, 139, 140, 152,
  - 160, 164
- flowSet (flowSet-class), 61
- flowSet-class, 61
- flowSets, 19, 53
- flowViz, 23, 25, 31, 56, 83, 99, 109, 112, 125,
  - 146
- formula, filter-method (filter), 40
- fsApply, 66, 140
- fsApply, flowSet, ANY (fsApply), 66
- fsApply, flowSet-method (flowSet-class),
  - 61
- function, 107
- gate (gateActionItem-class), 67
- gate, gateActionItem-method
  - (gateActionItem-class), 67
- gateActionItem, 5, 6, 15, 103, 143, 150, 161
- gateActionItem (gateActionItem-class),
  - 67
- gateActionItem-class, 67
- gateView, 18, 104, 144, 155, 158, 159, 161
- gateView (gateView-class), 69
- gateView-class, 69
- get, character, missing, workflow-method
  - (workflow-class), 160
- get, character, workflow, missing-method
  - (workflow-class), 160
- get, fcNullReference, missing, missing-method
  - (fcReference-class), 35
- get, fcReference, missing, missing-method
  - (fcReference-class), 35
- getIndexSort, 71
- getIndexSort, flowFrame-method
  - (getIndexSort), 71
- graphNEL, 37, 161
- GvHD, 72
- head, flowFrame-method
  - (flowFrame-class), 54
- here, 42
- histogram, 56
- hyperlog, 76
- hyperlog (hyperlog-class), 73
- hyperlog-class, 73
- hyperlogtGml2 (hyperlogtGml2-class), 74
- hyperlogtGml2-class, 74
- identifier, 57, 76
- identifier, actionItem-method
  - (actionItem-class), 5
- identifier, compensation-method
  - (compensation-class), 18
- identifier, fcReference-method
  - (fcReference-class), 35
- identifier, filter-method (identifier),
  - 76
- identifier, filterList-method
  - (filterList-class), 44
- identifier, filterReference-method
  - (identifier), 76
- identifier, filterResult-method
  - (identifier), 76

- identifier, filterSet, character-method  
(filterSet-class), 49
- identifier, filterSet-method  
(filterSet-class), 49
- identifier, flowFrame-method  
(identifier), 76
- identifier, flowSet-method  
(flowSet-class), 61
- identifier, normalization-method  
(normalization-class), 100
- identifier, NULL-method (view-class), 158
- identifier, subsetting-method  
(subsetting-class), 140
- identifier, transform-method  
(identifier), 76
- identifier, transformList-method  
(transformList-class), 152
- identifier, view-method (view-class), 158
- identifier-methods (identifier), 76
- identifier<- (identifier), 76
- identifier<-, compensation, character-method  
(compensation-class), 18
- identifier<-, filter, character-method  
(filter), 40
- identifier<-, filterList, character-method  
(filterList-class), 44
- identifier<-, flowFrame, ANY-method  
(identifier), 76
- identifier<-, flowFrame-method  
(identifier), 76
- identifier<-, flowSet, ANY-method  
(flowSet-class), 61
- identifier<-, normalization, character-method  
(normalization-class), 100
- identifier<-, subsetting, character-method  
(subsetting-class), 140
- identifier<-, transformList, character-method  
(transformList-class), 152
- initialize, dg1polynomial-method  
(dg1polynomial-class), 26
- initialize, flowFrame-method  
(flowFrame-class), 54
- initialize, parameterFilter-method  
(parameterFilter-class), 105
- initialize, ratio-method (ratio-class),  
116
- initialize, ratiotGm12-method  
(ratiotGm12-class), 117
- initialize, singleParameterTransform-method  
(singleParameterTransform-class),  
129
- intersectFilter-class  
(setOperationFilter-class), 129
- intersectFilter-method  
(filter-and-methods), 42
- inverseLogicTransform, 40, 77, 93
- invsplitscale (invsplitscale-class), 78
- invsplitscale-class, 78
- isFCSfile (read.FCS), 118
- isNull (fcReference-class), 35
- isNull, fcReference-method  
(fcReference-class), 35
- journal (workFlow-class), 160
- journal, environment-method  
(workFlow-class), 160
- journal, workFlow-method  
(workFlow-class), 160
- keyword, 56, 62
- keyword (keyword-methods), 80
- keyword, flowFrame, character-method  
(keyword-methods), 80
- keyword, flowFrame, function-method  
(keyword-methods), 80
- keyword, flowFrame, list-method  
(keyword-methods), 80
- keyword, flowFrame, missing-method  
(keyword-methods), 80
- keyword, flowSet, ANY-method  
(keyword-methods), 80
- keyword, flowSet, list-method  
(keyword-methods), 80
- keyword-methods, 80
- keyword<- (keyword-methods), 80
- keyword<-, flowFrame, ANY-method  
(keyword-methods), 80
- keyword<-, flowFrame, character-method  
(keyword-methods), 80
- keyword<-, flowFrame, list-method  
(keyword-methods), 80
- keyword<-, flowSet, list-method  
(keyword-methods), 80
- kmeansFilter, 42
- kmeansFilter (kmeansFilter-class), 82
- kmeansFilter(), 42
- kmeansFilter-class, 82

- length, filter-method (filter), 40
- length, filterReference-method (filterReference-class), 45
- length, filterSummary-method (filterSummary-class), 51
- length, flowSet-method (flowSet-class), 61
- length, kmeansFilter-method (kmeansFilter-class), 82
- length, logicalFilterResult-method (logicalFilterResult-class), 89
- length, manyFilterResult-method (manyFilterResult-class), 96
- length, multipleFilterResult-method (multipleFilterResult-class), 97
- linearTransform, 84, 86, 148
- lintGml2 (lintGml2-class), 85
- lintGml2-class, 85
- list, 45, 47, 49, 53, 107
- lnTransform, 86, 148
- logarithm (logarithm-class), 87
- logarithm-class, 87
- logicalFilterResult, 46, 48, 51, 52, 54, 98, 124, 133
- logicalFilterResult (logicalFilterResult-class), 89
- logicalFilterResult-class, 89
- logicalFilterResults, 69
- logicletGml2, 76
- logicletGml2 (logicletGml2-class), 89
- logicletGml2-class, 89
- logicleTransform, 40, 76, 78, 91, 92, 92, 148
- logtGml2 (logtGml2-class), 93
- logtGml2-class, 93
- logTransform, 94, 95, 148
- ls (workFlow-class), 160
- ls, workFlow, missing, missing, missing, character-method (workFlow-class), 160
- ls, workFlow, missing, missing, missing, missing-method (workFlow-class), 160
- make.names, 119
- manyFilterResult, 133
- manyFilterResult (manyFilterResult-class), 96
- manyFilterResult-class, 96
- mget, character, workFlow-method (workFlow-class), 160
- multipleFilterResult, 22, 25, 46, 48, 52, 54, 82, 111, 133
- multipleFilterResult (multipleFilterResult-class), 97
- multipleFilterResult-class, 97
- multipleFilterResults, 52, 69
- name, filter-method (filter), 40
- names (flowFrame-class), 54
- names, actionItem-method (actionItem-class), 5
- names, filterResultList-method (filterResultList-class), 47
- names, filterSet-method (filterSet-class), 49
- names, filterSummary-method (filterSummary-class), 51
- names, flowFrame-method (flowFrame-class), 54
- names, logicalFilterResult-method (logicalFilterResult-class), 89
- names, manyFilterResult-method (manyFilterResult-class), 96
- names, multipleFilterResult-method (multipleFilterResult-class), 97
- names, view-method (view-class), 158
- names, workFlow-method (workFlow-class), 160
- names<-, multipleFilterResult, ANY-method (multipleFilterResult-class), 97
- names<-, multipleFilterResult-method (multipleFilterResult-class), 97
- ncol, flowFrame-method (flowFrame-class), 54
- nodes, workFlow-method (workFlow-class), 160
- norm2Filter, 42, 43, 98, 132
- norm2Filter (norm2Filter-class), 98
- norm2Filter, filter-class (filter-class), 42
- norm2Filter-class, 98
- normalization, 102–104, 142
- normalization (normalization-class), 100
- normalization-class, 100
- normalize (normalization-class), 100



- normalize, flowSet, normalization-method  
(normalization-class), 100
- normalizeActionItem  
(normalizeActionItem-class),  
102
- normalizeActionItem-class, 102
- normalizeView, 18
- normalizeView (normalizeView-class), 103
- normalizeView-class, 103
- nrow, flowFrame-method  
(flowFrame-class), 54
  
- parameterFilter, 11, 22, 23, 25, 30, 42, 83,  
98, 105, 106, 108, 111, 124, 146
- parameterFilter-class, 105
- parameters, 56, 83, 105
- parameters, compensation-method  
(compensation-class), 18
- parameters, filter-method (parameters),  
105
- parameters, filterReference-method  
(parameters), 105
- parameters, filterResult-method  
(parameters), 105
- parameters, filterResultList-method  
(filterResultList-class), 47
- parameters, flowFrame, missing-method  
(parameters), 105
- parameters, flowFrame-method  
(parameters), 105
- parameters, manyFilterResult-method  
(manyFilterResult-class), 96
- parameters, normalization-method  
(normalization-class), 100
- parameters, nullParameter-method  
(parameters), 105
- parameters, parameterFilter-method  
(parameters), 105
- parameters, parameterTransform-method  
(parameters), 105
- parameters, ratio-method (parameters),  
105
- parameters, ratiotGml2-method  
(ratiotGml2-class), 117
- parameters, setOperationFilter-method  
(parameters), 105
- parameters, singleParameterTransform-method  
(singleParameterTransform-class),  
129
- parameters, transform-method  
(parameters), 105
- parameters, transformReference-method  
(transformReference-class), 154
- parameters-class, 106
- parameters<- (parameters), 105
- parameters<- , dg1polynomial, character-method  
(dg1polynomial-class), 26
- parameters<- , dg1polynomial, parameters-method  
(dg1polynomial-class), 26
- parameters<- , dg1polynomial, transform-method  
(parameters), 105
- parameters<- , flowFrame, AnnotatedDataFrame-method  
(parameters), 105
- parameters<- , parameterFilter, character-method  
(parameters), 105
- parameters<- , parameterFilter, list-method  
(parameters), 105
- parameters<- , parameterFilter, transform-method  
(parameters), 105
- parameters<- , singleParameterTransform, character-method  
(parameters), 105
- parameters<- , singleParameterTransform, transform-method  
(parameters), 105
- parameterTransform-class, 107
- parent (view-class), 158
- parent, actionItem-method  
(actionItem-class), 5
- parent, NULL-method (view-class), 158
- parent, view-method (view-class), 158
- pData, flowSet-method (flowSet-class), 61
- pData<- , flowSet, data.frame-method  
(flowSet-class), 61
- phenoData, flowSet-method  
(flowSet-class), 61
- phenoData<- , flowSet, ANY-method  
(flowSet-class), 61
- phenoData<- , flowSet, phenoData-method  
(flowSet-class), 61
- plot, flowFrame, ANY-method  
(flowFrame-class), 54
- plot, flowFrame-method  
(flowFrame-class), 54
- plot, flowSet, ANY-method  
(flowSet-class), 61
- plot, flowSet-method (flowSet-class), 61
- plot, workflow, missing-method  
(workflow-class), 160

- polygate, 31, 108, 110, 125
  - polygate (polygate-class), 108
  - polygate, filter-class
    - (filter-class), 42
  - polygate-class, 108
  - polytopeGate, 31, 109, 125
  - polytopeGate (polytopeGate-class), 110
  - polytopeGate-class, 110
  - print, compensateActionItem-method
    - (compensateActionItem-class), 14
  - print, filterSummary-method
    - (filterSummary-class), 51
  - print, gateActionItem-method
    - (gateActionItem-class), 67
  - print, normalizeActionItem-method
    - (normalizeActionItem-class), 102
  - print, subsettingActionItem-method
    - (subsettingActionItem-class), 141
  - print, transformActionItem-method
    - (transformActionItem-class), 148
  - print, view-method (view-class), 158
- quadGate (quadGate-class), 111
- quadGate-class, 111
- quadratic (quadratic-class), 113
- quadratic-class, 113
- quadraticTransform, 114, 148
- randomFilterResult, 46, 48
- randomFilterResult-class, 115
- range (flowFrame-class), 54
- range, flowFrame-method
  - (flowFrame-class), 54
- rangeGate, 132
- ratio, 118
- ratio (ratio-class), 116
- ratio-class, 116
- ratiotGml2 (ratiotGml2-class), 117
- ratiotGml2-class, 117
- rbind2, flowFrame, flowSet-method
  - (flowSet-class), 61
- rbind2, flowSet, flowFrame-method
  - (flowSet-class), 61
- rbind2, flowSet, flowSet, missing-method
  - (flowSet-class), 61
- rbind2, flowSet, flowSet-method
  - (flowSet-class), 61
- rbind2, flowSet, missing (flowSet-class), 61
- rbind2, flowSet, missing-method
  - (flowSet-class), 61
- read.AnnotatedDataFrame, 122, 123
- read.FCS, 55, 58, 118, 122, 123
- read.FCSheader, 121
- read.flowSet, 61, 64, 120, 122, 164
- rectangleGate, 31, 109, 110, 124
- rectangleGate (rectangleGate-class), 123
- rectangleGate(), 42
- rectangleGate, filter-class
  - (filter-class), 42
- rectangleGate-class, 123
- Rm (fcReference-class), 35
- Rm, actionItem, workflow, character-method
  - (actionItem-class), 5
- Rm, character, workflow, character-method
  - (workflow-class), 160
- Rm, compensateActionItem, workflow, character-method
  - (compensateActionItem-class), 14
- Rm, compensateView, workflow, character-method
  - (compensateView-class), 17
- Rm, fcNullReference, missing, character-method
  - (fcReference-class), 35
- Rm, fcReference, missing, character-method
  - (fcReference-class), 35
- Rm, fcReference, workflow, character-method
  - (fcReference-class), 35
- Rm, gateActionItem, workflow, character-method
  - (gateActionItem-class), 67
- Rm, gateView, workflow, character-method
  - (gateView-class), 69
- Rm, normalizeActionItem, workflow, character-method
  - (normalizeActionItem-class), 102
- Rm, normalizeView, workflow, character-method
  - (normalizeView-class), 103
- Rm, subsettingActionItem, workflow, character-method
  - (subsettingActionItem-class), 141
- Rm, subsettingView, workflow, character-method
  - (subsettingView-class), 143
- Rm, transformActionItem, workflow, character-method
  - (transformActionItem-class),

- 148
- Rm, transformView, workflow, character-method  
(transformView-class), 154
- Rm, view, workflow, character-method  
(view-class), 158
- sampleFilter (sampleFilter-class), 126
- sampleFilter-class, 126
- sampleNames, flowSet-method  
(flowSet-class), 61
- sampleNames<- , flowSet, ANY-method  
(flowSet-class), 61
- sapply, 63, 67
- scaleTransform, 128
- setOperationFilter-class, 129
- show, boundaryFilter-method  
(boundaryFilter-class), 10
- show, compensateActionItem-method  
(compensateActionItem-class),  
14
- show, compensation-method  
(compensation-class), 18
- show, complementFilter-method  
(setOperationFilter-class), 129
- show, curv1Filter-method  
(curv1Filter-class), 22
- show, curv2Filter-method  
(curv2Filter-class), 24
- show, ellipsoidGate-method  
(ellipsoidGate-class), 30
- show, expressionFilter-method  
(expressionFilter-class), 33
- show, fcNullReference-method  
(fcReference-class), 35
- show, fcReference-method  
(fcReference-class), 35
- show, filter-method (filter), 40
- show, filterList-method  
(filterList-class), 44
- show, filterReference-method  
(filterReference-class), 45
- show, filterResult-method  
(filterResult-class), 46
- show, filterResultList-method  
(filterResultList-class), 47
- show, filters-method (filters-class), 48
- show, filterSet-method  
(filterSet-class), 49
- show, filtersList-method  
(filters-class), 48
- show, filterSummary-method  
(filterSummary-class), 51
- show, flowFrame-method  
(flowFrame-class), 54
- show, flowSet-method (flowSet-class), 61
- show, gateActionItem-method  
(gateActionItem-class), 67
- show, intersectFilter-method  
(setOperationFilter-class), 129
- show, kmeansFilter-method  
(kmeansFilter-class), 82
- show, manyFilterResult-method  
(manyFilterResult-class), 96
- show, multipleFilterResult-method  
(multipleFilterResult-class),  
97
- show, norm2Filter-method  
(norm2Filter-class), 98
- show, normalizeActionItem-method  
(normalizeActionItem-class),  
102
- show, polygonGate-method  
(polygonGate-class), 108
- show, polytopeGate-method  
(polytopeGate-class), 110
- show, quadGate-method (quadGate-class),  
111
- show, rectangleGate-method  
(rectangleGate-class), 123
- show, sampleFilter-method  
(sampleFilter-class), 126
- show, subsetFilter-method  
(setOperationFilter-class), 129
- show, subsetting-method  
(subsetting-class), 140
- show, subsettingActionItem-method  
(subsettingActionItem-class),  
141
- show, timeFilter-method  
(timeFilter-class), 145
- show, transform-method  
(transform-class), 147
- show, transformActionItem-method  
(transformActionItem-class),  
148
- show, transformFilter-method

- (transformFilter-class), 151
- show, transformMap-method
  - (transformMap-class), 153
- show, unionFilter-method
  - (setOperationFilter-class), 129
- show, unitytransform-method
  - (unitytransform-class), 157
- show, view-method (view-class), 158
- show, workflow-method (workflow-class), 160
- singleParameterTransform, 7, 8, 29, 32, 73, 75, 79, 85, 88, 91, 94, 113, 130, 136, 138
- singleParameterTransform-class, 129
- sinht (sinht-class), 130
- sinht-class, 130
- smoothScatter, 56
- sort, filterSet-method
  - (filterSet-class), 49
- spillover, 19, 21, 131
- spillover, flowFrame-method
  - (flowFrame-class), 54
- spillover, flowSet-method (spillover), 131
- split, 23, 26, 31, 34, 47, 58, 63, 83, 99, 109, 112, 125, 127, 140, 146
- split (split-methods), 133
- split, flowFrame, ANY-method
  - (split-methods), 133
- split, flowFrame, character-method
  - (split-methods), 133
- split, flowFrame, factor-method
  - (split-methods), 133
- split, flowFrame, filter-method
  - (split-methods), 133
- split, flowFrame, filterSet-method
  - (split-methods), 133
- split, flowFrame, logicalFilterResult-method
  - (split-methods), 133
- split, flowFrame, manyFilterResult-method
  - (split-methods), 133
- split, flowFrame, multipleFilterResult-method
  - (split-methods), 133
- split, flowFrame, numeric-method
  - (split-methods), 133
- split, flowSet, ANY-method
  - (split-methods), 133
- split, flowSet, character-method
  - (split-methods), 133
- split, flowSet, factor-method
  - (split-methods), 133
- split, flowSet, filter-method
  - (split-methods), 133
- split, flowSet, filterResult-method
  - (split-methods), 133
- split, flowSet, filterResultList-method
  - (filterResultList-class), 47
- split, flowSet, list-method
  - (split-methods), 133
- split, flowSet, numeric-method
  - (split-methods), 133
- split-methods, 133
- splitscale (splitscale-class), 135
- splitscale-class, 135
- splitScaleTransform, 137
- splom, 56
- squareroot (squareroot-class), 138
- squareroot-class, 138
- Subset, 12, 31, 34, 41, 99, 109, 125, 127, 139, 146
- subset, 139, 140
- Subset, flowFrame, filter-method
  - (Subset), 139
- Subset, flowFrame, logical-method
  - (Subset), 139
- Subset, flowFrame-method (Subset), 139
- Subset, flowSet, ANY (Subset), 139
- Subset, flowSet, ANY-method (Subset), 139
- Subset, flowSet, filterResultList-method
  - (Subset), 139
- Subset, flowSet, list-method (Subset), 139
- subsetFilter-class
  - (setOperationFilter-class), 129
- subsetFilter-method
  - (filter-and-methods), 42
- subsetting, 142, 144
- subsetting (subsetting-class), 140
- subsetting-class, 140
- subsettingActionItem
  - (subsettingActionItem-class), 141
- subsettingActionItem-class, 141
- subsettingView (subsettingView-class), 143
- subsettingView-class, 143
- summarizeFilter

- (summarizeFilter-methods), 144
- summarizeFilter, filterResult, filter-method (summarizeFilter-methods), 144
- summarizeFilter, filterResult, filterReference-method (summarizeFilter-methods), 144
- summarizeFilter, filterResult, parameterFilter-method (summarizeFilter-methods), 144
- summarizeFilter, filterResult, subsetFilter-method (summarizeFilter-methods), 144
- summarizeFilter, logicalFilterResult, norm2Filter-method (summarizeFilter-methods), 144
- summarizeFilter, logicalFilterResult, parameterFilter-method (summarizeFilter-methods), 144
- summarizeFilter, multipleFilterResult, curv1Filter-method (summarizeFilter-methods), 144
- summarizeFilter, multipleFilterResult, curv2Filter-method (summarizeFilter-methods), 144
- summarizeFilter, multipleFilterResult, parameterFilter-method (summarizeFilter-methods), 144
- summarizeFilter-methods, 144
- summary, 42
- summary, filter-method (filter), 40
- summary, filterReference-method (filterReference-class), 45
- summary, filterResult-method (filterSummary-class), 51
- summary, filterResultList-method (filterResultList-class), 47
- summary, flowFrame-method (flowFrame-class), 54
- summary, flowSet-method (flowSet-class), 61
- summary, gateActionItem-method (gateActionItem-class), 67
- summary, gateView-method (gateView-class), 69
- summary, logicalFilterResult-method (logicalFilterResult-class), 89
- summary, manyFilterResult-method (manyFilterResult-class), 96
- summary, multipleFilterResult-method (multipleFilterResult-class), 97
- summary, rectangleGate-method (rectangleGate-class), 123
- summary, subsetFilter-method (setOperationFilter-class), 129
- summary, transform-method (transform-class), 147
- summary, workflow-method (workflow-class), 160
- tail, flowFrame-method (flowFrame-class), 54
- timeFilter, 146
- timeFilter (timeFilter-class), 145
- timeFilter-class, 145
- timeMethod, 146
- toTable (filterSummary-class), 51
- toTable, filterSummary-method (filterSummary-class), 51
- toTable, filterSummaryList-method (filterSummaryList-class), 53
- transformation, 6–10, 16, 19, 20, 27, 29, 32, 37, 42, 43, 57, 73, 75–77, 79, 82, 85–88, 94, 95, 107, 113, 115–118, 128, 130, 136, 138, 149, 151–157, 161
- transform (transform-class), 147
- transform, flowFrame-method (flowFrame-class), 54
- transform, flowSet-method (flowSet-class), 61
- transform, missing-method (transform-class), 147
- transform-class, 147
- transformActionItem, 5, 6, 15, 69, 103, 143, 161
- transformActionItem (transformActionItem-class), 148
- transformActionItem-class, 148
- transformation, 7, 8, 16, 27, 29, 32, 73, 75, 79, 82, 83, 85, 88, 91, 94, 113, 116, 117, 130, 136, 138, 154, 157
- transformation-class, 150
- transformFilter, 153
- transformFilter (transformFilter-class), 151
- transformFilter-class, 151
- transformList, 43, 151, 153
- transformList (transformList-class), 152
- transformList-class, 152
- transformMap, 152, 153
- transformMap (transformMap-class), 153
- transformMap-class, 153

- transformReference
  - (transformReference-class), [154](#)
- transformReference-class, [154](#)
- transformReferences, [20](#)
- transforms, [20](#)
- transformView, [18](#), [70](#), [104](#), [144](#), [158](#), [159](#), [161](#)
- transformView (transformView-class), [154](#)
- transformView-class, [154](#)
- tree (workFlow-class), [160](#)
- tree, environment-method
  - (workFlow-class), [160](#)
- tree, workFlow-method (workFlow-class), [160](#)
- truncateTransform, [156](#)
  
- undo (workFlow-class), [160](#)
- unionFilter-class
  - (setOperationFilter-class), [129](#)
- uniroot, [10](#)
- unitytransform (unitytransform-class), [157](#)
- unitytransform-class, [157](#)
  
- varLabels, flowSet-method
  - (flowSet-class), [61](#)
- varLabels<-, flowSet, ANY-method
  - (flowSet-class), [61](#)
- varLabels<-, flowSet-method
  - (flowSet-class), [61](#)
- varMetadata, flowSet-method
  - (flowSet-class), [61](#)
- varMetadata<-, flowSet, ANY-method
  - (flowSet-class), [61](#)
- vector, [107](#)
- view, [5](#), [6](#), [14](#), [15](#), [18](#), [37](#), [67–70](#), [102–104](#), [142–144](#), [149](#), [150](#), [155](#), [160](#), [162](#)
- view (view-class), [158](#)
- view-class, [158](#)
- views, [5](#), [161](#), [162](#)
- views (workFlow-class), [160](#)
- views, workFlow-method (workFlow-class), [160](#)
  
- workFlow, [5](#), [6](#), [14](#), [15](#), [17](#), [18](#), [36](#), [38](#), [39](#), [67–70](#), [102–104](#), [142–144](#), [149](#), [150](#), [155](#), [158–160](#)
- workFlow (workFlow-class), [160](#)
- workFlow-class, [160](#)
  
- write.FCS, [163](#), [164](#)
- write.flowSet, [164](#)
  
- xyplot, [48](#)
- xyplot, formula, gateView-method
  - (gateView-class), [69](#)
- xyplot, formula, view-method
  - (view-class), [158](#)
- xyplot, view, missing-method
  - (view-class), [158](#)