

Package ‘chipenrich.data’

April 4, 2014

Type Package

Title Gene set enrichment analysis for CHIP-seq data

Version 0.99.4

Date 2013-10-07

Depends R (>= 2.15.0)

Imports methods, GenomicRanges (>= 1.10.0), IRanges (>= 1.16.0), BiocGenerics (>= 0.2.0)

biocViews ExperimentData

Description Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

License GPL-3

LazyLoad yes

Author Ryan P. Welch [aut, cre, cph], Chee Lee [aut], Laura J. Scott [ths], Maureen A. Sartor [ths]

Maintainer Ryan P. Welch <welchr@umich.edu>

R topics documented:

chipenrich.data-package	4
example_datasets	6
genes.hsa	6
genes.mmu	7
genes.rno	8
GeneSet-class	8
geneset.biocarta_pathway.hsa	9
geneset.biocarta_pathway.mmu	10
geneset.biocarta_pathway.rno	10
geneset.cytoband.hsa	11
geneset.drug_bank.hsa	11
geneset.drug_bank.mmu	12

geneset.drug_bank.rno	12
geneset.ehmn_pathway_gene.hsa	13
geneset.ehmn_pathway_gene.mmu	13
geneset.ehmn_pathway_gene.rno	14
geneset.gene_expression.hsa	14
geneset.gene_expression.mmu	15
geneset.GOBP.hsa	15
geneset.GOBP.mmu	16
geneset.GOBP.rno	16
geneset.GOCC.hsa	17
geneset.GOCC.mmu	17
geneset.GOCC.rno	18
geneset.GOMF.hsa	18
geneset.GOMF.mmu	19
geneset.GOMF.rno	19
geneset.kegg_pathway.hsa	20
geneset.kegg_pathway.mmu	20
geneset.kegg_pathway.rno	21
geneset.mesh.hsa	21
geneset.mesh.mmu	22
geneset.mesh.rno	22
geneset.metabolite.hsa	23
geneset.metabolite.mmu	23
geneset.metabolite.rno	24
geneset.mirbase.hsa	24
geneset.mirbase.mmu	25
geneset.mirbase.rno	25
geneset.omim.hsa	26
geneset.omim.mmu	26
geneset.omim.rno	27
geneset.panther_pathway.hsa	27
geneset.panther_pathway.mmu	28
geneset.panther_pathway.rno	28
geneset.pfam.hsa	29
geneset.pfam.mmu	29
geneset.pfam.rno	30
geneset.protein_interaction_mimi.hsa	30
geneset.protein_interaction_mimi.mmu	31
geneset.protein_interaction_mimi.rno	31
geneset.transcription_factors.hsa	32
geneset.transcription_factors.mmu	32
geneset.transcription_factors.rno	33
locusdef.hg19.1kb	33
locusdef.hg19.5kb	34
locusdef.hg19.exon	34
locusdef.hg19.nearest_gene	35
locusdef.hg19.nearest_tss	35
locusdef.mm10.1kb	36

locusdef.mm10.5kb	36
locusdef.mm10.nearest_tss	37
locusdef.mm9.1kb	37
locusdef.mm9.5kb	38
locusdef.mm9.exon	38
locusdef.mm9.nearest_gene	39
locusdef.mm9.nearest_tss	39
locusdef.rn4.1kb	40
locusdef.rn4.5kb	40
locusdef.rn4.nearest_gene	41
locusdef.rn4.nearest_tss	41
LocusDefinition-class	42
mappa.hg19.1kb.100mer	43
mappa.hg19.1kb.24mer	43
mappa.hg19.1kb.36mer	44
mappa.hg19.1kb.40mer	45
mappa.hg19.1kb.50mer	45
mappa.hg19.1kb.75mer	46
mappa.hg19.5kb.100mer	47
mappa.hg19.5kb.24mer	47
mappa.hg19.5kb.36mer	48
mappa.hg19.5kb.40mer	49
mappa.hg19.5kb.50mer	49
mappa.hg19.5kb.75mer	50
mappa.hg19.exon.100mer	51
mappa.hg19.exon.24mer	51
mappa.hg19.exon.36mer	52
mappa.hg19.exon.40mer	53
mappa.hg19.exon.50mer	53
mappa.hg19.exon.75mer	54
mappa.hg19.nearest_gene.100mer	55
mappa.hg19.nearest_gene.24mer	55
mappa.hg19.nearest_gene.36mer	56
mappa.hg19.nearest_gene.40mer	57
mappa.hg19.nearest_gene.50mer	57
mappa.hg19.nearest_gene.75mer	58
mappa.hg19.nearest_tss.100mer	59
mappa.hg19.nearest_tss.24mer	59
mappa.hg19.nearest_tss.36mer	60
mappa.hg19.nearest_tss.40mer	61
mappa.hg19.nearest_tss.50mer	61
mappa.hg19.nearest_tss.75mer	62
mappa.mm9.1kb.100mer	63
mappa.mm9.1kb.36mer	63
mappa.mm9.1kb.40mer	64
mappa.mm9.1kb.50mer	65
mappa.mm9.1kb.75mer	65
mappa.mm9.5kb.100mer	66

mappa.mm9.5kb.36mer	67
mappa.mm9.5kb.40mer	67
mappa.mm9.5kb.50mer	68
mappa.mm9.5kb.75mer	69
mappa.mm9.exon.100mer	69
mappa.mm9.exon.36mer	70
mappa.mm9.exon.40mer	71
mappa.mm9.exon.50mer	71
mappa.mm9.exon.75mer	72
mappa.mm9.nearest_gene.100mer	73
mappa.mm9.nearest_gene.36mer	73
mappa.mm9.nearest_gene.40mer	74
mappa.mm9.nearest_gene.50mer	75
mappa.mm9.nearest_gene.75mer	75
mappa.mm9.nearest_tss.100mer	76
mappa.mm9.nearest_tss.36mer	77
mappa.mm9.nearest_tss.40mer	77
mappa.mm9.nearest_tss.50mer	78
mappa.mm9.nearest_tss.75mer	79
peaks_E2F4	79
tss.hg19	80
tss.mm10	81
tss.mm9	81
tss.rn4	82

Index	83
--------------	-----------

chipenrich.data-package

Datasets required for the chipenrich package

Description

This package includes genesets (KEGG, GO, etc.), gene locus definitions, gene locus mappabilities, and other required data for the chipenrich package. It also includes example ChIP-seq peak datasets for use with chipenrich.

Details

Almost all of the datasets within this package, with the exception of the example ChIP-seq peak datasets, are not intended for direct use by the user. They are automatically used by the chipenrich package itself. This help file attempts to document each data source should a user wish to understand how each is computed, where it came from, etc.

Genesets are exactly that - sets of genes - as defined in various databases such as KEGG, Gene Ontology, and others.

Each geneset is stored per genome in the format "geneset.<name of geneset>.<genome build>", use `data(package="chipenrich.data")` for a full list.

Each geneset and the description for how it was generated can be found in the "Geneset Database Information" vignette. Use `browseVignettes("chipenrich.data")` for a full list.

Gene locus definitions define regions in which peaks are assigned to genes. If a peak falls into a particular gene locus, it is assigned to that gene. Within the package, locus definitions are stored per genome and per definition in the format "locusdef.<genome>.<definition code>". We support multiple definitions currently:

- `nearest_tss`: assigns peaks to the gene with the closest transcription start site (TSS). Each gene locus stretches from the midpoint upstream between TSSs, and the midpoint downstream between TSSs.
- `nearest_gene`: assigns peaks to the nearest gene. Each gene locus stretches from the upstream midpoint between genes and the downstream midpoint between genes.
- `1kb`: each gene locus is defined as the region 1KB up- and down-stream of the TSS.
- `5kb`: each gene locus is defined as the region 5KB up- and down-stream of the TSS.

The mappability datasets stored within this package represent the average mappability per locus definition (above.) They are stored in the following format: "mappa.<genome build>.<locus definition code>.<read length>". Each dataset is simply an entrez ID, and the mappability score computed for the gene under the given locus definition and read length. For more information regarding how mappability is included, please see (Welch & Lee, 2012.)

Example ChIP-seq peak datasets are also included, and can be used for running `chipenrich`. Each dataset is stored as "peaks_<name of protein/transcription factor>". Use [example_datasets](#) or `data(package="chipenrich.data")` for a list.

Author(s)

Ryan Welch <welchr@umich.edu>

References

Welch RP*, Lee C*, Smith RA, Imbriano P, Scott LJ, Sartor MA. 2012. ChIP-Enrich: Gene set enrichment testing for ChIP-Seq data (in preparation.)

Examples

```
# Get a list of all ChIP-seq peak example datasets.
example_datasets();

# Inspect an example geneset.
data("geneset.kegg_pathway.hsa");
str(geneset.kegg_pathway.hsa);

# Get the mappings from geneset ID to genes for KEGG (loaded above)
kegg_to_genes = as.list(geneset.kegg_pathway.hsa@set.gene);

# Get the mappings from geneset ID to geneset descriptions for KEGG
kegg_to_names = as.list(geneset.kegg_pathway.hsa@set.name);

# List all genes within KEGG pathways (as Entrez IDs.)
```

```

kegg_genes = geneset.kegg_pathway.hsa@all.genes;

# Inspect an example locus definition.
data(locusdef.hg19.nearest_tss);
str(locusdef.hg19.nearest_tss);

# Get a data frame specifying each gene locus, its chromosome, and start/end positions.
ldef = locusdef.hg19.nearest_tss@dframe;

# Get a GRanges object containing each locus definition for fast lookups.
granges = locusdef.hg19.nearest_tss@granges;

```

example_datasets	<i>List ChIP-seq peak example datasets</i>
------------------	--

Description

Convenience function to list the example ChIP-seq peak datasets available for use with chipenrich.

Usage

```
example_datasets()
```

Details

Prints a list of all example datasets, and a tip on how to load them.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```

library(chipenrich.data)
example_datasets()

```

genes.hsa	<i>genes.hsa</i>
-----------	------------------

Description

Entrez Gene IDs for H. sapiens and their corresponding gene symbols.
This is used internally by the chipenrich package.

Usage

```
data(genes.hsa)
```

Format

A data frame with 19781 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

`genes.mmu`

genes.mmu

Description

Entrez Gene IDs for *M. musculus* and their corresponding gene symbols.

This is used internally by the `chipenrich` package.

Usage

```
data(genes.mmu)
```

Format

A data frame with 21388 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

`genes.rno``genes.rno`

Description

Entrez Gene IDs for *R. norvegicus* and their corresponding gene symbols.

This is used internally by the `chipenrich` package.

Usage

```
data(genes.rno)
```

Format

A data frame with 19746 observations on the following 2 variables.

GENEID Entrez Gene IDs

SYMBOL Official gene symbols

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

`GeneSet-class``Class "GeneSet"`

Description

Class for storing sets of genes and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("GeneSet")`.

These objects are used internally by the `chipenrich` package and users will not likely need to create these.

Slots

set.gene: Object of class "environment". Maps from geneset IDs to lists of Entrez gene IDs.
type: Object of class "character". The formal name for this collection of genesets.
set.name: Object of class "environment". Maps from geneset IDs to their descriptions/names.
all.genes: Object of class "character". A set of all genes present across every geneset.
organism: Object of class "character". Organism code for gene IDs.
dburl: Object of class "character". Web URL for this collection of genesets.

Note

Not typically accessed by the user - this is used internally by the chipenrich package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
library(chipenrich.data)

# Show information about class.
showClass("GeneSet")

# What is stored inside a geneset object?
data("geneset.metabolite.hsa");
str(geneset.metabolite.hsa);

# How are the mappings from geneset IDs to gene IDs stored?
ls.str(geneset.metabolite.hsa@set.gene);
```

```
geneset.biocarta_pathway.hsa
  geneset.biocarta_pathway.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.biocarta_pathway.mmu`

geneset.biocarta_pathway.mmu

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.biocarta_pathway.rno`

geneset.biocarta_pathway.rno

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.cytoband.hsa` *geneset.cytoband.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.cytoband.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.drug_bank.hsa` *geneset.drug_bank.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.drug_bank.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.drug_bank.mmu` *geneset.drug_bank.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.drug_bank.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.drug_bank.rno` *geneset.drug_bank.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.drug_bank.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.hsa  
  geneset.ehmn_pathway_gene.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.ehmn_pathway_gene.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.mmu  
  geneset.ehmn_pathway_gene.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.ehmn_pathway_gene.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.ehmn_pathway_gene.rno  
  geneset.ehmn_pathway_gene.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.ehmn_pathway_gene.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.gene_expression.hsa  
  geneset.gene_expression.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.gene_expression.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.gene_expression.mmu  
  geneset.gene_expression.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.gene_expression.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.GOBP.hsa    geneset.GOBP.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOBP.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.mmu` *geneset.GOBP.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOBP.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.rno` *geneset.GOBP.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOBP.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

<code>geneset.GOCC.hsa</code>	<i>geneset.GOCC.hsa</i>
-------------------------------	-------------------------

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOCC.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

<code>geneset.GOCC.mmu</code>	<i>geneset.GOCC.mmu</i>
-------------------------------	-------------------------

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOCC.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOCC.rno` *geneset.GOCC.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOCC.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOMF.hsa` *geneset.GOMF.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOMF.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.GOMF.mmu	<i>geneset.GOMF.mmu</i>
------------------	-------------------------

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOMF.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.GOMF.rno	<i>geneset.GOMF.rno</i>
------------------	-------------------------

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.GOMF.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.kegg_pathway.hsa  
  geneset.kegg_pathway.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.kegg_pathway.mmu  
  geneset.kegg_pathway.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.kegg_pathway.rno  
  geneset.kegg_pathway.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.mesh.hsa      geneset.mesh.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mesh.mmu *geneset.mesh.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mesh.rno *geneset.mesh.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.hsa
geneset.metabolite.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.mmu
geneset.metabolite.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.metabolite.rno`*geneset.metabolite.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mirbase.hsa`*geneset.mirbase.hsa*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mirbase.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mirbase.mmu *geneset.mirbase.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mirbase.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.mirbase.rno *geneset.mirbase.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mirbase.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.omim.hsa *geneset.omim.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.omim.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.omim.mmu *geneset.omim.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.omim.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.omim.rno *geneset.omim.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.omim.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.panther_pathway.hsa
geneset.panther_pathway.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.panther_pathway.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.panther_pathway.mmu  
geneset.panther_pathway.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.panther_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.panther_pathway.rno  
geneset.panther_pathway.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.panther_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.pfam.hsa	<i>geneset.pfam.hsa</i>
------------------	-------------------------

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.pfam.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.pfam.mmu	<i>geneset.pfam.mmu</i>
------------------	-------------------------

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.pfam.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.pfam.rno` *geneset.pfam.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.pfam.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.protein_interaction_mimi.hsa`
geneset.protein_interaction_mimi.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.protein_interaction_mimi.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.protein_interaction_mimi.mmu  
  geneset.protein_interaction_mimi.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.protein_interaction_mimi.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.protein_interaction_mimi.rno  
  geneset.protein_interaction_mimi.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.protein_interaction_mimi.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.transcription_factors.hsa  
  geneset.transcription_factors.hsa
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.transcription_factors.mmu  
  geneset.transcription_factors.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.transcription_factors.rno  
    geneset.transcription_factors.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.transcription_factors.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
locusdef.hg19.1kb    locusdef.hg19.1kb
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.hg19.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.hg19.5kb *locusdef.hg19.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.hg19.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.hg19.exon *locusdef.hg19.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.hg19.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.hg19.nearest_gene  
    locusdef.hg19.nearest_gene
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.hg19.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.hg19.nearest_tss  
    locusdef.hg19.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.hg19.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.mm10.1kb *locusdef.mm10.1kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm10.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.mm10.5kb *locusdef.mm10.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm10.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm10.nearest_tss  
    locusdef.mm10.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm10.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm9.1kb    locusdef.mm9.1kb
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm9.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.mm9.5kb *locusdef.mm9.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm9.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.mm9.exon *locusdef.mm9.exon*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm9.exon)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm9.nearest_gene  
    locusdef.mm9.nearest_gene
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm9.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.mm9.nearest_tss  
    locusdef.mm9.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.mm9.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.rn4.1kb *locusdef.rn4.1kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.rn4.1kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

locusdef.rn4.5kb *locusdef.rn4.5kb*

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.rn4.5kb)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.rn4.nearest_gene  
    locusdef.rn4.nearest_gene
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.rn4.nearest_gene)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
locusdef.rn4.nearest_tss  
    locusdef.rn4.nearest_tss
```

Description

LocusDefinition object which stores information about gene locus definitions.
These objects are used internally by the chipenrich package.

Usage

```
data(locusdef.rn4.nearest_tss)
```

Format

See [LocusDefinition-class](#) for a description of the format.

See Also

For more information about gene locus definitions: [chipenrich.data](#)

LocusDefinition-class *Class* "LocusDefinition"

Description

A storage class representing gene locus definitions and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("LocusDefinition")`. These objects are used internally by the `chipenrich` package and users will not likely need to create these.

Slots

`dframe`: Object of class "data.frame". Each row represents a locus for a particular geneid.
`granges`: Object of class "GenomicRanges". Locus definitions stored as a GenomicRanges object.
`chrom2iranges`: Object of class "list". List mapping chromosomes to IRanges objects.
`genome.build`: Object of class "character". Genome build these definitions were generated from.
`organism`: Object of class "character". Organism code.

Note

Not typically accessed by the user - this is used internally by the `chipenrich` package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
library(chipenrich.data)

# Show info about the class.
showClass("LocusDefinition");

# Example of what a locus definition object looks like.
data(locusdef.mm9.nearest_tss);
str(locusdef.mm9.nearest_tss);
```

`mappa.hg19.1kb.100mer` *mappa.hg19.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.24mer` *mappa.hg19.1kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.36mer *mappa.hg19.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.40mer` *mappa.hg19.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.50mer` *mappa.hg19.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.1kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.75mer *mappa.hg19.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.100mer` *mappa.hg19.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.24mer` *mappa.hg19.5kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.36mer *mappa.hg19.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.40mer` *mappa.hg19.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.50mer` *mappa.hg19.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.5kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.5kb.75mer` *mappa.hg19.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.exon.100mer`
mappa.hg19.exon.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.exon.24mer` *mappa.hg19.exon.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.36mer *mappa.hg19.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.exon.40mer` *mappa.hg19.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.exon.50mer` *mappa.hg19.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.exon.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.75mer *mappa.hg19.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_gene.100mer  
mappa.hg19.nearest_gene.100mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.hg19.nearest_gene.24mer  
mappa.hg19.nearest_gene.24mer
```

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.36mer

mappa.hg19.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.40mer`
mappa.hg19.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.50mer`
mappa.hg19.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.75mer

mappa.hg19.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_tss.100mer`
mappa.hg19.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_tss.24mer`
mappa.hg19.nearest_tss.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.36mer

mappa.hg19.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_tss.40mer`
mappa.hg19.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_tss.50mer`
mappa.hg19.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.75mer

mappa.hg19.nearest_tss.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.100mer` *mappa.mm9.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.36mer` *mappa.mm9.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.40mer *mappa.mm9.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.50mer` *mappa.mm9.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.50mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.75mer` *mappa.mm9.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.100mer *mappa.mm9.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.36mer` *mappa.mm9.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.36mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.40mer` *mappa.mm9.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.5kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.50mer *mappa.mm9.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.75mer` *mappa.mm9.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.75mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.100mer` *mappa.mm9.exon.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.36mer *mappa.mm9.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.40mer` *mappa.mm9.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.40mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.exon.50mer` *mappa.mm9.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.mm9.exon.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.75mer *mappa.mm9.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.nearest_gene.100mer  
mappa.mm9.nearest_gene.100mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.nearest_gene.36mer  
mappa.mm9.nearest_gene.36mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.40mer

mappa.mm9.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_gene.50mer`
mappa.mm9.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_gene.75mer`
mappa.mm9.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.100mer

mappa.mm9.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_tss.36mer`
mappa.mm9.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.nearest_tss.40mer`
mappa.mm9.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.50mer

mappa.mm9.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
mappa.mm9.nearest_tss.75mer
      mappa.mm9.nearest_tss.75mer
```

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.75mer)
```

Format

A data frame containing:

```
geneid  Entrez Gene IDs
mappa   Gene locus mappability
```

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

```
peaks_E2F4          ChIP-seq Peaks for the E2F4 Transcription Factor
```

Description

A dataset containing the binding locations (peaks) of the transcription factor E2F4 called from a ChIP-seq experiment

Usage

```
peaks_E2F4
```

Format

A data frame containing 16,245 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found in the following publication:

Lee, B. K., A. A. Bhinge, et al. (2011). "Wide-ranging functions of E2F4 in transcriptional activation and repression revealed by genome-wide analysis." *Nucleic Acids Res* 39(9): 3558-3573.

Examples

```
library(chipenrich.data)

# Load E2F4 peak data.
data(peaks_E2F4)

# Print the first 10 peaks in the dataset.
print(head(peaks_E2F4))
```

tss.hg19

tss.hg19

Description

Transcription start site information for hg19.

This is used internally by the chipenrich package.

Usage

```
data(tss.hg19)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

`tss.mm10`*tss.mm10*

Description

Transcription start site information for mm10.
This is used internally by the chipenrich package.

Usage

```
data(tss.mm10)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.
`ranges` A list mapping chromosomes to IRanges objects.
`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

`tss.mm9`*tss.mm9*

Description

Transcription start site information for mm9.
This is used internally by the chipenrich package.

Usage

```
data(tss.mm9)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.
`ranges` A list mapping chromosomes to IRanges objects.
`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

tss.rn4

tss.rn4

Description

Transcription start site information for rn4.

This is used internally by the chipenrich package.

Usage

```
data(tss.rn4)
```

Format

A list containing:

`data` A data frame containing TSSs for each gene.

`ranges` A list mapping chromosomes to IRanges objects.

`granges` TSSs stored as a GenomicRanges object, including strand info.

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

[chipenrich.data](#)

Index

*Topic **classes**

- GeneSet-class, 8
- LocusDefinition-class, 42

*Topic **datasets**

- genes.hsa, 6
- genes.mmu, 7
- genes.rno, 8
- geneset.biocarta_pathway.hsa, 9
- geneset.biocarta_pathway.mmu, 10
- geneset.biocarta_pathway.rno, 10
- geneset.cytoband.hsa, 11
- geneset.drug_bank.hsa, 11
- geneset.drug_bank.mmu, 12
- geneset.drug_bank.rno, 12
- geneset.ehmn_pathway_gene.hsa, 13
- geneset.ehmn_pathway_gene.mmu, 13
- geneset.ehmn_pathway_gene.rno, 14
- geneset.gene_expression.hsa, 14
- geneset.gene_expression.mmu, 15
- geneset.GOBP.hsa, 15
- geneset.GOBP.mmu, 16
- geneset.GOBP.rno, 16
- geneset.GOCC.hsa, 17
- geneset.GOCC.mmu, 17
- geneset.GOCC.rno, 18
- geneset.GOMF.hsa, 18
- geneset.GOMF.mmu, 19
- geneset.GOMF.rno, 19
- geneset.kegg_pathway.hsa, 20
- geneset.kegg_pathway.mmu, 20
- geneset.kegg_pathway.rno, 21
- geneset.mesh.hsa, 21
- geneset.mesh.mmu, 22
- geneset.mesh.rno, 22
- geneset.metabolite.hsa, 23
- geneset.metabolite.mmu, 23
- geneset.metabolite.rno, 24
- geneset.mirbase.hsa, 24
- geneset.mirbase.mmu, 25

- geneset.mirbase.rno, 25
- geneset.omim.hsa, 26
- geneset.omim.mmu, 26
- geneset.omim.rno, 27
- geneset.panther_pathway.hsa, 27
- geneset.panther_pathway.mmu, 28
- geneset.panther_pathway.rno, 28
- geneset.pfam.hsa, 29
- geneset.pfam.mmu, 29
- geneset.pfam.rno, 30
- geneset.protein_interaction_mimi.hsa, 30
- geneset.protein_interaction_mimi.mmu, 31
- geneset.protein_interaction_mimi.rno, 31
- geneset.transcription_factors.hsa, 32
- geneset.transcription_factors.mmu, 32
- geneset.transcription_factors.rno, 33
- locusdef.hg19.1kb, 33
- locusdef.hg19.5kb, 34
- locusdef.hg19.exon, 34
- locusdef.hg19.nearest_gene, 35
- locusdef.hg19.nearest_tss, 35
- locusdef.mm10.1kb, 36
- locusdef.mm10.5kb, 36
- locusdef.mm10.nearest_tss, 37
- locusdef.mm9.1kb, 37
- locusdef.mm9.5kb, 38
- locusdef.mm9.exon, 38
- locusdef.mm9.nearest_gene, 39
- locusdef.mm9.nearest_tss, 39
- locusdef.rn4.1kb, 40
- locusdef.rn4.5kb, 40
- locusdef.rn4.nearest_gene, 41
- locusdef.rn4.nearest_tss, 41

- mappa.hg19.1kb.100mer, [43](#)
 - mappa.hg19.1kb.24mer, [43](#)
 - mappa.hg19.1kb.36mer, [44](#)
 - mappa.hg19.1kb.40mer, [45](#)
 - mappa.hg19.1kb.50mer, [45](#)
 - mappa.hg19.1kb.75mer, [46](#)
 - mappa.hg19.5kb.100mer, [47](#)
 - mappa.hg19.5kb.24mer, [47](#)
 - mappa.hg19.5kb.36mer, [48](#)
 - mappa.hg19.5kb.40mer, [49](#)
 - mappa.hg19.5kb.50mer, [49](#)
 - mappa.hg19.5kb.75mer, [50](#)
 - mappa.hg19.exon.100mer, [51](#)
 - mappa.hg19.exon.24mer, [51](#)
 - mappa.hg19.exon.36mer, [52](#)
 - mappa.hg19.exon.40mer, [53](#)
 - mappa.hg19.exon.50mer, [53](#)
 - mappa.hg19.exon.75mer, [54](#)
 - mappa.hg19.nearest_gene.100mer, [55](#)
 - mappa.hg19.nearest_gene.24mer, [55](#)
 - mappa.hg19.nearest_gene.36mer, [56](#)
 - mappa.hg19.nearest_gene.40mer, [57](#)
 - mappa.hg19.nearest_gene.50mer, [57](#)
 - mappa.hg19.nearest_gene.75mer, [58](#)
 - mappa.hg19.nearest_tss.100mer, [59](#)
 - mappa.hg19.nearest_tss.24mer, [59](#)
 - mappa.hg19.nearest_tss.36mer, [60](#)
 - mappa.hg19.nearest_tss.40mer, [61](#)
 - mappa.hg19.nearest_tss.50mer, [61](#)
 - mappa.hg19.nearest_tss.75mer, [62](#)
 - mappa.mm9.1kb.100mer, [63](#)
 - mappa.mm9.1kb.36mer, [63](#)
 - mappa.mm9.1kb.40mer, [64](#)
 - mappa.mm9.1kb.50mer, [65](#)
 - mappa.mm9.1kb.75mer, [65](#)
 - mappa.mm9.5kb.100mer, [66](#)
 - mappa.mm9.5kb.36mer, [67](#)
 - mappa.mm9.5kb.40mer, [67](#)
 - mappa.mm9.5kb.50mer, [68](#)
 - mappa.mm9.5kb.75mer, [69](#)
 - mappa.mm9.exon.100mer, [69](#)
 - mappa.mm9.exon.36mer, [70](#)
 - mappa.mm9.exon.40mer, [71](#)
 - mappa.mm9.exon.50mer, [71](#)
 - mappa.mm9.exon.75mer, [72](#)
 - mappa.mm9.nearest_gene.100mer, [73](#)
 - mappa.mm9.nearest_gene.36mer, [73](#)
 - mappa.mm9.nearest_gene.40mer, [74](#)
 - mappa.mm9.nearest_gene.50mer, [75](#)
 - mappa.mm9.nearest_gene.75mer, [75](#)
 - mappa.mm9.nearest_tss.100mer, [76](#)
 - mappa.mm9.nearest_tss.36mer, [77](#)
 - mappa.mm9.nearest_tss.40mer, [77](#)
 - mappa.mm9.nearest_tss.50mer, [78](#)
 - mappa.mm9.nearest_tss.75mer, [79](#)
 - peaks_E2F4, [79](#)
 - tss.hg19, [80](#)
 - tss.mm10, [81](#)
 - tss.mm9, [81](#)
 - tss.rn4, [82](#)
- chipenrich.data, [7](#), [8](#), [10–41](#), [43–82](#)
 - chipenrich.data
 - (chipenrich.data-package), [4](#)
 - chipenrich.data-package, [4](#)
 - example_datasets, [5](#), [6](#)
 - genes.hsa, [6](#)
 - genes.mmu, [7](#)
 - genes.rno, [8](#)
 - GeneSet-class, [8](#)
 - geneset.biocarta_pathway.hsa, [9](#)
 - geneset.biocarta_pathway.mmu, [10](#)
 - geneset.biocarta_pathway.rno, [10](#)
 - geneset.cytoband.hsa, [11](#)
 - geneset.drug_bank.hsa, [11](#)
 - geneset.drug_bank.mmu, [12](#)
 - geneset.drug_bank.rno, [12](#)
 - geneset.ehmn_pathway_gene.hsa, [13](#)
 - geneset.ehmn_pathway_gene.mmu, [13](#)
 - geneset.ehmn_pathway_gene.rno, [14](#)
 - geneset.gene_expression.hsa, [14](#)
 - geneset.gene_expression.mmu, [15](#)
 - geneset.GOBP.hsa, [15](#)
 - geneset.GOBP.mmu, [16](#)
 - geneset.GOBP.rno, [16](#)
 - geneset.GOCC.hsa, [17](#)
 - geneset.GOCC.mmu, [17](#)
 - geneset.GOCC.rno, [18](#)
 - geneset.GOMF.hsa, [18](#)
 - geneset.GOMF.mmu, [19](#)
 - geneset.GOMF.rno, [19](#)
 - geneset.kegg_pathway.hsa, [20](#)
 - geneset.kegg_pathway.mmu, [20](#)
 - geneset.kegg_pathway.rno, [21](#)
 - geneset.mesh.hsa, [21](#)

geneset.mesh.mmu, 22
geneset.mesh.rno, 22
geneset.metabolite.hsa, 23
geneset.metabolite.mmu, 23
geneset.metabolite.rno, 24
geneset.mirbase.hsa, 24
geneset.mirbase.mmu, 25
geneset.mirbase.rno, 25
geneset.omim.hsa, 26
geneset.omim.mmu, 26
geneset.omim.rno, 27
geneset.panther_pathway.hsa, 27
geneset.panther_pathway.mmu, 28
geneset.panther_pathway.rno, 28
geneset.pfam.hsa, 29
geneset.pfam.mmu, 29
geneset.pfam.rno, 30
geneset.protein_interaction_mimi.hsa, 30
geneset.protein_interaction_mimi.mmu, 31
geneset.protein_interaction_mimi.rno, 31
geneset.transcription_factors.hsa, 32
geneset.transcription_factors.mmu, 32
geneset.transcription_factors.rno, 33

locusdef.hg19.1kb, 33
locusdef.hg19.5kb, 34
locusdef.hg19.exon, 34
locusdef.hg19.nearest_gene, 35
locusdef.hg19.nearest_tss, 35
locusdef.mm10.1kb, 36
locusdef.mm10.5kb, 36
locusdef.mm10.nearest_tss, 37
locusdef.mm9.1kb, 37
locusdef.mm9.5kb, 38
locusdef.mm9.exon, 38
locusdef.mm9.nearest_gene, 39
locusdef.mm9.nearest_tss, 39
locusdef.rn4.1kb, 40
locusdef.rn4.5kb, 40
locusdef.rn4.nearest_gene, 41
locusdef.rn4.nearest_tss, 41
LocusDefinition-class, 42

mappa.hg19.1kb.100mer, 43
mappa.hg19.1kb.24mer, 43
mappa.hg19.1kb.36mer, 44
mappa.hg19.1kb.40mer, 45
mappa.hg19.1kb.50mer, 45
mappa.hg19.1kb.75mer, 46
mappa.hg19.5kb.100mer, 47
mappa.hg19.5kb.24mer, 47
mappa.hg19.5kb.36mer, 48
mappa.hg19.5kb.40mer, 49
mappa.hg19.5kb.50mer, 49
mappa.hg19.5kb.75mer, 50
mappa.hg19.exon.100mer, 51
mappa.hg19.exon.24mer, 51
mappa.hg19.exon.36mer, 52
mappa.hg19.exon.40mer, 53
mappa.hg19.exon.50mer, 53
mappa.hg19.exon.75mer, 54
mappa.hg19.nearest_gene.100mer, 55
mappa.hg19.nearest_gene.24mer, 55
mappa.hg19.nearest_gene.36mer, 56
mappa.hg19.nearest_gene.40mer, 57
mappa.hg19.nearest_gene.50mer, 57
mappa.hg19.nearest_gene.75mer, 58
mappa.hg19.nearest_tss.100mer, 59
mappa.hg19.nearest_tss.24mer, 59
mappa.hg19.nearest_tss.36mer, 60
mappa.hg19.nearest_tss.40mer, 61
mappa.hg19.nearest_tss.50mer, 61
mappa.hg19.nearest_tss.75mer, 62
mappa.mm9.1kb.100mer, 63
mappa.mm9.1kb.36mer, 63
mappa.mm9.1kb.40mer, 64
mappa.mm9.1kb.50mer, 65
mappa.mm9.1kb.75mer, 65
mappa.mm9.5kb.100mer, 66
mappa.mm9.5kb.36mer, 67
mappa.mm9.5kb.40mer, 67
mappa.mm9.5kb.50mer, 68
mappa.mm9.5kb.75mer, 69
mappa.mm9.exon.100mer, 69
mappa.mm9.exon.36mer, 70
mappa.mm9.exon.40mer, 71
mappa.mm9.exon.50mer, 71
mappa.mm9.exon.75mer, 72
mappa.mm9.nearest_gene.100mer, 73
mappa.mm9.nearest_gene.36mer, 73
mappa.mm9.nearest_gene.40mer, 74
mappa.mm9.nearest_gene.50mer, 75
mappa.mm9.nearest_gene.75mer, 75
mappa.mm9.nearest_tss.100mer, 76

mappa.mm9.nearest_tss.36mer, [77](#)
mappa.mm9.nearest_tss.40mer, [77](#)
mappa.mm9.nearest_tss.50mer, [78](#)
mappa.mm9.nearest_tss.75mer, [79](#)

peaks_E2F4, [79](#)

tss.hg19, [80](#)
tss.mm10, [81](#)
tss.mm9, [81](#)
tss.rn4, [82](#)