

# Package ‘AffyRNADegradation’

October 7, 2014

**Type** Package

**Title** Analyze and correct probe positional bias in microarray data due to RNA degradation

**Version** 1.10.0

**Date** 2012-09-26

**Depends** R (>= 2.9.0), methods, affy

**Suggests** AmpAffyExample

**Author** Mario Fasold

**Maintainer** Mario Fasold <fasold@izbi.uni-leipzig.de>

**Description** The package helps with the assessment and correction of RNA degradation effects in Affymetrix 3' expression arrays. The parameter `d` gives a robust and accurate measure of RNA integrity. The correction removes the probe positional bias, and thus improves comparability of samples that are affected by RNA degradation.

**License** GPL-2

**Collate** AllClasses.R decayFunction.R AffyRNADegradation.R probeInfo.R tongs.R

**biocViews** GeneExpression, Microarray, OneChannel, Preprocessing, QualityControl

## R topics documented:

AffyDegradationBatch-class	2
AffyRNADegradation	3
GetTongs	4
RNADegradation	5

<b>Index</b>	<b>7</b>
--------------	----------

---

AffyDegradationBatch-class

*Class AffyDegradationBatch*

---

## Description

This class represents Affymetrix GeneChip probe level data that has been analysed and corrected for the probe location bias.

## Objects from the Class

Objects can be created using the function `RNADegradation`.

## Slots

`location.type`: Object of class `character` describing the type of probe position used for the analysis (probe index or probe location).

`afbatch`: Object of class `AffyBatch` containing corrected probe level data.

`stats`: Object of class `matrix` containing various statistical parameters from the analysis.

`means.pm`: Object of class `matrix` containing the average PM probe intensities for probe locations of expressed genes.

`means.mm`: Object of class `matrix` containing the average MM probe intensities for probe locations of expressed genes.

## Methods

**afbatch** `signature(x = "AffyDegradationBatch")`: returns as `AffyBatch` object containing corrected probe level data.

**d** `signature(x = "AffyDegradationBatch")`: returns a vector with a measure of RNA degradation for each sample

**plotDx** `signature(x = "AffyDegradationBatch")`: plots the probe location bias for all samples of the experiment.

## Author(s)

Mario Fasold

## See Also

`AffyBatch`

**Examples**

```
if (require(AmpAffyExample)) {  
  # Get example data  
  data(AmpData)  
  
  affy.deg <- RNADegradation(AmpData[,4])  
  
  ## Plot degradation  
  plotDx(affy.deg)  
  
  ## Get degradation measure  
  d(affy.deg)  
  
  ## Get AffyBatch object with corrected probe intensities  
  afbatch(affy.deg)  
}
```

---

AffyRNADegradation      *AffyRNADegradation: analyze and correct RNA degradation effects*

---

**Description**

The AffyRNADegradation package helps in the assessment of RNA degradation effects in Affymetrix 3' expression arrays. The parameter `d` gives a robust and accurate measure of RNA integrity. The correction removes the probe positional bias, and thus improves comparability of samples that are affected by RNA degradation.

**Details**

Package: AffyRNADegradation  
Type: Package  
Version: 0.1.0  
Date: 2011-10-13  
License: GPL >=2

The RNADegradation function performs both analysis and correction of RNA degradation effects, returning an object of type `AffyDegradationBatch`. The class provides accessor functions to obtain the degradation parameter `d` and a `AffyBatch` object containing corrected probe intensities. A more detailed look on the RNA degradation effects can be gained through the `tongs` plot, the `Dx` plot and further statistics.

**Author(s)**

Mario Fasold

## Examples

```
if (require(AmpAffyExample)) {  
  # Load example data (AmpData affybatch)  
  data(AmpData)  
  
  ## Compute and correct degradation for a single chip (for speed)  
  affy.deg <- RNADegradation(AmpData[,4])  
  
  ## Show degradation parameter d  
  d(affy.deg)  
  
  ## Replace data with corrected data for further analysis  
  AmpData <- abatch(affy.deg)  
}
```

---

GetTongs

*Generate and visualize the tongs plot*

---

## Description

The tongs plot and the related degradation hook show the relationship between expression level and probe location bias. They are required for the correct estimation of RNA degradation effects.

## Usage

```
GetTongs(affyData, chip.idx = 1)  
PlotTongs(tongs)  
PlotDegradationHooks(affyData, ...)
```

## Arguments

<code>affyData</code>	an AffyBatch object.
<code>chip.idx</code>	index of the sample to compute the tongs for.
<code>tongs</code>	the tongs plot data table.
<code>...</code>	optional graphical parameters.

## Value

<code>Tongs</code>	a table containing Tongs plot values ordered by expression level.
--------------------	---

## Author(s)

Mario Fasold

**Examples**

```
if (require(AmpAffyExample)) {  
  # Get example data  
  data(AmpData)  
  
  tongs <- GetTongs(AmpData, chip.idx = 4)  
  PlotTongs(tongs)  
  
  PlotDegradationHooks(AmpData[,c(3,4)])  
}
```

---

RNADegradation

*Compute degradation parameters and correct probe intensities*

---

**Description**

Given an AffyBatch object, the function RNADegradation computes the probe positional bias and several statistical parameters, including a robust and accurate measure of RNA degradation. Probe intensities are corrected for the bias for each sample within the AffyBatch object.

**Usage**

```
RNADegradation(affyData,  
               location.type = "index",  
               location.file.dir = NULL,  
               plot.images = FALSE)
```

**Arguments**

`affyData` an AffyBatch object containing the probe level microarray data.

`location.type` index-based probe alignment (x=k) if "index", or location-based alignment (x=L) if "absolute".

`location.file.dir` directory containing the probe location file(s).

`plot.images` if TRUE plots a set of debug images.

**Value**

An AffyDegradationBatch object.

**Author(s)**

Mario Fasold

**See Also**

AffyDegradationBatch

**Examples**

```
if (require(AmpAffyExample)) {  
  # Get example data  
  data(AmpData)  
  
  affy.deg <- RNADegradation(AmpData[,4])  
}
```

# Index

## \*Topic **classes**

AffyDegradationBatch-class, [2](#)

## \*Topic **methods**

GetTongs, [4](#)

RNADegradation, [5](#)

## \*Topic **package**

AffyRNADegradation, [3](#)

afbatch (AffyDegradationBatch-class), [2](#)

afbatch, AffyDegradationBatch-method  
(AffyDegradationBatch-class), [2](#)

AffyDegradationBatch  
(AffyDegradationBatch-class), [2](#)

AffyDegradationBatch, ANY  
(AffyDegradationBatch-class), [2](#)

AffyDegradationBatch-class, [2](#)

AffyRNADegradation, [3](#)

AffyRNADegradation-package  
(AffyRNADegradation), [3](#)

d (AffyDegradationBatch-class), [2](#)

d, AffyDegradationBatch-method  
(AffyDegradationBatch-class), [2](#)

GetTongs, [4](#)

PlotDegradationHooks (GetTongs), [4](#)

plotDx (AffyDegradationBatch-class), [2](#)

plotDx, AffyDegradationBatch-method  
(AffyDegradationBatch-class), [2](#)

PlotTongs (GetTongs), [4](#)

RNADegradation, [5](#)