

Package ‘a4Preproc’

April 9, 2015

Type Package

Title Automated Affymetrix Array Analysis Preprocessing Package

Version 1.14.0

Date 2011-04-07

Author Willem Talloen, Tobias Verbeke

Maintainer Tobias Verbeke <tobias.verbeke@openanalytics.eu>, Willem
Ligtenberg <willem.ligtenberg@openanalytics.eu>

Description Automated Affymetrix Array Analysis Preprocessing Package

Depends methods, AnnotationDbi

Suggests ALL, hgu95av2.db

License GPL-3

biocViews Microarray

R topics documented:

addGeneInfo 1

Index 3

addGeneInfo *Utility Function to Add Annotation to existing ExpressionSet Objects*

Description

Adds appropriate featureData, similar to the metadata added in the pipeline script, to the ExpressionSet object.

Usage

```
addGeneInfo(eset, annotationLibrary = NULL)
```

Arguments

`eset` ExpressionSet object for to which one wants to add additional annotation information

`annotationLibrary` Annotation Library to use. Must be specified when working with Entrez gene IDs. In this case, one can make use of the JnJ annotation packages such as `hgu133plus2hsentrezgJnJ`. If not specified, the annotation of the package will be automatically requested with `annotation()` of the expressionSet object `eset` and then Affymetrix probe set IDs are expected in `featureNames`

Details

Slots of `featureData(a4ALL)` are

- `Entrez ID~`: Entrez ID as retrieved from annotation package
- `Ensembl ID~`: Ensembl ID as retrieved from annotation package
- `Gene Symbol~`: Gene symbol as retrieved from annotation package
- `Description~`: Description as retrieved from annotation package

Value

a new ExpressionSet object with the additional information stored as feature data

Note

One should always use subscripting of `featureData` by column name (e.g. `featureData(a4ALL)$Entrez ID`); as the pipeline ExpressionSets have one additional column compared to the ExpressionSet objects produced by `addGeneInfo`, i.e. column 2 of the pipeline ExpressionSets corresponds to column one of an `addGeneInfo` ExpressionSet.

Author(s)

Tobias Verbeke, Steven Osselaer

Examples

```
library(ALL)
data(ALL)
a4ALL <- addGeneInfo(ALL)
head(featureData(a4ALL)$Entrez ID)
```

Index

*Topic **manip**

addGeneInfo, 1

addGeneInfo, 1