

Package ‘sparsenetgls’

April 15, 2020

Type Package

Title Using Gaussian graphical structure learning estimation in generalized least squared regression for multivariate normal regression

Version 1.4.0

Maintainer Irene Zeng <i.zeng@auckland.ac.nz>

Description The package provides methods of combining the graph structure learning and generalized least squares regression to improve the regression estimation. The main function `sparsenetgls()` provides solutions for multivariate regression with Gaussian distributed dependent variables and explanatory variables utilizing multiple well-known graph structure learning approaches to estimating the precision matrix, and uses a penalized variance covariance matrix with a distance tuning parameter of the graph structure in deriving the sandwich estimators in generalized least squares (gls) regression. This package also provides functions for assessing a Gaussian graphical model which uses the penalized approach. It uses Receiver Operative Characteristics curve as a visualization tool in the assessment.

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0), Matrix, MASS

Imports methods, glmnet, parcor, huge, stats, graphics, utils

Suggests testthat, lme4, BiocStyle, knitr, rmarkdown, roxygen2 (>= 5.0.0)

NeedsCompilation no

URL

RoxygenNote 6.0.1

biocViews ImmunoOncology,

GraphAndNetwork,Regression,Metabolomics,CopyNumberVariation,MassSpectrometry,Proteomics,Software,Visuali

bugReport <https://github.com/superOmics/sparsenetgls/issues>

VignetteBuilder knitr

SystemRequirements GNU make

git_url <https://git.bioconductor.org/packages/sparsenetgls>

git_branch RELEASE_3_10

git_last_commit 12e5920

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

Author Irene Zeng [aut, cre],
Thomas Lumley [ctb]

R topics documented:

assess_direct	2
bandprec	3
convertbeta	5
glassonet2	5
lassoglmnet	6
path_result_for_roc	7
plotsngls	8
plot_roc	9
sparsenetgls	10

Index	12
--------------	-----------

assess_direct	<i>The assess_direct() function</i>
---------------	-------------------------------------

Description

The assess_direct function is designed to produce the prediction accuracy of a Gaussian Graphical model(GGM) to the true graph structure with a known precision matrix.

Usage

```
assess_direct(PREC_for_graph, OMEGA_for_graph, p)
```

Arguments

PREC_for_graph It is the known precision matrix which is used to assess the estimated precision matrix from GGM.

OMEGA_for_graph It is the estimated precision matrix from a GGM.

p It is an integer representing the number of dimension of both the known and estimated precision matrix.

Value

Return the list of assessment results including sensitivity, specificity, NPV(test negative), PPV(test positive), true positive and true negative.

Examples

```
prec1 <- matrix(c(0,2,3,1,0,0.5,0,0,0.4),nrow=3,ncol=3)
prec0 <- matrix(c(0,1,2,1,0.5,0.2,0,1,1),nrow=3,ncol=3)

assessresult <- assess_direct(prec1,prec0,p=3)
```

bandprec

bandprec data for vignette

Description

bandprec and bandvar store the precision matrix and variance covariance matrix with the band diagonal structure.

Usage

```
data("bandprec")
```

Format

A data frame with 50 observations on the following 50 variables.

V1 a numeric vector
V2 a numeric vector
V3 a numeric vector
V4 a numeric vector
V5 a numeric vector
V6 a numeric vector
V7 a numeric vector
V8 a numeric vector
V9 a numeric vector
V10 a numeric vector
V11 a numeric vector
V12 a numeric vector
V13 a numeric vector
V14 a numeric vector
V15 a numeric vector
V16 a numeric vector
V17 a numeric vector
V18 a numeric vector
V19 a numeric vector
V20 a numeric vector
V21 a numeric vector
V22 a numeric vector

V23 a numeric vector
V24 a numeric vector
V25 a numeric vector
V26 a numeric vector
V27 a numeric vector
V28 a numeric vector
V29 a numeric vector
V30 a numeric vector
V31 a numeric vector
V32 a numeric vector
V33 a numeric vector
V34 a numeric vector
V35 a numeric vector
V36 a numeric vector
V37 a numeric vector
V38 a numeric vector
V39 a numeric vector
V40 a numeric vector
V41 a numeric vector
V42 a numeric vector
V43 a numeric vector
V44 a numeric vector
V45 a numeric vector
V46 a numeric vector
V47 a numeric vector
V48 a numeric vector
V49 a numeric vector
V50 a numeric vector

Examples

```
data(bandprec)  
## maybe str(bandprec) ; plot(bandprec) ...
```

convertbeta	<i>The convertbeta() function</i>
-------------	-----------------------------------

Description

The convertbeta function is designed to convert the regression coefficients derived from the standardized data.

Usage

```
convertbeta(X, Y, q, beta0)
```

Arguments

X	It is a dataset of explanatory variables.
Y	It is the multivariate response variables.
q	It is an integer representing the number of explanatory variables.
beta0	The vector contains the regression coefficients from sparsenetgls.

Value

Return the list of converted regression coefficients of the explanatory variables 'betaconv' and intercept value 'betaconv_int'.

Examples

```
X <- mvrnorm(n=20,mu=rep(0,5),Sigma=Diagonal(5,rep(1,5)))
Y <- mvrnorm(n=20,mu=rep(0.5,10),Sigma=Diagonal(10,rep(1,10)))
fitmodel <- sparsenetgls(responsetdata=Y,predictdata=X,nlambda=5,ndist=2,
method='elastic')
convertbeta(X=X,Y=Y,q=5+1,beta0=fitmodel$beta[,1])
```

glassonet2	<i>The glassonet2() function</i>
------------	----------------------------------

Description

The glassonet2 function is designed to learn the graph structure and the corresponding precision matrix and covariance matrix by using the graph lasso method.

Usage

```
glassonet2(Y0, nlambda = nlambda, lambda.min.ratio = 0.001, method)
```

Arguments

<code>Y0</code>	The data matrix for the GGM model.
<code>nlambda</code>	The number of interval used in the penalized path in lasso and elastics. It results in the number of lambda values to be used in the penalization. The default value is <code>nlambda</code> assigned in the parent function <code>sparsenetglis()</code> .
<code>lambda.min.ratio</code>	It is the default parameter set in function <code>huge()</code> in the package 'huge'. Quoted from <code>huge()</code> , it is the minial value of lambda, being a fraction of the upperbound (MAX) of the regularization/thresholding parameter that makes all the estimates equal to 0. The default value is 0.001.
<code>method</code>	There are two options for the method parameter which is provided in the <code>huge()</code> function. One is 'glasso' and the other one is 'mb'.

Value

Return the precision matrix 'OMEGAMATRIX', penalized path parameter lambda 'lambda' and covariance matrix 'COVMATRIX'.

Examples

```
n=20
VARknown <- rWishart(1, df=4, Sigma=matrix(c(1,0,0,0,1,0,0,0,1),
nrow=3,ncol=3))
Y0 <- mvrnorm(n=n,mu=rep(0.5,3),Sigma=VARknown[, ,1])
fitglasso <- glassonet2(Y0=Y0,nlambda=5,method='glasso')
```

lassoglmnet

The lassoglmnet() function

Description

The `lassoglmnet` function is designed to learn the graph structure by using the lasso and elastics net method.

Usage

```
lassoglmnet(Y0, nlambda = 10, alpha)
```

Arguments

<code>Y0</code>	The data matrix for the GGM model.
<code>nlambda</code>	The number of interval used in the penalized path in lasso and elastics. It results in the number of lambda values to be used in the penalization. The default value is 10.
<code>alpha</code>	The vaule to be used in enet, it has values betwee 0 and 1. The value of 0 is corresponding to l-1 penalization, and 1 is corresponding to the l-2 regularization (Ridge regression). The other values between 0 and 1 will result in a combination of l1-l2 norm regularization named as elastic net.

Value

Return the regression coefficients of glmnet 'coef_glmnet', residuals from the glmnet 'resid_glmnet' and lambda.

Examples

```
n=20
VARknown <- rWishart(1,df=4,Sigma=matrix(c(1,0,0,0,1,0,0,0,1),nrow=3,ncol=3))
Y0 <- mvrnorm(n=n,mu=rep(0.5,3),Sigma=VARknown[, ,1])
fitlasso <- lassoglmnet(Y0=Y0,alpha=0.5)
```

path_result_for_roc *The path_result_for_roc() function*

Description

The path_result_for_roc function is designed to produce the Receiver Operative Characteristics (ROC) Curve for visualizing the prediction accuracy of a Gaussian Graphical model (GGM) to the true graph structure. The GGM must use a l-p norm regularizations ($p=1,2$) with the series of solutions conditional on the regularization parameter.

Usage

```
path_result_for_roc(PREC_for_graph, OMEGA_path, pathnumber)
```

Arguments

PREC_for_graph	It is the known precision matrix which is used to assess the estimated precision matrix from GGM.
OMEGA_path	It is an estimated precision matrix from a GGM model using the penalized path with a range of values (i.e. $\lambda, \in [0, 1]$).
pathnumber	It represents the number of values (i.e. λ) used in the penalized GGM. This will result in the number of co-ordinates used to form the ROC curve.

Value

Return the list of assessment results for a serie of precision matrices. The results include sensitivity/specificity/NPV/PPV

Examples

```
prec1 <- matrix(c(0,2,3,1,0,0.5,0,0,0.4),nrow=3,ncol=3)
Omega_est <- array(dim=c(3,3,3))
Omega_est[, ,1] <- matrix(c(0,1,2,1,0.5,0.2,0,1,1),nrow=3,ncol=3)
Omega_est[, ,2] <- matrix(c(0,1,0,1,0.5,0.2,0,1,1),nrow=3,ncol=3)
Omega_est[, ,3] <- matrix(c(0,1,0,1,0,0.2,0,1,1),nrow=3,ncol=3)
rocpath <- path_result_for_roc(PREC_for_graph=prec1,OMEGA_path=Omega_est,
pathnumber=3)
```

plotsngls

*The plotsngls() function***Description**

The plotsngls function is designed to provide the line plots of penalized parameter lambda and variance of regression coefficients in gls regression. It also provides the graph structure of the solution to the precision matrix in the penalized path.

Usage

```
plotsngls(fitgls, lineplot = FALSE, nrow, ncol, structplot = TRUE,
ith_lambda = 1)
```

Arguments

fitgls	It is a returning object of the sparsenetgls() multivariate generalized least squared regression function.
lineplot	It is a logical indicator. When value=TRUE, it will provide line plot.
nrow	It is a graph parameter representing number of rows in the lineplot.
ncol	It is a graph parameter representing number of columns in the lineplot.
structplot	It is a logical indicator. When value=TRUE, it will provide the structure plot of the specified precision matrix from the series of the sparsenetgls results.
ith_lambda	It is the number for the specified precision matrix to be used in the structplot. It represents the ordering number in the precision matrix series from sparsenetgls.

Value

Return a plot subject for sparsenetgls including the plot of variance vs lambda and graph structure of the precision matrix estimates.

Examples

```
ndox=5;p=3;n=200
VARknown <- rWishart(1, df=4, Sigma=matrix(c(1,0,0,0,1,0,0,0,1),
nrow=3,ncol=3))
normc <- mvnorm(n=n,mu=rep(0,p),Sigma=VARknown[, , 1])
Y0=normc
##u-beta
u <- rep(1,ndox)
X <- mvnorm(n=n,mu=rep(0,ndox),Sigma=Diagonal(ndox,rep(1,ndox)))
X00 <- scale(X,center=TRUE,scale=TRUE)
X0 <- cbind(rep(1,n),X00)
#Add predictors of simulated CNA
abundance1 <- scale(Y0,center=TRUE,scale=TRUE)+as.vector(X00%*%as.matrix(u))

##sparsenetgls()
fitgls <- sparsenetgls(responedata=abundance1,predictdata=X00,
nlambda=5,ndist=4,method='glasso')
plotsngls(fitgls, ith_lambda=5)
#plotsngls(fitgls,lineplot=TRUE,structplot=FALSE,nrow=2,ncol=3)
```

plot_roc	<i>The plot_roc() function</i>
----------	--------------------------------

Description

The `plot_roc` function is designed to produce the Receiver Operative Characteristics (ROC) Curve for visualizing the prediction accuracy of a Gaussian Graphical model (GGM) to the true graph structure. The GGM must use a l-p norm regularizations ($p=1,2$) with the series of solutions conditional on the regularization parameter.

Usage

```
plot_roc(result_assessment, group = TRUE, ngroup = 0, est_names)
```

Arguments

<code>result_assessment</code>	It is the list result from function <code>path_result_for_roc()</code> which has five-dimensions recording the path number (i.e. the order of λ), the sensitivity, the specificity, the Negative predicted value (NPV) and the Positive predicted value (PPV) respectively.
<code>group</code>	It is a logical parameter indicating if the <code>result_assessment</code> is for several GGM models. When it is <code>TRUE</code> , it produces the ROC from several GGM models. when it is <code>FALSE</code> , it only produces a ROC for one model.
<code>ngroup</code>	It is an integer recording the number of models when <code>group</code> is <code>TRUE</code> .
<code>est_names</code>	it is used for labeling the GGM model in legend of ROC curve.

Value

Return the plot of Receiver Operational Curve

Examples

```
prec1 <- matrix(c(0,2,3,1,0,0.5,0,0,0.4),nrow=3,ncol=3)
Omega_est <- array(dim=c(3,3,3))
Omega_est[, ,1] <- matrix(c(1,1,1,0.2,0.5,0.2,2,0.2,0.3),nrow=3,ncol=3)
Omega_est[, ,2] <- matrix(c(0,1,1,1,0,0,0,0,1),nrow=3,ncol=3)
Omega_est[, ,3] <- matrix(c(0,0,0,0,0,0,0,0,0),nrow=3,ncol=3)
roc_path_result <- path_result_for_roc(PREC_for_graph=prec1,
OMEGA_path=Omega_est,pathnumber=3)
plot_roc(result_assessment=roc_path_result,group=FALSE,ngroup=0,
est_names='test example')
```

 sparsenetgls

The sparsenetgls() function

Description

The sparsenetgls function is a combination of the graph structure learning and generalized least square regression. It is designed for multivariate regression uses penalized and/or regularised approach to deriving the precision and covariance Matrix of the multivariate Gaussian distributed responses. Gaussian Graphical model is used to learn the structure of the graph and construct the precision and covariance matrix. Generalized least squared regression is used to derive the sandwich estimation of variances-covariance matrix for the regression coefficients of the explanatory variables, conditional on the solutions of the precision and covariance matrix.

Usage

```
sparsenetgls(responsetdata, predictdata, nlambda = 10, ndist = 5,
method = c("lasso", "glasso", "elastic", "mb"), lambda.min.ratio = 1e-05)
```

Arguments

- | | |
|------------------|---|
| responsetdata | It is a data matrix of multivariate normal distributed response variables. Each row represents one observation sample and each column represents one variable. |
| predictdata | It is a data matrix of explanatory variables and has the same number of rows as the response data. |
| nlambda | It is an interger recording the number of lambda value used in the penalized path for estimating the precision matrix. The default value is 10. |
| ndist | It is an interger recording the number of distant value used in the penalized path for estimating the covariance matrix. The default value is 5. |
| method | It is the option parameter for selecting the penalized method to derive the precision matrix in the calculation of the sandwich estimator of regression coefficients and their variance-covariance matrix. The options are 'glasso', 'lasso', 'elastic', and 'mb'. 'glasso' use the graphical lasso method documented in Yuan and Lin (2007) and Friedman, Hastie et al (2007). It used the imported function from R package 'huge'. 'lasso' use the penalized liner regression among the response variables ($Y_{[j]} \sim Y_{[1]} + \dots + Y_{[j-1]} + Y_{[j+1]} + \dots + Y_{[p]}$) to estimate the precision matrix. 'elastic' uses the enet-regularized linear regression among the response variables to estimate the precision matrix. Both of these methods utilize the coordinate descending algorithm documentd in Friedman, J., Hastie, T. and Tibshirani, R. (2008) and use the imported function from R package 'glmnet'. 'mb' use the Meinshausen and Buhlmann penalized linear regression and the neighbourhood selection with the lasso approach (2006) to select the covariance terms and derive the corresponding precision matrix ; It uses the imported function from 'huge' in function sparsenetgls(). |
| lambda.min.ratio | It is the default parameter set in function huge() in the package 'huge'. Quoted from huge(), it is the minial value of lambda, being a fraction of the upperbound (MAX) of the regularization/thresholding parameter that makes all the estimates equal to 0. The default value is 0.001. It is only applicable when 'glasso' and 'mb' method is used. |

Value

Return the list of regression results including the regression coefficients, array of variance-covariance matrix for different lambda and distance values, lambda and distance (power) values, bic and aic for model fitting, and the list of precision matrices on the penalized path.

Examples

```

ndox=5; p=3; n=1000
VARknown <- rWishart(1, df=4, Sigma=matrix(c(1,0,0,0,1,0,0,0,1),
nrow=3,ncol=3))
normc <- mvrnorm(n=n,mu=rep(0,p),Sigma=VARknown[, ,1])
Y0=normc
##u-beta
u <- rep(1,ndox)
X <- mvrnorm(n=n,mu=rep(0,ndox),Sigma=Diagonal(ndox,rep(1,ndox)))
X00 <- scale(X,center=TRUE,scale=TRUE)
X0 <- cbind(rep(1,n),X00)
#Add predictors of simulated CNA
abundance1 <- scale(Y0,center=TRUE,scale=TRUE)+as.vector(X00%*%as.matrix(u))

##sparsenetgls()
fitgls <- sparsenetgls(responsetdata=abundance1,predictdata=X00,
nlambda=5,ndist=2,method='glasso')
nlambda=5
##rescale regression coefficients from sparsenetgls
#betagls <- matrix(nrow=nlambda, ncol=ndox+1)
#for (i in seq_len(nlambda))
#betagls[i,] <- convertbeta(Y=abundance1, X=X00, q=ndox+1,
#beta0=fitgls$beta[,i])$betaconv

```

Index

*Topic **datasets**

bandprec, [3](#)

assess_direct, [2](#)

bandprec, [3](#)

convertbeta, [5](#)

glassonet2, [5](#)

lassoglmnet, [6](#)

path_result_for_roc, [7](#)

plot_roc, [9](#)

plotsngls, [8](#)

sparsenetgls, [10](#)