

Package ‘epivizr’

April 23, 2016

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

Author Hector Corrada Bravo, Florin Chelaru, Llewellyn Smith, Naomi Goldstein

Version 1.8.1

License Artistic-2.0

Title R Interface to epiviz web app

Description This package provides Websocket communication to the epiviz web app (<http://epiviz.cbcb.umd.edu>) for interactive visualization of genomic data. Objects in R/bioc interactive sessions can be displayed in genome browser tracks or plots to be explored by navigation through genomic regions. Fundamental Bioconductor data structures are supported (e.g., GenomicRanges and RangedSummarizedExperiment objects), while providing an easy mechanism to support other data structures. Visualizations (using d3.js) can be easily added to the web app as well.

VignetteBuilder knitr

Depends R (>= 3.0.1), methods, Biobase, SummarizedExperiment (>= 0.2.0), rtracklayer

Imports S4Vectors, httpuv (>= 1.3.0), rjson, OrganismDbi, R6 (>= 2.0.0), mime (>= 0.2), GenomeInfoDb, GenomicRanges, GenomicFeatures

Suggests testthat, roxygen2, knitr, antiProfilesData, hgu133plus2.db, knitrBootstrap, Mus.musculus

Collate 'utils.r' 'middleware-plus-supporting.R'
'EpivizServer-class.R' 'EpivizDeviceMgr-class.R'
'startEpiviz.R' 'startStandalone.R' 'EpivizData-class.R'
'EpivizTrackData-class.R' 'EpivizFeatureData-class.R'
'EpivizBlockData-class.R' 'EpivizBpData-class.R'
'EpivizGeneInfoData-class.R' 'makeGeneTrackAnnotation.R'
'EpivizDataCache-class.R' 'EpivizWigCache-class.R'
'EpivizWigData-class.R' 'register-methods.R'
'EpivizChart-class.R' 'EpivizDevice-class.R' 'zzz.R'

biocViews Visualization, Infrastructure, GUI

Video <https://www.youtube.com/watch?v=099c4wUxoZA>

NeedsCompilation no

R topics documented:

EpivizBlockData-class	2
EpivizBpData-class	3
EpivizChart-class	3
EpivizData-class	4
EpivizDataCache-class	5
EpivizDevice-class	6
EpivizDeviceMgr-class	7
EpivizFeatureData-class	11
EpivizGeneInfoData-class	12
EpivizServer-class	13
EpivizTrackData-class	14
EpivizWigCache-class	15
EpivizWigData-class	15
IndexedArray-class	16
makeGeneTrackAnnotation	16
Queue-class	17
register-methods	18
startEpiviz	20
startStandalone	21
tcga_colon_example	22
tcga_colon_expression	23
Index	25

EpivizBlockData-class *'EpivizBlockData' objects*

Description

Data displayed only as genomic regions (no quantitative data)

Details

This class extends [EpivizTrackData-class](#). Like its super-class, the data containing object is constrained to be of class [GIntervalTree](#). Its columns field is constrained to be NULL.

Methods

`plot()`: Calls the `blockChart` method of [EpivizDeviceMgr-class](#).

`getMeasurements()`: Returns a list describing data encapsulated by this object.

`parseMeasurement(msId=NULL)`: Checks `msId==id`.

Author(s)

Hector Corrada Bravo

EpivizBpData-class *'EpivizBpData' objects*

Description

Base-pair resolution quantitative data.

Details

This class extends [EpivizTrackData-class](#) directly. As such, its object field is constrained to contain a [GIntervalTree](#) object. Quantitative data for each genomic position is assumed to be stored in the elementMetadata slot of object.

Methods

.checkColumns(columns): Checks argument columns is a subset of names(mcols(object)).
.getColumns(): Returns names(mcols(object)).
plot(): Calls the lineChart method of [EpivizDeviceMgr-class](#) with columns as argument.
getMeasurements(): Returns a list describing data encapsulated by this object.

Author(s)

Hector Corrada Bravo

EpivizChart-class *'EpivizChart' objects*

Description

Encapsulate information about charts added to web app.

Fields

measurements: List describing measurements displayed in chart.
id: (character) id assigned by session manager to chart. Use getId method to get id.
mgr: ([EpivizDeviceMgr](#)) session manager object.
inDevice: (logical) TRUE if chart is defined within an [EpivizDevice-class](#) object.
type: (character) chart type.

Methods

setId(id):set id. Internal use only.
 getId():get id.
 setInDevice(x):set inDevice field. Internal use only.

Author(s)

Hector Corrada Bravo

EpivizData-class *'EpivizData' objects*

Description

This class serves as the basis for the epiviz data container class hierarchy.

Details

Objects of classes derived from this class define measurements in the measurement/chart design behind epiviz. Subclasses extended from this class correspond to specific data types, and are responsible for packaging data for display in the epiviz web app. In principle, each subclass corresponds to a data type in the epiviz JS framework. Use the listTypes method of [EpivizDeviceMgr-class](#) to see the R-JS class correspondence. This virtual class implements common functionality for subclass objects. Objects in this class hierarchy are created using link{register-methods}.

Fields

object: The data containing object
mgr: The epiviz session manager (object of class [EpivizDeviceMgr-class](#))
inDevice: (logical) TRUE if object defined in a [EpivizDevice-class](#) object.
id: (character) the measurement object id determined by the session manager. Use getId method to get this field.
name: (character) the measurement object name. Measurements declared by the object are given names derived from this field. Use getName method to get this field.
columns: (character vector) the names of the columns containing measurements encapsulated by this object.
ylim: (numeric matrix) data range for measurements encapsulated by this object. These are passed to the web app to determine plot ranges.
curQuery: (GRanges object) last query made to this object.
curHits: (integer) indexes returned by last query to this object.

Methods

Below, methods tagged as 'VIRTUAL' must be implemented by subclasses.

.checkColumns(columns): Check if argument columns is valid for data object. 'VIRTUAL'.

.getColumns(): Infer a valid set of columns from data object. 'VIRTUAL'.

.checkLimits(yLim): Check if argument yLim is valid for data object. 'VIRTUAL'.

.getLimits(): Infer a valid set of yLim from data object. 'VIRTUAL'.

update(newObject, sendRequest=TRUE): updates data object to argument newObject. This method checks that the classes of newObject and the current object are the same, that the columns field is valid for newObject and updates the yLim field using the .getLimits method. If sendRequest==TRUE the web app is refreshed to reflect the data in newObject.

getId(): Get the object's id.

setId(id): Set the object's id. For internal use only.

getName(): Get the object's name.

setName(name): Set the object's name. For internal use only.

setLimits(yLim): Set the object's yLim field. Argument is checked using the .checkLimits method.

getMeasurements(): Get the object's encapsulated measurements in format appropriate for web app. VIRTUAL, for internal use only.

parseMeasurement(msId=NULL): Parse measurement id msId to extract object id and column. VIRTUAL, for internal use only.

setMgr(): Set the associated session manager. For internal use only.

setInDevice(x): Set the inDevice field to x. For internal use only.

plot(): Plot data in this object. VIRTUAL.

getRows(query, metadata): Get rows overlapping query, a GenomicRanges object. metadata: list of metadata columns; metadata values returned for each row.

getValues(query, measurement): Get measurement values for rows overlapping query, a GenomicRanges object.

Author(s)

Hector Corrada Bravo

EpivizDataCache-class *Virtual class for data cache used by Epiviz.*

Description

Manage data cache from external resources (e.g., BigWig files) for use by epiviz queries.

Details

Manage data cache from external resources (e.g., BigWig files) for use by epiviz queries.

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

EpivizDevice-class *'EpivizDevice' objects*

Description

Encapsulate both measurement and chart for display in epiviz web app

Details

This provides a convenience interface to the measurement/chart interface. All measurements for a given object are encapsulated in an [EpivizData-class](#) object, and its plot method is called to create an [EpivizChart-class](#) object.

Fields

msObject: ([EpivizData-class](#)) object encapsulating measurements.

chartObject: ([EpivizChart-class](#)) object encapsulating a chart.

id: (character) device id set by session manager. Use getId method to get id.

Methods

getMsObject(): Return msObject.

getChartObject(): Return chartObject.

getMsId(): Return id of msObject.

getChartId(): Return id of chartObject.

setId(id): Set device id. For internal use only.

getId(): Return device object id.

update(newObject, sendRequest=TRUE): Update data object in msObject. Calls the update method of msObject.

Author(s)

Hector Corrada Bravo

EpivizDeviceMgr-class 'EpivizDeviceMgr' objects

Description

This class manages interactive visualization connections to the epiviz web app. It provides a mechanism to add measurements (from objects in the R/bioc workspace), charts (plots and tracks in the web app) or devices (a one-step combination of measurements and charts). It also provides navigation and other interactive functions. Setters and getters are defined for the pertinent fields, which should not be accessed directly. Objects of this class are usually created using the [startEpiviz](#) function.

Details

The most important aspect of interactive connections to the epiviz web app is the ability to add tracks and plots displaying data from an R/bioc session. This class is designed so that data and display are distinct, the former represented by measurements encapsulated in [EpivizData-class](#) objects, the latter by charts encapsulated by [EpivizChart-class](#) objects.

For a user to visualize data stored in an object that can be referenced by genomic location, e.g., a [GRanges](#) or [RangedSummarizedExperiment](#) objects, they must first indicate to the session manager which measurements are provided by this object using the `addMeasurements` method. This creates an object derived from class [EpivizData-class](#) (using `register-methods`) which wraps the data object so that efficient overlap queries are performed (using [GIntervalTree](#) objects) and adds the set of measurements provided to the web app. This allows users to create charts displaying data from this object either by using the `addChart` method or the web app UI itself. See section 'Measurement management methods' below for more information.

Once measurements have been declared, users can use the `addChart` method to visualize them in one or more different plot types (see section 'Chart types' below). Objects from classes derived from [EpivizData-class](#) have `plot` methods that use reasonable default chart types. See section 'Chart management methods' below for more information.

We also provide a 'device' interface to simplify the steps above. Users can call the `addDevice` method, passing a data object to be visualized and a chart is added with the default visualization for the object. The same mechanism above is used, so both a [EpivizData-class](#) and [EpivizChart-class](#) objects are added to the session manager. See section 'Device management methods' below for more information.

Fields

`url`: The url used to connect to the epiviz web app
`msList`: List of added measurements (objects of classes that inherit from [EpivizData-class](#))
`typeMap`: List of currently available measurements types
`msIdCounter`: Used internally to manage `msList`
`chartList`: List of currently added charts (objects of class [EpivizChart-class](#))
`chartIdCounter`: Used internally to manage `chartList`

activeId: Id of currently active chart (not used)
chartIdMap: Character vector of chart ids assigned by the web app. Vector names are chart ids set by the session manager
deviceList: List of currently added devices (objects of class [EpivizDevice-class](#))
deviceIdCounts: Used internally to manage deviceList
server: Object of class [EpivizServer-class](#) encapsulating the websocket connection to app
verbose: Log to console on requests received
nonInteractive: Run in non-interactive mode, for internal development use only
callbackArray: Object of class [IndexedArray-class](#) containing request callback functions

Utility methods

bindToServer(): Call the bindManager function of the server object passing this object as argument.
isClosed(): Returns TRUE if connection to app is closed.
openBrowser(url=NULL): Open browser for epiviz web app, if argument url is NULL (the default), the url field is used.
service(): Service requests from app (this call blocks the R/interactive session until loop is escaped)
stopService(): Stop the service loop
startServer(): Start the websocket connection server
stopServer(): Stops the websocket connection server. Also removes all currently added devices, charts and measurements from web app.

Seqinfo methods

addSeqinfo(x): Add sequence space (e.g., chromosome) information to the web app. x should be a [Seqinfo-class](#) object, or a named integer (or numeric) vector.
rmSeqinfo(seqnames): Remove sequence spaces (e.g., chromosome) information from the web app. seqnames should be a character vector containing chromosome names.

Navigation methods

refresh(): NOT SUPPORTED YET
navigate(chr, start, end): Navigate in web app to give genomic region
slideshow(granges, n=length(granges)): Navigate in web app to the first n regions in [GenomicRanges-class](#) object granges in succession.

Measurement management methods

addMeasurements(obj, msName, sendRequest=TRUE, ...): Add measurements in obj, calls the [register-methods](#) on obj passing extra arguments in Measurements are given names derived from msName. Measurements are added to the web app itself if sendRequest==TRUE (the default). This method adds a measurement object of class [EpivizData-class](#), returned by the [register-methods](#) to the mList field. Measurement ids are generated automatically using msIdCounter and are returned by this method.

`.clearDatasourceGroupCache(msObj, sendRequest=!nonInteractive)`: Clears data caches in web app using any of the measurements defined by `msObj` of class ([EpivizData-class](#)). Only affects web app if `sendRequest==TRUE`. This method is for internal use only.

`updateMeasurements(oldObject, newObject, sendRequest=TRUE)`: Update the data object wrapped in [EpivizData-class](#) object `oldObject` to `newObject`. The class of `newObject` depends on the type of data, but is checked for correctness, i.e., the the classes of the new and current data objects are the same. Argument `oldObject` can be a [EpivizData-class](#) object already added to the session, or a character containing the id of an object. Ids are returned by the `addMeasurements` method.

`.getMsObject(msObjId)`: Get the [EpivizData-class](#) object corresponding the the id `msObjId`. This method is for internal use only.

`rmMeasurements(msObj)`: Remove measurements stored in [EpivizData-class](#) object `msObj`. The `msObj` argument can be an [EpivizData-class](#) object added to the session manager, or the id of such an object.

`rmAllMeasurements()`: Remove all measurements added to the session manager.

`listMeasurements()`: List measurements added to the session manager.

`getMeasurements()`: Returns list of currently added measurements in format required by web app. This method is for internal use only.

`getMeasurementType(x)`: Returns type of measurement object `x` of class [EpivizData-class](#).

Data fetch methods

`getRows(chr, start, end, metadata, datasource)`: Get genomic location and metadata for rows in given datasource that overlap the region defined by `chr, start` and `end`.

`getValues(chr, start, end, datasource, measurement)`: Get data values for column measurement for rows in datasource that overlap the region defined by `chr, start` and `end`.

Chart management methods

`addChart(chartObject, sendRequest=TRUE, ...)`: Adds chart specified by `chartObject` of class [EpivizChart-class](#) to the session manager. The chart is added to the web app if `sendRequest==TRUE` (the default). The `chartObject` is inserted to the `chartList` field. Chart ids are generated automatically using `chartIdCounter` and are returned by this method.

`.getChartObject(chartId)`: Returns the [EpivizChart-class](#) object corresponding to id `chartId`.

`rmChart(chartObj)`: Remove chart corresponding to `chartObj`. Argument `chartObj` can be an object of class [EpivizChart-class](#) or the character id of such an object.

`rmAllCharts()`: Remove all charts currently in the session manager.

`listCharts()`: List all charts currently added to session manager.

Chart types

`blockChart(ms, ...)`: Used to display data in [GenomicRanges](#) objects as genomic regions using rectangles in a browser track. `ms` is a list of lists, each component describing a measurement provided by an object of class [EpivizBlockData-class](#). They can be obtained using the `getMeasurements` method in the [EpivizBlockData-class](#). `plot` method for [EpivizBlockData-class](#) calls this method.

- `lineChart(ms, ...)`: Used to display continuous data at base-pair level as a line plot in a browser track. `ms` is a list of lists, each component describing a measurement provided by objects of class [EpivizBpData-class](#). They can be obtained using the `getMeasurements` method in the [EpivizBlockData-class](#). The `plot` method for [EpivizBpData-class](#) calls this method.
- `scatterChart(x, y, ...)`: Used to display genomic feature data in [RangedSummarizedExperiment](#) objects as a scatter plot. `x` and `y` are lists for measurements provided by objects of class [EpivizFeatureData-class](#). They can be obtained using the `getMeasurements` method in the [EpivizFeatureData-class](#). The `plot` method for [EpivizFeatureData-class](#) calls this method.
- `heatmapChart(ms, ...)`: Used to display genomic feature data in [RangedSummarizedExperiment](#) objects as a heatmap. `ms` is a list of lists, each component describing a measurement provided by an object of class [EpivizFeatureData-class](#). They can be obtained using the `getMeasurements` method in the [EpivizFeatureData-class](#).
- `genesChart(ms, ...)`: Used to display a gene annotation track. `ms` is a list containing a single entry: a list describing data provided by an object of class [EpivizGeneInfoData-class](#). This list can be obtained using the `getMeasurements` method in the [EpivizGeneInfoData-class](#).

Device management methods

- `addDevice(obj, devName, sendRequest=TRUE, ...)`: Adds device for object `obj`. This method calls the `addMeasurements` method on `obj` and calls the `plot` method of the resulting [EpivizData-class](#) object. Measurements and charts added by this called are given names derived from `devName`. Arguments to `addMeasurement` and the `plot`-methods call can be given in `...`. Device ids are generated automatically using `devIdCounter` and are returned by this function. An object of class [EpivizDevice-class](#) is created and inserted into `devList`.
- `rmDevice(devObj)`: Remove the device corresponding to `devObj`: an object of class [EpivizDevice-class](#) or the id for such an object. This removes the corresponding chart and measurement objects from the session manager.
- `rmAllDevices()`: Remove all devices added to the session manager.
- `updateDevice(oldObject, newObject, sendRequest=TRUE, ...)`: Update the data object wrapped in [EpivizDevice-class](#) object `oldObject` to `newObject`. The class of `newObject` depends on the type of data, but is checked for correctness, i.e., the the classes of the new and current data objects are the same. Argument `oldObject` can be a [EpivizDevice-class](#) object already added to the session, or a character containing the id of an object. Ids are returned by the `addDevice` method.
- `listDevices()`: List all devices added to the session manager.

Author(s)

Hector Corrada Bravo

See Also

[startEpiviz](#) [EpivizData-class](#) [EpivizChart-class](#) [EpivizDevice-class](#) [GenomicRanges-class](#) [EpivizServer-class](#) [register-methods](#) [IndexedArray-class](#)

Examples

```
## Not run:
require(epivizrData)
data(tcga_colon_example)

mgr <- startEpiviz(openBrowser=interactive())

# using the device interface
blockDev <- mgr$addDevice(colon_blocks, "blocks_test", type="block")

# using the measurement/chart interface
# add measurements
blockMs <- mgr$addMeasurements(colon_blocks, "blocks_test2", type="block")

# add chart
blockChart <- mgr$blockChart(blockMs$getMeasurements()[1])

# using plot methods
blockChart2 <- blockMs$plot()

# list devices
mgr$listDevices()

# list measurements
mgr$listMeasurements()

# list charts
mgr$listCharts()

# remove a chart
mgr$rmChart(blockChart2)

# navigate to genomic region
mgr$navigate("chr2", 10000000, 30000000)
mgr$stopServer()

## End(Not run)
```

EpivizFeatureData-class

'EpivizFeatureData' objects

Description

Encapsulate data for genomic features

Details

The object field is constrained to be [RangedSummarizedExperiment](#). Data is obtained from columns of a determined assay. Measurement names are checked against the row names of the

colData slot. The rowRanges is assumed to be a [GIntervalTree](#) object, its mcols must contain columns PROBEID and SYMBOL.

Fields

assay: (integer or character) indicating assay from which data is obtained

Methods

.checkColumns(columns): Checks columns are a subset of names(colData(object)).

.getColumns(): Returns names(colData(object)).

plot(): Calls the scatterPlot method of [EpivizDeviceMgr-class](#) with the first measurements in columns as x and y.

getMeasurements(): Returns list describing data encapsulated in this object.

Author(s)

Hector Corrada Bravo

EpivizGeneInfoData-class

'EpivizGeneInfoData' objects

Description

Encapsulate gene annotation

Details

This class extends [EpivizTrackData-class](#). Like its super-class, the data containing object is constrained to be of class [GIntervalTree](#). Ranges contained in the object correspond to the genomic interval spanning all annotated exons for the gene. Columns Gene and Exons are assumed to be part of the elementMetadata of the data containing object. Column Gene (character) is used as gene names in the UI, column Exons (IRangesList) is used to annotate exon start and ends.

Methods

plot(): Calls the genesChart method of [EpivizDeviceMgr-class](#).

getMeasurements(): Returns a list describing data encapsulated by this object.

Author(s)

Hector Corrada bravo

EpivizServer-class *EpivizServer objects*

Description

This class encapsulates the websocket connection between the R/bioc session and the epiviz web app.

Details

Epiviz uses websockets to connect R/bioc sessions to the epiviz web app. Objects of this class encapsulates websocket objects defined in the [httpuv](#) package. The Epiviz session manager defined in class [EpivizDeviceMgr](#) calls methods in this class to send requests to the web app or to respond to requests. Can also be executed in standalone mode, serving the epiviz web app JS through the [httpuv](#) server.

Fields

port: Port for websocket connection (default 7312)
websocket: A [WebSocket](#) object from the [httpuv](#) package
server: Internal use only: A server object from the [httpuv](#) package, set by the [startServer](#) method
interrupted: Internal use only: has an interrupt been issued
socketConnected: Internal use only: is the websocket connected
msgCallback: Internal use only: callback functions on websocket or http requests. Created using [shiny:::HandlerManager](#)
requestQueue: Internal use only: Queue for unsent requests
tryPorts: Internal use only: Try more ports when opening websocket server if port requested by user is in use.
daemonized: Internal use only: is it running in daemonized mode
standalone: Internal use only: is it running in standalone mode

Methods

startServer(...): Sets up the server and websocket objects from [httpuv](#) package. Specifically, it sets the `server` field by calling [startServer](#) passing port and a set of callbacks, including a `onWSOpen` callback that sets the `websocket` field and sets the `msgCallback` method as the `websocket$onMessage` callback. In standalone mode, it also creates a callback for http requests.

stopServer(): Stops the websocket server, calling [stopServer](#).

service(): A blocking (if not running daemonized) loop for the websocket to listen and serve requests. Calls [service](#).

stopService(): Signals an interrupt so the service loop is stopped.

runServer(): A convenience function that runs startServer and service. stopServer is called on exit.

isClosed(): Returns TRUE if server connection is closed

bindManager(mgr): Sets the msgCallback on websocket message callback. It calls methods from argument mgr, usually an object of class [EpivizDeviceMgr](#). Methods currently called from mgr are: getMeasurements, getRows, getValues, getSeqInfos and getAllData. The latter is used only in testing.

sendRequest(request): Converts argument request to JSON and pushes it to the requestQueue.

popRequest(): Pop a request from requestQueue and send to web app.

emptyRequestQueue(): Empties request queue.

Author(s)

Hector Corrada Bravo

See Also

[EpivizDeviceMgr-class](#), [EpivizChart-class](#), [httpuv](#), [startServer](#), [service](#), [WebSocket](#)

Examples

```
## Not run:
mgr <- list(getData=function(measurements, chr, start, end) {
  return(chr)
},
  verbose=TRUE)

server <- epivizr::EpivizServer$new(port=7123L)
server$bindManager(mgr)
server$startServer()

browseURL("http://localhost:7123/")
tryCatch(server$service(), interrupt=function(int) invisible())

## End(Not run)
```

EpivizTrackData-class *'EpivizTrackData' objects*

Description

Data container for data displayed in tracks

Details

This class extends EpivizData-class directly. The data containing object is constrained to be of class [GIntervalTree](#).

Author(s)

Hector Corrada Bravo

EpivizWigCache-class *Cache for BigWig files*

Description

Manages a data cache for external BigWig files.

Details

Manages a data cache for external BigWig files.

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

EpivizWigData-class *Container for data read from external BigWig files*

Description

Container for data read from external BigWig files

Details

Container for data read from external BigWig files

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

IndexedArray-class *Indexed array*

Description

This class is used by [EpivizDeviceMgr-class](#) objects to store requests callbacks.

Fields

nextId Next integer id to return when item is appended
items Stored items

Methods

append(item): Append item to array, returns id of appended item
get(id): Return item with given id
empty(): Empty the array

Author(s)

Hector Corrada Bravo

See Also

[EpivizDeviceMgr-class](#)

Examples

```
array <- epivizr:::IndexedArray$new()
aId <- array$append("a")
array$get(aId)
```

makeGeneTrackAnnotation

Create a gene annotation object to use as gene track on the epiviz UI.

Description

Given an OrganismDb object, it creates a GRanges object in the required format to use with the epiviz UI. This allows users to create custom genome browsers from their Bioconductor environment.

Usage

```
makeGeneTrackAnnotation(object, kind = c("gene", "tx"), keepSeqlevels = NULL)
```


Arguments

`object` An object of class `OrganismDb`.

`kind` return a "gene" or "transcript" annotation. Only gene annotations are currently supported.

`keepSeqlevels` a list of seqnames to retain in the gene annotation. See [keepSeqlevels](#).

Details

This function creates a `GRanges` object that can be used by the `addDevice` method in class `EpivizDeviceMgr` to add a genes track to an epiviz UI.

Value

An object of class `GRanges`, with one row per gene. It includes columns `Gene` with gene symbol, and `Exons` including exon start and ends. The latter is of class `IRangesList`.

Author(s)

Hector Corrada Bravo

See Also

[startStandalone](#)

Examples

```
## Not run:
library(Mus.musculus)
gr <- makeGeneTrackAnnotation(Mus.musculus, keepSeqlevels=paste0("chr", c(1:19, "X", "Y")))
mgr <- startEpiviz()
mgr$addSeqinfo(seqinfo(gr))
mgr$addDevice(gr, "mm10", type="geneInfo")

## End(Not run)
```

Queue-class

A Queue

Description

A first-in-first-out data structure. Used by [EpivizServer-class](#) objects to queue requests.

Fields

`items` Items stored in queue

Methods

`push(item)`: Push item into queue
`pop()`: Pop item on top of queue
`peek()`: Return but not pop item on top of queue.
`empty()`: Empty the queue

Author(s)

Hector Corrada Bravo

See Also

[EpivizServer-class](#)

Examples

```
theQ <- epivizr:::Queue$new()
theQ$push("a")
theQ$pop()
```

register-methods

Encapsulate data object in Epiviz

Description

This method encapsulates data objects in R/bioc to be used for interactive visualization. It converts [GenomicRanges](#) objects to [GIntervalTree](#) objects when appropriate. It returns objects from the [EpivizData-class](#) hierarchy.

Usage

```
## S4 method for signature 'GenomicRanges'
register(object, columns=NULL, type=c("block", "bp", "geneInfo"), ...)
## S4 method for signature 'RangedSummarizedExperiment'
register(object, columns=NULL, assay=1)
## S4 method for signature 'ExpressionSet'
register(object, columns=NULL, annotation=NULL)
## S4 method for signature 'OrganismDb'
register(object, kind=c("gene", "tx"), keepSeqlevels=NULL, ...)
```

Arguments

object	data object to encapsulate
columns	columns in object to use. All columns are used if NULL
type	for GenomicRanges objects, use block representation, base-pair level quantitative representation, or gene annotation (see below)
assay	for RangedSummarizedExperiment and ExpressionSet objects, determine which assay to use
annotation	for ExpressionSet objects, determine the annotation to use to obtain feature genomic coordinates. If NULL, then <code>annotation(object)</code> is used
kind	for OrganismDb objects, return a "gene" or "transcript" annotation. Only gene annotations are currently supported.
keepSeqlevels	for OrganismDb objects, a list of seqnames to retain in the gene annotation. See keepSeqlevels .
...	arguments passed to EpivizData-class subclasses constructors

Details

This function converts [GenomicRanges](#) objects to [GIntervalTree](#) objects when appropriate. For example, the `rowRanges` slot in [RangedSummarizedExperiment](#) objects. Genomic coordinates for features in [ExpressionSet](#) objects are obtained used the [AnnotationDb](#) interface from the provided annotation.

Gene Annotations: Gene annotations can be provided through [GenomicRanges](#) (using `type="geneInfo"`) or [OrganismDb](#) objects. For the latter, we assume a `Gene` (character) column is available containing gene names, and a `Exons` ([IRangesList](#)) column is available. Annotations using [GRangesList](#) objects will be supported in the near future.

Value

Returns objects from the [EpivizData-class](#) hierarchy depending on the provided object. When object is a [GenomicRanges](#) object and `type=="block"`, a [EpivizBlockData-class](#) object is returned; a [EpivizBpData-class](#) object is returned if `type=="bp"`. For [RangedSummarizedExperiment](#) and [ExpressionSet](#) objects, a [EpivizFeatureData-class](#) object is returned. For [RangedSummarizedExperiment](#) objects, columns `SYMBOL` and `PROBEID` are assumed to be present in `mcols(rowRanges(object))`.

Author(s)

Hector Corrada Bravo

See Also

[EpivizData-class](#) and subclasses, [EpivizDeviceMgr-class](#), [GenomicRanges](#), [RangedSummarizedExperiment](#), [GIntervalTree](#), [OrganismDb](#) [ExpressionSet](#)

startEpiviz	<i>Start the epiviz interface</i>
-------------	-----------------------------------

Description

Create an epiviz session manager which can be used to add and delete tracks and plots in the browser web app.

Usage

```
startEpiviz(port = 7312L, localURL = NULL, useDevel = FALSE, standalone=FALSE,
  staticSitePath = "", chr = "chr11", start = 99800000, end = 103383180,
  debug = FALSE, workspace = NULL, scripts=NULL, gists=NULL, openBrowser = TRUE,
  daemonized = .epivizrCanDaemonize(), verbose = FALSE,
  nonInteractive = FALSE, tryPorts = FALSE)
```

Arguments

port	(integer) port for websocket server
localURL	(character) use this url for the epiviz server instead of the standard URL (http://epiviz.cbcb.umd.edu). For example localURL="http://localhost/epiviz" when serving from the local host
useDevel	(logical) use the devel branch of the epiviz server (http://epiviz-dev.cbcb.umd.edu)
standalone	(logical) run the epiviz app on localhost using the httpuv http server
staticSitePath	(character) location of standalone epiviz static site directory. Uses the "www" directory of the installed package by default (i.e., when staticSitePath=""
chr	(character) chromosome to browse to on startup
start	(integer) start position to browse to on startup
end	(integer) end position to browse to on startup
debug	(logical) start the epiviz browser in debug mode
workspace	(character) a workspace id to load in the epiviz web app on startup
scripts	(character vector) URLs for JavaScript plugin scripts to be imported when epiviz is loaded (see http://epiviz.cbcb.umd.edu/help for details).
gists	(character vector) Ids for github gists (http://gist.github.com) containing JavaScript plugin scripts to be imported when epiviz is loaded (see http://epiviz.cbcb.umd.edu/help for details).
openBrowser	(logical) browse to the epiviz URL before exiting function
daemonized	(logical) use non-blocking version if available (UNIX-like platforms only)
verbose	(logical) display log messages on websocket requests
nonInteractive	(logical) run in non-interactive mode, for development purposes only
tryPorts	(logical) try more ports if port number given by argument port is in use.

Value

an object of class [EpivizDeviceMgr](#).

Author(s)

Hector Corrada Bravo

See Also

[EpivizDeviceMgr-class](#)

Examples

```
## Not run:
mgr <- startEpiviz(openBrowser=FALSE)
mgr$startServer()
mgr$stopServer()

## End(Not run)
```

startStandalone	<i>Start the standalone epiviz interface</i>
-----------------	--

Description

Create an epiviz session manager for the epiviz web application served from the localhost.

Usage

```
startStandalone(geneInfo = NULL, geneInfoName = "", seqinfo = NULL, chr = NULL, start = NULL, end = NULL)
```

Arguments

geneInfo	An object containing gene annotation information. See register-methods for information on objects permitted.
geneInfoName	(character) The name of the gene annotation to display on the UI.
seqinfo	Seqinfo-class object containing sequence names and lengths. Ignored if geneInfo is not NULL.
chr	Sequence name to load the UI. If NULL, taken from seqinfo(geneInfo) or seqinfo in order.
start	Starting genomic position when loading UI. If NULL, taken from seqinfo(geneInfo) or seqinfo in order.
end	Ending genomic position when loading UI. If NULL, taken from seqinfo(geneInfo) or seqinfo in order.
start.args	List containing other arguments to pass startEpiviz .
...	Arguments passed to addDevice method of EpivizDeviceMgr when adding gene annotation. For instance, keepSeqlevels.

Details

One of geneInfo or seqinfo must be non-NULL. Otherwise an error is raised.

Value

An object of class [EpivizDeviceMgr](#).

Author(s)

Hector Corrada Bravo

See Also

[EpivizDeviceMgr-class register-methods](#)

Examples

```
## Not run:
library(Mus.musculus)
mgr <- startStandalone(Mus.musculus, geneInfoName="mm10",
  keepSeqlevels=paste0("chr",c(1:19,"X","Y")))

## End(Not run)
```

tcga_colon_example *Example methylation data for epivizr vignette*

Description

This package contains example results from methylation analysis of human chromosome 11 using the [minfi-package](#) package of TCGA 450k beadarray samples.

Usage

```
data(tcga_colon_example)
```

Format

Two [GRanges](#) objects. The first colon_blocks, described large regions of methylation difference between tumor and normal samples. It has the following as metadata:

```
value average smooth methylation difference within block
area block area estimate (abs(value) * length)
cluster id of cluster blockgroup within which block occurs
indexStart index of first cluster in block
indexEnd index of last cluster in block
L number of clusters in block
```

clusterL number of probes in block
p.value permutation p.value based on difference conditioned on length
fwer family-wise error rate estimate based on difference conditioned on length
p.valueArea permutation p.value based on area
fwerArea family-wise error rate estimate based on area

The second, `colon_curves`, is probe cluster-level methylation estimates. It has the following as element metadata:

id probe cluster id
type probe cluster type
blockgroup probe cluster block group
diff raw methylation percentage difference between normal and tumor
smooth smooth methylation percentage difference between normal and tumor
normalMean mean methylation estimate for normal samples
cancerMean mean methylation estimate for cancer samples

Author(s)

Hector Corrada Bravo

Source

TCGA project: <https://tcga-data.nci.nih.gov/tcga/>

See Also

[minfi-package](#)

Examples

```
data(tcga_colon_example)
show(colon_blocks)
show(colon_curves)
```

`tcga_colon_expression` *Example exon-level RNAseq data from TCGA project for epvizr.*

Description

A [RangedSummarizedExperiment](#) object containing exon-level counts from RNAseq data from the TCGA project. Only exons in human chromosome 11 are included.

Usage

```
data(tcga_colon_expression)
```

Format

A `RangedSummarizedExperiment` object with 12,800 rows (exons) and 40 samples.

assay(colonSE) exon-level count matrix

colData(colonSE) a `DataFrame` containing sample information. Normal/Tumor status is given in column `sample_type`

Source

TCGA project: <https://tcga-data.nci.nih.gov/tcga/>

Examples

```
data(tcga_colon_expression)
show(colonSE)
table(colData(colonSE)$sample_type)
```


Index

*Topic **datasets**

- tcga_colon_example, 22
 - tcga_colon_expression, 23
- AnnotationDb, 19
- class:EpivizBlockData
(EpivizBlockData-class), 2
- class:EpivizBpData
(EpivizBpData-class), 3
- class:EpivizChart (EpivizChart-class), 3
- class:EpivizData (EpivizData-class), 4
- class:EpivizDataCache
(EpivizDataCache-class), 5
- class:EpivizDevice
(EpivizDevice-class), 6
- class:EpivizDeviceMgr
(EpivizDeviceMgr-class), 7
- class:EpivizFeatureData
(EpivizFeatureData-class), 11
- class:EpivizGeneInfoData-class
(EpivizGeneInfoData-class), 12
- class:EpivizServer
(EpivizServer-class), 13
- class:EpivizTrackData
(EpivizTrackData-class), 14
- class:EpivizWigCache
(EpivizWigCache-class), 15
- class:EpivizWigData
(EpivizWigData-class), 15
- class:IndexedArray
(IndexedArray-class), 16
- class:Queue (Queue-class), 17
- colon_blocks (tcga_colon_example), 22
- colon_curves (tcga_colon_example), 22
- colonSE (tcga_colon_expression), 23
- EpivizBlockData-class, 2
- EpivizBpData-class, 3
- EpivizChart-class, 3, 10, 14
- EpivizData-class, 4, 10, 19
- EpivizDataCache-class, 5
- EpivizDevice-class, 6, 10
- EpivizDeviceMgr, 3, 13, 14, 21, 22
- EpivizDeviceMgr
(EpivizDeviceMgr-class), 7
- EpivizDeviceMgr-class, 7, 14, 19, 21, 22
- EpivizFeatureData-class, 11
- EpivizGeneInfoData-class, 12
- EpivizServer-class, 10, 13
- EpivizTrackData-class, 14
- EpivizWigCache-class, 15
- EpivizWigData-class, 15
- ExpressionSet, 19
- GenomicRanges, 9, 18, 19
- GenomicRanges-class, 10
- GIntervalTree, 2, 3, 7, 12, 14, 18, 19
- GRanges, 7, 22
- httpuv, 13, 14
- IndexedArray-class, 10, 16
- keepSeqlevels, 17, 19
- makeGeneTrackAnnotation, 16
- minfi-package, 23
- OrganismDb, 19
- Queue-class, 17
- RangedSummarizedExperiment, 7, 10, 11, 19, 23, 24
- register, ExpressionSet-method
(register-methods), 18
- register, GenomicRanges-method
(register-methods), 18
- register, OrganismDb-method
(register-methods), 18

register, RangedSummarizedExperiment-method
 (register-methods), 18
register-methods, 10, 18, 22

service, 13, 14
startEpiviz, 7, 10, 20, 21
startServer, 13, 14
startStandalone, 17, 21
stopServer, 13

tcga_colon_example, 22
tcga_colon_expression, 23

WebSocket, 13, 14