

Package ‘CODEX’

April 8, 2025

Type Package

Title A Normalization and Copy Number Variation Detection Method for Whole Exome Sequencing

Version 1.39.0

Author Yuchao Jiang, Nancy R. Zhang

Maintainer Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Description A normalization and copy number variation calling procedure for whole exome DNA sequencing data. CODEX relies on the availability of multiple samples processed using the same sequencing pipeline for normalization, and does not require matched controls. The normalization model in CODEX includes terms that specifically remove biases due to GC content, exon length and targeting and amplification efficiency, and latent systemic artifacts. CODEX also includes a Poisson likelihood-based recursive segmentation procedure that explicitly models the count-based exome sequencing data.

License GPL-2

Depends R (>= 3.2.3), Rsamtools, GenomeInfoDb, BSgenome.Hsapiens.UCSC.hg19, IRanges, Biostrings, S4Vectors

Suggests WES.1KG.WUGSC

biocViews ImmunoOncology, ExomeSeq, Normalization, QualityControl, CopyNumberVariation

LazyData yes

git_url <https://git.bioconductor.org/packages/CODEX>

git_branch devel

git_last_commit a803161

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2025-04-08

Contents

| | |
|---------------------------|----|
| CODEX-package | 2 |
| bambedObjDemo | 3 |
| choiceofK | 3 |
| coverageObjDemo | 4 |
| gcDemo | 5 |
| getbambed | 6 |
| getcoverage | 7 |
| getgc | 8 |
| getmapp | 9 |
| mappability | 10 |
| mappDemo | 10 |
| mapp_ref | 11 |
| normalize | 12 |
| normalize2 | 13 |
| normObjDemo | 14 |
| qc | 15 |
| qcObjDemo | 16 |
| segment | 17 |

| | |
|--------------|-----------|
| Index | 19 |
|--------------|-----------|

| | |
|---------------|--|
| CODEX-package | <i>A Normalization and Copy Number Variation Detection Method for Whole Exome Sequencing</i> |
|---------------|--|

Description

CODEX is a normalization and copy number variation calling procedure for whole exome DNA sequencing data. CODEX relies on the availability of multiple samples processed using the same sequencing pipeline for normalization, and does not require matched controls. The normalization model in CODEX includes terms that specifically remove biases due to GC content, exon length and targeting and amplification efficiency, and latent systemic artifacts. CODEX also includes a Poisson likelihood-based recursive segmentation procedure that explicitly models the count-based exome sequencing data.

Details

Package: CODEX
 Type: Package
 Version: 0.99.0
 Date: 2015-01-13
 License: GPL-2

CODEX takes as input the bam files/directories for whole exome sequencing datasets and bed files for exonic positions, returns raw and normalized coverage for each exon, and calls copy number variations with genotyping results.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>, Nancy R. Zhang

bambedObjDemo *Demo data pre-stored for bambedObj.*

Description

Pre-stored bambedObj data for demonstration purposes.

Usage

```
data(bambedObjDemo)
```

Details

Pre-computed using whole exome sequencing data of 46 HapMap samples.

Value

bambedObj demo data (list) pre-computed.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Examples

```
bamdir <- bambedObjDemo$bamdir
samprname <- bambedObjDemo$samprname
ref <- bambedObjDemo$ref
projectname <- bambedObjDemo$projectname
chr <- bambedObjDemo$chr
```

choiceofK *Determine the number of latent factors K.*

Description

Determines the number of latent variables K via AIC, BIC, and deviance reduction. A pdf file containing all three plots is generated.

Usage

```
choiceofK(AIC, BIC, RSS, K, filename)
```

Arguments

| | |
|----------|--|
| AIC | vector of AIC for each K returned from normalize |
| BIC | vector of BIC for each K returned from normalize |
| RSS | vector of RSS for each K returned from normalize |
| K | vector of K returned from normalize |
| filename | Filename of the output plot of AIC and RSS |

Details

AIC: Akaike information criterion, used for model selection; BIC: Bayesian information criterion, used for model selection; RSS: residue sum of squares, used to plot scree plot and determine the 'elbow'.

Value

pdf file with three plots: AIC, BIC, and percentage of variance explained versus the number of latent factors.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[normalize](#), [segment](#)

Examples

```
AIC <- normObjDemo$AIC
BIC <- normObjDemo$BIC
RSS <- normObjDemo$RSS
K <- normObjDemo$K
projectname <- bambedObjDemo$projectname
chr <- bambedObjDemo$chr
choiceofK(AIC, BIC, RSS, K, filename = paste(projectname, "_", chr,
      "_choiceofK", ".pdf", sep = ""))
```

coverageObjDemo

Demo data pre-stored for coverageObj.

Description

Pre-stored coverageObj data for demonstration purposes.

Usage

```
data(coverageObjDemo)
```

Details

Pre-computed using whole exome sequencing data of 46 HapMap samples.

Value

coverageObj demo data (list) pre-computed.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Examples

```
Y <- coverageObjDemo$Y
readlength <- coverageObjDemo$readlength
```

gcDemo

Demo data pre-stored for GC content.

Description

Pre-stored GC content data for demonstration purposes.

Usage

```
data(gcDemo)
```

Details

Pre-computed using whole exome sequencing data of 46 HapMap samples.

Value

gc demo data (vector) pre-computed.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Examples

```
head(round(gcDemo, 2))
```

`getbambed`*Get bam file directories, sample names, and exonic positions*

Description

Gets bam file directories, sample names from .txt file, and exonic positions from .bed file.

Usage

```
getbambed(bamdir, bedFile, sampname, projectname, chr)
```

Arguments

| | |
|--------------------------|--|
| <code>bamdir</code> | Column vector. Each line specifies directory of a bam file. Should be in same order as sample names in <code>sampname</code> . |
| <code>bedFile</code> | Path to bed file specifying exonic targets. Is of type character. |
| <code>sampname</code> | Column vector. Each line specifies name of a sample corresponding to the bam file. Should be in same order as bam directories in <code>bamdir</code> . |
| <code>projectname</code> | String specifying the name of the project. Data will be saved using this as prefix. |
| <code>chr</code> | Chromosome. |

Value

| | |
|--------------------------|--|
| <code>bamdir</code> | Bam directories |
| <code>sampname</code> | Sample names |
| <code>ref</code> | IRanges object specifying exonic positions |
| <code>projectname</code> | String specifying the name of the project. |
| <code>chr</code> | Chromosome |

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

References

Lawrence M, Huber W, Pages H, Aboyoun P, Carlson M, Gentleman R, Morgan M and Carey V (2013). "Software for Computing and Annotating Genomic Ranges." PLoS Computational Biology, 9.

See Also

[getcoverage](#)

Examples

```
library(WES.1KG.WUGSC)
dirPath <- system.file("extdata", package = "WES.1KG.WUGSC")
bamFile <- list.files(dirPath, pattern = '*.bam$')
bamdir <- file.path(dirPath, bamFile)
samnameFile <- file.path(dirPath, "samname")
samname <- as.matrix(read.table(samnameFile))
chr <- 22
bambedObj <- getbambed(bamdir = bamdir, bedFile = file.path(dirPath,
  "chr22_400_to_500.bed"), samname = samname,
  projectname = "CODEX_demo", chr)
bamdir <- bambedObj$bamdir
samname <- bambedObj$samname
ref <- bambedObj$ref
projectname <- bambedObj$projectname
chr <- bambedObj$chr
```

getcoverage

Get depth of coverage from whole exome sequencing

Description

Gets depth of coverage for each exon across all samples from whole exome sequencing files.

Usage

```
getcoverage(bambedObj, mapqthres)
```

Arguments

| | |
|-----------|--|
| bambedObj | Object returned from getbambed |
| mapqthres | Mapping quality threshold hold of reads. |

Value

| | |
|------------|---------------------------------------|
| Y | Read depth matrix |
| readlength | Vector of read length for each sample |

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[getbambed](#)

Examples

```
library(WES.1KG.WUGSC)
dirPath <- system.file("extdata", package = "WES.1KG.WUGSC")
bamFile <- list.files(dirPath, pattern = '*.bam$')
bamdir <- file.path(dirPath, bamFile)
samnameFile <- file.path(dirPath, "samname")
samname <- as.matrix(read.table(samnameFile))
chr <- 22
bambedObj <- getbambed(bamdir = bamdir, bedFile = file.path(dirPath,
  "chr22_400_to_500.bed"), samname = samname,
  projectname = "CODEX_demo", chr)
bamdir <- bambedObj$bamdir
samname <- bambedObj$samname
ref <- bambedObj$ref
projectname <- bambedObj$projectname
chr <- bambedObj$chr
coverageObj <- getcoverage(bambedObj, mapqthres = 20)
Y <- coverageObj$Y
readlength <- coverageObj$readlength
```

getgc

Get GC content for each exonic target

Description

Computes GC content for each exon. Will be later used in QC procedure and normalization.

Usage

```
getgc(chr, ref)
```

Arguments

| | |
|-----|--|
| chr | Chromosome returned from getbambed |
| ref | IRanges object returned from getbambed |

Value

Vector of GC content for each exon.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

References

Team TBD. BSgenome.Hsapiens.UCSC.hg19: Full genome sequences for Homo sapiens (UCSC version hg19). R package version 1.3.99.

See Also

[getbanded](#), [qc](#), [normalize](#)

Examples

```
ref <- IRanges(st = 51207851, end = 51207982)
gc <- getgc(chr = 22, ref)
```

getmapp

Get mappability for each exonic target

Description

Computes mappability for each exon. To save running time, take values from pre-computed results. Will be later used in QC procedure.

Usage

```
getmapp(chr, ref)
```

Arguments

| | |
|-----|--|
| chr | Chromosome returned from getbanded |
| ref | IRanges object returned from getbanded |

Details

To calculate the exonic mappability, we first construct consecutive reads of length 90 that are one base pair apart along the exon. The sequences are taken from the hg19 reference. We then find possible positions across the genome that the reads can map to allowing for two mismatches. We compute the mean of the probabilities that the overlapped reads map to the target places where they are generated and use this as the mappability of the exon.

Value

Vector of mappability for each exon.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[getbanded](#), [qc](#)

Examples

```
ref <- IRanges(st = 51207851, end = 51207982)
mapp <- getmapp(chr = 22, ref)
```

mappability

Pre-computed mappabilities

Description

The results of pre-computed mappabilities to save running time.

Usage

```
data(mappability)
```

Details

Pre-computed mappabilities. Method used is detailed in [getmapp](#).

Value

List of length 24 with pre-computed mappability of each chromosome.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[getmapp](#)

Examples

```
# mappability of chromosome 1
head(round(mappability[[1]], 2))
```

mappDemo*Demo data pre-stored for mappability.*

Description

Pre-stored mappability data for demonstration purposes.

Usage

```
data(mappDemo)
```

Details

Pre-computed using whole exome sequencing data of 46 HapMap samples.

Value

mapp demo data (vector) pre-computed.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Examples

```
head(round(mappDemo, 2))
```

mapp_ref

Position reference for pre-computed mappability results.

Description

List consisting of IRanges objects specifying exonic positions whose mappabilities are pre-computed across the genome.

Usage

```
data(mapp_ref)
```

Details

Genomic positions for pre-computed mappabilities. Method used is detailed in [getmapp](#).

Value

List of length 24 with genomic positions of pre-computed mappability of each chromosome.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[getmapp](#)

Examples

```
# mappability exon reference of chromosome 1  
mapp_ref[[1]]
```

`normalize`*Normalization of read depth from whole exome sequencing*

Description

Fits a Poisson log-linear model that normalizes the read depth data from whole exome sequencing. Includes terms that specifically remove biases due to GC content, exon capture and amplification efficiency, and latent systemic artifacts.

Usage

```
normalize(Y_qc, gc_qc, K)
```

Arguments

| | |
|--------------------|---|
| <code>Y_qc</code> | Read depth matrix after quality control procedure returned from qc |
| <code>gc_qc</code> | Vector of GC content for each exon after quality control procedure returned from qc |
| <code>K</code> | Number of latent Poisson factors. Can be an integer if optimal solution has been chosen or a vector of integers so that AIC, BIC, and RSS are computed for choice of optimal k. |

Value

| | |
|-------------------|----------------------------------|
| <code>Yhat</code> | Normalized read depth matrix |
| <code>AIC</code> | AIC for model selection |
| <code>BIC</code> | BIC for model selection |
| <code>RSS</code> | RSS for model selection |
| <code>K</code> | Number of latent Poisson factors |

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[qc](#), [choiceofK](#)

Examples

```
Y_qc <- qcObjDemo$Y_qc
gc_qc <- qcObjDemo$gc_qc
normObj <- normalize(Y_qc, gc_qc, K = 1:5)
Yhat <- normObj$Yhat
AIC <- normObj$AIC
BIC <- normObj$BIC
RSS <- normObj$RSS
K <- normObj$K
```

| | |
|------------|---|
| normalize2 | <i>Normalization of read depth from whole exome sequencing under the case-control setting</i> |
|------------|---|

Description

Fits a Poisson log-linear model that normalizes the read depth data from whole exome sequencing. Includes terms that specifically remove biases due to GC content, exon capture and amplification efficiency, and latent systemic artifacts. If the WES is designed under case-control setting, CODEX estimates the exon-wise Poisson latent factor using only the read depths in the control cohort, and then computes the sample-wise latent factor terms for the case samples by regression.

Usage

```
normalize2(Y_qc, gc_qc, K, normal_index)
```

Arguments

| | |
|--------------|---|
| Y_qc | Read depth matrix after quality control procedure returned from qc |
| gc_qc | Vector of GC content for each exon after quality control procedure returned from qc |
| K | Number of latent Poisson factors. Can be an integer if optimal solution has been chosen or a vector of integers so that AIC, BIC, and RSS are computed for choice of optimal k. |
| normal_index | Indices of control samples. |

Value

| | |
|------|----------------------------------|
| Yhat | Normalized read depth matrix |
| AIC | AIC for model selection |
| BIC | BIC for model selection |
| RSS | RSS for model selection |
| K | Number of latent Poisson factors |

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[qc](#), [choiceofK](#)

Examples

```
Y_qc <- qcObjDemo$Y_qc
gc_qc <- qcObjDemo$gc_qc
normObj <- normalize2(Y_qc, gc_qc, K = 1:5, normal_index = seq(1, 45, 2))
Yhat <- normObj$Yhat
AIC <- normObj$AIC
BIC <- normObj$BIC
RSS <- normObj$RSS
K <- normObj$K
```

normObjDemo

Demo data pre-stored for normObj.

Description

Pre-stored normObj data for demonstration purposes.

Usage

```
data(normObjDemo)
```

Details

Pre-computed using whole exome sequencing data of 46 HapMap samples.

Value

normObj demo data (list) pre-computed.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Examples

```
Yhat <- normObjDemo$Yhat
AIC <- normObjDemo$AIC
BIC <- normObjDemo$BIC
RSS <- normObjDemo$RSS
K <- normObjDemo$K
```

qc *Quality control procedure for depth of coverage*

Description

Applies a quality control procedure to the depth of coverage matrix both sample-wise and exon-wise before normalization.

Usage

```
qc(Y, sampname, chr, ref, mapp, gc, cov_thresh, length_thresh, mapp_thresh,
    gc_thresh)
```

Arguments

| | |
|---------------|--|
| Y | Original read depth matrix returned from getcoverage |
| sampname | Vector of sample names returned from getbanded |
| chr | Chromosome. |
| ref | IRanges object specifying exonic positions returned from getbanded |
| mapp | Vector of mappability for each exon returned from getmapp |
| gc | Vector of GC content for each exon returned from getgc |
| cov_thresh | Vector specifying the upper and lower bound of exonic median coverage threshold for QC. 20-4000 recommended. |
| length_thresh | Vector specifying the upper and lower bound of exonic length threshold for QC. 20-2000 recommended. |
| mapp_thresh | Scalar variable specifying exonic mappability threshold for QC. 0.9 recommended. |
| gc_thresh | Vector specifying the upper and lower bound of exonic GC content threshold for QC. 20-80 recommended. |

Details

It is suggested that analysis by CODEX be carried out in a batch-wise fashion if multiple batches exist. CODEX further filters out exons that: have extremely low coverage—median read depth across all samples less than 20 or greater than 4000; are extremely short—less than 20 bp; are extremely hard to map—mappability less than 0.9; have extreme GC content—less than 20 or greater than 80. The above filtering thresholds are recommended and can be user-defined to be adapted to different sequencing protocols.

Value

| | |
|-------------|---------------------------|
| Y_qc | Updated Y after QC |
| sampname_qc | Updated sampname after QC |
| gc_qc | Updated gc after QC |

| | |
|---------|--|
| mapp_qc | Updated mapp after QC |
| ref_qc | Updated ref after QC |
| qcmat | Matrix specifying results of exon-wise QC procedures |

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[getbambed](#), [getgc](#), [getmapp](#)

Examples

```
Y <- coverageObjDemo$Y
sampname <- bambedObjDemo$sampname
chr <- bambedObjDemo$chr
ref <- bambedObjDemo$ref
gc <- gcDemo
mapp <- mappDemo
cov_thresh <- c(20, 4000)
length_thresh <- c(20, 2000)
mapp_thresh <- 0.9
gc_thresh <- c(20, 80)
qcObj <- qc(Y, sampname, chr, ref, mapp, gc, cov_thresh, length_thresh,
           mapp_thresh, gc_thresh)
Y_qc <- qcObj$Y_qc
sampname_qc <- qcObj$sampname_qc
gc_qc <- qcObj$gc_qc
mapp_qc <- qcObj$mapp_qc
ref_qc <- qcObj$ref_qc
qcmat <- qcObj$qcmat
```

qcObjDemo

Demo data pre-stored for qcObj.

Description

Pre-stored qcObj data for demonstration purposes.

Usage

```
data(qcObjDemo)
```

Details

Pre-computed using whole exome sequencing data of 46 HapMap samples.

Value

qcObj demo data (list) pre-computed.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

Examples

```
Y_qc <- qcObjDemo$Y_qc
samprname_qc <- qcObjDemo$samprname_qc
gc_qc <- qcObjDemo$gc_qc
mapp_qc <- qcObjDemo$mapp_qc
ref_qc <- qcObjDemo$ref_qc
```

segment

Recursive segmentation algorithm for CNV detection and genotyping

Description

Recursive segmentation algorithm for CNV detection and genotyping, using normalized read depth from whole exome sequencing.

Usage

```
segment(Y_qc, Yhat, optK, K, samprname_qc, ref_qc, chr, lmax, mode)
```

Arguments

| | |
|--------------|---|
| Y_qc | Raw read depth matrix after quality control procedure returned from qc |
| Yhat | Normalized read depth matrix returned from normalize |
| optK | Optimal value K returned from choiceofK |
| K | Number of latent Poisson factors. Can be an integer if optimal solution has been chosen or a vector of integers so that AIC, BIC, and RSS are computed for choice of optimal k. |
| samprname_qc | Vector of sample names after quality control procedure returned from qc |
| ref_qc | IRanges object of genomic positions of each exon after quality control procedure returned from qc |
| chr | Chromosome number returned from getbanded |
| lmax | Maximum CNV length in number of exons returned. |
| mode | Can be either "integer" or "fraction", which respectively correspond to format of the returned copy numbers. |

Value

Final callset of CNVs with genotyping results.

Author(s)

Yuchao Jiang <yuchaoj@wharton.upenn.edu>

See Also

[normalize](#), [choiceofK](#)

Examples

```
Y_qc <- qcObjDemo$Y_qc
Yhat <- normObjDemo$Yhat
BIC <- normObjDemo$BIC
K <- normObjDemo$K
samprname_qc <- qcObjDemo$samprname_qc
ref_qc <- qcObjDemo$ref_qc
chr <- bambedObjDemo$chr
finalcall <- segment(Y_qc, Yhat, optK = K[which.max(BIC)], K = K, samprname_qc,
  ref_qc, chr, lmax = 200, mode = "integer")
finalcall
```

Index

* datasets

- bandedObjDemo, 3
- coverageObjDemo, 4
- gcDemo, 5
- mapp_ref, 11
- mappability, 10
- mappDemo, 10
- normObjDemo, 14
- qcObjDemo, 16

* package

- choiceofK, 3
- CODEX-package, 2
- getbanded, 6
- getcoverage, 7
- getgc, 8
- getmapp, 9
- normalize, 12
- normalize2, 13
- qc, 15
- segment, 17

bandedObjDemo, 3

choiceofK, 3, 12, 13, 17, 18
CODEX (CODEX-package), 2
CODEX-package, 2
coverageObjDemo, 4

gcDemo, 5
getbanded, 6, 7–9, 15–17
getcoverage, 6, 7, 15
getgc, 8, 15, 16
getmapp, 9, 10, 11, 15, 16

mapp_ref, 11
mappability, 10
mappDemo, 10

normalize, 4, 9, 12, 17, 18
normalize2, 13
normObjDemo, 14

qc, 9, 12, 13, 15, 17

qcObjDemo, 16

segment, 4, 17