

# Package ‘crisprBwa’

April 10, 2025

**Version** 1.11.0

**Date** 2022-10-17

**Title** BWA-based alignment of CRISPR gRNA spacer sequences

**Depends** methods

**Imports** BiocGenerics, BSgenome, crisprBase (>= 0.99.15), GenomeInfoDb, Rbwa, readr, stats, stringr, utils

**Suggests** BiocStyle, BSgenome.Hsapiens.UCSC.hg38, knitr, rmarkdown, testthat

**biocViews** CRISPR, FunctionalGenomics, Alignment

**Description** Provides a user-friendly interface to map on-targets and off-targets of CRISPR gRNA spacer sequences using bwa. The alignment is fast, and can be performed using either commonly-used or custom CRISPR nucleases. The alignment can work with any reference or custom genomes. Currently not supported on Windows machines.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**VignetteBuilder** knitr

**BugReports** <https://github.com/crisprVerse/crisprBwa/issues>

**URL** <https://github.com/crisprVerse/crisprBwa>

**OS\_type** unix

**git\_url** <https://git.bioconductor.org/packages/crisprBwa>

**git\_branch** devel

**git\_last\_commit** 3b1e984

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.21

**Date/Publication** 2025-04-10

**Author** Jean-Philippe Fortin [aut, cre]

**Maintainer** Jean-Philippe Fortin <fortin946@gmail.com>

## Contents

runBwa . . . . .	2
runCrisprBwa . . . . .	3

<b>Index</b>	<b>5</b>
--------------	----------

---

runBwa	<i>Run BWA short-read aligner</i>
--------	-----------------------------------

---

### Description

Return BWA alignments for a list of short sequences for a prebuilt BWA index.

### Usage

```
runBwa(sequences, bwa_index = NULL, n_mismatches = 3)
```

### Arguments

sequences	Character vector of DNA sequences.
bwa_index	String specifying path to the BWA index.
n_mismatches	Integer specifying maximum number of mismatches allowed between the query sequences and the index sequences.

### Details

runBwa can be used to map short DNA sequences to a reference genome. To search for sequences while imposing constraints on PAM sequences (such as gRNA spacer sequences), see runCrisprBwa instead.

### Value

A data.frame of the alignments with the following columns:

- query — string specifying query DNA sequence
- chr - string specifying chromosome name
- pos - string specifying genomic coordinate of the start of the target DNA sequence
- strand - string specifying strand ("+" or "-")
- n\_mismatches - integer specifying number of mismatches between query and target sequences

### Author(s)

Jean-Philippe Fortin

### See Also

[link{runCrisprBwa}](#) to map gRNA spacer sequences.

**Examples**

```

fasta <- system.file(package="crisprBwa", "example/chr12.fa")
outdir <- tempdir()
index <- file.path(outdir, "chr12")
Rbwa::bwa_build_index(fasta,
                      index_prefix=index)

seqs <- c("GGAAGTTG",
          "GTGGACAC",
          "GTGTGCAA")

aln <- runBwa(seqs,
              n_mismatches=1,
              bwa_index=index)

```

---

runCrisprBwa	<i>Find gRNA spacer alignments with bwa</i>
--------------	---

---

**Description**

Return bwa alignments for a list of gRNA spacer sequences.

**Usage**

```

runCrisprBwa(
  spacers,
  bwa_index = NULL,
  bsgenome = NULL,
  crisprNuclease = NULL,
  canonical = TRUE,
  ignore_pam = FALSE,
  n_mismatches = 0,
  force_spacer_length = FALSE,
  verbose = TRUE
)

```

**Arguments**

spacers	Character vector of DNA sequences corresponding to gRNA spacer sequences. Must all be of equal length.
bwa_index	Path to the bwa index to be used for alignment.
bsgenome	Bsgenome object.
crisprNuclease	CrisprNuclease object.
canonical	Should only canonical PAM sequences be considered? TRUE by default.
ignore_pam	If TRUE, will return all matches regardless of PAM sequence. FALSE by default.

<code>n_mismatches</code>	Integer specifying maximum number of mismatches allowed between spacer and protospacer sequences.
<code>force_spacer_length</code>	Should the spacer length be overwritten in the <code>crisprNuclease</code> object? FALSE by default.
<code>verbose</code>	Should messages be printed to the console? TRUE by default.

**Details**

`runCrisprBwa` is similar to `runBwa`, with the addition of imposing constraints on PAM sequences such that the query sequences are valid protospacer sequences in the searched genome.

**Value**

**runBwa** returns spacer alignment data, including genomic coordinates and sequence.

**Author(s)**

Jean-Philippe Fortin

**See Also**

`link{runBwa}` to map general DNA sequences.

**Examples**

```
# Building BWA index first:
fasta <- system.file(package="crisprBwa", "example/chr12.fa")
outdir <- tempdir()
index <- file.path(outdir, "chr12")
Rbwa::bwa_build_index(fasta,
                      index_prefix=index)

# Aligning Cas9 gRNA
library(BSgenome.Hsapiens.UCSC.hg38)
seqs <- c("AGCTGTCCGTGGGGTCCGC",
          "CCCCTGCTGCTGTGCCAGGC")
data(SpCas9, package="crisprBase")
bsgenome <- BSgenome.Hsapiens.UCSC.hg38
results <- runCrisprBwa(seqs,
                       bsgenome=bsgenome,
                       bwa_index=index,
                       n_mismatches=2,
                       crisprNuclease=SpCas9)
```

# Index

runBwa, [2](#)

runCrisprBwa, [3](#)