

Package ‘blima’

October 17, 2017

Encoding UTF-8

Type Package

Title Tools for the preprocessing and analysis of the Illumina microarrays on the detector (bead) level

Version 1.10.0

Date 2016-12-14

Author Vojtěch Kulvait

Maintainer Vojtěch Kulvait <kulvait@gmail.com>

Description Package blima includes several algorithms for the preprocessing of Illumina microarray data. It focuses to the bead level analysis and provides novel approach to the quantile normalization of the vectors of unequal lengths. It provides variety of the methods for background correction including background subtraction, RMA like convolution and background outlier removal. It also implements variance stabilizing transformation on the bead level. There are also implemented methods for data summarization. It also provides the methods for performing T-tests on the detector (bead) level and on the probe level for differential expression testing.

License GPL-3

LazyLoad yes

Depends R(>= 3.0.0)

Imports beadarray(>= 2.0.0), Biobase(>= 2.0.0), Rcpp (>= 0.12.8), BiocGenerics, grDevices, stats, graphics

LinkingTo Rcpp

Suggests xtable, blimaTestingData, BiocStyle, illuminaHumanv4.db, lumi

URL <https://bitbucket.org/kulvait/blima>

biocViews Microarray, Preprocessing, Normalization

NeedsCompilation yes

R topics documented:

blima-package	2
aggregateAndPreprocess	5
backgroundCorrect	5
backgroundCorrectSingleArray	6
backgroundChannelSubtract	7
backgroundChannelSubtractSingleArray	8

channelExistsIntegrityWithLogicalVectorList	9
checkIntegrity	9
checkIntegrityLogical	10
checkIntegrityOfListOfBeadLevelDataObjects	10
checkIntegrityOfSingleBeadLevelDataObject	11
chipArrayStatistics	11
createSummarizedMatrix	12
doAction	13
doProbeTTests	14
doTTests	15
filterBg	17
getNextVector	18
initMeanDistribution	18
insertColumn	19
interpolateSortedVector	19
interpolateSortedVectorRcpp_	20
log2TransformPositive	20
meanDistribution	21
nonParametricEstimator	22
nonPositiveCorrect	23
nonPositiveCorrectSingleArray	24
numberOfDistributionElements	24
performXieCorrection	25
plotBackgroundImageAfterCorrection	25
plotBackgroundImageBeforeCorrection	26
quantileNormalize	27
readToVector	28
selectedChannelTransform	29
selectedChannelTransformSingleArray	30
singleArrayNormalize	30
singleChannelExistsIntegrityWithLogicalVector	31
singleCheckIntegrityLogicalVector	32
singleNumberOfDistributionElements	32
updateMeanDistribution	33
varianceBeadStabilise	33
varianceBeadStabiliseSingleArray	34
vstFromLumi	35
writeBackgroundImages	36
xieBacgroundCorrect	37
xieBacgroundCorrectSingleArray	38

Index**39**

blima-package

*Package for the preprocessing and analysis of the Illumina microar-
rays on the detector (bead) level.*

Description

Package blima includes several algorithms for the preprocessing of Illumina microarray data. It focuses to the bead level analysis and provides novel approach to the quantile normalization of the vectors of unequal lengths. It provides variety of the methods for background correction including background subtraction, RMA like convolution and background outlier removal. It also implements variance stabilizing transformation on the bead level. There are also implemented methods for data summarization. It provides the methods for performing T-tests on the detector (bead) level and on the probe level for differential expression testing.

Details

The DESCRIPTION file:

```

Encoding:      UTF-8
Package:       blima
Type:          Package
Title:         Tools for the preprocessing and analysis of the Illumina microarrays on the detector (bead) level
Version:       1.10.0
Date:          2016-12-14
Author:        Vojtěch Kulvait
Maintainer:    Vojtěch Kulvait <kulvait@gmail.com>
Description:   Package blima includes several algorithms for the preprocessing of Illumina microarray data. It focuses to
License:       GPL-3
LazyLoad:     yes
Depends:       R(>= 3.0.0)
Imports:       beadarray(>= 2.0.0), Biobase(>= 2.0.0), Rcpp (>= 0.12.8), BiocGenerics, grDevices, stats, graphics
LinkingTo:     Rcpp
Suggests:     xtable, blimaTestingData, BiocStyle, illuminaHumanv4.db, lumi
URL:           https://bitbucket.org/kulvait/blima
biocViews:    Microarray, Preprocessing, Normalization

```

Index of help topics:

```

aggregateAndPreprocess      Aggregate data
backgroundCorrect           Data background correction.
backgroundCorrectSingleArray
                             Data background correction.
backgroundChannelSubtract   Background channel subtraction
backgroundChannelSubtractSingleArray
                             Background channel subtraction
blima-package               Package for the preprocessing and analysis of
                             the Illumina microarrays on the detector (bead)
                             level.
channelExistsIntegrityWithLogicalVectorList
                             Internal function
checkIntegrity              Internal function
checkIntegrityLogical       Internal function
checkIntegrityOfListOfBeadLevelDataObjects
                             Internal function

```

```

checkIntegrityOfSingleBeadLevelDataObject
    Internal function
chipArrayStatistics    Statistics of beadLevelData
createSummarizedMatrix
    Summarized value matrix.
doAction              Internal function
doProbeTTests        T-test for probe level data.
doTTests             T-test for bead (detector) level data.
filterBg             Bg correct vector
getNextVector        Support probe and beadl level testing.
initMeanDistribution  initMeanDistribution
insertColumn         Internal function to support
                    chipArrayStatistics
interpolateSortedVector
    Interpolate sorted vector
interpolateSortedVectorRcpp_
    interpolateSortedVectorRcpp
log2TransformPositive  Log2 transform of numbers >1.
meanDistribution      Produce sorted double vector with mean
                    distribution.
nonParametricEstimator
    INTERNAL FUNCTION Xie background correct.
nonPositiveCorrect    Correct non positive
nonPositiveCorrectSingleArray
    Correct non positive
numberOfDistributionElements
    Internal
performXieCorrection  INTERNAL FUNCTION Xie background correct.
plotBackgroundImageAfterCorrection
    Plot background image after correction
plotBackgroundImageBeforeCorrection
    Plot background image before correction
quantileNormalize     Bead level quantile normalization.
readToVector          Support doTTests function.
selectedChannelTransform
    Channel transformation
selectedChannelTransformSingleArray
    Channel transformation
singleArrayNormalize  Bead level quantile normalization.
singleChannelExistsIntegrityWithLogicalVector
    Internal function
singleCheckIntegrityLogicalVector
    Internal function
singleNumberOfDistributionElements
    Internal
updateMeanDistribution
    updateMeanDistribution
varianceBeadStabilise  Bead level VST.
varianceBeadStabiliseSingleArray
    Bead level VST.
vstFromLumi           Function from LGPL lumi package 2.16.0
writeBackgroundImages  Write Background Images

```

```
xieBackgroundCorrect      Xie background correct.
xieBackgroundCorrectSingleArray
                           INTERNAL FUNCTION Xie background correct.
```

Author(s)

Vojtěch Kulvait Maintainer: Vojtěch Kulvait <kulvait@gmail.com>

```
aggregateAndPreprocess
                           Aggregate data
```

Description

This function is not intended to direct use. It helps perform work of doProbeTTests function. For each probe it prints mean and sd of an quality.

Usage

```
aggregateAndPreprocess(x, quality = "qua", transformation = NULL)
```

Arguments

```
x                Two column matrix to agregate with columns "ProbeID" and quality.
quality           Quality to analyze, default is "qua".
transformation   Function of input data trasformation, default is NULL. Any function which for
input value returns transformed value may be supplied. T-test then will be eval-
uated on transformed data, consider use log2TranformPositive.
```

Author(s)

Vojtěch Kulvait

```
backgroundCorrect      Data background correction.
```

Description

Background correction procedure selecting beads with background Intensity I_b $| \text{lmean} - I_b | > k * \text{SD}(I_{bs})$ for exclusion.

Usage

```
backgroundCorrect(b, normalizationMod = NULL, channelBackground = "GrnB",
k = 3, channelBackgroundFilter = "bgf", channelAndVector = NULL)
```

Arguments

b	List of beadLevelData objects (or single object).
normalizationMod	NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.
channelBackground	Name of channel to normalize.
k	Parameter of method stringency (default is 3).
channelBackgroundFilter	Filtered beads will have weight 0 and non filtered weight 1.
channelAndVector	Represents vector to bitwise multiple to the channelBackgroundFilter vector.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && interactive())
{
  #To perform background correction on blimatesting object for two groups. Background correction is followed
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A and E.
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  c = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    c[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod=c, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=c, channelCorrect="GrnF", channelBackg
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite
}

```

backgroundCorrectSingleArray

Data background correction.

Description

Background correction procedure selecting beads with background Intensity I_b $| \text{lmean} - I_b | > k * \text{SD}(I_b)$ for exclusion, internal.

Usage

```
backgroundCorrectSingleArray(b, normalizationMod = NULL, channelBackground = "GrnB",
  k = 3, channelBackgroundFilter = "bgf", channelAndVector = NULL)
```

Arguments

b List of beadLevelData objects (or single object).

normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.

channelBackground Name of channel to normalize.

k Parameter of method stringency (default is 3).

channelBackgroundFilter Filtered beads will have weight 0 and non filtered weight 1.

channelAndVector Represents vector to bitwise multiple to the channelBackgroundFilter vector.

Author(s)

Vojtěch Kulvait

backgroundChannelSubtract

Background channel subtraction

Description

Function to subtract one channel from another producing new channel. Standard graphic subtraction.

Usage

```
backgroundChannelSubtract(b, normalizationMod = NULL, channelSubtractFrom = "GrnF",
  channelSubtractWhat = "GrnB", channelResult = "Grn")
```

Arguments

b List of beadLevelData objects (or single object).

normalizationMod NULL for performing on all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.

channelSubtractFrom Name of channel to subtract from.

channelSubtractWhat Name of channel to subtract.

channelResult Result channel, if this channel exists it will be overwritten.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && interactive())
{
  #To perform background correction on blimatesting object for two groups. Background correction is followed
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A and E.
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  c = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    c[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = backgroundCorrect(blimatesting, normalizationMod=c, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=c, channelCorrect="GrnF", channelBackgrou
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite
}

```

backgroundChannelSubtractSingleArray

Background channel subtraction

Description

INTERNAL FUNCTION Correction for positive values only

Usage

```

backgroundChannelSubtractSingleArray(b, normalizationMod = NULL,
  channelSubtractFrom = "GrnF", channelSubtractWhat = "GrnB",
  channelResult = "Grn")

```

Arguments

b List of beadLevelData objects (or single object).

normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.

channelSubtractFrom Name of channel to subtract from.

channelSubtractWhat Name of channel to subtract.

channelResult Result channel, if this channel exists it will be overwritten.

Author(s)

Vojtěch Kulvait

channelExistsIntegrityWithLogicalVectorList
Internal function

Description

Test existence of channel slot based on vector list

Usage

```
channelExistsIntegrityWithLogicalVectorList(b, spotsToCheck = NULL,  
      slotToCheck, action = c("returnText", "warn", "error"))
```

Arguments

b	List of beadLevelData objects.
spotsToCheck	NULL for check all spots from b. Otherwise specifies logical vector of the length equals to the number of arrays in b with TRUE for checking.
slotToCheck	Slot name to check
action	What type of action is required in case of invalid object structure. Either return text different from TRUE, warn or error.

Author(s)

Vojtěch Kulvait

checkIntegrity *Internal function*

Description

Check integrity of the list of beadLevelData objects or single beadLevelData object returns waslist.

Usage

```
checkIntegrity(b, action = c("warn", "error"))
```

Arguments

b	List of beadLevelData objects or single.
action	What type of action is required in case of invalid object structure. Either return text different from TRUE, warn or error.

Value

Returns value if the object was list or not before calling this function.

Author(s)

Vojtěch Kulvait

`checkIntegrityLogical` *Internal function*

Description

Check integrity of the list of logical objects, internal.

Usage

```
checkIntegrityLogical(xx, b, action = c("returnText", "warn",  
"error"))
```

Arguments

<code>xx</code>	List of logical objects compatible with a list <code>b</code> .
<code>b</code>	List of <code>beadLevelData</code> objects.
<code>action</code>	What type of action is required in case of invalid object structure. Either return text different from <code>TRUE</code> , <code>warn</code> or <code>error</code> .

Author(s)

Vojtěch Kulvait

`checkIntegrityOfListOfBeadLevelDataObjects`
Internal function

DescriptionCheck integrity of the list of `beadLevelData` objects, internal.**Usage**

```
checkIntegrityOfListOfBeadLevelDataObjects(listb, action = c("returnText",  
"warn", "error"))
```

Arguments

<code>listb</code>	List of <code>beadLevelData</code> objects.
<code>action</code>	What type of action is required in case of invalid object structure. Either return text different from <code>TRUE</code> , <code>warn</code> or <code>error</code> .

Author(s)

Vojtěch Kulvait

checkIntegrityOfSingleBeadLevelDataObject
Internal function

Description

Check integrity of single beadLevelData object, internal.

Usage

```
checkIntegrityOfSingleBeadLevelDataObject(b, action = c("returnText",
  "warn", "error"))
```

Arguments

b	beadLevelData object.
action	What type of action is required in case of invalid object structure. Either return text different from TRUE, warn or error.

Author(s)

Vojtěch Kulvait

chipArrayStatistics *Statistics of beadLevelData*

Description

This function returns table with statistics of single beadLevelData object indexed by order of spots. It prints number of beads on each array spot mean foreground intensity and optionally mean background intensity, mean number of beads in probe set and unbiased estimate of standard deviations of these parameters. Optionally you can also obtain percentage of removed beads within excludedOnSDMultiple multiple of standard deviations from the background value.

Usage

```
chipArrayStatistics(b, includeBeadStatistic = TRUE, channelForeground = "GrnF",
  channelBackground = "GrnB", includeBackground = TRUE, excludedOnSDMultiple = NA)
```

Arguments

b	Single beadLevelData object.
includeBeadStatistic	Include number of beads per probe in output.
channelForeground	Name of channel of foreground.
channelBackground	Name of channel of background.

includeBackground Whether to output background data.

excludedOnSDMultiple If positive number, print how much percents of the background lies more than excludedOnSDMultiple multipliers of standard deviation estimate away from background mean.

Author(s)

Vojtěch Kulvait

Examples

```
if(require("blimaTestingData") && interactive())
{
  #To print basic statistic data about blimatesting[[1]] object.
  data(blimatesting)
  array1stats = chipArrayStatistics(blimatesting[[1]], includeBeadStatistic=TRUE,
    excludedOnSDMultiple=3)
  array1pheno = pData(blimatesting[[1]]@experimentData$phenoData)
  array1stats = data.frame(array1pheno$Name, array1stats)
  colnames(array1stats)[1] <- "Array";
  print(array1stats);
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite")
}
```

createSummarizedMatrix

Summarized value matrix.

Description

This function creates summarized matrix of values of certain type.

Usage

```
createSummarizedMatrix(b, spotsToProcess = NULL, quality = "qua",
  channelInclude = "bgf", annotationTag = NULL)
```

Arguments

b List of beadLevelData objects (or single object).

spotsToProcess NULL for processing all spots in b. Otherwise specifies logical vector of the length equals to the number of arrays in b.

quality Quality to matirize.

channelInclude This field allows user to set channel with weights which have to be from 0,1. All zero weighted items are excluded from summarization. You can turn this off by setting this NULL. This option may be used together with backgroundCorrect method or/and with beadarray QC (defaults to "bgf").

annotationTag Tag from annotation file which to use in resulting matrix as colname.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && require("illuminaHumanv4.db") && interactive())
{
  #Create summarization of nonnormalized data from GrnF column.
  data(blimatesting)
  blimatesting = bacgroundCorrect(blimatesting, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, channelCorrect="GrnF", channelBackgroundFilter="bgf", cl
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(processingMod)
  nonnormalized = createSummarizedMatrix(blimatesting, quality="GrnF", channelInclude="bgf",
    annotationTag="Name")
  head(nonnormalized)
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite
}

```

doAction

*Internal function***Description**

Performs action of certain type

Usage

```
doAction(message, action = c("returnText", "warn", "error"))
```

Arguments

message	Text message.
action	What type of action is required in case of invalid object structure. Either return text different from TRUE, warn or error.

Author(s)

Vojtěch Kulvait

doProbeTTests *T-test for probe level data.*

Description

This function does aggregated probe level t-tests on the data provided by the object beadLevelData from package beadarray.

Usage

```
doProbeTTests(b, c1, c2, quality = "qua", channelInclude = "bgf",
              correction = "BY", transformation = NULL)
```

Arguments

b	List of beadLevelData objects (or single object).
c1	List of logical vectors of data to assign to the first group (or single vector).
c2	List of logical vectors of data to assign to the second group (or single vector).
quality	Quality to analyze, default is "qua".
channelInclude	This field allows user to set channel with weights which have to be 0,1. All zero weighted items are excluded from t-test. You can turn this off by setting this NULL. This option may be used together with bacgroundCorrect method or/and with beadarray QC (defaults to "bgf").
correction	Multiple testing adjustment method as defined by p.adjust function, default is "BY".
transformation	Function of input data trasformation, default is NULL. Any function which for input value returns transformed value may be supplied. T-test then will be evaluated on transformed data, consider use log2TranformPositive.

Author(s)

Vojtěch Kulvait

Examples

```
if(require("blimaTestingData") && require("illuminaHumanv4.db") && interactive())
{
  #To perform background correction, variance stabilization and quantile normalization then test on probe 1
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(processingMod)
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  groups1Mod = list()
  groups2Mod = list()
  processingMod = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    groups1Mod[[i]] = p$Group %in% groups1;
    groups2Mod[[i]] = p$Group %in% groups2;
```

```

        processingMod[[i]] = p$Group %in% c(groups1, groups2);
        sampleNames[[i]] = p$Name
    }
    #Background correction and quantile normalization followed by testing including log2TransformPositive tra
    blimatesting = bacgroundCorrect(blimatesting, normalizationMod =processingMod, channelBackgroundFilter="1
    blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=processingMod, channelCorrect="GrnF",
    blimatesting = varianceBeadStabilise(blimatesting, normalizationMod = processingMod,
        quality="GrnF", channelInclude="bgf", channelOutput="vst")
    blimatesting = quantileNormalize(blimatesting, normalizationMod = processingMod,
        channelNormalize="vst", channelOutput="qua", channelInclude="bgf")
    beadTest = doTTests(blimatesting, groups1Mod, groups2Mod, "qua", "bgf")
    probeTest = doProbeTTests(blimatesting, groups1Mod, groups2Mod, "qua", "bgf")
    adrToSymbol <- merge(toTable(illuminaHumanv4ARRAYADDRESS), toTable(illuminaHumanv4SYMBOLREANNOTATED))
    adrToSymbol <- adrToSymbol[,c("ArrayAddress", "SymbolReannotated") ]
    colnames(adrToSymbol) <- c("Array_Address_Id", "Symbol")
    probeTestID = probeTest[, "ProbeID"]
    beadTestID = beadTest[, "ProbeID"]
    probeTestFC = abs(probeTest[, "mean1"]-probeTest[, "mean2"])
    beadTestFC = abs(beadTest[, "mean1"]-beadTest[, "mean2"])
    probeTestP = probeTest[, "adjustedp"]
    beadTestP = beadTest[, "adjustedp"]
    probeTestMeasure = (1-probeTestP)*probeTestFC
    beadTestMeasure = (1-beadTestP)*beadTestFC
    probeTest = cbind(probeTestID, probeTestMeasure)
    beadTest = cbind(beadTestID, beadTestMeasure)
    colnames(probeTest) <- c("ArrayAddressID", "difexPL")
    colnames(beadTest) <- c("ArrayAddressID", "difexBL")
    tocmp <- merge(probeTest, beadTest)
    tocmp = merge(tocmp, adrToSymbol, by.x="ArrayAddressID", by.y="Array_Address_Id")
    tocmp = tocmp[, c("ArrayAddressID", "Symbol", "difexPL", "difexBL")]
    sortPL = sort(-tocmp[, "difexPL"], index.return=TRUE)$ix
    sortBL = sort(-tocmp[, "difexBL"], index.return=TRUE)$ix
    beadTop10 = tocmp[sortBL[1:10],]
    probeTop10 = tocmp[sortPL[1:10],]
    print(beadTop10)
    print(probeTop10)
}else
{
    print("To run this example, please install blimaTestingData package from bioconductor by running biocLite
}

```

doTTests

*T-test for bead (detector) level data.***Description**

This function does t-tests on the data provided by the object `beadLevelData` from package `beadarray`.

Usage

```
doTTests(b, c1, c2, quality = "qua", channelInclude = "bgf",
        correction = "BY", transformation = NULL)
```

Arguments

b	List of beadLevelData objects (or single object).
c1	List of logical vectors of data to assign to the first group (or single vector).
c2	List of logical vectors of data to assign to the second group (or single vector).
quality	Quality to analyze, default is "qua".
channelInclude	This field allows user to set channel with weights which have to be 0,1. All zero weighted items are excluded from t-test. You can turn this off by setting this NULL. This option may be used together with bacgroundCorrect method or/and with beadarray QC (defaults to "bgf").
correction	Multiple testing adjustment method as defined by p.adjust function, default is "BY".
transformation	Function of input data trasformation, default is NULL. Any function which for input value returns transformed value may be supplied. T-test then will be evaluated on transformed data, consider use log2TransformPositive.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && require("illuminaHumanv4.db") && interactive())
{
  #To perform background correction, variance stabilization and quantile normalization then test on probe 1
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(processingMod)
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  groups1Mod = list()
  groups2Mod = list()
  processingMod = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    groups1Mod[[i]] = p$Group %in% groups1;
    groups2Mod[[i]] = p$Group %in% groups2;
    processingMod[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod =processingMod, channelBackgroundFilter="1
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=processingMod, channelCorrect="GrnF", c
  blimatesting = varianceBeadStabilise(blimatesting, normalizationMod = processingMod,
    quality="GrnF", channelInclude="bgf", channelOutput="vst")
  blimatesting = quantileNormalize(blimatesting, normalizationMod = processingMod,
    channelNormalize="vst", channelOutput="qua", channelInclude="bgf")
  beadTest = doTTests(blimatesting, groups1Mod, groups2Mod, "qua", "bgf")
  probeTest = doProbeTTests(blimatesting, groups1Mod, groups2Mod, "qua", "bgf")
  adrToSymbol <- merge(toTable(illuminaHumanv4ARRAYADDRESS), toTable(illuminaHumanv4SYMBOLREANNOTATED))
  adrToSymbol <- adrToSymbol[,c("ArrayAddress", "SymbolReannotated") ]
  colnames(adrToSymbol) <- c("Array_Address_Id", "Symbol")
  probeTestID = probeTest[, "ProbeID"]
}

```



```

beadTestID = beadTest[, "ProbeID"]
probeTestFC = abs(probeTest[, "mean1"] - probeTest[, "mean2"])
beadTestFC = abs(beadTest[, "mean1"] - beadTest[, "mean2"])
probeTestP = probeTest[, "adjustedp"]
beadTestP = beadTest[, "adjustedp"]
probeTestMeasure = (1 - probeTestP) * probeTestFC
beadTestMeasure = (1 - beadTestP) * beadTestFC
probeTest = cbind(probeTestID, probeTestMeasure)
beadTest = cbind(beadTestID, beadTestMeasure)
colnames(probeTest) <- c("ArrayAddressID", "difexPL")
colnames(beadTest) <- c("ArrayAddressID", "difexBL")
tocmp <- merge(probeTest, beadTest)
tocmp = merge(tocmp, adrToSymbol, by.x="ArrayAddressID", by.y="Array_Address_Id")
tocmp = tocmp[, c("ArrayAddressID", "Symbol", "difexPL", "difexBL")]
sortPL = sort(-tocmp[, "difexPL"], index.return=TRUE)$ix
sortBL = sort(-tocmp[, "difexBL"], index.return=TRUE)$ix
beadTop10 = tocmp[sortBL[1:10],]
probeTop10 = tocmp[sortPL[1:10],]
print(beadTop10)
print(probeTop10)
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite")
}

```

filterBg

Bg correct vector

Description

Background correction procedure selecting beads with background Intensity I_b $|mean - I_b| > k * SD(I_b)$ for exclusion, internal.

Usage

```
filterBg(x, k = 3)
```

Arguments

x	Vector to correct
k	Parameter of method stringency (default is 3).

Author(s)

Vojtěch Kulvait

getNextVector *Support probe and beadl level testing.*

Description

Internal function supporting probe and beadl level testing.

Usage

```
getNextVector(what, from, length)
```

Arguments

what	Two column sorted matrix with probe values.
from	Index to start on
length	nrow(what)

Author(s)

Vojtěch Kulvait

initMeanDistribution *initMeanDistribution*

Description

This is internal function not intended to direct use which initializes mean distribution.

Usage

```
initMeanDistribution(srt, prvku)
```

Arguments

srt	vector of sorted values
prvku	number of items in meanDistribution

Author(s)

Vojtěch Kulvait

insertColumn	<i>Internal function to support chipArrayStatistics</i>
--------------	---------------------------------------------------------

Description

Internal

Usage

```
insertColumn(matrix, column, name)
```

Arguments

matrix	Object to insert column to
column	Column to insert
name	Name of column to assign.

Author(s)

Vojtěch Kulvait

interpolateSortedVector	<i>Interpolate sorted vector</i>
-------------------------	----------------------------------

Description

Interpolates given sorted vector to the vector of different length. It does not sort input vector thus for unsorted vectors do not guarantee functionality. Internal function.

Usage

```
interpolateSortedVector(vector, newSize)
```

Arguments

vector	Sorted vector to interpolate.
newSize	Size of the vector to produce.

Author(s)

Vojtěch Kulvait

```
interpolateSortedVectorRcpp_  
    interpolateSortedVectorRcpp
```

Usage

```
interpolateSortedVectorRcpp_(vector, newSize)
```

Arguments

```
vector  
newSize
```

Author(s)

```
Vojtěch Kulvait
```

```
log2TransformPositive Log2 transform of numbers >1.
```

Description

Transformation function are popular in beadarray package. Here this is similar concept. This function allow user to perform log transformation before doing t-tests.

Usage

```
log2TransformPositive(x)
```

Arguments

```
x          Number to transform.
```

Value

This function returns logarithm of base 2 for numbers ≥ 1 and zero for numbers < 1 .

Author(s)

```
Vojtěch Kulvait
```

Examples

```

if(require("blimaTestingData") && require("illuminaHumanv4.db") && interactive())
{
  #To perform background correction, quantile normalization and then bead level t-test on log data run. Vst :
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(c).
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  groups1Mod = list()
  groups2Mod = list()
  c = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    groups1Mod[[i]] = p$Group %in% groups1;
    groups2Mod[[i]] = p$Group %in% groups2;
    c[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod =c, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=c, channelCorrect="GrnF", channelBackg
  blimatesting = quantileNormalize(blimatesting, normalizationMod=c, channelNormalize="GrnF", channelOutput
  beadTest <- doTTests(blimatesting, groups1Mod, groups2Mod,
    transformation=log2TransformPositive, quality="qua", channelInclude="bgf")
  symbol2address <- merge(toTable(illuminaHumanv4ARRAYADDRESS), toTable(illuminaHumanv4SYMBOLREANNOTATED))
  symbol2address <- symbol2address[,c("SymbolReannotated", "ArrayAddress") ]
  colnames(symbol2address) <- c("Symbol", "ArrayAddressID")
  beadTest = merge(beadTest, symbol2address, by.x="ProbeID", by.y="ArrayAddressID")
  beadTestID = beadTest[,c("ProbeID", "Symbol")]
  beadTestFC = abs(beadTest[, "mean1"]-beadTest[, "mean2"])
  beadTestP = beadTest[, "adjustedp"]
  beadTestMeasure = (1-beadTestP)*beadTestFC
  beadTest = cbind(beadTestID, beadTestMeasure)
  colnames(beadTest) <- c("ArrayAddressID", "Symbol", "difexBL")
  sortBL = sort(-beadTest[, "difexBL"], index.return=TRUE)$ix
  beadTop10 = beadTest[sortBL[1:10],]
  print(beadTop10)
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running bioLite
}

```

meanDistribution

Produce sorted double vector with mean distribution.

Description

This function processes arrays in the object `beadLevelData` from package `beadarray` and returns sorted double vector. The vector has length `prvku`. And the distribution of this vector is a "mean" of all distributions of `distributionChannel` quantity in arrays. In case that probe numbers are different from `prvku` it does some averaging.

Usage

```
meanDistribution(b, normalizationMod = NULL, distributionChannel = "Grn",
  channelInclude = NULL, prvku)
```

Arguments

b Object beadLevelData from package beadarray or list of these objects

normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes (defaults to NULL).

distributionChannel Channel to do mean distribution from (defaults to "Grn").

channelInclude This field allows user to set channel with weights which have to be in 0,1. All zero weighted items are excluded from quantile normalization and the value assigned to such probes is a close to value which would be assigned to them if not being excluded. You can turn this off by setting this NULL. This option may be used together with bacgroundCorrect method or/and with beadarray QC (defaults to NULL).

prvku Number of items in a resulting double vector. Prvku must not be more than minimal number of included items in any distributionChannel.

Author(s)

Vojtěch Kulvait

nonParametricEstimator

INTERNAL FUNCTION Xie background correct.

Description

INTERNAL This function is not intended for direct use. Background correction according to non parametric estimator in Xie, Yang, Xinlei Wang, and Michael Story. "Statistical Methods of Background Correction for Illumina BeadArray Data." *Bioinformatics* 25, no. 6 (March 15, 2009): 751-57. doi:10.1093/bioinformatics/btp040. The method is applied on the bead level.

Usage

```
nonParametricEstimator(toCorrectAll, toCorrectNeg)
```

Arguments

toCorrectAll
toCorrectNeg

Author(s)

Vojtěch Kulvait

nonPositiveCorrect *Correct non positive*

Description

Correction for positive values only

Usage

```
nonPositiveCorrect(b, normalizationMod = NULL, channelCorrect = "GrnF",
  channelBackgroundFilter = "bgf", channelAndVector = NULL)
```

Arguments

b List of beadLevelData objects (or single object).

normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.

channelCorrect Name of channel to correct.

channelBackgroundFilter Filtered beads will have weight 0 and non filtered weight 1.

channelAndVector Represents vector to bitwise multiple to the channelBackgroundFilter vector.

Author(s)

Vojtěch Kulvait

Examples

```
if(require("blimaTestingData") && interactive())
{
  #To perform background correction on blimatesting object for two groups. Background correction is followed
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A and E.
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  c = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    c[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod=c, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=c, channelCorrect="GrnF", channelBackg
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite(
}
```

nonPositiveCorrectSingleArray
Correct non positive

Description

INTERNAL FUNCTION Correction for positive values only

Usage

```
nonPositiveCorrectSingleArray(b, normalizationMod = NULL, channelCorrect = "GrnF",
channelBackgroundFilter = "bgf", channelAndVector = NULL)
```

Arguments

b List of beadLevelData objects (or single object).
normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.
channelCorrect Name of channel to correct.
channelBackgroundFilter Filtered beads will have weight 0 and non filtered weight 1.
channelAndVector Represents vector to bitwise multiple to the channelBackgroundFilter vector.

Author(s)

Vojtěch Kulvait

numberOfDistributionElements
Internal

Description

Internal function

Usage

```
numberOfDistributionElements(b, normalizationMod = NULL, channelInclude = NULL)
```

Arguments

b Object beadLevelData from package beadarray or list of these objects
normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.
channelInclude

Author(s)

Vojtěch Kulvait

`performXieCorrection` *INTERNAL FUNCTION Xie background correct.*

Description

INTERNAL This function is not intended for direct use. Background correction according to non parametric estimator in Xie, Yang, Xinlei Wang, and Michael Story. "Statistical Methods of Background Correction for Illumina BeadArray Data." *Bioinformatics* 25, no. 6 (March 15, 2009): 751-57. doi:10.1093/bioinformatics/btp040. ###The method is applied on the bead level.

Usage

```
performXieCorrection(value, alpha, mu, sigma)
```

Arguments

value
alpha
mu
sigma

Author(s)

Vojtěch Kulvait

`plotBackgroundImageAfterCorrection`
Plot background image after correction

Description

This function plots image of background distribution versus to foreground after background subtraction.

Usage

```
plotBackgroundImageAfterCorrection(b, index, channelForeground = "GrnF",  
channelBackground = "GrnB", SDMultiple = 3, includePearson = FALSE)
```

Arguments

b Single beadLevelData object.
index Index of spot to generate.
channelForeground Name of channel of foreground.
channelBackground Name of channel of background.
SDMultiple Correct on this level.
includePearson Include Pearson correlation.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && interactive())
{
  #Write background images after correction. This function prints graph for condition D4. Call dev.off() to
  data(blimatesting)
  p = pData(blimatesting[[2]]@experimentData$phenoData)
  index = base::match("D4", p$Name)
  plotBackgroundImageAfterCorrection(blimatesting[[2]], index)
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite")
}

```

plotBackgroundImageBeforeCorrection

Plot background image before correction

Description

This function plots image of background distribution versus to foreground before background subtraction.

Usage

```

plotBackgroundImageBeforeCorrection(b, index, channelForeground = "GrnF",
  channelBackground = "GrnB", includePearson = FALSE)

```

Arguments

b Single beadLevelData object.
index Index of spot to generate.
channelForeground Name of channel of foreground.
channelBackground Name of channel of background.
includePearson Include Pearson correlation.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && interactive())
{
  #Write background images before correction. This function prints graph for condition D4. Call dev.off() to
  data(blimatesting)
  p = pData(blimatesting[[2]]@experimentData$phenoData)
  index = base::match("D4", p$Name)
  plotBackgroundImageBeforeCorrection(blimatesting[[2]], index)
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite()")
}

```

quantileNormalize	<i>Bead level quantile normalization.</i>
-------------------	-------------------------------------------

Description

This function does quantile normalization of object beadLevelData from package beadarray.

Usage

```

quantileNormalize(b, normalizationMod = NULL, channelNormalize = "Grn",
  channelOutput = "qua", channelInclude = NULL, dst)

```

Arguments

b	Object beadLevelData from package beadarray or list of these objects
normalizationMod	NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.
channelNormalize	Name of channel to normalize.
channelOutput	Name of output normalized channel.
channelInclude	This field allows user to set channel with weights which have to be in 0,1. All zero weighted items are excluded from quantile normalization and the value assigned to such probes is a close to value which would be assigned to them if not being excluded. You can turn this off by setting this NULL. This option may be used together with backgroundCorrect method or/and with beadarray QC (defaults to NULL).
dst	User can specify sorted vector which represents distribution that should be assigned to items.

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && interactive())
{
  #To perform background correction, variance stabilization and quantile normalization.
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(c).
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  processingMod = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    processingMod[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod = processingMod, channelBackgroundFilter=
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod = processingMod, channelCorrect="GrnF",
  blimatesting = varianceBeadStabilise(blimatesting, normalizationMod = processingMod,
    quality="GrnF", channelInclude="bgf", channelOutput="vst")
  blimatesting = quantileNormalize(blimatesting, normalizationMod = processingMod,
    channelNormalize="vst", channelOutput="qua", channelInclude="bgf")
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite()")
}

```

readToVector

Support doTTests function.

Description

Internal function supporting doTTests function.

Usage

```
readToVector(what, from, length, quality)
```

Arguments

what	Item to read.
from	From index.
length	Length of vector.
quality	Column.

Author(s)

Vojtěch Kulvait

selectedChannelTransform
Channel transformation

Description

Function to transform channel data.

Usage

```
selectedChannelTransform(b, normalizationMod = NULL, channelTransformFrom,
  channelResult, transformation = NULL)
```

Arguments

b List of beadLevelData objects (or single object).

normalizationMod NULL for performing on all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.

channelTransformFrom Name of channel to transform.

channelResult Result channel, if this channel exists it will be overwritten.

transformation Function of input data trasformation, default is NULL. Any function which for input value returns transformed value may be supplied. T-test then will be evaluated on transformed data, consider use log2TranformPositive.

Author(s)

Vojtěch Kulvait

Examples

```
if(require("blimaTestingData") && interactive())
{
  #To perform background correction on blimatesting object for two groups. Background correction is followed
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A and E.
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  c = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    c[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod=c, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod=c, channelCorrect="GrnF", channelBackg
}else
```

```
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite()")
}
```

```
selectedChannelTransformSingleArray
  Channel transformation
```

Description

Function to transform channel data.

Usage

```
selectedChannelTransformSingleArray(b, normalizationMod = NULL,
  channelTransformFrom, channelResult, transformation)
```

Arguments

b List of beadLevelData objects (or single object).

normalizationMod NULL for performing on all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.

channelTransformFrom Name of channel to transform.

channelResult Result channel, if this channel exists it will be overwritten.

transformation Function of input data transformation, default is NULL. Any function which for input value returns transformed value may be supplied. T-test then will be evaluated on transformed data, consider use log2TranformPositive.

Author(s)

Vojtěch Kulvait

```
singleArrayNormalize Bead level quantile normalization.
```

Description

This function does quantile normalization of object beadLevelData from package beadarray. Internal function not intended to direct use. Please use quantileNormalize.

Usage

```
singleArrayNormalize(b, normalizationMod = NULL, channelNormalize = "Grn",
  channelOutput = "qua", channelInclude = NULL, dst)
```

Arguments

b	Object beadLevelData from package beadarray
normalizationMod	NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b.
channelNormalize	Name of channel to normalize.
channelOutput	Name of output normalized channel.
channelInclude	This field allows user to set channel with weights which have to be in 0,1. All zero weighted items are excluded from quantile normalization and the value assigned to such probes is a close to value which would be assigned to them if not being excluded. You can turn this off by setting this NULL. This option may be used together with bacgroundCorrect method or/and with beadarray QC (defaults to NULL).
dst	This field must be sorted. It is a distribution of values to assign to ports. By default this distribution is computed using meanDistribution function.

Author(s)

Vojtěch Kulvait

singleChannelExistsIntegrityWithLogicalVector
Internal function

Description

Test existence of channel slot based on logical list

Usage

```
singleChannelExistsIntegrityWithLogicalVector(b, spotsToCheck = NULL,
  slotToCheck, action = c("returnText", "warn", "error"))
```

Arguments

b	single beadLevelData object
spotsToCheck	NULL for check all spots from b. Otherwise specifies logical vector of the length equals to the number of arrays in b with TRUE for checking.
slotToCheck	Slot name to check
action	What type of action is required in case of invalid object structure. Either return text different from TRUE, warn or error.

Author(s)

Vojtěch Kulvait

singleCheckIntegrityLogicalVector
Internal function

Description

Check integrity of the logical object, internal.

Usage

```
singleCheckIntegrityLogicalVector(xx, b, action = c("returnText",  
"warn", "error"))
```

Arguments

xx	Logical object compatible with b.
b	Single beadLevelData object.
action	What type of action is required in case of invalid object structure. Either return text different from TRUE, warn or error.

Author(s)

Vojtěch Kulvait

singleNumberOfDistributionElements
Internal

Description

Internal function

Usage

```
singleNumberOfDistributionElements(b, normalizationMod = NULL,  
channelInclude = NULL)
```

Arguments

b	Object beadLevelData from package beadarray
normalizationMod	NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b or list of such vectors if b is a list of beadLevelData classes.
channelInclude	

Author(s)

Vojtěch Kulvait

```
updateMeanDistribution
      updateMeanDistribution
```

Description

This is internal function not intended to direct use. Updates mean distribution.

Usage

```
updateMeanDistribution(meanDistribution, srt, arraysUsed)
```

Arguments

```
meanDistribution

srt          vector of sorted values
arraysUsed   number of arrays allready used to create distribution
```

Author(s)

Vojtěch Kulvait

```
varianceBeadStabilise Bead level VST.
```

Description

This function does variance stabilising step on bead level.

Usage

```
varianceBeadStabilise(b, normalizationMod = NULL, quality = "qua",
  channelInclude = "bgf", channelOutput = "vst")
```

Arguments

```
b          List of beadLevelData objects (or single object).
normalizationMod  NULL for normalization of all input b. Otherwise specifies logical vector of the
                  length equal to the number of arrays in b or list of such vectors if b is a list of
                  beadLevelData classes.
quality    Quality to analyze, default is "qua".
channelInclude  This field allows user to set channel with weights which have to be in 0,1. All
                  zero weighted items are excluded from t-test. You can turn this off by setting
                  this NULL. This option may be used together with backgroundCorrect method
                  or/and with beadarray QC (defaults to "bgf").
channelOutput  Output from VST.
```

Author(s)

Vojtěch Kulvait

Examples

```

if(require("blimaTestingData") && interactive())
{
  #To perform background correction, variance stabilization and quantile normalization.
  data(blimatesting)
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(c).
  groups1 = "A";
  groups2 = "E";
  sampleNames = list()
  processingMod = list()
  for(i in 1:length(blimatesting))
  {
    p = pData(blimatesting[[i]]@experimentData$phenoData)
    processingMod[[i]] = p$Group %in% c(groups1, groups2);
    sampleNames[[i]] = p$Name
  }
  #Background correction and quantile normalization followed by testing including log2TransformPositive tra
  blimatesting = bacgroundCorrect(blimatesting, normalizationMod = processingMod, channelBackgroundFilter=
  blimatesting = nonPositiveCorrect(blimatesting, normalizationMod = processingMod, channelCorrect="GrnF",
  blimatesting = varianceBeadStabilise(blimatesting, normalizationMod = processingMod,
    quality="GrnF", channelInclude="bgf", channelOutput="vst")
  blimatesting = quantileNormalize(blimatesting, normalizationMod = processingMod,
    channelNormalize="vst", channelOutput="qua", channelInclude="bgf")
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite
}

```

varianceBeadStabiliseSingleArray
Bead level VST.

Description

This function is not intended to direct use it takes single beadLevelData object and do bead level variance stabilisation.

Usage

```

varianceBeadStabiliseSingleArray(b, normalizationMod = NULL,
  quality = "qua", channelInclude = "bgf", channelOutput = "vst")

```

Arguments

b Object beadLevelData.

normalizationMod NULL for normalization of all input b. Otherwise specifies logical vector of the length equals to the number of arrays in b.

quality Quality to analyze, default is "qua".

- channelInclude This field allows user to set channel with weights which have to be in 0,1. All zero weighted items are excluded from t-test. You can turn this off by setting this NULL. This option may be used together with backgroundCorrect method or/and with beadarray QC (defaults to "bgf").
- channelOutput Output from VST.

Author(s)

Vojtěch Kulvait

vstFromLumi *Function from LGPL lumi package 2.16.0*

Description

This function is derived from copy and paste of lumi::vst function. Since lumi package has extensive imports I decided to hardcode this function to the blima instead of importing lumi package.

Usage

```
vstFromLumi(u, std, nSupport = min(length(u), 500), backgroundStd = NULL,  
            lowCutoff = 1/3)
```

Arguments

- u The mean of probe beads
- std The standard deviation of the probe beads
- nSupport Something for c3 guess.
- backgroundStd Estimate the background variance c3. Input should be variance according to article, not SD.
- lowCutoff Something for c3 guess.

Author(s)

authors are Pan Du, Simon Lin, the function was edited by Vojtěch Kulvait

References

<http://www.bioconductor.org/packages/release/bioc/html/lumi.html>

writeBackgroundImages *Write Background Images*

Description

This function writes images with background distribution according to foreground before and after background subtraction.

Usage

```
writeBackgroundImages(b, spotsToGenerate = NULL, imageType = c("jpg",
  "png", "eps"), channelForeground = "GrnF", channelBackground = "GrnB",
  SDMultiple = 3, includePearson = FALSE, outputDir = getwd(),
  width = 505, height = 505)
```

Arguments

b	Single beadLevelData object.
spotsToGenerate	NULL for generate images for all spots from b. Otherwise specifies logical vector of the length equals to the number of arrays in b with TRUE for images to generate.
imageType	Type of images produced, either jpg, png or eps
channelForeground	Name of channel of foreground.
channelBackground	Name of channel of background.
SDMultiple	Correct on this level.
includePearson	Include Pearson correlation.
outputDir	Directory where to output images.
width	Width of image (default 505 fits well for 86mm 150dpi illustration in Bioinformatics journal:)
height	Height of image

Author(s)

Vojtěch Kulvait

Examples

```
if(require("blimaTestingData") && interactive())
{
  #Write background images before and after correction for background into /tmp directory. This function cre
  data(blimatesting)
  p = pData(blimatesting[[2]]@experimentData$phenoData)
  spotsToGenerate = p$Group %in% "D";
  writeBackgroundImages(blimatesting[[2]], imageType="jpg", spotsToGenerate=spotsToGenerate, includePearson=
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite")
}
```

xieBackgroundCorrect *Xie background correct.*

Description

Background correction according to non parametric estimator in Xie, Yang, Xinlei Wang, and Michael Story. "Statistical Methods of Background Correction for Illumina BeadArray Data." *Bioinformatics* 25, no. 6 (March 15, 2009): 751-57. doi:10.1093/bioinformatics/btp040.###The method is applied on the bead level.

Usage

```
xieBackgroundCorrect(b, normalizationMod = NULL, negativeArrayAddresses,
  channelCorrect, channelResult, channelInclude = NULL)
```

Arguments

b List of beadLevelData objects (or single object).
normalizationMod NULL for processing all spots in b. Otherwise specifies logical vector of the length equals to the number of arrays in b.
negativeArrayAddresses Vector of addresses of negative control probes on array
channelCorrect Slot to perform convolution correction.
channelResult Result channel, if this channel exists it will be overwritten.
channelInclude This field allows user to set channel with weights which have to be from 0,1. All zero weighted items are excluded from summarization. You can turn this off by setting this NULL. This option may be used together with backgroundCorrect method or/and with beadarray QC (defaults to NULL).

Author(s)

Vojtěch Kulvait

Examples

```
if(require("blimaTestingData") && exists("annotationHumanHT12V4") && interactive())
{
  #Create vector of negative array addresses.
  negAdr = unique(annotationHumanHT12V4$Controls[annotationHumanHT12V4$Controls$Reporter_Group_Name=="neg"])
  #Create summarization of nonnormalized data from GrnF column.
  data(blimatesting)
  blimatesting = backgroundCorrect(blimatesting, channelBackgroundFilter="bgf")
  blimatesting = nonPositiveCorrect(blimatesting, channelCorrect="GrnF", channelBackgroundFilter="bgf", channelInclude="bgf")
  blimatesting = xieBackgroundCorrect(blimatesting, negativeArrayAddresses=negAdr, channelCorrect="GrnF", channelInclude="bgf")
  #Prepare logical vectors corresponding to conditions A(groups1Mod), E(groups2Mod) and both(processingMod)
  xiecorrected = createSummarizedMatrix(blimatesting, quality="GrnFXIE", channelInclude="bgf",
    annotationTag="Name")
  head(xiecorrected)
}else
{
  print("To run this example, please install blimaTestingData package from bioconductor by running biocLite()")
}
```

xieBackgroundCorrectSingleArray

INTERNAL FUNCTION Xie background correct.

Description

INTERNAL This function is not intended for direct use. Background correction according to non parametric estimator in Xie, Yang, Xinlei Wang, and Michael Story. "Statistical Methods of Background Correction for Illumina BeadArray Data." *Bioinformatics* 25, no. 6 (March 15, 2009): 751-57. doi:10.1093/bioinformatics/btp040. The method is applied on the bead level.

Usage

```
xieBackgroundCorrectSingleArray(b, normalizationMod = NULL, negativeArrayAddresses,  
channelCorrect, channelResult, channelInclude = NULL)
```

Arguments

b Single beadLevelData object.

normalizationMod NULL for processing all spots in b. Otherwise specifies logical vector of the length equals to the number of arrays in b.

negativeArrayAddresses Vector of addresses of negative control probes on array

channelCorrect Slot to perform convolution correction.

channelResult Result channel, if this channel exists it will be overwritten.

channelInclude This field allows user to set channel with weights which have to be from 0,1. All zero weighted items are excluded from summarization. You can turn this off by setting this NULL. This option may be used together with bacgroundCorrect method or/and with beadarray QC (defaults to NULL).

Author(s)

Vojtěch Kulvait

Index

*Topic **package**
 blima-package, 2

aggregateAndPreprocess, 5

backgroundCorrect, 5
backgroundCorrectSingleArray, 6
backgroundChannelSubtract, 7
backgroundChannelSubtractSingleArray, 8
blima (blima-package), 2
blima-package, 2

channelExistsIntegrityWithLogicalVectorList, 9
checkIntegrity, 9
checkIntegrityLogical, 10
checkIntegrityOfListOfBeadLevelDataObjects, 10
checkIntegrityOfSingleBeadLevelDataObject, 11
chipArrayStatistics, 11
createSummarizedMatrix, 12

doAction, 13
doProbeTTests, 14
doTTests, 15

filterBg, 17

getNextVector, 18

initMeanDistribution, 18
insertColumn, 19
interpolateSortedVector, 19
interpolateSortedVectorRcpp_, 20

log2TransformPositive, 20

meanDistribution, 21

nonParametricEstimator, 22
nonPositiveCorrect, 23
nonPositiveCorrectSingleArray, 24
numberOfDistributionElements, 24

performXieCorrection, 25
plotBackgroundImageAfterCorrection, 25
plotBackgroundImageBeforeCorrection, 26

quantileNormalize, 27

readToVector, 28

selectedChannelTransform, 29
selectedChannelTransformSingleArray, 30
singleArrayNormalize, 30
singleChannelExistsIntegrityWithLogicalVector, 31
singleCheckIntegrityLogicalVector, 32
singleNumberOfDistributionElements, 32

updateMeanDistribution, 33

varianceBeadStabilise, 33
varianceBeadStabiliseSingleArray, 34
vstFromLumi, 35

writeBackgroundImages, 36

xieBackgroundCorrect, 37
xieBackgroundCorrectSingleArray, 38