

# Package ‘rRDPData’

October 16, 2021

**Title** Database for the Default RDP Classifier

**Description** Database used by the default RDP Classifier

**Version** 1.12.0

**Date** 2014-08-19

**Author** Michael Hahsler, Anurag Nagar

**Maintainer** Michael Hahsler <mhahsler@lyle.smu.edu>

**biocViews** SequencingData, MicrobiomeData

**Depends** rRDP

**SystemRequirements** Java

**License** GPL-2

**git\_url** <https://git.bioconductor.org/packages/rRDPData>

**git\_branch** RELEASE\_3\_13

**git\_last\_commit** 1d86673

**git\_last\_commit\_date** 2021-05-19

**Date/Publication** 2021-10-16

## R topics documented:

|                   |          |
|-------------------|----------|
| 16SrRNA . . . . . | 1        |
| <b>Index</b>      | <b>3</b> |

---

|         |   |
|---------|---|
| 16SrRNA | <i>RDP Classifier Model for RDP 16S rRNA Trainingset No 9</i> |
|---------|---|

---

## Description

Model data for the RDP classifier trained with the RDP 16S rRNA Trainingset No 9. This is the default model data used by RDP.

## Details

`rdp()` creates a default classifier using this data set.

The model data is stored in `system.file("16srrna", package="rRDPData")` and consists of several files in proprietary format used by the RDP software. Since RDP is a naive Bayes classifier the data mainly contain conditional word (8-mer) probabilities.

## References

RDP Classifier <http://sourceforge.net/projects/rdp-classifier/>

## Examples

```
### Use the RDP with the default classifier model data
seq <- readRNAStringSet(system.file("examples/RNA_example.fasta",
package="rRDP"))

## shorten names
names(seq) <- sapply(strsplit(names(seq), " "), "[", 1)
seq

## use RDP for classification
pred <- predict(rdp(), seq)
pred

attr(pred, "confidence")
```

# Index

\* **model**

16SrRNA, [1](#)  
16S (16SrRNA), [1](#)  
16SrRNA, [1](#)