

# Package ‘shinybiocloader’

October 9, 2025

**Title** Use a Shiny Bioconductor CSS loader

**Version** 0.99.1

**Description** Add a Bioconductor themed CSS loader to your shiny app. It is based on the shinycustomloader R package. Use a spinning Bioconductor note loader to enhance your shiny app loading screen. This package is intended for developer use.

**Depends** htmltools

**Imports** shiny

**Suggests** shinydashboard, tinytest, quarto

**VignetteBuilder** quarto

**SystemRequirements** quarto

**biocViews** Software, Infrastructure, GUI

**License** Artistic-2.0

**BugReports** <https://github.com/Bioconductor/shinybiocloader/issues>

**URL** <https://github.com/Bioconductor/shinybiocloader>

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**git\_url** <https://git.bioconductor.org/packages/shinybiocloader>

**git\_branch** devel

**git\_last\_commit** 7a0f44f

**git\_last\_commit\_date** 2025-08-19

**Repository** Bioconductor 3.22

**Date/Publication** 2025-10-08

**Author** Marcel Ramos [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-3242-0582>>)

**Maintainer** Marcel Ramos <marcel.ramos@sph.cuny.edu>

## Contents

|                      |   |
|----------------------|---|
| withLoader . . . . . | 2 |
| Index                | 4 |

---

|            |                                           |
|------------|-------------------------------------------|
| withLoader | <i>Add a loader to a Shiny UI element</i> |
|------------|-------------------------------------------|

---

## Description

Add a loader to a Shiny UI element

## Usage

```
withLoader(ui_element, loader = "biocspin", proxy.height = "400px")
```

## Arguments

|              |                                                                                                                                                                     |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ui_element   | A Shiny UI element (e.g., uiOutput, plotOutput, etc.) for which to wrap with the loader.                                                                            |
| loader       | character(1) A string specifying the loader type. Default is "biocspin".                                                                                            |
| proxy.height | character(1) A string specifying the height of the proxy element. Default is "400px". If the ui_element already has a height specified, this will be set to "100%". |

## Value

A Shiny UI element wrapped with the Bioconductor loader

## References

shinycustomloader <https://github.com/emitanaka/shinycustomloader>  
 dna spin <https://codepen.io/knut/pen/ZopMWW>

## Examples

```
library(shiny)
library(shinydashboard)
library(shinybiocloader)

waitHist <- function() {
  waiting <- faithful[["waiting"]]
  Sys.sleep(3) # Simulate loading
  hist(
    waiting, col = 'darkgray', border = 'white',
    main = 'Old Faithful Geyser Waiting Times Histogram',
    xlab = 'Waiting Time (min)'
  )
}

ui <- dashboardPage(
  dashboardHeader(title = "Bioconductor Loader"),
  dashboardSidebar(disable = TRUE),
  dashboardBody(
    h2("Bioconductor Spinning Loader"),
    HTML(
      paste0(
        "<pre><code class='language-r'>",
```

```
      "withLoader(plotOutput('distPlot'), loader='biocspin')",
      "</code></pre>"
    )
  ),
  fluidRow(
    box(
      title = "With Loader", status = "primary", solidHeader = TRUE,
      withLoader(plotOutput("distPlot"), loader = "biocspin")
    ),
    box(
      title = "Without Loader", status = "warning", solidHeader = TRUE,
      plotOutput("distPlot2")
    )
  )
)
)

server <- function(input, output) {
  output$distPlot <- renderPlot(waitHist())
  output$distPlot2 <- renderPlot(waitHist())
}

shinyApp(ui = ui, server = server)
```

# Index

withLoader, [2](#)