

Package ‘CCPlotR’

September 14, 2025

Title Plots For Visualising Cell-Cell Interactions

Version 1.6.0

Description CCPlotR is an R package for visualising results from tools that predict cell-cell interactions from single-cell RNA-seq data. These plots are generic and can be used to visualise results from multiple tools such as Liana, CellPhoneDB, NATMI etc.

Imports plyr, tidyr, dplyr, ggplot2, forcats, ggraph, igraph, scatterpie, circlize, ComplexHeatmap, tibble, grid, ggbump, stringr, ggtext, ggh4x, patchwork, RColorBrewer, scales, viridis, grDevices, graphics, stats, methods

URL <https://github.com/Sarah145/CCPlotR>

BugReports <https://github.com/Sarah145/CCPlotR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData false

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Suggests knitr, rmarkdown, BiocStyle, testthat (>= 3.0.0)

VignetteBuilder knitr

biocViews SingleCell, Network, Visualization, CellBiology, SystemsBiology

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/CCPlotR>

git_branch RELEASE_3_21

git_last_commit 8bba4ee

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-09-14

Author Sarah Ennis [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6100-8573>>),
Pilib Ó Broin [aut],
Eva Szegezdi [aut]

Maintainer Sarah Ennis <ennissarah94@gmail.com>

Contents

cc_arrow	2
cc_circos	3
cc_dotplot	4
cc_heatmap	5
cc_network	6
cc_sigmoid	7
paletteMartin	7
toy_data	8
toy_exp	9
Index	10

cc_arrow	<i>Paired Arrow Plot Function</i>
----------	-----------------------------------

Description

This function plots interactions between a pair of cell types

Usage

```
cc_arrow(
  cc_df,
  cell_types = NULL,
  option = "A",
  n_top_ints = 15,
  exp_df = NULL,
  colours = setNames(paletteMartin(n = 2), cell_types),
  palette = "BuPu"
)
```

Arguments

cc_df	A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example.
cell_types	A vector of which two cell types to plot.
option	Either 'A' or 'B'. Option A will plot the top n_top_ints interactions between cell_types and their scores. Option B will plot the top n_top_ints interactions between cell_types, their scores and the expression of the ligand/receptor genes in the sender/receiver cell types.
n_top_ints	The number of top interactions to plot.
exp_df	A dataframe containing the mean expression values for each ligand/receptor in each cell type. See toy_exp for an example. Only required for option B.
colours	A named vector of colours for each cell type. Default is paletteMartin(), a colourblind-friendly palette. Only used for option A.

palette Which colour palette to use to show the mean expression. Should be one of the RColorBrewer sequential palettes. Only used for option B.

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, toy_exp, package = 'CCPlotR')
cc_arrow(toy_data, cell_types = c("B", "CD8 T"), colours = c(`B` = "hotpink", `CD8 T` = "orange"))
cc_arrow(toy_data,
  cell_types = c("NK", "CD8 T"), option = "B", exp_df = toy_exp,
  n_top_ints = 10, palette = "OrRd"
)
```

cc_circos	<i>Circos Plot Function</i>
-----------	-----------------------------

Description

This function creates a circos plot

Usage

```
cc_circos(
  cc_df,
  option = "A",
  n_top_ints = 15,
  exp_df = NULL,
  cell_cols = NULL,
  palette = "BuPu",
  cex = 1,
  show_legend = TRUE,
  scale = FALSE,
  ...
)
```

Arguments

- cc_df A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example.
- option Either 'A' , 'B' or 'C'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores. Option C will plot the top n_top_ints interactions, their scores and the mean expression of the ligands/receptors in the sending/receiver cell types.
- n_top_ints The number of top interactions to plot. Only required for options B and C.

exp_df	A dataframe containing the mean expression values for each ligand/receptor in each cell type. See toy_exp for an example. Only required for option C.
cell_cols	A named vector of colours for each cell type. Default uses paletteMartin(), a colourblind-friendly palette.
palette	Which colour palette to use to show the mean expression. Should be one of the RColorBrewer sequential palettes.
cex	Determines text size
show_legend	TRUE or FALSE - whether to add legend or not. Only required for options B and C.
scale	TRUE or FALSE - whether to scale each sector to same width. Only required for options B and C.
...	Additional parameters passed to chordDiagram function.

Value

Returns a chord diagram generated by the circlize R package

Examples

```
data(toy_data, toy_exp, package = 'CCPlotR')
cc_circos(toy_data)
cc_circos(toy_data, option = "B", n_top_ints = 10, cex = 0.5)
cc_circos(toy_data,
  option = "C", n_top_ints = 15, exp_df = toy_exp,
  cell_cols = c(`B` = "hotpink", `NK` = "orange", `CD8 T` = "cornflowerblue"),
  palette = "PuRd", cex = 0.5
)
```

cc_dotplot

Dotplot Function

Description

This function plots a dotplot

Usage

```
cc_dotplot(cc_df, option = "A", n_top_ints = 30)
```

Arguments

cc_df	A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example.
option	Either 'A', 'B', 'CellPhoneDB' or 'Liana'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores. The 'CellPhoneDB' and 'Liana' options will generate a dotplot in the style of these popular tools.
n_top_ints	The number of top interactions to plot. Only required for option B.

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_dotplot(toy_data)
cc_dotplot(toy_data, option = "B", n_top_ints = 10)
cc_dotplot(toy_data, option = "Liana", n_top_ints = 15)
```

cc_heatmap	<i>Heatmap Function</i>
------------	-------------------------

Description

This plots a heatmap

Usage

```
cc_heatmap(cc_df, option = "A", n_top_ints = 30)
```

Arguments

cc_df	A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example.
option	Either 'A', 'B', 'CellPhoneDB' or 'Liana'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores. The 'CellPhoneDB' and 'Liana' options will generate a heatmap in the style of these popular tools.
n_top_ints	The number of top interactions to plot. Only required for option B.

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_heatmap(toy_data)
cc_heatmap(toy_data, option = "B", n_top_ints = 10)
cc_heatmap(toy_data, option = "CellPhoneDB")
```

cc_network

*Network Plot Function***Description**

This function plots a network of representing the number of interactions between cell types

Usage

```
cc_network(
  cc_df,
  colours = paletteMartin(),
  option = "A",
  n_top_ints = 20,
  node_size = 2.75,
  label_size = 4,
  layout = "kk"
)
```

Arguments

cc_df	A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example.
colours	A vector of colours for each cell type. Default is paletteMartin(), a colourblind-friendly palette.
option	Either 'A' or 'B'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores.
n_top_ints	The number of top interactions to plot. Only required for option B.
node_size	Point size for nodes in option B.
label_size	Size for labels in option B.
layout	Algorithm for determining layout in option B. One of 'dh', 'drl', 'fr', 'gem', 'graphopt', 'kk', 'lgl', 'mds', 'nicely'. See iGraph layouts for more details.

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_network(toy_data)
cc_network(toy_data, colours = c("orange", "cornflowerblue", "hotpink"), option = "B")
```

cc_sigmoid

*Sigmoid Plot Function***Description**

This function plots interactions using the `geom_sigmoid` function from the `ggbump` R package

Usage

```
cc_sigmoid(cc_df, n_top_ints = 20, colours = paletteMartin())
```

Arguments

<code>cc_df</code>	A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See <code>toy_data</code> for example.
<code>n_top_ints</code>	The number of top interactions to plot.
<code>colours</code>	A named vector of colours for each cell type. Default is <code>paletteMartin()</code> , a colourblind-friendly palette.

Value

Returns a plot generated with the `ggplot2` package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_sigmoid(toy_data)
cc_sigmoid(toy_data, colours = c(
  `B` = "hotpink", `CD8 T` = "orange",
  `NK` = "cornflowerblue"
), n_top_ints = 25)
```

paletteMartin

*Discrete palette generator***Description**

Generate a palette of up to 15 colours. The colours are from the `paletteMartin` palette in the `colorBlindness` R package.

Usage

```
paletteMartin(n = 15)
```

Arguments

n Number of colours to return. Max = 15.

Value

Returns a vector of colours of length n.

Examples

```
scales::show_col(paletteMartin(n = 9))
```

toy_data	<i>Toy data for CCPlotR</i>
----------	-----------------------------

Description

A toy dataset of ligand-receptor interactions to demonstrate cell-cell interaction plots.

Usage

```
data(toy_data)
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 735 rows and 5 columns.

Value

toy_data:
A data frame with 735 rows and 5 columns:
source Cell type expressing the ligand
target Cell type expressing the receptor
ligand Ligand
receptor Receptor
score A score for each interaction e.g. $-\log_{10}(\text{aggregate_rank})$ returned by Liana

Source

This is a modified version of the toy dataset that comes with the Liana R package.

`toy_exp`*Toy expression data for CCPlotR*

Description

A dataframe showing the mean expression values for each ligand and receptor in each cell type.

Usage

```
data(toy_exp)
```

Format

An object of class `grouped_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 477 rows and 3 columns.

Value

`toy_exp`:

A data frame with 477 rows and 3 columns:

cell_type Cell type

gene Ligand/receptor gene

mean_exp Mean (normalised) expression of ligand/receptor gene in cell type

Index

* datasets

toy_data, [8](#)

toy_exp, [9](#)

cc_arrow, [2](#)

cc_circos, [3](#)

cc_dotplot, [4](#)

cc_heatmap, [5](#)

cc_network, [6](#)

cc_sigmoid, [7](#)

paletteMartin, [7](#)

toy_data, [8](#)

toy_exp, [9](#)