

# Package ‘geneLenDataBase’

October 7, 2025

**Title** Lengths of mRNA transcripts for a number of genomes

**Version** 1.45.0

**Date** 2024-06-08

**Description** Length of mRNA transcripts for a number of genomes and gene ID formats, largely based on UCSC table browser. Data objects are provided as individual pieces of information to be retrieved and loaded. A variety of different gene identifiers and genomes is supported to ensure wide applicability.

**Depends** R (>= 2.11.0)

**Imports** utils, rtracklayer, GenomicFeatures, txdbmaker

**URL** <https://github.com/federicomarini/geneLenDataBase>

**BugReports** <https://github.com/federicomarini/geneLenDataBase/issues>

**License** LGPL (>= 2)

**biocViews** ExperimentData, Genome

**RoxygenNote** 7.3.1

**Encoding** UTF-8

**git\_url** <https://git.bioconductor.org/packages/geneLenDataBase>

**git\_branch** devel

**git\_last\_commit** 109b234

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.22

**Date/Publication** 2025-10-07

**Author** Matthew Young [aut],  
Nadia Davidson [aut],  
Federico Marini [ctb, cre] (ORCID:  
<<https://orcid.org/0000-0003-3252-7758>>)

**Maintainer** Federico Marini <marinif@uni-mainz.de>

## Contents

|                                      |   |
|--------------------------------------|---|
| anoCar1.ensGene.LENGTH . . . . .     | 8 |
| anoCar1.genscan.LENGTH . . . . .     | 9 |
| anoCar1.xenoRefGene.LENGTH . . . . . | 9 |

|                                      |    |
|--------------------------------------|----|
| anoGam1.ensGene.LENGTH . . . . .     | 10 |
| anoGam1.geneid.LENGTH . . . . .      | 10 |
| anoGam1.genscan.LENGTH . . . . .     | 11 |
| apiMel1.genscan.LENGTH . . . . .     | 11 |
| apiMel2.ensGene.LENGTH . . . . .     | 12 |
| apiMel2.geneid.LENGTH . . . . .      | 12 |
| apiMel2.genscan.LENGTH . . . . .     | 13 |
| aplCal1.xenoRefGene.LENGTH . . . . . | 13 |
| bosTau2.geneid.LENGTH . . . . .      | 14 |
| bosTau2.geneSymbol.LENGTH . . . . .  | 14 |
| bosTau2.genscan.LENGTH . . . . .     | 15 |
| bosTau2.refGene.LENGTH . . . . .     | 15 |
| bosTau2.sgpGene.LENGTH . . . . .     | 16 |
| bosTau3.ensGene.LENGTH . . . . .     | 16 |
| bosTau3.geneid.LENGTH . . . . .      | 17 |
| bosTau3.geneSymbol.LENGTH . . . . .  | 17 |
| bosTau3.genscan.LENGTH . . . . .     | 18 |
| bosTau3.refGene.LENGTH . . . . .     | 18 |
| bosTau3.sgpGene.LENGTH . . . . .     | 19 |
| bosTau4.ensGene.LENGTH . . . . .     | 19 |
| bosTau4.geneSymbol.LENGTH . . . . .  | 20 |
| bosTau4.genscan.LENGTH . . . . .     | 20 |
| bosTau4.nscanGene.LENGTH . . . . .   | 21 |
| bosTau4.refGene.LENGTH . . . . .     | 21 |
| braFlo1.xenoRefGene.LENGTH . . . . . | 22 |
| caeJap1.xenoRefGene.LENGTH . . . . . | 22 |
| caePb1.xenoRefGene.LENGTH . . . . .  | 23 |
| caePb2.xenoRefGene.LENGTH . . . . .  | 23 |
| caeRem2.xenoRefGene.LENGTH . . . . . | 24 |
| caeRem3.xenoRefGene.LENGTH . . . . . | 24 |
| calJac1.genscan.LENGTH . . . . .     | 25 |
| calJac1.nscanGene.LENGTH . . . . .   | 25 |
| calJac1.xenoRefGene.LENGTH . . . . . | 26 |
| canFam1.ensGene.LENGTH . . . . .     | 26 |
| canFam1.geneSymbol.LENGTH . . . . .  | 27 |
| canFam1.genscan.LENGTH . . . . .     | 27 |
| canFam1.nscanGene.LENGTH . . . . .   | 28 |
| canFam1.refGene.LENGTH . . . . .     | 28 |
| canFam1.xenoRefGene.LENGTH . . . . . | 29 |
| canFam2.ensGene.LENGTH . . . . .     | 29 |
| canFam2.geneSymbol.LENGTH . . . . .  | 30 |
| canFam2.genscan.LENGTH . . . . .     | 30 |
| canFam2.nscanGene.LENGTH . . . . .   | 31 |
| canFam2.refGene.LENGTH . . . . .     | 31 |
| canFam2.xenoRefGene.LENGTH . . . . . | 32 |
| cavPor3.ensGene.LENGTH . . . . .     | 32 |
| cavPor3.genscan.LENGTH . . . . .     | 33 |
| cavPor3.nscanGene.LENGTH . . . . .   | 33 |
| cavPor3.xenoRefGene.LENGTH . . . . . | 34 |
| cb1.xenoRefGene.LENGTH . . . . .     | 34 |
| cb3.xenoRefGene.LENGTH . . . . .     | 35 |
| ce2.geneid.LENGTH . . . . .          | 35 |

|                                         |    |
|-----------------------------------------|----|
| ce2.geneSymbol.LENGTH . . . . .         | 36 |
| ce2.refGene.LENGTH . . . . .            | 36 |
| ce4.geneSymbol.LENGTH . . . . .         | 37 |
| ce4.refGene.LENGTH . . . . .            | 37 |
| ce4.xenoRefGene.LENGTH . . . . .        | 38 |
| ce6.ensGene.LENGTH . . . . .            | 38 |
| ce6.geneSymbol.LENGTH . . . . .         | 39 |
| ce6.refGene.LENGTH . . . . .            | 39 |
| ce6.xenoRefGene.LENGTH . . . . .        | 40 |
| ci1.geneSymbol.LENGTH . . . . .         | 40 |
| ci1.refGene.LENGTH . . . . .            | 41 |
| ci1.xenoRefGene.LENGTH . . . . .        | 41 |
| ci2.ensGene.LENGTH . . . . .            | 42 |
| ci2.geneSymbol.LENGTH . . . . .         | 42 |
| ci2.refGene.LENGTH . . . . .            | 43 |
| ci2.xenoRefGene.LENGTH . . . . .        | 43 |
| danRer3.ensGene.LENGTH . . . . .        | 44 |
| danRer3.geneSymbol.LENGTH . . . . .     | 44 |
| danRer3.refGene.LENGTH . . . . .        | 45 |
| danRer4.ensGene.LENGTH . . . . .        | 45 |
| danRer4.geneSymbol.LENGTH . . . . .     | 46 |
| danRer4.genscan.LENGTH . . . . .        | 46 |
| danRer4.nscanGene.LENGTH . . . . .      | 47 |
| danRer4.refGene.LENGTH . . . . .        | 47 |
| danRer5.ensGene.LENGTH . . . . .        | 48 |
| danRer5.geneSymbol.LENGTH . . . . .     | 48 |
| danRer5.refGene.LENGTH . . . . .        | 49 |
| danRer5.vegaGene.LENGTH . . . . .       | 49 |
| danRer5.vegaPseudoGene.LENGTH . . . . . | 50 |
| danRer6.ensGene.LENGTH . . . . .        | 50 |
| danRer6.geneSymbol.LENGTH . . . . .     | 51 |
| danRer6.refGene.LENGTH . . . . .        | 51 |
| danRer6.xenoRefGene.LENGTH . . . . .    | 52 |
| dm1.geneSymbol.LENGTH . . . . .         | 52 |
| dm1.genscan.LENGTH . . . . .            | 53 |
| dm1.refGene.LENGTH . . . . .            | 53 |
| dm2.geneid.LENGTH . . . . .             | 54 |
| dm2.geneSymbol.LENGTH . . . . .         | 54 |
| dm2.genscan.LENGTH . . . . .            | 55 |
| dm2.nscanGene.LENGTH . . . . .          | 55 |
| dm2.refGene.LENGTH . . . . .            | 56 |
| dm3.geneSymbol.LENGTH . . . . .         | 56 |
| dm3.nscanPasaGene.LENGTH . . . . .      | 57 |
| dm3.refGene.LENGTH . . . . .            | 57 |
| downloadLengthFromUCSC . . . . .        | 58 |
| dp2.genscan.LENGTH . . . . .            | 59 |
| dp2.xenoRefGene.LENGTH . . . . .        | 59 |
| dp3.geneid.LENGTH . . . . .             | 60 |
| dp3.genscan.LENGTH . . . . .            | 60 |
| dp3.xenoRefGene.LENGTH . . . . .        | 61 |
| droAna1.geneid.LENGTH . . . . .         | 61 |
| droAna1.genscan.LENGTH . . . . .        | 62 |

|                                      |    |
|--------------------------------------|----|
| droAna1.xenoRefGene.LENGTH . . . . . | 62 |
| droAna2.genscan.LENGTH . . . . .     | 63 |
| droAna2.xenoRefGene.LENGTH . . . . . | 63 |
| droEre1.genscan.LENGTH . . . . .     | 64 |
| droEre1.xenoRefGene.LENGTH . . . . . | 64 |
| droGri1.genscan.LENGTH . . . . .     | 65 |
| droGri1.xenoRefGene.LENGTH . . . . . | 65 |
| droMoj1.geneid.LENGTH . . . . .      | 66 |
| droMoj1.genscan.LENGTH . . . . .     | 66 |
| droMoj1.xenoRefGene.LENGTH . . . . . | 67 |
| droMoj2.genscan.LENGTH . . . . .     | 67 |
| droMoj2.xenoRefGene.LENGTH . . . . . | 68 |
| droPer1.genscan.LENGTH . . . . .     | 68 |
| droPer1.xenoRefGene.LENGTH . . . . . | 69 |
| droSec1.genscan.LENGTH . . . . .     | 69 |
| droSec1.xenoRefGene.LENGTH . . . . . | 70 |
| droSim1.geneid.LENGTH . . . . .      | 70 |
| droSim1.genscan.LENGTH . . . . .     | 71 |
| droSim1.xenoRefGene.LENGTH . . . . . | 71 |
| droVir1.geneid.LENGTH . . . . .      | 72 |
| droVir1.genscan.LENGTH . . . . .     | 72 |
| droVir1.xenoRefGene.LENGTH . . . . . | 73 |
| droVir2.genscan.LENGTH . . . . .     | 73 |
| droVir2.xenoRefGene.LENGTH . . . . . | 74 |
| droYak1.geneid.LENGTH . . . . .      | 74 |
| droYak1.genscan.LENGTH . . . . .     | 75 |
| droYak1.xenoRefGene.LENGTH . . . . . | 75 |
| droYak2.genscan.LENGTH . . . . .     | 76 |
| droYak2.xenoRefGene.LENGTH . . . . . | 76 |
| equCab1.geneid.LENGTH . . . . .      | 77 |
| equCab1.geneSymbol.LENGTH . . . . .  | 77 |
| equCab1.nscanGene.LENGTH . . . . .   | 78 |
| equCab1.refGene.LENGTH . . . . .     | 78 |
| equCab1.sgpGene.LENGTH . . . . .     | 79 |
| equCab2.ensGene.LENGTH . . . . .     | 79 |
| equCab2.geneSymbol.LENGTH . . . . .  | 80 |
| equCab2.nscanGene.LENGTH . . . . .   | 80 |
| equCab2.refGene.LENGTH . . . . .     | 81 |
| equCab2.xenoRefGene.LENGTH . . . . . | 81 |
| felCat3.ensGene.LENGTH . . . . .     | 82 |
| felCat3.geneid.LENGTH . . . . .      | 82 |
| felCat3.geneSymbol.LENGTH . . . . .  | 83 |
| felCat3.genscan.LENGTH . . . . .     | 83 |
| felCat3.nscanGene.LENGTH . . . . .   | 84 |
| felCat3.refGene.LENGTH . . . . .     | 84 |
| felCat3.sgpGene.LENGTH . . . . .     | 85 |
| felCat3.xenoRefGene.LENGTH . . . . . | 85 |
| fr1.ensGene.LENGTH . . . . .         | 86 |
| fr1.genscan.LENGTH . . . . .         | 86 |
| fr2.ensGene.LENGTH . . . . .         | 87 |
| galGal2.ensGene.LENGTH . . . . .     | 87 |
| galGal2.geneid.LENGTH . . . . .      | 88 |

|                                      |     |
|--------------------------------------|-----|
| galGal2.geneSymbol.LENGTH . . . . .  | 88  |
| galGal2.genscan.LENGTH . . . . .     | 89  |
| galGal2.refGene.LENGTH . . . . .     | 89  |
| galGal2.sgpGene.LENGTH . . . . .     | 90  |
| galGal3.ensGene.LENGTH . . . . .     | 90  |
| galGal3.geneSymbol.LENGTH . . . . .  | 91  |
| galGal3.genscan.LENGTH . . . . .     | 91  |
| galGal3.nscanGene.LENGTH . . . . .   | 92  |
| galGal3.refGene.LENGTH . . . . .     | 92  |
| galGal3.xenoRefGene.LENGTH . . . . . | 93  |
| gasAcu1.ensGene.LENGTH . . . . .     | 93  |
| gasAcu1.nscanGene.LENGTH . . . . .   | 94  |
| geneLenDatabase-pkg . . . . .        | 94  |
| hg16.acembly.LENGTH . . . . .        | 95  |
| hg16.ensGene.LENGTH . . . . .        | 95  |
| hg16.exoniphy.LENGTH . . . . .       | 96  |
| hg16.geneid.LENGTH . . . . .         | 96  |
| hg16.geneSymbol.LENGTH . . . . .     | 97  |
| hg16.genscan.LENGTH . . . . .        | 97  |
| hg16.knownGene.LENGTH . . . . .      | 98  |
| hg16.refGene.LENGTH . . . . .        | 98  |
| hg16.sgpGene.LENGTH . . . . .        | 99  |
| hg17.acembly.LENGTH . . . . .        | 99  |
| hg17.acescan.LENGTH . . . . .        | 100 |
| hg17.ccdsGene.LENGTH . . . . .       | 100 |
| hg17.ensGene.LENGTH . . . . .        | 101 |
| hg17.exoniphy.LENGTH . . . . .       | 101 |
| hg17.geneid.LENGTH . . . . .         | 102 |
| hg17.geneSymbol.LENGTH . . . . .     | 102 |
| hg17.genscan.LENGTH . . . . .        | 103 |
| hg17.knownGene.LENGTH . . . . .      | 103 |
| hg17.refGene.LENGTH . . . . .        | 104 |
| hg17.sgpGene.LENGTH . . . . .        | 104 |
| hg17.vegaGene.LENGTH . . . . .       | 105 |
| hg17.vegaPseudoGene.LENGTH . . . . . | 105 |
| hg17.xenoRefGene.LENGTH . . . . .    | 106 |
| hg18.acembly.LENGTH . . . . .        | 106 |
| hg18.acescan.LENGTH . . . . .        | 107 |
| hg18.ccdsGene.LENGTH . . . . .       | 107 |
| hg18.ensGene.LENGTH . . . . .        | 108 |
| hg18.exoniphy.LENGTH . . . . .       | 108 |
| hg18.geneid.LENGTH . . . . .         | 109 |
| hg18.geneSymbol.LENGTH . . . . .     | 109 |
| hg18.genscan.LENGTH . . . . .        | 110 |
| hg18.knownGene.LENGTH . . . . .      | 110 |
| hg18.knownGeneOld3.LENGTH . . . . .  | 111 |
| hg18.refGene.LENGTH . . . . .        | 111 |
| hg18.sgpGene.LENGTH . . . . .        | 112 |
| hg18.sibGene.LENGTH . . . . .        | 112 |
| hg18.xenoRefGene.LENGTH . . . . .    | 113 |
| hg19.ccdsGene.LENGTH . . . . .       | 113 |
| hg19.ensGene.LENGTH . . . . .        | 114 |

|                                      |     |
|--------------------------------------|-----|
| hg19.exoniphy.LENGTH . . . . .       | 114 |
| hg19.geneSymbol.LENGTH . . . . .     | 115 |
| hg19.knownGene.LENGTH . . . . .      | 115 |
| hg19.nscanGene.LENGTH . . . . .      | 116 |
| hg19.refGene.LENGTH . . . . .        | 116 |
| hg19.xenoRefGene.LENGTH . . . . .    | 117 |
| loxAfr3.xenoRefGene.LENGTH . . . . . | 117 |
| mm7.ensGene.LENGTH . . . . .         | 118 |
| mm7.geneid.LENGTH . . . . .          | 118 |
| mm7.geneSymbol.LENGTH . . . . .      | 119 |
| mm7.genscan.LENGTH . . . . .         | 119 |
| mm7.knownGene.LENGTH . . . . .       | 120 |
| mm7.refGene.LENGTH . . . . .         | 120 |
| mm7.sgpGene.LENGTH . . . . .         | 121 |
| mm7.xenoRefGene.LENGTH . . . . .     | 121 |
| mm8.ccdsGene.LENGTH . . . . .        | 122 |
| mm8.ensGene.LENGTH . . . . .         | 122 |
| mm8.geneid.LENGTH . . . . .          | 123 |
| mm8.geneSymbol.LENGTH . . . . .      | 123 |
| mm8.genscan.LENGTH . . . . .         | 124 |
| mm8.knownGene.LENGTH . . . . .       | 124 |
| mm8.nscanGene.LENGTH . . . . .       | 125 |
| mm8.refGene.LENGTH . . . . .         | 125 |
| mm8.sgpGene.LENGTH . . . . .         | 126 |
| mm8.sibGene.LENGTH . . . . .         | 126 |
| mm8.xenoRefGene.LENGTH . . . . .     | 127 |
| mm9.acembly.LENGTH . . . . .         | 127 |
| mm9.ccdsGene.LENGTH . . . . .        | 128 |
| mm9.ensGene.LENGTH . . . . .         | 128 |
| mm9.exoniphy.LENGTH . . . . .        | 129 |
| mm9.geneid.LENGTH . . . . .          | 129 |
| mm9.geneSymbol.LENGTH . . . . .      | 130 |
| mm9.genscan.LENGTH . . . . .         | 130 |
| mm9.knownGene.LENGTH . . . . .       | 131 |
| mm9.nscanGene.LENGTH . . . . .       | 131 |
| mm9.refGene.LENGTH . . . . .         | 132 |
| mm9.sgpGene.LENGTH . . . . .         | 132 |
| mm9.xenoRefGene.LENGTH . . . . .     | 133 |
| monDom1.genscan.LENGTH . . . . .     | 133 |
| monDom4.ensGene.LENGTH . . . . .     | 134 |
| monDom4.geneSymbol.LENGTH . . . . .  | 134 |
| monDom4.genscan.LENGTH . . . . .     | 135 |
| monDom4.nscanGene.LENGTH . . . . .   | 135 |
| monDom4.refGene.LENGTH . . . . .     | 136 |
| monDom4.xenoRefGene.LENGTH . . . . . | 136 |
| monDom5.ensGene.LENGTH . . . . .     | 137 |
| monDom5.geneSymbol.LENGTH . . . . .  | 137 |
| monDom5.genscan.LENGTH . . . . .     | 138 |
| monDom5.nscanGene.LENGTH . . . . .   | 138 |
| monDom5.refGene.LENGTH . . . . .     | 139 |
| monDom5.xenoRefGene.LENGTH . . . . . | 139 |
| ornAna1.ensGene.LENGTH . . . . .     | 140 |

|                            |     |
|----------------------------|-----|
| ornAna1.geneSymbol.LENGTH  | 140 |
| ornAna1.refGene.LENGTH     | 141 |
| ornAna1.xenoRefGene.LENGTH | 141 |
| oryLat2.ensGene.LENGTH     | 142 |
| oryLat2.geneSymbol.LENGTH  | 142 |
| oryLat2.refGene.LENGTH     | 143 |
| oryLat2.xenoRefGene.LENGTH | 143 |
| panTro1.ensGene.LENGTH     | 144 |
| panTro1.geneid.LENGTH      | 144 |
| panTro1.genscan.LENGTH     | 145 |
| panTro1.xenoRefGene.LENGTH | 145 |
| panTro2.ensGene.LENGTH     | 146 |
| panTro2.geneSymbol.LENGTH  | 146 |
| panTro2.genscan.LENGTH     | 147 |
| panTro2.nscanGene.LENGTH   | 147 |
| panTro2.refGene.LENGTH     | 148 |
| panTro2.xenoRefGene.LENGTH | 148 |
| petMar1.xenoRefGene.LENGTH | 149 |
| ponAbe2.ensGene.LENGTH     | 149 |
| ponAbe2.geneSymbol.LENGTH  | 150 |
| ponAbe2.genscan.LENGTH     | 150 |
| ponAbe2.nscanGene.LENGTH   | 151 |
| ponAbe2.refGene.LENGTH     | 151 |
| ponAbe2.xenoRefGene.LENGTH | 152 |
| priPac1.xenoRefGene.LENGTH | 152 |
| rheMac2.ensGene.LENGTH     | 153 |
| rheMac2.geneid.LENGTH      | 153 |
| rheMac2.geneSymbol.LENGTH  | 154 |
| rheMac2.nscanGene.LENGTH   | 154 |
| rheMac2.refGene.LENGTH     | 155 |
| rheMac2.sgpGene.LENGTH     | 155 |
| rheMac2.xenoRefGene.LENGTH | 156 |
| rn3.ensGene.LENGTH         | 156 |
| rn3.geneid.LENGTH          | 157 |
| rn3.geneSymbol.LENGTH      | 157 |
| rn3.genscan.LENGTH         | 158 |
| rn3.knownGene.LENGTH       | 158 |
| rn3.nscanGene.LENGTH       | 159 |
| rn3.refGene.LENGTH         | 159 |
| rn3.sgpGene.LENGTH         | 160 |
| rn3.xenoRefGene.LENGTH     | 160 |
| rn4.ensGene.LENGTH         | 161 |
| rn4.geneid.LENGTH          | 161 |
| rn4.geneSymbol.LENGTH      | 162 |
| rn4.genscan.LENGTH         | 162 |
| rn4.knownGene.LENGTH       | 163 |
| rn4.nscanGene.LENGTH       | 163 |
| rn4.refGene.LENGTH         | 164 |
| rn4.sgpGene.LENGTH         | 164 |
| rn4.xenoRefGene.LENGTH     | 165 |
| sacCer1.ensGene.LENGTH     | 165 |
| sacCer2.ensGene.LENGTH     | 166 |

|                                      |     |
|--------------------------------------|-----|
| strPur1.geneSymbol.LENGTH . . . . .  | 166 |
| strPur1.genscan.LENGTH . . . . .     | 167 |
| strPur1.refGene.LENGTH . . . . .     | 167 |
| strPur1.xenoRefGene.LENGTH . . . . . | 168 |
| strPur2.geneSymbol.LENGTH . . . . .  | 168 |
| strPur2.genscan.LENGTH . . . . .     | 169 |
| strPur2.refGene.LENGTH . . . . .     | 169 |
| strPur2.xenoRefGene.LENGTH . . . . . | 170 |
| supportedGeneIDs . . . . .           | 170 |
| supportedGenomes . . . . .           | 171 |
| taeGut1.ensGene.LENGTH . . . . .     | 171 |
| taeGut1.geneSymbol.LENGTH . . . . .  | 172 |
| taeGut1.genscan.LENGTH . . . . .     | 172 |
| taeGut1.nscanGene.LENGTH . . . . .   | 173 |
| taeGut1.refGene.LENGTH . . . . .     | 173 |
| taeGut1.xenoRefGene.LENGTH . . . . . | 174 |
| tetNig1.ensGene.LENGTH . . . . .     | 174 |
| tetNig1.geneid.LENGTH . . . . .      | 175 |
| tetNig1.genscan.LENGTH . . . . .     | 175 |
| tetNig1.nscanGene.LENGTH . . . . .   | 176 |
| tetNig2.ensGene.LENGTH . . . . .     | 176 |
| unfactor . . . . .                   | 177 |
| xenTro1.genscan.LENGTH . . . . .     | 178 |
| xenTro2.ensGene.LENGTH . . . . .     | 178 |
| xenTro2.geneSymbol.LENGTH . . . . .  | 179 |
| xenTro2.genscan.LENGTH . . . . .     | 179 |
| xenTro2.refGene.LENGTH . . . . .     | 180 |

## Index 181

---

anoCar1.ensGene.LENGTH

*Transcript length data for the organism anoCar*

---

### Description

anoCar1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.ensGene.LENGTH)
head(anoCar1.ensGene.LENGTH)
```

---

`anoCar1.genscan.LENGTH`*Transcript length data for the organism anoCar*

---

### Description

`anoCar1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.genscan.LENGTH)
head(anoCar1.genscan.LENGTH)
```

---

`anoCar1.xenoRefGene.LENGTH`*Transcript length data for the organism anoCar*

---

### Description

`anoCar1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(anoCar1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoCar1.xenoRefGene.LENGTH)
head(anoCar1.xenoRefGene.LENGTH)
```

---

```
anoGam1.ensGene.LENGTH
```

*Transcript length data for the organism anoGam*

---

### Description

anoGam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.ensGene.LENGTH)
head(anoGam1.ensGene.LENGTH)
```

---

```
anoGam1.geneid.LENGTH
```

*Transcript length data for the organism anoGam*

---

### Description

anoGam1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(anoGam1.geneid.LENGTH)
head(anoGam1.geneid.LENGTH)
```

---

`anoGam1.genscan.LENGTH`*Transcript length data for the organism anoGam*

---

**Description**

anoGam1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(anoGam1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(anoGam1.genscan.LENGTH)
head(anoGam1.genscan.LENGTH)
```

---

`apiMel1.genscan.LENGTH`*Transcript length data for the organism apiMel*

---

**Description**

apiMel1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(apiMel1.genscan.LENGTH)
head(apiMel1.genscan.LENGTH)
```

---

`apiMel2.ensGene.LENGTH`*Transcript length data for the organism apiMel*

---

**Description**

`apiMel2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(apiMel2.ensGene.LENGTH)
head(apiMel2.ensGene.LENGTH)
```

---

`apiMel2.geneid.LENGTH` *Transcript length data for the organism apiMel*

---

**Description**

`apiMel2.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, geneid)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(apiMel2.geneid.LENGTH)
head(apiMel2.geneid.LENGTH)
```

---

`apiMel2.genscan.LENGTH`*Transcript length data for the organism apiMel*

---

**Description**

apiMel2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(apiMel2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(apiMel2.genscan.LENGTH)
head(apiMel2.genscan.LENGTH)
```

---

`aplCal1.xenoRefGene.LENGTH`*Transcript length data for the organism aplCal*

---

**Description**

aplCal1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(aplCal1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(aplCal1.xenoRefGene.LENGTH)
head(aplCal1.xenoRefGene.LENGTH)
```

---

bosTau2.geneid.LENGTH *Transcript length data for the organism bosTau*

---

### Description

bosTau2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau2.geneid.LENGTH)
head(bosTau2.geneid.LENGTH)
```

---

bosTau2.geneSymbol.LENGTH  
*Transcript length data for the organism bosTau*

---

### Description

bosTau2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau2.geneSymbol.LENGTH)
head(bosTau2.geneSymbol.LENGTH)
```

---

`bosTau2.genscan.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.genscan.LENGTH)
head(bosTau2.genscan.LENGTH)
```

---

`bosTau2.refGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau2.refGene.LENGTH)
head(bosTau2.refGene.LENGTH)
```

---

```
bosTau2.sgpGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau2, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau2.sgpGene.LENGTH)
head(bosTau2.sgpGene.LENGTH)
```

---

```
bosTau3.ensGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.ensGene.LENGTH)
head(bosTau3.ensGene.LENGTH)
```

---

bosTau3.geneid.LENGTH *Transcript length data for the organism bosTau*

---

### Description

bosTau3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.geneid.LENGTH)
head(bosTau3.geneid.LENGTH)
```

---

bosTau3.geneSymbol.LENGTH  
*Transcript length data for the organism bosTau*

---

### Description

bosTau3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.geneSymbol.LENGTH)
head(bosTau3.geneSymbol.LENGTH)
```

---

```
bosTau3.genscan.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.genscan.LENGTH)
head(bosTau3.genscan.LENGTH)
```

---

```
bosTau3.refGene.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau3.refGene.LENGTH)
head(bosTau3.refGene.LENGTH)
```

---

`bosTau3.sgpGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau3.sgpGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `sgpGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau3, sgpGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau3.sgpGene.LENGTH)
head(bosTau3.sgpGene.LENGTH)
```

---

`bosTau4.ensGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau4.ensGene.LENGTH)
head(bosTau4.ensGene.LENGTH)
```

---

```
bosTau4.geneSymbol.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau4.geneSymbol.LENGTH)
head(bosTau4.geneSymbol.LENGTH)
```

---

```
bosTau4.genscan.LENGTH
```

*Transcript length data for the organism bosTau*

---

### Description

bosTau4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(bosTau4.genscan.LENGTH)
head(bosTau4.genscan.LENGTH)
```

---

`bosTau4.nscanGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau4.nscanGene.LENGTH)
head(bosTau4.nscanGene.LENGTH)
```

---

`bosTau4.refGene.LENGTH`*Transcript length data for the organism bosTau*

---

**Description**

`bosTau4.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(bosTau4, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(bosTau4.refGene.LENGTH)
head(bosTau4.refGene.LENGTH)
```

---

```
braFlo1.xenoRefGene.LENGTH
```

*Transcript length data for the organism braFlo*

---

### Description

braFlo1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(braFlo1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(braFlo1.xenoRefGene.LENGTH)
head(braFlo1.xenoRefGene.LENGTH)
```

---

```
caeJap1.xenoRefGene.LENGTH
```

*Transcript length data for the organism caeJap*

---

### Description

caeJap1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeJap1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeJap1.xenoRefGene.LENGTH)
head(caeJap1.xenoRefGene.LENGTH)
```

---

`caePb1.xenoRefGene.LENGTH`*Transcript length data for the organism caePb*

---

**Description**

caePb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(caePb1.xenoRefGene.LENGTH)
head(caePb1.xenoRefGene.LENGTH)
```

---

`caePb2.xenoRefGene.LENGTH`*Transcript length data for the organism caePb*

---

**Description**

caePb2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caePb2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(caePb2.xenoRefGene.LENGTH)
head(caePb2.xenoRefGene.LENGTH)
```

---

```
caeRem2.xenoRefGene.LENGTH
```

*Transcript length data for the organism caeRem*

---

### Description

caeRem2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeRem2.xenoRefGene.LENGTH)
head(caeRem2.xenoRefGene.LENGTH)
```

---

```
caeRem3.xenoRefGene.LENGTH
```

*Transcript length data for the organism caeRem*

---

### Description

caeRem3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(caeRem3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(caeRem3.xenoRefGene.LENGTH)
head(caeRem3.xenoRefGene.LENGTH)
```

---

`calJac1.genscan.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.genscan.LENGTH)
head(calJac1.genscan.LENGTH)
```

---

`calJac1.nscanGene.LENGTH`*Transcript length data for the organism calJac*

---

**Description**

calJac1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(calJac1.nscanGene.LENGTH)
head(calJac1.nscanGene.LENGTH)
```

---

```
calJac1.xenoRefGene.LENGTH
```

*Transcript length data for the organism calJac*

---

### Description

calJac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(calJac1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(calJac1.xenoRefGene.LENGTH)
head(calJac1.xenoRefGene.LENGTH)
```

---

```
canFam1.ensGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.ensGene.LENGTH)
head(canFam1.ensGene.LENGTH)
```

---

`canFam1.geneSymbol.LENGTH`*Transcript length data for the organism canFam*

---

### Description

`canFam1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.geneSymbol.LENGTH)
head(canFam1.geneSymbol.LENGTH)
```

---

`canFam1.genscan.LENGTH`*Transcript length data for the organism canFam*

---

### Description

`canFam1.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.genscan.LENGTH)
head(canFam1.genscan.LENGTH)
```

---

```
canFam1.nscanGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.nscanGene.LENGTH)
head(canFam1.nscanGene.LENGTH)
```

---

```
canFam1.refGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.refGene.LENGTH)
head(canFam1.refGene.LENGTH)
```

---

`canFam1.xenoRefGene.LENGTH`*Transcript length data for the organism canFam*

---

### Description

`canFam1.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(canFam1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam1.xenoRefGene.LENGTH)
head(canFam1.xenoRefGene.LENGTH)
```

---

`canFam2.ensGene.LENGTH`*Transcript length data for the organism canFam*

---

### Description

`canFam2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.ensGene.LENGTH)
head(canFam2.ensGene.LENGTH)
```

---

```
canFam2.geneSymbol.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.geneSymbol.LENGTH)
head(canFam2.geneSymbol.LENGTH)
```

---

```
canFam2.genscan.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.genscan.LENGTH)
head(canFam2.genscan.LENGTH)
```

---

`canFam2.nscanGene.LENGTH`*Transcript length data for the organism canFam*

---

### Description

canFam2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.nscanGene.LENGTH)
head(canFam2.nscanGene.LENGTH)
```

---

`canFam2.refGene.LENGTH`*Transcript length data for the organism canFam*

---

### Description

canFam2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.refGene.LENGTH)
head(canFam2.refGene.LENGTH)
```

---

```
canFam2.xenoRefGene.LENGTH
```

*Transcript length data for the organism canFam*

---

### Description

canFam2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(canFam2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(canFam2.xenoRefGene.LENGTH)
head(canFam2.xenoRefGene.LENGTH)
```

---

```
cavPor3.ensGene.LENGTH
```

*Transcript length data for the organism cavPor*

---

### Description

cavPor3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cavPor3.ensGene.LENGTH)
head(cavPor3.ensGene.LENGTH)
```

---

`cavPor3.genscan.LENGTH`*Transcript length data for the organism cavPor*

---

**Description**

cavPor3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cavPor3.genscan.LENGTH)
head(cavPor3.genscan.LENGTH)
```

---

`cavPor3.nscanGene.LENGTH`*Transcript length data for the organism cavPor*

---

**Description**

cavPor3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cavPor3.nscanGene.LENGTH)
head(cavPor3.nscanGene.LENGTH)
```

---

```
cavPor3.xenoRefGene.LENGTH
```

*Transcript length data for the organism cavPor*

---

### Description

cavPor3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cavPor3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cavPor3.xenoRefGene.LENGTH)
head(cavPor3.xenoRefGene.LENGTH)
```

---

```
cb1.xenoRefGene.LENGTH
```

*Transcript length data for the organism cb*

---

### Description

cb1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cb1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(cb1.xenoRefGene.LENGTH)
head(cb1.xenoRefGene.LENGTH)
```

---

`cb3.xenoRefGene.LENGTH`*Transcript length data for the organism cb*

---

**Description**

cb3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(cb3, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(cb3.xenoRefGene.LENGTH)
head(cb3.xenoRefGene.LENGTH)
```

---

`ce2.geneid.LENGTH`*Transcript length data for the organism ce*

---

**Description**

ce2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneid)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ce2.geneid.LENGTH)
head(ce2.geneid.LENGTH)
```

---

ce2.geneSymbol.LENGTH    *Transcript length data for the organism ce*

---

### Description

ce2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce2.geneSymbol.LENGTH)
head(ce2.geneSymbol.LENGTH)
```

---

ce2.refGene.LENGTH    *Transcript length data for the organism ce*

---

### Description

ce2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce2.refGene.LENGTH)
head(ce2.refGene.LENGTH)
```

---

ce4.geneSymbol.LENGTH    *Transcript length data for the organism ce*

---

### Description

ce4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.geneSymbol.LENGTH)
head(ce4.geneSymbol.LENGTH)
```

---

ce4.refGene.LENGTH    *Transcript length data for the organism ce*

---

### Description

ce4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce4.refGene.LENGTH)
head(ce4.refGene.LENGTH)
```

---

`ce4.xenoRefGene.LENGTH`*Transcript length data for the organism ce*

---

**Description**

`ce4.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(ce4, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ce4.xenoRefGene.LENGTH)
head(ce4.xenoRefGene.LENGTH)
```

---

`ce6.ensGene.LENGTH`*Transcript length data for the organism ce*

---

**Description**

`ce6.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(ce6, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ce6.ensGene.LENGTH)
head(ce6.ensGene.LENGTH)
```

---

ce6.geneSymbol.LENGTH    *Transcript length data for the organism ce*

---

### Description

ce6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ce6, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.geneSymbol.LENGTH)
head(ce6.geneSymbol.LENGTH)
```

---

ce6.refGene.LENGTH    *Transcript length data for the organism ce*

---

### Description

ce6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ce6, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.refGene.LENGTH)
head(ce6.refGene.LENGTH)
```

---

`ce6.xenoRefGene.LENGTH`*Transcript length data for the organism ce*

---

### Description

`ce6.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(ce6, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ce6.xenoRefGene.LENGTH)
head(ce6.xenoRefGene.LENGTH)
```

---

`ci1.geneSymbol.LENGTH` *Transcript length data for the organism ci*

---

### Description

`ci1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(ci1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.geneSymbol.LENGTH)
head(ci1.geneSymbol.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| ci1.refGene.LENGTH | <i>Transcript length data for the organism ci</i> |
|--------------------|---------------------------------------------------|

---

### Description

ci1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.refGene.LENGTH)
head(ci1.refGene.LENGTH)
```

---

|                        |                                                   |
|------------------------|---------------------------------------------------|
| ci1.xenoRefGene.LENGTH | <i>Transcript length data for the organism ci</i> |
|------------------------|---------------------------------------------------|

---

### Description

ci1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci1.xenoRefGene.LENGTH)
head(ci1.xenoRefGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| ci2.ensGene.LENGTH | <i>Transcript length data for the organism ci</i> |
|--------------------|---------------------------------------------------|

---

### Description

ci2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.ensGene.LENGTH)
head(ci2.ensGene.LENGTH)
```

---

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| ci2.geneSymbol.LENGTH | <i>Transcript length data for the organism ci</i> |
|-----------------------|---------------------------------------------------|

---

### Description

ci2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ci2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ci2.geneSymbol.LENGTH)
head(ci2.geneSymbol.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| ci2.refGene.LENGTH | <i>Transcript length data for the organism ci</i> |
|--------------------|---------------------------------------------------|

---

**Description**

ci2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ci2.refGene.LENGTH)
head(ci2.refGene.LENGTH)
```

---

|                        |                                                   |
|------------------------|---------------------------------------------------|
| ci2.xenoRefGene.LENGTH | <i>Transcript length data for the organism ci</i> |
|------------------------|---------------------------------------------------|

---

**Description**

ci2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ci2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(ci2.xenoRefGene.LENGTH)
head(ci2.xenoRefGene.LENGTH)
```

---

`danRer3.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

### Description

`danRer3.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer3.ensGene.LENGTH)
head(danRer3.ensGene.LENGTH)
```

---

`danRer3.geneSymbol.LENGTH`*Transcript length data for the organism danRer*

---

### Description

`danRer3.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer3.geneSymbol.LENGTH)
head(danRer3.geneSymbol.LENGTH)
```

---

`danRer3.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer3, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer3.refGene.LENGTH)
head(danRer3.refGene.LENGTH)
```

---

`danRer4.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.ensGene.LENGTH)
head(danRer4.ensGene.LENGTH)
```

---

```
danRer4.geneSymbol.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer4.geneSymbol.LENGTH)
head(danRer4.geneSymbol.LENGTH)
```

---

```
danRer4.genscan.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer4.genscan.LENGTH)
head(danRer4.genscan.LENGTH)
```

---

`danRer4.nscanGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.nscanGene.LENGTH)
head(danRer4.nscanGene.LENGTH)
```

---

`danRer4.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

danRer4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer4, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer4.refGene.LENGTH)
head(danRer4.refGene.LENGTH)
```

---

`danRer5.ensGene.LENGTH`*Transcript length data for the organism danRer*

---

### Description

`danRer5.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.ensGene.LENGTH)
head(danRer5.ensGene.LENGTH)
```

---

`danRer5.geneSymbol.LENGTH`*Transcript length data for the organism danRer*

---

### Description

`danRer5.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.geneSymbol.LENGTH)
head(danRer5.geneSymbol.LENGTH)
```

---

`danRer5.refGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer5.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.refGene.LENGTH)
head(danRer5.refGene.LENGTH)
```

---

`danRer5.vegaGene.LENGTH`*Transcript length data for the organism danRer*

---

**Description**

`danRer5.vegaGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `vegaGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(danRer5.vegaGene.LENGTH)
head(danRer5.vegaGene.LENGTH)
```

---

```
danRer5.vegaPseudoGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer5.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer5, vegaPseudoGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer5.vegaPseudoGene.LENGTH)
head(danRer5.vegaPseudoGene.LENGTH)
```

---

```
danRer6.ensGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.ensGene.LENGTH)
head(danRer6.ensGene.LENGTH)
```

---

```
danRer6.geneSymbol.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.geneSymbol.LENGTH)
head(danRer6.geneSymbol.LENGTH)
```

---

```
danRer6.refGene.LENGTH
```

*Transcript length data for the organism danRer*

---

### Description

danRer6.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.refGene.LENGTH)
head(danRer6.refGene.LENGTH)
```

---

`danRer6.xenoRefGene.LENGTH`*Transcript length data for the organism danRer*

---

### Description

`danRer6.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(danRer6, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(danRer6.xenoRefGene.LENGTH)
head(danRer6.xenoRefGene.LENGTH)
```

---

`dm1.geneSymbol.LENGTH` *Transcript length data for the organism dm*

---

### Description

`dm1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(dm1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.geneSymbol.LENGTH)
head(dm1.geneSymbol.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| dm1.genscan.LENGTH | <i>Transcript length data for the organism dm</i> |
|--------------------|---------------------------------------------------|

---

### Description

dm1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.genscan.LENGTH)
head(dm1.genscan.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| dm1.refGene.LENGTH | <i>Transcript length data for the organism dm</i> |
|--------------------|---------------------------------------------------|

---

### Description

dm1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm1.refGene.LENGTH)
head(dm1.refGene.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| dm2.geneid.LENGTH | <i>Transcript length data for the organism dm</i> |
|-------------------|---------------------------------------------------|

---

### Description

dm2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.geneid.LENGTH)
head(dm2.geneid.LENGTH)
```

---

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| dm2.geneSymbol.LENGTH | <i>Transcript length data for the organism dm</i> |
|-----------------------|---------------------------------------------------|

---

### Description

dm2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.geneSymbol.LENGTH)
head(dm2.geneSymbol.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| dm2.genscan.LENGTH | <i>Transcript length data for the organism dm</i> |
|--------------------|---------------------------------------------------|

---

### Description

dm2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dm2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.genscan.LENGTH)
head(dm2.genscan.LENGTH)
```

---

|                      |                                                   |
|----------------------|---------------------------------------------------|
| dm2.nscanGene.LENGTH | <i>Transcript length data for the organism dm</i> |
|----------------------|---------------------------------------------------|

---

### Description

dm2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.nscanGene.LENGTH)
head(dm2.nscanGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| dm2.refGene.LENGTH | <i>Transcript length data for the organism dm</i> |
|--------------------|---------------------------------------------------|

---

### Description

dm2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm2.refGene.LENGTH)
head(dm2.refGene.LENGTH)
```

---

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| dm3.geneSymbol.LENGTH | <i>Transcript length data for the organism dm</i> |
|-----------------------|---------------------------------------------------|

---

### Description

dm3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(dm3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dm3.geneSymbol.LENGTH)
head(dm3.geneSymbol.LENGTH)
```

---

`dm3.nscanPasaGene.LENGTH`*Transcript length data for the organism dm*

---

**Description**

dm3.nscanPasaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanPasaGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, nscanPasaGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(dm3.nscanPasaGene.LENGTH)
head(dm3.nscanPasaGene.LENGTH)
```

---

`dm3.refGene.LENGTH`*Transcript length data for the organism dm*

---

**Description**

dm3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(dm3, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(dm3.refGene.LENGTH)
head(dm3.refGene.LENGTH)
```

---

`downloadLengthFromUCSC`*Download Transcript Length Data*

---

**Description**

Attempts to download the length of each transcript for the genome and gene ID specified from the UCSC genome browser.

**Usage**

```
downloadLengthFromUCSC(genome, id)
```

**Arguments**

|                     |                                                                                                                                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <code>genome</code> | A string identifying the genome that genes refer to. For a list of supported organisms see <a href="#">supportedGenomes</a> .           |
| <code>id</code>     | A string identifying the gene identifier used by genes. For a list of supported gene identifiers see <a href="#">supportedGeneIDs</a> . |

**Details**

For each transcript, the UCSC genome browser is used to obtain the exon boundaries. The length of each transcript is then taken to be the sum of the lengths of all its exons. Each transcript is then associated with a gene.

The UCSC does not contain length information for all combinations of genome and gene ID listed by [supportedGeneIDs](#) and [supportedGenomes](#). If `downloadLengthFromUCSC` fails because your gene ID format is not supported for the genome you specified, a list of possible ID formats for the specified genome will be listed.

**Value**

A data.frame containing with three columns, the gene name, transcript identifier and the length of the transcript. Each row represents one transcript.

**Note**

For some genome / gene ID combinations, no gene ID will be provided by UCSC. In this case, the gene name column is set to NA. However, the transcript ID column will always be populated.

**Author(s)**

Matthew D. Young <[myoung@wehi.edu.au](mailto:myoung@wehi.edu.au)>

**See Also**

[supportedGenomes](#), [supportedGeneIDs](#)

**Examples**

```
## Not run:
flat_length <- downloadLengthFromUCSC('hg19', 'ensGene')

## End(Not run)
```

---

dp2.genscan.LENGTH      *Transcript length data for the organism dp*

---

**Description**

dp2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp2, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(dp2.genscan.LENGTH)
head(dp2.genscan.LENGTH)
```

---

dp2.xenoRefGene.LENGTH      *Transcript length data for the organism dp*

---

**Description**

dp2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp2, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(dp2.xenoRefGene.LENGTH)
head(dp2.xenoRefGene.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| dp3.geneid.LENGTH | <i>Transcript length data for the organism dp</i> |
|-------------------|---------------------------------------------------|

---

### Description

dp3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(dp3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.geneid.LENGTH)
head(dp3.geneid.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| dp3.genscan.LENGTH | <i>Transcript length data for the organism dp</i> |
|--------------------|---------------------------------------------------|

---

### Description

dp3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(dp3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.genscan.LENGTH)
head(dp3.genscan.LENGTH)
```

---

```
dp3.xenoRefGene.LENGTH
```

*Transcript length data for the organism dp*

---

### Description

dp3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(dp3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(dp3.xenoRefGene.LENGTH)
head(dp3.xenoRefGene.LENGTH)
```

---

```
droAna1.geneid.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.geneid.LENGTH)
head(droAna1.geneid.LENGTH)
```

---

```
droAna1.genscan.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.genscan.LENGTH)
head(droAna1.genscan.LENGTH)
```

---

```
droAna1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droAna*

---

### Description

droAna1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droAna1.xenoRefGene.LENGTH)
head(droAna1.xenoRefGene.LENGTH)
```

---

`droAna2.genscan.LENGTH`*Transcript length data for the organism droAna*

---

**Description**

droAna2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droAna2.genscan.LENGTH)
head(droAna2.genscan.LENGTH)
```

---

`droAna2.xenoRefGene.LENGTH`*Transcript length data for the organism droAna*

---

**Description**

droAna2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droAna2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droAna2.xenoRefGene.LENGTH)
head(droAna2.xenoRefGene.LENGTH)
```

---

```
droEre1.genscan.LENGTH
```

*Transcript length data for the organism droEre*

---

### Description

droEre1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droEre1.genscan.LENGTH)
head(droEre1.genscan.LENGTH)
```

---

```
droEre1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droEre*

---

### Description

droEre1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droEre1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droEre1.xenoRefGene.LENGTH)
head(droEre1.xenoRefGene.LENGTH)
```

---

`droGri1.genscan.LENGTH`*Transcript length data for the organism droGri*

---

**Description**

droGri1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droGri1.genscan.LENGTH)
head(droGri1.genscan.LENGTH)
```

---

`droGri1.xenoRefGene.LENGTH`*Transcript length data for the organism droGri*

---

**Description**

droGri1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droGri1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droGri1.xenoRefGene.LENGTH)
head(droGri1.xenoRefGene.LENGTH)
```

---

droMoj1.geneid.LENGTH *Transcript length data for the organism droMoj*

---

### Description

droMoj1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj1.geneid.LENGTH)
head(droMoj1.geneid.LENGTH)
```

---

droMoj1.genscan.LENGTH  
*Transcript length data for the organism droMoj*

---

### Description

droMoj1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj1.genscan.LENGTH)
head(droMoj1.genscan.LENGTH)
```

---

`droMoj1.xenoRefGene.LENGTH`*Transcript length data for the organism droMoj*

---

**Description**

droMoj1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj1.xenoRefGene.LENGTH)
head(droMoj1.xenoRefGene.LENGTH)
```

---

`droMoj2.genscan.LENGTH`*Transcript length data for the organism droMoj*

---

**Description**

droMoj2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droMoj2.genscan.LENGTH)
head(droMoj2.genscan.LENGTH)
```

---

```
droMoj2.xenoRefGene.LENGTH
```

*Transcript length data for the organism droMoj*

---

### Description

droMoj2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droMoj2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droMoj2.xenoRefGene.LENGTH)
head(droMoj2.xenoRefGene.LENGTH)
```

---

```
droPer1.genscan.LENGTH
```

*Transcript length data for the organism droPer*

---

### Description

droPer1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droPer1.genscan.LENGTH)
head(droPer1.genscan.LENGTH)
```

---

`droPer1.xenoRefGene.LENGTH`*Transcript length data for the organism droPer*

---

**Description**

droPer1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droPer1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droPer1.xenoRefGene.LENGTH)
head(droPer1.xenoRefGene.LENGTH)
```

---

`droSec1.genscan.LENGTH`*Transcript length data for the organism droSec*

---

**Description**

droSec1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droSec1.genscan.LENGTH)
head(droSec1.genscan.LENGTH)
```

---

```
droSec1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droSec*

---

### Description

droSec1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSec1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSec1.xenoRefGene.LENGTH)
head(droSec1.xenoRefGene.LENGTH)
```

---

```
droSim1.geneid.LENGTH
```

*Transcript length data for the organism droSim*

---

### Description

droSim1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.geneid.LENGTH)
head(droSim1.geneid.LENGTH)
```

---

`droSim1.genscan.LENGTH`*Transcript length data for the organism droSim*

---

### Description

droSim1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.genscan.LENGTH)
head(droSim1.genscan.LENGTH)
```

---

`droSim1.xenoRefGene.LENGTH`*Transcript length data for the organism droSim*

---

### Description

droSim1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droSim1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droSim1.xenoRefGene.LENGTH)
head(droSim1.xenoRefGene.LENGTH)
```

---

droVir1.geneid.LENGTH *Transcript length data for the organism droVir*

---

### Description

droVir1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir1.geneid.LENGTH)
head(droVir1.geneid.LENGTH)
```

---

droVir1.genscan.LENGTH  
*Transcript length data for the organism droVir*

---

### Description

droVir1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir1.genscan.LENGTH)
head(droVir1.genscan.LENGTH)
```

---

`droVir1.xenoRefGene.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droVir1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir1.xenoRefGene.LENGTH)
head(droVir1.xenoRefGene.LENGTH)
```

---

`droVir2.genscan.LENGTH`*Transcript length data for the organism droVir*

---

**Description**

droVir2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(droVir2.genscan.LENGTH)
head(droVir2.genscan.LENGTH)
```

---

`droVir2.xenoRefGene.LENGTH`*Transcript length data for the organism droVir*

---

### Description

`droVir2.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(droVir2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droVir2.xenoRefGene.LENGTH)
head(droVir2.xenoRefGene.LENGTH)
```

---

`droYak1.geneid.LENGTH` *Transcript length data for the organism droYak*

---

### Description

`droYak1.geneid.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneid` table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.geneid.LENGTH)
head(droYak1.geneid.LENGTH)
```

---

```
droYak1.genscan.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.genscan.LENGTH)
head(droYak1.genscan.LENGTH)
```

---

```
droYak1.xenoRefGene.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak1.xenoRefGene.LENGTH)
head(droYak1.xenoRefGene.LENGTH)
```

---

```
droYak2.genscan.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak2.genscan.LENGTH)
head(droYak2.genscan.LENGTH)
```

---

```
droYak2.xenoRefGene.LENGTH
```

*Transcript length data for the organism droYak*

---

### Description

droYak2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(droYak2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(droYak2.xenoRefGene.LENGTH)
head(droYak2.xenoRefGene.LENGTH)
```

---

equCab1.geneid.LENGTH *Transcript length data for the organism equCab*

---

### Description

equCab1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab1.geneid.LENGTH)
head(equCab1.geneid.LENGTH)
```

---

equCab1.geneSymbol.LENGTH  
*Transcript length data for the organism equCab*

---

### Description

equCab1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(equCab1.geneSymbol.LENGTH)
head(equCab1.geneSymbol.LENGTH)
```

---

`equCab1.nscanGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab1.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.nscanGene.LENGTH)
head(equCab1.nscanGene.LENGTH)
```

---

`equCab1.refGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab1.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.refGene.LENGTH)
head(equCab1.refGene.LENGTH)
```

---

`equCab1.sgpGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab1.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab1, sgpGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab1.sgpGene.LENGTH)
head(equCab1.sgpGene.LENGTH)
```

---

`equCab2.ensGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.ensGene.LENGTH)
head(equCab2.ensGene.LENGTH)
```

---

`equCab2.geneSymbol.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.geneSymbol.LENGTH)
head(equCab2.geneSymbol.LENGTH)
```

---

`equCab2.nscanGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

`equCab2.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.nscanGene.LENGTH)
head(equCab2.nscanGene.LENGTH)
```

---

`equCab2.refGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.refGene.LENGTH)
head(equCab2.refGene.LENGTH)
```

---

`equCab2.xenoRefGene.LENGTH`*Transcript length data for the organism equCab*

---

**Description**

equCab2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(equCab2, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(equCab2.xenoRefGene.LENGTH)
head(equCab2.xenoRefGene.LENGTH)
```

---

`felCat3.ensGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, ensGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(felCat3.ensGene.LENGTH)
head(felCat3.ensGene.LENGTH)
```

---

`felCat3.geneid.LENGTH` *Transcript length data for the organism felCat*

---

**Description**

felCat3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneid)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(felCat3.geneid.LENGTH)
head(felCat3.geneid.LENGTH)
```

---

```
felCat3.geneSymbol.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.geneSymbol.LENGTH)
head(felCat3.geneSymbol.LENGTH)
```

---

```
felCat3.genscan.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.genscan.LENGTH)
head(felCat3.genscan.LENGTH)
```

---

```
felCat3.nscanGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.nscanGene.LENGTH)
head(felCat3.nscanGene.LENGTH)
```

---

```
felCat3.refGene.LENGTH
```

*Transcript length data for the organism felCat*

---

### Description

felCat3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(felCat3.refGene.LENGTH)
head(felCat3.refGene.LENGTH)
```

---

`felCat3.sgpGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, sgpGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.sgpGene.LENGTH)
head(felCat3.sgpGene.LENGTH)
```

---

`felCat3.xenoRefGene.LENGTH`*Transcript length data for the organism felCat*

---

**Description**

felCat3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(felCat3, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(felCat3.xenoRefGene.LENGTH)
head(felCat3.xenoRefGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| fr1.ensGene.LENGTH | <i>Transcript length data for the organism fr</i> |
|--------------------|---------------------------------------------------|

---

### Description

fr1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr1.ensGene.LENGTH)
head(fr1.ensGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| fr1.genscan.LENGTH | <i>Transcript length data for the organism fr</i> |
|--------------------|---------------------------------------------------|

---

### Description

fr1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(fr1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr1.genscan.LENGTH)
head(fr1.genscan.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| fr2.ensGene.LENGTH | <i>Transcript length data for the organism fr</i> |
|--------------------|---------------------------------------------------|

---

### Description

fr2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(fr2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(fr2.ensGene.LENGTH)
head(fr2.ensGene.LENGTH)
```

---

|                        |                                                       |
|------------------------|-------------------------------------------------------|
| galGal2.ensGene.LENGTH | <i>Transcript length data for the organism galGal</i> |
|------------------------|-------------------------------------------------------|

---

### Description

galGal2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.ensGene.LENGTH)
head(galGal2.ensGene.LENGTH)
```

---

galGal2.geneid.LENGTH    *Transcript length data for the organism galGal*

---

### Description

galGal2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.geneid.LENGTH)
head(galGal2.geneid.LENGTH)
```

---

galGal2.geneSymbol.LENGTH  
                                  *Transcript length data for the organism galGal*

---

### Description

galGal2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.geneSymbol.LENGTH)
head(galGal2.geneSymbol.LENGTH)
```

---

`galGal2.genscan.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(galGal2.genscan.LENGTH)
head(galGal2.genscan.LENGTH)
```

---

`galGal2.refGene.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(galGal2.refGene.LENGTH)
head(galGal2.refGene.LENGTH)
```

---

```
galGal2.sgpGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal2, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal2.sgpGene.LENGTH)
head(galGal2.sgpGene.LENGTH)
```

---

```
galGal3.ensGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.ensGene.LENGTH)
head(galGal3.ensGene.LENGTH)
```

---

`galGal3.geneSymbol.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(galGal3.geneSymbol.LENGTH)
head(galGal3.geneSymbol.LENGTH)
```

---

`galGal3.genscan.LENGTH`*Transcript length data for the organism galGal*

---

**Description**

galGal3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(galGal3.genscan.LENGTH)
head(galGal3.genscan.LENGTH)
```

---

```
galGal3.nscanGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.nscanGene.LENGTH)
head(galGal3.nscanGene.LENGTH)
```

---

```
galGal3.refGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.refGene.LENGTH)
head(galGal3.refGene.LENGTH)
```

---

```
galGal3.xenoRefGene.LENGTH
```

*Transcript length data for the organism galGal*

---

### Description

galGal3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(galGal3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(galGal3.xenoRefGene.LENGTH)
head(galGal3.xenoRefGene.LENGTH)
```

---

```
gasAcu1.ensGene.LENGTH
```

*Transcript length data for the organism gasAcu*

---

### Description

gasAcu1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(gasAcu1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(gasAcu1.ensGene.LENGTH)
head(gasAcu1.ensGene.LENGTH)
```

---

```
gasAcu1.nscanGene.LENGTH
```

*Transcript length data for the organism gasAcu*

---

### Description

gasAcu1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling downloadLengthFromUCSC(gasAcu1, nscanGene) on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(gasAcu1.nscanGene.LENGTH)
head(gasAcu1.nscanGene.LENGTH)
```

---

```
geneLenDatabase-pkg    geneLenDatabase:
```

---

### Description

Lengths of mRNA transcripts for a number of genomes

### Details

Length of mRNA transcripts for a number of genomes and gene ID formats, largely based on UCSC table browser. Data objects are provided as individual pieces of information to be retrieved and loaded. A variety of different gene identifiers and genomes is supported to ensure wide applicability.

### Author(s)

**Maintainer:** Federico Marini <marinif@uni-mainz.de> ([ORCID](#)) [contributor]

Authors:

- Matthew Young <my4@sanger.ac.uk>
- Nadia Davidson <nadia.davidson@mcri.edu.au>

### See Also

Useful links:

- <https://github.com/federicomarini/geneLenDataBase>
- Report bugs at <https://github.com/federicomarini/geneLenDataBase/issues>

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg16.acembly.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

### Description

hg16.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg16, acembly)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.acembly.LENGTH)
head(hg16.acembly.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg16.ensGene.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

### Description

hg16.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.ensGene.LENGTH)
head(hg16.ensGene.LENGTH)
```

---

hg16.exoniphy.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg16, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.exoniphy.LENGTH)
head(hg16.exoniphy.LENGTH)
```

---

hg16.geneid.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.geneid.LENGTH)
head(hg16.geneid.LENGTH)
```

---

`hg16.geneSymbol.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg16.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg16, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg16.geneSymbol.LENGTH)
head(hg16.geneSymbol.LENGTH)
```

---

`hg16.genscan.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg16.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg16, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg16.genscan.LENGTH)
head(hg16.genscan.LENGTH)
```

---

hg16.knownGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.knownGene.LENGTH)
head(hg16.knownGene.LENGTH)
```

---

hg16.refGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg16.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg16.refGene.LENGTH)
head(hg16.refGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg16.sgpGene.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

**Description**

hg16.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg16, sgpGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg16.sgpGene.LENGTH)
head(hg16.sgpGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg17.acembly.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

**Description**

hg17.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acembly)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.acembly.LENGTH)
head(hg17.acembly.LENGTH)
```

---

hg17.acescan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, acescan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.acescan.LENGTH)
head(hg17.acescan.LENGTH)
```

---

hg17.ccdsGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.ccdsGene.LENGTH)
head(hg17.ccdsGene.LENGTH)
```

---

hg17.ensGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.ensGene.LENGTH)
head(hg17.ensGene.LENGTH)
```

---

hg17.exoniphy.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg17.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg17, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.exoniphy.LENGTH)
head(hg17.exoniphy.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| hg17.geneid.LENGTH | <i>Transcript length data for the organism hg</i> |
|--------------------|---------------------------------------------------|

---

### Description

hg17.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.geneid.LENGTH)
head(hg17.geneid.LENGTH)
```

---

|                        |                                                   |
|------------------------|---------------------------------------------------|
| hg17.geneSymbol.LENGTH | <i>Transcript length data for the organism hg</i> |
|------------------------|---------------------------------------------------|

---

### Description

hg17.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg17, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.geneSymbol.LENGTH)
head(hg17.geneSymbol.LENGTH)
```

---

hg17.genscan.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg17.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg17, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.genscan.LENGTH)
head(hg17.genscan.LENGTH)
```

---

hg17.knownGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg17.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.knownGene.LENGTH)
head(hg17.knownGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg17.refGene.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

### Description

hg17.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.refGene.LENGTH)
head(hg17.refGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg17.sgpGene.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

### Description

hg17.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.sgpGene.LENGTH)
head(hg17.sgpGene.LENGTH)
```

---

hg17.vegaGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg17.vegaGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.vegaGene.LENGTH)
head(hg17.vegaGene.LENGTH)
```

---

hg17.vegaPseudoGene.LENGTH  
                                  *Transcript length data for the organism hg*

---

### Description

hg17.vegaPseudoGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the vegaPseudoGene table.

The data file was made by calling `downloadLengthFromUCSC(hg17, vegaPseudoGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg17.vegaPseudoGene.LENGTH)
head(hg17.vegaPseudoGene.LENGTH)
```

---

`hg17.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

`hg17.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(hg17, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg17.xenoRefGene.LENGTH)
head(hg17.xenoRefGene.LENGTH)
```

---

`hg18.acembly.LENGTH`*Transcript length data for the organism hg*

---

**Description**

`hg18.acembly.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `acembly` table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acembly)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg18.acembly.LENGTH)
head(hg18.acembly.LENGTH)
```

---

hg18.acescan.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.acescan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acescan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, acescan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.acescan.LENGTH)
head(hg18.acescan.LENGTH)
```

---

hg18.ccdsGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.ccdsGene.LENGTH)
head(hg18.ccdsGene.LENGTH)
```

---

hg18.ensGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.ensGene.LENGTH)
head(hg18.ensGene.LENGTH)
```

---

hg18.exoniphy.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg18.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg18, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.exoniphy.LENGTH)
head(hg18.exoniphy.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| hg18.geneid.LENGTH | <i>Transcript length data for the organism hg</i> |
|--------------------|---------------------------------------------------|

---

### Description

hg18.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.geneid.LENGTH)
head(hg18.geneid.LENGTH)
```

---

|                        |                                                   |
|------------------------|---------------------------------------------------|
| hg18.geneSymbol.LENGTH | <i>Transcript length data for the organism hg</i> |
|------------------------|---------------------------------------------------|

---

### Description

hg18.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg18, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.geneSymbol.LENGTH)
head(hg18.geneSymbol.LENGTH)
```

---

hg18.genscan.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg18.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(hg18, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.genscan.LENGTH)
head(hg18.genscan.LENGTH)
```

---

hg18.knownGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg18.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.knownGene.LENGTH)
head(hg18.knownGene.LENGTH)
```

---

`hg18.knownGeneOld3.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.knownGeneOld3.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGeneOld3 table.

The data file was made by calling `downloadLengthFromUCSC(hg18, knownGeneOld3)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg18.knownGeneOld3.LENGTH)
head(hg18.knownGeneOld3.LENGTH)
```

---

`hg18.refGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(hg18.refGene.LENGTH)
head(hg18.refGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg18.sgpGene.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

### Description

hg18.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.sgpGene.LENGTH)
head(hg18.sgpGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| hg18.sibGene.LENGTH | <i>Transcript length data for the organism hg</i> |
|---------------------|---------------------------------------------------|

---

### Description

hg18.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, sibGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg18.sibGene.LENGTH)
head(hg18.sibGene.LENGTH)
```

---

`hg18.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg18.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg18, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg18.xenoRefGene.LENGTH)
head(hg18.xenoRefGene.LENGTH)
```

---

`hg19.ccdsGene.LENGTH` *Transcript length data for the organism hg*

---

**Description**

hg19.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ccdsGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg19.ccdsGene.LENGTH)
head(hg19.ccdsGene.LENGTH)
```

---

hg19.ensGene.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg19.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.ensGene.LENGTH)
head(hg19.ensGene.LENGTH)
```

---

hg19.exoniphy.LENGTH     *Transcript length data for the organism hg*

---

### Description

hg19.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(hg19, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.exoniphy.LENGTH)
head(hg19.exoniphy.LENGTH)
```

---

`hg19.geneSymbol.LENGTH`*Transcript length data for the organism hg*

---

**Description**

hg19.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(hg19, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg19.geneSymbol.LENGTH)
head(hg19.geneSymbol.LENGTH)
```

---

`hg19.knownGene.LENGTH` *Transcript length data for the organism hg*

---

**Description**

hg19.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, knownGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(hg19.knownGene.LENGTH)
head(hg19.knownGene.LENGTH)
```

---

hg19.nscanGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg19.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.nscanGene.LENGTH)
head(hg19.nscanGene.LENGTH)
```

---

hg19.refGene.LENGTH    *Transcript length data for the organism hg*

---

### Description

hg19.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.refGene.LENGTH)
head(hg19.refGene.LENGTH)
```

---

`hg19.xenoRefGene.LENGTH`*Transcript length data for the organism hg*

---

### Description

hg19.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(hg19, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(hg19.xenoRefGene.LENGTH)
head(hg19.xenoRefGene.LENGTH)
```

---

`loxAfr3.xenoRefGene.LENGTH`*Transcript length data for the organism loxAfr*

---

### Description

loxAfr3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(loxAfr3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(loxAfr3.xenoRefGene.LENGTH)
head(loxAfr3.xenoRefGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm7.ensGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm7.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.ensGene.LENGTH)
head(mm7.ensGene.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| mm7.geneid.LENGTH | <i>Transcript length data for the organism mm</i> |
|-------------------|---------------------------------------------------|

---

### Description

mm7.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.geneid.LENGTH)
head(mm7.geneid.LENGTH)
```

---

mm7.geneSymbol.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm7, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.geneSymbol.LENGTH)
head(mm7.geneSymbol.LENGTH)
```

---

mm7.genscan.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm7, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.genscan.LENGTH)
head(mm7.genscan.LENGTH)
```

---

mm7.knownGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.knownGene.LENGTH)
head(mm7.knownGene.LENGTH)
```

---

mm7.refGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm7.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.refGene.LENGTH)
head(mm7.refGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm7.sgpGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm7.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.sgpGene.LENGTH)
head(mm7.sgpGene.LENGTH)
```

---

|                        |                                                   |
|------------------------|---------------------------------------------------|
| mm7.xenoRefGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|------------------------|---------------------------------------------------|

---

### Description

mm7.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm7, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm7.xenoRefGene.LENGTH)
head(mm7.xenoRefGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| mm8.ccdsGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|---------------------|---------------------------------------------------|

---

### Description

mm8.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.ccdsGene.LENGTH)
head(mm8.ccdsGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm8.ensGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm8.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.ensGene.LENGTH)
head(mm8.ensGene.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| mm8.geneid.LENGTH | <i>Transcript length data for the organism mm</i> |
|-------------------|---------------------------------------------------|

---

### Description

mm8.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.geneid.LENGTH)
head(mm8.geneid.LENGTH)
```

---

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| mm8.geneSymbol.LENGTH | <i>Transcript length data for the organism mm</i> |
|-----------------------|---------------------------------------------------|

---

### Description

mm8.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm8, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.geneSymbol.LENGTH)
head(mm8.geneSymbol.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm8.genscan.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm8.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm8, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.genscan.LENGTH)
head(mm8.genscan.LENGTH)
```

---

|                      |                                                   |
|----------------------|---------------------------------------------------|
| mm8.knownGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|----------------------|---------------------------------------------------|

---

### Description

mm8.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.knownGene.LENGTH)
head(mm8.knownGene.LENGTH)
```

---

mm8.nscanGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm8.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.nscanGene.LENGTH)
head(mm8.nscanGene.LENGTH)
```

---

mm8.refGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm8.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.refGene.LENGTH)
head(mm8.refGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm8.sgpGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm8.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.sgpGene.LENGTH)
head(mm8.sgpGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm8.sibGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm8.sibGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sibGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, sibGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.sibGene.LENGTH)
head(mm8.sibGene.LENGTH)
```

---

`mm8.xenoRefGene.LENGTH`*Transcript length data for the organism mm*

---

### Description

mm8.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm8, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm8.xenoRefGene.LENGTH)
head(mm8.xenoRefGene.LENGTH)
```

---

`mm9.acembly.LENGTH`*Transcript length data for the organism mm*

---

### Description

mm9.acembly.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the acembly table.

The data file was made by calling `downloadLengthFromUCSC(mm9, acembly)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.acembly.LENGTH)
head(mm9.acembly.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| mm9.ccdsGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|---------------------|---------------------------------------------------|

---

### Description

mm9.ccdsGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ccdsGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ccdsGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.ccdsGene.LENGTH)
head(mm9.ccdsGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm9.ensGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm9.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.ensGene.LENGTH)
head(mm9.ensGene.LENGTH)
```

---

|                     |                                                   |
|---------------------|---------------------------------------------------|
| mm9.exoniphy.LENGTH | <i>Transcript length data for the organism mm</i> |
|---------------------|---------------------------------------------------|

---

### Description

mm9.exoniphy.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the exoniphy table.

The data file was made by calling `downloadLengthFromUCSC(mm9, exoniphy)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.exoniphy.LENGTH)
head(mm9.exoniphy.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| mm9.geneid.LENGTH | <i>Transcript length data for the organism mm</i> |
|-------------------|---------------------------------------------------|

---

### Description

mm9.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.geneid.LENGTH)
head(mm9.geneid.LENGTH)
```

---

mm9.geneSymbol.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(mm9, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.geneSymbol.LENGTH)
head(mm9.geneSymbol.LENGTH)
```

---

mm9.genscan.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(mm9, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.genscan.LENGTH)
head(mm9.genscan.LENGTH)
```

---

mm9.knownGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.knownGene.LENGTH)
head(mm9.knownGene.LENGTH)
```

---

mm9.nscanGene.LENGTH    *Transcript length data for the organism mm*

---

### Description

mm9.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.nscanGene.LENGTH)
head(mm9.nscanGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm9.refGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm9.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.refGene.LENGTH)
head(mm9.refGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| mm9.sgpGene.LENGTH | <i>Transcript length data for the organism mm</i> |
|--------------------|---------------------------------------------------|

---

### Description

mm9.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(mm9.sgpGene.LENGTH)
head(mm9.sgpGene.LENGTH)
```

---

`mm9.xenoRefGene.LENGTH`*Transcript length data for the organism mm*

---

**Description**

mm9.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(mm9, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(mm9.xenoRefGene.LENGTH)
head(mm9.xenoRefGene.LENGTH)
```

---

`monDom1.genscan.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

monDom1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(monDom1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(monDom1.genscan.LENGTH)
head(monDom1.genscan.LENGTH)
```

---

`monDom4.ensGene.LENGTH`*Transcript length data for the organism monDom*

---

### Description

`monDom4.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.ensGene.LENGTH)
head(monDom4.ensGene.LENGTH)
```

---

`monDom4.geneSymbol.LENGTH`*Transcript length data for the organism monDom*

---

### Description

`monDom4.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom4.geneSymbol.LENGTH)
head(monDom4.geneSymbol.LENGTH)
```

---

`monDom4.genscan.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.genscan.LENGTH)
head(monDom4.genscan.LENGTH)
```

---

`monDom4.nscanGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.nscanGene.LENGTH)
head(monDom4.nscanGene.LENGTH)
```

---

`monDom4.refGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.refGene.LENGTH)
head(monDom4.refGene.LENGTH)
```

---

`monDom4.xenoRefGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom4.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom4, xenoRefGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom4.xenoRefGene.LENGTH)
head(monDom4.xenoRefGene.LENGTH)
```

---

`monDom5.ensGene.LENGTH`*Transcript length data for the organism monDom*

---

### Description

`monDom5.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.ensGene.LENGTH)
head(monDom5.ensGene.LENGTH)
```

---

`monDom5.geneSymbol.LENGTH`*Transcript length data for the organism monDom*

---

### Description

`monDom5.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(monDom5.geneSymbol.LENGTH)
head(monDom5.geneSymbol.LENGTH)
```

---

`monDom5.genscan.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.genscan.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `genscan` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, genscan)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.genscan.LENGTH)
head(monDom5.genscan.LENGTH)
```

---

`monDom5.nscanGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, nscanGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(monDom5.nscanGene.LENGTH)
head(monDom5.nscanGene.LENGTH)
```

---

`monDom5.refGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(monDom5.refGene.LENGTH)
head(monDom5.refGene.LENGTH)
```

---

`monDom5.xenoRefGene.LENGTH`*Transcript length data for the organism monDom*

---

**Description**

`monDom5.xenoRefGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `xenoRefGene` table.

The data file was made by calling `downloadLengthFromUCSC(monDom5, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(monDom5.xenoRefGene.LENGTH)
head(monDom5.xenoRefGene.LENGTH)
```

---

`ornAna1.ensGene.LENGTH`*Transcript length data for the organism ornAna*

---

### Description

`ornAna1.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ornAna1.ensGene.LENGTH)
head(ornAna1.ensGene.LENGTH)
```

---

`ornAna1.geneSymbol.LENGTH`*Transcript length data for the organism ornAna*

---

### Description

`ornAna1.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ornAna1.geneSymbol.LENGTH)
head(ornAna1.geneSymbol.LENGTH)
```

---

`ornAna1.refGene.LENGTH`*Transcript length data for the organism ornAna*

---

**Description**

ornAna1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ornAna1.refGene.LENGTH)
head(ornAna1.refGene.LENGTH)
```

---

`ornAna1.xenoRefGene.LENGTH`*Transcript length data for the organism ornAna*

---

**Description**

ornAna1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ornAna1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ornAna1.xenoRefGene.LENGTH)
head(ornAna1.xenoRefGene.LENGTH)
```

---

`oryLat2.ensGene.LENGTH`*Transcript length data for the organism oryLat*

---

### Description

`oryLat2.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.ensGene.LENGTH)
head(oryLat2.ensGene.LENGTH)
```

---

`oryLat2.geneSymbol.LENGTH`*Transcript length data for the organism oryLat*

---

### Description

`oryLat2.geneSymbol.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `geneSymbol` table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.geneSymbol.LENGTH)
head(oryLat2.geneSymbol.LENGTH)
```

---

```
oryLat2.refGene.LENGTH
```

*Transcript length data for the organism oryLat*

---

### Description

oryLat2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.refGene.LENGTH)
head(oryLat2.refGene.LENGTH)
```

---

```
oryLat2.xenoRefGene.LENGTH
```

*Transcript length data for the organism oryLat*

---

### Description

oryLat2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(oryLat2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(oryLat2.xenoRefGene.LENGTH)
head(oryLat2.xenoRefGene.LENGTH)
```

---

```
panTro1.ensGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro1.ensGene.LENGTH)
head(panTro1.ensGene.LENGTH)
```

---

```
panTro1.geneid.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro1.geneid.LENGTH)
head(panTro1.geneid.LENGTH)
```

---

`panTro1.genscan.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro1.genscan.LENGTH)
head(panTro1.genscan.LENGTH)
```

---

`panTro1.xenoRefGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro1, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro1.xenoRefGene.LENGTH)
head(panTro1.xenoRefGene.LENGTH)
```

---

```
panTro2.ensGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.ensGene.LENGTH)
head(panTro2.ensGene.LENGTH)
```

---

```
panTro2.geneSymbol.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.geneSymbol.LENGTH)
head(panTro2.geneSymbol.LENGTH)
```

---

`panTro2.genscan.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.genscan.LENGTH)
head(panTro2.genscan.LENGTH)
```

---

`panTro2.nscanGene.LENGTH`*Transcript length data for the organism panTro*

---

**Description**

panTro2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(panTro2.nscanGene.LENGTH)
head(panTro2.nscanGene.LENGTH)
```

---

```
panTro2.refGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.refGene.LENGTH)
head(panTro2.refGene.LENGTH)
```

---

```
panTro2.xenoRefGene.LENGTH
```

*Transcript length data for the organism panTro*

---

### Description

panTro2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(panTro2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(panTro2.xenoRefGene.LENGTH)
head(panTro2.xenoRefGene.LENGTH)
```

---

```
petMar1.xenoRefGene.LENGTH
```

*Transcript length data for the organism petMar*

---

### Description

petMar1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(petMar1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(petMar1.xenoRefGene.LENGTH)
head(petMar1.xenoRefGene.LENGTH)
```

---

```
ponAbe2.ensGene.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.ensGene.LENGTH)
head(ponAbe2.ensGene.LENGTH)
```

ponAbe2.geneSymbol.LENGTH

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.geneSymbol.LENGTH)
head(ponAbe2.geneSymbol.LENGTH)
```

---

ponAbe2.genscan.LENGTH

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.genscan.LENGTH)
head(ponAbe2.genscan.LENGTH)
```

---

`ponAbe2.nscanGene.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.nscanGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `nscanGene` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, nscanGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.nscanGene.LENGTH)
head(ponAbe2.nscanGene.LENGTH)
```

---

`ponAbe2.refGene.LENGTH`*Transcript length data for the organism ponAbe*

---

**Description**

`ponAbe2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(ponAbe2.refGene.LENGTH)
head(ponAbe2.refGene.LENGTH)
```

---

```
ponAbe2.xenoRefGene.LENGTH
```

*Transcript length data for the organism ponAbe*

---

### Description

ponAbe2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(ponAbe2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(ponAbe2.xenoRefGene.LENGTH)
head(ponAbe2.xenoRefGene.LENGTH)
```

---

```
priPac1.xenoRefGene.LENGTH
```

*Transcript length data for the organism priPac*

---

### Description

priPac1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(priPac1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(priPac1.xenoRefGene.LENGTH)
head(priPac1.xenoRefGene.LENGTH)
```

---

```
rheMac2.ensGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.ensGene.LENGTH)
head(rheMac2.ensGene.LENGTH)
```

---

```
rheMac2.geneid.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.geneid.LENGTH)
head(rheMac2.geneid.LENGTH)
```

---

```
rheMac2.geneSymbol.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.geneSymbol.LENGTH)
head(rheMac2.geneSymbol.LENGTH)
```

---

```
rheMac2.nscanGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.nscanGene.LENGTH)
head(rheMac2.nscanGene.LENGTH)
```

---

```
rheMac2.refGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.refGene.LENGTH)
head(rheMac2.refGene.LENGTH)
```

---

```
rheMac2.sgpGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.sgpGene.LENGTH)
head(rheMac2.sgpGene.LENGTH)
```

---

```
rheMac2.xenoRefGene.LENGTH
```

*Transcript length data for the organism rheMac*

---

### Description

rheMac2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rheMac2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rheMac2.xenoRefGene.LENGTH)
head(rheMac2.xenoRefGene.LENGTH)
```

---

```
rn3.ensGene.LENGTH
```

*Transcript length data for the organism rn*

---

### Description

rn3.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.ensGene.LENGTH)
head(rn3.ensGene.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| rn3.geneid.LENGTH | <i>Transcript length data for the organism rn</i> |
|-------------------|---------------------------------------------------|

---

### Description

rn3.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.geneid.LENGTH)
head(rn3.geneid.LENGTH)
```

---

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| rn3.geneSymbol.LENGTH | <i>Transcript length data for the organism rn</i> |
|-----------------------|---------------------------------------------------|

---

### Description

rn3.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn3, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.geneSymbol.LENGTH)
head(rn3.geneSymbol.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| rn3.genscan.LENGTH | <i>Transcript length data for the organism rn</i> |
|--------------------|---------------------------------------------------|

---

### Description

rn3.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn3, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.genscan.LENGTH)
head(rn3.genscan.LENGTH)
```

---

|                      |                                                   |
|----------------------|---------------------------------------------------|
| rn3.knownGene.LENGTH | <i>Transcript length data for the organism rn</i> |
|----------------------|---------------------------------------------------|

---

### Description

rn3.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.knownGene.LENGTH)
head(rn3.knownGene.LENGTH)
```

---

rn3.nscanGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn3.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.nscanGene.LENGTH)
head(rn3.nscanGene.LENGTH)
```

---

rn3.refGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn3.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.refGene.LENGTH)
head(rn3.refGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| rn3.sgpGene.LENGTH | <i>Transcript length data for the organism rn</i> |
|--------------------|---------------------------------------------------|

---

### Description

rn3.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.sgpGene.LENGTH)
head(rn3.sgpGene.LENGTH)
```

---

|                        |                                                   |
|------------------------|---------------------------------------------------|
| rn3.xenoRefGene.LENGTH | <i>Transcript length data for the organism rn</i> |
|------------------------|---------------------------------------------------|

---

### Description

rn3.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn3, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn3.xenoRefGene.LENGTH)
head(rn3.xenoRefGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| rn4.ensGene.LENGTH | <i>Transcript length data for the organism rn</i> |
|--------------------|---------------------------------------------------|

---

### Description

rn4.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.ensGene.LENGTH)
head(rn4.ensGene.LENGTH)
```

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| rn4.geneid.LENGTH | <i>Transcript length data for the organism rn</i> |
|-------------------|---------------------------------------------------|

---

### Description

rn4.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.geneid.LENGTH)
head(rn4.geneid.LENGTH)
```

---

rn4.geneSymbol.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(rn4, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.geneSymbol.LENGTH)
head(rn4.geneSymbol.LENGTH)
```

---

rn4.genscan.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(rn4, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.genscan.LENGTH)
head(rn4.genscan.LENGTH)
```

---

rn4.knownGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.knownGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the knownGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, knownGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.knownGene.LENGTH)
head(rn4.knownGene.LENGTH)
```

---

rn4.nscanGene.LENGTH    *Transcript length data for the organism rn*

---

### Description

rn4.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.nscanGene.LENGTH)
head(rn4.nscanGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| rn4.refGene.LENGTH | <i>Transcript length data for the organism rn</i> |
|--------------------|---------------------------------------------------|

---

### Description

rn4.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.refGene.LENGTH)
head(rn4.refGene.LENGTH)
```

---

|                    |                                                   |
|--------------------|---------------------------------------------------|
| rn4.sgpGene.LENGTH | <i>Transcript length data for the organism rn</i> |
|--------------------|---------------------------------------------------|

---

### Description

rn4.sgpGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the sgpGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, sgpGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(rn4.sgpGene.LENGTH)
head(rn4.sgpGene.LENGTH)
```

---

`rn4.xenoRefGene.LENGTH`*Transcript length data for the organism rn*

---

**Description**

rn4.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(rn4, xenoRefGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(rn4.xenoRefGene.LENGTH)
head(rn4.xenoRefGene.LENGTH)
```

---

`sacCer1.ensGene.LENGTH`*Transcript length data for the organism sacCer*

---

**Description**

sacCer1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(sacCer1.ensGene.LENGTH)
head(sacCer1.ensGene.LENGTH)
```

---

```
sacCer2.ensGene.LENGTH
```

*Transcript length data for the organism sacCer*

---

### Description

sacCer2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(sacCer2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(sacCer2.ensGene.LENGTH)
head(sacCer2.ensGene.LENGTH)
```

---

```
strPur1.geneSymbol.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur1.geneSymbol.LENGTH)
head(strPur1.geneSymbol.LENGTH)
```

---

`strPur1.genscan.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur1.genscan.LENGTH)
head(strPur1.genscan.LENGTH)
```

---

`strPur1.refGene.LENGTH`*Transcript length data for the organism strPur*

---

**Description**

strPur1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, refGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(strPur1.refGene.LENGTH)
head(strPur1.refGene.LENGTH)
```

---

```
strPur1.xenoRefGene.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur1.xenoRefGene.LENGTH)
head(strPur1.xenoRefGene.LENGTH)
```

---

```
strPur2.geneSymbol.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, geneSymbol)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.geneSymbol.LENGTH)
head(strPur2.geneSymbol.LENGTH)
```

---

`strPur2.genscan.LENGTH`*Transcript length data for the organism strPur*

---

### Description

strPur2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.genscan.LENGTH)
head(strPur2.genscan.LENGTH)
```

---

`strPur2.refGene.LENGTH`*Transcript length data for the organism strPur*

---

### Description

strPur2.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.refGene.LENGTH)
head(strPur2.refGene.LENGTH)
```

---

```
strPur2.xenoRefGene.LENGTH
```

*Transcript length data for the organism strPur*

---

### Description

strPur2.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(strPur2, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(strPur2.xenoRefGene.LENGTH)
head(strPur2.xenoRefGene.LENGTH)
```

---

```
supportedGeneIDs
```

*Supported Gene IDs*

---

### Description

Lists supported gene ID formats

### Usage

```
supportedGeneIDs()
```

### Details

Uses the `supportedUCSCTables` function from the `GenomicFeatures` package to obtain a list of gene ID formats available from the UCSC genome browser. The `db` column gives the gene ID formats which are provided to the `id` argument of various functions. The `track` and `subtrack` columns are the names of the UCSC track/subtrack from which information is fetched.

The `GeneID` column lists the "full name" of the gene ID format where available.

The final column, headed `AvailableGenomes` lists the genomes for which there is a local copy of the length information available for the gene ID format listed in the `geneLenDataBase` package.

### Value

A data.frame containing supported gene ID formats.

### Author(s)

Matthew D. Young <[myoung@wehi.edu.au](mailto:myoung@wehi.edu.au)>

**Examples**

```
supportedGeneIDs()
```

---

|                  |                          |
|------------------|--------------------------|
| supportedGenomes | <i>Supported Genomes</i> |
|------------------|--------------------------|

---

**Description**

Lists supported genomes

**Usage**

```
supportedGenomes()
```

**Details**

Uses the `ucscGenomes()` function from the `rtracklayer` package to obtain a list of genomes available from the UCSC genome browser. The `db` column lists genomes as they are provided to the genome argument of various functions.

The final column, headed `AvailableGeneIDs` lists the gene ID formats for which there is a local copy of the length information available for the genome listed in the `geneLenDataBase` package.

**Value**

A data.frame containing supported genomes.

**Author(s)**

Matthew D. Young <[myoung@wehi.edu.au](mailto:myoung@wehi.edu.au)>

**Examples**

```
supportedGenomes()
```

---

|                                     |                                                       |
|-------------------------------------|-------------------------------------------------------|
| <code>taeGut1.ensGene.LENGTH</code> | <i>Transcript length data for the organism taeGut</i> |
|-------------------------------------|-------------------------------------------------------|

---

**Description**

`taeGut1.ensGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `ensGene` table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, ensGene)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.ensGene.LENGTH)
head(taeGut1.ensGene.LENGTH)
```

---

```
taeGut1.geneSymbol.LENGTH
```

*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.geneSymbol.LENGTH)
head(taeGut1.geneSymbol.LENGTH)
```

---

```
taeGut1.genscan.LENGTH
```

*Transcript length data for the organism taeGut*

---

**Description**

taeGut1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(taeGut1.genscan.LENGTH)
head(taeGut1.genscan.LENGTH)
```

---

```
taeGut1.nscanGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

### Description

taeGut1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(taeGut1.nscanGene.LENGTH)
head(taeGut1.nscanGene.LENGTH)
```

---

```
taeGut1.refGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

### Description

taeGut1.refGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the refGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, refGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(taeGut1.refGene.LENGTH)
head(taeGut1.refGene.LENGTH)
```

---

```
taeGut1.xenoRefGene.LENGTH
```

*Transcript length data for the organism taeGut*

---

### Description

taeGut1.xenoRefGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the xenoRefGene table.

The data file was made by calling `downloadLengthFromUCSC(taeGut1, xenoRefGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(taeGut1.xenoRefGene.LENGTH)
head(taeGut1.xenoRefGene.LENGTH)
```

---

```
tetNig1.ensGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig1.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.ensGene.LENGTH)
head(tetNig1.ensGene.LENGTH)
```

---

tetNig1.geneid.LENGTH *Transcript length data for the organism tetNig*

---

### Description

tetNig1.geneid.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneid table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, geneid)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.geneid.LENGTH)
head(tetNig1.geneid.LENGTH)
```

---

tetNig1.genscan.LENGTH  
*Transcript length data for the organism tetNig*

---

### Description

tetNig1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.genscan.LENGTH)
head(tetNig1.genscan.LENGTH)
```

---

```
tetNig1.nscanGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig1.nscanGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the nscanGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig1, nscanGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig1.nscanGene.LENGTH)
head(tetNig1.nscanGene.LENGTH)
```

---

```
tetNig2.ensGene.LENGTH
```

*Transcript length data for the organism tetNig*

---

### Description

tetNig2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(tetNig2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(tetNig2.ensGene.LENGTH)
head(tetNig2.ensGene.LENGTH)
```

---

`unfactor`*Purge factors*

---

**Description**

Removes all factors from a variable in a sensible way.

**Usage**

```
unfactor(var)
```

**Arguments**

`var`                      The variable from which you want the factors removed.

**Details**

As factors are their own type, to remove factors we must convert each level into another type. This is currently done using "typeless" behaviour: a factor is converted to a numeric vector if this can be done without inducing NAs, otherwise it is coerced using `as.character`. Currently supported types are: `factor`, `data.frame` and `list`.

**Value**

The variable with all factors converted to characters or numbers (see details).

**Author(s)**

Matthew D. Young <[myoung@wehi.edu.au](mailto:myoung@wehi.edu.au)>

**Examples**

```
# A named factor
x <- factor(sample(1:6, 100, replace=TRUE))
names(x) <- paste("Roll.No", 1:100, sep='.')
x
unfactor(x)

# A data.frame
x <- data.frame(player <- c("Alice", "Bob", "Mary", "Fred"),
                score <- factor(c(9, 7, 8, 9)), stringsAsFactors=TRUE)
x$player
x$score
y <- unfactor(x)
y$player
y$score
```

---

```
xenTro1.genscan.LENGTH
```

*Transcript length data for the organism xenTro*

---

### Description

xenTro1.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro1, genscan)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(xenTro1.genscan.LENGTH)
head(xenTro1.genscan.LENGTH)
```

---

```
xenTro2.ensGene.LENGTH
```

*Transcript length data for the organism xenTro*

---

### Description

xenTro2.ensGene.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the ensGene table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, ensGene)` on the date on which the package was last updated.

### See Also

[downloadLengthFromUCSC](#)

### Examples

```
data(xenTro2.ensGene.LENGTH)
head(xenTro2.ensGene.LENGTH)
```

---

`xenTro2.geneSymbol.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.geneSymbol.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the geneSymbol table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, geneSymbol)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(xenTro2.geneSymbol.LENGTH)
head(xenTro2.geneSymbol.LENGTH)
```

---

`xenTro2.genscan.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

xenTro2.genscan.LENGTH is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the genscan table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, genscan)` on the date on which the package was last updated.

**See Also**[downloadLengthFromUCSC](#)**Examples**

```
data(xenTro2.genscan.LENGTH)
head(xenTro2.genscan.LENGTH)
```

---

`xenTro2.refGene.LENGTH`*Transcript length data for the organism xenTro*

---

**Description**

`xenTro2.refGene.LENGTH` is an R object which maps transcripts to the length (in bp) of their mature mRNA transcripts. Where available, it will also provide the mapping between a gene ID and its associated transcripts. The data is obtained from the UCSC table browser (<http://genome.ucsc.edu/cgi-bin/hgTables>) using the `refGene` table.

The data file was made by calling `downloadLengthFromUCSC(xenTro2, refGene)` on the date on which the package was last updated.

**See Also**

[downloadLengthFromUCSC](#)

**Examples**

```
data(xenTro2.refGene.LENGTH)
head(xenTro2.refGene.LENGTH)
```

# Index

## \* datasets

anoCar1.ensGene.LENGTH, 8  
anoCar1.genscan.LENGTH, 9  
anoCar1.xenoRefGene.LENGTH, 9  
anoGam1.ensGene.LENGTH, 10  
anoGam1.geneid.LENGTH, 10  
anoGam1.genscan.LENGTH, 11  
apiMe11.genscan.LENGTH, 11  
apiMe12.ensGene.LENGTH, 12  
apiMe12.geneid.LENGTH, 12  
apiMe12.genscan.LENGTH, 13  
aplCal1.xenoRefGene.LENGTH, 13  
bosTau2.geneid.LENGTH, 14  
bosTau2.geneSymbol.LENGTH, 14  
bosTau2.genscan.LENGTH, 15  
bosTau2.refGene.LENGTH, 15  
bosTau2.sgpGene.LENGTH, 16  
bosTau3.ensGene.LENGTH, 16  
bosTau3.geneid.LENGTH, 17  
bosTau3.geneSymbol.LENGTH, 17  
bosTau3.genscan.LENGTH, 18  
bosTau3.refGene.LENGTH, 18  
bosTau3.sgpGene.LENGTH, 19  
bosTau4.ensGene.LENGTH, 19  
bosTau4.geneSymbol.LENGTH, 20  
bosTau4.genscan.LENGTH, 20  
bosTau4.nscanGene.LENGTH, 21  
bosTau4.refGene.LENGTH, 21  
braFlo1.xenoRefGene.LENGTH, 22  
caeJap1.xenoRefGene.LENGTH, 22  
caePb1.xenoRefGene.LENGTH, 23  
caePb2.xenoRefGene.LENGTH, 23  
caeRem2.xenoRefGene.LENGTH, 24  
caeRem3.xenoRefGene.LENGTH, 24  
calJac1.genscan.LENGTH, 25  
calJac1.nscanGene.LENGTH, 25  
calJac1.xenoRefGene.LENGTH, 26  
canFam1.ensGene.LENGTH, 26  
canFam1.geneSymbol.LENGTH, 27  
canFam1.genscan.LENGTH, 27  
canFam1.nscanGene.LENGTH, 28  
canFam1.refGene.LENGTH, 28  
canFam1.xenoRefGene.LENGTH, 29  
canFam2.ensGene.LENGTH, 29  
canFam2.geneSymbol.LENGTH, 30  
canFam2.genscan.LENGTH, 30  
canFam2.nscanGene.LENGTH, 31  
canFam2.refGene.LENGTH, 31  
canFam2.xenoRefGene.LENGTH, 32  
cavPor3.ensGene.LENGTH, 32  
cavPor3.genscan.LENGTH, 33  
cavPor3.nscanGene.LENGTH, 33  
cavPor3.xenoRefGene.LENGTH, 34  
cb1.xenoRefGene.LENGTH, 34  
cb3.xenoRefGene.LENGTH, 35  
ce2.geneid.LENGTH, 35  
ce2.geneSymbol.LENGTH, 36  
ce2.refGene.LENGTH, 36  
ce4.geneSymbol.LENGTH, 37  
ce4.refGene.LENGTH, 37  
ce4.xenoRefGene.LENGTH, 38  
ce6.ensGene.LENGTH, 38  
ce6.geneSymbol.LENGTH, 39  
ce6.refGene.LENGTH, 39  
ce6.xenoRefGene.LENGTH, 40  
ci1.geneSymbol.LENGTH, 40  
ci1.refGene.LENGTH, 41  
ci1.xenoRefGene.LENGTH, 41  
ci2.ensGene.LENGTH, 42  
ci2.geneSymbol.LENGTH, 42  
ci2.refGene.LENGTH, 43  
ci2.xenoRefGene.LENGTH, 43  
danRer3.ensGene.LENGTH, 44  
danRer3.geneSymbol.LENGTH, 44  
danRer3.refGene.LENGTH, 45  
danRer4.ensGene.LENGTH, 45  
danRer4.geneSymbol.LENGTH, 46  
danRer4.genscan.LENGTH, 46  
danRer4.nscanGene.LENGTH, 47  
danRer4.refGene.LENGTH, 47  
danRer5.ensGene.LENGTH, 48  
danRer5.geneSymbol.LENGTH, 48  
danRer5.refGene.LENGTH, 49  
danRer5.vegaGene.LENGTH, 49  
danRer5.vegaPseudoGene.LENGTH, 50  
danRer6.ensGene.LENGTH, 50

danRer6.geneSymbol.LENGTH, 51  
 danRer6.refGene.LENGTH, 51  
 danRer6.xenoRefGene.LENGTH, 52  
 dm1.geneSymbol.LENGTH, 52  
 dm1.genscan.LENGTH, 53  
 dm1.refGene.LENGTH, 53  
 dm2.geneid.LENGTH, 54  
 dm2.geneSymbol.LENGTH, 54  
 dm2.genscan.LENGTH, 55  
 dm2.nscanGene.LENGTH, 55  
 dm2.refGene.LENGTH, 56  
 dm3.geneSymbol.LENGTH, 56  
 dm3.nscanPasaGene.LENGTH, 57  
 dm3.refGene.LENGTH, 57  
 dp2.genscan.LENGTH, 59  
 dp2.xenoRefGene.LENGTH, 59  
 dp3.geneid.LENGTH, 60  
 dp3.genscan.LENGTH, 60  
 dp3.xenoRefGene.LENGTH, 61  
 droAna1.geneid.LENGTH, 61  
 droAna1.genscan.LENGTH, 62  
 droAna1.xenoRefGene.LENGTH, 62  
 droAna2.genscan.LENGTH, 63  
 droAna2.xenoRefGene.LENGTH, 63  
 droEre1.genscan.LENGTH, 64  
 droEre1.xenoRefGene.LENGTH, 64  
 droGri1.genscan.LENGTH, 65  
 droGri1.xenoRefGene.LENGTH, 65  
 droMoj1.geneid.LENGTH, 66  
 droMoj1.genscan.LENGTH, 66  
 droMoj1.xenoRefGene.LENGTH, 67  
 droMoj2.genscan.LENGTH, 67  
 droMoj2.xenoRefGene.LENGTH, 68  
 droPer1.genscan.LENGTH, 68  
 droPer1.xenoRefGene.LENGTH, 69  
 droSec1.genscan.LENGTH, 69  
 droSec1.xenoRefGene.LENGTH, 70  
 droSim1.geneid.LENGTH, 70  
 droSim1.genscan.LENGTH, 71  
 droSim1.xenoRefGene.LENGTH, 71  
 droVir1.geneid.LENGTH, 72  
 droVir1.genscan.LENGTH, 72  
 droVir1.xenoRefGene.LENGTH, 73  
 droVir2.genscan.LENGTH, 73  
 droVir2.xenoRefGene.LENGTH, 74  
 droYak1.geneid.LENGTH, 74  
 droYak1.genscan.LENGTH, 75  
 droYak1.xenoRefGene.LENGTH, 75  
 droYak2.genscan.LENGTH, 76  
 droYak2.xenoRefGene.LENGTH, 76  
 equCab1.geneid.LENGTH, 77  
 equCab1.geneSymbol.LENGTH, 77  
 equCab1.nscanGene.LENGTH, 78  
 equCab1.refGene.LENGTH, 78  
 equCab1.sgpGene.LENGTH, 79  
 equCab2.ensGene.LENGTH, 79  
 equCab2.geneSymbol.LENGTH, 80  
 equCab2.nscanGene.LENGTH, 80  
 equCab2.refGene.LENGTH, 81  
 equCab2.xenoRefGene.LENGTH, 81  
 felCat3.ensGene.LENGTH, 82  
 felCat3.geneid.LENGTH, 82  
 felCat3.geneSymbol.LENGTH, 83  
 felCat3.genscan.LENGTH, 83  
 felCat3.nscanGene.LENGTH, 84  
 felCat3.refGene.LENGTH, 84  
 felCat3.sgpGene.LENGTH, 85  
 felCat3.xenoRefGene.LENGTH, 85  
 fr1.ensGene.LENGTH, 86  
 fr1.genscan.LENGTH, 86  
 fr2.ensGene.LENGTH, 87  
 galGal2.ensGene.LENGTH, 87  
 galGal2.geneid.LENGTH, 88  
 galGal2.geneSymbol.LENGTH, 88  
 galGal2.genscan.LENGTH, 89  
 galGal2.refGene.LENGTH, 89  
 galGal2.sgpGene.LENGTH, 90  
 galGal3.ensGene.LENGTH, 90  
 galGal3.geneSymbol.LENGTH, 91  
 galGal3.genscan.LENGTH, 91  
 galGal3.nscanGene.LENGTH, 92  
 galGal3.refGene.LENGTH, 92  
 galGal3.xenoRefGene.LENGTH, 93  
 gasAcu1.ensGene.LENGTH, 93  
 gasAcu1.nscanGene.LENGTH, 94  
 hg16.acembly.LENGTH, 95  
 hg16.ensGene.LENGTH, 95  
 hg16.exoniphy.LENGTH, 96  
 hg16.geneid.LENGTH, 96  
 hg16.geneSymbol.LENGTH, 97  
 hg16.genscan.LENGTH, 97  
 hg16.knownGene.LENGTH, 98  
 hg16.refGene.LENGTH, 98  
 hg16.sgpGene.LENGTH, 99  
 hg17.acembly.LENGTH, 99  
 hg17.acescan.LENGTH, 100  
 hg17.ccdsGene.LENGTH, 100  
 hg17.ensGene.LENGTH, 101  
 hg17.exoniphy.LENGTH, 101  
 hg17.geneid.LENGTH, 102  
 hg17.geneSymbol.LENGTH, 102  
 hg17.genscan.LENGTH, 103  
 hg17.knownGene.LENGTH, 103  
 hg17.refGene.LENGTH, 104

- hg17.sgpGene.LENGTH, 104  
hg17.vegaGene.LENGTH, 105  
hg17.vegaPseudoGene.LENGTH, 105  
hg17.xenoRefGene.LENGTH, 106  
hg18.acembly.LENGTH, 106  
hg18.acescan.LENGTH, 107  
hg18.ccdsGene.LENGTH, 107  
hg18.ensGene.LENGTH, 108  
hg18.exoniphy.LENGTH, 108  
hg18.geneid.LENGTH, 109  
hg18.geneSymbol.LENGTH, 109  
hg18.genscan.LENGTH, 110  
hg18.knownGene.LENGTH, 110  
hg18.knownGeneOld3.LENGTH, 111  
hg18.refGene.LENGTH, 111  
hg18.sgpGene.LENGTH, 112  
hg18.sibGene.LENGTH, 112  
hg18.xenoRefGene.LENGTH, 113  
hg19.ccdsGene.LENGTH, 113  
hg19.ensGene.LENGTH, 114  
hg19.exoniphy.LENGTH, 114  
hg19.geneSymbol.LENGTH, 115  
hg19.knownGene.LENGTH, 115  
hg19.nscanGene.LENGTH, 116  
hg19.refGene.LENGTH, 116  
hg19.xenoRefGene.LENGTH, 117  
loxAfr3.xenoRefGene.LENGTH, 117  
mm7.ensGene.LENGTH, 118  
mm7.geneid.LENGTH, 118  
mm7.geneSymbol.LENGTH, 119  
mm7.genscan.LENGTH, 119  
mm7.knownGene.LENGTH, 120  
mm7.refGene.LENGTH, 120  
mm7.sgpGene.LENGTH, 121  
mm7.xenoRefGene.LENGTH, 121  
mm8.ccdsGene.LENGTH, 122  
mm8.ensGene.LENGTH, 122  
mm8.geneid.LENGTH, 123  
mm8.geneSymbol.LENGTH, 123  
mm8.genscan.LENGTH, 124  
mm8.knownGene.LENGTH, 124  
mm8.nscanGene.LENGTH, 125  
mm8.refGene.LENGTH, 125  
mm8.sgpGene.LENGTH, 126  
mm8.sibGene.LENGTH, 126  
mm8.xenoRefGene.LENGTH, 127  
mm9.acembly.LENGTH, 127  
mm9.ccdsGene.LENGTH, 128  
mm9.ensGene.LENGTH, 128  
mm9.exoniphy.LENGTH, 129  
mm9.geneid.LENGTH, 129  
mm9.geneSymbol.LENGTH, 130  
mm9.genscan.LENGTH, 130  
mm9.knownGene.LENGTH, 131  
mm9.nscanGene.LENGTH, 131  
mm9.refGene.LENGTH, 132  
mm9.sgpGene.LENGTH, 132  
mm9.xenoRefGene.LENGTH, 133  
monDom1.genscan.LENGTH, 133  
monDom4.ensGene.LENGTH, 134  
monDom4.geneSymbol.LENGTH, 134  
monDom4.genscan.LENGTH, 135  
monDom4.nscanGene.LENGTH, 135  
monDom4.refGene.LENGTH, 136  
monDom4.xenoRefGene.LENGTH, 136  
monDom5.ensGene.LENGTH, 137  
monDom5.geneSymbol.LENGTH, 137  
monDom5.genscan.LENGTH, 138  
monDom5.nscanGene.LENGTH, 138  
monDom5.refGene.LENGTH, 139  
monDom5.xenoRefGene.LENGTH, 139  
ornAna1.ensGene.LENGTH, 140  
ornAna1.geneSymbol.LENGTH, 140  
ornAna1.refGene.LENGTH, 141  
ornAna1.xenoRefGene.LENGTH, 141  
oryLat2.ensGene.LENGTH, 142  
oryLat2.geneSymbol.LENGTH, 142  
oryLat2.refGene.LENGTH, 143  
oryLat2.xenoRefGene.LENGTH, 143  
panTro1.ensGene.LENGTH, 144  
panTro1.geneid.LENGTH, 144  
panTro1.genscan.LENGTH, 145  
panTro1.xenoRefGene.LENGTH, 145  
panTro2.ensGene.LENGTH, 146  
panTro2.geneSymbol.LENGTH, 146  
panTro2.genscan.LENGTH, 147  
panTro2.nscanGene.LENGTH, 147  
panTro2.refGene.LENGTH, 148  
panTro2.xenoRefGene.LENGTH, 148  
petMar1.xenoRefGene.LENGTH, 149  
ponAbe2.ensGene.LENGTH, 149  
ponAbe2.geneSymbol.LENGTH, 150  
ponAbe2.genscan.LENGTH, 150  
ponAbe2.nscanGene.LENGTH, 151  
ponAbe2.refGene.LENGTH, 151  
ponAbe2.xenoRefGene.LENGTH, 152  
priPac1.xenoRefGene.LENGTH, 152  
rheMac2.ensGene.LENGTH, 153  
rheMac2.geneid.LENGTH, 153  
rheMac2.geneSymbol.LENGTH, 154  
rheMac2.nscanGene.LENGTH, 154  
rheMac2.refGene.LENGTH, 155  
rheMac2.sgpGene.LENGTH, 155  
rheMac2.xenoRefGene.LENGTH, 156

- rn3.ensGene.LENGTH, 156
- rn3.geneid.LENGTH, 157
- rn3.geneSymbol.LENGTH, 157
- rn3.genscan.LENGTH, 158
- rn3.knownGene.LENGTH, 158
- rn3.nscanGene.LENGTH, 159
- rn3.refGene.LENGTH, 159
- rn3.sgpGene.LENGTH, 160
- rn3.xenoRefGene.LENGTH, 160
- rn4.ensGene.LENGTH, 161
- rn4.geneid.LENGTH, 161
- rn4.geneSymbol.LENGTH, 162
- rn4.genscan.LENGTH, 162
- rn4.knownGene.LENGTH, 163
- rn4.nscanGene.LENGTH, 163
- rn4.refGene.LENGTH, 164
- rn4.sgpGene.LENGTH, 164
- rn4.xenoRefGene.LENGTH, 165
- sacCer1.ensGene.LENGTH, 165
- sacCer2.ensGene.LENGTH, 166
- strPur1.geneSymbol.LENGTH, 166
- strPur1.genscan.LENGTH, 167
- strPur1.refGene.LENGTH, 167
- strPur1.xenoRefGene.LENGTH, 168
- strPur2.geneSymbol.LENGTH, 168
- strPur2.genscan.LENGTH, 169
- strPur2.refGene.LENGTH, 169
- strPur2.xenoRefGene.LENGTH, 170
- taeGut1.ensGene.LENGTH, 171
- taeGut1.geneSymbol.LENGTH, 172
- taeGut1.genscan.LENGTH, 172
- taeGut1.nscanGene.LENGTH, 173
- taeGut1.refGene.LENGTH, 173
- taeGut1.xenoRefGene.LENGTH, 174
- tetNig1.ensGene.LENGTH, 174
- tetNig1.geneid.LENGTH, 175
- tetNig1.genscan.LENGTH, 175
- tetNig1.nscanGene.LENGTH, 176
- tetNig2.ensGene.LENGTH, 176
- xenTro1.genscan.LENGTH, 178
- xenTro2.ensGene.LENGTH, 178
- xenTro2.geneSymbol.LENGTH, 179
- xenTro2.genscan.LENGTH, 179
- xenTro2.refGene.LENGTH, 180
- \* **internal**
  - geneLenDatabase-pkg, 94
- anoCar1.ensGene.LENGTH, 8
- anoCar1.genscan.LENGTH, 9
- anoCar1.xenoRefGene.LENGTH, 9
- anoGam1.ensGene.LENGTH, 10
- anoGam1.geneid.LENGTH, 10
- anoGam1.genscan.LENGTH, 11
- apiMel1.genscan.LENGTH, 11
- apiMel2.ensGene.LENGTH, 12
- apiMel2.geneid.LENGTH, 12
- apiMel2.genscan.LENGTH, 13
- aplCa11.xenoRefGene.LENGTH, 13
- bosTau2.geneid.LENGTH, 14
- bosTau2.geneSymbol.LENGTH, 14
- bosTau2.genscan.LENGTH, 15
- bosTau2.refGene.LENGTH, 15
- bosTau2.sgpGene.LENGTH, 16
- bosTau3.ensGene.LENGTH, 16
- bosTau3.geneid.LENGTH, 17
- bosTau3.geneSymbol.LENGTH, 17
- bosTau3.genscan.LENGTH, 18
- bosTau3.refGene.LENGTH, 18
- bosTau3.sgpGene.LENGTH, 19
- bosTau4.ensGene.LENGTH, 19
- bosTau4.geneSymbol.LENGTH, 20
- bosTau4.genscan.LENGTH, 20
- bosTau4.nscanGene.LENGTH, 21
- bosTau4.refGene.LENGTH, 21
- braFlo1.xenoRefGene.LENGTH, 22
- caeJap1.xenoRefGene.LENGTH, 22
- caePb1.xenoRefGene.LENGTH, 23
- caePb2.xenoRefGene.LENGTH, 23
- caeRem2.xenoRefGene.LENGTH, 24
- caeRem3.xenoRefGene.LENGTH, 24
- calJac1.genscan.LENGTH, 25
- calJac1.nscanGene.LENGTH, 25
- calJac1.xenoRefGene.LENGTH, 26
- canFam1.ensGene.LENGTH, 26
- canFam1.geneSymbol.LENGTH, 27
- canFam1.genscan.LENGTH, 27
- canFam1.nscanGene.LENGTH, 28
- canFam1.refGene.LENGTH, 28
- canFam1.xenoRefGene.LENGTH, 29
- canFam2.ensGene.LENGTH, 29
- canFam2.geneSymbol.LENGTH, 30
- canFam2.genscan.LENGTH, 30
- canFam2.nscanGene.LENGTH, 31
- canFam2.refGene.LENGTH, 31
- canFam2.xenoRefGene.LENGTH, 32
- cavPor3.ensGene.LENGTH, 32
- cavPor3.genscan.LENGTH, 33
- cavPor3.nscanGene.LENGTH, 33
- cavPor3.xenoRefGene.LENGTH, 34
- cb1.xenoRefGene.LENGTH, 34
- cb3.xenoRefGene.LENGTH, 35
- ce2.geneid.LENGTH, 35
- ce2.geneSymbol.LENGTH, 36
- ce2.refGene.LENGTH, 36

- ce4.geneSymbol.LENGTH, 37
- ce4.refGene.LENGTH, 37
- ce4.xenoRefGene.LENGTH, 38
- ce6.ensGene.LENGTH, 38
- ce6.geneSymbol.LENGTH, 39
- ce6.refGene.LENGTH, 39
- ce6.xenoRefGene.LENGTH, 40
- ci1.geneSymbol.LENGTH, 40
- ci1.refGene.LENGTH, 41
- ci1.xenoRefGene.LENGTH, 41
- ci2.ensGene.LENGTH, 42
- ci2.geneSymbol.LENGTH, 42
- ci2.refGene.LENGTH, 43
- ci2.xenoRefGene.LENGTH, 43
- danRer3.ensGene.LENGTH, 44
- danRer3.geneSymbol.LENGTH, 44
- danRer3.refGene.LENGTH, 45
- danRer4.ensGene.LENGTH, 45
- danRer4.geneSymbol.LENGTH, 46
- danRer4.genscan.LENGTH, 46
- danRer4.nscanGene.LENGTH, 47
- danRer4.refGene.LENGTH, 47
- danRer5.ensGene.LENGTH, 48
- danRer5.geneSymbol.LENGTH, 48
- danRer5.refGene.LENGTH, 49
- danRer5.vegaGene.LENGTH, 49
- danRer5.vegaPseudoGene.LENGTH, 50
- danRer6.ensGene.LENGTH, 50
- danRer6.geneSymbol.LENGTH, 51
- danRer6.refGene.LENGTH, 51
- danRer6.xenoRefGene.LENGTH, 52
- dm1.geneSymbol.LENGTH, 52
- dm1.genscan.LENGTH, 53
- dm1.refGene.LENGTH, 53
- dm2.geneid.LENGTH, 54
- dm2.geneSymbol.LENGTH, 54
- dm2.genscan.LENGTH, 55
- dm2.nscanGene.LENGTH, 55
- dm2.refGene.LENGTH, 56
- dm3.geneSymbol.LENGTH, 56
- dm3.nscanPasaGene.LENGTH, 57
- dm3.refGene.LENGTH, 57
- downloadLengthFromUCSC, 8–57, 58, 59–170, 172–176, 178–180
- dp2.genscan.LENGTH, 59
- dp2.xenoRefGene.LENGTH, 59
- dp3.geneid.LENGTH, 60
- dp3.genscan.LENGTH, 60
- dp3.xenoRefGene.LENGTH, 61
- droAna1.geneid.LENGTH, 61
- droAna1.genscan.LENGTH, 62
- droAna1.xenoRefGene.LENGTH, 62
- droAna2.genscan.LENGTH, 63
- droAna2.xenoRefGene.LENGTH, 63
- droEre1.genscan.LENGTH, 64
- droEre1.xenoRefGene.LENGTH, 64
- droGri1.genscan.LENGTH, 65
- droGri1.xenoRefGene.LENGTH, 65
- droMoj1.geneid.LENGTH, 66
- droMoj1.genscan.LENGTH, 66
- droMoj1.xenoRefGene.LENGTH, 67
- droMoj2.genscan.LENGTH, 67
- droMoj2.xenoRefGene.LENGTH, 68
- droPer1.genscan.LENGTH, 68
- droPer1.xenoRefGene.LENGTH, 69
- droSec1.genscan.LENGTH, 69
- droSec1.xenoRefGene.LENGTH, 70
- droSim1.geneid.LENGTH, 70
- droSim1.genscan.LENGTH, 71
- droSim1.xenoRefGene.LENGTH, 71
- droVir1.geneid.LENGTH, 72
- droVir1.genscan.LENGTH, 72
- droVir1.xenoRefGene.LENGTH, 73
- droVir2.genscan.LENGTH, 73
- droVir2.xenoRefGene.LENGTH, 74
- droYak1.geneid.LENGTH, 74
- droYak1.genscan.LENGTH, 75
- droYak1.xenoRefGene.LENGTH, 75
- droYak2.genscan.LENGTH, 76
- droYak2.xenoRefGene.LENGTH, 76
- equCab1.geneid.LENGTH, 77
- equCab1.geneSymbol.LENGTH, 77
- equCab1.nscanGene.LENGTH, 78
- equCab1.refGene.LENGTH, 78
- equCab1.sgpGene.LENGTH, 79
- equCab2.ensGene.LENGTH, 79
- equCab2.geneSymbol.LENGTH, 80
- equCab2.nscanGene.LENGTH, 80
- equCab2.refGene.LENGTH, 81
- equCab2.xenoRefGene.LENGTH, 81
- felCat3.ensGene.LENGTH, 82
- felCat3.geneid.LENGTH, 82
- felCat3.geneSymbol.LENGTH, 83
- felCat3.genscan.LENGTH, 83
- felCat3.nscanGene.LENGTH, 84
- felCat3.refGene.LENGTH, 84
- felCat3.sgpGene.LENGTH, 85
- felCat3.xenoRefGene.LENGTH, 85
- fr1.ensGene.LENGTH, 86
- fr1.genscan.LENGTH, 86
- fr2.ensGene.LENGTH, 87
- galGal2.ensGene.LENGTH, 87

- galGal2.geneid.LENGTH, 88
- galGal2.geneSymbol.LENGTH, 88
- galGal2.genscan.LENGTH, 89
- galGal2.refGene.LENGTH, 89
- galGal2.sgpGene.LENGTH, 90
- galGal3.ensGene.LENGTH, 90
- galGal3.geneSymbol.LENGTH, 91
- galGal3.genscan.LENGTH, 91
- galGal3.nscanGene.LENGTH, 92
- galGal3.refGene.LENGTH, 92
- galGal3.xenoRefGene.LENGTH, 93
- gasAcu1.ensGene.LENGTH, 93
- gasAcu1.nscanGene.LENGTH, 94
- geneLenDataBase (geneLenDatabase-pkg), 94
- geneLenDataBase-package (geneLenDatabase-pkg), 94
- geneLenDatabase-pkg, 94
- hg16.acembly.LENGTH, 95
- hg16.ensGene.LENGTH, 95
- hg16.exoniphy.LENGTH, 96
- hg16.geneid.LENGTH, 96
- hg16.geneSymbol.LENGTH, 97
- hg16.genscan.LENGTH, 97
- hg16.knownGene.LENGTH, 98
- hg16.refGene.LENGTH, 98
- hg16.sgpGene.LENGTH, 99
- hg17.acembly.LENGTH, 99
- hg17.acescan.LENGTH, 100
- hg17.ccdsGene.LENGTH, 100
- hg17.ensGene.LENGTH, 101
- hg17.exoniphy.LENGTH, 101
- hg17.geneid.LENGTH, 102
- hg17.geneSymbol.LENGTH, 102
- hg17.genscan.LENGTH, 103
- hg17.knownGene.LENGTH, 103
- hg17.refGene.LENGTH, 104
- hg17.sgpGene.LENGTH, 104
- hg17.vegaGene.LENGTH, 105
- hg17.vegaPseudoGene.LENGTH, 105
- hg17.xenoRefGene.LENGTH, 106
- hg18.acembly.LENGTH, 106
- hg18.acescan.LENGTH, 107
- hg18.ccdsGene.LENGTH, 107
- hg18.ensGene.LENGTH, 108
- hg18.exoniphy.LENGTH, 108
- hg18.geneid.LENGTH, 109
- hg18.geneSymbol.LENGTH, 109
- hg18.genscan.LENGTH, 110
- hg18.knownGene.LENGTH, 110
- hg18.knownGeneOld3.LENGTH, 111
- hg18.refGene.LENGTH, 111
- hg18.sgpGene.LENGTH, 112
- hg18.sibGene.LENGTH, 112
- hg18.xenoRefGene.LENGTH, 113
- hg19.ccdsGene.LENGTH, 113
- hg19.ensGene.LENGTH, 114
- hg19.exoniphy.LENGTH, 114
- hg19.geneSymbol.LENGTH, 115
- hg19.knownGene.LENGTH, 115
- hg19.nscanGene.LENGTH, 116
- hg19.refGene.LENGTH, 116
- hg19.xenoRefGene.LENGTH, 117
- loxAfr3.xenoRefGene.LENGTH, 117
- mm7.ensGene.LENGTH, 118
- mm7.geneid.LENGTH, 118
- mm7.geneSymbol.LENGTH, 119
- mm7.genscan.LENGTH, 119
- mm7.knownGene.LENGTH, 120
- mm7.refGene.LENGTH, 120
- mm7.sgpGene.LENGTH, 121
- mm7.xenoRefGene.LENGTH, 121
- mm8.ccdsGene.LENGTH, 122
- mm8.ensGene.LENGTH, 122
- mm8.geneid.LENGTH, 123
- mm8.geneSymbol.LENGTH, 123
- mm8.genscan.LENGTH, 124
- mm8.knownGene.LENGTH, 124
- mm8.nscanGene.LENGTH, 125
- mm8.refGene.LENGTH, 125
- mm8.sgpGene.LENGTH, 126
- mm8.sibGene.LENGTH, 126
- mm8.xenoRefGene.LENGTH, 127
- mm9.acembly.LENGTH, 127
- mm9.ccdsGene.LENGTH, 128
- mm9.ensGene.LENGTH, 128
- mm9.exoniphy.LENGTH, 129
- mm9.geneid.LENGTH, 129
- mm9.geneSymbol.LENGTH, 130
- mm9.genscan.LENGTH, 130
- mm9.knownGene.LENGTH, 131
- mm9.nscanGene.LENGTH, 131
- mm9.refGene.LENGTH, 132
- mm9.sgpGene.LENGTH, 132
- mm9.xenoRefGene.LENGTH, 133
- monDom1.genscan.LENGTH, 133
- monDom4.ensGene.LENGTH, 134
- monDom4.geneSymbol.LENGTH, 134
- monDom4.genscan.LENGTH, 135
- monDom4.nscanGene.LENGTH, 135
- monDom4.refGene.LENGTH, 136
- monDom4.xenoRefGene.LENGTH, 136
- monDom5.ensGene.LENGTH, 137

monDom5.geneSymbol.LENGTH, 137  
 monDom5.genscan.LENGTH, 138  
 monDom5.nscanGene.LENGTH, 138  
 monDom5.refGene.LENGTH, 139  
 monDom5.xenoRefGene.LENGTH, 139

ornAna1.ensGene.LENGTH, 140  
 ornAna1.geneSymbol.LENGTH, 140  
 ornAna1.refGene.LENGTH, 141  
 ornAna1.xenoRefGene.LENGTH, 141  
 oryLat2.ensGene.LENGTH, 142  
 oryLat2.geneSymbol.LENGTH, 142  
 oryLat2.refGene.LENGTH, 143  
 oryLat2.xenoRefGene.LENGTH, 143

panTro1.ensGene.LENGTH, 144  
 panTro1.geneid.LENGTH, 144  
 panTro1.genscan.LENGTH, 145  
 panTro1.xenoRefGene.LENGTH, 145  
 panTro2.ensGene.LENGTH, 146  
 panTro2.geneSymbol.LENGTH, 146  
 panTro2.genscan.LENGTH, 147  
 panTro2.nscanGene.LENGTH, 147  
 panTro2.refGene.LENGTH, 148  
 panTro2.xenoRefGene.LENGTH, 148  
 petMar1.xenoRefGene.LENGTH, 149  
 ponAbe2.ensGene.LENGTH, 149  
 ponAbe2.geneSymbol.LENGTH, 150  
 ponAbe2.genscan.LENGTH, 150  
 ponAbe2.nscanGene.LENGTH, 151  
 ponAbe2.refGene.LENGTH, 151  
 ponAbe2.xenoRefGene.LENGTH, 152  
 priPac1.xenoRefGene.LENGTH, 152

rheMac2.ensGene.LENGTH, 153  
 rheMac2.geneid.LENGTH, 153  
 rheMac2.geneSymbol.LENGTH, 154  
 rheMac2.nscanGene.LENGTH, 154  
 rheMac2.refGene.LENGTH, 155  
 rheMac2.sgpGene.LENGTH, 155  
 rheMac2.xenoRefGene.LENGTH, 156  
 rn3.ensGene.LENGTH, 156  
 rn3.geneid.LENGTH, 157  
 rn3.geneSymbol.LENGTH, 157  
 rn3.genscan.LENGTH, 158  
 rn3.knownGene.LENGTH, 158  
 rn3.nscanGene.LENGTH, 159  
 rn3.refGene.LENGTH, 159  
 rn3.sgpGene.LENGTH, 160  
 rn3.xenoRefGene.LENGTH, 160  
 rn4.ensGene.LENGTH, 161  
 rn4.geneid.LENGTH, 161  
 rn4.geneSymbol.LENGTH, 162

rn4.genscan.LENGTH, 162  
 rn4.knownGene.LENGTH, 163  
 rn4.nscanGene.LENGTH, 163  
 rn4.refGene.LENGTH, 164  
 rn4.sgpGene.LENGTH, 164  
 rn4.xenoRefGene.LENGTH, 165

sacCer1.ensGene.LENGTH, 165  
 sacCer2.ensGene.LENGTH, 166  
 strPur1.geneSymbol.LENGTH, 166  
 strPur1.genscan.LENGTH, 167  
 strPur1.refGene.LENGTH, 167  
 strPur1.xenoRefGene.LENGTH, 168  
 strPur2.geneSymbol.LENGTH, 168  
 strPur2.genscan.LENGTH, 169  
 strPur2.refGene.LENGTH, 169  
 strPur2.xenoRefGene.LENGTH, 170  
 supportedGeneIDs, 58, 170  
 supportedGenomes, 58, 171

taeGut1.ensGene.LENGTH, 171  
 taeGut1.geneSymbol.LENGTH, 172  
 taeGut1.genscan.LENGTH, 172  
 taeGut1.nscanGene.LENGTH, 173  
 taeGut1.refGene.LENGTH, 173  
 taeGut1.xenoRefGene.LENGTH, 174  
 tetNig1.ensGene.LENGTH, 174  
 tetNig1.geneid.LENGTH, 175  
 tetNig1.genscan.LENGTH, 175  
 tetNig1.nscanGene.LENGTH, 176  
 tetNig2.ensGene.LENGTH, 176

unfactor, 177

xenTro1.genscan.LENGTH, 178  
 xenTro2.ensGene.LENGTH, 178  
 xenTro2.geneSymbol.LENGTH, 179  
 xenTro2.genscan.LENGTH, 179  
 xenTro2.refGene.LENGTH, 180