

# Package ‘AnVILGCP’

November 5, 2025

**Title** The GCP R Client for the AnVIL

**Version** 1.5.0

**Date** 2025-09-25

**Description** The package provides a set of functions to interact with the Google Cloud Platform (GCP) services on the AnVIL platform. The package is designed to use the API calls from the AnVIL package. It coordinates AnVIL workspace functionality with native GCP tools.

**biocViews** Software, Infrastructure, ThirdPartyClient, DataImport

**Depends** R (>= 4.5.0)

**Imports** AnVILBase, BiocBaseUtils, dplyr, GCPTools (>= 0.99.4), httr, jsonlite, methods, rlang, stats, tibble, tidyr, utils

**Suggests** AnVIL, BiocStyle, knitr, rmarkdown, testthat, withr

**VignetteBuilder** knitr

**BugReports** <https://github.com/Bioconductor/AnVILGCP/issues>

**URL** <https://github.com/Bioconductor/AnVILGCP>

**License** Artistic-2.0

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.3

**Collate** 'av.R' 'avdata.R' 'gcp-class.R' 'avnotebooks-methods.R' 'avtable-methods.R' 'avworkflow-methods.R' 'avworkflow.R' 'avworkflow\_configuration.R' 'avworkspace-methods.R' 'drs.R' 'gcloud.R' 'gcloud\_sdk.R' 'gcp-methods.R' 'gsutil.R' 'has\_avworkspace-methods.R' 'localize.R' 'utilities.R'

**git\_url** <https://git.bioconductor.org/packages/AnVILGCP>

**git\_branch** devel

**git\_last\_commit** e244142

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-11-05

**Author** Marcel Ramos [aut, cre] (ORCID: <https://orcid.org/0000-0002-3242-0582>),  
Nitesh Turaga [aut],  
Martin Morgan [aut] (ORCID: <https://orcid.org/0000-0002-5874-8148>)

**Maintainer** Marcel Ramos <marcel.ramos@sph.cuny.edu>

Contents

|                                     |           |
|-------------------------------------|-----------|
| av . . . . .                        | 2         |
| avdata . . . . .                    | 7         |
| avnotebooks-methods . . . . .       | 8         |
| avtable-methods . . . . .           | 9         |
| avworkflow-methods . . . . .        | 14        |
| avworkflows . . . . .               | 15        |
| avworkflow_configurations . . . . . | 19        |
| avworkspace-methods . . . . .       | 23        |
| drs . . . . .                       | 25        |
| gcloud-deprecated . . . . .         | 27        |
| gcp-class . . . . .                 | 28        |
| gcp-methods . . . . .               | 29        |
| gsutil-deprecated . . . . .         | 32        |
| has_avworkspace-methods . . . . .   | 35        |
| localize . . . . .                  | 35        |
| <b>Index</b>                        | <b>37</b> |

---

|    |                                                                            |
|----|----------------------------------------------------------------------------|
| av | <i>Miscellaneous functions for interacting with AnVIL tables and files</i> |
|----|----------------------------------------------------------------------------|

---

Description

avtable\_import\_status() queries for the status of an 'asynchronous' table import.

avfiles\_ls() returns the paths of files in the workspace bucket. avfiles\_backup() copies files from the compute node file system to the workspace bucket. avfiles\_restore() copies files from the workspace bucket to the compute node file system. avfiles\_rm() removes files or directories from the workspace bucket.

avruntimes() returns a tibble containing information about runtimes (notebooks or RStudio instances, for example) that the current user has access to.

avruntime() returns a tibble with the runtimes associated with a particular google project and account number; usually there is a single runtime satisfying these criteria, and it is the runtime active in AnVIL.

'avdisks()' returns a tibble containing information about persistent disks associatd with the current user.

**Usage**

```
avtable_paged(  
  table,  
  n = Inf,  
  page = 1L,  
  pageSize = 1000L,  
  sortField = "name",  
  sortDirection = c("asc", "desc"),  
  filterTerms = character(),  
  filterOperator = c("and", "or"),  
  namespace = avworkspace_namespace(),  
  name = avworkspace_name(),  
  na = c("", "NA")  
)  
  
avtable_import_status(  
  job_status,  
  namespace = avworkspace_namespace(),  
  name = avworkspace_name()  
)  
  
avfiles_ls(  
  path = "",  
  full_names = FALSE,  
  recursive = FALSE,  
  namespace = avworkspace_namespace(),  
  name = avworkspace_name()  
)  
  
avfiles_backup(  
  source,  
  destination = "",  
  recursive = FALSE,  
  parallel = TRUE,  
  namespace = avworkspace_namespace(),  
  name = avworkspace_name()  
)  
  
avfiles_restore(  
  source,  
  destination = ".",  
  recursive = FALSE,  
  parallel = TRUE,  
  namespace = avworkspace_namespace(),  
  name = avworkspace_name()  
)  
  
avfiles_rm(  
  path = "",  
  recursive = FALSE,  
  namespace = avworkspace_namespace(),  
  name = avworkspace_name()  
)
```

```

    source,
    recursive = FALSE,
    parallel = TRUE,
    namespace = avworkspace_namespace(),
    name = avworkspace_name()
)

avruntimes()

avruntime(
  project = GCPtools::gcloud_project(),
  account = GCPtools::gcloud_account()
)

avdisks()

```

### Arguments

|                |                                                                                                                                                                                          |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| table          | character(1) table name as returned by, e.g., avtables().                                                                                                                                |
| n              | numeric(1) maximum number of rows to return                                                                                                                                              |
| page           | integer(1) first page of iteration                                                                                                                                                       |
| pageSize       | integer(1) number of records per page. Generally, larger page sizes are more efficient.                                                                                                  |
| sortField      | character(1) field used to sort records when determining page order. Default is the entity field.                                                                                        |
| sortDirection  | character(1) direction to sort entities ("asc"ending or "desc"ending) when paging.                                                                                                       |
| filterTerms    | character(1) string literal to select rows with an exact (substring) matches in column.                                                                                                  |
| filterOperator | character(1) operator to use when multiple terms in filterTerms=, either "and" (default) or "or".                                                                                        |
| namespace      | character(1) AnVIL workspace namespace as returned by, e.g., avworkspace_namespace()                                                                                                     |
| name           | character(1) AnVIL workspace name as returned by, eg., avworkspace_name().                                                                                                               |
| na             | in avtable() and avtable_paged(), character() of strings to be interpreted as missing values. In avtable_import() character(1) value to use for representing NA_character_. See Details. |
| job_status     | tibble() of job identifiers, returned by avtable_import() and avtable_import_set().                                                                                                      |
| path           | For avfiles_ls(), the character(1) file or directory path to list. For avfiles_rm(), the character() (perhaps with length greater than 1) of files or directory paths.                   |
| full_names     | logical(1) return names relative to path (FALSE, default) or root of the workspace bucket?                                                                                               |
| recursive      | logical(1) list files recursively?                                                                                                                                                       |
| source         | character() file paths. for avfiles_backup(), source can include directory names when recursive = TRUE.                                                                                  |

|             |                                                                                                                 |
|-------------|-----------------------------------------------------------------------------------------------------------------|
| destination | character(1) a google bucket (gs://<bucket-id>/...) to write files. The default is the workspace bucket.        |
| parallel    | logical(1) backup files using parallel transfer? See ?avcopy().                                                 |
| project     | character(1) project (billing account) name, as returned by, e.g., gcloud_project() or avworkspace_namespace(). |
| account     | character(1) google account (email address associated with billing account), as returned by gcloud_account().   |

## Details

avfiles\_backup() can be used to back-up individual files or entire directories, recursively. When recursive = FALSE, files are backed up to the bucket with names approximately paste0(destination, "/", basename(source)). When recursive = TRUE and source is a directory path/to/foo/, files are backed up to b "/", dir(basename(source), full.names = TRUE)). Naming conventions are described in detail in gsutil\_help("cp").

avfiles\_restore() behaves in a manner analogous to avfiles\_backup(), copying files from the workspace bucket to the compute node file system.

## Value

avtable\_paged(): a tibble of data corresponding to the AnVIL table table in the specified workspace.

avfiles\_ls() returns a character vector of files in the workspace bucket.

avfiles\_backup() returns, invisibly, the status code of the avcopy() command used to back up the files.

avfiles\_rm() on success, returns a list of the return codes of avremove(), invisibly.

avruntimes() returns a tibble with columns

- id: integer() runtime identifier.
- googleProject: character() billing account.
- tool: character() e.g., "Jupyter", "RStudio".
- status character() e.g., "Stopped", "Running".
- creator character() AnVIL account, typically "user@gmail.com".
- createdDate character() creation date.
- destroyedDate character() destruction date, or NA.
- dateAccessed character() date of (first?) access.
- runtimeName character().
- clusterServiceAccount character() service ('pet') account for this runtime.
- masterMachineType character() It is unclear which 'tool' populates which of the machineType columns).
- workerMachineType character().
- machineType character().
- persistentDiskId integer() identifier of persistent disk (see avdisks()), or NA.

`avruntime()` returns a tibble with the same structure as the return value of `avruntimes()`.

`avdisks()` returns a tibble with columns

- `id` character() disk identifier.
- `googleProject`: character() billing account.
- `status`, e.g. "Ready"
- `size` integer() in GB.
- `diskType` character().
- `blockSize` integer().
- `creator` character() AnVIL account, typically "user@gmail.com".
- `createdDate` character() creation date.
- `destroyedDate` character() destruction date, or NA.
- `dateAccessed` character() date of (first?) access.
- `zone` character() e.g.. "us-central1-a".
- `name` character().

## Examples

```
library(AnVILBase)
if (has_avworkspace(platform = gcp()) && interactive())
  avfiles_ls()

library(AnVILBase)
if (has_avworkspace(platform = gcp()) && interactive()) {
  ## backup all files in the current directory
  ## default buckets are gs://<bucket-id>/<file-names>
  avfiles_backup(dir())
  ## backup working directory, recursively
  ## default buckets are gs://<bucket-id>/<basename(getwd())>/...
  avfiles_backup(getwd(), recursive = TRUE)
}

if (has_avworkspace(platform = gcp()))
  ## from within AnVIL
  avruntimes()

if (has_avworkspace(strict = TRUE, platform = gcp()))
  ## from within AnVIL
  avdisks()
```

avdata

*Import data into the current workspace***Description**

avdata() returns key-value tables representing the information visualized under the DATA tab, 'REFERENCE DATA' and 'OTHER DATA' items. avdata\_import() updates (modifies or creates new, but does not delete) rows in 'REFERENCE DATA' or 'OTHER DATA' tables.

**Usage**

```
avdata(namespace = avworkspace_namespace(), name = avworkspace_name())
```

```
avdata_import(
  .data,
  namespace = avworkspace_namespace(),
  name = avworkspace_name()
)
```

**Arguments**

|           |                                                                                      |
|-----------|--------------------------------------------------------------------------------------|
| namespace | character(1) AnVIL workspace namespace as returned by, e.g., avworkspace_namespace() |
| name      | character(1) AnVIL workspace name as returned by, eg., avworkspace_name().           |
| .data     | A tibble or data.frame for import as an AnVIL table.                                 |

**Value**

avdata() returns a tibble with five columns: "type" represents the origin of the data from the 'REFERENCE' or 'OTHER' data menus. "table" is the table name in the REFERENCE menu, or 'workspace' for the table in the 'OTHER' menu, the key used to access the data element, the value label associated with the data element and the value (e.g., google bucket) of the element.

avdata\_import() returns, invisibly, the subset of the input table used to update the AnVIL tables.

**Examples**

```
library(AnVILBase)
if (has_avworkspace(strict = TRUE, platform = gcp())) {
  ## from within AnVIL
  data <- avdata()
  data
  if (interactive())
    avdata_import(data)
}
```

## Description

avnotebooks() returns the names of the notebooks associated with the current workspace.

## Usage

```
## S4 method for signature 'gcp'
avnotebooks(
  local = FALSE,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  ...,
  platform = cloud_platform()
)
```

```
## S4 method for signature 'gcp'
avnotebooks_localize(
  destination,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  dry = TRUE,
  ...,
  platform = cloud_platform()
)
```

```
## S4 method for signature 'gcp'
avnotebooks_delocalize(
  source,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  dry = TRUE,
  ...,
  platform = cloud_platform()
)
```

## Arguments

|           |                                                                                                                                                                                            |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| local     | = logical(1) notebooks located on the workspace (local = FALSE, default) or runtime / local instance (local = TRUE). When local = TRUE, the notebook path is <avworkspace_name>/notebooks. |
| namespace | character(1) AnVIL workspace namespace as returned by, e.g., avworkspace_namespace()                                                                                                       |
| name      | character(1) AnVIL workspace name as returned by, eg., avworkspace_name().                                                                                                                 |
| ...       | Additional arguments passed to lower level functions (not used).                                                                                                                           |

|             |                                                                                                                                                                                                                                        |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| platform    | gcp() The cloud platform class to dispatch on as given by <code>AnVILBase::cloud_platform</code> . Typically not set manually as <code>cloud_platform()</code> returns the "gcp" class for Google Cloud Platform workspaces on AnVIL.  |
| destination | missing or character(1) file path to the local file system directory for synchronization. The default location is <code>~/&lt;avworkspace_name&gt;/notebooks</code> . Out-of-date local files are replaced with the workspace version. |
| dry         | logical(1), when TRUE (default), return the consequences of the operation without actually performing the operation.                                                                                                                   |
| source      | missing or character(1) file path to the local file system directory for synchronization. The default location is <code>~/&lt;avworkspace_name&gt;/notebooks</code> . Out-of-date local files are replaced with the workspace version. |

### Value

`avnotebooks()` returns a character vector of buckets / files located in the workspace 'Files/notebooks' bucket path, or on the local file system.

`avnotebooks_localize()` returns the exit status of `gsutil_rsync()`.

`avnotebooks_delocalize()` returns the exit status of `gsutil_rsync()`.

### Functions

- `avnotebooks(gcp)`: List notebooks in the workspace
- `avnotebooks_localize(gcp)`: Synchronizes the content of the workspace bucket to the local file system.
- `avnotebooks_delocalize(gcp)`: Synchronizes the content of the notebook location of the local file system to the workspace bucket.

### Examples

```
library(AnVILBase)
if (has_avworkspace(strict = TRUE, platform = gcp())) {
  avnotebooks()
  avnotebooks_localize() # dry run
  try(avnotebooks_delocalize()) # dry run, fails if no local resource
}
```

### Description

Tables can be visualized under the DATA tab, TABLES item. `avtable()` returns an AnVIL table. `avtable_paged()` retrieves an AnVIL table by requesting the table in 'chunks', and may be appropriate for large tables. `avtable_import()` imports a data.frame to an AnVIL table. `avtable_import_set()` imports set membership (i.e., a subset of an existing table) information to an AnVIL table. `avtable_delete_values()` removes rows from an AnVIL table.

**Usage**

```
## S4 method for signature 'gcp'
avtables(
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avtable(
  table,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  na = c("", "NA"),
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avtable_import(
  .data,
  entity = names(.data)[[1L]],
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  delete_empty_values = FALSE,
  na = "NA",
  n = Inf,
  page = 1L,
  pageSize = NULL,
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avtable_import_set(
  .data,
  origin,
  set = names(.data)[[1]],
  member = names(.data)[[2]],
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  delete_empty_values = FALSE,
  na = "NA",
  n = Inf,
  page = 1L,
  pageSize = NULL,
  ...,

```

```

    platform = cloud_platform()
  )

## S4 method for signature 'gcp'
avtable_delete(
  table,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avtable_delete_values(
  table,
  values,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  ...,
  platform = cloud_platform()
)

```

## Arguments

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| namespace           | character(1) AnVIL workspace namespace as returned by, e.g., <code>avworkspace_namespace()</code>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| name                | character(1) AnVIL workspace name as returned by, eg., <code>avworkspace_name()</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| ...                 | Additional arguments passed to lower level functions (not used).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| platform            | <code>gcp()</code> The cloud platform class to dispatch on as given by <a href="#">AnVILBase::cloud_platform</a> . Typically not set manually as <code>cloud_platform()</code> returns the "gcp" class for Google Cloud Platform workspaces on AnVIL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| table               | character(1) table name as returned by, e.g., <code>avtables()</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| na                  | in <code>avtable()</code> and <code>avtable_paged()</code> , character() of strings to be interpreted as missing values. In <code>avtable_import()</code> character(1) value to use for representing <code>NA_character_</code> . See Details.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| .data               | A tibble or data.frame for import as an AnVIL table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| entity              | character(1) column name of .data to be used as imported table name. When the table comes from R, this is usually a column name such as <code>sample</code> . The data will be imported into AnVIL as a table <code>sample</code> , with the sample column included with suffix <code>_id</code> , e.g., <code>sample_id</code> . A column in .data with suffix <code>_id</code> can also be used, e.g., <code>entity = "sample_id"</code> , creating the table <code>sample</code> with column <code>sample_id</code> in AnVIL. Finally, a value of <code>entity</code> that is not a column in .data, e.g., <code>entity = "unknown"</code> , will cause a new table with name <code>entity</code> and entity values <code>seq_len(nrow(.data))</code> . |
| delete_empty_values | logical(1) when TRUE, remove entities not include in .data from the DATA table. Default: FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                       |                                                                                                                                                                                                                                               |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>n</code>        | numeric(1) maximum number of rows to return                                                                                                                                                                                                   |
| <code>page</code>     | integer(1) first page of iteration                                                                                                                                                                                                            |
| <code>pageSize</code> | integer(1) number of records per page. Generally, larger page sizes are more efficient.                                                                                                                                                       |
| <code>origin</code>   | character(1) name of the entity (table) used to create the set e.g "sample", "participant", etc.                                                                                                                                              |
| <code>set</code>      | character(1) column name of <code>.data</code> identifying the set(s) to be created.                                                                                                                                                          |
| <code>member</code>   | character() vector of entity from the avtable identified by <code>origin</code> . The values may repeat if an ID is in more than one set                                                                                                      |
| <code>values</code>   | vector of values in the entity (key) column of table to be deleted. A table sample has an associated entity column with suffix <code>_id</code> , e.g., <code>sample_id</code> . Rows with entity column entries matching values are deleted. |

## Details

Treatment of missing values in `avtable()`, `avtable_paged()` and `avtable_import()` are handled by the `na` parameter.

`avtable()` may sometimes result in a curl error 'Error in curl::curl\_fetch\_memory' or a 'Internal Server Error (HTTP 500)' This may be due to a server time-out when trying to read a large (more than 50,000 rows?) table; using `avtable_paged()` may address this problem.

For `avtable()` and `avtable_paged()`, the default `na = c("", "NA")` treats empty cells or cells containing "NA" in a Terra data table as `NA_character_` in R. Use `na = character()` to indicate no missing values, `na = "NA"` to retain the distinction between "" and `NA_character_`.

For `avtable_import()`, the default `na = "NA"` records `NA_character_` in R as the character string "NA" in an AnVIL data table.

The default setting (`na = "NA"` in `avtable_import()`, `na = c("", NA_character_)` in `avtable()`), is appropriate to 'round-trip' data from R to AnVIL and back when character vectors contain only `NA_character_`. Use `na = "NA"` in both functions to round-trip data containing both `NA_character_` and "NA". Use a distinct string, e.g., `na = "__MISSING_VALUE__"`, for both arguments if the data contains a string "NA" as well as `NA_character_`.

`avtable_import()` tries to work around limitations in `.data` size in the AnVIL platform, using `pageSize` (number of rows) to import so that approximately 1500000 elements (rows x columns) are uploaded per chunk. For large `.data`, a progress bar summarizes progress on the import. Individual chunks may nonetheless fail to upload, with common reasons being an internal server error (HTTP error code 500) or transient authorization failure (HTTP 401). In these and other cases `avtable_import()` reports the failed page(s) as warnings. The user can attempt to import these individually using the `page` argument. If many pages fail to import, a strategy might be to provide an explicit `pageSize` less than the automatically determined size.

`avtable_import_set()` creates new rows in a table `<origin>_set`. One row will be created for each distinct value in the column identified by `set`. Each row entry has a corresponding column `<origin>` linking to one or more rows in the `<origin>` table, as given in the `member` column. The operation is somewhat like `split(member, set)`.

**Value**

`avtables()`: A tibble with columns identifying the table, the number of records, and the column names.

`avtable()`: a tibble of data corresponding to the AnVIL table `table` in the specified workspace.

`avtable_import_set()` returns a character(1) name of the imported AnVIL tibble.

`avtable_delete()` returns TRUE if the table is successfully deleted.

`avtable_delete_values()` returns a tibble representing deleted entities, invisibly.

**Functions**

- `avtables(gcp)`: `avtables()` describes tables available in a workspace
- `avtable(gcp)`: `avtable()` retrieves a table from an AnVIL workspace
- `avtable_import(gcp)`: upload a table to the DATA tab
- `avtable_import_set(gcp)`:
- `avtable_delete(gcp)`: Delete a table from the AnVIL workspace.
- `avtable_delete_values(gcp)`:

**Examples**

```
if (interactive()) {
  avtables("waldronlab-terra", "Tumor_Only_CNV")
  avtable("participant", "waldronlab-terra", "Tumor_Only_CNV")

  library(dplyr)
  ## mtcars dataset
  mtcars_tbl <-
    mtcars |>
    as_tibble(rownames = "model_id") |>
    mutate(model_id = gsub(" ", "-", model_id))

  avworkspace("waldronlab-terra/mramos-wlab-gcp-0")

  avstatus <- avtable_import(mtcars_tbl)

  avtable_import_status(avstatus)

  set_status <- avtable("model") |>
    avtable_import_set("model", "cyl", "model_id")

  avtable_import_status(set_status)

  ## won't be able to delete a row that is referenced in another table
  avtable_delete_values("model", "Mazda-RX4")

  ## delete the set
  avtable_delete("model_set")

  ## then delete the row
```

```

avtable_delete_values("model", "Mazda-RX4")

## recreate the set (if needed)
avtable("model") |>
  avtable_import_set("model", "cyl", "model_id")

}
library(AnVILBase)
if (has_avworkspace(platform = gcp()) && interactive()) {
  ## editable copy of '1000G-high-coverage-2019' workspace
  avworkspace("bioconductor-rpci-anvil/1000G-high-coverage-2019")
  sample <-
    avtable("sample") %>% # existing table
    mutate(set = sample(head(LETTERS), nrow(.), TRUE)) # arbitrary groups
  sample %>% # new 'participant_set' table
    avtable_import_set("participant", "set", "participant")
  sample %>% # new 'sample_set' table
    avtable_import_set("sample", "set", "name")
}

```

---

avworkflow-methods      *AnVIL workflow methods*

---

## Description

Methods for working with AnVIL workflow execution. `avworkflow_jobs()` returns a tibble summarizing submitted workflow jobs for a namespace and name.

## Usage

```

## S4 method for signature 'gcp'
avworkflow_jobs(
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  ...,
  platform = cloud_platform()
)

```

## Arguments

|                        |                                                                                                                                                                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>namespace</code> | character(1) AnVIL workspace namespace as returned by, e.g., <code>avworkspace_namespace()</code>                                                                                                                                                     |
| <code>name</code>      | character(1) AnVIL workspace name as returned by, eg., <code>avworkspace_name()</code> .                                                                                                                                                              |
| <code>...</code>       | Additional arguments passed to lower level functions (not used).                                                                                                                                                                                      |
| <code>platform</code>  | <code>gcp()</code> The cloud platform class to dispatch on as given by <a href="#">AnVILBase::cloud_platform</a> . Typically not set manually as <code>cloud_platform()</code> returns the "gcp" class for Google Cloud Platform workspaces on AnVIL. |

**Value**

avworkflow\_jobs() returns a tibble, sorted by submissionDate, with columns

- submissionId character() job identifier from the workflow runner.
- submitter character() AnVIL user id of individual submitting the job.
- submissionDate POSIXct() date (in local time zone) of job submission.
- status character() job status, with values 'Accepted' 'Evaluating' 'Submitting' 'Submitted' 'Aborting' 'Aborted' 'Done'
- succeeded integer() number of workflows succeeding.
- failed integer() number of workflows failing.

**Functions**

- avworkflow\_jobs(gcp): List workflow jobs in the workspace

**Examples**

```
library(AnVILBase)
if (has_avworkspace(strict = TRUE, platform = gcp()))
  ## from within AnVIL
  avworkflow_jobs()
```

---

avworkflows

*Workflow submissions and file outputs*


---

**Description**

avworkflows() returns a tibble summarizing available workflows.

avworkflow\_files() returns a tibble containing information and file paths to workflow outputs.

avworkflow\_localize() creates or synchronizes a local copy of files with files stored in the workspace bucket and produced by the workflow.

avworkflow\_run() runs the workflow of the configuration.

avworkflow\_stop() stops the most recently submitted workflow job from running.

avworkflow\_info() returns a tibble containing workflow information, including workflowName, status, start and end time, inputs and outputs.

**Usage**

```
avworkflows(namespace = avworkspace_namespace(), name = avworkspace_name())
```

```
avworkflow_files(
  submissionId = NULL,
  workflowId = NULL,
  bucket,
```

```

    namespace = avworkspace_namespace(),
    name = avworkspace_name()
  )

  avworkflow_localize(
    submissionId = NULL,
    workflowId = NULL,
    destination = NULL,
    type = c("control", "output", "all"),
    bucket = avstorage(),
    dry = TRUE
  )

  avworkflow_run(
    config,
    entityName,
    entityType = config$rootEntityType,
    deleteIntermediateOutputFiles = FALSE,
    useCallCache = TRUE,
    useReferenceDisks = FALSE,
    namespace = avworkspace_namespace(),
    name = avworkspace_name(),
    dry = TRUE
  )

  avworkflow_stop(
    submissionId = NULL,
    namespace = avworkspace_namespace(),
    name = avworkspace_name(),
    dry = TRUE
  )

  avworkflow_info(
    submissionId = NULL,
    namespace = avworkspace_namespace(),
    name = avworkspace_name()
  )

```

### Arguments

|              |                                                                                                                                                                       |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| namespace    | character(1) AnVIL workspace namespace as returned by, e.g., <code>avworkspace_namespace()</code>                                                                     |
| name         | character(1) AnVIL workspace name as returned by, e.g., <code>avworkspace_name()</code> .                                                                             |
| submissionId | a character() of workflow submission ids, or a tibble with column <code>submissionId</code> , or NULL / missing. See 'Details'.                                       |
| workflowId   | a character(1) of internal identifier associated with one workflow in the submission, or NULL / missing.                                                              |
| bucket       | character(1) DEFUNCT - name of the google bucket in which the workflow products are available, as <code>gs://...</code> . Usually the bucket of the active workspace, |

|                                            |                                                                                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                            | returned by <code>avstorage()</code> .                                                                                                                                                                                                                                                                                                                                                                  |
| <code>destination</code>                   | character(1) file path to the location where files will be synchronized. For directories in the current working directory, be sure to prepend with <code>"/"</code> . When <code>NULL</code> , the <code>submissionId</code> is used as the destination. <code>destination</code> may also be a google bucket, in which case the workflow files are synchronized from the workspace to a second bucket. |
| <code>type</code>                          | character(1) copy "control" (default), "output", or "all" files produced by a workflow.                                                                                                                                                                                                                                                                                                                 |
| <code>dry</code>                           | logical(1) when <code>TRUE</code> (default), report the consequences but do not perform the action requested. When <code>FALSE</code> , perform the action.                                                                                                                                                                                                                                             |
| <code>config</code>                        | a <code>avworkflow_configuration</code> object of the workflow that will be run. Only <code>entityType</code> and method configuration name and namespace are used from <code>config</code> ; other configuration values must be communicated to AnVIL using <code>avworkflow_configuration_set()</code> .                                                                                              |
| <code>entityName</code>                    | character(1) or <code>NULL</code> name of the set of samples to be used when running the workflow. <code>NULL</code> indicates that no sample set will be used.                                                                                                                                                                                                                                         |
| <code>entityType</code>                    | character(1) or <code>NULL</code> type of root entity used for the workflow. <code>NULL</code> means that no root entity will be used.                                                                                                                                                                                                                                                                  |
| <code>deleteIntermediateOutputFiles</code> | logical(1) whether or not to delete intermediate output files when the workflow completes.                                                                                                                                                                                                                                                                                                              |
| <code>useCallCache</code>                  | logical(1) whether or not to read from cache for this submission.                                                                                                                                                                                                                                                                                                                                       |
| <code>useReferenceDisks</code>             | logical(1) whether or not to use pre-built disks for common genome references. Default: <code>FALSE</code> .                                                                                                                                                                                                                                                                                            |

## Details

For `avworkflow_files()`, the `submissionId` is the identifier associated with the submission of one (or more) workflows, and is present in the return value of `avworkflow_jobs()`; the example illustrates how the first row of `avworkflow_jobs()` (i.e., the most recently completed workflow) can be used as input to `avworkflow_files()`. When `submissionId` is not provided, the return value is for the most recently submitted workflow of the namespace and name of `avworkspace()`.

`avworkflow_localize()`. `type = "control"` files summarize workflow progress; they can be numerous but are frequently small and quickly synchronized. `type = "output"` files are the output products of the workflow stored in the workspace bucket. Depending on the workflow, outputs may be large, e.g., aligned reads in bam files. See `avcopy()` to copy individual files from the bucket to the local drive.

`avworkflow_localize()` treats `submissionId` in the same way as `avworkflow_files()`: when missing, files from the most recent workflow job are candidates for localization.

## Value

`avworkflows()` returns a tibble. Each workflow is in a 'namespace' and has a 'name', as illustrated in the example. Columns are

- `name`: workflow name.

- namespace: workflow namespace (often the same as the workspace namespace).
- rootEntityType: name of the avtable() used to retrieve inputs.
- methodRepoMethod.methodUri: source of the method, e.g., a dockstore URI.
- methodRepoMethod.sourceRepo: source repository, e.g., dockstore.
- methodRepoMethod.methodPath: path to method, e.g., a dockerstore method might reference a github repository.
- methodRepoMethod.methodVersion: the version of the method, e.g., 'main' branch of a github repository.

avworkflow\_files() returns a tibble with columns

- file: character() 'base name' of the file in the bucket.
- workflow: character() name of the workflow the file is associated with.
- task: character() name of the task in the workflow that generated the file.
- path: character() full path to the file in the google bucket.
- submissionId: character() internal identifier associated with the submission the files belong to.
- workflowId: character() internal identifier associated with each workflow (e.g., row of an avtable() used as input) in the submission.
- submissionRoot: character() path in the workspace bucket to the root of files created by this submission.
- namespace: character() AnVIL workspace namespace (billing account) associated with the submissionId.
- name: character(1) AnVIL workspace name associated with the submissionId.

avworkflow\_localize() prints a message indicating the number of files that are (if dry = FALSE) or would be localized. If no files require localization (i.e., local files are not older than the bucket files), then no files are localized. avworkflow\_localize() returns a tibble of file name and bucket path of files to be synchronized.

avworkflow\_run() returns config, invisibly.

avworkflow\_stop() returns (invisibly) TRUE on successfully requesting that the workflow stop, FALSE if the workflow is already aborting, aborted, or done.

avworkflow\_info() returns a tibble with columns: submissionId, workflowId, workflowName, status, start, end, inputs and outputs.

## Examples

```
library(AnVILBase)
if (has_avworkspace(strict = TRUE, platform = gcp()))
  ## from within AnVIL
  avworkflows() %>% select(namespace, name)

if (has_avworkspace(strict = TRUE, platform = gcp())) {
  ## e.g., from within AnVIL
  jobs <- avworkflow_jobs()
  if (nrow(jobs)) {
    jobs |>
```

```

        ## select most recent workflow
        head(1) |>
        ## find paths to output and log files on the bucket
        avworkflow_files()
    }
}

if (has_avworkspace(strict = TRUE, platform = gcp()))
  avworkflow_localize(dry = TRUE)

if (has_avworkspace(strict = TRUE, platform = gcp()) && interactive()) {
  entityName <- avtable("participant_set") |>
    pull(participant_set_id) |>
    head(1)
  avworkflow_run(new_config, entityName)
}

if (has_avworkspace(strict = TRUE, platform = gcp()) && interactive()) {
  avworkflow_stop()
}
if (has_avworkspace(strict = TRUE, platform = gcp()))
  avworkflow_info()

```

---

avworkflow\_configurations

*Workflow configuration*


---

## Description

Functions on this help page facilitate getting, updating, and setting workflow configuration parameters. See `?avworkflow` for additional relevant functionality.

`avworkflow_namespace()` and `avworkflow_name()` are utility functions to record the workflow namespace and name required when working with workflow configurations. `avworkflow()` provides a convenient way to provide workflow namespace and name in a single command, `namespace/name`.

`avworkflow_configuration_get()` returns a list structure describing an existing workflow configuration.

`avworkflow_configuration_inputs()` returns a data.frame template for the inputs defined in a workflow configuration. This template can be used to provide custom inputs for a configuration.

`avworkflow_configuration_outputs()` returns a data.frame template for the outputs defined in a workflow configuration. This template can be used to provide custom outputs for a configuration.

`avworkflow_configuration_update()` returns a list structure describing a workflow configuration with updated inputs and / or outputs.

`avworkflow_configuration_set()` updates an existing configuration in Terra / AnVIL, e.g., changing inputs to the workflow.

`avworkflow_configuration_template()` returns a template for defining workflow configurations. This template can be used as a starting point for providing a custom configuration.

**Usage**

```

avworkflow_namespace(workflow_namespace = NULL)

avworkflow_name(workflow_name = NULL)

avworkflow(workflow = NULL)

avworkflow_configuration_get(
  workflow_namespace = avworkflow_namespace(),
  workflow_name = avworkflow_name(),
  namespace = avworkspace_namespace(),
  name = avworkspace_name()
)

avworkflow_configuration_inputs(config)

avworkflow_configuration_outputs(config)

avworkflow_configuration_update(
  config,
  inputs = avworkflow_configuration_inputs(config),
  outputs = avworkflow_configuration_outputs(config)
)

avworkflow_configuration_set(
  config,
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  dry = TRUE
)

avworkflow_configuration_template()

## S3 method for class 'avworkflow_configuration'
print(x, ...)
```

**Arguments**

|                    |                                                                                                     |
|--------------------|-----------------------------------------------------------------------------------------------------|
| workflow_namespace | character(1) AnVIL workflow namespace, as returned by, e.g., the namespace column of avworkflows(). |
| workflow_name      | character(1) AnVIL workflow name, as returned by, e.g., the name column of avworkflows().           |
| workflow           | character(1) representing the combined workflow namespace and name, as namespace/name.              |
| namespace          | character(1) AnVIL workspace namespace as returned by, e.g., avworkspace_namespace().               |
| name               | character(1) AnVIL workspace name as returned by, e.g., avworkspace_name().                         |

|         |                                                                                                                                                                                                  |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| config  | a named list describing the full configuration, e.g., created from editing the return value of <code>avworkflow_configuration_set()</code> or <code>avworkflow_configuration_template()</code> . |
| inputs  | the new inputs to be updated in the workflow configuration. If none are specified, the inputs from the original configuration will be used and no changes will be made.                          |
| outputs | the new outputs to be updated in the workflow configuration. If none are specified, the outputs from the original configuration will be used and no changes will be made.                        |
| dry     | logical(1) when TRUE (default), report the consequences but do not perform the action requested. When FALSE, perform the action.                                                                 |
| x       | Object of class <code>avworkflow_configuration</code> .                                                                                                                                          |
| ...     | additional arguments to <code>print()</code> ; unused.                                                                                                                                           |

### Details

The exact format of the configuration is important.

One common problem is that a scalar character vector `"bar"` is interpreted as a json 'array' `["bar"]` rather than a json string `"bar"`. Enclose the string with `jsonlite::unbox("bar")` in the configuration list if the length 1 character vector in R is to be interpreted as a json string.

A second problem is that an unquoted unboxed character string `unbox("foo")` is required by AnVIL to be quoted. This is reported as a warning() about invalid inputs or outputs, and the solution is to provide a quoted string `unbox('"foo"')`.

### Value

`avworkflow_namespace()`, and `avworkflow_name()` return `character(1)` identifiers. `avworkflow()` returns the `character(1)` concatenated namespace and name. The value returned by `avworkflow_name()` will be percent-encoded (e.g., spaces `" "` replaced by `"%20"`).

`avworkflow_configuration_get()` returns a list structure describing the configuration. See `avworkflow_configuration_` for the structure of a typical workflow.

`avworkflow_configuration_inputs()` returns a `data.frame` providing a template for the configuration inputs, with the following columns:

- `inputType`
- `name`
- `optional`
- `attribute`

The only column of interest to the user is the `attribute` column, this is the column that should be changed for customization.

`avworkflow_configuration_outputs()` returns a `data.frame` providing a template for the configuration outputs, with the following columns:

- `name`
- `outputType`

- attribute

The only column of interest to the user is the attribute column, this is the column that should be changed for customization.

`avworkflow_configuration_update()` returns a list structure describing the updated configuration.

`avworkflow_configuration_set()` returns an object describing the updated configuration. The return value includes invalid or unused elements of the config input. Invalid or unused elements of config are also reported as a warning.

`avworkflow_configuration_template()` returns a list providing a template for configuration lists, with the following structure:

- namespace character(1) configuration namespace.
- name character(1) configuration name.
- rootEntityType character(1) or missing. the name of the table (from `avtables()`) containing the entities referenced in inputs, etc., by the keyword 'this.'
- prerequisites named list (possibly empty) of prerequisites.
- inputs named list (possibly empty) of inputs. Form of input depends on method, and might include, e.g., a reference to a field in a table referenced by `avtables()` or a character string defining an input constant.
- outputs named list (possibly empty) of outputs.
- methodConfigVersion integer(1) identifier for the method configuration.
- methodRepoMethod named list describing the method, with character(1) elements described in the return value for `avworkflows()`.
  - methodUri
  - sourceRepo
  - methodPath
  - methodVersion. The REST specification indicates that this has type integer, but the documentation indicates either integer or string.
- deleted logical(1) of uncertain purpose.

### See Also

The help page `?avworkflow` for discovering, running, stopping, and retrieving outputs from workflows.

### Examples

```
if (has_avworkspace(platform = gcp()) && interactive()) {
  ## set the namespace and name as appropriate
  avworkspace("bioconductor-rpci-anvil/Bioconductor-Workflow-DESeq2")

  ## discover available workflows in the workspace
  avworkflows()

  ## record the workflow of interest
```

```

avworkflow("bioconductor-rpci-anvil/AnVILBulkRNASeq")

## what workflows are available?
available_workflows <- avworkflows()

## retrieve the current configuration
config <- avworkflow_configuration_get()
config

## what are the inputs and outputs?
inputs <- avworkflow_configuration_inputs(config)
inputs

outputs <- avworkflow_configuration_outputs(config)
outputs

## update inputs or outputs, e.g., this input can be anything...
inputs <-
  inputs |>
  dplyr::mutate(attribute = ifelse(
    name == "salmon.transcriptome_index_name",
    "new_index_name",
    attribute
  ))
new_config <- avworkflow_configuration_update(config, inputs)
new_config

## set the new configuration in AnVIL; use dry = FALSE to actually
## update the configuration
avworkflow_configuration_set(config)
}

## avworkflow_configuration_template() is a utility function that may
## help understanding what the inputs and outputs should be
avworkflow_configuration_template() |>
  str()

avworkflow_configuration_template()

```

---

avworkspace-methods      *AnVIL Workspace GCP methods*

---

## Description

`avworkspace_namespace()` and `avworkspace_name()` are utility functions to retrieve workspace namespace and name from environment variables or interfaces usually available in AnVIL notebooks or RStudio sessions. `avworkspace()` provides a convenient way to specify workspace namespace and name in a single command. `avworkspace_clone()` clones (copies) an existing workspace, possibly into a new namespace (billing account).

**Usage**

```
## S4 method for signature 'gcp'
avworkspaces(..., platform = cloud_platform())

## S4 method for signature 'gcp'
avworkspace_namespace(
  namespace = NULL,
  warn = TRUE,
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avworkspace_name(name = NULL, warn = TRUE, ..., platform = cloud_platform())

## S4 method for signature 'gcp'
avworkspace(workspace = NULL, ..., platform = cloud_platform())

## S4 method for signature 'gcp'
avworkspace_clone(
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  to_namespace = namespace,
  to_name,
  storage_region = "US",
  bucket_location,
  ...,
  platform = cloud_platform()
)
```

**Arguments**

|                             |                                                                                                                                                                                                                                                       |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>...</code>            | additional arguments passed as-is to the <code>gsutil</code> subcommand.                                                                                                                                                                              |
| <code>platform</code>       | <code>gcp()</code> The cloud platform class to dispatch on as given by <a href="#">AnVILBase::cloud_platform</a> . Typically not set manually as <code>cloud_platform()</code> returns the "gcp" class for Google Cloud Platform workspaces on AnVIL. |
| <code>namespace</code>      | character(1) AnVIL workspace namespace as returned by, e.g., <code>avworkspace_namespace()</code>                                                                                                                                                     |
| <code>warn</code>           | logical(1) when TRUE (default), generate a warning when the workspace namespace or name cannot be determined.                                                                                                                                         |
| <code>name</code>           | character(1) AnVIL workspace name as returned by, e.g., <code>avworkspace_name()</code> .                                                                                                                                                             |
| <code>workspace</code>      | when present, a character(1) providing the concatenated namespace and name, e.g., "bioconductor-rpci-anvil/Bioconductor-Package-AnVIL"                                                                                                                |
| <code>to_namespace</code>   | character(1) workspace (billing account) in which to make the clone.                                                                                                                                                                                  |
| <code>to_name</code>        | character(1) name of the cloned workspace.                                                                                                                                                                                                            |
| <code>storage_region</code> | character(1) region (NO multi-region, except the default) in which bucket attached to the workspace should be created.                                                                                                                                |

bucket\_location

character(1) DEFUNCT; use storage\_region instead. Region (NO multi-region, except the default) in which bucket attached to the workspace should be created.

## Details

avworkspace\_namespace() is the billing account. If the namespace= argument is not provided, try gcloud\_project(), and if that fails try Sys.getenv("WORKSPACE\_NAMESPACE").

avworkspace\_name() is the name of the workspace as it appears in <https://app.terra.bio/#workspaces>. If not provided, avworkspace\_name() tries to use Sys.getenv("WORKSPACE\_NAME").

Namespace and name values are cached across sessions, so explicitly providing avworkspace\_name\*() is required at most once per session. Revert to system settings with arguments NA.

## Value

avworkspace\_namespace(), and avworkspace\_name() return character(1) identifiers. avworkspace() returns the character(1) concatenated namespace and name. The value returned by avworkspace\_name() will be percent-encoded (e.g., spaces " " replaced by "%20").

avworkspace\_clone() returns the namespace and name, in the format namespace/name, of the cloned workspace.

## Functions

- avworkspaces(gcp): list workspaces in the current project as a tibble
- avworkspace\_namespace(gcp): Get or set the namespace of the current workspace
- avworkspace\_name(gcp): Get or set the name of the current workspace
- avworkspace(gcp): Get the current workspace namespace and name combination
- avworkspace\_clone(gcp): Clone the current workspace

## Examples

```
if (has_avworkspace(platform = gcp())) {
  avworkspaces()
  avworkspace_namespace()
  avworkspace_name()
  avworkspace()
}
```

---

drs

*DRS (Data Repository Service) URL management*

---

## Description

drs\_hub() resolves zero or more DRS URLs to their Google bucket location using the DRS Hub API endpoint.

**Usage**

```
drs_hub(source = character())
```

```
drs_nci_crdc(source = character())
```

**Arguments**

source                      character() DRS URLs (beginning with 'drs://') to resources managed by the DRS Hub server (drs\_hub()).

**Value**

drs\_hub() returns a tbl with the following columns:

- drs: character() DRS URIs
- bucket: character() Google cloud bucket
- name: character() object name in bucket
- size: numeric() object size in bytes
- timeCreated: character() object creation time
- timeUpdated: character() object update time
- fileName: character() local file name
- accessUrl: character() signed URL for object access

**drs\_hub**

drs\_hub() uses the DRS Hub API endpoint to resolve a single or multiple DRS URLs to their Google bucket location. The DRS Hub API endpoint requires a gcloud\_access\_token(). The DRS Hub API service is hosted at <https://drshub.dsde-prod.broadinstitute.org>.

**drs\_nci\_crdc**

drs\_nci\_crdc() resolves one or more DRS URLs to their <gdc.cancer.gov> location. The implementation allows the extraction of access\_url values to download the DRS objects. The DRS NCI CRDC service is hosted at <https://nci-crdc.datacommons.io>.

**Examples**

```
if (gcloud_exists() && interactive()) {
  drs_urls <- c(
    "drs://drs.anv0:v2_b3b815c7-b012-37b8-9866-1cb44b597924",
    "drs://drs.anv0:v2_2823eac3-77ae-35e4-b674-13dfab629dc5",
    "drs://drs.anv0:v2_c6077800-4562-30e3-a0ff-aa03a7e0e24f"
  )
  drs_hub(drs_urls)

  drs_nci <- c(
    "drs://nci-crdc.datacommons.io/56e35487-b20f-45ba-8d84-9f16b26c85ea",
    "drs://nci-crdc.datacommons.io/f814f1ec-6850-4ab6-ac0f-df9f77ee185b",
```

```

        "drs://nci-crdc.datacommons.io/d9b591d5-7fe8-43fe-b0b3-4fc0f9736866"
    )
    drs_nci_crdc(drs_nci)
}

```

---

gcloud-deprecated      *gcloud command line utility interface (DEPRECATED)*

---

## Description

These functions invoke the gcloud command line utility. See [GCPtools::gsutil](#) for details on how gcloud is located. **NOTE.** These functions have been moved to the GCPtools package.

gcloud\_access\_token() generates a token for the given service account. The token is cached for the duration of its validity. The token is refreshed when it expires. The token is obtained using the gcloud command line utility for the given gcloud\_account(). The function is mainly used internally by API service functions, e.g., AnVIL::Terra()

gcloud\_exists() tests whether the gcloud() command can be found on this system. After finding the binary location, it runs gcloud version to identify potentially misconfigured installations. See 'Details' section of gsutil for where the application is searched.

gcloud\_account(): report the current gcloud account via gcloud config get-value account.

gcloud\_project(): report the current gcloud project via gcloud config get-value project.

gcloud\_help(): queries gcloud for help for a command or sub-command via gcloud help ....

gcloud\_cmd() allows arbitrary gcloud command execution via gcloud .... Use pre-defined functions in preference to this.

gcloud\_storage() allows arbitrary gcloud storage command execution via gcloud storage .... Typically used for bucket management commands such as rm and cp.

gcloud\_storage\_buckets() provides an interface to the gcloud storage buckets command. This command can be used to create a new bucket via gcloud storage buckets create ....

## Usage

```

gcloud_access_token(service)

gcloud_exists()

gcloud_account(account = NULL)

gcloud_project(project = NULL)

gcloud_help(...)

gcloud_cmd(cmd, ...)

gcloud_storage(cmd, ...)

gcloud_storage_buckets(bucket_cmd = "create", bucket, ...)

```

**Arguments**

|            |                                                                                                                                                                            |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| service    | character(1) The name of the service, e.g. "terra" for which to obtain an access token for.                                                                                |
| account    | character(1) Google account (e.g., user@gmail.com) to use for authentication.                                                                                              |
| project    | character(1) billing project name.                                                                                                                                         |
| ...        | Additional arguments appended to gcloud commands.                                                                                                                          |
| cmd        | character(1) representing a command used to evaluate gcloud cmd ....                                                                                                       |
| bucket_cmd | character(1) representing a buckets command typically used to create a new bucket. It can also be used to add-iam-policy-binding or remove-iam-policy-binding to a bucket. |
| bucket     | character(1) representing a unique bucket name to be created or modified.                                                                                                  |

**Value**

gcloud\_access\_token() returns a simple token string to be used with the given service.  
 gcloud\_exists() returns TRUE when the gcloud application can be found, FALSE otherwise.  
 gcloud\_account() returns a character(1) vector containing the active gcloud account, typically a gmail email address.  
 gcloud\_project() returns a character(1) vector containing the active gcloud project.  
 gcloud\_help() returns an unquoted character() vector representing the text of the help manual page returned by gcloud help ....  
 gcloud\_cmd() returns a character() vector representing the text of the output of gcloud cmd ...

**Examples**

```
if (has_avworkspace(platform = gcp()) && interactive())
  GCPtools::gcloud_access_token("rawls") |> invisible()
GCPtools::gcloud_exists()

if (has_avworkspace(platform = gcp()))
  GCPtools::gcloud_account()

if (has_avworkspace(platform = gcp()))
  GCPtools::gcloud_help()
```

---

gcp-class

*GCP platform class*


---

**Description**

This class is used to represent the GCP platform.

**Usage**

```
gcp()
```

gcp-methods

*Methods compatible with the GCP platform class***Description**

`avcopy()`: copy contents of source to destination. At least one of source or destination must be Google cloud bucket; source can be a character vector with length greater than 1. Use `gsutil_help("cp")` for `gsutil` help.

`avlist()`: List contents of a google cloud bucket or, if source is missing, all Cloud Storage buckets under your default project ID

`avremove()`: remove contents of a Google Cloud Bucket.

`avbackup()`, `avrestore()`: synchronize a source and a destination. If the destination is on the local file system, it must be a directory or not yet exist (in which case a directory will be created).

`avstorage()` returns the workspace bucket, i.e., the google bucket associated with a workspace. Bucket content can be visualized under the 'DATA' tab, 'Files' item.

`avworkspaces()`: returns a tibble with columns including the name, last modification time, namespace, and owner status.

`avtable_import()`: returns a tibble() containing the page number, 'from' and 'to' rows included in the page, job identifier, initial status of the uploaded 'chunks', and any (error) messages generated during status check. Use `avtable_import_status()` to query current status.

**Usage**

```
## S4 method for signature 'gcp'
avcopy(
  source,
  destination,
  ...,
  recursive = FALSE,
  parallel = TRUE,
  platform = cloud_platform()
)
```

```
## S4 method for signature 'gcp'
avlist(
  source = character(),
  recursive = FALSE,
  ...,
  platform = cloud_platform()
)
```

```
## S4 method for signature 'gcp'
avremove(
  source,
  recursive = FALSE,
```

```

    force = FALSE,
    parallel = TRUE,
    ...,
    platform = cloud_platform()
)

## S4 method for signature 'gcp'
avbackup(
  source,
  destination,
  recursive = FALSE,
  exclude = NULL,
  dry = TRUE,
  delete = FALSE,
  parallel = TRUE,
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avrestore(
  source,
  destination,
  recursive = FALSE,
  exclude = NULL,
  dry = TRUE,
  delete = FALSE,
  parallel = TRUE,
  ...,
  platform = cloud_platform()
)

## S4 method for signature 'gcp'
avstorage(
  namespace = avworkspace_namespace(),
  name = avworkspace_name(),
  ...,
  platform = cloud_platform()
)

```

## Arguments

|             |                                                                                                                                                |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| source      | character(1), (character() for avlist(), avcopy()) paths to a google storage bucket, possibly with wild-cards for file-level pattern matching. |
| destination | character(1), google cloud bucket or local file system destination path.                                                                       |
| ...         | additional arguments passed as-is to the gsutil subcommand.                                                                                    |
| recursive   | logical(1); perform operation recursively from source?. Default: FALSE.                                                                        |
| parallel    | logical(1), perform parallel multi-threaded / multi-processing (default is TRUE).                                                              |

|           |                                                                                                                                                                                                                                                                 |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| platform  | <code>gcp()</code> The cloud platform class to dispatch on as given by <a href="#">AnVILBase::cloud_platform</a> . Typically not set manually as <code>cloud_platform()</code> returns the "gcp" class for Google Cloud Platform workspaces on AnVIL.           |
| force     | <code>logical(1)</code> : continue silently despite errors when removing multiple objects. Default: FALSE.                                                                                                                                                      |
| exclude   | <code>character(1)</code> a python regular expression of bucket paths to exclude from synchronization. E.g., <code>'.*(\\.png \\.txt)\$'</code> excludes '.png' and '.txt' files.                                                                               |
| dry       | <code>logical(1)</code> , when TRUE (default), return the consequences of the operation without actually performing the operation.                                                                                                                              |
| delete    | <code>logical(1)</code> , when TRUE, remove files in destination that are not in source. Exercise caution when you use this option: it's possible to delete large amounts of data accidentally if, for example, you erroneously reverse source and destination. |
| namespace | <code>character(1)</code> AnVIL workspace namespace as returned by, e.g., <code>avworkspace_namespace()</code>                                                                                                                                                  |
| name      | <code>character(1)</code> AnVIL workspace name as returned by, e.g., <code>avworkspace_name()</code> .                                                                                                                                                          |

### Details

`avbackup()`: To make "gs://mybucket/data" match the contents of the local directory "data" you could do:

```
avbackup("data", "gs://mybucket/data", delete = TRUE)
```

To make the local directory "data" the same as the contents of gs://mybucket/data:

```
avrestore("gs://mybucket/data", "data", delete = TRUE)
```

If destination is a local path and does not exist, it will be created.

### Value

`avcopy()`: exit status of `avcopy()`, invisibly. `avlist()`: `character()` listing of source content. `avremove()`: exit status of `gsutil rm`, invisibly. `avbackup()`: exit status of `gsutil rsync`, invisibly. `avrestore()`: exit status of `gsutil rsync`, invisibly. `avstorage()` returns a `character(1)` bucket identifier prefixed with `gs://`

### Functions

- `avcopy(gcp)`: copy contents of source to destination with `gsutil`
- `avlist(gcp)`: list contents of source with `gsutil`
- `avremove(gcp)`: remove contents of source with `gsutil`
- `avbackup(gcp)`: backup contents of source with `gsutil`
- `avrestore(gcp)`: restore contents of source with `gsutil`
- `avstorage(gcp)`: get the storage bucket location

## Examples

```
src <-
  "gs://genomics-public-data/1000-genomes/other/sample_info/sample_info.csv"
if (has_avworkspace(platform = gcp())) {
  avcopy(src, tempdir())
  ## internal gsutil_*() commands work with spaces in source or destination
  destination <- file.path(tempdir(), "foo bar")
  avcopy(src, destination)
  file.exists(destination)
}
if (has_avworkspace(strict = TRUE, platform = gcp()))
  ## From within AnVIL...
  bucket <- avstorage() # discover bucket

if (has_avworkspace(strict = TRUE, platform = gcp()) && interactive()) {
  path <- file.path(bucket, "mtcars.tab")
  avlist(dirname(path)) # no 'mtcars.tab'...
  write.table(mtcars, gsutil_pipe(path, "w")) # write to bucket
  gsutil_stat(path) # yep, there!
  read.table(gsutil_pipe(path, "r")) # read from bucket
}
```

---

gsutil-deprecated

*gsutil command line utility interface (DEPRECATED)*


---

## Description

These functions invoke the gsutil command line utility. See the "Details:" section if you have gsutil installed but the package cannot find it. These functions have been moved to the GCPtools package.

gsutil\_requester Pays(): does the google bucket require that the requester pay for access?

gsutil\_exists(): check if the bucket or object exists.

gsutil\_stat(): print, as a side effect, the status of a bucket, directory, or file.

gsutil\_rsync(): synchronize a source and a destination. If the destination is on the local file system, it must be a directory or not yet exist (in which case a directory will be created).

gsutil\_cat(): concatenate bucket objects to standard output

gsutil\_help(): print 'man' page for the gsutil command or subcommand. Note that only commandes documented on this R help page are supported.

gsutil\_pipe(): create a pipe to read from or write to a goooogle bucket object.

## Usage

```
gsutil_requester Pays(source)
```

```
gsutil_exists(source)
```

```

gsutil_stat(source)

gsutil_rsync(
  source,
  destination,
  ...,
  exclude = NULL,
  dry = TRUE,
  delete = FALSE,
  recursive = FALSE,
  parallel = TRUE
)

gsutil_cat(source, ..., header = FALSE, range = integer())

gsutil_help(cmd = character(0))

gsutil_pipe(source, open = "r", ...)

```

### Arguments

|             |                                                                                                                                                                                                                                                   |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| source      | character() for gsutil_requester Pays() and gsutil_exists(): paths to a Google Storage Bucket, possibly with wild-cards for file-level pattern matching.                                                                                          |
| destination | character(1), google cloud bucket or local file system destination path.                                                                                                                                                                          |
| ...         | additional arguments passed as-is to the gsutil subcommand.                                                                                                                                                                                       |
| exclude     | character(1) a python regular expression of bucket paths to exclude from synchronization. E.g., '.*(\\.png \\.txt)\$' excludes '.png' and '.txt' files.                                                                                           |
| dry         | logical(1), when TRUE (default), return the consequences of the operation without actually performing the operation.                                                                                                                              |
| delete      | logical(1), when TRUE, remove files in destination that are not in source. Exercise caution when you use this option: it's possible to delete large amounts of data accidentally if, for example, you erroneously reverse source and destination. |
| recursive   | logical(1); perform operation recursively from source?. Default: FALSE.                                                                                                                                                                           |
| parallel    | logical(1), perform parallel multi-threaded / multi-processing (default is TRUE).                                                                                                                                                                 |
| header      | logical(1) when TRUE annotate each                                                                                                                                                                                                                |
| range       | (optional) integer(2) vector used to form a range from-to of bytes to concatenate. NA values signify concatenation from the start (first position) or to the end (second position) of the file.                                                   |
| cmd         | character() (optional) command name, e.g., "ls" for help.                                                                                                                                                                                         |
| open        | character(1) either "r" (read) or "w" (write) from the bucket.                                                                                                                                                                                    |

### Details

The gsutil system command is required. The search for gsutil starts with environment variable GCLLOUD\_SDK\_PATH providing a path to a directory containing a bin directory containingin gsutil,

gcloud, etc. The path variable is searched for first as an option() and then system variable. If no option or global variable is found, Sys.which() is tried. If that fails, gsutil is searched for on defined paths. On Windows, the search tries to find Google\\Cloud SDK\\google-cloud-sdk\\bin\\gsutil.cmd in the LOCAL APP DATA, Program Files, and Program Files (x86) directories. On linux / macOS, the search continues with ~/google-cloud-sdk.

gsutil\_rsync(): To make "gs://mybucket/data" match the contents of the local directory "data" you could do:

```
gsutil_rsync("data", "gs://mybucket/data", delete = TRUE)
```

To make the local directory "data" the same as the contents of gs://mybucket/data:

```
gsutil_rsync("gs://mybucket/data", "data", delete = TRUE)
```

If destination is a local path and does not exist, it will be created.

## Value

gsutil\_requester Pays(): named logical() vector TRUE when requester-pays is enabled.

gsutil\_exists(): logical(1) TRUE if bucket or object exists.

gsutil\_stat(): tibble() summarizing status of each bucket member.

gsutil\_rsync(): exit status of gsutil\_rsync(), invisibly.

gsutil\_cat() returns the content as a character vector.

gsutil\_help(): character() help text for subcommand cmd.

gsutil\_pipe() an unopened R pipe(); the mode is *not* specified, and the pipe must be used in the appropriate context (e.g., a pipe created with open = "r" for input as read.csv())

## Examples

```
src <-
  "gs://genomics-public-data/1000-genomes/other/sample_info/sample_info.csv"
if (has_avworkspace(platform = gcp()))
  GCPtools::gsutil_requester Pays(src) # FALSE -- no cost download

if (has_avworkspace(platform = gcp())) {
  GCPtools::gsutil_exists(src)
  GCPtools::gsutil_stat(src)
  avlist(dirname(src))
}

if (has_avworkspace(platform = gcp()))
  GCPtools::gsutil_help("ls")

if (has_avworkspace(platform = gcp())) {
  df <- read.csv(gsutil_pipe(src), 5L)
  class(df)
  dim(df)
  head(df)
}
```

---

has\_avworkspace-methods

*Helper to check AnVIL environment is set up to work with GCP*


---

## Description

has\_avworkspace() checks that the AnVIL environment is set up to work with GCP. If strict = TRUE, it also checks that the workspace name is set.

## Usage

```
## S4 method for signature 'gcp'
has_avworkspace(strict = FALSE, ..., platform = cloud_platform())
```

## Arguments

|          |                                                                                                             |
|----------|-------------------------------------------------------------------------------------------------------------|
| strict   | logical(1) Whether to include a check for an existing avworkspace_name() setting. Default FALSE.            |
| ...      | Arguments passed to the methods.                                                                            |
| platform | A Platform derived class indicating the AnVIL environment, currently, azure and gcp classes are compatible. |

## Value

logical(1) TRUE if the AnVIL environment is set up properly to interact with GCP, otherwise FALSE.

## Functions

- has\_avworkspace(gcp): Check if the AnVIL environment is set up

## Examples

```
has_avworkspace(platform = gcp())
```

---

localize

*Copy packages, folders, or files to or from google buckets.*


---

## Description

localize(): recursively synchronizes files from a Google storage bucket (source) to the local file system (destination). This command acts recursively on the source directory, and does not delete files in destination that are not in 'source'.

delocalize(): synchronize files from a local file system (source) to a Google storage bucket (destination). This command acts recursively on the source directory, and does not delete files in destination that are not in source.

**Usage**

```
localize(source, destination, dry = TRUE)
```

```
delocalize(source, destination, unlink = FALSE, dry = TRUE)
```

**Arguments**

|             |                                                                                                                      |
|-------------|----------------------------------------------------------------------------------------------------------------------|
| source      | character(1), a google storage bucket or local file system directory location.                                       |
| destination | character(1), a google storage bucket or local file system directory location.                                       |
| dry         | logical(1), when TRUE (default), return the consequences of the operation without actually performing the operation. |
| unlink      | logical(1) remove (unlink) the file or directory in source. Default: FALSE.                                          |

**Value**

localize(): exit status of function gsutil\_rsync().

delocalize(): exit status of function gsutil\_rsync()

# Index

.gcp (gcp-class), 28

AnVILBase::cloud\_platform, 9, 11, 14, 24, 31

av, 2

avbackup (gcp-methods), 29

avbackup, gcp-method (gcp-methods), 29

avcopy (gcp-methods), 29

avcopy, gcp-method (gcp-methods), 29

avdata, 7

avdata\_import (avdata), 7

avdisks (av), 2

avfiles\_backup (av), 2

avfiles\_ls (av), 2

avfiles\_restore (av), 2

avfiles\_rm (av), 2

avlist (gcp-methods), 29

avlist, gcp-method (gcp-methods), 29

avnotebooks (avnotebooks-methods), 8

avnotebooks, gcp-method (avnotebooks-methods), 8

avnotebooks-methods, 8

avnotebooks\_delocalize (avnotebooks-methods), 8

avnotebooks\_delocalize, gcp-method (avnotebooks-methods), 8

avnotebooks\_localize (avnotebooks-methods), 8

avnotebooks\_localize, gcp-method (avnotebooks-methods), 8

avremove (gcp-methods), 29

avremove, gcp-method (gcp-methods), 29

avrestore (gcp-methods), 29

avrestore, gcp-method (gcp-methods), 29

avruntime (av), 2

avruntimes (av), 2

avstorage (gcp-methods), 29

avstorage, gcp-method (gcp-methods), 29

avtable (avtable-methods), 9

avtable, gcp-method (avtable-methods), 9

avtable-methods, 9

avtable\_delete, gcp-method (avtable-methods), 9

avtable\_delete\_values (avtable-methods), 9

avtable\_delete\_values, gcp-method (avtable-methods), 9

avtable\_import (avtable-methods), 9

avtable\_import, gcp-method (avtable-methods), 9

avtable\_import\_set (avtable-methods), 9

avtable\_import\_set, gcp-method (avtable-methods), 9

avtable\_import\_status (av), 2

avtable\_paged (av), 2

avtables (avtable-methods), 9

avtables, gcp-method (avtable-methods), 9

avworkflow (avworkflow\_configurations), 19

avworkflow-methods, 14

avworkflow\_configuration\_get (avworkflow\_configurations), 19

avworkflow\_configuration\_inputs (avworkflow\_configurations), 19

avworkflow\_configuration\_outputs (avworkflow\_configurations), 19

avworkflow\_configuration\_set (avworkflow\_configurations), 19

avworkflow\_configuration\_template (avworkflow\_configurations), 19

avworkflow\_configuration\_update (avworkflow\_configurations), 19

avworkflow\_configurations, 19

avworkflow\_files (avworkflows), 15

avworkflow\_info (avworkflows), 15

avworkflow\_jobs, gcp-method (avworkflow-methods), 14

avworkflow\_localize (avworkflows), 15

avworkflow\_name

- (avworkflow\_configurations), 19
- avworkflow\_namespace
  - (avworkflow\_configurations), 19
- avworkflow\_run (avworkflows), 15
- avworkflow\_stop (avworkflows), 15
- avworkflows, 15
- avworkspace, gcp-method
  - (avworkspace-methods), 23
- avworkspace-methods, 23
- avworkspace\_clone, gcp-method
  - (avworkspace-methods), 23
- avworkspace\_name, gcp-method
  - (avworkspace-methods), 23
- avworkspace\_namespace, gcp-method
  - (avworkspace-methods), 23
- avworkspaces, gcp-method
  - (avworkspace-methods), 23
- delocalize (localize), 35
- drs, 25
- drs\_hub (drs), 25
- drs\_nci\_crnc (drs), 25
- gcloud-deprecated, 27
- gcloud\_access\_token
  - (gcloud-deprecated), 27
- gcloud\_account (gcloud-deprecated), 27
- gcloud\_cmd (gcloud-deprecated), 27
- gcloud\_exists (gcloud-deprecated), 27
- gcloud\_help (gcloud-deprecated), 27
- gcloud\_project (gcloud-deprecated), 27
- gcloud\_storage (gcloud-deprecated), 27
- gcloud\_storage\_buckets
  - (gcloud-deprecated), 27
- gcp (gcp-class), 28
- gcp-class, 28
- gcp-methods, 29
- GCPtools:gsutil, 27
- gsutil-deprecated, 32
- gsutil\_cat (gsutil-deprecated), 32
- gsutil\_exists (gsutil-deprecated), 32
- gsutil\_help (gsutil-deprecated), 32
- gsutil\_pipe (gsutil-deprecated), 32
- gsutil\_requesterpays
  - (gsutil-deprecated), 32
- gsutil\_rsync (gsutil-deprecated), 32
- gsutil\_stat (gsutil-deprecated), 32
- has\_avworkspace, gcp-method
  - (has\_avworkspace-methods), 35
- has\_avworkspace-methods, 35
- localize, 35
- print.avworkflow\_configuration
  - (avworkflow\_configurations), 19