

# Package ‘SPICEY’

September 23, 2025

**Title** Calculates cell type specificity from single cell data

**Version** 0.99.3

**Description** SPICEY (SPecificity Index for Coding and Epigenetic activitY) is an R package designed to quantify cell-type specificity in single-cell transcriptomic and epigenomic data, particularly scRNA-seq and scATAC-seq. It introduces two complementary indices: the Gene Expression Tissue Specificity Index (GETSI) and the Regulatory Element Tissue Specificity Index (RETSI), both based on entropy to provide continuous, interpretable measures of specificity. By integrating gene expression and chromatin accessibility, SPICEY enables standardized analysis of cell-type-specific regulatory programs across diverse tissues and conditions.

**License** Artistic-2.0

**Encoding** UTF-8

**Depends** R (>= 4.5.0), utils, stats, grDevices

**Imports** GenomicRanges, GenomicFeatures, AnnotationDbi, S4Vectors, ggplot2, dplyr, tidyr, tibble, GenomeInfoDb, scales, cowplot

**Suggests** BiocStyle, knitr, rmarkdown,  
TxDb.Hsapiens.UCSC.hg38.knownGene, org.Hs.eg.db, testthat (>= 3.0.0)

**VignetteBuilder** knitr

**biocViews** Transcriptomics, Epigenetics, SingleCell,  
DifferentialExpression, DifferentialPeakCalling,  
GeneRegulation, GeneTarget, GeneExpression, Transcription

**RoxygenNote** 7.3.2

**Roxygen** list(markdown = TRUE)

**URL** <https://georginafp.github.io/SPICEY>

**BugReports** <https://github.com/georginafp/SPICEY/issues>

**LazyData** false

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/SPICEY>

**git\_branch** devel

**git\_last\_commit** 8f23b82

**git\_last\_commit\_date** 2025-09-10

**Repository** Bioconductor 3.22

**Date/Publication** 2025-09-22

**Author** Georgina Fuentes-Páez [aut, cre] (ORCID:  
<https://orcid.org/0009-0003-9417-7148>),  
 Nacho Molina [aut],  
 Mireia Ramos-Rodriguez [aut],  
 Lorenzo Pasquali [aut],  
 Ministerio de Ciencia e Innovación Spain [fnd] (program: FPI  
 Fellowship)  
**Maintainer** Georgina Fuentes-Páez <georgina.fuentes@upf.edu>

## Contents

|                                         |           |
|-----------------------------------------|-----------|
| .add_tss_annotation . . . . .           | 2         |
| .parse_input_diff . . . . .             | 3         |
| .standardize_peaks . . . . .            | 4         |
| annotate_with_coaccessibility . . . . . | 4         |
| annotate_with_nearest . . . . .         | 6         |
| atac . . . . .                          | 7         |
| cicero_links . . . . .                  | 8         |
| compute_spicey_index . . . . .          | 8         |
| entropy_index . . . . .                 | 9         |
| extract_gene_peak_annotations . . . . . | 10        |
| get_promoters . . . . .                 | 11        |
| link_spicey . . . . .                   | 12        |
| plot_heatmap . . . . .                  | 13        |
| prepare_heatmap_data . . . . .          | 13        |
| rna . . . . .                           | 14        |
| specificity_index . . . . .             | 15        |
| SPICEY . . . . .                        | 15        |
| spicey_heatmap . . . . .                | 18        |
| <b>Index</b>                            | <b>20</b> |

---

|                     |                                    |
|---------------------|------------------------------------|
| .add_tss_annotation | <i>Add TSS annotation to peaks</i> |
|---------------------|------------------------------------|

---

## Description

Identifies transcription start sites (TSS) overlapping with input peaks and adds logical and gene ID columns to an annotation table.

## Usage

```
.add_tss_annotation(  
  annotation,  
  peaks,  
  txdb,  
  annot_dbi,  
  protein_coding_only,  
  verbose  
)
```

### Arguments

|                                  |                                                                                                                           |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <code>annotation</code>          | A <code>data.frame</code> or <code>GRanges</code> containing peak annotations, including a <code>region_id</code> column. |
| <code>peaks</code>               | A <code>GRanges</code> object containing the original peak set.                                                           |
| <code>txdb</code>                | <code>TxDb</code> object for genome annotation (required if annotation requested).                                        |
| <code>annot_db</code>            | <code>AnnotationDbi</code> object for gene ID mapping (required if annotation requested).                                 |
| <code>protein_coding_only</code> | Logical; restrict to protein-coding genes (default <code>TRUE</code> ).                                                   |
| <code>verbose</code>             | Logical; print messages (default <code>TRUE</code> ).                                                                     |

### Value

A `data.frame` or `GRanges` (depending on input) with added columns:

**`in_TSS`** Logical, `TRUE` if the peak overlaps a TSS.

**`TSS_gene`** Gene symbol of the overlapping TSS, if any.

---

|                                |                                                                                                                                                                                                                                   |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>.parse_input_diff</code> | <i>Parses input data of various types (e.g., named lists of <code>GRanges</code> or <code>data.frame</code>, or a <code>GRangesList</code>) into a single tidy <code>data.frame</code>, with a <code>cell_type</code> column.</i> |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

---

### Description

Parses input data of various types (e.g., named lists of `GRanges` or `data.frame`, or a `GRangesList`) into a single tidy `data.frame`, with a `cell_type` column.

### Usage

```
.parse_input_diff(input)
```

### Arguments

|                    |                                                                                                                                                                                                                                                 |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>input</code> | An object representing differential results, such as: <ul style="list-style-type: none"><li>• A named list of <code>GRanges</code> objects.</li><li>• A named list of <code>data.frames</code>.</li><li>• A <code>GRangesList</code>.</li></ul> |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Value

A `data.frame` combining all elements, with an added `cell_type` column indicating the source.

---

|                                 |                                                                                                                                                                                                                          |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>.standardize_peaks</code> | <i>Standardizes peak input, ensuring that input peaks is a GRanges object, removes alternate scaffolds (<code>_alt</code>, <code>random</code>, <code>fix</code>, <code>Un</code>), and assigns region IDs as names.</i> |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

---

### Description

Standardizes peak input, ensuring that input peaks is a GRanges object, removes alternate scaffolds (`_alt`, `random`, `fix`, `Un`), and assigns region IDs as names.

### Usage

```
.standardize_peaks(peaks)
```

### Arguments

|                    |                                                                                                                                                   |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>peaks</code> | A <code>data.frame</code> with genomic coordinates and a <code>region_id</code> column, or a GRanges object with a <code>region_id</code> column. |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|

### Value

A GRanges object with:

**seqnames, start, end** Coordinates of the input regions.

**region\_id** Unique identifier of the region (e.g., `chr1-5000-5800`).

**metadata columns** Any additional columns present in the input.

---

`annotate_with_coaccessibility`

*Annotate peaks with co-accessible genes using Cicero links*

---

### Description

Links peaks to genes based on Cicero co-accessibility with promoters or TSSs.

### Usage

```
annotate_with_coaccessibility(
  peaks,
  txdb,
  links_df,
  annot_dbi,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream,
  downstream
)
```

## Arguments

|                     |                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| peaks               | A GRanges or data.frame of peaks with at least the following columns:<br><b>seqnames</b> Chromosome name of the regulatory region (e.g., "chr1"). Only for data.frames.<br><b>start</b> Start coordinate of the peak. Only for data.frames.<br><b>end</b> End coordinate of the peak. Only for data.frames.<br><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800) |
| txdb                | TxDb object for genome annotation (required if annotation requested).                                                                                                                                                                                                                                                                                                                  |
| links_df            | A data.frame with Cicero links. Must contain columns: Peak1, Peak2, and coaccess.                                                                                                                                                                                                                                                                                                      |
| annot_dbi           | AnnotationDbi object for gene ID mapping (required if annotation requested).                                                                                                                                                                                                                                                                                                           |
| protein_coding_only | Logical; restrict to protein-coding genes (default TRUE).                                                                                                                                                                                                                                                                                                                              |
| verbose             | Logical; print messages (default TRUE).                                                                                                                                                                                                                                                                                                                                                |
| add_tss_annotation  | Logical; annotate regulatory elements overlapping TSS (default FALSE). If TRUE, use +/- 1bp TSS.                                                                                                                                                                                                                                                                                       |
| upstream            | Single integer value indicating the number of bases upstream from the TSS (transcription start sites) (default "2000kb").                                                                                                                                                                                                                                                              |
| downstream          | Single integer values indicating the number of bases downstream from the TSS (transcription start sites) (default "2000kb").                                                                                                                                                                                                                                                           |

## Value

A data.frame with the original metadata columns from peaks, along with an added gene\_id column containing the symbol of the co-accessible gene. Peaks with no gene annotation will have NA in the gene\_id field.

## Examples

```
library(TxDb.Hsapiens.UCSC.hg38.knownGene)
library(org.Hs.eg.db)

data(atac)
data(cicero_links)

peaks <- unique(unlist(atac)[, c("region_id")])
annotation_coacc <- annotate_with_coaccessibility(
  peaks = peaks,
  txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  links_df = cicero_links,
  annot_dbi = org.Hs.eg.db,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream = 2000,
  downstream = 2000
)
```

---

annotate\_with\_nearest *Annotates regulatory elements (e.g., ATAC-seq peaks) to the nearest gene*

---

## Description

based on distance to the transcription start site (TSS), using a TxDb reference and gene annotations from org.\*.db packages.

## Usage

```
annotate_with_nearest(
  peaks,
  txdb,
  annot_dbi,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream,
  downstream
)
```

## Arguments

|                     |                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| peaks               | A GRanges or data.frame of peaks with at least the following columns:<br><b>seqnames</b> Chromosome name of the regulatory region (e.g., "chr1"). Only for data.frames.<br><b>start</b> Start coordinate of the peak. Only for data.frames.<br><b>end</b> End coordinate of the peak. Only for data.frames.<br><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800) |
| txdb                | TxDb object for genome annotation (required if annotation requested).                                                                                                                                                                                                                                                                                                                  |
| annot_dbi           | AnnotationDbi object for gene ID mapping (required if annotation requested).                                                                                                                                                                                                                                                                                                           |
| protein_coding_only | Logical; restrict to protein-coding genes (default TRUE).                                                                                                                                                                                                                                                                                                                              |
| verbose             | Logical; print messages (default TRUE).                                                                                                                                                                                                                                                                                                                                                |
| add_tss_annotation  | Logical; annotate regulatory elements overlapping TSS (default FALSE). If TRUE, use +/- 1bp TSS.                                                                                                                                                                                                                                                                                       |
| upstream            | Single integer value indicating the number of bases upstream from the TSS (transcription start sites) (default "2000kb").                                                                                                                                                                                                                                                              |
| downstream          | Single integer values indicating the number of bases downstream from the TSS (transcription start sites) (default "2000kb").                                                                                                                                                                                                                                                           |

## Value

A data.frame of peaks annotated to its nearest gene, with columns:

|               |                                                                       |
|---------------|-----------------------------------------------------------------------|
| distanceToTSS | Distance to the nearest TSS                                           |
| gene_id       | Identifier of the gene. Must be an official gene symbol (e.g., GAPDH) |
| annotation    | "Promoter" or "Distal" based on distance                              |

## Examples

```
library(dplyr)
library(TxDb.Hsapiens.UCSC.hg38.knownGene)
library(org.Hs.eg.db)

data(atac)
peaks <- unique(unlist(atac)[, c("region_id")])

annotation_near <- annotate_with_nearest(
  peaks = peaks,
  txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  annot_dbi = org.Hs.eg.db,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream = 2000,
  downstream = 2000
)
```

---

atac

*Example single-cell ATAC-seq differential accessibility data*

---

## Description

A toy example dataset representing single-cell ATAC-seq differential accessibility results. Each row corresponds to a chromatin accessibility peak tested for differential accessibility across one or more cell types. The dataset is formatted as a list of GRanges objects or data frames (convertible to GRanges), where each element represents differential accessibility statistics for a specific cell type. Multiple rows may exist per peak, each representing results in a different cell type.

## Usage

```
data(atac)
```

## Format

A data frame or GRanges-like object with the following required columns:

**region\_id** Unique identifier of the region (e.g., chr1-5000-5800).

**avg\_log2FC** Average log2 fold-change of accessibility for the peak in the specific cell type

**p\_val\_adj** Adjusted p-value (e.g., FDR-corrected)

**cell\_type** Cell type or cluster label associated with each measurement (e.g., Acinar)

## Source

Precomputed using FindMarkers() (Wilcoxon test, via Presto if available) on control samples from the Human Pancreas Analysis Program (HPAP), using paired snATAC-seq and snRNA-seq data from three non-diabetic human donors.

---

|              |                                              |
|--------------|----------------------------------------------|
| cicero_links | <i>Example Cicero co-accessibility links</i> |
|--------------|----------------------------------------------|

---

### Description

A toy example dataset of co-accessibility links inferred from single-cell ATAC-seq data using tools such as Cicero or Signac's LinkPeaks(). These links support integrative analysis by associating regulatory elements with putative target genes. The peaks referenced here must exactly match those in the ATAC-seq differential accessibility dataset.

### Usage

```
data(cicero_links)
```

### Format

A data frame with the following columns:

**Peak1** Genomic coordinate or peak identifier for the first peak in the pair (e.g., chr1-110209621-110211746)

**Peak2** Genomic coordinate or peak identifier for the second peak in the pair (e.g., chr1-110209621-110211746)

**coaccess** Co-accessibility score or correlation value quantifying the linkage

### Source

Cicero co-accessibility links were computed from UMAP-reduced snATAC-seq data (HPAP, control donors) using run\_cicero() with chromosome sizes from hg38. Input data matched the peaks in the provided ATAC dataset.

---

|                      |                                                                                   |
|----------------------|-----------------------------------------------------------------------------------|
| compute_spicey_index | <i>Compute cell type specificity scores from single-cell RNA and/or ATAC data</i> |
|----------------------|-----------------------------------------------------------------------------------|

---

### Description

Computes:

- GETSI (Gene Expression Tissue Specificity Index) from single-cell RNA-seq differential expression data.
- RETSI (Regulatory Element Tissue Specificity Index) from single-cell ATAC-seq differential accessibility data.

Either RNA or ATAC input must be provided.

### Usage

```
compute_spicey_index(diff = NULL, id = NULL)
```

**Arguments**

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>diff</code> | <p>Single <code>data.frame</code> with differential results, with required columns:</p> <p><b>id</b> Identifier for either genes or regions. Gene IDs must be official gene symbols, while region IDs should follow the usual genomic coordinate format such as <code>chr-start-end</code> or <code>chr:start-end</code>. The name of this column must match the <code>id</code> argument.</p> <p><b>avg_log2FC</b> Average log2 fold-change for the gene in that cell type.</p> <p><b>p_val_adj</b> Adjusted p-value (e.g., FDR-corrected)</p> <p><b>cell_type</b> Cell type or cluster label (e.g., Acinar)</p> |
| <code>id</code>   | A character string specifying the name of the column in <code>diff</code> that contains the unique identifiers for features (e.g., genes or regions). Must match a column name in <code>diff</code> , such as <code>"gene_id"</code> or <code>"region_id"</code> .                                                                                                                                                                                                                                                                                                                                                |

**Value**

A data frame with specificity scores for each feature:

**score (GETSI or RETSI)** Specificity score (weighted log2FC).

**norm\_entropy** Shannon entropy-based specificity measure.

---

|                            |                                                                   |
|----------------------------|-------------------------------------------------------------------|
| <code>entropy_index</code> | <i>Calculate normalized Shannon-entropy of specificity scores</i> |
|----------------------------|-------------------------------------------------------------------|

---

**Description**

Computes the normalized entropy of specificity scores (RETSI or GETSI) across cell types. Entropy quantifies how evenly a feature's activity is distributed among cell types, and if normalized, yields scores from 0 to 1, where values close to 1 indicate widespread distribution across cell types, and values near 0 denote dominating distribution towards one cell type.

**Usage**

```
entropy_index(spec_df, group_col)
```

**Arguments**

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>spec_df</code>   | <p>A <code>data.frame</code> containing the computed specificity scores containing at least the following columns:</p> <p><b>cell_type</b> Cell type or cluster label.</p> <p><b>score</b> Specificity score for each feature in each cell type.</p> <p>[<code>group_col</code>] Column containing the feature identifier (e.g., <code>gene_id</code> or <code>region</code>)<br/> <b>The name of this column must match the value passed to the <code>group_col</code> argument</b></p> |
| <code>group_col</code> | A string specifying the name of the column in <code>da</code> that identifies each feature, such as <code>gene_id</code> for genes or <code>region</code> for ATAC peaks.                                                                                                                                                                                                                                                                                                                |

**Value**

A data.frame with one row per feature, containing:

**group\_col** Feature identifier.

**entropy** Raw Shannon entropy computed from specificity scores.

**norm\_entropy** Normalized Shannon entropy score ( $1 - \exp(-\text{entropy})$ ) bounded between 0 and 1, where lower values indicate higher specificity.

---

extract\_gene\_peak\_annotations

*Overlap peaks with gene promoters to obtain gene annotations*

---

**Description**

Identifies overlaps between a set of peaks and promoter regions, optionally restricted to protein-coding genes.

**Usage**

```
extract_gene_peak_annotations(
  peaks,
  txdb,
  annot_dbi,
  protein_coding_only = TRUE,
  upstream,
  downstream,
  verbose = FALSE
)
```

**Arguments**

|                     |                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| peaks               | A GRanges or data.frame of peaks with at least the following columns:<br><b>seqnames</b> Chromosome name of the regulatory region (e.g., "chr1"). Only for data.frames.<br><b>start</b> Start coordinate of the peak. Only for data.frames.<br><b>end</b> End coordinate of the peak. Only for data.frames.<br><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800) |
| txdb                | TxDb object for genome annotation (required if annotation requested).                                                                                                                                                                                                                                                                                                                  |
| annot_dbi           | AnnotationDbi object for gene ID mapping (required if annotation requested).                                                                                                                                                                                                                                                                                                           |
| protein_coding_only | Logical; restrict to protein-coding genes (default TRUE).                                                                                                                                                                                                                                                                                                                              |
| upstream            | Single integer value indicating the number of bases upstream from the TSS (transcription start sites) (default "2000kb").                                                                                                                                                                                                                                                              |
| downstream          | Single integer values indicating the number of bases downstream from the TSS (transcription start sites) (default "2000kb").                                                                                                                                                                                                                                                           |
| verbose             | Logical; print messages (default TRUE).                                                                                                                                                                                                                                                                                                                                                |

**Value**

A GRanges with with:

**seqnames, start, end** Coordinates of the peak that overlaps with a gene promoter.

**region\_id** Unique identifier of the region (e.g., chr1-5000-5800).

**gene\_id** Identifier of the gene. Must be an official gene symbol (e.g., GAPDH)

---

|               |                                                                                             |
|---------------|---------------------------------------------------------------------------------------------|
| get_promoters | <i>Extract promoter regions annotated gene symbols from a TxDb and AnnotationDbi object</i> |
|---------------|---------------------------------------------------------------------------------------------|

---

**Description**

Extract promoter regions annotated gene symbols from a TxDb and AnnotationDbi object

**Usage**

```
get_promoters(
  txdb,
  annot_dbi,
  upstream,
  downstream,
  protein_coding_only = TRUE
)
```

**Arguments**

|                     |                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| txdb                | TxDb object for genome annotation (required if annotation requested).                                                        |
| annot_dbi           | AnnotationDbi object for gene ID mapping (required if annotation requested).                                                 |
| upstream            | Single integer value indicating the number of bases upstream from the TSS (transcription start sites) (default "2000kb").    |
| downstream          | Single integer values indicating the number of bases downstream from the TSS (transcription start sites) (default "2000kb"). |
| protein_coding_only | Logical; restrict to protein-coding genes (default TRUE).                                                                    |

**Value**

A GRanges object with the chromosomes, start and end positions of defined specie promoter regions together with the official gene symbol stored in the gene\_id metadata column.

---

|             |                                                                                |
|-------------|--------------------------------------------------------------------------------|
| link_spicey | <i>Link RETSI regions to GETSI scores using gene-based association methods</i> |
|-------------|--------------------------------------------------------------------------------|

---

## Description

This function connects regulatory regions scored with RETSI

## Usage

```
link_spicey(retsi = NULL, getsi = NULL, annotation = NULL)
```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| retsi      | <p>A data.frame containing RETSI scores for chromatin accessibility regions, as returned by <code>compute_spicey_index()</code> using single-cell ATAC-seq differential accessibility data. Must include at least the following columns:</p> <p><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800).</p> <p><b>cell_type</b> Cell type or cluster label (e.g., Acinar)</p> <p><b>RETSI</b> RETSI value: cell-type specificity score</p> <p><b>norm_entropy</b> Normalized Shannon entropy of RETSI</p>                                                                                                                                                                                                                                                    |
| getsi      | <p>A data.frame containing GETSI scores for genes, as returned by <code>compute_spicey_index()</code> using single-cell RNA-seq differential expression data. Must include at least the following columns:</p> <p><b>gene_id</b> Identifier of the gene. Must be an official gene symbol (e.g., GAPDH).</p> <p><b>cell_type</b> Cell type or cluster label (e.g., Acinar)</p> <p><b>GETSI</b> GETSI value: cell-type specificity score</p> <p><b>norm_entropy</b> Normalized Shannon entropy of GETSI</p>                                                                                                                                                                                                                                                                     |
| annotation | <p>(Optional). A data.frame linking <code>gene_id</code> to <code>region_id</code>. They should have the same names provided in the respective parameters. This can be provided by the user or generated using the functions: <a href="#">annotate_with_nearest</a> or <a href="#">annotate_with_coaccessibility</a>. It should contain at least the following columns:</p> <p><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800). The name of this column should match the <code>region_id</code> argument.</p> <p><b>cell_type</b> Cell type or cluster label. (e.g., Acinar)</p> <p><b>gene_id</b> Identifier of the gene. Must be an official gene symbol (e.g., GAPDH). The name of this column should match the <code>gene_id</code> argument.</p> |

## Value

A data.frame where each row represents a regulatory element–gene pair linked within a given cell type. The output includes:

**region\_id** Unique identifier of the region (e.g., chr1-5000-5800)

**gene\_id** Identifier of the gene. Must be an official gene symbol (e.g., GAPDH).

**cell\_type** Cell type or cluster in which the association is observed (e.g., Acinar)

**RETSI** RETSI score: regulatory element specificity in this cell type.

**RETSI\_entropy** Normalized shannon-entropy of RETSI (lower = more specific).

**GETSI** GETSI score: gene expression specificity in this cell type.

**GETSI\_entropy** Normalized shannon-entropy of GETSI (lower = more specific).

... Any additional columns from the original `retsi` and `getsi` inputs, suffixed with `_ATAC` and `_RNA` respectively (e.g., `avg_log2FC_ATAC`, `p_val_RNA`).

---

|              |                                                  |
|--------------|--------------------------------------------------|
| plot_heatmap | <i>Plot a z-scored gene-by-cell-type heatmap</i> |
|--------------|--------------------------------------------------|

---

## Description

Generates a heatmap using `ggplot2` to visualize expression or accessibility z-scores for genes across different cell types. Genes are ordered by their highest-scoring cell type, and then by maximum z-score within that group.

## Usage

```
plot_heatmap(df_z, title_text, fill_label)
```

## Arguments

|                         |                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>df_z</code>       | A data frame with z-scored values. Must contain:<br><b>gene_id</b> Identifier of the gene. Must be an official gene symbol (e.g., <code>GAPDH</code> ).<br><b>cell_type</b> Cell type or cluster label (e.g., <code>Acinar</code> )<br><b>z_score</b> Numeric. Z-scored values of the specificity score (e.g., <code>RETSI_z</code> , <code>GETSI_z</code> ) |
| <code>title_text</code> | Character. Title of the heatmap.                                                                                                                                                                                                                                                                                                                             |
| <code>fill_label</code> | Character. Legend label for the color scale.                                                                                                                                                                                                                                                                                                                 |

## Value

A `ggplot2` object representing the heatmap.

## See Also

[prepare\\_heatmap\\_data](#), [spicey\\_heatmap](#)

---

|                      |                                        |
|----------------------|----------------------------------------|
| prepare_heatmap_data | <i>Prepare data for SPICEY heatmap</i> |
|----------------------|----------------------------------------|

---

## Description

Filters and processes a gene–cell-type matrix for heatmap visualization. Computes z-scores for a specified score column, selects the top `n` genes per cell type, and returns a summary matrix suitable for plotting.

## Usage

```
prepare_heatmap_data(df, score_col, top_n)
```

**Arguments**

**df** A data frame with at least: `gene_id`, `cell_type`, and a score column.

**score\_col** Character. Name of the score column to z-score and rank.

**top\_n** Integer. Number of top-ranked genes per cell type.

**Value**

A data frame with: `gene_id`, `cell_type`, and `z_score`.

**See Also**

[plot\\_heatmap](#), [spicey\\_heatmap](#)

---

|     |                                                                 |
|-----|-----------------------------------------------------------------|
| rna | <i>Example single-cell RNA-seq differential expression data</i> |
|-----|-----------------------------------------------------------------|

---

**Description**

A toy example dataset representing single-cell RNA-seq differential expression results. Each row corresponds to a gene tested across one or more cell types. The dataset is formatted as a list of GRanges objects or data frames (convertible to GRanges), where each element contains differential expression statistics for a specific cell type. Multiple rows may exist per gene, each representing results in a different cell type.

**Usage**

```
data(rna)
```

**Format**

A data frame or GRanges-like object with the following required columns:

**gene\_id** Identifier of the gene. Must be an official gene symbol (e.g., GAPDH)

**avg\_log2FC** Average log2 fold-change of expression for the gene in the specific cell type

**p\_val\_adj** Adjusted p-value (e.g., FDR-corrected)

**cell\_type** Cell type or cluster label associated with each measurement (e.g., Acinar)

**Source**

Precomputed using FindMarkers() (Wilcoxon test, via Presto if available) on control samples from the Human Pancreas Analysis Program (HPAP), using paired snATAC-seq and scRNA-seq data from three non-diabetic human donors.

---

|                   |                                                   |
|-------------------|---------------------------------------------------|
| specificity_index | Calculate specificity scores for grouped features |
|-------------------|---------------------------------------------------|

---

## Description

This function computes a specificity index for different features (e.g., genes or regions) based on differential expression/accessibility data. It rescales fold-change values and weights them by significance to quantify how specific a feature's activity is to a particular cell type.

## Usage

```
specificity_index(da, group_col)
```

## Arguments

|           |                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| da        | A data.frame containing differential results with at least the following columns:<br><b>avg_log2FC</b> Average log2 fold-change of the feature (gene or region).<br><b>cell_type</b> Cell type or cluster label. (e.g., Acinar)<br><b>[group_col]</b> Column containing the feature identifier (e.g., gene_id or region)<br><b>The name of this column must match the value passed to the group_col argument</b> |
| group_col | A string specifying the name of the column in da that identifies each feature, such as gene_id for genes or region for ATAC peaks.                                                                                                                                                                                                                                                                               |

## Value

A data.frame identical to the input but with additional columns:

**avg\_FC** Fold-change converted from log2 scale.

**max\_FC** Maximum fold-change observed within each feature group.

**weight** Normalized significance weight derived from adjusted p-values.

**norm\_FC** Fold-change normalized by maximum fold-change in the group.

**score** Specificity score computed as the product of normalized fold-change significantly weighted.

---

SPICEY

*SPICEY: Tissue specificity analysis for single-cell data The SPICEY package provides a user-friendly pipeline for quantifying and visualizing tissue specificity specificity from single-cell ATAC-seq and/or single cell RNA-seq datasets, typically processed with tools such as Seurat or Signac. The core outputs of SPICEY are two tissue specific metrics, combined with entropy-based measures.*

---

## Description

Computes tissue-specificity scores from differential accessibility (RETSI) and/or gene expression (GETSI) data obtained from single cell experiments. Supports:

- RETSI calculation from differential accessibility data in different cell types/clusters (scATAC-seq).
- GETSI calculation from differential expression data in different cell types/clusters (scRNA-seq).
- Optional integration of RETSI and GETSI scores by linking gene associations (see [annotate\\_with\\_nearest](#) or [annotate\\_with\\_coaccessibility](#))

## Usage

```
SPICEY(atac = NULL, rna = NULL, annotation = NULL, verbose = TRUE)
```

## Arguments

|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| atac       | <p>Either a single <code>data.frame</code> or a named list of <code>data.frames</code> or <code>GRanges</code> where each element corresponds to a cell type. It should contain differential chromatin accessibility results with required columns:</p> <p><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800).</p> <p><b>avg_log2FC</b> Average log2 fold-change for accessibility in that cell type.</p> <p><b>p_val_adj</b> Adjusted p-value (e.g., FDR-corrected).</p> <p><b>cell_type</b> Cell type or cluster label. Only necessary when input is a single <code>data.frame</code>. If input is a list, it will be generated from list names. Note that the same region may appear multiple times across cell types.</p>                                                                   |
| rna        | <p>Either a single <code>data.frame</code> or a named list of <code>data.frames</code> or <code>GRanges</code> where each element corresponds to a cell type. It should contain differential expression results, with required columns:</p> <p><b>gene_id</b> Identifier of the gene. Must be an official gene symbol (e.g., GAPDH). The name of this column should match the <code>gene_id</code> argument.</p> <p><b>avg_log2FC</b> Average log2 fold-change for the gene in that cell type.</p> <p><b>p_val_adj</b> Adjusted p-value (e.g., FDR-corrected).</p> <p><b>cell_type</b> Cell type or cluster label. Only necessary when input is a single <code>data.frame</code>. If input is a list, it will be generated from list names. Note that the same gene may appear multiple times across cell types.</p> |
| annotation | <p>(Optional). A <code>data.frame</code> linking <code>gene_id</code> to <code>region_id</code>. They should have the same names provided in the respective parameters. This can be provided by the user or generated using the functions: <a href="#">annotate_with_nearest</a> or <a href="#">annotate_with_coaccessibility</a>. It should contain at least the following columns:</p> <p><b>region_id</b> Unique identifier of the region (e.g., chr1-5000-5800). The name of this column should match the <code>region_id</code> argument.</p> <p><b>cell_type</b> Cell type or cluster label. (e.g., Acinar)</p> <p><b>gene_id</b> Identifier of the gene. Must be an official gene symbol (e.g., GAPDH). The name of this column should match the <code>gene_id</code> argument.</p>                           |
| verbose    | Logical; print messages (default TRUE).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## Value

Depending on inputs, returns RETSI and/or GETSI data frames, optionally linked and annotated.

**Examples**

```
data(rna)
data(atac)

# Calculate RETSI only
retsi <- SPICEY(atac = atac)

# Calculate GETSI only
getsi <- SPICEY(rna = rna)

# Calculate both
both <- SPICEY(
  rna = rna,
  atac = atac
)

# Integrate RETSI and GETSI with nearest gene
library(TxDb.Hsapiens.UCSC.hg38.knownGene)
library(org.Hs.eg.db)
peaks <- unique(unlist(atac)[, c("region_id")])

annotation_near <- annotate_with_nearest(
  peaks = peaks,
  txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  annot_dbi = org.Hs.eg.db,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream = 2000,
  downstream = 2000
)
spicey_near <- SPICEY(
  rna = rna,
  atac = atac,
  annotation = annotation_near
)

# Integrate RETSI and GETSI with coaccessibility
data(cicero_links)

annotation_coacc <- annotate_with_coaccessibility(
  peaks = peaks,
  txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  links_df = cicero_links,
  annot_dbi = org.Hs.eg.db,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream = 2000,
  downstream = 2000
)
spicey_coacc <- SPICEY(
  rna = rna,
  atac = atac,
  annotation = annotation_coacc
)
```

---

spicey\_heatmap

*SPICEY heatmap for gene specificity across cell types*


---

## Description

Visualizes gene-level specificity scores (RETSI and/or GETSI) across cell types using a z-scored heatmap representation. Depending on the chosen mode, the function can display either RETSI or GETSI scores independently, or compute and visualize a combined SPICEY score (mean z-score of RETSI and GETSI). If `spicey_measure = "SPICEY"` and `combined_zscore = TRUE`, RETSI and GETSI scores are scaled, averaged, and shown in a unified heatmap. Otherwise, separate heatmaps are produced for RETSI and GETSI, respectively.

## Usage

```
spicey_heatmap(
  df,
  top_n = 5,
  spicey_measure = c("RETSI", "GETSI", "SPICEY"),
  combined_zscore = FALSE
)
```

## Arguments

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>df</code>              | <p>A data frame with at least the following columns:</p> <ul style="list-style-type: none"> <li><b>gene_id</b> Identifier of the gene. Must be an official gene symbol (e.g., GAPDH). If you only have ATAC data, link to nearest gene (<a href="#">annotate_with_nearest</a>) or using coaccessibility (<a href="#">annotate_with_coaccessibility</a>).</li> <li><b>cell_type</b> Cell type or cluster label (e.g., Acinar)</li> <li><b>RETSI</b> Numeric. RETSI specificity scores (optional unless used).</li> <li><b>GETSI</b> Numeric. GETSI specificity scores (optional unless used).</li> </ul> |
| <code>top_n</code>           | Integer. Number of top-ranked genes to include per cell type (default "5")                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <code>spicey_measure</code>  | <p>Character. Score type to visualize. Must be one of the following:</p> <ul style="list-style-type: none"> <li>"RETSI" Only RETSI will be plotted.</li> <li>"GETSI" Only GETSI will be plotted.</li> <li>"SPICEY" Both RETSI and GETSI are used (requires both columns)</li> </ul>                                                                                                                                                                                                                                                                                                                     |
| <code>combined_zscore</code> | <p>Logical. Only relevant if <code>spicey_measure = "SPICEY"</code>. If TRUE, a single heatmap of mean RETSI/GETSI z-score is generated. If FALSE, two heatmaps are produced side by side (RETSI and GETSI).</p>                                                                                                                                                                                                                                                                                                                                                                                        |

## Value

A ggplot2 object, or a patchwork layout if two heatmaps are returned.

## See Also

[SPICEY](#), [prepare\\_heatmap\\_data](#), [plot\\_heatmap](#)

**Examples**

```

library(TxDb.Hsapiens.UCSC.hg38.knownGene)
library(org.Hs.eg.db)

data(rna)
data(atac)
data(cicero_links)

# Obtain annotation with coaccessibility
peaks <- unique(unlist(atac[, c("region_id")])
annotation_coacc <- annotate_with_coaccessibility(
  peaks = peaks,
  txdb = TxDb.Hsapiens.UCSC.hg38.knownGene,
  links_df = cicero_links,
  annot_dbi = org.Hs.eg.db,
  protein_coding_only = TRUE,
  verbose = TRUE,
  add_tss_annotation = FALSE,
  upstream = 2000,
  downstream = 2000
)

# Obtain linked SPICEY measures
spicey_coacc <- SPICEY(
  rna = rna,
  atac = atac,
  annotation = annotation_coacc
)

# Make plots
retsi <- spicey_coacc$RETSI |> dplyr::left_join(annotation_coacc, by = c("region_id"))
spicey_heatmap(retsi, spicey_measure = "RETSI")

spicey_heatmap(spicey_coacc$GETSI, spicey_measure = "GETSI")

spicey_heatmap(spicey_coacc$linkeds, spicey_measure = "SPICEY", combined_zscore = FALSE)

spicey_heatmap(spicey_coacc$linkeds, spicey_measure = "SPICEY", combined_zscore = TRUE)

```

# Index

- \* **datasets**
  - atac, [7](#)
  - cicero\_links, [8](#)
  - rna, [14](#)
  - .add\_tss\_annotation, [2](#)
  - .parse\_input\_diff, [3](#)
  - .standardize\_peaks, [4](#)
- annotate\_with\_coaccessibility, [4](#), [12](#), [16](#), [18](#)
- annotate\_with\_nearest, [6](#), [12](#), [16](#), [18](#)
- atac, [7](#)
- cicero\_links, [8](#)
- compute\_spicey\_index, [8](#)
- entropy\_index, [9](#)
- extract\_gene\_peak\_annotations, [10](#)
- get\_promoters, [11](#)
- link\_spicey, [12](#)
- plot\_heatmap, [13](#), [14](#), [18](#)
- prepare\_heatmap\_data, [13](#), [13](#), [18](#)
- rna, [14](#)
- specificity\_index, [15](#)
- SPICEY, [15](#), [18](#)
- spicey\_heatmap, [13](#), [14](#), [18](#)