

Package ‘tangle’

September 3, 2025

Type Package

Title Visualization of Phylogenetic Networks

Version 1.15.2

Description Offers functions for plotting split (or implicit) networks (unrooted, undirected) and explicit networks (rooted, directed) with reticulations extending. 'ggtree' and using functions from 'ape' and 'phangorn'. It extends the 'ggtree' package [Yu2017] to allow the visualization of phylogenetic networks using the 'ggplot2' syntax. It offers an alternative to the plot functions already available in 'ape' Paradis and Schliep (2019) <doi:10.1093/bioinformatics/bty633> and 'phangorn' Schliep (2011) <doi:10.1093/bioinformatics/btq706>.

Depends R (>= 4.1), ggplot2 (>= 2.2.0), ggtree

Imports ape (>= 5.0), phangorn (>= 2.12), utils, methods

Suggests tinytest, BiocStyle, ggimage, knitr, rmarkdown

VignetteBuilder knitr

biocViews Software, Visualization, Phylogenetics, Alignment, Clustering, MultipleSequenceAlignment, DataImport

License Artistic-2.0

URL <https://klausvigo.github.io/tangle>,
<https://github.com/KlausVigo/tangle>

BugReports <https://github.com/KlausVigo/tangle/issues>

Encoding UTF-8

RoxygenNote 7.3.2

Roxygen list(old_usage = TRUE)

git_url <https://git.bioconductor.org/packages/tangle>

git_branch devel

git_last_commit 6637b6d

git_last_commit_date 2025-07-01

Repository Bioconductor 3.22

Date/Publication 2025-09-02

Author Klaus Schliep [aut, cre] (ORCID:
 <<https://orcid.org/0000-0003-2941-0161>>),
Marta Vidal-Garcia [aut],
Claudia Solis-Lemus [aut] (ORCID:
 <<https://orcid.org/0000-0002-9789-8915>>),
Leann Biancani [aut],
Eren Ada [aut],
L. Francisco Henao Diaz [aut],
Guangchuang Yu [ctb],
Joshua Justison [aut]

Maintainer Klaus Schliep <klaus.schliep@gmail.com>

Contents

tanggle-package	2
geom_splitnet	3
ggevonet	4
ggsplitnet	5
minimize_overlap	6
node_depth_evonet	7
swap_hybrid_minor	7

Index	9
--------------	----------

tanggle-package	<i>tanggle: Visualization of Phylogenetic Networks</i>
-----------------	--

Description

Offers functions for plotting split (or implicit) networks (unrooted, undirected) and explicit networks (rooted, directed) with reticulations extending. 'ggtree' and using functions from 'ape' and 'phangorn'. It extends the 'ggtree' package [Yu2017] to allow the visualization of phylogenetic networks using the 'ggplot2' syntax. It offers an alternative to the plot functions already available in 'ape' Paradis and Schliep (2019) [doi:10.1093/bioinformatics/bty633](https://doi.org/10.1093/bioinformatics/bty633) and 'phangorn' Schliep (2011) [doi:10.1093/bioinformatics/btq706](https://doi.org/10.1093/bioinformatics/btq706).

Author(s)

Maintainer: Klaus Schliep <klaus.schliep@gmail.com> (ORCID)

Authors:

- Marta Vidal-Garcia
- Claudia Solis-Lemus <solislemus@wisc.edu> (ORCID)
- Leann Biancani
- Eren Ada
- L. Francisco Henao Diaz
- Joshua Justison

Other contributors:

- Guangchuang Yu [contributor]

See Also

Useful links:

- <https://klausvigo.github.io/tanggle>
- <https://github.com/KlausVigo/tanggle>
- Report bugs at <https://github.com/KlausVigo/tanggle/issues>

geom_splitnet

geom_splitnet

Description

add splitnet layer

Usage

```
geom_splitnet(layout = "slanted", ...)
```

Arguments

layout	one of 'rectangular', 'slanted', 'circular', 'radial' or 'unrooted'
...	additional parameter

Value

splitnet layer

Author(s)

Klaus Schliep

Examples

```
data(yeast, package='phangorn')
dm <- phangorn::dist.ml(yeast)
nnet <- phangorn::neighborNet(dm)
ggplot(nnet, aes(x, y)) + geom_splitnet() + theme_tree()
```

`ggevonet`*ggevonet*

Description

drawing phylogenetic tree from phylo object

Usage

```
ggevonet(tr, mapping = NULL, layout = "slanted", mrsd = NULL,  
  as.Date = FALSE, yscale = "none", yscale_mapping = NULL,  
  ladderize = FALSE, right = FALSE, branch.length = "branch.length",  
  ndigits = NULL, min_crossing = TRUE, ...)
```

Arguments

<code>tr</code>	a evonet object
<code>mapping</code>	aes mapping
<code>layout</code>	one of 'rectangular', 'slanted'
<code>mrsd</code>	most recent sampling date
<code>as.Date</code>	logical whether using Date class in time tree
<code>yscale</code>	y scale
<code>yscale_mapping</code>	yscale mapping for category variable
<code>ladderize</code>	logical
<code>right</code>	logical
<code>branch.length</code>	variable for scaling branch, if 'none' draw cladogram
<code>ndigits</code>	number of digits to round numerical annotation variable
<code>min_crossing</code>	logical, rotate clades to minimize crossings
<code>...</code>	additional parameter

Value

tree

Author(s)

Klaus Schliep

See Also

[evonet](#), [ggtree](#)

Examples

```
(enet <- ape::read.evonet(text='((a:2,(b:1)#H1:1):1,(#H1,c:1):2);'))  
ggevonet(enet) + geom_tiplab()
```

`ggsplitnet`*ggsplitnet*

Description

drawing phylogenetic tree from phylo object

Usage

```
ggsplitnet(tr, mapping = NULL, layout = "slanted", mrsd = NULL,  
  as.Date = FALSE, yscale = "none", yscale_mapping = NULL,  
  ladderize = FALSE, right = FALSE, branch.length = "branch.length",  
  ndigits = NULL, ...)
```

Arguments

<code>tr</code>	a network object
<code>mapping</code>	aes mapping
<code>layout</code>	so far only 'slanted' is supported.
<code>mrsd</code>	most recent sampling date
<code>as.Date</code>	logical whether using Date class in time tree
<code>yscale</code>	y scale
<code>yscale_mapping</code>	yscale mapping for category variable
<code>ladderize</code>	logical
<code>right</code>	logical
<code>branch.length</code>	variable for scaling branch, if 'none' draw cladogram
<code>ndigits</code>	number of digits to round numerical annotation variable
<code>...</code>	additional parameter

Value

tree

Author(s)

Klaus Schliep

References

Schliep, K., Potts, A. J., Morrison, D. A. and Grimm, G. W. (2017), Intertwining phylogenetic trees and networks. *Methods Ecol Evol.* **8**, 1212–1220. doi:10.1111/2041-210X.12760

See Also

[ggtree](#), [networkx](#), [consensusNet](#), [neighborNet](#)

Examples

```
data(yeast, package='phangorn')
dm <- phangorn::dist.ml(yeast)
nnet <- phangorn::neighborNet(dm)
ggsplitnet(nnet) + geom_tiplab2()
```

minimize_overlap

minimize_overlap reduces reticulation lines crossing over in plots

Description

minimize_overlap reduces reticulation lines crossing over in plots

Usage

```
minimize_overlap(x)
```

Arguments

x Tree of class 'evonet'

Value

A Tree with rotated nodes of class 'evonet'

Author(s)

L. Francisco Henao Diaz

Examples

```
fishnet <- ape::read.evonet(text='(Xalvarezi,Xmayae,((Xsignum,((Xmonticolus,
(Xclemenciae_F2,#H25)),(((((((Xgordoni,Xmeyer),Xcouchianus),Xvariatus),
Xvelynae),(Xxiphidium,#H24)),Xmilleri),Xandersi),Xmaculatus),((Xmontezumae,
(Xcortez),Xbirmanni_GARC,Xmalinche_CHIC2))),((Xnigrens, Xmultilineatus),
(Xpygmaeus,Xcontinens))))#H24)),(Xhellerii)#H25));')
fishnet$edge.length <- NULL
new_tre <- minimize_overlap(fishnet)

par(mfrow=c(1,2))
ggevonet(fishnet, min_crossing = FALSE)
ggevonet(new_tre)

net2 <- ape::read.evonet(text='(15,(1,((14,((#H1,(((12,13),(11,#H3)),(7,
((10)#H3,(8,9)))))),((((2,3))#H2,(6,(5,((#H2,4))))#H1)))));')
# Cui et al. 2013 Evol.
new_net2 <- minimize_overlap(net2)
ggevonet(net2, min_crossing = FALSE)
ggevonet(new_net2)
```

node_depth_evonet	<i>Depth of Nodes</i>
-------------------	-----------------------

Description

These functions return the depths or heights of nodes and tips.

Usage

```
node_depth_evonet(x, ...)
```

Arguments

x	an object of class 'evonet'
...	Further arguments passed to or from other methods.

Value

a vector with the depth of the nodes

See Also

[node.depth](#)

Examples

```
z <- ape::read.evonet(text = '((1,((2,(3,(4)Y#H1)g)e,
(((Y#H1, 5)h,6)f)X#H2)c)a,((X#H2,7)d,8)b)r;')
nd <- node_depth_evonet(z)
z$edge.length <- nd[z$edge[,1]] - nd[z$edge[,2]]
ggevonet(z)
```

swap_hybrid_minor	<i>swap_hybrid_minor</i>
-------------------	--------------------------

Description

Swapping the minor edges of an evonet object

Usage

```
swap_hybrid_minor(x, hybrid_nodes, node_times = NULL)
```

Arguments

x	evonet object
hybrid_nodes	a vector of hybrid nodes to have their minor edges swapped
node_times	an optional argument with node times

Value

network

Examples

```
(enet <- ape::read.evonet(text='((a:2,(b:1)#H1:1):1,(#H1,c:1):2);'))  
ggevonet(enet) + geom_tiplab()  
swapped_enet<-swap_hybrid_minor(enet,6)  
ggevonet(swapped_enet) + geom_tiplab()
```

Index

- * **internal**
 - tangle-package, [2](#)
- consensusNet, [5](#)
- evonet, [4](#)
- geom_splitnet, [3](#)
- ggevonet, [4](#)
- ggsplitnet, [5](#)
- ggtree, [4](#), [5](#)
- minimize_overlap, [6](#)
- neighborNet, [5](#)
- networx, [5](#)
- node.depth, [7](#)
- node_depth_evonet, [7](#)
- swap_hybrid_minor, [7](#)
- tangle (tangle-package), [2](#)
- tangle-package, [2](#)