

# Application of VAM to Seurat pbmc\_small scRNA-seq data using Seurat log normalization.

H. Robert Frost

## 1 Load the VAM package

Loading VAM will also load the required packages Seurat and MASS.

```
> library(VAM)
> if (!requireNamespace("Seurat", quietly=TRUE)) {
+   stop("Seurat package not available!")
+ }
```

## 2 Summary statistics for the pbmc\_small scRNA-seq data

This example uses the pbmc\_small data set included in the SeuratObject package and a single contrived gene set. Please see the other vignettes for more realistic examples using larger scRNA-seq data sets and gene set collections based on MSigDB.

```
> SeuratObject::pbmc_small

An object of class Seurat
230 features across 80 samples within 1 assay
Active assay: RNA (230 features, 20 variable features)
2 dimensional reductions calculated: pca, tsne

> gene.names = rownames(SeuratObject::pbmc_small)
> gene.names[1:5]

[1] "MS4A1"    "CD79B"    "CD79A"    "HLA-DRA"   "TCL1A"

> Seurat:::VariableFeatures(SeuratObject::pbmc_small)[1:5]

[1] "PPBP"     "IGLL5"    "VDAC3"    "CD1C"      "AKR1C3"
```

## 3 Define gene set collection

A gene set collection containing just a single contrived set (containing the top 5 variable genes) will be used for this example.

```
> gene.set.name = "Test"
> gene.ids = c("PPBP", "IGLL5", "VDAC3", "CD1C", "AKR1C3")
> # Create a collection list for this gene set
> gene.set.id.list = list()
> gene.set.id.list[[1]] = gene.ids
> names(gene.set.id.list)[1] = gene.set.name
> gene.set.id.list
```

```

$Test
[1] "PPBP"    "IGLL5"    "VDAC3"    "CD1C"     "AKR1C3"

> # Create the list of gene indices required by vamForSeurat()
> (gene.set.collection = createGeneSetCollection(gene.ids=gene.names,
+         gene.set.collection=gene.set.id.list))

$Test
PPBP  IGLL5  VDAC3  CD1C  AKR1C3
 174      28     203     133     208

> gene.indices = gene.set.collection[[1]]
> (gene.names = gene.names[gene.indices])

[1] "PPBP"    "IGLL5"    "VDAC3"    "CD1C"     "AKR1C3"

```

## 4 Execute VAM method

Since the scRNA-seq data has been processed using Seurat, we execute VAM using the vamForSeurat() function. We have set return.dist=T so that the squared adjusted Mahalanobis distances will be returned in a "VAMdist" Assay.

```

> pbmc.vam = vamForSeurat(seurat.data=SeuratObject::pbmc_small,
+   gene.set.collection=gene.set.collection,
+   center=F, gamma=T, sample.cov=F, return.dist=T)

```

Look at the first few entries in the "VAMdist" and "VAMcdf" Assays.

```

> pbmc.vam@assays$VAMdist[1,1:10]

1 x 10 sparse Matrix of class "dgCMatrix"

Test . . 8.598434 17.68048 . . 23.5895 . . 19.64062

> pbmc.vam@assays$VAMcdf[1,1:10]

1 x 10 sparse Matrix of class "dgCMatrix"

Test . . 0.1260139 0.3157103 . . 0.4313759 . . 0.3553561

```

## 5 Visualize VAM scores

Visualize VAM scores using Seurat FeaturePlot(). The default Assay must first be changed to "VAMcdf".

```

> Seurat::DefaultAssay(object = pbmc.vam) = "VAMcdf"
> Seurat::FeaturePlot(pbmc.vam, reduction="tsne", features=gene.set.name)

```

## Test

