

# Package ‘hdm’

January 31, 2016

**Type** Package

**Title** High-Dimensional Metrics

**Version** 0.1

**Date** 2015-10-08

**Depends** R (>= 3.0.0)

**Description** Implementation of selected high-dimensional statistical and econometric methods for estimation and inference. Efficient estimators and uniformly valid confidence intervals for various low-dimensional causal/structural parameters are provided which appear in high-dimensional approximately sparse models. Including functions for fitting heteroscedastic robust Lasso regressions with non-Gaussian errors and for instrumental variable (IV) and treatment effect estimation in a high-dimensional setting. Moreover, the methods enable valid post-selection inference and rely on a theoretically grounded, data-driven choice of the penalty.

**License** GPL-3

**LazyData** TRUE

**Imports** MASS,  
glmnet,  
ggplot2,  
checkmate

**Suggests** testthat,  
knitr,  
xtable

**VignetteBuilder** knitr

## R topics documented:

hdm-package . . . . .	2
AJR . . . . .	3
EminentDomain . . . . .	4
Growth Data . . . . .	4
lambdaCalculation . . . . .	5
LassoShooting.fit . . . . .	6
pension . . . . .	7
predict.rlassologit . . . . .	8
print.rlasso . . . . .	9
print.rlassoEffects . . . . .	9
print.rlassoIV . . . . .	10

print.rlassoIVselectX . . . . .	11
print.rlassoIVselectZ . . . . .	12
print.rlassologitEffects . . . . .	12
print.rlassoTE . . . . .	13
print.tsls . . . . .	14
rlasso . . . . .	14
rlassoATE . . . . .	17
rlassoEffects . . . . .	18
rlassoIV . . . . .	19
rlassoIVselectX . . . . .	20
rlassoIVselectZ . . . . .	21
rlassologit . . . . .	22
rlassologitEffects . . . . .	24
summary.rlassoEffects . . . . .	25
tsls . . . . .	26

**Index****27**

---

hdm-package*hdm: High-Dimensional Metrics*

---

**Description**

This package implements methods for estimation and inference in a high-dimensional setting.

**Details**

Package:	hdm
Type:	Package
Version:	0.1
Date:	2015-05-25
License:	GPL-3

This package provides efficient estimators and uniformly valid confidence intervals for various low-dimensional causal/structural parameters appearing in high-dimensional approximately sparse models. The package includes functions for fitting heteroskedastic robust Lasso regressions with non-Gaussian errors and for instrumental variable (IV) and treatment effect estimation in a high-dimensional setting. Moreover, the methods enable valid post-selection inference. Moreover, a theoretically grounded, data-driven choice of the penalty level is provided.

**Author(s)**

Victor Chernozhukov, Christian Hansen, Martin Spindler

Maintainer: Martin Spindler <spindler@mea.mpisoc.mpg.de>

**References**

A. Belloni, D. Chen, V. Chernozhukov and C. Hansen (2012). Sparse models and methods for optimal instruments with an application to eminent domain. *Econometrica* 80 (6), 2369-2429.

A. Belloni, V. Chernozhukov and C. Hansen (2013). Inference for high-dimensional sparse econometric models. In Advances in Economics and Econometrics: 10th World Congress, Vol. 3: Econometrics, Cambridge University Press: Cambridge, 245-295.

A. Belloni, V. Chernozhukov, C. Hansen (2014). Inference on treatment effects after selection among high-dimensional controls. The Review of Economic Studies 81(2), 608-650.

---

AJR

*AJR data set*

---

## Description

Dataset on settler mortality.

## Format

**Mort** Settler mortality

**logMort** logarithm of Mort

**Latitude** Latitude

**Latitude2** Latitude<sup>2</sup>

**Africa** Africa

**Asia** Asia

**Namer** North America

**Samer** South America

**Neo** Neo-Europe

**GDP** GDP

**Exprop** Average protection against expropriation risk

## Details

Data set was analysed in Acemoglu et al. (2001). A detailed description of the data can be found at  
<http://economics.mit.edu/faculty/acemoglu/data/ajr2001>

## References

D. Acemoglu, S. Johnson, J. A. Robinson (2001). Colonial origins of comparative development: an empirical investigation. American Economic Review, 91, 1369–1401.

## Examples

```
data(AJR)
```

EminentDomain	<i>Eminent Domain data set</i>
---------------	--------------------------------

### Description

Dataset on judicial eminent domain decisions.

### Format

- y** economic outcome variable
- x** set of exogenous variables
- d** eminent domain decisions
- z** set of potential instruments

### Details

Data set was analyzed in Belloni et al. (2012). They estimate the effect of judicial eminent domain decisions on economic outcomes with instrumental variables (IV) in a setting high a large set of potential IVs. A detailed decription of the data can be found at <https://www.econometricsociety.org/publications/econometrica/2012/11/01/sparse-models-and-methods-optimal-instruments-application>. The data set contains four "sub-data sets" which differ mainly in the dependent variables: repeat-sales FHFA/OFHEO house price index for metro (FHFA) and non-metro (NM) area, the Case-Shiller home price index (CS), and state-level GDP from the Bureau of Economic Analysis - all transformed with the logarithm. The structure of each subdata set is comparable and given above.

### References

D. Belloni, D. Chen, V. Chernozhukov and C. Hansen (2012). Sparse models and methods for optimal instruments with an application to eminent domain. *Econometrica* 80 (6), 2369–2429.

### Examples

```
data(EminentDomain)
```

Growth Data	<i>Growth data set</i>
-------------	------------------------

### Description

Data set of growth compiled by Barro Lee.

### Format

Dataframe with the following variables:

dependent variable: national growth rates in GDP per capita for the periods 1965-1975 and 1975-1985

**outcome** variates which might influence growth

## Details

The data set contains growth data of Barro-Lee. The Barro Lee data consists of a panel of 138 countries for the period 1960 to 1985. The dependent variable is national growth rates in GDP per capita for the periods 1965-1975 and 1975-1985. The growth rate in GDP over a period from  $t_1$  to  $t_2$  is commonly defined as  $\log(GDP_{t_1}/GDP_{t_2})$ . The number of covariates is p=62. The number of complete observations is 90.

## Source

The full data set and further details can be found at <http://www.nber.org/pub/barro.lee>, <http://www.barrolee.com>, and, <http://www.bristol.ac.uk//Depts//Economics//Growth//barlee.htm>.

## References

- R.J. Barro, J.W. Lee (1994). Data set for a panel of 139 countries. NBER.
- R.J. Barro, X. Sala-i-Martin (1995). Economic Growth. McGraw-Hill, New York.

## Examples

```
data(GrwothData)
```

lambdaCalculation	<i>Function for Calculation of the penalty parameter</i>
-------------------	--

## Description

This function implements different methods for calculation of the penalization parameter  $\lambda$ . Further details can be found under [rlasso](#).

## Usage

```
lambdaCalculation(penalty = list(homoscedastic = FALSE, X.dependent.lambda =
FALSE, lambda.start = NULL, c = 1.1, gamma = 0.1), y = NULL, x = NULL)
```

## Arguments

- |         |  |
|---------|--|
| penalty | list with options for the calculation of the penalty. <ul style="list-style-type: none"> <li>• c and gamma constants for the penalty with default c=1.1 and gamma=0.1</li> <li>• homoscedastic logical, if homoscedastic errors are considered (default FALSE). Option none is described below.</li> <li>• X.dependent.lambda if independent or dependent design matrix X is assumed for calculation of the parameter <math>\lambda</math></li> <li>• numSim number of simulations for the X-dependent methods</li> <li>• lambda.start initial penalization value, compulsory for method "none"</li> </ul> |
| y       | residual which is used for calculation of the variance or the data-dependent loadings  |
| x       | matrix of regressor variables  |

**Value**

The function returns a list with the penalty `lambda` which is the product of `lambda0` and `Ups0`. `Ups0` denotes either the variance (independent case) or the data-dependent loadings for the regressors. `method` gives the selected method for the calculation.

`LassoShooting.fit`      *Shooting Lasso*

**Description**

Implementation of the Shooting Lasso (Fu, 1998) with variable dependent penalization weights.

**Usage**

```
LassoShooting.fit(x, y, lambda, control = list(maxIter = 1000, optTol =
  10^(-5), zeroThreshold = 10^(-6)), XX = NULL, Xy = NULL,
  beta.start = NULL)
```

**Arguments**

<code>x</code>	matrix of regressor variables (n times p where n denotes the number of observations and p the number of regressors)
<code>y</code>	dependent variable (vector or matrix)
<code>lambda</code>	vector of length p of penalization parameters for each regressor
<code>control</code>	list with control parameters: <code>maxIter</code> maximal number of iterations, <code>optTol</code> tolerance for parameter precision, <code>zeroThreshold</code> threshold applied to the estimated coefficients for numerical issues.
<code>XX</code>	optional, precalculated matrix $t(X) * X$
<code>Xy</code>	optional, precalculated matrix $t(X) * y$
<code>beta.start</code>	start value for beta

**Details**

The function implements the Shooting Lasso (Fu, 1998) with variable dependent penalization. The arguments `XX` and `Xy` are optional and allow to use precalculated matrices which might improve performance.

**Value**

<code>coefficients</code>	estimated coefficients by the Shooting Lasso Algorithm
<code>coef.list</code>	matrix of coefficients from each iteration
<code>num.it</code>	number of iterations run

**References**

Fu, W. (1998). Penalized regressions: the bridge vs the lasso. *Journal of Computational and Graphical Software* 7, 397-416.

---

pension                    *Pension 401(k) data set*

---

**Description**

Data set on financial wealth and 401(k) plan participation

**Format**

Dataframe with the following variables (amongst others):

participation in 401(k)

**p401** eligibility for 401(k)

**a401** 401(k) assets

**tw** total wealth (in US \$)

**tfa** financial assets (in US \$)

**net\_tfa** net financial assets (in US \$)

**nifa** non-401k financial assets (in US \$)

**net\_nifa** net non-401k financial assets

**net\_n401** net non-401(k) assets (in US \$)

**ira** individual retirement account (IRA)

**inc** income (in US \$)

**age** age

**fsize** family size

**marr** married

**pira** participation in IRA

**db** defined benefit pension

**hown** home owner

**educ** education (in years)

**male** male

**twoearn** two earners

**nohs, hs, smcol, col** dummies for education: no high-school, high-school, some college, college

**hmort** home mortage (in US \$)

**hequity** home equity (in US \$)

**hval** home value (in US \$)

**Details**

The sample is drawn from the 1991 Survey of Income and Program Participation (SIPP) and consists of 9,915 observations. The observational units are household reference persons aged 25-64 and spouse if present. Households are included in the sample if at least one person is employed and no one is self-employed. The data set was analysed in Chernozhukov and Hansen (2004) and Belloni et al. (2014) where further details can be found. They examine the effects of 401(k) plans on wealth using data from the Survey of Income and Program Participation using 401(k) eligibility as an instrument for 401(k) participation.

## References

- V. Chernohukov, C. Hansen (2004). The impact of 401(k) participation on the wealth distribution: An instrumental quantile regression analysis. *The Review of Economic and Statistics* 86 (3), 735–751.
- A. Belloni, V. Chernozhukov, I. Fernandez-Val, and C. Hansen (2014). Program evaluation with high-dimensional data. Working Paper.

## Examples

```
data(pension)
```

---

```
predict.rlassologit      Methods for S3 object rlassologit
```

---

## Description

Objects of class `rlassologit` are constructed by `rlassologit` or `rlassologit.fit`. `print.rlassologit` prints and displays some information about fitted `rlassologit` objects. `summary.rlassologit` summarizes information of a fitted `rlassologit` object. `predict.rlassologit` predicts values based on a `rlassologit` object. `model.matrix.rlassologit` constructs the model matrix of a lasso object.

## Usage

```
## S3 method for class 'rlassologit'
predict(object, newdata = NULL, type = "response",
        ...)

## S3 method for class 'rlassologit'
model.matrix(object, ...)

## S3 method for class 'rlassologit'
print(x, all = TRUE, digits = max(3L,
        getOption("digits") - 3L), ...)

## S3 method for class 'rlassologit'
summary(object, all = TRUE, digits = max(3L,
        getOption("digits") - 3L), ...)
```

## Arguments

<code>object</code>	an object of class <code>rlassologit</code>
<code>newdata</code>	new data set for prediction
<code>type</code>	type of prediction required. The default ('response') is on the scale of the response variable; the alternative 'link' is on the scale of the linear predictors.
<code>...</code>	arguments passed to the <code>print</code> function and other methods
<code>x</code>	an object of class <code>rlassologit</code>
<code>all</code>	logical, indicates if coefficients of all variables (TRUE) should be displayed or only the non-zero ones (FALSE)
<code>digits</code>	significant digits in printout

---

<code>print.rlasso</code>	<i>Methods for S3 object rlasso</i>
---------------------------	-------------------------------------

---

## Description

Objects of class `rlasso` are constructed by `rlasso.formula` or `rlasso.fit`. `print.rlasso` prints and displays some information about fitted `rlasso` objects. `summary.rlasso` summarizes information of a fitted `rlasso` object. `predict.rlasso` predicts values based on a `rlasso` object. `model.matrix.rlasso` constructs the model matrix of a `rlasso` object.

## Usage

```
## S3 method for class 'rlasso'
print(x, all = TRUE, digits = max(3L, getOption("digits") -
  3L), ...)

## S3 method for class 'rlasso'
summary(object, all = TRUE, digits = max(3L,
  getOption("digits") - 3L), ...)

## S3 method for class 'rlasso'
model.matrix(object, ...)

## S3 method for class 'rlasso'
predict(object, newdata = NULL, ...)
```

## Arguments

<code>x</code>	an object of class <code>rlasso</code>
<code>all</code>	logical, indicates if coefficients of all variables (TRUE) should be displayed or only the non-zero ones (FALSE)
<code>digits</code>	significant digits in printout
<code>...</code>	arguments passed to the <code>print</code> function and other methods
<code>object</code>	an object of class <code>rlasso</code>
<code>newdata</code>	new data set for prediction. An optional data frame in which to look for variables with which to predict. If omitted, the fitted values are returned.

---

<code>print.rlassoEffects</code>	<i>Methods for S3 object rlassoEffects</i>
----------------------------------	--

---

## Description

Objects of class `rlassoEffects` are constructed by `rlassoEffects`. `print.rlassoEffects` prints and displays some information about fitted `rlassoEffect` objects. `summary.rlassoEffects` summarizes information of a fitted `rlassoEffect` object and is described at [summary.rlassoEffects](#). `confint.rlassoEffects` extracts the confidence intervals. `plot.rlassoEffects` plots the estimates with confidence intervals.

**Usage**

```
## S3 method for class 'rlassoEffects'
print(x, digits = max(3L, getOption("digits") - 3L),
      ...)

## S3 method for class 'rlassoEffects'
confint(object, parm, level = 0.95, joint = FALSE,
        ...)

## S3 method for class 'rlassoEffects'
plot(x, main = "", xlab = "coef", ylab = "",
      xlim = NULL, ...)
```

**Arguments**

<code>x</code>	an object of class <code>rlassoEffects</code>
<code>digits</code>	significant digits in printout
<code>...</code>	arguments passed to the print function and other methods.
<code>object</code>	an object of class <code>rlassoEffects</code>
<code>parm</code>	a specification of which parameters are to be given confidence intervals among the variables for which inference was done, either a vector of numbers or a vector of names. If missing, all parameters are considered.
<code>level</code>	confidence level required
<code>joint</code>	logical, if TRUE joint confidence intervals are calculated.
<code>main</code>	an overall title for the plot
<code>xlab</code>	a title for the x axis
<code>ylab</code>	a title for the y axis
<code>xlim</code>	vector of length two giving lower and upper bound of x axis

**Description**

Objects of class `rlassoIV` are constructed by `rlassoIV`. `print.rlassoIV` prints and displays some information about fitted `rlassoIV` objects. `summary.rlassoIV` summarizes information of a fitted `rlassoIV` object. `confint.rlassoIV` extracts the confidence intervals.

**Usage**

```
## S3 method for class 'rlassoIV'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

## S3 method for class 'rlassoIV'
summary(object, digits = max(3L, getOption("digits") - 3L),
        ...)

## S3 method for class 'rlassoIV'
confint(object, parm, level = 0.95, ...)
```

**Arguments**

x	an object of class <code>rlassoIV</code>
digits	significant digits in printout
...	arguments passed to the print function and other methods
object	An object of class <code>rlassoIV</code>
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	confidence level required.

`print.rlassoIVselectX` *Methods for S3 object `rlassoIVselectX`*

**Description**

Objects of class `rlassoIVselectX` are constructed by `rlassoIVselectX`. `print.rlassoIVselectX` prints and displays some information about fitted `rlassoIVselectX` objects. `summary.rlassoIVselectX` summarizes information of a fitted `rlassoIVselectX` object. `confint.rlassoIVselectX` extracts the confidence intervals.

**Usage**

```
## S3 method for class 'rlassoIVselectX'
print(x, digits = max(3L, getOption("digits") - 3L),
      ...)

## S3 method for class 'rlassoIVselectX'
summary(object, digits = max(3L, getOption("digits")
    - 3L), ...)

## S3 method for class 'rlassoIVselectX'
confint(object, parm, level = 0.95, ...)
```

**Arguments**

x	an object of class <code>rlassoIVselectX</code>
digits	significant digits in printout
...	arguments passed to the print function and other methods
object	An object of class <code>rlassoIVselectX</code>
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	the confidence level required.

**print.rlassoIVselectZ** *Methods for S3 object rlassoIVselectZ*

### Description

Objects of class `rlassoIVselectZ` are constructed by `rlassoIVselectZ`. `print.rlassoIVselectZ` prints and displays some information about fitted `rlassoIVselectZ` objects. `summary.rlassoIVselectZ` summarizes information of a fitted `rlassoIVselectZ` object. `confint.rlassoIVselectZ` extracts the confidence intervals.

### Usage

```
## S3 method for class 'rlassoIVselectZ'
print(x, digits = max(3L, getOption("digits") - 3L),
      ...)

## S3 method for class 'rlassoIVselectZ'
summary(object, digits = max(3L, getOption("digits")
  - 3L), ...)

## S3 method for class 'rlassoIVselectZ'
confint(object, parm, level = 0.95, ...)
```

### Arguments

<code>x</code>	an object of class <code>rlassoIVselectZ</code>
<code>digits</code>	significant digits in printout
<code>...</code>	arguments passed to the print function and other methods
<code>object</code>	an object of class <code>rlassoIVselectZ</code>
<code>parm</code>	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
<code>level</code>	confidence level required.

**print.rlassologitEffects**  
*Methods for S3 object rlassologitEffects*

### Description

Objects of class `rlassologitEffects` are constructed by `rlassologitEffects` or `rlassologitEffect`. `print.rlassologitEffects` prints and displays some information about fitted `rlassologitEffect` objects. `summary.rlassologitEffects` summarizes information of a fitted `rlassologitEffects` object. `confint.rlassologitEffects` extracts the confidence intervals.

**Usage**

```
## S3 method for class 'rlassologitEffects'
print(x, digits = max(3L, getOption("digits") -
  3L), ...)

## S3 method for class 'rlassologitEffects'
summary(object, digits = max(3L,
  getOption("digits") - 3L), ...)

## S3 method for class 'rlassologitEffects'
confint(object, parm, level = 0.95,
  joint = FALSE, ...)
```

**Arguments**

<code>x</code>	an object of class <code>rlassologitEffects</code>
<code>digits</code>	number of significant digits in printout
<code>...</code>	arguments passed to the print function and other methods
<code>object</code>	an object of class <code>rlassologitEffects</code>
<code>parm</code>	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
<code>level</code>	confidence level required.
<code>joint</code>	logical, if joint confidence intervals should be calculated

**Description**

Objects of class `rlassoTE` are constructed by `rlassoATE`, `rlassoATET`, `rlassoLATE`, `rlassoLATET`. `print.rlassoTE` prints and displays some information about fitted `rlassoTE` objects. `summary.rlassoTE` summarizes information of a fitted `rlassoTE` object. `confint.rlassoTE` extracts the confidence intervals.

**Usage**

```
## S3 method for class 'rlassoTE'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

## S3 method for class 'rlassoTE'
summary(object, digits = max(3L, getOption("digits") - 3L),
  ...)

## S3 method for class 'rlassoTE'
confint(object, parm, level = 0.95, ...)
```

### Arguments

x	an object of class rlassoTE
digits	number of significant digits in printout
...	arguments passed to the print function and other methods
object	an object of class rlassoTE
parm	a specification of which parameters are to be given confidence intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	confidence level required.

print.tsls

*Methods for S3 object tsls*

### Description

Objects of class tsls are constructed by tsls. print.tsls prints and displays some information about fitted tsls objects. summary.tsls summarizes information of a fitted tsls object.

### Usage

```
## S3 method for class 'tsls'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

## S3 method for class 'tsls'
summary(object, digits = max(3L, getOption("digits") - 3L),
       ...)
```

### Arguments

x	an object of class tsls
digits	significant digits in printout
...	arguments passed to the print function and other methods
object	an object of class tsls

rlasso

*rlasso: Function for Lasso estimation under homoscedastic and heteroscedastic non-Gaussian disturbances*

### Description

The function estimates the coefficients of a Lasso regression with data-driven penalty under homoscedasticity and heteroscedasticity with non-Gaussian noise and X-dependent or X-independent design. The method of the data-driven penalty can be chosen. The object which is returned is of the S3 class rlasso.

## Usage

```
rlasso(formula, data, post = TRUE, intercept = TRUE,
       penalty = list(homoscedastic = FALSE, X.dependent.lambda = FALSE,
                      lambda.start = NULL, c = 1.1, gamma = 0.1/log(n)), control = list(numIter =
                      15, tol = 10^-5, threshold = NULL), ...)

rlasso.fit(x, y, post = TRUE, intercept = TRUE,
           penalty = list(homoscedastic = FALSE, X.dependent.lambda = FALSE,
                          lambda.start = NULL, c = 1.1, gamma = 0.1), control = list(numIter = 15, tol
                          = 10^-5, threshold = NULL), ...)
```

## Arguments

formula	an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted in the form $y \sim x$
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>rlasso</code> is called.
post	logical. If TRUE, post-Lasso estimation is conducted.
intercept	logical. If TRUE, intercept is included which is not penalized.
penalty	list with options for the calculation of the penalty. <ul style="list-style-type: none"> <li>• <code>c</code> and <code>gamma</code> constants for the penalty with default <code>c=1.1</code> and <code>gamma=0.1</code></li> <li>• <code>homoscedastic</code> logical, if homoscedastic errors are considered (default FALSE). Option <code>none</code> is described below.</li> <li>• <code>X.dependent.lambda</code> logical, TRUE, if the penalization parameter depends on the design of the matrix <code>x</code>. FALSE, if independent of the design matrix (default).</li> <li>• <code>numSim</code> number of simulations for the dependent methods, default=5000</li> <li>• <code>lambda.start</code> initial penalization value, compulsory for method "none"</li> </ul>
control	list with control values. <code>numIter</code> number of iterations for the algorithm for the estimation of the variance and data-driven penalty, ie. <code>loadings</code> , <code>tol</code> tolerance for improvement of the estimated variances. <code>threshold</code> is applied to the final estimated lasso coefficients. Absolute values below the threshold are set to zero.
...	further arguments (only for consistent definition of methods)
x	regressors (vector, matrix or object can be coerced to matrix)
y	dependent variable (vector, matrix or object can be coerced to matrix)

## Details

The function estimates the coefficients of a Lasso regression with data-driven penalty under homoscedasticity / heteroscedasticity and non-Gaussian noise. The option `homoscedastic` is a logical with FALSE by default. Moreover, for the calculation of the penalty parameter it can be chosen, if the penalization parameter depends on the design matrix (`X.dependent.lambda=TRUE`) or independent (default, `X.dependent.lambda=FALSE`). The default value of the constant `c` is 1.1 in the post-Lasso case and 0.5 in the Lasso case. A *special* option is to set `homoscedastic` to none and to supply a values `lambda.start`. Then this value is used as penalty parameter with independent design and heteroscedastic errors to weight the regressors. For details of the implementation of the Algorithm for estimation of the data-driven penalty, in particular the regressor-independent loadings, we refer to Appendix A in Belloni et al. (2012). When the option "none" is

chosen for homoscedastic (together with `lambda.start`), `lambda` is set to `lambda.start` and the regressor-independent loadings und heteroscedasticity are used. The options "X-dependent" and "X-independent" under homoscedasticity are described in Belloni et al. (2013).

The option `post=TRUE` conducts post-lasso estimation, i.e. a refit of the model with the selected variables.

### Value

`rlasso` returns an object of class `rlasso`. An object of class "rlasso" is a list containing at least the following components:

<code>coefficients</code>	parameter estimates (named vector of coefficients without intercept)
<code>intercept.value</code>	value of the intercept
<code>index</code>	index of selected variables (logical vector)
<code>lambda</code>	data-driven penalty term for each variable, product of <code>lambda0</code> (the penalization parameter) and the loadings
<code>lambda0</code>	penalty term
<code>loadings</code>	loading for each regressor
<code>residuals</code>	residuals, response minus fitted values
<code>sigma</code>	root of the variance of the residuals
<code>iter</code>	number of iterations
<code>call</code>	function call
<code>options</code>	options

### References

- A. Belloni, D. Chen, V. Chernozhukov and C. Hansen (2012). Sparse models and methods for optimal instruments with an application to eminent domain. *Econometrica* 80 (6), 2369-2429.
- A. Belloni, V. Chernozhukov and C. Hansen (2013). Inference for high-dimensional sparse econometric models. In Advances in Economics and Econometrics: 10th World Congress, Vol. 3: Econometrics, Cambridge University Press: Cambridge, 245-295.

### Examples

```
set.seed(1)
n = 100 #sample size
p = 100 # number of variables
s = 3 # number of non-zero variables
X = matrix(rnorm(n*p), ncol=p)
beta = c(rep(3,s), rep(0,p-s))
y = 1 + X%*%beta + rnorm(n)
lasso.reg = rlasso(y~X, post=TRUE, intercept=TRUE)
lasso.reg = rlasso(y~X, post=FALSE) # use Lasso, not Post-Lasso
print(lasso.reg, all=FALSE)
summary(lasso.reg, all=FALSE) # use this option to summarize results
yhat.lasso = predict(lasso.reg) #in-sample prediction
Xnew = matrix(rnorm(n*p), ncol=p) # new X
Ynew = Xnew%*%beta + rnorm(n) #new Y
yhat.lasso.new = predict(lasso.reg, newdata=Xnew) #out-of-sample prediction
```

---

rlassoATE*Functions for estimation of treatment effects*

---

## Description

This class of functions estimates the average treatment effect (ATE), the ATE of the treated (ATET), the local average treatment effects (LATE) and the LATE of the treated (LATET). The estimation methods rely on immunized / orthogonal moment conditions which guarantee valid post-selection inference in a high-dimensional setting. Further details can be found in Belloni et al. (2014).

## Usage

```
rlassoATE(x, d, y, bootstrap = "none", nRep = 500, ...)
rlassoATET(x, d, y, bootstrap = "none", nRep = 500, ...)
rlassoLATE(x, d, y, z, bootstrap = "none", nRep = 500, post = TRUE,
           intercept = TRUE)
rlassoLATET(x, d, y, z, bootstrap = "none", nRep = 500, post = TRUE,
            intercept = TRUE)
```

## Arguments

x	exogenous variables
d	treatment variable (binary)
y	outcome variable / dependent variable
bootstrap	bootstrap method which should be employed: 'none', 'Bayes', 'normal', 'wild'
nRep	number of replications for the bootstrap
...	arguments passed, e.g. <code>intercept</code> and <code>post</code>
z	instrumental variables (binary)
post	logical. If TRUE, post-lasso estimation is conducted.
intercept	logical. If TRUE, intercept is included which is not penalized.

## Details

Details can be found in Belloni et al. (2014).

## Value

Functions return an object of class `rlassoTE` with estimated effects, standard errors and individual effects in the form of a list.

## References

A. Belloni, V. Chernozhukov, I. Fernandez-Val, and C. Hansen (2014). Program evaluation with high-dimensional data. Working Paper.

## Description

Estimation and inference of (low-dimensional) target coefficients in a high-dimensional linear model.

## Usage

```
rlassoEffects(x, y, index = c(1:ncol(x)), method = "partialling out",
              I3 = NULL, post = TRUE, ...)

rlassoEffect(x, y, d, method = "double selection", I3 = NULL, post = TRUE,
             ...)
```

## Arguments

<b>x</b>	matrix of regressor variables serving as controls and potential treatments. For <code>rlassoEffect</code> it contains only controls, for <code>rlassoEffects</code> both controls and potential treatments. For <code>rlassoEffects</code> it must have at least two columns.
<b>y</b>	outcome variable (vector or matrix)
<b>index</b>	vector of integers, logicals or variables names indicating the position (column) of variables (integer case), logical vector of length of the variables (TRUE or FALSE) or the variable names of <b>x</b> which should be used for inference / as treatment variables.
<b>method</b>	method for inference, either 'partialling out' (default) or 'double selection'.
<b>I3</b>	For the 'double selection'-method the logical vector <b>I3</b> has same length as the number of variables in <b>x</b> ; indicates if variables (TRUE) should be included in any case to the model and they are exempt from selection. These variables should not be included in the <b>index</b> ; hence the intersection with <b>index</b> must be the empty set. In the case of partialling out it is ignored.
<b>post</b>	logical, if post Lasso is conducted with default TRUE.
<b>d</b>	variable for which inference is conducted (treatment variable)
<b>...</b>	parameters passed to the <code>rlasso</code> function.

## Details

The functions estimates (low-dimensional) target coefficients in a high-dimensional linear model. An application is e.g. estimation of a treatment effect  $\alpha_0$  in a setting of high-dimensional controls. The user can choose between the so-called post-double-selection method and partialling-out. The idea of the double selection method is to select variables by Lasso regression of the outcome variable on the control variables and the treatment variable on the control variables. The final estimation is done by a regression of the outcome on the treatment effect and the union of the selected variables in the first two steps. In partialling-out first the effect of the regressors on the outcome and the treatment variable is taken out by Lasso and then a regression of the residuals is conducted. The resulting estimator for  $\alpha_0$  is normal distributed which allows inference on the treatment effect. It presents a wrap function for `rlassoEffect` which does inference for a single variable.

### Value

The function returns an object of class `rlassoEffects` with the following entries:

<code>coefficients</code>	vector with estimated values of the coefficients for each selected variable
<code>se</code>	standard error (vector)
<code>t</code>	t-statistic
<code>pval</code>	p-value
<code>samplesize</code>	sample size of the data set
<code>index</code>	index of the variables for which inference is performed

### References

A. Belloni, V. Chernozhukov, C. Hansen (2014). Inference on treatment effects after selection among high-dimensional controls. *The Review of Economic Studies* 81(2), 608-650.

### Examples

```
library(hdm)
## DGP
n <- 250
p <- 100
px <- 10
X <- matrix(rnorm(n*p), ncol=p)
beta <- c(rep(2,px), rep(0,p-px))
intercept <- 1
y <- intercept + X %*% beta + rnorm(n)
## fit rlassoEffects object with inference on three variables
rlassoEffects.reg <- rlassoEffects(x=X, y=y, index=c(1,7,20))
## methods
summary(rlassoEffects.reg)
confint(rlassoEffects.reg, level=0.9)
```

### Description

The function estimates a treatment effect in a setting with very many controls and very many instruments (even larger than the sample size).

### Usage

```
rlassoIV(x, d, y, z, select.Z = TRUE, select.X = TRUE, post = TRUE, ...)
rlassoIVmult(x, d, y, z, select.Z = TRUE, select.X = TRUE, ...)
```

### Arguments

x	matrix of exogenous variables
d	endogenous variable
y	outcome / dependent variable (vector or matrix)
z	matrix of instrumental variables
select.Z	logical, indicating selection on the instruments
select.X	logical, indicating selection on the exogenous variables
post	logical, whether post-Lasso should be conducted (default=TRUE)
...	arguments passed to the function <code>rlasso</code>

### Details

The implementation for selection on x and z follows the procedure described in Chernozhukov et al. (2015) and is built on 'triple selection' to achieve an orthogonal moment function. The function returns an object of S3 class `rlassoIV`. Moreover, it is wrap function for the case that selection should be done only with the instruments Z (`rlassoIVselectZ`) or with the control variables X (`rlassoIVselectX`) or without selection (`tsls`).

### Value

an object of class `rlassoIV` containing at least the following components:

coefficients	estimated parameter value
se	variance-covariance matrix

### References

V. Chernozhukov, C. Hansen, M. Spindler (2015). Post-selection and post-regularization inference in linear models with many controls and instruments. *American Economic Review: Paper & Proceedings* 105(5), 486–490.

### Description

This function estimates the coefficient of an endogenous variable by employing Instrument Variables in a setting where the exogenous variables are high-dimensional and hence selection on the exogenous variables is required. The function returns an element of class `rlassoIVselectX`

### Usage

```
rlassoIVselectX(x, d, y, z, post = TRUE, ...)
```

### Arguments

x	exogenous variables in the structural equation (matrix)
d	endogenous variables in the structural equation (vector or matrix)
y	outcome or dependent variable in the structural equation (vector or matrix)
z	set of potential instruments for the endogenous variables.
post	logical. If TRUE, post-lasso estimation is conducted.
...	arguments passed to the function rlasso

### Details

The implementation is a special case of of Chernozhukov et al. (2015). The option post=TRUE conducts post-lasso estimation for the Lasso estimations, i.e. a refit of the model with the selected variables. If variables of the exogenous variables in x should be used as instruments, they have to be added to the instrument set z explicitly.

### Value

An object of class rlassoIVselectX containing at least the following components:

coefficients	estimated parameter vector
vcov	variance-covariance matrix
residuals	residuals
samplesize	sample size

### References

Chernozhukov, V., Hansen, C. and M. Spindler (2015). Post-Selection and Post-Regularization Inference in Linear Models with Many Controls and Instruments *American Economic Review, Papers and Proceedings* 105(5), 486–490.

### Description

This function selects the instrumental variables in the first stage by Lasso. First stage predictions are then used in the second stage as optimal instruments to estimate the parameter vector. The function returns an element of class rlassoIVselectZ

### Usage

```
rlassoIVselectZ(x, d, y, z, post = TRUE, ...)
```

## Arguments

x	exogenous variables in the structural equation (matrix)
d	endogenous variables in the structural equation (vector or matrix)
y	outcome or dependent variable in the structural equation (vector or matrix)
z	set of potential instruments for the endogenous variables. Exogenous variables serve as their own instruments.
post	logical. If TRUE, post-lasso estimation is conducted.
...	arguments passed to the function <code>rlasso</code>

## Details

The implementation follows the procedure described in Belloni et al. (2012). Option `post=TRUE` conducts post-lasso estimation, i.e. a refit of the model with the selected variables, to estimate the optimal instruments. The parameter vector of the structural equation is then fitted by two-stage least square (tsls) estimation.

## Value

An object of class `rlassoIVselectZ` containing at least the following components:

coefficients	estimated parameter vector
vcov	variance-covariance matrix
residuals	residuals
samplesize	sample size

## References

D. Belloni, D. Chen, V. Chernozhukov and C. Hansen (2012). Sparse models and methods for optimal instruments with an application to eminent domain. *Econometrica* 80 (6), 2369–2429.

## Description

The function estimates the coefficients of a logistic Lasso regression with data-driven penalty. The method of the data-driven penalty can be chosen. The object which is returned is of the S3 class `rlassologit`

## Usage

```
rlassologit(formula, data, post = TRUE, intercept = TRUE,
            penalty = list(lambda = NULL, c = 1.1, gamma = 0.1/log(n)),
            control = list(threshold = NULL), ...)

rlassologit.fit(x, y, post = TRUE, intercept = TRUE, penalty = list(lambda
            = NULL, c = 1.1, gamma = 0.1/log(n)), control = list(threshold = NULL), ...)
```

## Arguments

formula	an object of class 'formula' (or one that can be coerced to that class): a symbolic description of the model to be fitted in the form $y \sim x$
data	an optional data frame, list or environment
post	logical. If TRUE, post-lasso estimation is conducted.
intercept	logical. If TRUE, intercept is included which is not penalized.
penalty	list with options for the calculation of the penalty. c and gamma constants for the penalty.
control	list with control values. threshold is applied to the final estimated lasso coefficients. Absolute values below the threshold are set to zero.
...	further parameters passed to glmnet
x	regressors (matrix)
y	dependent variable (vector or matrix)

## Details

The function estimates the coefficients of a Logistic Lasso regression with data-driven penalty. The option post=TRUE conducts post-lasso estimation, i.e. a refit of the model with the selected variables.

## Value

rlassologit returns an object of class rlassologit. An object of class rlassologit is a list containing at least the following components:

coefficients	parameter estimates (without intercept)
a0	value of intercept
index	index of selected variables (logicals)
lambda	penalty term
residuals	residuals
sigma	root of the variance of the residuals
call	function call
options	options

## References

Belloni, A., Chernozhukov and Y. Wei (2013). Honest confidence regions for logistic regression with a large number of controls. arXiv preprint arXiv:1304.3969.

## Examples

```
## Not run:
library(hdm)
## DGP
set.seed(2)
n <- 250
p <- 100
px <- 10
X <- matrix(rnorm(n*p), ncol=p)
```

```

beta <- c(rep(2,px), rep(0,p-px))
intercept <- 1
P <- exp(intercept + X %*% beta)/(1+exp(intercept + X %*% beta))
y <- numeric(length=250)
for(i in 1:n){
  y[i] <- sample(x=c(1,0), size=1, prob=c(P[i],1-P[i]))
}
## fit rlassologit object
rlassologit.reg <- rlassologit(y~X)
## methods
summary(rlassologit.reg, all=F)
print(rlassologit.reg)
predict(rlassologit.reg, type='response')
X3 <- matrix(rnorm(n*p), ncol=p)
predict(rlassologit.reg, newdata=X3)

## End(Not run)

```

## rlassologitEffects      *rigorous Lasso for Logistic Models: Inference*

### Description

The function estimates (low-dimensional) target coefficients in a high-dimensional logistic model.

### Usage

```

rlassologitEffects(x, y, index = c(1:ncol(x)), I3 = NULL, ...)
rlassologitEffect(x, y, d, I3 = NULL)

```

### Arguments

<b>x</b>	matrix of regressor variables serving as controls and potential treatments. For <b>rlassologitEffect</b> it contains only controls, for <b>rlassologitEffects</b> both controls and potential treatments. For <b>rlassologitEffects</b> it must have at least two columns.
<b>y</b>	outcome variable
<b>index</b>	vector of integers, logical or names indicating the position (column) or name of variables of x which should be used as treatment variables.
<b>I3</b>	logical vector with same length as the number of controls; indicates if variables (TRUE) should be included in any case.
<b>d</b>	variable for which inference is conducted (treatment variable)
<b>...</b>	additional parameters

### Details

The functions estimates (low-dimensional) target coefficients in a high-dimensional logistic model. An application is e.g. estimation of a treatment effect  $\alpha_0$  in a setting of high-dimensional controls. The function is a wrap function for **rlassologitEffect** which does inference for only one variable (d).

**Value**

The function returns an object of class `rlassologitEffects` with the following entries:

<code>coefficients</code>	estimated value of the coefficients
<code>se</code>	standard errors
<code>t</code>	t-statistics
<code>pval</code>	p-values
<code>samplesize</code>	sample size of the data set
<code>I</code>	index of variables of the union of the lasso regressions

**References**

A. Belloni, V. Chernozhukov, Y. Wei (2013). Honest confidence regions for a regression parameter in logistic regression with a loarge number of controls. cemmap working paper CWP67/13.

`summary.rlassoEffects` *Summarizing rlassoEffects fits*

**Description**

Summary method for class `rlassoEffects`

**Usage**

```
## S3 method for class 'rlassoEffects'
summary(object, ...)

## S3 method for class 'summary.rlassoEffects'
print(x, digits = max(3L, getOption("digits")
- 3L), ...)
```

**Arguments**

<code>object</code>	an object of class <code>rlassoEffects</code> , usually a result of a call to <code>rlassoEffects</code>
<code>...</code>	further arguments passed to or from other methods.
<code>x</code>	an object of class <code>summary.rlassoEffects</code> , usually a result of a call to <code>summary.rlassoEffects</code>
<code>digits</code>	the number of significant digits to use when printing.

**Details**

Summary of objects of class `rlassoEffects`

**tsls***Two-Stage Least Squares Estimation (TSLS)***Description**

The function does Two-Stage Least Squares Estimation (TSLS).

**Usage**

```
tsls(y, d, x, z, intercept = TRUE, homoscedastic = TRUE)
```

**Arguments**

<b>y</b>	outcome variable
<b>d</b>	endogenous variables
<b>x</b>	exogenous variables
<b>z</b>	instruments
<b>intercept</b>	logical, if intercept should be included
<b>homoscedastic</b>	logical, if homoscedastic (TRUE, default) or heteroscedastic errors (FALSE) should be calculated.

**Details**

The function computes tsls estimate (coefficients) and variance-covariance-matrix assuming homoskedasticity for outcome variable **y** where **d** are endogenous variables in structural equation, **x** are exogenous variables in structural equation and **z** are instruments. It returns an object of class **tsls** for which the methods **print** and **summary** are provided.

**Value**

The function returns a list with the following elements

<b>coefficients</b>	coefficients
<b>vcov</b>	variance-covariance matrix
<b>residuals</b>	outcome minus predicted values
<b>call</b>	function call
<b>samplesize</b>	sample size
<b>se</b>	standard error

# Index

- \*Topic **2SLS**
  - tsls, 26
- \*Topic **401(k)**
  - pension, 7
- \*Topic **Endogeneity**
  - hdm-package, 2
  - tsls, 26
- \*Topic **Estimation**
  - rlassoEffects, 18
  - rlassologitEffects, 24
- \*Topic **Evaluation**
  - hdm-package, 2
- \*Topic **GDP**
  - Growth Data, 4
- \*Topic **Growth**
  - Growth Data, 4
- \*Topic **Hig-dimensional**
  - rlassoIVselectX, 20
  - rlassoIVselectZ, 21
- \*Topic **High-dimensional**
  - rlassoEffects, 18
- \*Topic **Inference**
  - rlassoEffects, 18
  - rlassologitEffects, 24
- \*Topic **Instrumental**
  - hdm-package, 2
  - rlassoIV, 19
  - rlassoIVselectX, 20
  - rlassoIVselectZ, 21
  - tsls, 26
- \*Topic **Lasso**
  - hdm-package, 2
  - LassoShooting.fit, 6
  - rlasso, 14
  - rlassoIV, 19
  - rlassoIVselectX, 20
  - rlassoIVselectZ, 21
  - rlassologitEffects, 24
- \*Topic **Logistic**
  - rlassologitEffects, 24
- \*Topic **Many**
  - rlassoIV, 19
- \*Topic **Microeconomics**
- hdm-package, 2
- \*Topic **Program**
  - hdm-package, 2
- \*Topic **Shooting**
  - LassoShooting.fit, 6
- \*Topic **TSLS**
  - tsls, 26
- \*Topic **Treatment**
  - rlassoEffects, 18
- \*Topic **Variables**
  - hdm-package, 2
  - rlassoIVselectX, 20
  - rlassoIVselectZ, 21
  - tsls, 26
- \*Topic **Variable**
  - rlassoIV, 19
- \*Topic **and**
  - rlassoIV, 19
- \*Topic **average**
  - rlassoATE, 17
- \*Topic **controls**
  - rlassoEffects, 18
  - rlassoIV, 19
- \*Topic **data-driven**
  - rlasso, 14
- \*Topic **datasets**
  - AJR, 3
  - EminentDomain, 4
  - Growth Data, 4
  - pension, 7
- \*Topic **effects**
  - hdm-package, 2
- \*Topic **effect**
  - rlassoATE, 17
  - rlassoEffects, 18
- \*Topic **heteroscedasticity**
  - rlasso, 14
- \*Topic **instruments**
  - rlassoIV, 19
- \*Topic **lasft**
  - rlassoATE, 17
- \*Topic **lasf**
  - rlassoATE, 17

\*Topic **lasso**  
     rlassologit, 22

\*Topic **late**  
     rlassoATE, 17

\*Topic **latt**  
     rlassoATE, 17

\*Topic **local**  
     rlassoATE, 17

\*Topic **logistic**  
     rlassologit, 22

\*Topic **methods**  
     predict.rlassologit, 8  
     print.rlasso, 9  
     print.rlassoEffects, 9  
     print.rlassoIV, 10  
     print.rlassoIVselectX, 11  
     print.rlassoIVselectZ, 12  
     print.rlassologitEffects, 12  
     print.rlassoTE, 13  
     print.tsls, 14

\*Topic **non-Gaussian**  
     rlasso, 14

\*Topic **package**  
     hdm-package, 2

\*Topic **penalty**  
     rlasso, 14

\*Topic **pension**  
     pension, 7

\*Topic **regression**  
     rlassologit, 22

\*Topic **rlassoEffects**  
     print.rlassoEffects, 9

\*Topic **rlassoIVselectX**  
     print.rlassoIVselectX, 11

\*Topic **rlassoIVselectZ**  
     print.rlassoIVselectZ, 12

\*Topic **rlassoIV**  
     print.rlassoIV, 10

\*Topic **rlassoTE**  
     print.rlassoTE, 13

\*Topic **rlassologitEffects**  
     print.rlassologitEffects, 12

\*Topic **rlassologit**  
     predict.rlassologit, 8

\*Topic **rlasso**  
     print.rlasso, 9

\*Topic **setting**  
     rlassoIVselectX, 20  
     rlassoIVselectZ, 21

\*Topic **structural**  
     rlassoATE, 17

\*Topic **treatment**

    hdm-package, 2  
     rlassoATE, 17

\*Topic **tsls**  
     print.tsls, 14

AJR, 3

ATE (rlassoATE), 17

ate (rlassoATE), 17

ATET (rlassoATE), 17

atet (rlassoATE), 17

confint.rlassoEffects  
     (print.rlassoEffects), 9

confint.rlassoIV (print.rlassoIV), 10

confint.rlassoIVselectX  
     (print.rlassoIVselectX), 11

confint.rlassoIVselectZ  
     (print.rlassoIVselectZ), 12

confint.rlassologitEffects  
     (print.rlassologitEffects), 12

confint.rlassoTE (print.rlassoTE), 13

data (pension), 7

EminentDomain, 4

Example (Growth Data), 4

GDP (Growth Data), 4

Growth (Growth Data), 4

Growth Data, 4

GrowthData (Growth Data), 4

hdm (hdm-package), 2

hdm-package, 2

lambdaCalculation, 5

LassoShooting.fit, 6

LATE (rlassoATE), 17

late (rlassoATE), 17

LATET (rlassoATE), 17

latet (rlassoATE), 17

methods.rlasso (print.rlasso), 9

methods.rlassoEffects  
     (print.rlassoEffects), 9

methods.rlassoIV (print.rlassoIV), 10

methods.rlassoIVselectX  
     (print.rlassoIVselectX), 11

methods.rlassoIVselectZ  
     (print.rlassoIVselectZ), 12

methods.rlassologit  
     (predict.rlassologit), 8

methods.rlassologitEffects  
     (print.rlassologitEffects), 12

methods.rlassoTE (print.rlassoTE), 13  
methods.tsls (print.tsls), 14  
model.matrix.rlasso (print.rlasso), 9  
model.matrix.rlassologit  
    (predict.rlassologit), 8  
  
pension, 7  
plans (pension), 7  
plot.rlassoEffects  
    (print.rlassoEffects), 9  
predict.rlasso (print.rlasso), 9  
predict.rlassologit, 8  
print.rlasso, 9  
print.rlassoEffects, 9  
print.rlassoIV, 10  
print.rlassoIVselectX, 11  
print.rlassoIVselectZ, 12  
print.rlassologit  
    (predict.rlassologit), 8  
print.rlassologitEffects, 12  
print.rlassoTE, 13  
print.summary.rlassoEffects  
    (summary.rlassoEffects), 25  
print.tsls, 14  
  
rlasso, 5, 14  
rlassoATE, 17  
rlassoATET (rlassoATE), 17  
rlassoEffect (rlassoEffects), 18  
rlassoEffects, 18  
rlassoIV, 19  
rlassoIVmult (rlassoIV), 19  
rlassoIVselectX, 20  
rlassoIVselectZ, 21  
rlassoLATE (rlassoATE), 17  
rlassoLATET (rlassoATE), 17  
rlassologit, 22  
rlassologitEffect (rlassologitEffects),  
    24  
rlassologitEffects, 24  
  
summary.rlasso (print.rlasso), 9  
summary.rlassoEffects, 9, 25  
summary.rlassoIV (print.rlassoIV), 10  
summary.rlassoIVselectX  
    (print.rlassoIVselectX), 11  
summary.rlassoIVselectZ  
    (print.rlassoIVselectZ), 12  
summary.rlassologit  
    (predict.rlassologit), 8  
summary.rlassologitEffects  
    (print.rlassologitEffects), 12  
summary.rlassoTE (print.rlassoTE), 13