List of functions in package 'rgr' and other package functions they call:

1. **Statistical graphics functions and required package functions:**

    gx.hist
            remove.na
    cnnplt
            remove.na
    gx.cnpplts
            remove.na
    gx.cnpplts.setup
    gx.ecdf
            remove.na
    gx.ks.test
            gx.ecdf, remove.na
    bxplot
            remove.na
    shape
            gx.hist, bxplot, gx.ecdf, cnpplt, remove.na
    inset
            gx.hist, gx.stats, cnpplt, remove.na
    inset.exporter
            inset
    bwplots
            cat2list
    bwplots.by.var
            var2fact, bwplots
    tbplots
            cat2list
    tbplots.by.var
            var2fact, tbplots

2. **Mapping s and XY Plotting functions and required package functions:**

    map.eda7
            cutter, remove.na, eqscplot (Library MASS)
    map.eda8
            cutter, remove.na, eqscplot (Library MASS)
    map.tags
            remove.na, eqscplot (Library MASS)
    map.z
            syms, remove.na, eqscplot (Library MASS)
    caplot
            cnpplt, eqscplot (Library MASS), interp (Library akima)
    xyplot.eda7
            cutter, remove.na
    xyplot.eda8
            cutter, remove.na
    xyplot.tags
            remove.na
    xyplot.z
            syms, remove.na

3. Summary statistics functions and required package functions:

gx.stats (display = TRUE)
        remove.na
gx.summary1
        gx.summary
gx.summary.mat
        gx.summary
gx.summary.groups
        gx.summary
gx.summary2
        gx.stats
fences
        remove.na
fences.summary
        fences
framework.summary
        framework.stats
gx.fractile
        remove.na
gx.quantile
        remove.na

4. Bivariate and Multivariate functions and required package functions:

gx.adjr2
gx.lm.vif
gx.2dproj
        remove.na, sammon & isoMDS (Library MASS), fastICA (Library fastICA)
gx.2dproj.plot
gx.md.gait
        remove.na, cov.mcd (Library MASS), gx.md.plt0
gx.md.gait.closed
        remove.na, ilr, cov.mcd (Library MASS), gx.md.plt0
gx.md.plot
        gx.md.plt0
gx.md.print
gx.mva
        remove.na
gx.mvalloc
gx.mvalloc.closed
        clr
gx.mvalloc.print
gx.pearson
        remove.na, clr
gx.spearman
        remove.na, clr
gx.rma
        remove.na
gx.robmva
        remove.na, cov.mcd (Library MASS), cov.mve (Library MASS)
gx.robmva.closed
        remove.na, ilr, orthonorm, cov.mcd (Library MASS), cov.mve (Library MASS)
gx.rotate
gx.rqpca.screeplot
gx.rqpca.print

gx.rqpca.loadplot
gx.rqpca.plot
wtd.sums
     remove.na

5. QA/QC support functions and required package functions:

anova1
     remove.na
anova2
     anova1
gx.triples.aov
gx.triples.fgx
     remove.na
thplot1
     remove.na
thplot2
     thplot1

6. Data conditioning functions:

ltdl.fix
ltdl.fix.df
remove.na
gx.subset
alr
clr
ilr
rng

7. Utility functions and required package functions :

df.test
gx.sort
gx.sort.df
gx.hypergeom
gx.runs
display.lty
display.marks
display.ascii.o
display.rainbow
where.na
syms.pfunc
     syms

8. Internally called functions and required package functions :

cat2list
var2fact
cutter
gx.summary
     gx.stats (display = FALSE)
framework.stats
     gx.stats (display = FALSE)
gx.stats (display = FALSE)
     remove.na

```
gx.add.chisq
gx.md.plt0
        gx.add.chisq
syms
orthonorm
```

Robert G. Garrett
2011/02/26