

Package ‘SCDA’

October 14, 2024

Type Package

Title Spatially-Clustered Data Analysis

Version 0.0.1

Description Contains functions for statistical data analysis based on spatially-clustered techniques. The package allows estimating the spatially-clustered spatial regression models presented in Cerqueti, Maranzano & Mattera (2024), “Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe”, arXiv preprint 2407.15874 <[doi:10.48550/arXiv.2407.15874](https://doi.org/10.48550/arXiv.2407.15874)>. Specifically, the current release allows the estimation of the spatially-clustered linear regression model (SCLM), the spatially-clustered spatial autoregressive model (SCSAR), the spatially-clustered spatial Durbin model (SCSEM), and the spatially-clustered linear regression model with spatially-lagged exogenous covariates (SCSLX).

License GPL (>= 2)

Imports spatialreg,sp,spdep,utils,rlang,performance,stats,methods,dplyr

Depends R (>= 3.5.0)

Suggests tidyverse, ggplot2, sf

Encoding UTF-8

Language en-US

RoxygenNote 7.3.1

LazyData true

Maintainer Paolo Maranzano <pmaranzano.ricercastatistica@gmail.com>

NeedsCompilation no

Author Paolo Maranzano [aut, cre, cph]
(<<https://orcid.org/0000-0002-9228-2759>>),
Raffaele Mattera [aut, cph] (<<https://orcid.org/0000-0001-8770-7049>>)

Repository CRAN

Date/Publication 2024-10-14 12:20:04 UTC

Contents

Data2010	2
Data2020	3
Elbow_finder	4
listW	5
SCSR_Estim	6
SCSR_InfoCrit	9
SpatReg_Extract	11
SpatReg_GoF	12
SpatReg_Perf	13
SpatReg_PseudoR2	14
Index	15

Data2010	<i>Spatial dataset to replicate the results for 2010 from Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<https://doi.org/10.48550/arXiv.2407.15874>)</i>
----------	--

Description

The 'Data_RC_PM_RM_JABES2024' dataset was created merging information from the Eurostat regional database (<<https://ec.europa.eu/eurostat/web/regions/database>>). it is a spatial dataset to replicate the results for 2010 from Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<<https://doi.org/10.48550/arXiv.2407.15874>>). Data contained in this file refer to the agricultural sector industry for 222 European regions (NUTS-2 classification) for 2010. For more information see the database 'Economic accounts for agriculture by NUTS 2 region' (agr_r_accts, DOI:10.2908/agr_r_accts). The file includes 6 mixed-type objects:

Usage

```
data(Data_RC_PM_RM_JABES2024)
```

Format

Data2010 is a spatial data frame (sf/data.frame) with 222 rows, 13 variables and a geometry representing the regions' polygons:

Reference year for the data, that is, 2010

year_lab Extended name (English-translated) of the regions

geo Eurostat NUTS-2 code of the regions

Gini_SO Gini index for the standard output of farms and agricultural holdings in each region

GDPPC_PPS2020 Regional per capita GDP measured as Euros PPS 2020

Share_AgroEmp Share of employment in agriculture: relevance of agricultural industry on the regional labor market

HoursWorked_AgroEmp Hours worked per agro-employed: agricultural labor market intensity

GVA_AgroEmp Gross value added per agro-employed: agricultural productivity intensity

GFCF_AgroEmp Investment per agro-employed: propensity to invest according to the economic size

Share_AgroGVA Share of agricultural GVA on total GVA: relevance of agricultural industry on the regional economy

Share_AgroLand Share of agricultural land: relevance of agricultural industry on the regional activities

Alt_mean Average altitude: geography and landscape

HDD Heating degree days (HDD): proxy of temperature and weather conditions

Note

All source data files prepared by Paolo Maranzano (Department of Economics, Management and Statistics, University of Milano-Bicocca, Italy).

Source

Eurostat – Economic accounts for agriculture by NUTS 2 region’ (agr_r_accts, DOI:10.2908/agr_r_accts)

Data2020

Spatial dataset to replicate the results for 2020 from Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<<https://doi.org/10.48550/arXiv.2407.15874>>)

Description

The 'Data_RC_PM_RM_JABES2024' dataset was created merging information from the Eurostat regional database (<<https://ec.europa.eu/eurostat/web/regions/database>>). it is a spatial dataset to replicate the results for 2020 from Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<<https://doi.org/10.48550/arXiv.2407.15874>>). Data contained in this file refer to the agricultural sector industry for 222 European regions (NUTS-2 classification) for 2020. For more information see the database 'Economic accounts for agriculture by NUTS 2 region' (agr_r_accts, DOI:10.2908/agr_r_accts). The file includes 6 mixed-type objects:

Usage

data(Data_RC_PM_RM_JABES2024)

Format

Data2020 is a data frame with 222 rows, 13 variables and a geometry representing the regions' polygons:

Reference year for the data, that is, 2020

Year_lab Extended name (English-translated) of the regions

geo Eurostat NUTS-2 code of the regions

Gini_SO Gini index for the standard output of farms and agricultural holdings in each region

GDPPC_PPS2020 Regional per capita GDP measured as Euros PPS 2020

Share_AgroEmp Share of employment in agriculture: relevance of agricultural industry on the regional labor market

HoursWorked_AgroEmp Hours worked per agro-employed: agricultural labor market intensity

GVA_AgroEmp Gross value added per agro-employed: agricultural productivity intensity

GFCF_AgroEmp Investment per agro-employed: propensity to invest according to the economic size

Share_AgroGVA Share of agricultural GVA on total GVA: relevance of agricultural industry on the regional economy

Share_AgroLand Share of agricultural land: relevance of agricultural industry on the regional activities

Alt_mean Average altitude: geography and landscape

HDD Heating degree days (HDD): proxy of temperature and weather conditions

Note

All source data files prepared by Paolo Maranzano (Department of Economics, Management and Statistics, University of Milano-Bicocca, Italy).

Source

Eurostat – Economic accounts for agriculture by NUTS 2 region' (agr_r_accts, DOI:10.2908/agr_r_accts)

Elbow_finder

Automatically selects the optimal number of clusters based on elbow criterion.

Description

Automatically selects the optimal number of clusters (X-axis) based on elbow criterion computed on a metric (Y-axis). Potential metrics are the AIC and the BIC. The function can be applied to any other context in which the objective is to find the optimal X producing an elbow in Y.

Usage

Elbow_finder(x, y, Plot = TRUE)

Arguments

x	Numeric (m x 1) vector of integer values (usually, the number of clusters from 1 to G)
y	Numeric (m x 1) vector of values (usually, the criterion values) associated with the number of groups.
Plot	Logical value (TRUE or FALSE). If Plot = TRUE a plot of the relationship between x and y is produced. The plot is a scatterplot with connecting lines. A vertical line is depicted in correspondence of the optimal value of x.

Value

Returns the following outputs:

- x_max_dist: optimal value of x (i.e., the x satisfying the elbow rule)
- y_max_dist: optimal value of y (i.e., the y satisfying the elbow rule)
- Scatterplot (non-compulsory) of x and y with connecting lines and vertical line in correspondence of the optimal value of x.

Examples

```
## Compute the Elbow criterion on two generic vectors x and y
x <- 1:10
y <- c(10,9,6,5,4,3,2,1,1,1)
Elbow_finder(x,y,Plot = TRUE)
```

listW	<i>List of 222 spatial weights (style = "W", zero.policy=TRUE) used in Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<https://doi.org/10.48550/arXiv.2407.15874>)</i>
-------	---

Description

The 'Data_RC_PM_RM_JABES2024' dataset was created merging information from the Eurostat regional database (<<https://ec.europa.eu/eurostat/web/regions/database>>). it is a spatial dataset to replicate the results for 2020 from Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<<https://doi.org/10.48550/arXiv.2407.15874>>). Data contained in this file refer to the agricultural sector industry for 222 European regions (NUTS-2 classification) for 2020. For more information see the database 'Economic accounts for agriculture by NUTS 2 region' (agr_r_accts, DOI:10.2908/agr_r_accts). The file includes 6 mixed-type objects:

Usage

```
data(Data_RC_PM_RM_JABES2024)
```

Format

`listW` is a list of 222 spatial weights (`style = "W"`, `zero.policy=TRUE`) for the European NUTS-2 regions

Note

All source data files prepared by Paolo Maranzano (Department of Economics, Management and Statistics, University of Milano-Bicocca, Italy).

Source

Eurostat – GISCO Territorial units for statistics (NUTS) (<https://ec.europa.eu/eurostat/web/gisco/geodata/statistical-units/territorial-units-statistics>)

SCSR_Estim

Estimate spatially-clustered spatial regression models

Description

Estimates spatially-clustered spatial regression (SCSR) models, such as the spatially-clustered linear regression model (SCLM), the spatially-clustered spatial autoregressive model (SCSAR), the spatially-clustered spatial durbin model (SCSEM), and the spatially-clustered linear regression model with spatially-lagged exogenous covariates and response variable (SCSLX). Estimation is performed via cluster-wise maximum likelihood as presented in <https://arxiv.org/abs/2407.15874>.

Usage

```
SCSR_Estim(
  Formula,
  Data_sf,
  listW,
  G = 2,
  Phi = 1,
  Type = c("SCLM", "SCSAR", "SCSEM", "SCSLX"),
  CenterVars = FALSE,
  ScaleVars = FALSE,
  Maxitr = 100,
  RelTol = 10^-6,
  AbsTol = 10^-5,
  Verbose = TRUE,
  Seed = 123456789
)
```

Arguments

Formula	a symbolic description of the regression model to be fit. The details of model specification are given for <code>lm(...)</code>
Data_sf	A <code>data.frame</code> object of class <code>sf</code> with <code>n</code> rows (each one corresponding to a location/polygon) and a user-defined number of columns. The data frame must contain the response variable and all the covariates to be used in the model. Also, it must include the geometry feature for spatial modelling and representation. Typically, <code>sf data.frame</code> are built using the <code>st_as_sf(...)</code> command from the <code>sf</code> package (see its documentation for details).
listW	<code>listw</code> object. It contains the spatial weights for the spatial autoregressive component. Typically, <code>listW</code> is built using the <code>nb2listw(...)</code> command from the <code>spdep</code> package (see its documentation for details). We suggest to adopt one of matrix styles suggested in the <code>spdep</code> package, such as <code>W</code> (row-standardized) or <code>B</code> (binary). We also suggest to adopt a <code>zero.policy = TRUE</code> option to allow the computation of groups/clusters with isolated units. In this regard, we recall that if <code>zero.policy = FALSE</code> and <code>Type = "SCSAR"</code> causes <code>SCSR_Estim(...)</code> to terminate with an error. See package <code>spatialreg</code> for details on the <code>zero.policy</code> input.
G	Integer value. Number of clusters to be considered. When <code>'G=1'</code> , the pooled regression (no clusterwise) is estimated. Default is <code>'G = 2'</code> .
Phi	Non-negative (≥ 0) real value. Spatial penalty parameter. Default is <code>'Phi = 1'</code> .
Type	Character. Declares which model specification has to be estimated. Admitted strings are: <ul style="list-style-type: none"> • <code>"SCLM"</code> for linear regression model without spatial effects (LM); • <code>"SCSAR"</code> for spatial autoregressive (SAR) model; • <code>"SCSEM"</code> for linear regression model with spatial autoregressive error term or spatial Durbin model (SEM); • <code>"SCSLX"</code> for linear regression model with spatially-lagged response variable and covariates (SLX);
CenterVars	Logical value (TRUE or FALSE) stating whether the response variable and the covariates have to be centered around the mean in the iterative algorithm to update memberships and group-wise parameters. Centering is only use in the iterative procedure, while final estimates provided to the user are computed original (i.e., non-centered) variables.
ScaleVars	Logical value (TRUE or FALSE) stating whether the response variable and the covariates have to be scaled with respect to their standard deviation in the iterative algorithm to update memberships and group-wise parameters. Scaling is only used in the iterative procedure, while final estimates provided to the user are computed original (i.e., non-scaled) variables.
Maxitr	Integer value. Maximum number of iterations for the iterative algorithm. Convergence criterion is fixed to $\varepsilon = 10^{(-5)}$.
RelTol	Tolerance for the relative improvement in the log-likelihood (exit criterion) from iteration <code>k</code> to <code>k+1</code> . Default is $\varepsilon_{Rel} = 10^{-6}$
AbsTol	Tolerance for the absolute improvement in the log-likelihood (exit criterion) from iteration <code>k</code> to <code>k+1</code> . Default is $\varepsilon_{Abs} = 10^{-5}$

Verbose	Logical value (TRUE or FALSE). Toggle warnings and messages. If verbose = TRUE (default) the function prints on the screen some messages describing the progress of the tasks. If verbose = FALSE any message about the progression is suppressed.
Seed	Integer value. Define the random number generator (RNG) state for random number generation in R. Deafult is seed = 123456789.

Details

The package SCSR computes the spatially-clustered spatial regression models based on the `spatialreg` package (see <https://cran.r-project.org/web/packages/spatialreg/index.html>). SCSAR model is estimated using the function `lagsar1m`; SCSEM model is estimated using the function `errorsar1m`; SCSLX model is estimated using the function `lmSLX`. SCLM model is estimated using the `lm` function from package `stats`. Thus, estimated SCSAR, SCSEM and SCSLX models belong to class `Sar1m`, while estimated SCLM belongs to class `lm`. We kindly refer to the package `spatialreg` for any detail regarding computational aspects (e.g., optimization). Also, we refer to the package `spdep` for computational details on the spatial weighting matrix via `listw2mat(...)`, `nb2listw(...)` and `nb2mat(...)` from the `spdep` package. For computational details on the spatially-clustered models, we kindly refer to Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<doi:10.48550/arXiv.2407.15874>)

Value

A list object containing the following outputs:

- `ClusterFitModels`: G-dimensional list containing the estimated clustered regression models of class `lm` or `Sar1m`
- `Beta`: (G x p) matrix of cluster-wise or pooled regression coefficients
- `Sig`: G-dimensional vector of cluster-wise standard deviations
- `VCov`: (p x p x G) array of cluster-wise variance-covariance matrices of coefficients
- `W_g`: G-dimensional list containing for the g-th cluster with cardinality `n_g` a (`n_g` x `n_g`) spatial weighting matrix
- `listW_g`: G-dimensional list containing for the g-th cluster the weights list
- `Group`: (n x 1) vector of group assignment
- `sBeta`: (n x p) matrix of location-wise regression coefficients
- `sSig`: (n x 1) vector of location-wise standard deviations
- `MLE`: Estimated maximum log-likelihood
- `Iter`: The number of iteration needed to satisfy the convergence criterion and end up the clustering iterative loop

Examples

```
data(Data_RC_PM_RM_JABES2024, package="SCDA")
SCSAR <- SCSR_Estim(Formula = "Gini_S0 ~ GDPPC_PPS2020 + Share_AgroEmp",
  Data_sf = Data2020, G=3, listW=listW, Type="SCSAR", Phi = 0.50)
```

```
SCLM <- SCSR_Estim(Formula = "Gini_SO ~ GDPPC_PPS2020 + Share_AgroEmp",
                  Data_sf = Data2020, G=3, listW=listW, Type="SCLM", Phi = 0.50)
```

SCSR_InfoCrit	<i>Automatically select the optimal number of clusters based on likelihood information criteria (i.e., AIC, BIC and HQC) for a given SCSR model.</i>
---------------	--

Description

Computes the likelihood-based information criteria (i.e, Akaike's IC, Bayesian IC, and Hannan–Quinn IC) for every SCSR model given by the combination of the G and Phi contained in the G.set and Phi.set inputs and provides the associated likelihood-based information criteria. Given the minimization rule, SCSR_InfoCrit automatically identifies the optimal number of clusters for every criterion.

Usage

```
SCSR_InfoCrit(
  Formula,
  Data_sf,
  listW,
  Phi.set = c(0.5, 1),
  G.set = c(2, 3, 4),
  Type = c("SCLM", "SCSAR", "SCSEM", "SCSLX"),
  CenterVars = TRUE,
  ScaleVars = TRUE,
  Maxitr = 200,
  RelTol = 10^-6,
  AbsTol = 10^-5,
  Verbose = TRUE,
  Seed = 123456789
)
```

Arguments

Formula	a symbolic description of the regression model to be fit. The details of model specification are given for <code>lm(...)</code>
Data_sf	A <code>data.frame</code> object of class <code>sf</code> with <code>n</code> rows (each one corresponding to a location/polygon) and a user-defined number of columns. The data frame must contain the response variable and all the covariates to be used in the model. Also, it must include the geometry feature for spatial modelling and representation. Typically, <code>sf</code> data.frame are built using the <code>st_as_sf(...)</code> command from the <code>sf</code> package (see its documentation for details).

<code>listW</code>	<code>listw</code> object. It contains the spatial weights for the spatial autoregressive component. Typically, <code>listW</code> is built using the <code>nb2listw(...)</code> command from the <code>spdep</code> package (see its documentation for details). We suggest to adopt one of matrix styles suggested in the <code>spdep</code> package, such as <code>W</code> (row-standardized) or <code>B</code> (binary). We also suggest to adopt a <code>zero.policy = TRUE</code> option to allow the computation of groups/clusters with isolated units. In this regard, we recall that if <code>zero.policy = FALSE</code> and <code>Type = "SCSAR"</code> causes <code>SCSR_Estim(...)</code> to terminate with an error. See package <code>spatialreg</code> for details on the <code>zero.policy</code> input.
<code>Phi.set</code>	Non-negative (≥ 0) real-valued vector. Sequence of spatial penalty parameter. Default is <code>Phi = c(0.50, 1)</code> .
<code>G.set</code>	Integer vector. Sequence of clusters to be considered. Default is <code>G = c(2, 3, 4)</code> .
<code>Type</code>	Character. Declares which model specification has to be estimated. Admitted strings are: <ul style="list-style-type: none"> • "SCLM" for linear regression model without spatial effects (LM); • "SCSAR" for spatial autoregressive (SAR) model; • "SCSEM" for linear regression model with spatial autoregressive error term or spatial Durbin model (SEM); • "SCSLX" for linear regression model with spatially-lagged response variable and covariates (SLX);
<code>CenterVars</code>	Logical value (TRUE or FALSE) stating whether the response variable and the covariates have to be centered around the mean in the iterative algorithm to update memberships and group-wise parameters. Centering is only use in the iterative procedure, while final estimates provided to the user are computed original (i.e., non-centered) variables.
<code>ScaleVars</code>	Logical value (TRUE or FALSE) stating whether the response variable and the covariates have to be scaled with respect to their standard deviation in the iterative algorithm to update memberships and group-wise parameters. Scaling is only used in the iterative procedure, while final estimates provided to the user are computed original (i.e., non-scaled) variables.
<code>Maxitr</code>	Integer value. Maximum number of iterations for the iterative algorithm. Convergence criterion is fixed to $\varepsilon = 10^{-5}$.
<code>RelTol</code>	Tolerance for the relative improvement in the log-likelihood (exit criterion) from iteration k to $k+1$. Default is $\varepsilon_{Rel} = 10^{-6}$
<code>AbsTol</code>	Tolerance for the absolute improvement in the log-likelihood (exit criterion) from iteration k to $k+1$. Default is $\varepsilon_{Abs} = 10^{-5}$
<code>Verbose</code>	Logical value (TRUE or FALSE). Toggle warnings and messages. If <code>verbose = TRUE</code> (default) the function prints on the screen some messages describing the progress of the tasks. If <code>verbose = FALSE</code> any message about the progression is suppressed.
<code>Seed</code>	Integer value. Define the random number generator (RNG) state for random number generation in R. Deafult is <code>seed = 123456789</code> .

Details

Given the vectors $G.set = c(2,3,4)$ and $\Phi.set = c(0.50,1)$, the function 'SCSR_InfoCrit' will compute $3 \times 2 = 6$ models, each at a given combination of G and Φ . For computational details on the spatially-clustered models, we kindly refer to Cerqueti, R., Maranzano, P. & Mattera, R. "Spatially-clustered spatial autoregressive models with application to agricultural market concentration in Europe". arXiv preprints (<doi:10.48550/arXiv.2407.15874>)

Value

A list object containing the following outputs:

- **IC**: a data.frame object containing one row for each combination of the supplied vectors $G.set$ and $\Phi.set$ and 5 columns (G, Φ, AIC, BIC, HQC).
- **OptimPars**: a data.frame object with 3 rows (criteria) and 2 columns (Parameters) with the optimal combination of G and Φ for every criterion.

Examples

```
data(Data_RC_PM_RM_JABES2024, package="SCDA")
SCSAR_IC <- SCSR_InfoCrit(Formula = "Gini_S0 ~ GDPPC_PPS2020 + Share_AgroEmp",
  Data_sf = Data2020, listW=listW, Type="SCSAR",
  Maxitr = 100, Phi.set = c(0.50,1), G.set=c(2,3))
```

SpatReg_Extract	<i>Extracts numerical values for the estimated regression parameters (i.e., spatial coefficients, regression coefficients, and residuals variance) for a given spatial regression model of class lm or Sarlm.</i>
-----------------	---

Description

Extracts the numerical values for the regression parameters (i.e., estimated spatial parameters, regression coefficients, and residuals variance) for a given spatial regression model of class `lm` or `Sarlm` as defined in package `spatialreg`. The function can be applied to the output of any SCSR model and contained in the `ClusterFitModels` output of `SCSR_Estim` function.

Usage

```
SpatReg_Extract(SRModel)
```

Arguments

SRModel	Estimated spatial or non-spatial regression model of class <code>lm</code> or <code>Sarlm</code> (see package <code>spatialreg</code> for details.)
---------	---

Value

A named vector containing numerical values for the estimated spatial parameters (e.g., ρ in SAR or λ in SEM), regression coefficients, and residuals variance for the input model in SRModel.

Examples

```
data(Data_RC_PM_RM_JABES2024, package="SCDA")
SCSAR <- SCSR_Estim(Formula = "Gini_S0 ~ GDPPC_PPS2020 + Share_AgroEmp",
                  Data_sf = Data2020, G=3, listW=listW, Type="SCSAR", Phi = 0.50)
SpatReg_Extract(SRModel = SCSAR$ClusterFitModels[[1]])
SpatReg_Extract(SRModel = SCSAR$ClusterFitModels[[2]])
SpatReg_Extract(SRModel = SCSAR$ClusterFitModels[[3]])
```

SpatReg_GoF

Computes a set of goodness-of-fit indices (e.g., likelihood-based information criteria, Wald and LR test, Moran's I statistic) for a given spatial regression model of class lm or Sarlm.

Description

Computes a set of goodness-of-fit indices (e.g., likelihood-based information criteria, Wald and LR test, Moran's I statistic) for a given spatial regression model of class lm or Sarlm as defined in package spatialreg. The function can be applied to the output of any SCSR model and contained in the ClusterFitModels output of SCSR_Estim function.

Usage

```
SpatReg_GoF(SRModel_list, SRModel_W_list)
```

Arguments

- SRModel_list List of estimated spatial or non-spatial regression model of class lm or Sarlm (see package spatialreg for details.)
- SRModel_W_list List of listw objects (see package spdep for details) containing the spatial weights for the spatial autoregressive component for the G groups.

Value

A matrix containing 15 goodness-of-fit indices (e.g., likelihood-based information criteria, Wald and LR test, Moran's I statistic) for the list of models given as a input in SRModel_list.

Examples

```
data(Data_RC_PM_RM_JABES2024, package="SCDA")
SCSAR <- SCSR_Estim(Formula = "Gini_SO ~ GDPPC_PPS2020 + Share_AgroEmp",
                   Data_sf = Data2020, G=3, listW=listW, Type="SCSAR", Phi = 0.50)
reglist <- c(SCSAR$ClusterFitModels[1],SCSAR$ClusterFitModels[2],SCSAR$ClusterFitModels[3])
Wlist <- c(SCSAR$listW_g[1],SCSAR$listW_g[2],SCSAR$listW_g[3])
SpatReg_GoF(SRModel_list = reglist,SRModel_W_list = Wlist)
```

SpatReg_Perf	<i>Computes a set of in-sample performance metrics (i.e., AIC, BIC, RMSE, Sigma, and Pseudo R^2) for a given spatial regression model of class <code>lm</code> or <code>Sarlm</code>.</i>
--------------	--

Description

Computes a set of in-sample performance metrics (i.e., AIC, BIC, RMSE, Sigma, and Pseudo R^2) for a given spatial regression model of class `lm` or `Sarlm` as defined in package `spatialreg`. The function can be applied to the output of any SCSR model and contained in the `ClusterFitModels` output of `SCSR_Estim` function.

Usage

```
SpatReg_Perf(SRModel)
```

Arguments

SRModel	Estimated spatial or non-spatial regression model of class <code>lm</code> or <code>Sarlm</code> (see package <code>spatialreg</code> for details.)
---------	---

Value

A named vector containing numerical values for the estimated performance metrics (i.e., AIC, BIC, RMSE, Sigma, and Pseudo R^2) for the input model in `SRModel`.

Examples

```
data(Data_RC_PM_RM_JABES2024, package="SCDA")
SCSAR <- SCSR_Estim(Formula = "Gini_SO ~ GDPPC_PPS2020 + Share_AgroEmp",
                   Data_sf = Data2020, G=3, listW=listW, Type="SCSAR", Phi = 0.50)
SpatReg_Perf(SRModel = SCSAR$ClusterFitModels[[1]])
SpatReg_Perf(SRModel = SCSAR$ClusterFitModels[[2]])
SpatReg_Perf(SRModel = SCSAR$ClusterFitModels[[3]])
```

SpatReg_PseudoR2	<i>Computes the Pseudo R^2 metric for a given spatial regression model of class <code>lm</code> or <code>Sarlm</code>.</i>
------------------	---

Description

Computes the Pseudo R^2 metric for a given spatial regression model of class `lm` or `Sarlm` as defined in package `spatialreg`. The function can be applied to the output of any SCSR model and contained in the `ClusterFitModels` output of `SCSR_Estim` function.

Usage

```
SpatReg_PseudoR2(SRModel)
```

Arguments

SRModel	Estimated spatial or non-spatial regression model of class <code>lm</code> or <code>Sarlm</code> (see package <code>spatialreg</code> for details.)
---------	---

Value

A numeric value reporting the Pseudo R^2 for the input model in `SRModel`.

Examples

```
data(Data_RC_PM_RM_JABES2024, package="SCDA")
SCSAR <- SCSR_Estim(Formula = "Gini_SO ~ GDPPC_PPS2020 + Share_AgroEmp",
                   Data_sf = Data2020, G=3, listW=listW, Type="SCSAR", Phi = 0.50)
SpatReg_PseudoR2(SRModel = SCSAR$ClusterFitModels[[1]])
SpatReg_PseudoR2(SRModel = SCSAR$ClusterFitModels[[2]])
SpatReg_PseudoR2(SRModel = SCSAR$ClusterFitModels[[3]])
```

Index

* datasets

Data2010, [2](#)

Data2020, [3](#)

listW, [5](#)

Data2010, [2](#)

Data2020, [3](#)

Elbow_finder, [4](#)

listW, [5](#)

SCSR_Estim, [6](#)

SCSR_InfoCrit, [9](#)

SpatReg_Extract, [11](#)

SpatReg_GoF, [12](#)

SpatReg_Perf, [13](#)

SpatReg_PseudoR2, [14](#)