

Package ‘cpp11bigwig’

August 18, 2025

Type Package

Title Read bigWig and bigBed Files

Version 0.1.2

Description Read bigWig and bigBed files using ``libBigWig"
<<https://github.com/dpryan79/libBigWig>>. Provides lightweight access
to the binary bigWig and bigBed formats developed by the UCSC Genome
Browser group.

License MIT + file LICENSE

URL <https://rnabioco.github.io/cpp11bigwig/>,
<https://github.com/rnabioco/cpp11bigwig>

BugReports <https://github.com/rnabioco/cpp11bigwig/issues>

Imports GenomicRanges, IRanges, tibble

Suggests testthat (>= 3.0.0)

LinkingTo cpp11

Config/Needs/website rnabioco/rbitemplate

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation yes

Author Jay Hesselberth [aut, cre],
RNA Bioscience Initiative [fnd, cph],
Devon Ryan [cph]

Maintainer Jay Hesselberth <jay.hesselberth@gmail.com>

Repository CRAN

Date/Publication 2025-08-18 12:20:07 UTC

Contents

read_bigbed	2
read_bigwig	3

Index**4**

read_bigbed	<i>Read data from bigBed files.</i>
-------------	-------------------------------------

Description

Read data from bigBed files.

Usage

```
read_bigbed(bbfile, chrom = NULL, start = NULL, end = NULL, convert = TRUE)
```

Arguments

bbfile	filename for bigBed file
chrom	read data for specific chromosome
start	start position for data
end	end position for data
convert	convert bigBed values to individual columns

Value

tibble

See Also

<https://github.com/dpryan79/libBigWig>

<https://github.com/brentp/bw-python>

Examples

```
bb <- system.file("extdata", "test.bb", package = "cpp11bigwig")  
read_bigbed(bb)  
read_bigbed(bb, chrom = "chr10")
```

read_bigwig	<i>Read data from bigWig files.</i>
-------------	-------------------------------------

Description

Read data from bigWig files.

Usage

```
read_bigwig(bwfile, chrom = NULL, start = NULL, end = NULL, as = NULL)
```

Arguments

bwfile	filename for bigWig file
chrom	read data for specific chromosome
start	start position for data
end	end position for data
as	return data as a specific type. The default is a tibble (tbl) or GRanges (gr)

Value

tibble

See Also

<https://github.com/dpryan79/libBigWig>

<https://github.com/brentp/bw-python>

Examples

```
bw <- system.file("extdata", "test.bw", package = "cpp11bigwig")  
  
read_bigwig(bw)  
  
read_bigwig(bw, chrom = "10")  
  
read_bigwig(bw, chrom = "1", start = 100, end = 130)  
  
read_bigwig(bw, as = "GRanges")
```

Index

`read_bigbed`, [2](#)
`read_bigwig`, [3](#)