

Package ‘NADfinder’

October 17, 2020

Type Package

Title Call wide peaks for sequencing data

Version 1.12.0

Encoding UTF-8

Author Jianhong Ou, Haibo Liu, Jun Yu, Hervé Pagès, Paul Kaufman, Lihua Julie Zhu

Maintainer Jianhong Ou <jianhong.ou@duke.edu>,
Lihua Julie Zhu <julie.zhu@umassmed.edu>

Description Nucleolus is an important structure inside the nucleus in eukaryotic cells. It is the site for transcribing rDNA into rRNA and for assembling ribosomes, aka ribosome biogenesis. In addition, nucleoli are dynamic hubs through which numerous proteins shuttle and contact specific non-rDNA genomic loci. Deep sequencing analyses of DNA associated with isolated nucleoli (NAD-seq) have shown that specific loci, termed nucleolus-associated domains (NADs) form frequent three-dimensional associations with nucleoli. NAD-seq has been used to study the biological functions of NAD and the dynamics of NAD distribution during embryonic stem cell (ESC) differentiation.

Here, we developed a

Bioconductor package NADfinder for bioinformatic analysis of the NAD-seq data, including baseline correction, smoothing, normalization, peak calling, and annotation.

License GPL (≥ 2)

Depends R (≥ 3.4), BiocGenerics, IRanges, GenomicRanges, S4Vectors, SummarizedExperiment

Imports graphics, methods, baseline, signal, GenomicAlignments, GenomeInfoDb, rtracklayer, limma, trackViewer, stats, utils, Rsamtools, metap, EmpiricalBrownsMethod, ATACseqQC, corrplot, csaw

Suggests RUnit, BiocStyle, knitr, BSgenome.Mmusculus.UCSC.mm10, testthat, BiocManager

biocViews Sequencing, DNaseq, GeneRegulation, PeakDetection

LazyData TRUE

VignetteBuilder knitr

RoxygenNote 7.0.2

git_url <https://git.bioconductor.org/packages/NADfinder>

git_branch RELEASE_3_11

git_last_commit c8860cf

git_last_commit_date 2020-04-27

Date/Publication 2020-10-16

R topics documented:

NADfinder-package	2
backgroundCorrection	3
butterFilter	3
callPeaks	4
computeLibSizeChrom	6
cumulativePercentage	6
exportSignals	7
getCorrelations	8
groupZscores	9
IntersectionNotStrict	10
log2se	10
peakdet	11
plotSig	12
single.count	13
smoothRatiosByChromosome	13
tileCount	14
tileCount2	15
transformData	17
trimPeaks	18
triplicate.count	19
zscoreOverBck	20
Index	21

NADfinder-package	<i>Identify nucleolus-associated domains (NADs) from NAD-seq</i>
-------------------	--

Description

Sliding-window based peak calling algorithm using whole genome sequences as control

backgroundCorrection *Correct ratios for background*

Description

Correct ratios of read counts per sliding window for background.

Usage

```
backgroundCorrection(ratios, degree = 3, ...)
```

Arguments

ratios	A vector of numeric. It is log2-transformed ratios, CPMRatios or OddRatios of counts for each window.
degree	Degree of polynomial. default 3.
...	parameters could be passed to baseline.modpolyfit .

Details

This function implements the background correction methods of algorithm for polynomial fitting. See details via [baseline.modpolyfit](#). This function expects the tendency of decreasing of the ratios from 5' end to 3' end.

Value

A vector of numeric. It is the background corrected log2-transformed ratios, CPMRatios or OddRatios.

Examples

```
x <- runif(200)
background <- rep(c(20:1)/100, each=10)
backgroundCorrection(x)
```

butterFilter *Low pass filter on ratios by butterworth filter*

Description

The Butterworth filter is a type of signal processing filter designed to have as flat a frequency response as possible in the passband.

Usage

```
butterFilter(ratios, N = ceiling(length(ratios)/200))
```

Arguments

ratios	A vector of numeric. It is log2-transformed ratios, CPMRatios or OddRatios in each window.
N	numeric(1) or integer(1). Critical frequencies of the low pass filter will be set as 1/N. 1/N is a cutoff at 1/N-th of the Nyquist frequency. By default, it is suppose there are about 200 peaks in the inputs.

Value

A vector of numeric with same length of input ratios. The vector indicates smoothed ratios.

Examples

```
ratios <- runif(20000)
butterFilter(ratios)
```

callPeaks	<i>Call peaks using transformed, background corrected, and smoothed ratios with biological replicates</i>
-----------	---

Description

Use limma to calculate p-values for NADs

Usage

```
callPeaks(
  se,
  backgroundCorrectedAssay = "bcRatio",
  normalization.method = "quantile",
  N = 100,
  cutoffAdjPvalue = 1e-04,
  countFilter = 1000,
  combineP.method = "minimump",
  smooth.method = "loess",
  lfc = log2(1.5),
  ...
)
```

Arguments

se	An object of RangedSummarizedExperiment with assays of raw counts, transformed ratios, background corrected ratios, smoothed ratios and z-scores. It should be an element of output of smoothRatiosByChromosome
backgroundCorrectedAssay	character(1). Assays names for background corrected log2-transformed ratios, CPMRatios or OddRatios.
normalization.method	character(1) specifying the normalization method to be used. Choices are "none", "scale", "quantile" or "cyclicloess". See normalizeBetweenArrays for details.

N	numeric(1) or integer(1). The number of neighboring windows used for loess smoothing or the inverse of the critical frequencies of the low pass filter for butterworth filter. 1/N is a cutoff at 1/N-th of the Nyquist frequency. Default 100.
cutoffAdjPvalue	numeric(1). Cutoff adjust p-value.
countFilter	numeric(1). Cutoff value for mean of raw reads count in each window.
combineP.method	A method used to combine P-values. Default minimump
smooth.method	A method used to smooth the ratios. Choices are "loess", "none" and "butterworthfilter".
lfc	the minimum log2-fold-change that is considered scientifically meaningful
...	Parameter not used.

Details

By default, use the mean smoothed ratio for each peak region to calculate p-values

Value

An object of GRanges of peak list with metadata "AveSig", "P.Value", and "adj.P.Val", where "AveSig" means average signal such as average log2OddsRatio, log2CPMRatio or log2Ratio.

Author(s)

Jianhong Ou, Haibo Liu and Julie Zhu

Examples

```
data(triplicate.count)
se <- triplicate.count
se <- log2se(se, transformation = "log2CPMRatio",
            nucleolusCols = c("N18.subsampled.srt-2.bam",
                              "N18.subsampled.srt-3.bam",
                              "N18.subsampled.srt.bam"),
            genomeCols = c("G18.subsampled.srt-2.bam",
                            "G18.subsampled.srt-3.bam",
                            "G18.subsampled.srt.bam"))
se<- smoothRatiosByChromosome(se, chr="chr18")
#add some variability to the data since the triplicate.count data was created using one sample only
assays(se[[1]])$bcRatio[,2] <- assays(se[[1]])$bcRatio[,2] + 0.3
assays(se[[1]])$bcRatio[,3] <- assays(se[[1]])$bcRatio[,3] - 0.3
peaks <- callPeaks(se[[1]],
                  cutoffAdjPvalue=0.001, countFilter=10)
```

`computeLibSizeChrom` *Perform overlap queries between reads and genome by sliding windows Count reads over sliding windows.*

Description

Perform overlap queries between reads and genome by sliding windows Count reads over sliding windows.

Usage

```
computeLibSizeChrom(aln_list)
```

Arguments

`aln_list` a list.

Value

A [RangedSummarizedExperiment](#) object with chromosome-level depth The assays slot holds the counts, `rowRanges` holds the annotation from the sliding widows of genome. `metadata` contains `lib.size.chrom` for holding chromosome-level sequence depth

Author(s)

Jun Yu, Hervé Pagès and Julie Zhu

`cumulativePercentage` *Plot the cumulative percentage of tag allocation*

Description

Plot the difference between the cumulative percentage of tag allocation in paired samples.

Usage

```
cumulativePercentage(
  se,
  binWidth = 1e+05,
  backgroundCorrectedAssay = "bcRatio",
  ...
)
```

Arguments

`se` An object of [RangedSummarizedExperiment](#) with assays of raw counts, transformed ratios, background correct ratios, smoothed ratios and z-scores. It should be an element of the output of [smoothRatiosByChromosome](#).

`binWidth` `numeric(1)` or `integer(1)`. The width of each bin.

`backgroundCorrectedAssay` `character(1)`. Assays names for background correction ratios.

`...` Parameter not used.

Value

A list of data.frame with the cumulative percentages.

References

Normalization, bias correction, and peak calling for ChIP-seq Aaron Diaz, Kiyoub Park, Daniel A. Lim, Jun S. Song Stat Appl Genet Mol Biol. Author manuscript; available in PMC 2012 May 3. Published in final edited form as: Stat Appl Genet Mol Biol. 2012 Mar 31; 11(3): 10.1515/1544-6115.1750 /j/sagmb.2012.11.issue-3/1544-6115.1750/1544-6115.1750.xml. Published online 2012 Mar 31. doi: 10.1515/1544-6115.1750 PMID: PMC3342857

Examples

```
library(SummarizedExperiment)
data(triplicate.count)
se <- triplicate.count
se <- log2se(se, transformation = "log2CPMRatio",
            nucleolusCols = c("N18.subsampled.srt-2.bam",
                              "N18.subsampled.srt-3.bam",
                              "N18.subsampled.srt.bam"),
            genomeCols = c("G18.subsampled.srt-2.bam",
                           "G18.subsampled.srt-3.bam",
                           "G18.subsampled.srt.bam"))
se <- smoothRatiosByChromosome(se, chr="chr18")
cumulativePercentage(se[["chr18"]])
```

exportSignals

Output signals for visualization

Description

Output signals to bedgraph, bed, wig, etc, for track viewer

Usage

```
exportSignals(dat, assayName, colName, con, format = "bedGraph", ...)
```

Arguments

dat	An object of GRanges , or RangedSummarizedExperiment with assays of raw counts, ratios, background correct ratios, smoothed ratios and z-scores. It should be an element of output of smoothRatiosByChromosome
assayName	character(1). Assay name for RangedSummarizedExperiment
colName	character(1). Column name of metadata of dat or assay of dat for coverage weight, see coverage , RangedSummarizedExperiment .
con	The connection to which data is saved. If this is a character vector, it is assumed to be a filename and a corresponding file connection is created and then closed after exporting the object. If missing, a SimpleRleList will be returned.
format	The format of the output. see export .
...	Parameters to be passed to export

Value

If con is missing, a [SimpleRleList](#) will be returned. Otherwise, nothing is returned.

Examples

```
gr <- GRanges("chr1", IRanges(seq_len(100), 201:300), reads=rep(1, 100))
myTrackLine <- new("TrackLine", name="my track",
  description="description of my track",
  color=col2rgb("red")[, 1],
  visibility="full")
exportSignals(gr, colName="reads",
  con="test.bedGraph", trackLine=myTrackLine)
data(triplicate.count)
exportSignals(triplicate.count, "counts",
  "G18.subsampled.srt.bam", "test.bw", format="bigWig")
```

getCorrelations

Get correlation coefficients and p-values between biological replicates

Description

Get correlations and p-values between biological replicates based on coverage signal for peak regions. The signals will be filtered by the background cutoff value before calculated correlations. This function also output a correlation plots using the [corrplot](#).

Usage

```
getCorrelations(
  se,
  chr = paste0("chr", seq_len(19)),
  ratioAssay = "ratio",
  window = 10000L,
  cutoff = 1,
  method = c("spearman", "pearson", "kendall"),
  file_name = "Correlation plots.pdf",
  ...
)
```

Arguments

se	A RangedSummarizedExperiment object. The output from log2se .
chr	A vector of character. Filter for seqnames. It should be the chromosome names to be kept.
ratioAssay	character(1). Column name of ratio for correlation calculation.
window	numeric(1) or integer(1). The window size for summary of the ratios.
cutoff	numeric(1). All the coverage signals lower than cutoff value in a given window will be filtered out.
method	character(1) indicating which correlation coefficient is to be computed. See cor .
file_name	A file name for output correlation plots
...	Parameters not used.

Value

A list of matrixes of correlation coefficients and p-values.

Author(s)

Jianhong Ou, Haibo Liu

Examples

```
data(triplicate.count)
se <- triplicate.count
se <- log2se(se, transformation = "log2CPMRatio",
            nucleolusCols = c("N18.subsampled.srt-2.bam",
                              "N18.subsampled.srt-3.bam",
                              "N18.subsampled.srt.bam"),
            genomeCols = c("G18.subsampled.srt-2.bam",
                           "G18.subsampled.srt-3.bam",
                           "G18.subsampled.srt.bam"))
getCorrelations(se, chr="chr18")
```

groupZscores

Calculate z-scores for each peak

Description

Detect peaks and calculate z-scores for each peak

Usage

```
groupZscores(zscore)
```

Arguments

zscore A vector of numeric. It is the z-scores of ratios for each window.

Value

A data.frame with column names as "zscore", "group", "grp.zscore", and "pvalue".

Examples

```
x <- seq_len(500)
a <- 2 * 2*pi/length(x)
y <- 20 * sin(x*a)
noise1 <- 20 * 1/10 * sin(x*a*10)
zscore <- y+noise1
groupZscores(zscore)
```

IntersectionNotStrict *Count reads overlapping genomic ranges*

Description

Count reads overlapping a set of genomic features represented as genomic ranges. This function does not work for parallel.

Usage

```
IntersectionNotStrict(
  features,
  reads,
  ignore.strand = TRUE,
  inter.feature = FALSE
)
```

Arguments

features	A object of GRanges representing the feature regions to be counted.
reads	An object that represents the data to be counted. See summarizeOverlaps . If reads are more than 1 bam files, it should be a vector of character with full path, otherwise current working directory is the default directory. For paired end reads,
ignore.strand	logical(1). ignore strand?
inter.feature	not used. This parameter is required by summarizeOverlaps .

Value

return a summarized experiment object with chromosome-level depth information for each input sample as metadata.

log2se *calculate the log2 transformed ratios for SummarizedExperiment class*

Description

Calculate the log2 transformed ratios for nucleolus vs genome. pseudo-count will be used to avoid x/0 or log(0).

Usage

```
log2se(
  se,
  nucleolusCols,
  genomeCols,
  pseudocount = 1L,
  transformation = c("log2OddsRatio", "log2CPMRatio", "log2Ratio"),
  chrom.level.lib = TRUE
)
```

Arguments

`se` A [RangedSummarizedExperiment](#) object. The output of `tileCount`.

`nucleolusCols`, `genomeCols` column Names of counts for nucleolus and genome. They should be the column names in the assays of `se`. Ratios will be calculated as $\log_2(\text{transformed nucleolusCols}/\text{transformed genomeCols})$.

`pseudocount` default to 1, pseudo-count used to avoid $x/0$ or $\log(0)$.

`transformation` transformation type

`chrom.level.lib` indicating whether calculating CPM or odds using sequence depth of the whole genome or the corresponding chromosome

Value

A [RangedSummarizedExperiment](#) object with \log_2 transformed ratios. Assays will be named as `nucleolus`, `genome` and `ratio`.

Author(s)

Jianhong Ou and Julie Zhu

Examples

```
library(SummarizedExperiment)
se <- SummarizedExperiment(assays=list(counts=DataFrame(A=seq_len(3),
  B=rep(1, 3), C=rep(4, 3), D=rep(2, 3))),
  rowRanges=GRanges(c("chr1", "chr1", "chr2"),
    IRanges(c(1, 10, 20),
      width=9)))
metadata(se)$lib.size.chrom <- data.frame(c(1000, 1000), c(2000, 2000), c(200, 200), c(300, 300))
colnames(metadata(se)$lib.size.chrom) <- c("A", "B", "C", "D")
rownames(metadata(se)$lib.size.chrom) <- c("chr1", "chr2")
log2se(se, nucleolusCols = c("A", "C"), genomeCols = c("B", "D"), transformation = "log2Ratio")
log2se(se, nucleolusCols = c("A", "C"), genomeCols = c("B", "D"), transformation = "log2CPMRatio")
log2se(se, nucleolusCols = c("A", "C"), genomeCols = c("B", "D"),
  transformation = "log2OddsRatio")
```

peakdet

Detect peak positions

Description

Detect the peak positions and valley positions leveraging `github::dgromer/peakdet`

Usage

```
peakdet(y, delta = 0, silence = TRUE)
```

Arguments

y	A numeric vector for searching peaks
delta	A numeric vector of length 1, defining the minimum absolute changes required for local maximum or minimum detection when slope sign changes. If it is set to 0, the delta will be set to 1/10 of the range of y.
silence	logical(1). If false, echo the delta value when delta is set as 0.

Value

A list with peakpos and valleypos. Both peakpos and valleypos are numeric vectors storing the positions of peaks or valleys.

Examples

```
y <- runif(200)
peakdet(y)
y <- sin(seq(0,20))
peakdet(y)
```

plotSig

Plot signals with ideograms

Description

Plot signals with ideograms for [GRangesList](#).

Usage

```
plotSig(ideo, grList, mcolName, ...)
```

Arguments

ideo	Output of loadIdeogram .
grList	A GRangesList of data to plot.
mcolName	Column name of metadata of GRangesList for plotting.
...	Parameters to pass to ideogramPlot

Value

Invisible argument list for [ideogramPlot](#).

Examples

```
library(trackViewer)
#ideo <- loadIdeogram("mm10")
ideo <- readRDS(system.file("extdata", "ideo.mm10.rds",
                           package = "NADfinder"))
gr1 <- gr2 <- ideo
mcols(gr1) <- DataFrame(score=runif(length(gr1)))
mcols(gr2) <- DataFrame(score=runif(length(gr2)))
```

```
grList <- GRangesList(gr1, gr2)
plotSig(ideo, grList, mcolName="score", layout=list("chr1"))
```

single.count	<i>Counts data for chromosome 18 for an experiment of a single pair of samples</i>
--------------	--

Description

Counts data for chromosome 18 for an experiment of a single pair of samples

smoothRatiosByChromosome	<i>Background correction and signal smoothing per chromosome</i>
--------------------------	--

Description

Split the ratios by chromosome and do background correction and signal smoothing.

Usage

```
smoothRatiosByChromosome(
  se,
  chr = paste0("chr", c(seq_len(21), "X", "Y")),
  ratioAssay = "ratio",
  backgroundCorrectedAssay = "bcRatio",
  smoothedRatioAssay = "smoothedRatio",
  zscoreAssay = "zscore",
  backgroundPercentage = 0.25,
  chrom.level.background = TRUE,
  ...
)
```

Arguments

se	An object of RangedSummarizedExperiment with log2-transformed ratios, CPM-Ratios or OddRatios. Output of log2se
chr	A character vector, used to filter out seqnames. It should be the chromosome names to be kept.
ratioAssay	The name of assay in se, which store the values (log2-transformed ratios, CPM-Ratios or OddRatios) to be smoothed.
backgroundCorrectedAssay, smoothedRatioAssay, zscoreAssay	character(1). Assays names for background corrected ratios, smoothed ratios and z-scores based on background corrected ratios.
backgroundPercentage	numeric(1). Percentage of values for background, see zscoreOverBck . The percentage of values lower than this threshold will be treated as background, with 25 percentile as default.

```
chrom.level.background
      logical(1): TRUE or FALSE, default to TRUE, use chromosome-level back-
      ground to calculate z-score
...      Parameters could be passed to butterFilter.
```

Value

A [SimpleList](#) of [RangedSummarizedExperiment](#) with smoothed ratios.

Author(s)

Jianhong Ou, Haibo Liu and Julie Zhu

Examples

```
data(single.count)
se <- single.count
dat <- log2se(se, nucleolusCols="N18.subsampled.srt.bam", genomeCols="G18.subsampled.srt.bam",
transformation="log2CPMRatio")
dat1 <- smoothRatiosByChromosome(dat, N=100, chr = c("chr18", "chr19"))
dat2 <- smoothRatiosByChromosome(dat, N=100, chr = c("chr18", "chr19"),
      chrom.level.background = FALSE)
```

tileCount

Perform overlap queries between reads and genome by windows

Description

tileCount extends [summarizeOverlaps](#) by finding coverage for each fixed window in the whole genome

Usage

```
tileCount(
  reads,
  genome,
  excludeChrs = c("chrM", "M", "Mt", "MT"),
  windowSize = 50000,
  step = 10000,
  mode = IntersectionNotStrict,
  dataOverSamples = FALSE,
  ...
)
```

Arguments

reads A [GRanges](#), [GRangesList](#) (should be one read per list element), [GAlignments](#), [GAlignmentsList](#), [GAlignmentPairs](#) or [BamFileList](#) object that represents the data to be counted by [summarizeOverlaps](#). If reads are more than 1 bam files, it should be a vector of character with full path, otherwise current working directory is the default directory.

genome	A BSgenome object from/on which to get/set the sequence and metadata information.
excludeChrs	A vector of string: chromosomes/scaffolds of no interest for NAD analysis. see summarizeOverlaps . default is countByOverlaps, alia of countOverlaps(features, reads, ignore.strand=ignore.strand)
windowSize	numeric(1) or integer(1). Size of the windows.
step	numeric(1) or integer(1). Step of generating silding windows.
mode	One of the pre-defined count methods.
dataOverSamples	logical(1). Data over several samples when use GRangesList as input.
...	Additional arguments passed to summarizeOverlaps .

Value

A [RangedSummarizedExperiment](#) object. The assays slot holds the counts, rowRanges holds the annotation from the sliding widows of genome. metadata contains lib.size.chrom for holding chromosome-level sequence depth

Author(s)

Jianhong Ou, Haibo Liu, Herve Pages and Julie Zhu

Examples

```
if (interactive())
{
  fls <- list.files(system.file("extdata", package="NADfinder"),
    recursive=FALSE, pattern="*bam$", full=TRUE)
  names(fls) <- basename(fls)
  if (!require(BSgenome.Mmusculus.UCSC.mm10))
  {
    if (!requireNamespace("BiocManager", quietly=TRUE))
      install.packages("BiocManager")
    BiocManager::install("BSgenome.Mmusculus.UCSC.mm10")
    library(BSgenome.Mmusculus.UCSC.mm10)
  }
  se <- tileCount(reads = fls,
    genome = Mmusculus,
    excludeChrs = c("chrM", paste0("chr", c(1:17,19)),
      "chrX", "chrY"),
    windowSize=50000, step=10000)
}
```

Description

Perform overlap queries between reads and genome by sliding windows Count reads over sliding windows.

```
if (interactive())
```

```
fls <- list.files(system.file("extdata", package="NADfinder"), recursive=FALSE, pattern="*bam$",
full=TRUE) names(fls) <- basename(fls)
```

```
se <- tileCount2(reads = fls, windowSize=50000, step=10000)
```

Usage

```
tileCount2(
  reads,
  fragment.length = 100,
  windowSize = 50000,
  restrict = paste0("chr", c(1:19, "X", "Y")),
  step = 1000,
  filter = 0,
  pe = "both"
)
```

```
tileCount2(
  reads,
  fragment.length = 100,
  windowSize = 50000,
  restrict = paste0("chr", c(1:19, "X", "Y")),
  step = 1000,
  filter = 0,
  pe = "both"
)
```

Arguments

reads	An object that represents the names and path of the bam files to be counted. If reads are more than 1 bam files, it should be a vector of character with full path. This function now works for paired end reads
fragment.length	integer(1). An integer scalar or a list of two integer scalars/vectors, containing the average length(s) of the sequenced fragments in each library.
windowSize	numeric(1) or integer(1). Size of the windows.
restrict	restrict to a set of chromosomes, default to mouse chromosomes.
step	numeric(1) or integer(1). Step of generating silding windows.
filter	default to 0 without filtering. An integer scalar for the minimum count sum across libraries for each window
pe	a character string indicating whether paired-end data is present; set to "none", "both", "first" or "second"

Value

A [RangedSummarizedExperiment](#) object with chromosome-level depth The assays slot holds the counts, rowRanges holds the annotation from the sliding widows of genome. metadata contains lib.size.chrom for holding chromosome-level sequence depth

Author(s)

Jun Yu, Hervé Pagès and Julie Zhu

Examples

```

if (interactive())
{
  fls <- list.files(system.file("extdata", package="NADfinder"),
    recursive=FALSE, pattern="*bam$", full=TRUE)
  names(fls) <- basename(fls)

  se <- tileCount2(reads = fls,
    windowSize=50000, step=10000)
}

```

transformData

*transform counts to log2 cpm ratios, log2 ratios or log2 odds ratios***Description**

calculate the log2 ratios, log2 cpm (count per million) ratios, or log2 odds ratios for nucleolus vs genome. pseudo-count will be used to avoid x/0 or log(0).

Usage

```

transformData(
  A,
  B,
  seqnames.A,
  seqnames.B,
  pseudo.count = 1L,
  transformation = c("log2OddsRatio", "log2CPMRatio", "log2Ratio"),
  chrom.level.lib = TRUE,
  lib.size.A,
  lib.size.B
)

```

Arguments

A, B window-level counts for nucleolus and genome, extracted from the assays of the output of the tileCounts function

seqnames.A, seqnames.B seqnames, extracted from the rowRanges of the output of the tileCounts function

pseudo.count pseudo-count will be used to avoid x/0 or log0, default to 1.

transformation transformation type

chrom.level.lib indicating whether calculating CPM or odds using sequence depth of the whole genome or the corresponding chromosome

lib.size.A, lib.size.B

library size for A and B. these two dataframes contain chromosome-level sequence depth for the chromosomes, which can be extracted from the metadata of the output of the tileCounts function

Value

a numeric vector of log2 ratios, log2 CPM ratios or log2 odds ratios.

Author(s)

Julie Zhu

Examples

```
transformData(seq_len(10), 10:1, seqnames.A = Rle(c("chr1", "chr2" ) , c(5,5)),
Rle(c("chr1", "chr2" ) , c(5,5)), transformation = "log2OddsRatio",
chrom.level.lib = FALSE, lib.size.A = cbind(c("chr1", "chr2"), c(10000, 12000)),
lib.size.B = cbind(c("chr1", "chr2"), c(10000, 12000)))
transformData(seq_len(10), 10:1, seqnames.A = Rle(c("chr1", "chr2" ) , c(5,5)),
Rle(c("chr1", "chr2" ) , c(5,5)), transformation = "log2CPMRatio",
chrom.level.lib = FALSE, lib.size.A = cbind(c("chr1", "chr2"), c(10000, 12000)),
lib.size.B = cbind(c("chr1", "chr2"), c(10000, 12000)))
transformData(seq_len(10), 10:1, seqnames.A = Rle(c("chr1", "chr2" ) , c(5,5)),
Rle(c("chr1", "chr2" ) , c(5,5)), transformation = "log2CPMRatio",
chrom.level.lib = TRUE, lib.size.A = cbind(c("chr1", "chr2"), c(100, 12000)),
lib.size.B = cbind(c("chr1", "chr2"), c(10000, 200)))
transformData(seq_len(10), 10:1, seqnames.A = Rle(c("chr1", "chr2" ) , c(5,5)),
Rle(c("chr1", "chr2" ) , c(5,5)), transformation = "log2OddsRatio",
chrom.level.lib = TRUE, lib.size.A = cbind(c("chr1", "chr2"), c(100, 12000)),
lib.size.B = cbind(c("chr1", "chr2"), c(10000, 200)))
transformData(seq_len(10), 10:1, transformation = "log2Ratio")
```

trimPeaks

Trim peaks

Description

Filter the peaks by pvalue and trim the range of peaks for an NAD or ChIP-seq experiment without biological replicates.

Usage

```
trimPeaks(
  se,
  cutoffAdjPvalue = 0.05,
  padjust.method = "BH",
  backgroundPercentage = 0.25,
  countFilter = 1000,
  ratioAssay = "ratio",
  backgroundCorrectedAssay = "bcRatio",
  smoothedRatioAssay = "smoothedRatio",
  zscoreAssay = "zscore"
)
```

Arguments

se	An object of RangedSummarizedExperiment with assays of raw counts, ratios, background corrected ratios, smoothed ratios and z-scores. It should be an element of the output of smoothRatiosByChromosome
cutoffAdjPvalue	numeric(1). Cutoff of adjusted p-value.
padjust.method	character(1). The method to use for adjusting p-values, which is passed to p.adjust function
backgroundPercentage	numeric(1). Cutoff value for the peaks height.
countFilter	numeric(1) or integer(1). Cutoff value for mean of raw reads count of the Nucleolar/ChIP samples in each window.
ratioAssay	character(1). The name of assay in se, which store the values to be smoothed.
backgroundCorrectedAssay, smoothedRatioAssay, zscoreAssay	Assays names for background-corrected ratios, smoothed ratios and z-scores based on background corrected ratios.

Value

An object of [GRanges](#).

Examples

```
data(single.count)
se <- single.count
dat <- log2se(se, nucleolusCols="N18.subsampled.srt.bam", genomeCols="G18.subsampled.srt.bam",
transformation="log2CPMRatio")
## Smooth the ratios for each chromosome.
dat <- smoothRatiosByChromosome(dat, N=100, chr=c("chr18", "chr19"))
peaks <- trimPeaks(dat[["chr18"]],
backgroundPercentage=.25,
cutoffAdjPvalue=0.05, countFilter=1000)
```

triplicate.count	<i>Counts data for chromosome 18 for an experiment with triplicates</i>
------------------	---

Description

Counts data for chromosome 18 for an experiment with triplicates

zscoreOverBck	<i>Z-scores over the background</i>
---------------	-------------------------------------

Description

Calculate the z-scores over the background distribution.

Usage

```
zscoreOverBck(ratios, backgroundPercentage = 0.25)
```

Arguments

ratios	A numeric vector containing the transformed, background corrected and smoothed ratios in each window.
backgroundPercentage	numeric(1). Low percentile for background distribution.

Value

A vector of numeric. Z-scores.

Author(s)

Jianhong Ou and Julie Zhu

Examples

```
r <- runif(200)
zscoreOverBck(r)
```

Index

- * **data**
 - single.count, 13
 - triplicate.count, 19
- backgroundCorrection, 3
- BamFileList, 14
- baseline.modpolyfit, 3
- butterFilter, 3, 14
- callPeaks, 4
- computeLibSizeChrom, 6
- cor, 8
- corrplot, 8
- coverage, 7
- cumulativePercentage, 6
- export, 7
- exportSignals, 7
- GAlignmentPairs, 14
- GAlignments, 14
- GAlignmentsList, 14
- getCorrelations, 8
- GRanges, 7, 10, 14, 19
- GRangesList, 12, 14, 15
- groupZscores, 9
- ideogramPlot, 12
- IntersectionNotStrict, 10
- loadIdeogram, 12
- log2se, 8, 10, 13
- NADfinder (NADfinder-package), 2
- NADfinder-package, 2
- normalizeBetweenArrays, 4
- peakdet, 11
- plotSig, 12
- RangedSummarizedExperiment, 4, 6–8, 11, 13–16, 19
- SimpleList, 14
- SimpleRleList, 7, 8
- single.count, 13
- smoothRatiosByChromosome, 4, 6, 7, 13, 19
- summarizeOverlaps, 10, 14, 15
- tileCount, 11, 14
- tileCount2, 15
- transformData, 17
- trimPeaks, 18
- triplicate.count, 19
- zscoreOverBck, 13, 20