

Counting reads with `summarizeOverlaps`

Valerie Obenchain

Edited: April 2016; Compiled: April 27, 2020

Contents

1	Introduction	1
2	A First Example	1
3	Counting Modes	2
4	Counting Features	3
5	<code>pasilla</code> Data	6
	5.1 source files	6
	5.2 counting	7
6	References	8

1 Introduction

This vignette illustrates how reads mapped to a genome can be counted with `summarizeOverlaps`. Different "modes" of counting are provided to resolve reads that overlap multiple features. The built-in count modes are fashioned after the "Union", "IntersectionStrict", and "IntersectionNotEmpty" methods found in the HTSeq package by Simon Anders (see references).

2 A First Example

In this example reads are counted from a list of BAM files and returned in a `matrix` for use in further analysis such as those offered in `DESeq2` and `edgeR`.

```
> library(GenomicAlignments)
> library(DESeq2)
> library(edgeR)
> fls <- list.files(system.file("extdata", package="GenomicAlignments"),
+   recursive=TRUE, pattern="*bam$", full=TRUE)
> features <- GRanges(
```

Counting reads with `summarizeOverlaps`








```
+ seqnames = c(rep("chr2L", 4), rep("chr2R", 5), rep("chr3L", 2)),
+ ranges = IRanges(c(1000, 3000, 4000, 7000, 2000, 3000, 3600, 4000,
+ 7500, 5000, 5400), width=c(rep(500, 3), 600, 900, 500, 300, 900,
+ 300, 500, 500)), "-"),
+ group_id=c(rep("A", 4), rep("B", 5), rep("C", 2)))
> olap <- summarizeOverlaps(features, fls)
> deseq <- DESeqDataSet(olap, design= ~ 1)
> edger <- DGEList(assay(olap), group=rownames(colData(olap)))
```

By default, the `summarizeOverlaps` function iterates through files in 'chunks' and with files processed in parallel. For finer-grain control over memory consumption, use the `BamFileList` function and specify the `yieldSize` argument (e.g., `yieldSize=1000000`) to determine the size of each 'chunk' (smaller chunks consume less memory, but are a little less efficient to process). For controlling the number of processors in use, use `BiocParallel::register` to use an appropriate back-end, e.g., in linux or Mac to process on 6 cores of a single machine use `register(MulticoreParam(workers=6))`; see the [BiocParallel](#) vignette for further details.

3 Counting Modes

The modes of "Union", "IntersectionStrict" and "IntersectionNotEmpty" provide different approaches to resolving reads that overlap multiple features. Figure 1 illustrates how both simple and gapped reads are handled by the modes. Note that a read is counted a maximum of once; there is no double counting. For additional detail on the counting modes see the `summarizeOverlaps` man page.

Counting reads with `summarizeOverlaps`

	Union	IntersectionStrict	IntersectionNotEmpty
	Feature I	Feature I	Feature I
	Feature I	No hit	Feature I
	Feature I	No hit	Feature I
	Feature I	Feature I	Feature I
	Feature I	Feature I	Feature I
	No hit	Feature I	Feature I
	No hit	No hit	No hit

* Picture reproduced from HTSeq web site : <http://www-huber.embl.de/users/anders/HTSeq/doc/count.html>

Figure 1: Counting Modes

4 Counting Features

Features can be exons, transcripts, genes or any region of interest. The number of ranges that define a single feature is specified in the `features` argument.

When annotation regions of interest are defined by a single range a `GRanges` should be used as the `features` argument. With a `GRanges` it is assumed that each row (i.e., each range) represents a distinct feature. If `features` was a `GRanges` of exons, the result would be counts per exon.

Counting reads with `summarizeOverlaps`

When the region of interest is defined by one or more ranges the `features` argument should be a `GRangesList`. In practice this could be a list of exons by gene or transcripts by gene or other similar relationships. The count result will be the same length as the `GRangesList`. For a list of exons by genes, the result would be counts per gene.

The combination of defining the features as either `GRanges` or `GRangesList` and choosing a counting mode controls how `summarizeOverlaps` assigns hits. Regardless of the mode chosen, each read is assigned to at most a single feature. These options are intended to provide flexibility in defining different biological problems.

This next example demonstrates how the same read can be counted differently depending on how the `features` argument is specified. We use a single read that overlaps two ranges, `gr1` and `gr2`.

```
> rd <- GAlignments("a", seqnames = Rle("chr1"), pos = as.integer(100),
+   cigar = "300M", strand = strand("+"))
> gr1 <- GRanges("chr1", IRanges(start=50, width=150), strand="+")
> gr2 <- GRanges("chr1", IRanges(start=350, width=150), strand="+")
```

When provided as a `GRanges` both `gr1` and `gr2` are considered distinct features. In this case none of the modes count the read as a hit. Mode `Union` discards the read because more than 1 feature is overlapped. `IntersectionStrict` requires the read to fall completely within a feature which is not the case for either `gr1` or `gr2`. `IntersectionNotEmpty` requires the read to overlap a single unique disjoint region of the features. In this case `gr1` and `gr2` do not overlap so each range is considered a unique disjoint region. However, the read overlaps both `gr1` and `gr2` so a decision cannot be made and the read is discarded.

```
> gr <- c(gr1, gr2)
> data.frame(union = assay(summarizeOverlaps(gr, rd)),
+   intStrict = assay(summarizeOverlaps(gr, rd,
+   mode="IntersectionStrict")),
+   intNotEmpty = assay(summarizeOverlaps(gr, rd,
+   mode="IntersectionNotEmpty")))
  reads reads.1 reads.2
1     0     0     0
2     0     0     0
```

Next we count with `features` as a `GRangesList`; this is list of length 1 with 2 elements. Modes `Union` and `IntersectionNotEmpty` both count the read for the single feature.

```
> grl <- GRangesList(c(gr1, gr2))
> data.frame(union = assay(summarizeOverlaps(grl, rd)),
+   intStrict = assay(summarizeOverlaps(grl, rd,
+   mode="IntersectionStrict")),
+   intNotEmpty = assay(summarizeOverlaps(grl, rd,
+   mode="IntersectionNotEmpty")))
  reads reads.1 reads.2
1     1     0     1
```

In this more complicated example we have 7 reads, 5 are simple and 2 have gaps in the CIGAR. There are 12 ranges that will serve as the `features`.

Counting reads with `summarizeOverlaps`

```
> group_id <- c("A", "B", "C", "C", "D", "D", "E", "F", "G", "G", "H", "H")
> features <- GRanges(
+   seqnames = Rle(c("chr1", "chr2", "chr1", "chr1", "chr2", "chr2",
+     "chr1", "chr1", "chr2", "chr2", "chr1", "chr1")),
+   strand = strand(rep("+", length(group_id))),
+   ranges = IRanges(
+     start=c(1000, 2000, 3000, 3600, 7000, 7500, 4000, 4000, 3000, 3350, 5000, 5400),
+     width=c(500, 900, 500, 300, 600, 300, 500, 900, 150, 200, 500, 500)),
+   DataFrame(group_id)
+ )
> reads <- GAlignments(
+   names = c("a", "b", "c", "d", "e", "f", "g"),
+   seqnames = Rle(c(rep(c("chr1", "chr2"), 3), "chr1")),
+   pos = as.integer(c(1400, 2700, 3400, 7100, 4000, 3100, 5200)),
+   cigar = c("500M", "100M", "300M", "500M", "300M", "50M200N50M", "50M150N50M"),
+   strand = strand(rep.int("+", 7L))
+ )
>
```

Using a `GRanges` as the `features` all 12 ranges are considered to be different features and counts are produced for each row,

```
> data.frame(union = assay(summarizeOverlaps(features, reads)),
+   intStrict = assay(summarizeOverlaps(features, reads,
+     mode="IntersectionStrict")),
+   intNotEmpty = assay(summarizeOverlaps(features, reads,
+     mode="IntersectionNotEmpty")))
  reads reads.1 reads.2
1     1       0       1
2     1       1       1
3     0       0       0
4     0       0       0
5     0       1       1
6     0       0       0
7     0       0       0
8     0       0       0
9     0       0       0
10    0       0       0
11    0       1       1
12    0       0       0
```

When the data are split by group to create a `GRangesList` the highest list-levels are treated as different features and the multiple list elements are considered part of the same features. Counts are returned for each group.

```
> lst <- split(features, mcols(features)[["group_id"]])
> length(lst)

[1] 8
```

```
> data.frame(union = assay(summarizeOverlaps(lst, reads)),
+   intStrict = assay(summarizeOverlaps(lst, reads,
+     mode="IntersectionStrict")),
```

Counting reads with `summarizeOverlaps`

```
+ intNotEmpty = assay(summarizeOverlaps(lst, reads,
+ mode="IntersectionNotEmpty"))
  reads reads.1 reads.2
A      1      0      1
B      1      1      1
C      1      0      1
D      1      1      1
E      0      0      0
F      0      0      0
G      1      1      1
H      1      1      1
```

If desired, users can supply their own counting function as the `mode` argument and take advantage of the infrastructure for counting over multiple BAM files and parsing the results into a `RangedSummarizedExperiment` object. See `?'BamViews-class'` or `?'BamFile-class'` in the `Rsamtools` package.

5 pasilla Data

In this exercise we count the `pasilla` data by gene and by transcript then create a `DESeqDataSet`. This object can be used in differential expression methods offered in the `DESeq2` package.

5.1 source files

Files are available through NCBI Gene Expression Omnibus (GEO), accession number GSE18508. <http://www.ncbi.nlm.nih.gov/projects/geo/query/acc.cgi?acc=GSE18508>. SAM files can be converted to BAM with the `asBam` function in the `Rsamtools` package. Of the seven files available, 3 are single-reads and 4 are paired-end. Smaller versions of untreated1 (single-end) and untreated2 (paired-end) have been made available in the `pasillaBamSubset` package. This subset includes chromosome 4 only.

`summarizeOverlaps` is capable of counting paired-end reads in both a `BamFile`-method (set argument `singleEnd=TRUE`) or a `GAlignmentPairs`-method. For this example, we use the 3 single-end read files,

- `treated1.bam`
- `untreated1.bam`
- `untreated2.bam`

Annotations are retrieved as a GTF file from the ENSEMBL web site. We download the file our local disk, then use `Rtracklayer`'s `import` function to parse the file to a `GRanges` instance.

```
> library(rtracklayer)
> fl <- paste0("ftp://ftp.ensembl.org/pub/release-62/",
+             "gtf/drosophila_melanogaster/",
+             "Drosophila_melanogaster.BDGP5.25.62.gtf.gz")
> gffFile <- file.path(tempdir(), basename(fl))
```

Counting reads with `summarizeOverlaps`

```
> download.file(fl, gffFile)
> gff0 <- import(gffFile)
```

Subset on the protein-coding, exon regions of chromosome 4 and split by gene id.

```
> idx <- mcols(gff0)$source == "protein_coding" &
+       mcols(gff0)$type == "exon" &
+       seqnames(gff0) == "4"
> gff <- gff0[idx]
> ## adjust seqnames to match Bam files
> seqlevels(gff) <- paste("chr", seqlevels(gff), sep="")
> chr4genes <- split(gff, mcols(gff)$gene_id)
```

5.2 counting

The `param` argument can be used to subset the reads in the bam file on characteristics such as position, unmapped or paired-end reads. Quality scores or the "NH" tag, which identifies reads with multiple mappings, can be included as metadata columns for further subsetting. See `?ScanBamParam` for details about specifying the `param` argument.

```
> param <- ScanBamParam(
+   what='qual',
+   which=GRanges("chr4", IRanges(1, 1e6)),
+   flag=scanBamFlag(isUnmappedQuery=FALSE, isPaired=NA),
+   tag="NH")
```

We use `summarizeOverlaps` to count with the default mode of "Union". If a `param` argument is not included all reads from the BAM file are counted.

```
> fls <- c("treated1.bam", "untreated1.bam", "untreated2.bam")
> path <- "pathToBAMFiles"
> bamlst <- BamFileList(fl)
> genehits <- summarizeOverlaps(chr4genes, bamlst, mode="Union")
```

A `CountDataSet` is constructed from the counts and experiment data in `pasilla`.

```
> expdata <- MIAME(
+   name="pasilla knockdown",
+   lab="Genetics and Developmental Biology, University of
+     Connecticut Health Center",
+   contact="Dr. Brenton Graveley",
+   title="modENCODE Drosophila pasilla RNA Binding Protein RNAi
+     knockdown RNA-Seq Studies",
+   pubMedIds="20921232",
+   url="http://www.ncbi.nlm.nih.gov/projects/geo/query/acc.cgi?acc=GSE18508",
+   abstract="RNA-seq of 3 biological replicates of from the Drosophila
+     melanogaster S2-DRSC cells that have been RNAi depleted of mRNAs
+     encoding pasilla, a mRNA binding protein and 4 biological replicates
+     of the the untreated cell line.")
> design <- data.frame(
```

Counting reads with `summarizeOverlaps`

```
+           condition=c("treated", "untreated", "untreated"),
+           replicate=c(1,1,2),
+           type=rep("single-read", 3),
+           countfiles=path(colData(genehits)[,1]), stringsAsFactors=TRUE)
> geneCDS <- DESeqDataSet(genehits, design=design, metadata=list(expdata=expdata))
```

If the primary interest is to count by transcript instead of by gene, the annotation file can be split on transcript id.

```
> chr4tx <- split(gff, mcols(gff)$transcript_id)
> txhits <- summarizeOverlaps(chr4tx, bamlst)
> txCDS <- DESeqDataSet(txhits, design=design, metadata=list(expdata=expdata))
```

6 References

<http://www-huber.embl.de/users/anders/HTSeq/doc/overview.html> <http://www-huber.embl.de/users/anders/HTSeq/doc/count.html>