

Package ‘BiocFileCache’

October 18, 2022

Title Manage Files Across Sessions

Version 2.4.0

Description This package creates a persistent on-disk cache of files that the user can add, update, and retrieve. It is useful for managing resources (such as custom Txdb objects) that are costly or difficult to create, web resources, and data files used across sessions.

Depends R (>= 3.4.0), dbplyr (>= 1.0.0)

Imports methods, stats, utils, dplyr, RSQLite, DBI, rappdirs, filelock, curl, httr

BugReports <https://github.com/Bioconductor/BiocFileCache/issues>

DevelopmentURL <https://github.com/Bioconductor/BiocFileCache>

License Artistic-2.0

Encoding UTF-8

RoxygenNote 7.1.1

biocViews DataImport

VignetteBuilder knitr

Suggests testthat, knitr, BiocStyle, rmarkdown, rtracklayer

git_url <https://git.bioconductor.org/packages/BiocFileCache>

git_branch RELEASE_3_15

git_last_commit 2c00eee

git_last_commit_date 2022-04-26

Date/Publication 2022-10-18

Author Lori Shepherd [aut, cre],
Martin Morgan [aut]

Maintainer Lori Shepherd <lori.shepherd@roswellpark.org>

R topics documented:

| | |
|--------------------------------|----|
| BFCOption | 2 |
| BiocFileCache-class | 3 |
| makeBiocFileCacheFromDataFrame | 13 |
| makeCachedActiveBinding | 14 |

| | |
|--------------|-----------|
| Index | 16 |
|--------------|-----------|

| | |
|-----------|---|
| BFCOption | <i>BFCOption</i> These functions help get and set an R variable CACHE that controls the default caching location. |
|-----------|---|

Description

BFCOption These functions help get and set an R variable CACHE that controls the default caching location.

Usage

```
setBFCOption(arg, value)
```

Arguments

| | |
|-------|---|
| arg | character(1) option to get or set |
| value | The value to be assigned to the designated option |

Details

Currently the only supported option is CACHE. This controls the default location of the BiocFileCache caching directory. By default the value is established by `tools::R_user_dir("BiocFileCache", which="cache")`. This value can also be defaultly set by using system and global environment variables visible *before* the package is loaded. The variable that should be set if utilized is "BFC_CACHE"

Value

Value of request option or invisible successfully set option

Author(s)

Lori Shepherd

Examples

```
origPath = getBFCOption('CACHE')
setBFCOption('CACHE', "~/myBFC")
```

BiocFileCache-class *BiocFileCache class*

Description

This class represents the location of files stored on disk. Use the return value to add and retrieve files that persist across sessions.

Usage

```
BiocFileCache(cache = getBFCOption("CACHE"), ask = interactive())

## S4 method for signature 'BiocFileCacheBase'
bfccache(x)

## S4 method for signature 'missing'
bfccache(x)

## S4 method for signature 'BiocFileCacheBase'
length(x)

bfccrid(x)

## S4 method for signature 'missing'
bfccrid(x)

## S4 method for signature 'BiocFileCacheReadOnly'
bfccrid(x)

## S4 method for signature 'BiocFileCache'
bfccrid(x)

## S4 method for signature 'BiocFileCache,character,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'BiocFileCacheReadOnly,character,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'BiocFileCache,missing,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'BiocFileCacheReadOnly,missing,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'BiocFileCacheBase,character,missing'
x[[i, j]]
```

```
## S4 replacement method for signature 'BiocFileCache,character,missing,character'  
x[[i, j, ...]] <- value  
  
## S4 method for signature 'missing'  
bfcnew(x, rname, rtype = c("relative", "local"), ext = NA_character_)  
  
## S4 method for signature 'BiocFileCache'  
bfcnew(x, rname, rtype = c("relative", "local"), ext = NA_character_)  
  
## S4 method for signature 'missing'  
bfcadd(  
  x,  
  rname,  
  fpath = rname,  
  rtype = c("auto", "relative", "local", "web"),  
  action = c("copy", "move", "asis"),  
  proxy = "",  
  download = TRUE,  
  config = list(),  
  ext = NA_character_,  
  ...  
)  
  
## S4 method for signature 'BiocFileCache'  
bfcadd(  
  x,  
  rname,  
  fpath = rname,  
  rtype = c("auto", "relative", "local", "web"),  
  action = c("copy", "move", "asis"),  
  proxy = "",  
  download = TRUE,  
  config = list(),  
  ext = NA_character_,  
  ...  
)  
  
## S4 method for signature 'missing'  
bfcinfo(x, rids)  
  
## S4 method for signature 'BiocFileCacheBase'  
bfcinfo(x, rids)  
  
## S4 method for signature 'tbl_bfc'  
bfcrid(x)  
  
## S4 method for signature 'missing'  
bfcpath(x, rids)
```

```
## S4 method for signature 'BiocFileCacheBase'
bfcpath(x, rids)

## S4 method for signature 'missing'
bfcrcpath(x, rnames, ..., rids, exact = TRUE)

## S4 method for signature 'BiocFileCacheBase'
bfcrcpath(x, rnames, ..., rids, exact = TRUE)

## S4 method for signature 'missing'
bfcupdate(x, rids, value, ...)

## S4 method for signature 'BiocFileCache'
bfcupdate(
  x,
  rids,
  rname = NULL,
  rpath = NULL,
  fpath = NULL,
  proxy = "",
  config = list(),
  ask = TRUE,
  ...
)

bfcmeta(x, name, ...) <- value

## S4 replacement method for signature 'BiocFileCacheBase'
bfcmeta(x, name, ...) <- value

## S4 method for signature 'missing'
bfcmetaremove(x, name, ...)

## S4 method for signature 'BiocFileCacheBase'
bfcmetaremove(x, name, ...)

## S4 method for signature 'missing'
bfcmetalist(x)

## S4 method for signature 'BiocFileCacheBase'
bfcmetalist(x)

## S4 method for signature 'missing'
bfcmeta(x, name, ...)

## S4 method for signature 'BiocFileCacheBase'
bfcmeta(x, name, ...)
```

```
## S4 method for signature 'missing'
bfcquerycols(x)

## S4 method for signature 'BiocFileCacheBase'
bfcquerycols(x)

## S4 method for signature 'missing'
bfcquery(x, query, field = c("rname", "rpath", "fpath"), ..., exact = FALSE)

## S4 method for signature 'BiocFileCacheBase'
bfcquery(x, query, field = c("rname", "rpath", "fpath"), ..., exact = FALSE)

## S4 method for signature 'missing'
bfccount(x)

## S4 method for signature 'BiocFileCacheBase'
bfccount(x)

## S4 method for signature 'tbl_bfc'
bfccount(x)

## S4 method for signature 'missing'
bfcneedsupdate(x, rids)

## S4 method for signature 'BiocFileCacheBase'
bfcneedsupdate(x, rids)

## S4 method for signature 'missing'
bfcdownload(x, rid, proxy = "", config = list(), ask = TRUE, FUN, ...)

## S4 method for signature 'BiocFileCache'
bfcdownload(x, rid, proxy = "", config = list(), ask = TRUE, FUN, ...)

## S4 method for signature 'missing'
bfcremove(x, rids)

## S4 method for signature 'BiocFileCache'
bfcremove(x, rids)

## S4 method for signature 'missing'
bfcsync(x, verbose = TRUE, ask = TRUE)

## S4 method for signature 'BiocFileCache'
bfcsync(x, verbose = TRUE, ask = TRUE)

## S4 method for signature 'missing'
exportbfc(
```

```

    x,
    rids,
    outputFile = "BiocFileCacheExport.tar",
    outputMethod = c("tar", "zip"),
    verbose = TRUE,
    ...
)

## S4 method for signature 'BiocFileCacheBase'
exportbfc(
  x,
  rids,
  outputFile = "BiocFileCacheExport.tar",
  outputMethod = c("tar", "zip"),
  verbose = TRUE,
  ...
)

## S4 method for signature 'character'
importbfc(filename, archiveMethod = c("untar", "unzip"), exdir = ".", ...)

## S4 method for signature 'missing'
cleanbfc(x, days = 120, ask = TRUE)

## S4 method for signature 'BiocFileCache'
cleanbfc(x, days = 120, ask = TRUE)

## S4 method for signature 'missing'
removebfc(x, ask = TRUE)

## S4 method for signature 'BiocFileCache'
removebfc(x, ask = TRUE)

## S4 method for signature 'BiocFileCacheBase'
show(object)

```

Arguments

| | |
|-------|---|
| cache | character(1) On-disk location (directory path) of cache. For default location see R_user_dir . |
| ask | logical(1) Ask before creating, updating, overwriting, or removing cache or local file locations. |
| x | A BiocFileCache instance or, if missing, the result of BiocFileCache(). |
| i | character() 'rid' identifiers. |
| j | Ignored. |
| ... | For 'bfcadd', 'bfcupdate' and 'bfcdownload': Additional arguments passed to internal download functions for use with <code>httr::GET</code> . For 'bfcpaths': Addi- |

tional arguments passed to 'bfcadd', or exact passed to 'bfcquery'. For 'bfcquery': Additional arguments passed to grepl. For 'exportbfc': Additional arguments to the selected outputMethod function. See `utils::tar` or `utils::zip` for more information. For 'importbfc': Additional arguments to the selected archiveMethod function. See `utils::untar` or `utils::unzip` for more information.

| | |
|----------|---|
| drop | Ignored. |
| value | character(1) Replacement file path. |
| rname | character(1) Name of object in file cache. For 'bfcupdate' a character vector of replacement rnames. |
| rtype | character(1) 'local', 'relative', or 'web' indicating if the resource is a local file, a relative path in the cache, or a web resource. For <code>bfcnew</code> : local or relative are only options. For <code>bfcadd</code> , the default 'auto' creates relative or web paths, based on the path prefix. |
| ext | character(1) A file extension to add to the local copy of the file (e.g., 'sqlite', 'txt', 'tar.gz'). |
| fpath | For <code>bfcadd()</code> , character(1) path to current file location or remote web resource. If none is given, the rname is assumed to also be the path location. For <code>bfcupdate()</code> character() vector of replacement web resources. |
| action | character(1) How to handle the file: create a copy of fpath in the cache directory; move the file to the cache directory; or asis leave the file in current location but save the path in the cache. If 'rtype == "relative"', action can not be "asis". |
| proxy | character(1) (Optional) proxy server. |
| download | logical(1) If rtype=web, should remote resource be downloaded locally immediately. |
| config | list() passed as config argument in <code>httr::GET</code> |
| rids | character() Vector of rids. |
| rnames | character() to match against rnames. Each element of rnames must match exactly one record. Use <code>exact = FALSE</code> to use regular expression matching. |
| exact | logical(1) when FALSE, treat query as a regular expression. When TRUE, use exact matching. For <code>bfcquery</code> , the default is FALSE (regular expression matching; for <code>bfcrcpath</code> , the default is TRUE (exact matching). |
| rpath | character() vector of replacement rpaths. |
| name | character(1) name of metadata table. |
| query | character() Regular expression pattern(s) to match in resource. It will match the pattern against fields, using & logic across query element. By default, case sensitive. When <code>exact = TRUE</code> , query uses exact matching. |
| field | character() column names in resource to query, using logic across multiple field elements. By default, matches pattern against rname, rpath, and fpath. If exact matching, may only be a single value. |
| rid | character(1) Unique resource id. |

| | |
|---------------|--|
| FUN | A specialized implemented function designed by the user. This function can be used to perform and save the results of a post download processing step rather than direct output. The function should ONLY take in two file names: the first the raw downloaded file and the second the output file for saved results. The output of the function should be TRUE/FALSE if step was successful. See vignette section on Specialty Advance Use Case for more details. |
| verbose | logical(1) If descriptive message and list of issues should be included as output. |
| outputFile | character(1) The <filepath>/basename for the output archive. Please include appropriate extension based on outMethod and any additional parameters selected for <code>utils::tar</code> or <code>utils::zip</code> |
| outputMethod | Either 'tar' or 'zip' for how the directory should be archived. Default is 'tar'. |
| filename | character(1) The name of the archive. |
| archiveMethod | Either 'untar' or 'unzip' for how the directory should be extracted. Default is 'untar'. |
| exdir | Directory to extract files too. See <code>utils::untar</code> or <code>utils::unzip</code> for more details. |
| days | integer(1) Number of days between accessDate and currentDate; if exceeded entry will be deleted. |
| object | A BiocFileCache instance. |

Details

The package defines 'BiocFileCache', 'BiocFileCacheBase' and 'BiocFileCacheReadOnly' classes. Slots unique to 'BiocFileCache' and related classes:

- 'cache': character(1) on-disk location (directory path) of the cache
- 'rid': character() of unique rids in the cache.

The cache creates an RSQLite database to keep track of local and remote resources. Each item located in the database will have the following information:

- 'rid': resource id. Autogenerated. This is a unique identifier automatically generated when a resource is added to the cache
- 'rname': resource name. This is given by the user when a resource is added to the cache. It does not have to be unique and can be updated at anytime. We recommend descriptive key words and identifiers.
- 'create_time': The date and time a resource is added to the cache.
- 'access_time': The date and time a resource is utilized within the cache. The access time is updated when the resource is updated or accessed
- 'rpath': resource path. This is the path to the local (on-disk) file
- 'rtype': resource type. Either "relative", "local", or "web", indicating if the resource has a remote origin
- 'fpath': If rtype is "web", this is the link to the remote resource. It will be utilized to download or update the remote data

- `'last_modified_time'`: For a remote resource, the `last_modified` (if available) information for the local copy of the data. This information is checked against the remote resource to determine if the local copy is stale and needs to be updated

All functions have a quick implementation where if the `BiocFileCache` object is not passed as an argument, the function uses default `'BiocFileCache()'` for implementation. e.g `'bfcinfo()'` can be used instead of `'bfcinfo(BiocFileCache())'`. The only function this is not available for is `'bfcmeta()<-'`; The `BiocFileCache` object must be defined as a variable and passed as an argument. See vignette("BiocFileCache") for more details.

Value

For `'BiocFileCache'`: a `BiocFileCache` instance.

For `'bfccache'`: `character(1)` location of the directory containing the cache.

For `'length'`: `integer(1)` Number of objects in the file cache.

For `'['`: A subset of the `BiocFileCache` object.

For `'[['`: `named character(1)` rpath for the given resource in the cache.

For `'[<-'`: Updated `BiocFileCache`, invisibly.

For `'bfcnew'`: `named character(1)`, the path to save your object / file. The name of the return value is the unique rid for the resource.

For `'bfcadd'`: `named character(1)`, the path to save your object / file. The name of the character is the unique rid for the resource.

For `'bfcinfo'`: A `bfc_tbl` of current resources in the database.

For `'bfcpath'`: the file path location to load

For `'bfc_rpath'`: The local file path location to load.

For `'bfcupdate'`: an updated `BiocFileCache` object, invisibly.

For `'bfcmeta'`: updated `BiocFileCache`, invisibly

For `'bfcmetaremove'`: updated `BiocFileCache`, invisibly

For `'bfcmetalist'`: returns a `character()` of all metadata tables currently in the database. If no metadata tables are available returns `character(0)`

For `'bfcmeta'`: returns a `data.frame` representation of database table

For `'bfcquerycols'`: `character()` all columns in all database tables available for query.

For `'bfcquery'`: A `bfc_tbl` of current resources in the database whose field contained query. If multiple values are given, the resource must contain all of the patterns. A `tbl` with zero rows is returned when no resources match the query.

For `'bfccount'`: `integer(1)` Number of objects in the cache or query.

For `'bfcneedsupdate'`: `named logical vector` if resource needs to be updated. The name is the resource `'rid'`. `TRUE`: `fpath etag` or `modified time` of web resource more recent than in `BiocFileCache`; `FALSE`: `fpath etag` or `modified time` of web resource not more recent than in `BiocFileCache`; `NA`: web resource `etag` and `modified time` could not be determined. If the `etag` is available the function will use that information definitively and only compare `last modified time` if `etag` is not available. If there is an `expires` time that will be used to initially determine if the resource should be updated.

For 'bfcdownload': character(1) path to downloaded resource in cache.

For 'bfcremove': updated BiocFileCache object, invisibly

For 'bfcsync': logical(1) indicating whether the cache is in sync (TRUE) or not. 'verbose' is TRUE by default, so descriptive messages will also be included.

character(1) The outputFile path.

A BiocFileCache object

For 'cleanbfc': updated BiocFileCache, invisibly.

For 'removebfc': TRUE if successfully removed.

Methods (by generic)

- bfccache: Get the location of the on-disk cache.
- length: Get the number of objects in the file cache.
- bfcrid: Get the rids of the object.
- [: Subset a BiocFileCache object.
- [[]: Get a file path for select resources from the cache.
- [[<-: Set the file path of selected resources from the cache.
- bfcnew: Add a resource to the database
- bfcadd: Add an existing resource to the database
- bfcinfo: list resources in database
- bfcrid: Get the rids of the object
- bfcpath: display rpaths of resource.
- bfcrcpath: display rpath of resource. If 'rnames' is in the cache the path is returned, if it is not it will try to add it to the cache with 'bfcadd'
- bfcupdate: Update a resource in the cache
- bfcmeta<-: add meta data table in database
- bfcmetaremove: remove meta data table in database
- bfcmetalist: retrieve listing of metadata tables
- bfcmeta: retrieve metadata table
- bfcquerycols: Get all the possible columns to query
- bfcquery: query resource
- bfccount: Get the number of objects in the file cache or query.
- bfcneedsupdate: check if a resource needs to be updated
- bfcdownload: Redownload resource to location in cache
- bfcremove: Remove a resource to the database. If the local file is located in bfccache(x), the file will also be deleted. This will not delete information in any metadata table.
- bfcsync: sync cache and resource.
- exportbfc: Create exportable file containing BiocFileCache.
- importbfc: Import file created with exportbfc containing BiocFileCache.

- `cleanbfc`: Remove old/unused files in BiocFileCache. If file to be removed is not in the `bfcache` location it will not be deleted. Setting `days=-Inf` will remove all cached files.
- `removebfc`: Completely remove the BiocFileCache
- `show`: Display a BiocFileCache instance.

Examples

```
# bfc <- BiocFileCache()           # global cache
# bfc
bfc0 <- BiocFileCache(tempfile())  # temporary catch for examples
bfccache(bfc0)
length(bfc0)
path <- bfcnew(bfc0, "NewResource")
path
f11 <- tempfile(); file.create(f11)
bfcadd(bfc0, "Test1", f11)          # copy
f12 <- tempfile(); file.create(f12)
bfcadd(bfc0, "Test2", f12, action="move") # move
f13 <- tempfile(); file.create(f13)
add3 <- bfcadd(bfc0, "Test3", f13, rtype="local", action="asis") # reference
rid3 <- names(add3)

bfc0
file.exists(f11)                    # TRUE
file.exists(f12)                    # FALSE
file.exists(f13)                    # TRUE

# add a remote resource
url <- "http://httpbin.org/get"
bfcadd(bfc0, "TestWeb", fpath=url)
bfcinfo(bfc0)
bfcpath(bfc0, rid3)
bfcpath(bfc0, rids = rid3)
bfcupdate(bfc0, rid3, rpath=f13, rname="NewRname")
bfc0[[rid3]] = f11
bfcupdate(bfc0, "BFC5", fpath="http://google.com")
meta = data.frame(list(rid = paste("BFC", seq_len(bfccount(bfc0))), sep=""),
                  num=seq(bfccount(bfc0),1,-1),
                  data=c(paste("Letter",
                                letters[seq_len(bfccount(bfc0))])),
                  stringsAsFactors=FALSE)
bfcmeta(bfc0, name="resourcedata") <- meta
## Not run: bfcmetaremove(bfc0, "resourcedata")
bfcmetalists(bfc0)
tbl = bfcmeta(bfc0, "resourcedata")
tbl
bfcquerycols(bfc0)
bfcquery(bfc0, "Test")
bfcquery(bfc0, "^Test1$", field="rname")
bfccount(bfc0)
bfccount(bfcquery(bfc0, "test"))
bfcneedsupdate(bfc0, "BFC5")
```

```

bfcdownload(bfc0, "BFC5")
bfcremove(bfc0, rid3)
bfcinfo(bfc0)
bfcsync(bfc0)

if (!interactive()){
  # in interactive mode, in the sync above
  # this was probably already removed
  # noninteractive mode does not remove resources
  # so can remove manually here
  bfcremove(bfc0, "BFC1")
}
bfcsync(bfc0, FALSE)
## Not run: exportbfc(bfc)
## Not run: importbfc("ExportBiocFileCache.tar")
## Not run: cleanbfc(bfc, ask=FALSE)
## Not run: removebfc(bfc, ask=FALSE)

```

```
makeBiocFileCacheFromDataFrame
```

Make BiocFileCache objects from an existing data.frame

Description

If there are a lot of resources being added this could take some time but if a cache is saved in a permanent location this should only have to be run once. The original data.frame must have the required columns 'rtype', 'fpath', and 'rpath'; See the vignette for more information on the expected information contained in these columns. Similarly, the optional columns 'rname', 'etag', 'last_modified_time', and 'expires' may be included. Any additional columns not listed as required or optional will be kept as an additional metadata table in the BiocFileCache database.

Usage

```

makeBiocFileCacheFromDataFrame(
  df,
  cache,
  actionLocal = c("move", "copy", "asis"),
  actionWeb = c("move", "copy"),
  metadataName,
  ...,
  ask = TRUE
)

## S4 method for signature 'ANY'
makeBiocFileCacheFromDataFrame(
  df,
  cache,
  actionLocal = c("move", "copy", "asis"),

```

```

  actionWeb = c("move", "copy"),
  metadataName,
  ...,
  ask = TRUE
)

```

Arguments

| | |
|--------------|---|
| df | data.frame or tibble to convert |
| cache | character(1) On-disk location (directory path) of cache. For default location see R_user_dir . |
| actionLocal | If local copy of file should be moved, copied or left in original location. See 'action' param of <code>bfcadd</code> . |
| actionWeb | If a local copy of a remote resource already exists, should the file be copied or moved to the cache. Locally downloaded remote resources must exist in the cache location. |
| metadataName | If there are additional columns of data in the original data.frame besides required BiocFileCache columns, this data will be added as a metadata table with this name. |
| ... | additional arguments passed to 'file.copy()' |
| ask | logical(1) Confirm creation of BiocFileCache. |

Value

A BiocFileCache object

```

makeCachedActiveBinding
      makeCachedActiveBinding

```

Description

Like [makeActiveBinding](#) but the value of the active binding gets only evaluated once and is "remembered".

Usage

```
makeCachedActiveBinding(sym, fun, env = .GlobalEnv, verbose = FALSE)
```

Arguments

| | |
|---------|--|
| sym | See makeActiveBinding in the base package. |
| fun | See makeActiveBinding in the base package. |
| env | See makeActiveBinding in the base package. |
| verbose | Set to TRUE to see caching in action (useful for troubleshooting). |

Examples

```
makeCachedActiveBinding("x", function() runif(1), verbose=TRUE)  
x  
x
```

Index

[,BiocFileCache,character,missing-method (BiocFileCache-class), 3
[,BiocFileCache,missing,missing-method (BiocFileCache-class), 3
[,BiocFileCacheReadOnly,character,missing-method (BiocFileCache-class), 3
[,BiocFileCacheReadOnly,missing,missing-method (BiocFileCache-class), 3
[[,BiocFileCacheBase,character,missing-method (BiocFileCache-class), 3
[[<- ,BiocFileCache,character,missing,character-method (BiocFileCache-class), 3

bfcadd (BiocFileCache-class), 3
bfcadd,BiocFileCache-method (BiocFileCache-class), 3
bfcadd,missing-method (BiocFileCache-class), 3
bfccache (BiocFileCache-class), 3
bfccache,BiocFileCacheBase-method (BiocFileCache-class), 3
bfccache,missing-method (BiocFileCache-class), 3
bfccount (BiocFileCache-class), 3
bfccount,BiocFileCacheBase-method (BiocFileCache-class), 3
bfccount,missing-method (BiocFileCache-class), 3
bfccount,tbl_bfc-method (BiocFileCache-class), 3
bfcdownload (BiocFileCache-class), 3
bfcdownload,BiocFileCache-method (BiocFileCache-class), 3
bfcdownload,missing-method (BiocFileCache-class), 3
bfcinfo (BiocFileCache-class), 3
bfcinfo,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcinfo,missing-method (BiocFileCache-class), 3
bfcmeta (BiocFileCache-class), 3
bfcmeta,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcmeta,missing-method (BiocFileCache-class), 3
bfcmeta<- (BiocFileCache-class), 3
bfcmeta<- ,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcmetalist (BiocFileCache-class), 3
bfcmetalist,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcmetalist,missing-method (BiocFileCache-class), 3
bfcmetaremove (BiocFileCache-class), 3
bfcmetaremove,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcmetaremove,missing-method (BiocFileCache-class), 3
bfcneedsupdate (BiocFileCache-class), 3
bfcneedsupdate,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcneedsupdate,missing-method (BiocFileCache-class), 3
bfcnew (BiocFileCache-class), 3
bfcnew,BiocFileCache-method (BiocFileCache-class), 3
bfcnew,missing-method (BiocFileCache-class), 3
BFCOption, 2
bfcpath (BiocFileCache-class), 3
bfcpath,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcpath,missing-method (BiocFileCache-class), 3
bfcquery (BiocFileCache-class), 3
bfcquery,BiocFileCacheBase-method (BiocFileCache-class), 3
bfcquery,missing-method (BiocFileCache-class), 3

- bfcquerycols (BiocFileCache-class), 3
- bfcquerycols, BiocFileCacheBase-method (BiocFileCache-class), 3
- bfcquerycols, missing-method (BiocFileCache-class), 3
- bfcremove (BiocFileCache-class), 3
- bfcremove, BiocFileCache-method (BiocFileCache-class), 3
- bfcremove, missing-method (BiocFileCache-class), 3
- bfcrid (BiocFileCache-class), 3
- bfcrid, BiocFileCache-method (BiocFileCache-class), 3
- bfcrid, BiocFileCacheReadOnly-method (BiocFileCache-class), 3
- bfcrid, missing-method (BiocFileCache-class), 3
- bfcrid, tbl_bfc-method (BiocFileCache-class), 3
- bfcrcpath (BiocFileCache-class), 3
- bfcrcpath, BiocFileCacheBase-method (BiocFileCache-class), 3
- bfcrcpath, missing-method (BiocFileCache-class), 3
- bfcsync (BiocFileCache-class), 3
- bfcsync, BiocFileCache-method (BiocFileCache-class), 3
- bfcsync, missing-method (BiocFileCache-class), 3
- bfcupdate (BiocFileCache-class), 3
- bfcupdate, BiocFileCache-method (BiocFileCache-class), 3
- bfcupdate, missing-method (BiocFileCache-class), 3
- BiocFileCache (BiocFileCache-class), 3
- BiocFileCache-class, 3

- cleanbfc (BiocFileCache-class), 3
- cleanbfc, BiocFileCache-method (BiocFileCache-class), 3
- cleanbfc, missing-method (BiocFileCache-class), 3

- exportbfc (BiocFileCache-class), 3
- exportbfc, BiocFileCacheBase-method (BiocFileCache-class), 3
- exportbfc, missing-method (BiocFileCache-class), 3

- getBFCOption (BFCOption), 2
- importbfc (BiocFileCache-class), 3
- importbfc, character-method (BiocFileCache-class), 3
- length, BiocFileCacheBase-method (BiocFileCache-class), 3

- makeActiveBinding, 14
- makeBiocFileCacheFromDataFrame, 13
- makeBiocFileCacheFromDataFrame, ANY-method (makeBiocFileCacheFromDataFrame), 13
- makeCachedActiveBinding, 14

- R_user_dir, 7, 14
- removebfc (BiocFileCache-class), 3
- removebfc, BiocFileCache-method (BiocFileCache-class), 3
- removebfc, missing-method (BiocFileCache-class), 3

- setBFCOption (BFCOption), 2
- show, BiocFileCacheBase-method (BiocFileCache-class), 3