

Package ‘NanoStringNCTools’

September 11, 2025

Title NanoString nCounter Tools

Description Tools for NanoString Technologies nCounter Technology. Provides support for reading RCC files into an ExpressionSet derived object. Also includes methods for QC and normalization of NanoString data.

Version 1.17.1

Encoding UTF-8

Depends R (>= 3.6), Biobase, S4Vectors, ggplot2

Imports BiocGenerics, Biostrings, ggbeeswarm, ggiraph, ggthemes, grDevices, IRanges, methods, pheatmap, RColorBrewer, stats, utils

Suggests biovizBase, ggbio, RUnit, rmarkdown, knitr, qpdf

License MIT

Collate SignatureSet-class.R RccMetadata.R NanoStringRccSet-class.R
NanoStringRccSet-validity.R NanoStringRccSet-accessors.R
NanoStringRccSet-signatures.R NanoStringRccSet-subset.R
NanoStringRccSet-utils.R NanoStringRccSet-summary.R
NanoStringRccSet-qc.R NanoStringRccSet-normalize.R
NanoStringRccSet-munge.R NanoStringRccSet-ggplot.R
NanoStringRccSet-autoplot.R readRccFile.R readRlfFile.R
readNanoStringRccSet.R writeNanoStringRccSet.R utils.R

biocViews GeneExpression, Transcription, CellBasedAssays, DataImport, Transcriptomics, Proteomics, mRNAArray, ProprietaryPlatforms, RNASeq

VignetteEngine knitr

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/NanoStringNCTools>

git_branch devel

git_last_commit 6c5e935

git_last_commit_date 2025-07-07

Repository Bioconductor 3.22

Date/Publication 2025-09-10

Author Patrick Aboyoun [aut],
Nicole Ortogero [aut],
Maddy Griswold [cre],
Zhi Yang [ctb]

Maintainer Maddy Griswold <mgriswold@nanosttring.com>

Contents

geom_beeswarm_interactive	2
log2t	3
NanoStringRccSet-autoplot	4
NanoStringRccSet-class	6
normalize	11
readNanoStringRccSet	12
readRccFile	13
readRlffFile	14
setQCFlags	15
SignatureSet-class	16
sThresh	18
writeNanoStringRccSet	20
Index	21

geom_beeswarm_interactive

Geometry for Interactive Bee Swarm Points

Description

The interactive version of [geom_beeswarm](#) from **ggbeeswarm**.

Usage

```
geom_beeswarm_interactive(mapping = NULL, data = NULL,
                           priority = c("ascending", "descending", "density",
                                         "random", "none"),
                           cex = 1, groupOnX = NULL, dodge.width = 0,
                           stat = "identity", na.rm = FALSE, show.legend = NA,
                           inherit.aes = TRUE, ...)
```

Arguments

mapping	The aesthetic mapping. See geom_beeswarm .
data	The data to be displayed at this layer. See geom_beeswarm .
priority	Method used to perform point layout. See geom_beeswarm .
cex	Scaling for adjusting point spacing. See geom_beeswarm .
groupOnX	Indicator for jittering on x-axis. See geom_beeswarm .
dodge.width	Dodge amount for points from different aesthetic groups. See geom_beeswarm .
stat	The statistical transformation to use on the data for this layer. See geom_beeswarm .
na.rm	Indicator for removing missing values with a warning. See geom_beeswarm .
show.legend	Indicator for including this layer in the legend. See geom_beeswarm .
inherit.aes	Indicator for inheriting the aesthetics. See geom_beeswarm .
...	Additional arguments. See geom_beeswarm .

Value

The interactive geometry based on [geom_beeswarm](#).

Author(s)

Patrick Aboyoun

See Also

[geom_beeswarm](#)

Examples

```
# Create NanoStringRccSet from data files
datadir <- system.file("extdata", "3D_Bio_Example_Data",
                      package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
rlf <- file.path(datadir, "3D_SolidTumor_Sig.rlf")
pheno <- file.path(datadir, "3D_SolidTumor_PhenoData.csv")
solidTumor <-
  readNanoStringRccSet(rccs, rlfFile = rlf, phenoDataFile = pheno)

eg_data <- as.data.frame(assayDataElement(solidTumor, "exprs")[1:5, 1])
eg_data[["tooltip"]] <- names(eg_data)
geom_beeswarm_interactive(aes_string(tooltip = "tooltip"), data=eg_data)
```

log2t

Logarithm With Thresholding

Description

Safe log and log2 calculations where values within [0, thresh) are thresholded to thresh prior to the transformation.

Usage

```
logt(x, thresh = 0.5)
log2t(x, thresh = 0.5)
```

Arguments

x	a numeric or complex vector.
thresh	a positive number specifying the threshold.

Details

For non-negative elements in x, calculates $\log(\text{pmax}(x, \text{thresh}))$ or $\log_2(\text{pmax}(x, \text{thresh}))$.

Value

A vector of the same length as x containing the transformed values.

Author(s)

Patrick Aboyoun

See Also

[log](#), [log2](#)

Examples

```
logt(0:8)
identical(logt(0:8), log(c(0.5, 1:8)))

log2t(0:8)
identical(log2t(0:8), log2(c(0.5, 1:8)))
```

NanoStringRccSet-autoplot

Plot NanoStringRccSet Data

Description

Generate common plots to visualize and QC NanoStringRccSet data.

Usage

```
## S3 method for class 'NanoStringRccSet'
autoplot(object,
  type = c("boxplot-feature",
    "boxplot-signature",
    "bindingDensity-mean",
    "bindingDensity-sd",
    "ercc-linearity",
    "ercc-lod",
    "heatmap-genes",
    "heatmap-signatures",
    "housekeep-geom",
    "lane-bindingDensity",
    "lane-fov",
    "mean-sd-features",
    "mean-sd-samples"),
  log2scale = TRUE,
  elt = "exprs",
  index = 1L,
  geomParams = list(),
  tooltipDigits = 4L,
  heatmapGroup = NULL,
  blacklist = NULL,
  tooltipID = NULL,
  qcCutoffs = list(
    Housekeeper = c("failingCutoff" = 32, "passingCutoff" = 100) ,
    Imaging = c("fovCutoff" = 0.75) ,
```

```

BindingDensity = c("minimumBD" = 0.1, "maximumBD" = 2.25,
                    "maximumBDSprint" = 1.8) ,
ERCCLinearity = c("correlationValue" = 0.95) ,
ERCCLoD = c("standardDeviations" = 2) ),
scalingFactor=1L,
show_rownames_gene_limit=60L,
show_colnames_gene_limit=36L,
show_rownames_sig_limit=60L,
show_colnames_sig_limit=36L,
subSet = NULL ,
...)
```

Arguments

object	A NanoStringRccSet object
type	Character string referencing the type of plot to generate
log2scale	An optional boolean indicating expression data is on log2 scale
elt	An optional character string of the expression matrix name
index	An optional integer giving the feature of interest row location
geomParams	An option list of parameters for geometry
tooltipDigits	An optional integer for number of tooltip decimal places to display
heatmapGroup	An optional character string referencing pData column to color samples by in heatmap
blacklist	An optional character vector of features not to plot
tooltipID	An optional character string referencing pData column to use for sample ID in the tooltip
qcCutoffs	An optional list of QC cutoffs
scalingFactor	An optional numeric value indicating a scaling factor to apply to plot drawing
show_rownames_gene_limit	An optional integer limit on number of features to display row-wise
show_colnames_gene_limit	An optional integer limit on number of features to display column-wise
show_rownames_sig_limit	An optional integer limit on number of signatures to display row-wise
show_colnames_sig_limit	An optional integer limit on number of signatures to display column-wise
subSet	An optional subset to plot on
...	Additional arguments to pass on to autoplot function

Details

"boxplot-feature" Generate feature boxplots

"boxplot-signature" Generate signature boxplots

"bindingDensity-mean" Plot binding density displayed as average expression

"bindingDensity-sd" Plot binding density displayed as standard deviation of expression

"ercc-linearity" Assess linearity of ERCCs

"ercc-lod" Assess limit of detection based on ERCC expression

Arguments

assayData	A matrix or environment containing the RCCs.
phenoData	An AnnotatedDataFrame containing the phenotypic data.
featureData	An AnnotatedDataFrame containing columns "CodeClass", "GeneName", "Accession", "IsControl", and "ControlConc".
experimentData	An optional MIAME instance with meta-data about the experiment.
annotation	A character string for the "GeneRLF".
protocolData	An AnnotatedDataFrame containing columns "FileVersion", "SoftwareVersion", "SystemType", "SampleID", "SampleOwner", "SampleComments", "SampleDate", "SystemAPF", "AssayType", "LaneID", "FovCount", "FovCounted", "ScannerID", "StagePosition", "BindingDensity", "CartridgeID", and "CartridgeBarcode".
dimLabels	A character vector of length 2 that provides the column names to use as labels for the features and samples respectively in the autoplot method.
signatures	An optional SignatureSet object containing signature definitions.
design	An optional one-sided formula representing the experimental design based on columns from phenoData
...	Additional arguments for ExpressionSet .

Value

An S4 class containing NanoString Expression Level Assays

Accessing

In addition to the standard [ExpressionSet](#) accessor methods, NanoStringRccSet objects have the following:

sData(object) extracts the data.frame containing the sample data, cbind(pData(object), pData(protocolData(object)))

svarLabels(object) extracts the sample data column names, c(varLabels(object), varLabels(protocolData(object)))

dimLabels(object) extracts the column names to use as labels for the features and samples in the autoplot method.

dimLabels(object) <- value replaces the dimLabels of the object.

signatures(object) extracts the [SignatureSet](#) of the object.

signatures(object) <- value replaces the [SignatureSet](#) of the object.

signatureScores(object, elt = "exprs") extracts the matrix of computed signature scores.

design(object) extracts the one-sided formula representing the experimental design based on columns from [phenoData](#).

design(object) <- value replaces the one-sided formula representing the experimental design based on columns from [phenoData](#).

setSignatureFuncs(object) returns the signature functions.

setSignatureFuncs(object) <- value replaces the signature functions.

setSignatureGroups(object) <- value returns the signature groups.

setSignatureGroups(object) <- value replaces the signature groups.

Summarizing

summary(object, MARGIN = 2L, GROUP = NULL, log2scale = TRUE, elt = "exprs", signatureScores = FALSE)

When signatureScores = FALSE, the marginal summaries of the elt `assayData` matrix along either the feature (MARGIN = 1) or sample (MARGIN = 2) dimension.

When signatureScores = TRUE, the marginal summaries of the elt signatureScores matrix along either the signature (MARGIN = 1) or sample (MARGIN = 2) dimension.

When log2scale = FALSE, the summary statistics are Mean, Standard Deviation, Skewness, Excess Kurtosis, Minimum, First Quartile, Median, Third Quartile, and Maximum.

When log2scale = TRUE, the summary statistics are Geometric Mean with thresholding at 0.5, Size Factor ($2^{(\text{MeanLog2} - \text{mean}(\text{MeanLog2}))}$), Mean of Log2 with thresholding at 0.5, Standard Deviation of Log2 with thresholding at 0.5, Minimum, First Quartile, Median, Third Quartile, and Maximum.

Subsetting

In addition to the standard `ExpressionSet` subsetting methods, NanoStringRccSet objects have the following:

subset(x, subset, select, ...) Subset the feature and sample dimensions using the subset and select arguments respectively. The subset argument will be evaluated with respect to the `featureData`, while the select argument will be evaluated with respect to the `phenoData` and `protocolData`.

endogenousSubset(x, subset, select) Extracts the endogenous barcode class feature subset of x with optional additional subsetting using subset and select.

housekeepingSubset(x, subset, select) Extracts the housekeeping barcode class feature subset of x with optional additional subsetting using subset and select.

negativeControlSubset(x, subset, select) Extracts the negative control barcode class feature subset of x with optional additional subsetting using subset and select.

positiveControlSubset(x, subset, select) Extracts the positive control barcode class feature subset of x with optional additional subsetting using subset and select.

controlSubset(x, subset, select) Extracts the feature subset representing the controls of x with optional additional subsetting using subset and select.

nonControlSubset(x, subset, select) Extracts the feature subset representing the non-controls of x with optional additional subsetting using subset and select.

signatureSubset(x, subset, select) Extracts the feature subset representing the genes in the signatures of x with optional additional subsetting using subset and select.

Looping

assayDataApply(X, MARGIN, FUN, ..., elt = "exprs") Loop over the feature (MARGIN = 1) or sample (MARGIN = 2) dimension of `assayDataElement(X, elt)`.

signatureScoresApply(X, MARGIN, FUN, ..., elt = "exprs") Loop over the signature (MARGIN = 1) or sample (MARGIN = 2) dimension of `signatureScores(X, elt)`.

esBy(X, GROUP, FUN, ..., simplify = TRUE) Split X by GROUP column within `featureData`, `phenoData`, or `protocolData` and apply FUN to each partition.

Transforming

munge(data, mapping = update(design(data), exprs ~ .), extradata = NULL, elt = "exprs", ...)
munge argument data into a data.frame object for modeling and visualization using the mapping argument. Supplemental data can be specified using the extradata argument.

transform(*'_data'*, ...) Similar to the [transform](#) generic in the **base** package, creates or modifies one or more [assayData](#) matrices based upon name = value pairs in The expressions in ... are appended to the preprocessing list in [experimentData](#), which can be extracted using the [preproc](#) method.

Evaluating

with(*data*, *expr*, ...) Evaluate expression *expr* with respect to [assayData](#), [featureData](#), [phenoData](#), and [protocolData](#); `c(as.list(assayData(data)), fData(data), sData(data))`.

Normalizing

normalize(*object*, *type*, *fromElt* = "exprs", *toElt* = "exprs_norm", ...)

Plotting

ggplot(*data*, *mapping* = [aes](#)(), ..., *extradata* = NULL, *tooltip_digits* = 4L, *environment* = [parent.frame](#)())
the NanoStringRccSet method for ggplot.

autoplot(*object*, *type*, *log2scale* = TRUE, *elt* = "exprs", *index* = 1L, *geomParams* = [list](#)(), *tooltipDigits* = 4L, *heats* = ...)

Author(s)

Patrick Aboyoun

See Also

[readNanoStringRccSet](#), [writeNanoStringRccSet](#), [ExpressionSet](#)

Examples

```
# Create NanoStringRccSet from data files
datadir <- system.file("extdata", "3D_Bio_Example_Data",
                      package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
rlf <- file.path(datadir, "3D_SolidTumor_Sig.rlf")
pheno <- file.path(datadir, "3D_SolidTumor_PhenoData.csv")
solidTumor <-
  readNanoStringRccSet(rccs, rlfFile = rlf, phenoDataFile = pheno)
```

```
# Create a deep copy of a NanoStringRccSet object
deepCopy <- NanoStringRccSet(solidTumor)
all.equal(solidTumor, deepCopy)
identical(solidTumor, deepCopy)
```

```
# Accessing sample data and column names
head(sData(solidTumor))
svarLabels(solidTumor)
```

```
# Set experimental design
design(solidTumor) <- ~ BRAFGenotype + Treatment
design(solidTumor)
munge(solidTumor)
```

```

# Marginal summarizing of NanoStringRccSet assayData matrices
head(summary(solidTumor, 1)) # Marginal summaries along features
head(summary(solidTumor, 2)) # Marginal summaries along samples

# Subsetting NanoStringRccSet objects
# Extract the positive controls for wildtype BRAF
dim(solidTumor)
dim(subset(solidTumor, CodeClass == "Positive", BRAFGenotype == "wt/wt"))

# Extract by barcode class
with(solidTumor, table(CodeClass))
with(endogenousSubset(solidTumor), table(CodeClass))
with(housekeepingSubset(solidTumor), table(CodeClass))
with(negativeControlSubset(solidTumor), table(CodeClass))
with(positiveControlSubset(solidTumor), table(CodeClass))
with(controlSubset(solidTumor), table(CodeClass))
with(nonControlSubset(solidTumor), table(CodeClass))

# Looping over NanoStringRccSet assayData matrices
log1pCoefVar <- function(x){
  x <- log1p(x)
  sd(x) / mean(x)
}

# Log1p Coefficient of Variation along Features
head(assayDataApply(solidTumor, 1, log1pCoefVar))

# Log1p Coefficient of Variation along Samples
head(assayDataApply(solidTumor, 2, log1pCoefVar))

# Transforming NanoSetRccSet assayData matrices
# Subtract max count from each sample
# Create log1p transformation of adjusted counts
thresh <- assayDataApply(negativeControlSubset(solidTumor), 2, max)
solidTumor2 <-
  transform(solidTumor,
            negCtrlZeroed = sweep(exprs, 2, thresh),
            log1p_negCtrlZeroed = log1p(pmax(negCtrlZeroed, 0)))
assayDataElementNames(solidTumor2)

# Evaluating expression using NanoStringRccSet data
meanLog1pExprs <-
  with(solidTumor,
    {
      means <- split(apply(exprs, 1, function(x) mean(log1p(x))), CodeClass)
      means <- means[order(sapply(means, median))]
      boxplot(means, horizontal = TRUE)
      means
    })

```

normalize	<i>Normalize RCCSet</i>
-----------	-------------------------

Description

This package performs normalization on NanoStringRccSet data using one of three methods.

Usage

```
normalize(object, ...)
```

Arguments

object	object NanoStringRccSet object
...	object additional arguments to pass on to normalize function

Details

Normalization is performed in one of three ways with data pulled from one slot of assayData and inserted into another. It is possible to overwrite the original slot of assayData if the fromElt and toElt are set to the same slot. nSolver normalization uses positive controls to scale and housekeepers to standardize the data and mimics the normalization performed by default in the nSolver software. The Housekeeping-Log2 normalization calculates the log2 sizeFactor of the housekeeping genes and then takes $2^{\log_2 \text{expression data centered by the log transformed sizeFactor}}$. PositiveControl-Log2Log2 regresses the log2 positive control probes greater than 0.5 concentration on their geometric mean and then uses the intercept and slope to predict normalized values from the log2 transformed expression values. The predictions are then rescaled by $2^{\text{intercept}}$. Additional parameters with NanoStringRccSet method include:

type normalization method to use. Options are nSolver, Housekeeping-Log2, and PositiveControl-Log2Log2

fromElt assayData slot from which to pull raw data

toElt assayData slot to which normalized data will be inserted

Value

The function returns a new NanoStringRccSet with either an additional assayData slot of normalized data, or overwrites the original assayData depending on whether fromElt and toElt are identical.

Author(s)

Patrick Aboyoun

References

NanoString nSolver User Manual https://www.nanostring.com/download_file/view/1168

Examples

```

datadir <- system.file("extdata", "3D_Bio_Example_Data",
                      package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
rlf <- file.path(datadir, "3D_SolidTumor_Sig.rlf")
pheno <- file.path(datadir, "3D_SolidTumor_Phenodata.csv")

solidTumor <-
  readNanoStringRccSet(rccs, rlfFile = rlf, phenoDataFile = pheno)

solidTumor <- normalize(solidTumor, "nSolver" , fromElt = "exprs", toElt = "exprs_norm")
head( assayDataElement( solidTumor , elt = "exprs_norm" ) )

```

readNanoStringRccSet *Read 'NanoStringRccSet'*

Description

Create an instance of class [NanoStringRccSet](#) by reading data from NanoString Reporter Code Count (RCC) files.

Usage

```

readNanoStringRccSet(rccFiles, rlfFile = NULL,
                    phenoDataFile = NULL,
                    phenoDataRccColName = "^RCC",
                    phenoDataColPrefix = "")

```

Arguments

rccFiles	A character vector containing the paths to the RCC files.
rlfFile	An optional character string representing the path to the corresponding RLF file.
phenoDataFile	An optional character string representing the path to the corresponding phenotypic csv data file.
phenoDataRccColName	The regular expression that specifies the RCC column in the phenoDataFile.
phenoDataColPrefix	An optional prefix to add to the phenoData column names to distinguish them from the names of assayData matrices, featureData columns, and protocolData columns.

Value

An instance of the [NanoStringRccSet](#) class.

Author(s)

Patrick Aboyoun

See Also

[NanoStringRccSet](#), [writeNanoStringRccSet](#)

Examples

```
# Data file paths
datadir <- system.file("extdata", "3D_Bio_Example_Data",
                       package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
rlf <- file.path(datadir, "3D_SolidTumor_Sig.rlf")
pheno <- file.path(datadir, "3D_SolidTumor_Phenodata.csv")

# Just RCC data
solidTumorNoRlfPheno <- readNanoStringRccSet(rccs)
varLabels(solidTumorNoRlfPheno)
fvarLabels(solidTumorNoRlfPheno)

# RCC and RLF data
solidTumorNoPheno <- readNanoStringRccSet(rccs, rlfFile = rlf)
setdiff(fvarLabels(solidTumorNoPheno), fvarLabels(solidTumorNoRlfPheno))

# All data
solidTumor <-
  readNanoStringRccSet(rccs, rlfFile = rlf, phenoDataFile = pheno)
varLabels(solidTumor)
design(solidTumor) <- ~ BRAFGenotype + Treatment

# All data with phenoData prefix
solidTumorPhenoPrefix <-
  readNanoStringRccSet(rccs, rlfFile = rlf, phenoDataFile = pheno,
                      phenoDataColPrefix = "PHENO_")
varLabels(solidTumorPhenoPrefix)
design(solidTumorPhenoPrefix) <- ~ PHENO_BRAFGenotype + PHENO_Treatment
```

readRccFile

*Read RCC File***Description**

Read a NanoString Reporter Code Count (RCC) file.

Usage

```
readRccFile(file)
```

Arguments

file A character string containing the path to the RCC file.

Value

An list object with five elements:

"Header" a data.frame object containing the header information.
 "Sample_Attributes" a data.frame object containing the attributes of the sample.
 "Lane_Attributes" a data.frame object containing the attributes of the lane.

"Code_Summary" a data.frame object containing the reporter code counts.
 "Messages" A character vector containing messages, if any.

Author(s)

Patrick Aboyoun

See Also

[readNanoStringRccSet](#)

Examples

```
datadir <- system.file("extdata", "3D_Bio_Example_Data",
                       package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
rccData <- lapply(rccs, readRccFile)
```

readRlfFile

Read RLF File

Description

Read a NanoString Reporter Library File (RLF) file.

Usage

```
readRlfFile(file)
```

Arguments

file A character string containing the path to the RLF file.

Value

An instance of the [DataFrame](#) class containing columns:

"CodeClass"	code class
"GeneName"	gene name
"Accession"	accession number
...	additional columns

Author(s)

Patrick Aboyoun

See Also

[readNanoStringRccSet](#)

Examples

```
datadir <- system.file("extdata", "3D_Bio_Example_Data",
                      package = "NanoStringNCTools")
rlf <- file.path(datadir, "3D_SolidTumor_Sig.rlf")
rlfData <- readRlfFile(rlf)
```

setQCFlags

*Set flags for QC of the assayData in a NanoStringRccSet.***Description**

This function takes a list containing the quality control (QC) thresholds for data in a NanoStringRccSet and then returns a matrix of QC results by sample to protocolData.

Usage

```
setQCFlags(object, ...)
```

Arguments

object	A valid NanoStringRccSet object with all housekeeping genes, positive control probes, and negative control probes present
...	Additional arguments to pass

Details

This function checks that the housekeeping genes, positive control, and negative control probes or genes are within acceptable boundaries. Additional parameters with NanoStringRccSet method include:

qcCutoffs An optional list with members named `Housekeeper`, `Imaging`, `BindingDensity`, `ERCCLinearity`, and `ERCCLoD`

hkGenes An optional vector of housekeeping gene names if alternative genes to those defined in the panel are to be used

ReferenceSampleColumn An optional character string indicating the pData column containing reference sample information

Borderline thresholds and fail thresholds are defined and each sample receives a row in a matrix that contains flags indicating either borderline or failing performance.

`Housekeeper` is a vector with names members. `failingCutoff` sets the lower bound of housekeeper gene expression such that samples with a value below this threshold are labeled as failures. `passingCutoff` sets a lower bound of housekeeper gene expression such that samples with a value below this threshold are labeled as borderline. Values greater than or equal to either threshold are labeled as either borderline or passing. The default values are `failingCutoff = 32` and `passingCutoff = 100`.

`Imaging` is a vector with a single named member `fovCutoff`. This threshold determines the minimum proportion of FOV to be counted. The default value is 0.75.

`BindingDensity` is a named vector with members `minimumBD`, `maximumBD`, and `maximumBDSprint`. `minimumBD` sets a minimum threshold for binding density across machine platforms. `maximumBD` sets a maximum binding density for non-Sprint machines while `maximumBDSprint` does the

same for Sprint machines. The default values are `minimumBD = 0.1`, `maximumBD = 2.25`, and `maximumBDSprint = 1.8`.

`ERCCLinearity` is a named vector with a single member `correlationValue`. This member sets a minimum threshold for the correlation between the observed counts of positive controls and their theoretical concentration. The default value is 0.95.

`ERCCLoD` is a named vector with a single member `standardDeviations`. This sets a minimum threshold for the 0.5uMol concentration to be above the `geoMean` of the negative controls in units of standard deviation of the negative controls. The default value is 2.

Value

This function returns a new `NanoStringRccSet` with matrices of QC pass and QC borderline criteria added to the `protocolData` slots called `QCFlags` and `QCBorderlineFlags`, respectively.

Examples

```
# Create NanoStringRccSet from data files
datadir <- system.file("extdata", "3D_Bio_Example_Data",
                      package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
rlf <- file.path(datadir, "3D_SolidTumor_Sig.rlf")
pheno <- file.path(datadir, "3D_SolidTumor_Phenodata.csv")
solidTumor <-
  readNanoStringRccSet(rccs, rlfFile = rlf, phenoDataFile = pheno)

#Set QC flags with default cutoffs
solidTumorDefaultQC <- setQCFlags(solidTumor)
head( protocolData( solidTumorDefaultQC )["QCFlags"] )
head( protocolData( solidTumorDefaultQC )["QCBorderlineFlags"] )

#Update cutoffs
newQCCutoffs <- list(
  Housekeeper = c("failingCutoff" = 32,"passingCutoff" = 100) ,
  Imaging = c("fovCutoff" = 0.75) ,
  BindingDensity = c("minimumBD" = 0.1, "maximumBD" = 2.25, "maximumBDSprint" = 1.8) ,
  ERCCLinearity = c("correlationValue" = 0.98) ,
  ERCCLoD = c("standardDeviations" = 2)
)

#Set QC flags with new cutoffs
solidTumorNewQC <- setQCFlags(solidTumor, qcCutoffs=newQCCutoffs)

#Compare QC results with default and new cutoffs
head( protocolData( solidTumorDefaultQC )["QCFlags"] )
head( protocolData( solidTumorNewQC )["QCFlags"] )
```

SignatureSet-class	<i>Class to Contain Signature Definitions</i>
--------------------	---

Description

The `SignatureSet` class defines gene-based signatures.

Usage

```
SignatureSet(weights = NumericList(), groups = factor(), func = character(),
             version = character(), ...)
```

Arguments

<code>weights</code>	A named <code>NumericList</code> defining signatures based on linear combinations of genes.
<code>groups</code>	A factor vector indicating groups in the <code>SignatureSet</code>
<code>func</code>	Character indicating function to use
<code>version</code>	Character indicating version to use
<code>...</code>	Additional arguments for future use.

Value

A `SignatureSet` object

Utilities

length(x) returns the number of signatures in x.

lengths(x, use.names = TRUE) returns a named integer vector containing the number of genes in each of the signatures in x.

names(x) returns a character vector containing the signature names in x.

weights(object) returns a named `NumericList` that defines the linear combination based signatures.

weights(object) <- value replaces the `NumericList` that defines the linear combination based signatures.

getSigFuncs(object) returns the signature functions of an object.

groups(object) returns a factor vector representing the signature groups.

groups(object) <- value replaces the factor vector representing the signature groups.

version(object) : returns the signature version.

Author(s)

Patrick Aboyoun

See Also

[NanoStringRccSet](#)

Examples

```
SignatureSet(weights=list(x = c(a = 1),
                          y = c(b = 1/3, d = 2/3),
                          z = c(a = 2, c = 4)),
             groups=factor("x", "y", "z"),
             func = c(x="default", y="default", z="default"))
```

sThresh

Convenience Functions for Assay Data Element Sweep Operations

Description

Convenience functions for matrix thresholding, centering, and scaling based upon margin statistics.

Usage

```
# Loop over features
fThresh(x, STATS)
fCenter(x, STATS)
fScale(x, STATS)

## Round results to integers
fIntThresh(x, STATS)
fIntCenter(x, STATS)
fIntScale(x, STATS)

## Comparisons
fAbove(x, STATS)
fBelow(x, STATS)
fAtLeast(x, STATS)
fAtMost(x, STATS)

# Loop over samples
sThresh(x, STATS)
sCenter(x, STATS)
sScale(x, STATS)

# Round results to integers
sIntThresh(x, STATS)
sIntCenter(x, STATS)
sIntScale(x, STATS)

## Comparisons
sAbove(x, STATS)
sBelow(x, STATS)
sAtLeast(x, STATS)
sAtMost(x, STATS)
```

Arguments

x	a numeric array.
STATS	the summary statistic for thresholding, centering, or scaling.

Details

These functions are convenience wrappers for the following code:

```

fThresh: sweep(x, 1L, STATS, FUN = "pmax")
fCenter: sweep(x, 1L, STATS, FUN = "-")
fScale: sweep(x, 1L, STATS, FUN = "/")
fIntThresh: round(sweep(x, 1L, STATS, FUN = "pmax"))
fIntCenter: round(sweep(x, 1L, STATS, FUN = "-"))
fIntScale: round(sweep(x, 1L, STATS, FUN = "/"))
fAbove: sweep(x, 1L, STATS, FUN = ">")
fBelow: sweep(x, 1L, STATS, FUN = "<")
fAtLeast: sweep(x, 1L, STATS, FUN = ">=")
fAtMost: sweep(x, 1L, STATS, FUN = "<=")
sThresh: sweep(x, 2L, STATS, FUN = "pmax")
sCenter: sweep(x, 2L, STATS, FUN = "-")
sScale: sweep(x, 2L, STATS, FUN = "/")
sIntThresh: round(sweep(x, 2L, STATS, FUN = "pmax"))
sIntCenter: round(sweep(x, 2L, STATS, FUN = "-"))
sIntScale: round(sweep(x, 2L, STATS, FUN = "/"))
sAbove: sweep(x, 2L, STATS, FUN = ">")
sBelow: sweep(x, 2L, STATS, FUN = "<")
sAtLeast: sweep(x, 2L, STATS, FUN = ">=")
sAtMost: sweep(x, 2L, STATS, FUN = "<=")

```

Value

An array with the same shape as x that has been modified by thresholding, centering, or scaling.

Author(s)

Patrick Aboyoun

See Also

[sweep](#)

Examples

```

# Find reasonable column minimums
thresh <- apply(stack.x, 2L, quantile, 0.05)

# Threshold column values
identical(sThresh(stack.x, thresh),
          sweep(stack.x, 2L, thresh, FUN = "pmax"))

# Subtract column values
identical(sCenter(stack.x, thresh),
          sweep(stack.x, 2L, thresh))

# Scale to common mean
identical(sScale(stack.x, colMeans(stack.x) / mean(colMeans(stack.x))),
          sweep(stack.x, 2L, colMeans(stack.x) / mean(colMeans(stack.x))),

```

```

FUN = "/""))

# Scale to common mean, rounded to the nearest integer
sIntScale(stack.x, colMeans(stack.x) / mean(colMeans(stack.x)))

```

writeNanoStringRccSet *Write NanoString Reporter Code Count (RCC) files*

Description

Write NanoString Reporter Code Count (RCC) files from an instance of class [NanoStringRccSet](#).

Usage

```
writeNanoStringRccSet(x, dir = getwd())
```

Arguments

x	an instance of class NanoStringRccSet .
dir	An optional character string representing the path to the directory for the RCC files.

Details

Writes a set of NanoString Reporter Code Count (RCC) files based upon x in dir.

Value

A character vector containing the paths for all the newly created RCC files.

Author(s)

Patrick Aboyoun

See Also

[NanoStringRccSet](#), [readNanoStringRccSet](#)

Examples

```

datadir <- system.file("extdata", "3D_Bio_Example_Data",
                      package = "NanoStringNCTools")
rccs <- dir(datadir, pattern = "SKMEL.*\\.RCC$", full.names = TRUE)
solidTumorNoRlfPheno <- readNanoStringRccSet(rccs)
writeNanoStringRccSet(solidTumorNoRlfPheno, tempdir())
for (i in seq_along(rccs)) {
  stopifnot(identical(readLines(rccs[i]),
                      readLines(file.path(tempdir(), basename(rccs[i])))))
}

```

Index

- * **NanoStringRccSet**
 - readNanoStringRccSet, [12](#)
 - writeNanoStringRccSet, [20](#)
- * **array**
 - sThresh, [18](#)
- * **classes**
 - NanoStringRccSet-class, [6](#)
 - SignatureSet-class, [16](#)
- * **datasets**
 - NanoStringRccSet-autoplot, [4](#)
 - setQCFlags, [15](#)
- * **file**
 - readNanoStringRccSet, [12](#)
 - readRccFile, [13](#)
 - readRlfFile, [14](#)
 - writeNanoStringRccSet, [20](#)
- * **graphics**
 - geom_beeswarm_interactive, [2](#)
- * **iteration**
 - sThresh, [18](#)
- * **manip**
 - readNanoStringRccSet, [12](#)
 - readRccFile, [13](#)
 - readRlfFile, [14](#)
 - writeNanoStringRccSet, [20](#)
- * **math**
 - log2t, [3](#)
- * **methods**
 - NanoStringRccSet-class, [6](#)
 - SignatureSet-class, [16](#)
- * **normalize**
 - normalize, [11](#)
- [, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- AnnotatedDataFrame, [7](#)
- assayData, [8](#), [9](#)
- assayDataApply
 - (NanoStringRccSet-class), [6](#)
- assayDataApply, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- autoplot (NanoStringRccSet-autoplot), [4](#)
- class:NanoStringRccSet
 - (NanoStringRccSet-class), [6](#)
- class:SignatureSet
 - (SignatureSet-class), [16](#)
- coerce, ExpressionSet, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- controlSubset (NanoStringRccSet-class),
 - [6](#)
- controlSubset, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- DataFrame, [14](#)
- design, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- design<-, NanoStringRccSet, ANY-method
 - (NanoStringRccSet-class), [6](#)
- design<-, NanoStringRccSet, formula-method
 - (NanoStringRccSet-class), [6](#)
- design<-, NanoStringRccSet, NULL-method
 - (NanoStringRccSet-class), [6](#)
- dimLabels, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- dimLabels<-, NanoStringRccSet, character-method
 - (NanoStringRccSet-class), [6](#)
- endogenousSubset
 - (NanoStringRccSet-class), [6](#)
- endogenousSubset, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- esBy (NanoStringRccSet-class), [6](#)
- esBy, NanoStringRccSet-method
 - (NanoStringRccSet-class), [6](#)
- experimentData, [9](#)
- ExpressionSet, [6–9](#)
- fAbove (sThresh), [18](#)
- fAtLeast (sThresh), [18](#)
- fAtMost (sThresh), [18](#)
- fBelow (sThresh), [18](#)
- fCenter (sThresh), [18](#)
- featureData, [8](#), [9](#)
- fIntCenter (sThresh), [18](#)
- fIntScale (sThresh), [18](#)
- fIntThresh (sThresh), [18](#)
- fScale (sThresh), [18](#)

- fThresh (sThresh), 18
- geom_beeswarm, 2, 3
- geom_beeswarm_interactive, 2
- getSigFuncs (SignatureSet-class), 16
- getSigFuncs, SignatureSet-method
(SignatureSet-class), 16
- ggplot.NanoStringRccSet
(NanoStringRccSet-class), 6
- groups (SignatureSet-class), 16
- groups, SignatureSet-method
(SignatureSet-class), 16
- groups<- (SignatureSet-class), 16
- groups<-, SignatureSet, ANY-method
(SignatureSet-class), 16
- groups<-, SignatureSet, factor-method
(SignatureSet-class), 16
- groups<-, SignatureSet, NULL-method
(SignatureSet-class), 16
- housekeepingSubset
(NanoStringRccSet-class), 6
- housekeepingSubset, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- length, SignatureSet-method
(SignatureSet-class), 16
- lengths, SignatureSet-method
(SignatureSet-class), 16
- log, 4
- log2, 4
- log2t, 3
- logt (log2t), 3
- MIAME, 7
- munge (NanoStringRccSet-class), 6
- munge, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- names, SignatureSet-method
(SignatureSet-class), 16
- NanoStringRccSet, 12, 16, 17, 20
- NanoStringRccSet
(NanoStringRccSet-class), 6
- NanoStringRccSet, environment-method
(NanoStringRccSet-class), 6
- NanoStringRccSet, ExpressionSet-method
(NanoStringRccSet-class), 6
- NanoStringRccSet, matrix-method
(NanoStringRccSet-class), 6
- NanoStringRccSet, missing-method
(NanoStringRccSet-class), 6
- NanoStringRccSet, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- NanoStringRccSet-autoplot, 4
- NanoStringRccSet-class, 6
- negativeControlSubset
(NanoStringRccSet-class), 6
- negativeControlSubset, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- nonControlSubset
(NanoStringRccSet-class), 6
- nonControlSubset, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- normalize, 11
- normalize, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- NumericList, 17
- phenoData, 7–9
- positiveControlSubset
(NanoStringRccSet-class), 6
- positiveControlSubset, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- preproc, 9
- protocolData, 8, 9
- readNanoStringRccSet, 9, 12, 14, 20
- readRccFile, 13
- readRlffFile, 14
- sAbove (sThresh), 18
- sAtLeast (sThresh), 18
- sAtMost (sThresh), 18
- sBelow (sThresh), 18
- sCenter (sThresh), 18
- sData (NanoStringRccSet-class), 6
- sData, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- setQCFlags, 15
- setQCFlags, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- setSignatureFuncs<-
(NanoStringRccSet-class), 6
- setSignatureFuncs<-, NanoStringRccSet, character-method
(NanoStringRccSet-class), 6
- setSignatureGroups<-
(NanoStringRccSet-class), 6
- setSignatureGroups<-, NanoStringRccSet, character-method
(NanoStringRccSet-class), 6
- setSignatureGroups<-, NanoStringRccSet, factor-method
(NanoStringRccSet-class), 6
- show, NanoStringRccSet-method
(NanoStringRccSet-class), 6
- show, SignatureSet-method
(SignatureSet-class), 16

signatureFuncs
 (NanoStringRccSet-class), 6
 signatureFuncs, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 signatureGroups
 (NanoStringRccSet-class), 6
 signatureGroups, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 signatures (NanoStringRccSet-class), 6
 signatures, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 signatures<- (NanoStringRccSet-class), 6
 signatures<-, NanoStringRccSet, SignatureSet-method
 (NanoStringRccSet-class), 6
 signatureScores
 (NanoStringRccSet-class), 6
 signatureScores, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 signatureScoresApply
 (NanoStringRccSet-class), 6
 signatureScoresApply, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 SignatureSet, 7
 SignatureSet (SignatureSet-class), 16
 SignatureSet-class, 16
 signatureSubset
 (NanoStringRccSet-class), 6
 signatureSubset, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 sIntCenter (sThresh), 18
 sIntScale (sThresh), 18
 sIntThresh (sThresh), 18
 sScale (sThresh), 18
 sThresh, 18
 subset, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 summary, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 svarLabels (NanoStringRccSet-class), 6
 svarLabels, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 sweep, 19

 transform, 9
 transform, NanoStringRccSet-method
 (NanoStringRccSet-class), 6

 update_geom_params
 (NanoStringRccSet-class), 6

 version (SignatureSet-class), 16
 version, SignatureSet-method
 (SignatureSet-class), 16

 version<- (SignatureSet-class), 16
 version<-, SignatureSet, ANY-method
 (SignatureSet-class), 16
 version<-, SignatureSet, character-method
 (SignatureSet-class), 16
 version<-, SignatureSet, NULL-method
 (SignatureSet-class), 16

 weights, SignatureSet-method
 (SignatureSet-class), 16
 weights<- (SignatureSet-class), 16
 weights<-, SignatureSet, ANY-method
 (SignatureSet-class), 16
 weights<-, SignatureSet, CompressedNumericList-method
 (SignatureSet-class), 16
 weights<-, SignatureSet, list-method
 (SignatureSet-class), 16
 weights<-, SignatureSet, NULL-method
 (SignatureSet-class), 16
 weights<-, SignatureSet, NumericList-method
 (SignatureSet-class), 16
 with, NanoStringRccSet-method
 (NanoStringRccSet-class), 6
 writeNanoStringRccSet, 9, 12, 20