

Package ‘Cogito’

September 17, 2025

Type Package

Title Compare genomic intervals tool - Automated, complete, reproducible and clear report about genomic and epigenomic data sets

Version 1.14.0

Date 2022-06-20

Description Biological studies often consist of multiple conditions which are examined with different laboratory set ups like RNA-sequencing or ChIP-sequencing. To get an overview about the whole resulting data set, Cogito provides an automated, complete, reproducible and clear report about all samples and basic comparisons between all different samples. This report can be used as documentation about the data set or as starting point for further custom analysis.

License LGPL-3

Encoding UTF-8

LazyData TRUE

Depends R (>= 4.1), GenomicRanges, jsonlite, GenomicFeatures, entropy

Imports BiocManager, rmarkdown, GenomeInfoDb, S4Vectors, AnnotationDbi, graphics, stats, utils, methods, magrittr, ggplot2, TxDb.Mmusculus.UCSC.mm9.knownGene

biocViews FunctionalGenomics, GeneRegulation, Software, Sequencing

Suggests BiocStyle, knitr, markdown, testthat (>= 3.0.0)

VignetteBuilder knitr

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/Cogito>

git_branch RELEASE_3_21

git_last_commit 4c28c7d

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-09-17

Author Annika Bürger [cre, aut]
Maintainer Annika Bürger <a.buerger@uni-muenster.de>

Contents

aggregateRanges	2
MurEpi.ChIP.small	3
MurEpi.RNA.small	4
MurEpi.RRBS.small	5
summarizeRanges	6
Index	8

aggregateRanges	<i>Aggregate GRanges with columns of attached values to genes</i>
-----------------	---

Description

Aggregates multiple GRanges objects with present columns of attached values (mcols) to genes or ranges of given reference of given organism.

Usage

```
aggregateRanges(ranges, configfile = NULL, organism = NULL,  
                referenceRanges = NULL, name = "", verbose = FALSE)
```

Arguments

ranges	list of GRanges, GRangesList or CompressedGRangesList with names in "RRBS DNA CNV RNA ChIP"
configfile	character, path to configuration file in json format
organism	TxDb or OrganismDb object, default value NULL
referenceRanges	list of GRanges, GRangesList or CompressedGRangesList with length one and name of reference, default value NULL
name	character, default value ""
verbose	logical, default value FALSE

Value

List object with three members: One GRanges object with one gene or range of given reference per line and one column per sample, configuration information, and name.

Author(s)

Annika Bürger

See Also[summarizeRanges](#)**Examples**

```

mm9 <- TxDb.Mmusculus.UCSC.mm9.knownGene::TxDb.Mmusculus.UCSC.mm9.knownGene

### small artificial example ###
ranges.RNA.control <-
  GRanges(seq = "chr10",
    IRanges(c(41023369, 41211825, 41528287, 41994926, 42301673,
      43256520, 43618919, 49503584, 51349066, 52099001),
      c(41023544, 41212385, 41528663, 41995357, 42302290,
      43257075, 43619492, 49504033, 51349425, 52099521)),
    seqinfo = GenomeInfoDb::seqinfo(mm9),
    expr = runif(5, 0, 1))
ranges.RNA.condition <-
  GRanges(seq = "chr10",
    IRanges(c(41013942, 41208731, 41535166, 41999999, 42292275,
      43256194, 43615562, 49497888, 51347046, 52092180),
      c(41014274, 41209664, 41536039, 42000182, 42292965,
      43256430, 43615866, 49498362, 51347969, 52092733)),
    seqinfo = GenomeInfoDb::seqinfo(mm9),
    expr = runif(5, 0, 1))
ranges.ChIP.control <-
  GRanges(seq = "chr10",
    IRanges(c(41022835, 41307587, 42197924, 42302387, 42893825,
      43259749, 43620352, 43721891, 44248812, 45207572,
      49508713, 51309978, 51348779, 52101900, 52265513),
      c(41022954, 41307745, 42198201, 42302555, 42893974,
      43259889, 43620604, 43722051, 44248920, 45207704,
      49508859, 51310187, 51348921, 52102030, 52265689)),
    seqinfo = GenomeInfoDb::seqinfo(mm9),
    score = round(runif(15, 5, 90)))

example.dataset <- list(RNA = GRangesList(control = ranges.RNA.control,
  condition = ranges.RNA.condition),
  ChIP = ranges.ChIP.control)

aggregated.ranges <- aggregateRanges(ranges = example.dataset,
  organism = mm9,
  name = "art.example",
  verbose = TRUE)

names(aggregated.ranges)
head(aggregated.ranges$genes)

```

Description

This murine data from King et al. was downloaded from the NCBI GEO database under accession number GSE77004.

The available ChIP-seq data (GSE77002) was then processed as described in King et al.: After alignment with bowtie with parameters selecting for uniquely mapped, best-matching reads and a maximum of two mismatches per read, the peak calling was done with homer findPeaks algorithm and an input control. Subsequently, the raw peaks were filtered with the following parameters: -F 8 for H3K4me3, -size 1000 -minDist 3000 -F 4 -tagThreshold 32 for H3K27me3, -F 4 for H3K27ac and -size 1000 -minDist1000 -nfr for H3K4me1.

To reduce the storage size and complexity of the murine example data, the data only contains data of chr5 and four sample conditions (3x TFX and 1x mut) were removed.

Usage

```
MurEpi.ChIP.small
```

Format

A GRanges Object containing a lot of Ranges with scores.

Source

NCBI GEO database accession number GSE77002 <https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE77002>

References

King AD, Huang K, Rubbi L, Liu S, Wang CY, Wang Y, Pellegrini M, Fan G. Reversible Regulation of Promoter and Enhancer Histone Landscape by DNA Methylation in Mouse Embryonic Stem Cells. Cell Rep. 2016 Sep 27;17(1):289-302. doi: 10.1016/j.celrep.2016.08.083

MurEpi.RNA.small

Example data set: Murine RNA-seq RPKM values of GSE77004

Description

This murine data from King et al. was downloaded from the NCBI GEO database under accession number GSE77004.

The available RNA-seq RPKM values per gene from the same study, provided under the accession number GSE77003.

To reduce the storage size and complexity of the murine example data, the data only contains data of chr5 and four sample conditions (3x TFX and 1x mut) were removed.

Usage

```
MurEpi.RNA.small
```

Format

A GRanges Object containing a lot of Ranges with expression values scores.

Source

NCBI GEO database accession number GSE77003 <https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE77003>

References

King AD, Huang K, Rubbi L, Liu S, Wang CY, Wang Y, Pellegrini M, Fan G. Reversible Regulation of Promoter and Enhancer Histone Landscape by DNA Methylation in Mouse Embryonic Stem Cells. Cell Rep. 2016 Sep 27;17(1):289-302. doi: 10.1016/j.celrep.2016.08.083

MurEpi.RRBS.small

Example data set: Murine methylation status data set of GSE77004

Description

This murine data from King et al. was downloaded from the NCBI GEO database under accession number GSE77004.

The methylation status, measured by RRBS, was similarly taken from the published files (accession number GSE84103), which contain the fraction of methylated cytosine for every CpG context supported by a minimum of 5 reads.

To reduce the storage size and complexity of the murine example data, the data only contains data of chr5 and four sample conditions (3x TFX and 1x mut) were removed.

Usage

MurEpi.RRBS.small

Format

A GRanges Object containing a lot of Ranges with methylation status.

Source

NCBI GEO database accession number GSE84103 <https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE84103>

References

King AD, Huang K, Rubbi L, Liu S, Wang CY, Wang Y, Pellegrini M, Fan G. Reversible Regulation of Promoter and Enhancer Histone Landscape by DNA Methylation in Mouse Embryonic Stem Cells. Cell Rep. 2016 Sep 27;17(1):289-302. doi: 10.1016/j.celrep.2016.08.083

summarizeRanges	<i>Summarize Aggregated GRanges</i>
-----------------	-------------------------------------

Description

Summarize GRanges with present columns of attached values (mcols).

Usage

```
summarizeRanges(aggregated.ranges, outputFormat = "pdf", verbose = FALSE)
```

Arguments

aggregated.ranges	list of GRanges, configuration information, and name for example result from function Cogito::summarizeRanges
outputFormat	character, can be pdf or html default value pdf
verbose	logical, default value FALSE

Value

No return value, only side effects: creation of a rmd, a pdf or html and a data file (RData).

Author(s)

Annika Bürger

See Also

[aggregateRanges](#)

Examples

```
mm9 <- TxDb.Mmusculus.UCSC.mm9.knownGene::TxDb.Mmusculus.UCSC.mm9.knownGene

### small artificial example ###
ranges.RNA.control <-
  GRanges(seq = "chr10",
    IRanges(c(41023369, 41211825, 41528287, 41994926, 42301673,
      43256520, 43618919, 49503584, 51349066, 52099001),
    c(41023544, 41212385, 41528663, 41995357, 42302290,
      43257075, 43619492, 49504033, 51349425, 52099521)),
    seqinfo = GenomeInfoDb::seqinfo(mm9),
    expr = runif(5, 0, 1))
ranges.RNA.condition <-
  GRanges(seq = "chr10",
    IRanges(c(41013942, 41208731, 41535166, 41999999, 42292275,
      43256194, 43615562, 49497888, 51347046, 52092180),
    c(41014274, 41209664, 41536039, 42000182, 42292965,
```

```

      43256430, 43615866, 49498362, 51347969, 52092733)),
    seqinfo = GenomeInfoDb::seqinfo(mm9),
    expr = runif(5, 0, 1))
ranges.ChIP.control <-
  GRanges(seq = "chr10",
    IRanges(c(41022835, 41307587, 42197924, 42302387, 42893825,
      43259749, 43620352, 43721891, 44248812, 45207572,
      49508713, 51309978, 51348779, 52101900, 52265513),
    c(41022954, 41307745, 42198201, 42302555, 42893974,
      43259889, 43620604, 43722051, 44248920, 45207704,
      49508859, 51310187, 51348921, 52102030, 52265689)),
    seqinfo = GenomeInfoDb::seqinfo(mm9),
    score = round(runif(15, 5, 90)))

example.dataset <- list(RNA = GRangesList(control = ranges.RNA.control,
      condition = ranges.RNA.condition),
    ChIP = ranges.ChIP.control)

aggregated.ranges <- aggregateRanges(ranges = example.dataset,
    organism = mm9,
    name = "art.example",
    verbose = TRUE)

# adding information about conditions
aggregated.ranges$config$conditions <- list(condition = c("RNA.condition.expr"),
    control = c("RNA.control.expr",
      "ChIP.score"))

summarizeRanges(aggregated.ranges = aggregated.ranges,
    outputFormat = "pdf",
    verbose = TRUE)

```

Index

* **datasets**

MurEpi.ChIP.small, [3](#)

MurEpi.RNA.small, [4](#)

MurEpi.RRBS.small, [5](#)

aggregateRanges, [2](#), [6](#)

MurEpi.ChIP.small, [3](#)

MurEpi.RNA.small, [4](#)

MurEpi.RRBS.small, [5](#)

summarizeRanges, [3](#), [6](#)