

Package ‘gdsfmt’

September 17, 2025

Type Package

Title R Interface to CoreArray Genomic Data Structure (GDS) Files

Version 1.44.1

Date 2025-07-04

Depends R (>= 2.15.0), methods

Suggests parallel, digest, Matrix, crayon, RUnit, knitr, markdown,
rmarkdown, BiocGenerics

Author Xiuwen Zheng [aut, cre] (<<https://orcid.org/0000-0002-1390-0708>>),
Stephanie Gogarten [ctb],
Jean-loup Gailly and Mark Adler [ctb] (for the included zlib sources),
Yann Collet [ctb] (for the included LZ4 sources),
xz contributors [ctb] (for the included liblzma sources)

Maintainer Xiuwen Zheng <zhengx@u.washington.edu>

Description Provides a high-level R interface to CoreArray Genomic Data Structure (GDS) data files. GDS is portable across platforms with hierarchical structure to store multiple scalable array-oriented data sets with metadata information. It is suited for large-scale datasets, especially for data which are much larger than the available random-access memory. The gdsfmt package offers the efficient operations specifically designed for integers of less than 8 bits, since a diploid genotype, like single-nucleotide polymorphism (SNP), usually occupies fewer bits than a byte. Data compression and decompression are available with relatively efficient random access. It is also allowed to read a GDS file in parallel with multiple R processes supported by the package parallel.

License LGPL-3

Copyright This package includes the sources of CoreArray C++ library written by Xiuwen Zheng (LGPL-3), zlib written by Jean-loup Gailly and Mark Adler (zlib license), LZ4 written by Yann Collet (simplified BSD), and liblzma written by Lasse Collin and other xz contributors (public domain).

VignetteBuilder knitr

ByteCompile TRUE

BugReports <https://github.com/zhengxwen/gdsfmt/issues>

URL <https://github.com/zhengxwen/gdsfmt>

biocViews Infrastructure, DataImport

git_url <https://git.bioconductor.org/packages/gdsfmt>

git_branch RELEASE_3_21

git_last_commit ba1ba0d

git_last_commit_date 2025-07-05

Repository Bioconductor 3.21

Date/Publication 2025-09-17

Contents

gdsfmt-package	3
add.gdsn	5
addfile.gdsn	9
addfolder.gdsn	11
append.gdsn	13
apply.gdsn	15
assign.gdsn	19
cache.gdsn	21
cleanup.gds	22
closefn.gds	23
clusterApply.gdsn	24
cnt.gdsn	27
compression.gdsn	28
copyto.gdsn	30
createfn.gds	31
delete.attr.gdsn	32
delete.gdsn	33
diagnosis.gds	34
digest.gdsn	36
exist.gdsn	38
gds.class	39
gdsn.class	40
get.attr.gdsn	40
getfile.gdsn	41
getfolder.gdsn	42
index.gdsn	43
is.element.gdsn	45
is.sparse.gdsn	46
lasterr.gds	47
ls.gdsn	47
moveto.gdsn	48
name.gdsn	50
objdesp.gdsn	51

openfn.gds	53
permdim.gdsn	54
print.gds.class	56
put.attr.gdsn	57
read.gdsn	58
readex.gdsn	60
readmode.gdsn	62
rename.gdsn	63
setdim.gdsn	64
showfile.gds	65
summarize.gdsn	66
sync.gds	67
system.gds	69
unload.gdsn	70
write.gdsn	71

Index	73
--------------	-----------

gdsfmt-package	<i>R Interface to CoreArray Genomic Data Structure (GDS) files</i>
----------------	--

Description

This package provides a high-level R interface to CoreArray Genomic Data Structure (GDS) data files, which are portable across platforms and include hierarchical structure to store multiple scalable array-oriented data sets with metadata information. It is suited for large-scale datasets, especially for data which are much larger than the available random-access memory. The gdsfmt package offers the efficient operations specifically designed for integers with less than 8 bits, since a single genetic/genomic variant, such like single-nucleotide polymorphism, usually occupies fewer bits than a byte. It is also allowed to read a GDS file in parallel with multiple R processes supported by the parallel package.

Details

Package: gdsfmt
 Type: R/Bioconductor Package
 License: LGPL version 3

R interface of CoreArray GDS is based on the CoreArray project initiated and developed from 2007 (<http://corearray.sourceforge.net>). The CoreArray project is to develop portable, scalable, bioinformatic data visualization and storage technologies.

R is the most popular statistical environment, but one not necessarily optimized for high performance or parallel computing which ease the burden of large-scale calculations. To support efficient data management in parallel for numerical genomic data, we developed the Genomic Data Structure (GDS) file format. gdsfmt provides fundamental functions to support accessing data in parallel, and allows future R packages to call these functions.

Webpage: <http://corearray.sourceforge.net>, or <https://github.com/zhengxwen/gdsfmt>

Copyright notice: The package includes the sources of CoreArray C++ library written by Xiuwen Zheng (LGPL-3), zlib written by Jean-loup Gailly and Mark Adler (zlib license), and LZ4 written by Yann Collet (simplified BSD).

Author(s)

Xiuwen Zheng <zhengx@u.washington.edu>

References

<http://corearray.sourceforge.net>, <https://github.com/zhengxwen/gdsfmt>

Xiuwen Zheng, David Levine, Jess Shen, Stephanie M. Gogarten, Cathy Laurie, Bruce S. Weir. A High-performance Computing Toolset for Relatedness and Principal Component Analysis of SNP Data. Bioinformatics 2012; doi: 10.1093/bioinformatics/bts606.

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")
L <- -2500:2499

# common types
add.gdsn(f, "label", NULL)
add.gdsn(f, "int", val=1:10000, compress="ZIP", closezip=TRUE)
add.gdsn(f, "int.matrix", val=matrix(L, nrow=100, ncol=50))
add.gdsn(f, "mat", val=matrix(1:(10*6), nrow=10))
add.gdsn(f, "double", val=seq(1, 1000, 0.4))
add.gdsn(f, "character", val=c("int", "double", "logical", "factor"))
add.gdsn(f, "logical", val=rep(c(TRUE, FALSE, NA), 50))
add.gdsn(f, "factor", val=as.factor(c(letters, NA, "AA", "CC")))
add.gdsn(f, "NA", val=rep(NA, 10))
add.gdsn(f, "NaN", val=c(rep(NaN, 20), 1:20))
add.gdsn(f, "bit2-matrix", val=matrix(L[1:5000], nrow=50, ncol=100),
      storage="bit2")
# list and data.frame
add.gdsn(f, "list", val=list(X=1:10, Y=seq(1, 10, 0.25)))
add.gdsn(f, "data.frame", val=data.frame(X=1:19, Y=seq(1, 10, 0.5)))

# save a .RData object
obj <- list(X=1:10, Y=seq(1, 10, 0.1))
save(obj, file="tmp.RData")
addfile.gdsn(f, "tmp.RData", filename="tmp.RData")

f

read.gdsn(index.gdsn(f, "list"))
read.gdsn(index.gdsn(f, "list/Y"))
read.gdsn(index.gdsn(f, "data.frame"))
read.gdsn(index.gdsn(f, "mat"))
```

```
# Apply functions over columns of matrix
tmp <- apply.gdsn(index.gdsn(f, "mat"), margin=2, FUN=function(x) print(x))
tmp <- apply.gdsn(index.gdsn(f, "mat"), margin=2,
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(x) print(x))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

add.gdsn

Add a new GDS node

Description

Add a new GDS node to the GDS file.

Usage

```
add.gdsn(node, name, val=NULL, storage=storage.mode(val), valdim=NULL,
  compress=c("", "ZIP", "ZIP_RA", "LZMA", "LZMA_RA", "LZ4", "LZ4_RA"),
  closezip=FALSE, check=TRUE, replace=FALSE, visible=TRUE, ...)
```

Arguments

node	an object of class <code>gdsn.class</code> or <code>gds.class</code> : " <code>gdsn.class</code> " – the node of hierarchical structure; " <code>gds.class</code> " – the root of hierarchical structure
name	the variable name; if it is not specified, a temporary name is assigned
val	the R value can be integers, real numbers, characters, factor, logical or raw variable, list and data.frame
storage	to specify data type (not case-sensitive), signed integer: " <code>int8</code> ", " <code>int16</code> ", " <code>int24</code> ", " <code>int32</code> ", " <code>int64</code> ", " <code>sbit2</code> ", " <code>sbit3</code> ", ..., " <code>sbit16</code> ", " <code>sbit24</code> ", " <code>sbit32</code> ", " <code>sbit64</code> ", " <code>vl_int</code> " (encoding variable-length signed integer); unsigned integer: " <code>uint8</code> ", " <code>uint16</code> ", " <code>uint24</code> ", " <code>uint32</code> ", " <code>uint64</code> ", " <code>bit1</code> ", " <code>bit2</code> ", " <code>bit3</code> ", ..., " <code>bit15</code> ", " <code>bit16</code> ", " <code>bit24</code> ", " <code>bit32</code> ", " <code>bit64</code> ", " <code>vl_uint</code> " (encoding variable-length unsigned integer); floating-point number (" <code>float32</code> ", " <code>float64</code> "); packed real number (" <code>packedreal8</code> ", " <code>packedreal16</code> ", " <code>packedreal24</code> ", " <code>packedreal32</code> ": pack a floating-point number to a signed 8/16/24/32-bit integer with two attributes " <code>offset</code> " and " <code>scale</code> ", representing " <code>(signed int)*scale + offset</code> ", where the minimum of the signed integer is used to represent NaN; " <code>packedreal8u</code> ", " <code>packedreal16u</code> ", " <code>packedreal24u</code> ", " <code>packedreal32u</code> ": pack a floating-point number to an unsigned 8/16/24/32-bit integer with two attributes " <code>offset</code> " and " <code>scale</code> ", representing " <code>(unsigned int)*scale + offset</code> ", where the maximum of the unsigned integer is used to represent NaN); sparse array (" <code>sp.int</code> " (" <code>sp.int32</code> "), " <code>sp.int8</code> ", " <code>sp.int16</code> ", " <code>sp.int32</code> ", " <code>sp.int64</code> ",

	"sp.uint8", "sp.uint16", "sp.uint32", "sp.uint64", "sp.real"(="sp.real64"), "sp.real32", "sp.real64"); string (variable-length: "string", "string16", "string32"; C [null-terminated] string: "cstring", "cstring16", "cstring32"; fixed-length: "fstring", "fstring16", "fstring32"); Or "char" (="int8"), "int"/"integer" (="int32"), "single" (="float32"), "float" (="float32"), "double" (="float64"), "character" (="string"), "logical", "list", "factor", "folder"; Or a <code>gdsn.class</code> object, the storage mode is set to be the same as the object specified by storage.
valdim	the dimension attribute for the array to be created, which is a vector of length one or more giving the maximal indices in each dimension
compress	the compression method can be "" (no compression), "ZIP", "ZIP.fast", "ZIP.def", "ZIP.max" or "ZIP.none" (original zlib); "ZIP_RA", "ZIP_RA.fast", "ZIP_RA.def", "ZIP_RA.max" or "ZIP_RA.none" (zlib with efficient random access); "LZ4", "LZ4.none", "LZ4.fast", "LZ4.hc" or "LZ4.max" (LZ4 compression/decompression library); "LZ4_RA", "LZ4_RA.none", "LZ4_RA.fast", "LZ4_RA.hc" or "LZ4_RA.max" (with efficient random access); "LZMA", "LZMA.fast", "LZMA.def", "LZMA.max", "LZMA_RA", "LZMA_RA.fast", "LZMA_RA.def", "LZMA_RA.max" (lzma compression/decompression algorithm). See details
closezip	if a compression method is specified, get into read mode after compression
check	if TRUE, a warning will be given when val is character and there are missing values in val. GDS format does not support missing characters NA, and any NA will be converted to a blank string ""
replace	if TRUE, replace the existing variable silently if possible
visible	FALSE – invisible/hidden, except print(, all=TRUE)
...	additional parameters for specific storage, see details

Details

val: if val is list or data.frame, the child node(s) will be added corresponding to objects in list or data.frame. If calling add.gdsn(node, name, val=NULL), then a label will be added which does not have any other data except the name and attributes. If val is raw-type, it is interpreted as 8-bit signed integer.

storage: the default value is storage.mode(val), "int" denotes signed integer, "uint" denotes unsigned integer, 8, 16, 24, 32 and 64 denote the number of bits. "bit1" to "bit32" denote the packed data types for 1 to 32 bits which are packed on disk, and "sbit2" to "sbit32" denote the corresponding signed integers. "float32" denotes single-precision number, and "float64" denotes double-precision number. "string" represents strings of 8-bit characters, "string16" represents strings of 16-bit characters following UTF16 industry standard, and "string32" represents a string of 32-bit characters following UTF32 industry standard. "folder" is to create a folder.

valdim: the values in data are taken to be those in the array with the leftmost subscript moving fastest. The last entry could be ZERO. If the total number of elements is zero, gdsfmt does not allocate storage space. NA is treated as 0.

compress: Z compression algorithm (<http://www.zlib.net>) can be used to deflate the data stored in the GDS file. "ZIP" option is equivalent to "ZIP.def". "ZIP.fast", "ZIP.def" and "ZIP.max" correspond to different compression levels.

To support efficient random access of Z stream, "ZIP_RA", "ZIP_RA.fast", "ZIP_RA.def" or "ZIP_RA.max" should be specified. "ZIP_RA" option is equivalent to "ZIP_RA.def:256K". The block size can be

specified by following colon, and "16K", "32K", "64K", "128K", "256K", "512K", "1M", "2M", "4M" and "8M" are allowed, like "ZIP_RA:64K". The compression algorithm tries to keep each independent compressed data block to be about of the specified block size, like 64K.

LZ4 fast lossless compression algorithm is allowed when compress="LZ4" (<https://github.com/lz4/lz4>). Three compression levels can be specified, "LZ4.fast" (LZ4 fast mode), "LZ4.hc" (LZ4 high compression mode), "LZ4.max" (maximize the compression ratio). The block size can be specified by following colon, and "64K", "256K", "1M" and "4M" are allowed according to LZ4 frame format. "LZ4" is equivalent to "LZ4.hc:256K".

To support efficient random access of LZ4 stream, "LZ4_RA", "LZ4_RA.fast", "LZ4_RA.hc" or "ZIP_RA.max" should be specified. "LZ4_RA" option is equivalent to "LZ4_RA.hc:256K". The block size can be specified by following colon, and "16K", "32K", "64K", "128K", "256K", "512K", "1M", "2M", "4M" and "8M" are allowed, like "LZ4_RA:64K". The compression algorithm tries to keep each independent compressed data block to be about of the specified block size, like 64K.

LZMA compression algorithm (<https://tukaani.org/xz/>) is available since gdsfmt_v1.7.18, which has a higher compression ratio than ZIP algorithm. "LZMA", "LZMA.fast", "LZMA.def" and "LZMA.max" available. To support efficient random access of LZMA stream, "LZMA_RA", "LZMA_RA.fast", "LZMA_RA.def" and "LZMA_RA.max" can be used. The block size can be specified by following colon. "LZMA_RA" is equivalent to "LZMA_RA.def:256K".

To finish compressing, you should call `readmode.gdsn` to close the writing mode.

the parameter details with equivalent command lines can be found at [compression.gdsn](#).

closezip: if compression option is specified, then enter a read mode after deflating the data. see [readmode.gdsn](#).

...: if storage = "fstring", "fstring16" or "fstring32", users can set the max length of string in advance by maxlen=. If storage = "packedreal8", "packedreal8u", "packedreal16", "packedreal16u", "packedreal32" or "packedreal32u", users can define offset and scale to represent real numbers by "val*scale + offset" where "val" is a 8/16/32-bit integer. By default, offset=0, scale=0.01 for "packedreal8" and "packedreal8u", scale=0.0001 for "packedreal16" and "packedreal16u", scale=0.00001 for "packedreal24" and "packedreal24u", scale=0.000001 for "packedreal32" and "packedreal32u". For example, packedreal8:scale=1/127,offset=0, packedreal16:scale=1/32767,offset=0 for correlation [-1, 1]; packedreal8u:scale=1/254,offset=0, packedreal16u:scale=1/65534,offset=0 for a probability [0, 1].

Value

An object of class `gdsn.class` of the new node.

Author(s)

Xiuwen Zheng

References

<http://zlib.net>, <https://github.com/lz4/lz4>, <https://tukaani.org/xz/>

See Also

`addfile.gdsn`, `addfolder.gdsn`, `compression.gdsn`, `index.gdsn`, `read.gdsn`, `readex.gdsn`, `write.gdsn`, `append.gdsn`

Examples

```

# create a GDS file
f <- createfn.gds("test.gds")
L <- -2500:2499

#####
# common types

add.gdsn(f, "label", NULL)
add.gdsn(f, "int", 1:10000, compress="ZIP", closezip=TRUE)
add.gdsn(f, "int.matrix", matrix(L, nrow=100, ncol=50))
add.gdsn(f, "double", seq(1, 1000, 0.4))
add.gdsn(f, "character", c("int", "double", "logical", "factor"))
add.gdsn(f, "logical", rep(c(TRUE, FALSE, NA), 50))
add.gdsn(f, "factor", as.factor(c(letters, NA, "AA", "CC")))
add.gdsn(f, "NA", rep(NA, 10))
add.gdsn(f, "NaN", c(rep(NaN, 20), 1:20))
add.gdsn(f, "bit2-matrix", matrix(L[1:5000], nrow=50, ncol=100),
  storage="bit2")
# list and data.frame
add.gdsn(f, "list", list(X=1:10, Y=seq(1, 10, 0.25)))
add.gdsn(f, "data.frame", data.frame(X=1:19, Y=seq(1, 10, 0.5)))

#####
# save a .RData object

obj <- list(X=1:10, Y=seq(1, 10, 0.1))
save(obj, file="tmp.RData")
addfile.gdsn(f, "tmp.RData", filename="tmp.RData")

f

read.gdsn(index.gdsn(f, "list"))
read.gdsn(index.gdsn(f, "list/Y"))
read.gdsn(index.gdsn(f, "data.frame"))

#####
# allocate the disk spaces

n1 <- add.gdsn(f, "n1", 1:100, valdim=c(10, 20))
read.gdsn(index.gdsn(f, "n1"))

n2 <- add.gdsn(f, "n2", matrix(1:100, 10, 10), valdim=c(15, 20))
read.gdsn(index.gdsn(f, "n2"))

#####
# replace variables

f

```

```

add.gdsn(f, "double", 1:100, storage="float", replace=TRUE)
f
read.gdsn(index.gdsn(f, "double"))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

addfile.gdsn	<i>Add a GDS node with a file</i>
--------------	-----------------------------------

Description

Add a file to a GDS file as a node.

Usage

```

addfile.gdsn(node, name, filename,
  compress=c("ZIP", "ZIP_RA", "LZMA", "LZMA_RA", "LZ4", "LZ4_RA"),
  replace=FALSE, visible=TRUE)

```

Arguments

node	an object of class <code>gdsn.class</code> or <code>gds.class</code>
name	the variable name; if it is not specified, a temporary name is assigned
filename	the file name of input stream.
compress	the compression method can be "" (no compression), "ZIP", "ZIP.fast", "ZIP.default", "ZIP.max" or "ZIP.none" (original zlib); "ZIP_RA", "ZIP_RA.fast", "ZIP_RA.default", "ZIP_RA.max" or "ZIP_RA.none" (zlib with efficient random access); "LZ4", "LZ4.none", "LZ4.fast", "LZ4.hc" or "LZ4.max"; "LZ4_RA", "LZ4_RA.none", "LZ4_RA.fast", "LZ4_RA.hc" or "LZ4_RA.max" (with efficient random access). See details
replace	if TRUE, replace the existing variable silently if possible
visible	FALSE – invisible/hidden, except <code>print()</code> , <code>all=TRUE</code>

Details

compress: Z compression algorithm (<http://www.zlib.net/>) can be used to deflate the data stored in the GDS file. "ZIP" option is equivalent to "ZIP.default". "ZIP.fast", "ZIP.default" and "ZIP.max" correspond to different compression levels.

To support efficient random access of Z stream, "ZIP_RA", "ZIP_RA.fast", "ZIP_RA.default", "ZIP_RA.max" or "ZIP_RA.none" should be specified. "ZIP_RA" option is equivalent to "ZIP_RA.default:256K".

The block size can be specified by following colon, and "16K", "32K", "64K", "128K", "256K", "512K", "1M", "2M", "4M" and "8M" are allowed, like "ZIP_RA:64K". The compression algorithm tries to keep each independent compressed data block to be about of the specified block size, like 64K.

LZ4 fast lossless compression algorithm is allowed when compress="LZ4" (<https://github.com/lz4/lz4>). Three compression levels can be specified, "LZ4.fast" (LZ4 fast mode), "LZ4.hc" (LZ4 high compression mode), "LZ4.max" (maximize the compression ratio). The block size can be specified by following colon, and "64K", "256K", "1M" and "4M" are allowed according to LZ4 frame format. "LZ4" is equivalent to "LZ4.hc:256K".

To support efficient random access of LZ4 stream, "LZ4_RA", "LZ4_RA.fast", "LZ4_RA.hc", "ZIP_RA.max" or "LZ4_RA.none" should be specified. "LZ4_RA" option is equivalent to "LZ4_RA.hc:256K". The block size can be specified by following colon, and "16K", "32K", "64K", "128K", "256K", "512K", "1M", "2M", "4M" and "8M" are allowed, like "LZ4_RA:64K". The compression algorithm tries to keep each independent compressed data block to be about of the specified block size, like 64K.

Value

An object of class `gdsn.class`.

Author(s)

Xiuwen Zheng

See Also

`getfile.gdsn`, `add.gdsn`

Examples

```
# save a .RData object
obj <- list(X=1:10, Y=seq(1, 10, 0.1))
save(obj, file="tmp.RData")

# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "double", val=seq(1, 1000, 0.4))
addfile.gdsn(f, "tmp.RData", "tmp.RData")

# open the GDS file
closefn.gds(f)

# open the existing file
(f <- openfn.gds("test.gds"))

getfile.gdsn(index.gdsn(f, "tmp.RData"), "tmp1.RData")
(obj <- get(load("tmp1.RData")))
```

```
# open the GDS file
closefn.gds(f)

# delete the temporary files
unlink(c("test.gds", "tmp.RData", "tmp1.RData"), force=TRUE)
```

addfolder.gdsn	<i>Add a folder to the GDS node</i>
----------------	-------------------------------------

Description

Add a directory or a virtual folder to the GDS node.

Usage

```
addfolder.gdsn(node, name, type=c("directory", "virtual"), gds.fn="",
  replace=FALSE, visible=TRUE)
```

Arguments

node	an object of class gdsn.class or gds.class
name	the variable name; if it is not specified, a temporary name is assigned
type	"directory" (default) – create a directory of GDS node; "virtual" – create a virtual folder linking another GDS file by mapping all of the content to this virtual folder
gds.fn	the name of another GDS file; it is applicable only if type="virtual"
replace	if TRUE, replace the existing variable silently if possible
visible	FALSE – invisible/hidden, except print(, all=TRUE)

Value

An object of class [gdsn.class](#).

Author(s)

Xiuwen Zheng

See Also

[add.gdsn](#), [addfile.gdsn](#)

Examples

```

# create the first GDS file
f1 <- createfn.gds("test1.gds")

add.gdsn(f1, "NULL")
addfolder.gdsn(f1, "dir")
add.gdsn(f1, "int", 1:100)
f1

# open the GDS file
closefn.gds(f1)

#####

# create the second GDS file
f2 <- createfn.gds("test2.gds")

add.gdsn(f2, "int", 101:200)

# link to the first file
addfolder.gdsn(f2, "virtual_folder", type="virtual", gds.fn="test1.gds")

f2

# open the GDS file
closefn.gds(f2)

#####

# open the second file (writable)
(f <- openfn.gds("test2.gds", FALSE))
# +   [ ]
# |--+ int    { Int32 100, 400 bytes }
# |--+ virtual_folder  [ --> test1.gds ]
# |   |--+ NULL
# |   |--+ dir    [ ]
# |   |--+ int    { Int32 100, 400 bytes }

read.gdsn(index.gdsn(f, "int"))
read.gdsn(index.gdsn(f, "virtual_folder/int"))
add.gdsn(index.gdsn(f, "virtual_folder/dir"), "nm", 1:10)

f

# open the GDS file
closefn.gds(f)

#####
# open 'test1.gds', there is a new variable "dir/nm"

```

```

(f <- openfn.gds("test1.gds"))
closefn.gds(f)

#####
# remove 'test1.gds'

file.remove("test1.gds")

## Not run:
(f <- openfn.gds("test2.gds"))
# +      [ ]
# |--+ int    { Int32 100, 400 bytes }
# |--+ virtual_folder [ -X- test1.gds ]

closefn.gds(f)
## End(Not run)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

append.gdsn

Append data to a specified variable

Description

Append new data to the data field of a GDS node.

Usage

```
append.gdsn(node, val, check=TRUE)
```

Arguments

node	an object of class gdsn.class
val	R primitive data, like integer; or an object of class gdsn.class
check	whether a warning is given, when appended data can not match the capability of data field; if val is character-type, a warning will be shown if there is any NA in val

Details

storage.mode(val) should be "integer", "double", "character" or "logical". GDS format does not support missing characters NA, and any NA will be converted to a blank string "".

Value

None.

Author(s)

Xiuwen Zheng

See Also

[read.gdsn](#), [write.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# common types
n <- add.gdsn(f, "int", val=matrix(1:10000, nrow=100, ncol=100),
  compress="ZIP")

# no warning, and add a new column
append.gdsn(n, -1:-100)
f

# a warning
append.gdsn(n, -1:-50)
f

# no warning here, and add a new column
append.gdsn(n, -51:-100)
f

# you should call "readmode.gdsn" before reading, since compress="ZIP"
readmode.gdsn(n)

# check the last column
read.gdsn(n, start=c(1, 102), count=c(-1, 1))

# characters
n <- add.gdsn(f, "string", val=as.character(1:100))
append.gdsn(n, as.character(rep(NA, 25)))

read.gdsn(n)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

 apply.gdsn

Apply functions over margins

Description

Return a vector or list of values obtained by applying a function to margins of a GDS matrix or array.

Usage

```
apply.gdsn(node, margin, FUN, selection=NULL,
  as.is=c("list", "none", "integer", "double", "character", "logical",
    "raw", "gdsnnode"), var.index=c("none", "relative", "absolute"),
  target.node=NULL, .useraw=FALSE, .value=NULL, .substitute=NULL, ...)
```

Arguments

node	an object of class <code>gdsn.class</code> , or a list of objects of class <code>gdsn.class</code>
margin	an integer giving the subscripts which the function will be applied over. E.g., for a matrix 1 indicates rows, 2 indicates columns
FUN	the function to be applied
selection	a list or NULL; if a list, it is a list of logical vectors according to dimensions indicating selection; if NULL, uses all data
as.is	returned value: a list, an integer vector, etc; "gdsnnode" – the returned value from the user-defined function will be appended to target.node.
var.index	if "none", call FUN(x, ...) without an index; if "relative" or "absolute", add an argument to the user-defined function FUN like FUN(index, x, ...) where index in the function is an index starting from 1: "relative" for indexing in the selection defined by selection, "absolute" for indexing with respect to all data
target.node	NULL, an object of class <code>gdsn.class</code> or a list of <code>gdsn.class</code> : output to the target GDS node(s) when as.is="gdsnnode". See details
.useraw	use R RAW storage mode if integers can be stored in a byte, to reduce memory usage
.value	a vector of values to be replaced in the original data array, or NULL for nothing
.substitute	a vector of values after replacing, or NULL for nothing; length(.substitute) should be one or length(.value); if length(.substitute) = length(.value), it is a mapping from .value to .substitute
...	optional arguments to FUN

Details

The algorithm is optimized by blocking the computations to exploit the high-speed memory instead of disk.

When `as.is="gdsnode"` and there are more than one `gdsn.class` object in `target.node`, the user-defined function should return a list with elements corresponding to `target.node`, or `NULL` indicating no appending.

Value

A vector or list of values.

Author(s)

Xiuwen Zheng

See Also

[read.gdsn](#), [readex.gdsn](#), [clusterApply.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

(n1 <- add.gdsn(f, "matrix", val=matrix(1:(10*6), nrow=10)))
read.gdsn(index.gdsn(f, "matrix"))

(n2 <- add.gdsn(f, "string",
  val=matrix(paste("L", 1:(10*6), sep=","), nrow=10)))
read.gdsn(index.gdsn(f, "string"))

# Apply functions over rows of matrix
apply.gdsn(n1, margin=1, FUN=function(x) print(x), as.is="none")
apply.gdsn(n1, margin=1,
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(x) print(x), as.is="none")
apply.gdsn(n1, margin=1, var.index="relative",
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(i, x) { cat("index: ", i, ", ", sep=""); print(x) },
  as.is="none")
apply.gdsn(n1, margin=1, var.index="absolute",
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(i, x) { cat("index: ", i, ", ", sep=""); print(x) },
  as.is="none")
apply.gdsn(n2, margin=1, FUN=function(x) print(x), as.is="none")

# Apply functions over columns of matrix
apply.gdsn(n1, margin=2, FUN=function(x) print(x), as.is="none")
apply.gdsn(n1, margin=2,
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
```

```

    FUN=function(x) print(x), as.is="none")
apply.gdsn(n2, margin=2,
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(x) print(x), as.is="none")

apply.gdsn(n1, margin=1, FUN=function(x) print(x), as.is="none",
  .value=16:40, .substitute=NA)
apply.gdsn(n1, margin=2, FUN=function(x) print(x), as.is="none",
  .value=16:40, .substitute=NA)

# close
closefn.gds(f)

#####
#
# Append to a target GDS node
#

# create a GDS file
f <- createfn.gds("test.gds")

(n2 <- add.gdsn(f, "matrix", val=matrix(1:(10*6), nrow=10)))

(n2 <- add.gdsn(f, "string",
  val=matrix(paste("L", 1:(10*6), sep=",", nrow=10)))
read.gdsn(index.gdsn(f, "string"))

n2.1 <- add.gdsn(f, "transpose.matrix", storage="int", valdim=c(6,0))
n2.1 <- add.gdsn(f, "transpose.string", storage="string", valdim=c(6,0))

# Apply functions over rows of matrix
apply.gdsn(n2, margin=1, FUN=`c`, as.is="gdsnode", target.node=n2.1)

# matrix transpose
read.gdsn(n2)
read.gdsn(n2.1)

# Apply functions over rows of matrix
apply.gdsn(n2, margin=1, FUN=`c`, as.is="gdsnode", target.node=n2.1)

# matrix transpose
read.gdsn(n2)
read.gdsn(n2.1)

# close
closefn.gds(f)

```

```
#####
#
# Append to multiple target GDS node
#

# create a GDS file
f <- createfn.gds("test.gds")

(n2 <- add.gdsn(f, "matrix", val=matrix(1:(10*6), nrow=10)))

n2.1 <- add.gdsn(f, "transpose.matrix", storage="int", valdim=c(6,0))
n2.2 <- add.gdsn(f, "n.matrix", storage="int", valdim=c(0))

# Apply functions over rows of matrix
apply.gdsn(n2, margin=1, FUN=function(x) list(x, x[1]),
  as.is="gdsnode", target.node=list(n2.1, n2.2))

# matrix transpose
read.gdsn(n2)
read.gdsn(n2.1)
read.gdsn(n2.2)

# close
closefn.gds(f)

#####
#
# Multiple variables
#

# create a GDS file
f <- createfn.gds("test.gds")

X <- matrix(1:50, nrow=10)
Y <- matrix((1:50)/100, nrow=10)
Z1 <- factor(c(rep(c("ABC", "DEF", "ETD"), 3), "TTT"))
Z2 <- c(TRUE, FALSE, TRUE, FALSE, TRUE)

node.X <- add.gdsn(f, "X", X)
node.Y <- add.gdsn(f, "Y", Y)
node.Z1 <- add.gdsn(f, "Z1", Z1)
node.Z2 <- add.gdsn(f, "Z2", Z2)

v <- apply.gdsn(list(X=node.X, Y=node.Y, Z=node.Z1), margin=c(1, 1, 1),
  FUN=print, as.is="none")

v <- apply.gdsn(list(X=node.X, Y=node.Y, Z=node.Z2), margin=c(2, 2, 1),
  FUN=print)
```

```

v <- apply.gdsn(list(X=node.X, Y=node.Y, Z=node.Z2), margin=c(2, 2, 1),
  FUN=print, .value=35:45, .substitute=NA)

v <- apply.gdsn(list(X=node.X, Y=node.Y, Z=node.Z2), margin=c(2, 2, 1),
  FUN=print, .value=35:45, .substitute=NA)

# with selection

s1 <- rep(c(FALSE, TRUE), 5)
s2 <- c(TRUE, FALSE, TRUE, FALSE, TRUE)

v <- apply.gdsn(list(X=node.X, Y=node.Y, Z=node.Z1), margin=c(1, 1, 1),
  selection = list(list(s1, s2), list(s1, s2), list(s1)),
  FUN=function(x) print(x))

v <- apply.gdsn(list(X=node.X, Y=node.Y, Z=node.Z2), margin=c(2, 2, 1),
  selection = list(list(s1, s2), list(s1, s2), list(s2)),
  FUN=function(x) print(x))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

assign.gdsn

Assign/append data to a GDS node

Description

Assign data to a GDS node, or append data to a GDS node

Usage

```

assign.gdsn(node, src.node=NULL, resize=TRUE, seldim=NULL, append=FALSE,
  .value=NULL, .substitute=NULL)

```

Arguments

node	an object of class <code>gdsn.class</code> , a target GDS node
src.node	an object of class <code>gdsn.class</code> , a source GDS node
resize	whether call <code>setdim.gdsn</code> to reset the dimension(s)
seldim	the selection of src.obj with numeric or logical indicators, or NULL for all data
append	if TRUE, append data by calling <code>append.gdsn</code> ; otherwise, replace the old one

.value	a vector of values to be replaced in the original data array, or NULL for nothing
.substitute	a vector of values after replacing, or NULL for nothing; length(.substitute) should be one or length(.value); if length(.substitute) = length(.value), it is a mapping from .value to .substitute

Value

None.

Author(s)

Xiuwen Zheng

See Also[read.gdsn](#), [readex.gdsn](#), [apply.gdsn](#), [write.gdsn](#), [append.gdsn](#)**Examples**

```
f <- createfn.gds("test.gds")

n1 <- add.gdsn(f, "n1", 1:100)
n2 <- add.gdsn(f, "n2", storage="int", valdim=c(20, 0))
n3 <- add.gdsn(f, "n3", storage="int", valdim=c(0))
n4 <- add.gdsn(f, "n4", matrix(1:48, 6))
f

assign.gdsn(n2, n1, resize=FALSE, append=TRUE)

read.gdsn(n1)
read.gdsn(n2)

assign.gdsn(n2, n1, resize=FALSE, append=TRUE)
append.gdsn(n2, n1)
read.gdsn(n2)

assign.gdsn(n3, n2, seldim=
  list(rep(c(TRUE, FALSE), 10), c(rep(c(TRUE, FALSE), 7), TRUE)))
read.gdsn(n3)

setdim.gdsn(n2, c(25,0))
assign.gdsn(n2, n1, append=TRUE, seldim=rep(c(TRUE, FALSE), 50))
read.gdsn(n2)

assign.gdsn(n2, n1); read.gdsn(n2)
f

##

read.gdsn(n4)

# substitute
```

```

assign.gdsn(n4, .value=c(3:8,35:40), .substitute=NA); read.gdsn(n4)

# subset
assign.gdsn(n4, seldim=list(c(4,2,6,NA), c(5,6,NA,2,8,NA,4))); read.gdsn(n4)

n4 <- add.gdsn(f, "n4", matrix(1:48, 6), replace=TRUE)
read.gdsn(n4)
# sort into descending order
assign.gdsn(n4, seldim=list(6:1, 8:1)); read.gdsn(n4)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

cache.gdsn

*Caching variable data***Description**

Caching the data associated with a GDS variable

Usage

```
cache.gdsn(node)
```

Arguments

node an object of class `gdsn.class`, a GDS node

Details

If random access of array-based data is required, it is possible to speed up the access time by caching data in memory. This function tries to force the operating system to cache the data associated with the GDS node, however how to cache data depends on the configuration of operating system, including system memory and caching strategy. Note that this function does not explicitly allocate memory for the data.

If the data has been compressed, caching strategy almost has no effect on random access, since the data has to be decompressed serially.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[read.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

n <- add.gdsn(f, "int.matrix", matrix(1:50*100, nrow=100, ncol=50))
n

cache.gdsn(n)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

cleanup.gds

Clean up fragments

Description

Clean up the fragments of a CoreArray Genomic Data Structure (GDS) file.

Usage

```
cleanup.gds(filename, verbose=TRUE)
```

Arguments

filename	the file name of a GDS file to be opened
verbose	if TRUE, show information

Value

None.

Author(s)

Xiuwen Zheng

See Also

[openfn.gds](#), [createfn.gds](#), [closefn.gds](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# common types
add.gdsn(f, "int", val=1:10000)
L <- -2500:2499
add.gdsn(f, "int.matrix", val=matrix(L, nrow=100, ncol=50))

# save a .RData object
obj <- list(X=1:10, Y=seq(1, 10, 0.1))
save(obj, file="tmp.RData")
addfile.gdsn(f, "tmp.RData", filename="tmp.RData")

f

# close the GDS file
closefn.gds(f)

# clean up fragments
cleanup.gds("test.gds")

# open ...
(f <- openfn.gds("test.gds"))
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

closefn.gds

Close a GDS file

Description

Close a CoreArray Genomic Data Structure (GDS) file.

Usage

```
closefn.gds(gdsfile)
```

Arguments

gdsfile an object of class [gds.class](#), a GDS file

Details

For better performance, data in a GDS file are usually cached in memory. Keep in mind that the new file may not actually be written to disk, until [closefn.gds](#) or [sync.gds](#) is called. Anyway, when R shuts down, all GDS files created or opened would be automatically closed.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[createfn.gds](#), [openfn.gds](#), [sync.gds](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "int.matrix", matrix(1:50*100, nrow=100, ncol=50))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

clusterApply.gdsn

Apply functions over matrix margins in parallel

Description

Return a vector or list of values obtained by applying a function to margins of a GDS matrix in parallel.

Usage

```
clusterApply.gdsn(cl, gds.fn, node.name, margin, FUN, selection=NULL,
  as.is=c("list", "none", "integer", "double", "character", "logical", "raw"),
  var.index=c("none", "relative", "absolute"), .useraw=FALSE,
  .value=NULL, .substitute=NULL, ...)
```

Arguments

<code>cl</code>	a cluster object, created by this package or by the package parallel
<code>gds.fn</code>	the file name of a GDS file
<code>node.name</code>	a character vector indicating GDS node path
<code>margin</code>	an integer giving the subscripts which the function will be applied over. E.g., for a matrix 1 indicates rows, 2 indicates columns
<code>FUN</code>	the function to be applied
<code>selection</code>	a list or NULL; if a list, it is a list of logical vectors according to dimensions indicating selection; if NULL, uses all data
<code>as.is</code>	returned value: a list, an integer vector, etc
<code>var.index</code>	if "none", call FUN(x, ...) without an index; if "relative" or "absolute", add an argument to the user-defined function FUN like FUN(index, x, ...) where index in the function is an index starting from 1: "relative" for indexing in the selection defined by selection, "absolute" for indexing with respect to all data
<code>.useraw</code>	use R RAW storage mode if integers can be stored in a byte, to reduce memory usage
<code>.value</code>	a vector of values to be replaced in the original data array, or NULL for nothing
<code>.substitute</code>	a vector of values after replacing, or NULL for nothing; length(.substitute) should be one or length(.value); if length(.substitute) = length(.value), it is a mapping from .value to .substitute
<code>...</code>	optional arguments to FUN

Details

The algorithm of applying is optimized by blocking the computations to exploit the high-speed memory instead of disk.

Value

A vector or list of values.

Author(s)

Xiuwen Zheng

See Also

[apply.gdsn](#)

Examples

```
#####
# prepare a GDS file

# cteate a GDS file
```

```

f <- createfn.gds("test1.gds")

(n <- add.gdsn(f, "matrix", val=matrix(1:(10*6), nrow=10)))
read.gdsn(index.gdsn(f, "matrix"))

closefn.gds(f)

# create the GDS file "test2.gds"
(f <- createfn.gds("test2.gds"))

X <- matrix(1:50, nrow=10)
Y <- matrix((1:50)/100, nrow=10)
Z1 <- factor(c(rep(c("ABC", "DEF", "ETD"), 3), "TTT"))
Z2 <- c(TRUE, FALSE, TRUE, FALSE, TRUE)

node.X <- add.gdsn(f, "X", X)
node.Y <- add.gdsn(f, "Y", Y)
node.Z1 <- add.gdsn(f, "Z1", Z1)
node.Z2 <- add.gdsn(f, "Z2", Z2)
f

closefn.gds(f)

#####
# apply in parallel

library(parallel)

# Use option cl.core to choose an appropriate cluster size.
cl <- makeCluster(getOption("cl.cores", 2L))

# Apply functions over rows or columns of matrix

clusterApply.gdsn(cl, "test1.gds", "matrix", margin=1, FUN=function(x) x)

clusterApply.gdsn(cl, "test1.gds", "matrix", margin=2, FUN=function(x) x)

clusterApply.gdsn(cl, "test1.gds", "matrix", margin=1,
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(x) x)

clusterApply.gdsn(cl, "test1.gds", "matrix", margin=2,
  selection = list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)),
  FUN=function(x) x)

# Apply functions over rows or columns of multiple data sets

```

```

clusterApply.gdsn(cl, "test2.gds", c("X", "Y", "Z1"), margin=c(1, 1, 1),
  FUN=function(x) x)

# with variable names
clusterApply.gdsn(cl, "test2.gds", c(X="X", Y="Y", Z="Z2"), margin=c(2, 2, 1),
  FUN=function(x) x)

# stop clusters
stopCluster(cl)

# delete the temporary file
unlink(c("test1.gds", "test2.gds"), force=TRUE)

```

cnt.gdsn

*Return the number of child nodes***Description**

Return the number of child nodes for a GDS node.

Usage

```
cnt.gdsn(node, include.hidden=FALSE)
```

Arguments

`node` an object of class `gdsn.class`, a GDS node
`include.hidden` whether including hidden variables or folders

Value

If node is a folder, return the numbers of variables in the folder including child folders. Otherwise, return 0.

Author(s)

Xiuwen Zheng

See Also

[objdesp.gdsn](#), [ls.gdsn](#), [index.gdsn](#), [delete.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T","B","C"), z=TRUE))
cnt.gdsn(node)
# 3

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

compression.gdsn	<i>Modify compression mode</i>
------------------	--------------------------------

Description

Modify the compression mode of data field in the GDS node.

Usage

```
compression.gdsn(node,
  compress=c("", "ZIP", "ZIP_RA", "LZMA", "LZMA_RA", "LZ4", "LZ4_RA"))
```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
compress	the compression method can be "" (no compression), "ZIP", "ZIP.fast", "ZIP.def", "ZIP.max" or "ZIP.none" (original zlib); "ZIP_RA", "ZIP_RA.fast", "ZIP_RA.def", "ZIP_RA.max" or "ZIP_RA.none" (zlib with efficient random access); "LZ4", "LZ4.none", "LZ4.fast", "LZ4.hc" or "LZ4.max" (LZ4 compression/decompression library); "LZ4_RA", "LZ4_RA.none", "LZ4_RA.fast", "LZ4_RA.hc" or "LZ4_RA.max" (with efficient random access). "LZMA", "LZMA.fast", "LZMA.def", "LZMA.max", "LZMA_RA", "LZMA_RA.fast", "LZMA_RA.def", "LZMA_RA.max" (lzma compression/decompression algorithm). See details

Details

Z compression algorithm (<http://www.zlib.net>) can be used to deflate the data stored in the GDS file. "ZIP" option is equivalent to "ZIP.def". "ZIP.fast", "ZIP.def" and "ZIP.max" correspond to different compression levels.

To support efficient random access of Z stream, "ZIP_RA", "ZIP_RA.fast", "ZIP_RA.def" or "ZIP_RA.max" should be specified. "ZIP_RA" option is equivalent to "ZIP_RA.def:256K". The block size can be

specified by following colon, and "16K", "32K", "64K", "128K", "256K", "512K", "1M", "2M", "4M" and "8M" are allowed, like "ZIP_RA:64K". The compression algorithm tries to keep each independent compressed data block to be about of the specified block size, like 64K.

LZ4 fast lossless compression algorithm is allowed when compress="LZ4" (<https://github.com/lz4/lz4>). Three compression levels can be specified, "LZ4.fast" (LZ4 fast mode), "LZ4.hc" (LZ4 high compression mode), "LZ4.max" (maximize the compression ratio). The block size can be specified by following colon, and "64K", "256K", "1M" and "4M" are allowed according to LZ4 frame format. "LZ4" is equivalent to "LZ4.hc:256K".

To support efficient random access of LZ4 stream, "LZ4_RA", "LZ4_RA.fast", "LZ4_RA.hc" or "ZIP_RA.max" should be specified. "LZ4_RA" option is equivalent to "LZ4_RA.hc:256K". The block size can be specified by following colon, and "16K", "32K", "64K", "128K", "256K", "512K", "1M", "2M", "4M" and "8M" are allowed, like "LZ4_RA:64K". The compression algorithm tries to keep each independent compressed data block to be about of the specified block size, like 64K.

LZMA compression algorithm (<https://tukaani.org/xz/>) is available since gdsfmt_v1.7.18, which has a higher compression ratio than ZIP algorithm. "LZMA", "LZMA.fast", "LZMA.def" and "LZMA.max" available. To support efficient random access of LZMA stream, "LZMA_RA", "LZMA_RA.fast", "LZMA_RA.def" and "LZMA_RA.max" can be used. The block size can be specified by following colon. "LZMA_RA" is equivalent to "LZMA_RA.def:256K".

compression 1	compression 2	command line
ZIP	ZIP_RA	gzip -6
ZIP.fast	ZIP_RA.fast	gzip -fast
ZIP.def	ZIP_RA.def	gzip -6
ZIP.max	ZIP_RA.max	gzip -best
LZ4	LZ4_RA	LZ4 HC -6
LZ4.min	LZ4_RA.min	LZ4 fast 0
LZ4.fast	LZ4_RA.fast	LZ4 fast 2
LZ4.hc	LZ4_RA.hc	LZ4 HC -6
LZ4.max	LZ4_RA.max	LZ4 HC -9
LZMA	LZMA_RA	xz -6
LZMA.min	LZMA_RA.min	xz -0
LZMA.fast	LZMA_RA.fast	xz -2
LZMA.def	LZMA_RA.def	xz -6
LZMA.max	LZMA_RA.max	xz -9e
LZMA.ultra	LZMA_RA.ultra	xz -lzma2=dict=512Mi
LZMA.ultra_max	LZMA_RA.ultra_max	xz -lzma2=dict=1536Mi

Value

Return node.

Author(s)

Xiuwen Zheng

References

<http://zlib.net>, <https://github.com/lz4/lz4>, <https://tukaani.org/xz/>

See Also

[readmode.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

n <- add.gdsn(f, "int.matrix", matrix(1:50*100, nrow=100, ncol=50))
n

compression.gdsn(n, "ZIP")

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

copyto.gdsn

Copy GDS nodes

Description

Copy GDS node(s) to a folder with a new name

Usage

```
copyto.gdsn(node, source, name=NULL)
```

Arguments

node	a folder of class gdsn.class or gds.class
source	an object of class gdsn.class or gds.class
name	a specified name; if NULL, it is determined by source

Value

None.

Author(s)

Xiuwen Zheng

See Also

[moveto.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "label", NULL)
add.gdsn(f, "int", 1:100, compress="ZIP", closezip=TRUE)
add.gdsn(f, "int.matrix", matrix(1:100, nrow=20))
addfolder.gdsn(f, "folder1")
addfolder.gdsn(f, "folder2")

for (nm in c("label", "int", "int.matrix"))
  copyto.gdsn(index.gdsn(f, "folder1"), index.gdsn(f, nm))
f

copyto.gdsn(index.gdsn(f, "folder2"), index.gdsn(f, "folder1"))
f

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

createfn.gds

*Create a GDS file***Description**

Create a new CoreArray Genomic Data Structure (GDS) file.

Usage

```
createfn.gds(filename, allow.duplicate=FALSE, use.abbrev=TRUE)
```

Arguments

filename	the file name of a new GDS file to be created
allow.duplicate	if TRUE, it is allowed to open a GDS file with read-only mode when it has been opened in the same R session
use.abbrev	if TRUE, 'filename' of the gds.class object is set to be the absolute path

Details

Keep in mind that the new file may not actually be written to disk until [closefn.gds](#) or [sync.gds](#) is called.

Value

Return an object of class `gds.class`:

filename	the file name to be created
id	internal file id
root	an object of class <code>gdsn.class</code> , the root of hierarchical structure
readonly	whether it is read-only or not

Author(s)

Xiuwen Zheng

See Also

`openfn.gds`, `closefn.gds`

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, val=list(x=c(1,2), y=c("T", "B", "C"), z=TRUE))

f

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

delete.attr.gdsn	<i>Delete attribute(s)</i>
------------------	----------------------------

Description

Remove the attribute(s) of a GDS node.

Usage

```
delete.attr.gdsn(node, name)
```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
name	the name(s) of an attribute

Value

None.

Author(s)

Xiuwen Zheng

See Also

[put.attr.gdsn](#), [get.attr.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

node <- add.gdsn(f, "int", val=1:10000)
put.attr.gdsn(node, "missing.value", 10000)
put.attr.gdsn(node, "one.value", 1L)
put.attr.gdsn(node, "string", c("ABCDEF", "THIS"))
put.attr.gdsn(node, "bool", c(TRUE, TRUE, FALSE))

f
get.attr.gdsn(node)

delete.attr.gdsn(node, c("one.value", "bool"))
get.attr.gdsn(node)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

delete.gdsn

Delete a GDS node

Description

Delete a specified GDS node.

Usage

```
delete.gdsn(node, force=FALSE)
```

Arguments

node	an object of class gdsn.class , a GDS node
force	if FALSE, it is not allowed to delete a non-empty folder

Value

None.

Author(s)

Xiuwen Zheng

See Also

[add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T", "B", "C"), z=TRUE))
f

## Not run:
# delete "node", but an error occurs
delete.gdsn(node)

## End(Not run)

# delete "node"
delete.gdsn(node, TRUE)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

diagnosis.gds

Diagnose the GDS file

Description

Diagnose the GDS file and data information.

Usage

```
diagnosis.gds(gds, log.only=FALSE)
```

Arguments

<code>gds</code>	an object of class <code>gdsn.class</code> or <code>gds.class</code>
<code>log.only</code>	if TRUE, return a character vector of log only

Value

A list with stream and chunk information.

If `gds` is a `"gds.class"` object (i.e., a GDS file), the function returns a list with components, like:

<code>stream</code>	summary of byte stream
<code>log</code>	event log records

If `gds` is a `"gdsn.class"` object, the function returns a list with components, like:

<code>head</code>	<code>total_size</code> , <code>chunk_offset</code> , <code>chunk_size</code>
<code>data</code>	<code>total_size</code> , <code>chunk_offset</code> , <code>chunk_size</code>
<code>...</code>	

Author(s)

Xiuwen Zheng

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

set.seed(1000)
rawval <- as.raw(rep(0:99, 50))

add.gdsn(f, "label", NULL)
add.gdsn(f, "raw", rawval)

closefn.gds(f)

##

f <- openfn.gds("test.gds")

diagnosis.gds(f)
diagnosis.gds(f$root)
diagnosis.gds(index.gdsn(f, "label"))
diagnosis.gds(index.gdsn(f, "raw"))

closefn.gds(f)

## remove fragments

cleanup.gds("test.gds")
```

```
##

f <- openfn.gds("test.gds")

diagnosis.gds(f$root)
diagnosis.gds(index.gdsn(f, "label"))
(adr <- diagnosis.gds(index.gdsn(f, "raw"))))

closefn.gds(f)

## read binary data directly

f <- file("test.gds", "rb")

dat <- NULL
for (i in seq_len(length(adr$data$chunk_offset)))
{
  seek(f, adr$data$chunk_offset[i])
  dat <- c(dat, readBin(f, "raw", adr$data$chunk_size[i]))
}

identical(dat, rawval) # should be TRUE

close(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

digest.gdsn	<i>create hash function digests</i>
-------------	-------------------------------------

Description

Create hash function digests for a GDS node.

Usage

```
digest.gdsn(node, algo=c("md5", "sha1", "sha256", "sha384", "sha512"),
  action=c("none", "Robject", "add", "add.Robj", "clear", "verify", "return"))
```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
algo	the algorithm to be used; currently available choices are "md5" (by default), "sha1", "sha256", "sha384", "sha512"

action "none": nothing (by default); "Robject": convert to R object, i.e., raw, integer, double or character before applying hash digests; "add": add a barcode attribute; "add.Robj": add a barcode attribute generated from R object; "clear": remove all hash barcodes; "verify": verify data integrity if there is any hash code in the attributes, and stop if any fails; "return": compare the existing hash code in the attributes, and return FALSE if fails, NA if no hash code, and TRUE if the verification succeeds

Details

The R package digest should be installed to perform hash function digests.

Value

A character or NA_character_ when the hash algorithm is not available.

Author(s)

Xiuwen Zheng

Examples

```
library(digest)
library(tools)

# create a GDS file
f <- createfn.gds("test.gds")

val <- as.raw(rep(1:128, 1024))
n1 <- add.gdsn(f, "raw1", val)
n2 <- add.gdsn(f, "int1", as.integer(val))
n3 <- add.gdsn(f, "int2", as.integer(val), compress="ZIP", closezip=TRUE)

digest.gdsn(n1)
digest.gdsn(n1, action="Robject")
digest.gdsn(n1, action="add")
digest.gdsn(n1, action="add.Robj")
writeBin(read.gdsn(n1, .useraw=TRUE), con="test1.bin")

write.gdsn(n1, 0, start=1027, count=1)
digest.gdsn(n1, action="add")
digest.gdsn(n1, action="add.Robj")
digest.gdsn(n1, "sha1", action="add")
digest.gdsn(n1, "sha256", action="add")
# digest.gdsn(n1, "sha384", action="add") ## digest_0.6.11 does not work
digest.gdsn(n1, "sha512", action="add")
writeBin(read.gdsn(n1, .useraw=TRUE), con="test2.bin")

print(n1, attribute=TRUE)
digest.gdsn(n1, action="verify")

digest.gdsn(n1, action="clear")
```

```

print(n1, attribute=TRUE)

digest.gdsn(n2)
digest.gdsn(n2, action="Robject")

# using R object
digest.gdsn(n2) == digest.gdsn(n3) # FALSE
digest.gdsn(n2, action="Robject") == digest.gdsn(n3, action="Robject") # TRUE

# close the GDS file
closefn.gds(f)

# check with other program
md5sum(c("test1.bin", "test2.bin"))

# delete the temporary file
unlink(c("test.gds", "test1.bin", "test2.bin"), force=TRUE)

```

exist.gdsn	<i>Return whether the path exists or not</i>
------------	--

Description

Get a logical vector to show whether the path exists or not.

Usage

```
exist.gdsn(node, path)
```

Arguments

node	an object of class gdsn.class , a GDS node
path	the path(s) specifying a GDS node with '/' as a separator

Value

A logical vector.

Author(s)

Xiuwen Zheng

See Also

[ls.gdsn](#), [index.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T", "B", "C"), z=TRUE))
ls.gdsn(node)
# "x" "y" "z"

exist.gdsn(f, c("list", "list/z", "wuw/dj"))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

gds.class*the class of GDS file*

Description

The class of a CoreArray Genomic Data Structure (GDS) file.

Value

There are three components:

filename	the file name to be created
id	internal file id, an integer
root	an object of class gdsn.class , the root of hierarchical structure
readonly	whether it is read-only or not

Author(s)

Xiuwen Zheng

See Also

[createfn.gds](#), [openfn.gds](#), [closefn.gds](#)

`gdsn.class`*the class of variable node in the GDS file*

Description

The class of variable node in the GDS file.

Author(s)

Xiuwen Zheng

See Also

[add.gdsn](#), [read.gdsn](#), [write.gdsn](#)

`get.attr.gdsn`*Get attributes*

Description

Get the attributes of a GDS node.

Usage

```
get.attr.gdsn(node)
```

Arguments

`node` an object of class [gdsn.class](#), a GDS node

Value

A list of attributes.

Author(s)

Xiuwen Zheng

See Also

[put.attr.gdsn](#), [delete.attr.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

node <- add.gdsn(f, "int", val=1:10000)
put.attr.gdsn(node, "missing.value", 10000)

f
get.attr.gdsn(node)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

getfile.gdsn

Output a file from a stream container

Description

Get a file from a GDS node of stream container.

Usage

```
getfile.gdsn(node, out.filename)
```

Arguments

node	an object of class gdsn.class , a GDS node
out.filename	the file name of output stream

Value

None.

Author(s)

Xiuwen Zheng

See Also

[addfile.gdsn](#)

Examples

```
# save a .RData object
obj <- list(X=1:10, Y=seq(1, 10, 0.1))
save(obj, file="tmp.RData")

# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "double", val=seq(1, 1000, 0.4))
addfile.gdsn(f, "tmp.RData", "tmp.RData")

# open the GDS file
closefn.gds(f)

# open the existing file
(f <- openfn.gds("test.gds"))

getfile.gdsn(index.gdsn(f, "tmp.RData"), "tmp1.RData")
(obj <- get(load("tmp1.RData"))))

# open the GDS file
closefn.gds(f)

# delete the temporary files
unlink(c("test.gds", "tmp.RData", "tmp1.RData"), force=TRUE)
```

getfolder.gdsn

Get the folder

Description

Get the folder which contains the specified GDS node.

Usage

```
getfolder.gdsn(node)
```

Arguments

node an object of class `gdsn.class`

Value

An object of class `gdsn.class`.

Author(s)

Xiuwen Zheng

See Also[index.gdsn](#)**Examples**

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "label", NULL)
add.gdsn(f, "double", seq(1, 1000, 0.4))
add.gdsn(f, "list", list(X=1:10, Y=seq(1, 10, 0.25)))
add.gdsn(f, "data.frame", data.frame(X=1:19, Y=seq(1, 10, 0.5)))

f

getfolder.gdsn(index.gdsn(f, "label"))
getfolder.gdsn(index.gdsn(f, "double"))
getfolder.gdsn(index.gdsn(f, "list/X"))
getfolder.gdsn(index.gdsn(f, "data.frame/Y"))

getfolder.gdsn(f$root)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

index.gdsn	<i>Get the specified node</i>
------------	-------------------------------

Description

Get a specified GDS node.

Usage

```
index.gdsn(node, path=NULL, index=NULL, silent=FALSE)
```

Arguments

node	an object of class gdsn.class (a GDS node), or gds.class (a GDS file)
path	the path specifying a GDS node with '/' as a separator
index	a numeric vector or characters, specifying the path; it is applicable if path=NULL
silent	if TRUE, return NULL if the specified node does not exist

Details

If `index` is a numeric vector, e.g., `c(1, 2)`, the result is the second child node of the first child of node. If `index` is a vector of characters, e.g., `c("list", "x")`, the result is the child node with name "x" of the "list" child node.

Value

An object of class `gdsn.class` for the specified node.

Author(s)

Xiuwen Zheng

See Also

`cnt.gdsn`, `ls.gdsn`, `name.gdsn`, `add.gdsn`, `delete.gdsn`

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T","B","C"), z=TRUE))
f

index.gdsn(f, "list/x")
index.gdsn(f, index=c("list", "x"))
index.gdsn(f, index=c(1, 1))
index.gdsn(f, index=c("list", "z"))

## Not run:
index.gdsn(f, "list/x/z")
# Error in index.gdsn(f, "list/x/z") : Invalid path "list/x/z"!

## End(Not run)

# return NULL
index.gdsn(f, "list/x/z", silent=TRUE)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

is.element.gdsn	<i>whether the elements are in a set</i>
-----------------	--

Description

Determine whether the elements are in a specified set.

Usage

```
is.element.gdsn(node, set)
```

Arguments

node	an object of class gdsn.class (a GDS node)
set	the specified set of elements

Value

A logical vector or array.

Author(s)

Xiuwen Zheng

See Also

[read.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "int", val=1:100)
add.gdsn(f, "mat", val=matrix(1:12, nrow=4, ncol=3))
add.gdsn(f, "double", val=seq(1, 10, 0.1))
add.gdsn(f, "character", val=c("int", "double", "logical", "factor"))

is.element.gdsn(index.gdsn(f, "int"), c(1, 10, 20))
is.element.gdsn(index.gdsn(f, "mat"), c(2, 8, 12))
is.element.gdsn(index.gdsn(f, "double"), c(1.1, 1.3, 1.5))
is.element.gdsn(index.gdsn(f, "character"), c("int", "factor"))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

is.sparse.gdsn	<i>whether a sparse array or not</i>
----------------	--------------------------------------

Description

Determine whether the node is a sparse array or not.

Usage

```
is.sparse.gdsn(node)
```

Arguments

node	an object of class gdsn.class (a GDS node)
------	--

Value

TRUE / FALSE.

Author(s)

Xiuwen Zheng

See Also

[add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

cnt <- matrix(0, nrow=4, ncol=8)
set.seed(100)
cnt[sample.int(length(cnt), 8)] <- rpois(8, 4)
cnt

add.gdsn(f, "mat", val=cnt)
add.gdsn(f, "sp.mat", val=cnt, storage="sp.real")
f

is.sparse.gdsn(index.gdsn(f, "mat"))
is.sparse.gdsn(index.gdsn(f, "sp.mat"))

read.gdsn(index.gdsn(f, "sp.mat"))

# close the GDS file
closefn.gds(f)
```

```
# delete the temporary file
unlink("test.gds", force=TRUE)
```

lasterr.gds	<i>Return the last error message</i>
-------------	--------------------------------------

Description

Get the last error message and clear the error message(s) in the gdsfmt package.

Usage

```
lasterr.gds()
```

Value

Character.

Author(s)

Xiuwen Zheng

Examples

```
lasterr.gds()
```

ls.gdsn	<i>Return the names of child nodes</i>
---------	--

Description

Get a list of names for its child nodes.

Usage

```
ls.gdsn(node, include.hidden=FALSE, recursive=FALSE, include.dirs=TRUE)
```

Arguments

node	an object of class gdsn.class , a GDS node
include.hidden	whether including hidden variables or folders
recursive	whether the listing recurses into directories or not
include.dirs	whether subdirectory names should be included in recursive listings

Value

A vector of characters, or character(0) if node is not a folder.

Author(s)

Xiuwen Zheng

See Also

[cnt.gdsn](#), [objdesp.gdsn](#), [ls.gdsn](#), [index.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T","B","C"), z=TRUE))
ls.gdsn(node)
# "x" "y" "z"

ls.gdsn(f$root)
# "list"

ls.gdsn(f$root, recursive=TRUE)
# "list" "list/x" "list/y" "list/z"

ls.gdsn(f$root, recursive=TRUE, include.dirs=FALSE)
# "list/x" "list/y" "list/z"

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

moveto.gdsn

Relocate a GDS node

Description

Move a GDS node to a new place in the same file

Usage

```
moveto.gdsn(node, loc.node,
  relpos = c("after", "before", "replace", "replace+rename"))
```

Arguments

node	an object of class gdsn.class (a GDS node)
loc.node	an object of class gdsn.class (a GDS node), indicates the new location
relpos	"after": after loc.node, "before": before loc.node, "replace": replace loc.node (loc.node will be deleted); "replace+rename": replace loc.node (loc.node will be deleted and node has a new name as loc.node)

Value

None.

Author(s)

Xiuwen Zheng

See Also

[createfn.gds](#), [openfn.gds](#), [index.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")
L <- -2500:2499

# common types

add.gdsn(f, "label", NULL)
add.gdsn(f, "int", 1:10000, compress="ZIP", closezip=TRUE)
add.gdsn(f, "int.matrix", matrix(L, nrow=100, ncol=50))
add.gdsn(f, "double", seq(1, 1000, 0.4))
add.gdsn(f, "character", c("int", "double", "logical", "factor"))

f
# +      [ ]
# |--+ label
# |--+ int  { Int32 10000 ZIP(34.74%) }
# |--+ int.matrix { Int32 100x50 }
# |--+ double { Float64 2498 }
# |--+ character { VStr8 4 }

n1 <- index.gdsn(f, "label")
n2 <- index.gdsn(f, "double")

moveto.gdsn(n1, n2, relpos="after")
f

moveto.gdsn(n1, n2, relpos="before")
f

moveto.gdsn(n1, n2, relpos="replace")
```

```

f

n2 <- index.gdsn(f, "int")
moveto.gdsn(n1, n2, relpos="replace+rename")
f

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

name.gdsn	<i>Return the variable name of a node</i>
-----------	---

Description

Get the variable name of a GDS node.

Usage

```
name.gdsn(node, fullname=FALSE)
```

Arguments

node	an object of class gdsn.class , a GDS node
fullname	if FALSE, return the node name (by default); otherwise the name with a full path

Value

Characters.

Author(s)

Xiuwen Zheng

See Also

[cnt.gdsn](#), [objdesp.gdsn](#), [ls.gdsn](#), [rename.gdsn](#)

Examples

```

# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T","B","C"), z=TRUE))
node <- index.gdsn(f, "list/x")

```

```

name.gdsn(node)
# "x"

name.gdsn(node, fullname=TRUE)
# "list/x"

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

objdesp.gdsn	<i>Variable description</i>
--------------	-----------------------------

Description

Get the description of a GDS node.

Usage

```
objdesp.gdsn(node)
```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
------	---

Value

Returns a list:

name	the variable name of a specified node
fullname	the full name of a specified node
storage	the storage mode in the GDS file
trait	the description of data field, like "Int8"
type	a factor indicating the storage mode in R: Label – a label node, Folder – a directory, VFolder – a virtual folder linking to another GDS file, Raw – raw data (addfile.gdsn), Integer – integers, Factor – factor values, Logical – logical values (FALSE, TRUE and NA), Real – floating numbers, String – characters, Unknown – unknown type
is.array	indicates whether it is array-type
is.sparse	TRUE, if it is a sparse array
dim	the dimension of data field
encoder	encoder for compressed data, such like "ZIP"

compress	the compression method: "", "ZIP.max", etc
cpratio	data compression ratio, NaN indicates no compression
size	the size of data stored in the GDS file
good	logical, indicates the state of GDS file, e.g., FALSE if the virtual folder fails to link the target GDS file
hidden	logical, TRUE if it is a hidden object
message	if applicable, messages of the GDS node, such like error messages, log information
param	the parameters, used in add.gdsn , like "maxlen", "offset", "scale"

Author(s)

Xiuwen Zheng

See Also

[cnt.gdsn](#), [name.gdsn](#), [ls.gdsn](#), [index.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a vector to "test.gds"
node1 <- add.gdsn(f, name="vector1", val=1:10000)
objdesp.gdsn(node1)

# add a vector to "test.gds"
node2 <- add.gdsn(f, name="vector2", val=1:10000, compress="ZIP.max",
  closezip=FALSE)
objdesp.gdsn(node2)

# add a character to "test.gds"
node3 <- add.gdsn(f, name="vector3", val=c("A", "BC", "DEF"),
  compress="ZIP", closezip=TRUE)
objdesp.gdsn(node3)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

openfn.gds	<i>Open a GDS file</i>
------------	------------------------

Description

Open an existing file of CoreArray Genomic Data Structure (GDS) for reading or writing.

Usage

```
openfn.gds(filename, readonly=TRUE, allow.duplicate=FALSE, allow.fork=FALSE,
  allow.error=FALSE, use.abspath=TRUE)
```

Arguments

filename	the file name of a GDS file to be opened
readonly	if TRUE, the file is opened read-only; otherwise, it is allowed to write data to the file
allow.duplicate	if TRUE, it is allowed to open a GDS file with read-only mode when it has been opened in the same R session
allow.fork	TRUE for parallel environment using forking, see details
allow.error	TRUE for data recovery from a crashed GDS file
use.abspath	if TRUE, 'filename' of the gds.class object is set to be the absolute path

Details

This function opens an existing GDS file for reading (or, if `readonly=FALSE`, for writing). To create a new GDS file, use [createfn.gds](#) instead.

If the file is opened read-only, all data in the file are not allowed to be changed, including hierarchical structure, variable names, data fields, etc.

[mclapply](#) and [mcmapply](#) in the R package `parallel` rely on unix forking. However, the forked child process inherits copies of the parent's set of open file descriptors. Each file descriptor in the child refers to the same open file description as the corresponding file descriptor in the parent. This means that the two descriptors share open file status flags, current file offset, and signal-driven I/O attributes. The sharing of file description can cause a serious problem (wrong reading, even program crashes), when child processes read or write the same GDS file simultaneously. `allow.fork=TRUE` adds additional file operations to avoid any conflict using forking. The current implementation does not support writing in forked processes.

Value

Return an object of class [gds.class](#).

filename	the file name to be created
id	internal file id, an integer
root	an object of class gdsn.class , the root of hierarchical structure
readonly	whether it is read-only or not

Author(s)

Xiuwen Zheng

See Also

[createfn.gds](#), [closefn.gds](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, name="list", val=list(x=c(1,2), y=c("T", "B", "C"), z=TRUE))
# close
closefn.gds(f)

# open the same file
f <- openfn.gds("test.gds")

# read
(node <- index.gdsn(f, "list"))
read.gdsn(node)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

permdim.gdsn

Array Transposition

Description

Transpose an array by permuting its dimensions.

Usage

```
permdim.gdsn(node, dimidx, target=NULL)
```

Arguments

node	an object of class gdsn.class , a GDS node
dimidx	the subscript permutation vector, and it should be a permutation of the integers '1:n', where 'n' is the number of dimensions
target	if it is not NULL, the transposed data are saved to target

Value

None.

Author(s)

Xiuwen Zheng

See Also

[setdim.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

(node <- add.gdsn(f, "matrix", val=matrix(1:48, nrow=6),
  compress="ZIP", closezip=TRUE))
read.gdsn(node)

permdim.gdsn(node, c(2,1))
read.gdsn(node)

(node <- add.gdsn(f, "array", val=array(1:120, dim=c(5,4,3,2)),
  compress="ZIP", closezip=TRUE))
read.gdsn(node)

mat <- read.gdsn(node)
permdim.gdsn(node, c(1,2,3,4))
stopifnot(identical(mat, read.gdsn(node)))

mat <- read.gdsn(node)
permdim.gdsn(node, c(4,2,1,3))
stopifnot(identical(aperm(mat, c(4,2,1,3)), read.gdsn(node)))

mat <- read.gdsn(node)
permdim.gdsn(node, c(3,2,4,1))
stopifnot(identical(aperm(mat, c(3,2,4,1)), read.gdsn(node)))

mat <- read.gdsn(node)
permdim.gdsn(node, c(2,3,1,4))
stopifnot(identical(aperm(mat, c(2,3,1,4)), read.gdsn(node)))

# close the GDS file
closefn.gds(f)

# remove unused space after permuting dimensions
cleanup.gds("test.gds")
```

```
# delete the temporary file
unlink("test.gds", force=TRUE)
```

print.gds.class	Show the information of class "gds.class" and "gdsn.class"
-----------------	--

Description

Displays the contents of "gds.class" (a GDS file) and "gdsn.class" (a GDS node).

Usage

```
## S3 method for class 'gds.class'
print(x, path="", show=TRUE, ...)
## S3 method for class 'gdsn.class'
print(x, expand=TRUE, all=FALSE, nmax=Inf, depth=Inf,
      attribute=FALSE, attribute.trim=FALSE, ...)
## S4 method for signature 'gdsn.class'
show(object)
```

Arguments

x	an object of class <code>gds.class</code> , a GDS file; or <code>gdsn.class</code> , a GDS node
object	an object of class <code>gds.class</code> , the number of elements in the preview can be specified via the option <code>getOption("gds.preview.num", 6L)</code> , while 6L is the default value
path	the path specifying a GDS node with '/' as a separator
show	if TRUE, display the preview of array node
expand	whether enumerate all of child nodes
all	if FALSE, hide GDS nodes with an attribute "R.invisible"
nmax	display nodes within the maximum number nmax
depth	display nodes under maximum depth
attribute	if TRUE, show the attribute(s)
attribute.trim	if TRUE, trim the attribute information if it is too long
...	the arguments passed to or from other methods

Value

None.

Author(s)

Xiuwen Zheng

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "int", 1:100)
add.gdsn(f, "int.matrix", matrix(1:(50*100), nrow=100, ncol=50))
put.attr.gdsn(index.gdsn(f, "int.matrix"), "int", 1:10)

print(f, all=TRUE)
print(f, all=TRUE, attribute=TRUE)
print(f, all=TRUE, attribute=TRUE, attribute.trim=FALSE)

show(index.gdsn(f, "int"))
show(index.gdsn(f, "int.matrix"))

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

put.attr.gdsn	<i>Add an attribute into a GDS node</i>
---------------	---

Description

Add an attribute to a GDS node.

Usage

```
put.attr.gdsn(node, name, val=NULL)
```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
name	the name of an attribute
val	the value of an attribute, or a <code>gdsn.class</code> object

Details

Missing values are allowed in a numerical attribute, but not allowed for characters or logical values. Missing characters are converted to "NA", and missing logical values are converted to FALSE.

If `val` is a `gdsn.class` object, copy all attributes to node.

Value

None.

Author(s)

Xiuwen Zheng

See Also[get.attr.gdsn](#), [delete.attr.gdsn](#)**Examples**

```
# create a GDS file
f <- createfn.gds("test.gds")

node <- add.gdsn(f, "int", val=1:10000)
put.attr.gdsn(node, "missing.value", 10000)
put.attr.gdsn(node, "one.value", 1L)
put.attr.gdsn(node, "string", c("ABCDEF", "THIS", paste(letters, collapse="")))
put.attr.gdsn(node, "bool", c(TRUE, TRUE, FALSE))

f
get.attr.gdsn(node)

delete.attr.gdsn(node, "one.value")
get.attr.gdsn(node)

node2 <- add.gdsn(f, "char", val=letters)
get.attr.gdsn(node2)
put.attr.gdsn(node2, val=node)
get.attr.gdsn(node2)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

read.gdsn

*Read data field of a GDS node***Description**

Get data from a GDS node.

Usage

```
read.gdsn(node, start=NULL, count=NULL,
  simplify=c("auto", "none", "force"), .useraw=FALSE, .value=NULL,
  .substitute=NULL, .sparse=TRUE)
```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
start	a vector of integers, starting from 1 for each dimension component
count	a vector of integers, the length of each dimension. As a special case, the value "-1" indicates that all entries along that dimension should be read, starting from start
simplify	if "auto", the result is collapsed to be a vector if possible; "force", the result is forced to be a vector
.useraw	use R RAW storage mode if integers can be stored in a byte, to reduce memory usage
.value	a vector of values to be replaced in the original data array, or NULL for nothing
.substitute	a vector of values after replacing, or NULL for nothing; <code>length(.substitute)</code> should be one or <code>length(.value)</code> ; if <code>length(.substitute) = length(.value)</code> , it is a mapping from .value to .substitute
.sparse	only applicable for the sparse array nodes, if TRUE and it is a vector or matrix, return a <code>Matrix::dgCMatrix</code> object

Details

start, count: the values in data are taken to be those in the array with the leftmost subscript moving fastest.

Value

Return an array, list, or data.frame.

Author(s)

Xiuwen Zheng

See Also

[readex.gdsn](#), [append.gdsn](#), [write.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "vector", 1:128)
add.gdsn(f, "list", list(X=1:10, Y=seq(1, 10, 0.25)))
add.gdsn(f, "data.frame", data.frame(X=1:19, Y=seq(1, 10, 0.5)))
add.gdsn(f, "matrix", matrix(1:12, ncol=4))

f

read.gdsn(index.gdsn(f, "vector"))
read.gdsn(index.gdsn(f, "list"))
```

```

read.gdsn(index.gdsn(f, "data.frame"))

# the effects of 'simplify'
read.gdsn(index.gdsn(f, "matrix"), start=c(2,2), count=c(-1,1))
# [1] 5 6 <- a vector

read.gdsn(index.gdsn(f, "matrix"), start=c(2,2), count=c(-1,1),
  simplify="none")
#      [,1] <- a matrix
# [1,]    5
# [2,]    6

read.gdsn(index.gdsn(f, "matrix"), start=c(2,2), count=c(-1,3))
read.gdsn(index.gdsn(f, "matrix"), start=c(2,2), count=c(-1,3),
  .value=c(12,5), .substitute=NA)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

readex.gdsn

Read data field of a GDS node with a selection

Description

Get data from a GDS node with subset selection.

Usage

```

readex.gdsn(node, sel=NULL, simplify=c("auto", "none", "force"),
  .useraw=FALSE, .value=NULL, .substitute=NULL, .sparse=TRUE)

```

Arguments

node	an object of class <code>gdsn.class</code> , a GDS node
sel	a list of m logical vectors, where m is the number of dimensions of node and each logical vector should have the same size of dimension in node
simplify	if "auto", the result is collapsed to be a vector if possible; "force", the result is forced to be a vector
.useraw	use R RAW storage mode if integers can be stored in a byte, to reduce memory usage
.value	a vector of values to be replaced in the original data array, or NULL for nothing

<code>.substitute</code>	a vector of values after replacing, or NULL for nothing; <code>length(.substitute)</code> should be one or <code>length(.value)</code> ; if <code>length(.substitute) = length(.value)</code> , it is a mapping from <code>.value</code> to <code>.substitute</code>
<code>.sparse</code>	only applicable for the sparse array nodes, if TRUE and it is a vector or matrix, return a <code>Matrix::dgCMatrix</code> object

Details

If `sel` is a list of numeric vectors, the internal method converts the numeric vectors to logical vectors first, extract data with logical vectors, and then call [\[](#) to reorder or expend data.

Value

Return an array.

Author(s)

Xiuwen Zheng

See Also

[read.gdsn](#), [append.gdsn](#), [write.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "vector", 1:128)
add.gdsn(f, "matrix", matrix(as.character(1:(10*6)), nrow=10))
f

# read vector
readex.gdsn(index.gdsn(f, "vector"), sel=rep(c(TRUE, FALSE), 64))
readex.gdsn(index.gdsn(f, "vector"), sel=c(4:8, 1, 2, 12))
readex.gdsn(index.gdsn(f, "vector"), sel=-1:-10)

readex.gdsn(index.gdsn(f, "vector"), sel=c(4, 1, 10, NA, 12, NA))
readex.gdsn(index.gdsn(f, "vector"), sel=c(4, 1, 10, NA, 12, NA),
  .value=c(NA, 1, 12), .substitute=c(6, 7, NA))

# read matrix
readex.gdsn(index.gdsn(f, "matrix"))
readex.gdsn(index.gdsn(f, "matrix"),
  sel=list(rep(c(TRUE, FALSE), 5), rep(c(TRUE, FALSE), 3)))
readex.gdsn(index.gdsn(f, "matrix"), sel=list(NULL, c(1,3,6)))
readex.gdsn(index.gdsn(f, "matrix"),
  sel=list(rep(c(TRUE, FALSE), 5), c(1,3,6)))
readex.gdsn(index.gdsn(f, "matrix"), sel=list(c(1,3,6,10), c(1,3,6)))
readex.gdsn(index.gdsn(f, "matrix"), sel=list(c(-1,-3), -6))
```

```

readex.gdsn(index.gdsn(f, "matrix"), sel=list(c(1,3,NA,10), c(1,3,NA,5)))
readex.gdsn(index.gdsn(f, "matrix"), sel=list(c(1,3,NA,10), c(1,3,NA,5)),
  simplify="force")

readex.gdsn(index.gdsn(f, "matrix"), sel=list(c(1,3,NA,10), c(1,3,NA,5)))
readex.gdsn(index.gdsn(f, "matrix"), sel=list(c(1,3,NA,10), c(1,3,NA,5)),
  .value=NA, .substitute="X")

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)

```

readmode.gdsn	<i>Switch to read mode in the compression settings</i>
---------------	--

Description

Switch to read mode for a GDS node with respect to its compression settings.

Usage

```
readmode.gdsn(node)
```

Arguments

node an object of class `gdsn.class`, a GDS node

Details

After the compressed data field is created, it is in writing mode. Users can add new data to the compressed data field, but can not read data from the data field. Users have to call `readmode.gdsn` to finish writing, before reading any data from the compressed data field.

Once switch to the read mode, users can not add more data to the data field. If users would like to append more data or modify the data field, please call `compression.gdsn(node, compress="")` to decompress data first.

Value

Return node.

Author(s)

Xiuwen Zheng

See Also

[compression.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# common types
n <- add.gdsn(f, "int", val=1:100, compress="ZIP")

# you can not read the variable "int" because of writing mode
# read.gdsn(n)

readmode.gdsn(n)

# now you can read "int"
read.gdsn(n)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

rename.gdsn

Rename a GDS node

Description

Rename a GDS node.

Usage

```
rename.gdsn(node, newname)
```

Arguments

node	an object of class gdsn.class , a GDS node
newname	the new name of a specified node

Details

CoreArray hierarchical structure does not allow duplicate names in the same folder.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[name.gdsn](#), [ls.gdsn](#), [index.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")
n <- add.gdsn(f, "old.name", val=1:10)
f

rename.gdsn(n, "new.name")
f

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

setdim.gdsn

Set the dimension of data field

Description

Assign new dimensions to the data field of a GDS node.

Usage

```
setdim.gdsn(node, valdim, permute=FALSE)
```

Arguments

node	an object of class gdsn.class , a GDS node
valdim	the new dimension(s) for the array to be created, which is a vector of length one or more giving the maximal indices in each dimension. The values in data are taken to be those in the array with the leftmost subscript moving fastest. The last entry could be ZERO. If the total number of elements is zero, gdsfmt does not allocate storage space. NA is treated as 0.
permute	if TRUE, the elements are rearranged to preserve their relative positions in each dimension of the array

Value

Returns node.

Author(s)

Xiuwen Zheng

See Also[read.gdsn](#), [write.gdsn](#), [add.gdsn](#), [append.gdsn](#)**Examples**

```
# create a GDS file
f <- createfn.gds("test.gds")

n <- add.gdsn(f, "int", val=1:24)
read.gdsn(n)

setdim.gdsn(n, c(6, 4))
read.gdsn(n)

setdim.gdsn(n, c(8, 5), permute=TRUE)
read.gdsn(n)

setdim.gdsn(n, c(3, 4), permute=TRUE)
read.gdsn(n)

n <- add.gdsn(f, "bit3", val=1:24, storage="bit3")
read.gdsn(n)

setdim.gdsn(n, c(6, 4))
read.gdsn(n)

setdim.gdsn(n, c(8, 5), permute=TRUE)
read.gdsn(n)

setdim.gdsn(n, c(3, 4), permute=TRUE)
read.gdsn(n)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

Description

Enumerate all opened GDS files

Usage

```
showfile.gds(closeall=FALSE, verbose=TRUE)
```

Arguments

closeall	if TRUE, close all GDS files
verbose	if TRUE, show information

Value

A data.frame with the columns "FileName", "ReadOnly" and "State", or NULL if there is no opened gds file.

Author(s)

Xiuwen Zheng

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

add.gdsn(f, "int", val=1:10000)

showfile.gds()

showfile.gds(closeall=TRUE)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

summarize.gdsn

GDS object Summaries

Description

Get the summaries of a GDS node.

Usage

```
summarize.gdsn(node)
```

Arguments

node an object of class `gdsn.class`, a GDS node

Value

A list including

min the minimum value
 max the maximum value
 num_na the number of invalid numbers or NA
 decimal the count of each decimal (integer, 0.1, 0.01, ..., or other)

Author(s)

Xiuwen Zheng

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

n1 <- add.gdsn(f, "x", seq(1, 10, 0.1), storage="float")
n2 <- add.gdsn(f, "y", seq(1, 10, 0.1), storage="double")
n3 <- add.gdsn(f, "int", c(1:100, NA, 112, NA), storage="int")
n4 <- add.gdsn(f, "int8", c(1:100, NA, 112, NA), storage="int8")

summarize.gdsn(n1)
summarize.gdsn(n2)
summarize.gdsn(n3)
summarize.gdsn(n4)

# close the file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

sync.gds

Synchronize a GDS file

Description

Write the data cached in memory to disk.

Usage

```
sync.gds(gdsfile)
```

Arguments

gdsfile An object of class [gds.class](#), a GDS file

Details

For better performance, Data in a GDS file are usually cached in memory. Keep in mind that the new file may not actually be written to disk, until [closefn.gds](#) or [sync.gds](#) is called. Anyway, when R shuts down, all GDS files created or opened would be automatically closed.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[createfn.gds](#), [openfn.gds](#)

Examples

```
options(gds.verbose=TRUE)

# create a GDS file
f <- createfn.gds("test.gds")

node <- add.gdsn(f, "int", val=1:10000)
put.attr.gdsn(node, "missing.value", 10000)
f

sync.gds(f)

get.attr.gdsn(node)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

`system.gds`*Get the parameters in the GDS system*

Description

Get a list of parameters in the GDS system

Usage

```
system.gds()
```

Value

A list including

`num.logical.core`

the number of logical cores

`l1i.cache.size` L1 instruction cache

`l1d.cache.size` L1 data cache

`l2.cache.size` L2 data cache

`l3.cache.size` L3 data cache

`l4.cache.size` L4 data cache if applicable

`compression.encoder`

compression/decompression algorithms

`compiler` information of compiler

`compiler.flag` SIMD instructions supported by the compiler

`class.list` class list in the GDS system

`options` list all options associated with GDS format or package, including `gds.crayon(FALSE` for no stylish terminal output), `gds.parallel` and `gds.verbose`

Author(s)

Xiuwen Zheng

Examples

```
system.gds()
```

unload.gdsn

Unload a GDS node

Description

Unload a specified GDS node.

Usage

```
unload.gdsn(node)
```

Arguments

node an object of class `gdsn.class`, a GDS node

Value

None.

Author(s)

Xiuwen Zheng

See Also

[delete.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

# add a list to "test.gds"
node <- add.gdsn(f, "val", 1:1000)
node

## Not run:
unload.gdsn(node)
node # Error: Invalid GDS node object (it was unloaded or deleted).

## End(Not run)

index.gdsn(f, "val")

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

`write.gdsn`*Write data to a GDS node*

Description

Write data to a GDS node.

Usage

```
write.gdsn(node, val, start=NULL, count=NULL, check=TRUE)
```

Arguments

<code>node</code>	an object of class <code>gdsn.class</code> , a GDS node
<code>val</code>	the data to be written
<code>start</code>	a vector of integers, starting from 1 for each dimension
<code>count</code>	a vector of integers, the length of each dimension
<code>check</code>	if TRUE, a warning will be given when <code>val</code> is character and there are missing values in <code>val</code>

Details

`start`, `count`: The values in data are taken to be those in the array with the leftmost subscript moving fastest.

`start` and `count` should both exist or be missing. If `start` and `count` are both missing, the dimensions and values of `val` will be assigned to the data field.

GDS format does not support missing characters NA, and any NA will be converted to a blank string "".

Value

None.

Author(s)

Xiuwen Zheng

See Also

[append.gdsn](#), [read.gdsn](#), [add.gdsn](#)

Examples

```
# create a GDS file
f <- createfn.gds("test.gds")

#####

n <- add.gdsn(f, "matrix", matrix(1:20, ncol=5))
read.gdsn(n)

write.gdsn(n, val=c(NA, NA), start=c(2, 2), count=c(2, 1))
read.gdsn(n)

#####

n <- add.gdsn(f, "n", val=1:12)
read.gdsn(n)

write.gdsn(n, matrix(1:24, ncol=6))
read.gdsn(n)

write.gdsn(n, array(1:24, c(4,3,2)))
read.gdsn(n)

# close the GDS file
closefn.gds(f)

# delete the temporary file
unlink("test.gds", force=TRUE)
```

Index

* GDS

- add.gdsn, 5
- addfile.gdsn, 9
- addfolder.gdsn, 11
- append.gdsn, 13
- apply.gdsn, 15
- assign.gdsn, 19
- cache.gdsn, 21
- cleanup.gds, 22
- closefn.gds, 23
- clusterApply.gdsn, 24
- cnt.gdsn, 27
- compression.gdsn, 28
- copyto.gdsn, 30
- createfn.gds, 31
- delete.attr.gdsn, 32
- delete.gdsn, 33
- diagnosis.gds, 34
- digest.gdsn, 36
- exist.gdsn, 38
- gds.class, 39
- gdsfmt-package, 3
- gdsn.class, 40
- get.attr.gdsn, 40
- getfile.gdsn, 41
- getfolder.gdsn, 42
- index.gdsn, 43
- is.element.gdsn, 45
- is.sparse.gdsn, 46
- lasterr.gds, 47
- ls.gdsn, 47
- moveto.gdsn, 48
- name.gdsn, 50
- objdesp.gdsn, 51
- openfn.gds, 53
- permdim.gdsn, 54
- print.gds.class, 56
- put.attr.gdsn, 57
- read.gdsn, 58

- readex.gdsn, 60
- readmode.gdsn, 62
- rename.gdsn, 63
- setdim.gdsn, 64
- showfile.gds, 65
- summarize.gdsn, 66
- sync.gds, 67
- system.gds, 69
- unload.gdsn, 70
- write.gdsn, 71

* IO

- gdsfmt-package, 3

* database

- gdsfmt-package, 3

* file

- gdsfmt-package, 3

* interface

- gdsfmt-package, 3

* utilities

- add.gdsn, 5
- addfile.gdsn, 9
- addfolder.gdsn, 11
- append.gdsn, 13
- apply.gdsn, 15
- assign.gdsn, 19
- cache.gdsn, 21
- cleanup.gds, 22
- closefn.gds, 23
- clusterApply.gdsn, 24
- cnt.gdsn, 27
- compression.gdsn, 28
- copyto.gdsn, 30
- createfn.gds, 31
- delete.attr.gdsn, 32
- delete.gdsn, 33
- diagnosis.gds, 34
- digest.gdsn, 36
- exist.gdsn, 38
- gds.class, 39

- gdsfmt-package, 3
- gdsn.class, 40
- get.attr.gdsn, 40
- getfile.gdsn, 41
- getfolder.gdsn, 42
- index.gdsn, 43
- is.element.gdsn, 45
- is.sparse.gdsn, 46
- lasterr.gds, 47
- ls.gdsn, 47
- moveto.gdsn, 48
- name.gdsn, 50
- objdesp.gdsn, 51
- openfn.gds, 53
- permdim.gdsn, 54
- print.gds.class, 56
- put.attr.gdsn, 57
- read.gdsn, 58
- readex.gdsn, 60
- readmode.gdsn, 62
- rename.gdsn, 63
- setdim.gdsn, 64
- showfile.gds, 65
- summarize.gdsn, 66
- sync.gds, 67
- system.gds, 69
- unload.gdsn, 70
- write.gdsn, 71
- [, 61
- add.gdsn, 5, 10, 11, 14, 27, 30, 34, 40, 44, 46, 49, 52, 59, 61, 63, 65, 71
- addfile.gdsn, 7, 9, 11, 41, 51
- addfolder.gdsn, 7, 11
- append.gdsn, 7, 13, 19, 20, 59, 61, 65, 71
- apply.gdsn, 15, 20, 25
- assign.gdsn, 19
- cache.gdsn, 21
- cleanup.gds, 22
- closefn.gds, 23, 23, 24, 31, 32, 39, 54, 68
- clusterApply.gdsn, 16, 24
- cnt.gdsn, 27, 44, 48, 50, 52
- compression.gdsn, 7, 28, 63
- copyto.gdsn, 30
- createfn.gds, 23, 24, 31, 39, 49, 53, 54, 68
- delete.attr.gdsn, 32, 40, 58
- delete.gdsn, 27, 33, 44, 70
- diagnosis.gds, 34
- digest.gdsn, 36
- exist.gdsn, 38
- gds.class, 5, 9, 11, 23, 30, 32, 35, 39, 43, 53, 56, 68
- gdsfmt (gdsfmt-package), 3
- gdsfmt-package, 3
- gdsn.class, 5–7, 9–11, 13, 15, 16, 19, 21, 27, 28, 30, 32, 33, 35, 36, 38–40, 40, 41–47, 49–51, 53, 54, 56, 57, 59, 60, 62–64, 67, 70, 71
- get.attr.gdsn, 33, 40, 58
- getfile.gdsn, 10, 41
- getfolder.gdsn, 42
- index.gdsn, 7, 27, 38, 43, 43, 48, 49, 52, 64
- is.element.gdsn, 45
- is.sparse.gdsn, 46
- lasterr.gds, 47
- ls.gdsn, 27, 38, 44, 47, 48, 50, 52, 64
- mclapply, 53
- mcmapply, 53
- moveto.gdsn, 30, 48
- name.gdsn, 44, 50, 52, 64
- objdesp.gdsn, 27, 48, 50, 51
- openfn.gds, 23, 24, 32, 39, 49, 53, 68
- parallel, 25
- permdim.gdsn, 54
- print.gds.class, 56
- print.gdsn.class (print.gds.class), 56
- put.attr.gdsn, 33, 40, 57
- read.gdsn, 7, 14, 16, 20, 22, 40, 45, 58, 61, 65, 71
- readex.gdsn, 7, 16, 20, 59, 60
- readmode.gdsn, 7, 30, 62
- rename.gdsn, 50, 63
- setdim.gdsn, 19, 55, 64
- show.gdsn.class-method (print.gds.class), 56
- showfile.gds, 65
- summarize.gdsn, 66

sync.gds, [24](#), [31](#), [67](#), [68](#)

system.gds, [69](#)

unload.gdsn, [70](#)

write.gdsn, [7](#), [14](#), [20](#), [40](#), [59](#), [61](#), [65](#), [71](#)