

Package ‘klassR’

January 15, 2024

Type Package

Title Classifications and Codelists for Statistics Norway

Version 0.2.3

Description Functions to search, retrieve and apply classifications and codelists using Statistics Norway's API <<https://www.ssb.no/klass>> from the system 'KLASS'. Retrieves classifications by date with options to choose language, hierarchical level and formatting.

Imports tm, httr, jsonlite

URL <https://statisticsnorway.github.io/klassR/>

BugReports <https://github.com/statisticsnorway/klassR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.0

Suggests rmarkdown, knitr, testthat (>= 3.0.0), kableExtra, magrittr

Config/testthat/edition 3

NeedsCompilation no

Author Susie Jentoft [aut, cre],
Diana-Cristina Iancu [aut],
Lisa Li [aut],
Statistics Norway [cph]

Maintainer Susie Jentoft <susie.jentoft@ssb.no>

Repository CRAN

Date/Publication 2024-01-15 13:30:02 UTC

R topics documented:

ApplyKlass	2
CorrespondList	3

GetFamily	4
GetKlass	4
GetName	5
GetVersion	6
klassdata	7
ListFamily	7
ListKlass	8
SearchKlass	8

Index	10
--------------	-----------

ApplyKlass	<i>Match and convert a classification</i>
------------	---

Description

Match and convert a classification

Usage

```
ApplyKlass(
  x,
  klass,
  date = NULL,
  variant = NULL,
  correspond = NULL,
  language = "nb",
  output_level = NULL,
  output = "name",
  format = TRUE
)
```

Arguments

x	Input vector
klass	Classification number
date	Date for classification (format = "YYYY-mm-dd"). Default is current date
variant	The classification variant to fetch (if a variant is wanted).
correspond	ID number for target in correspondence table. For correspondence between two dates within the same classification, use correspond = TRUE.
language	Default "nb" for Norwegian (Bokmål). Also "nn" (Nynorsk) and "en" (English available for some classifications)
output_level	Desired output level
output	String describing output. May be "name" (default), "code" or "both".
format	Logical for whether to run formatting on input vector x (Default = TRUE), important to check if formatting is in one level.

Value

A vector or data frame is returned with names and/or code of the desired output level.

Examples

```
data(klassdata)
kommune_names <- ApplyKlass(x = klassdata$kommune, klass = 131, language = "en", format=FALSE)
```

CorrespondList	<i>Correspondence list Print a list of correspondence tables for a given class with source and target IDs</i>
----------------	---

Description

Correspondence list Print a list of correspondence tables for a given class with source and target IDs

Usage

```
CorrespondList(klass, date = NULL)
```

Arguments

klass	Classification number
date	Date for classification (format = "YYYY-mm-dd"). Default is current date

Value

Data frame with list of correspondence tables, source ID and target ID.

Examples

```
CorrespondList("7")
```

GetFamily*Identify corresponding family from a classification number*

Description

Identify corresponding family from a classification number

Usage

```
GetFamily(klass)
```

Arguments

klass Classification number

Value

Family number

Examples

```
GetFamily(klass = 7)
```

GetKlass*Fetch classification data Fetch Statistics Norway classification data using API*

Description

Fetch classification data Fetch Statistics Norway classification data using API

Usage

```
GetKlass(  
  klass,  
  date = NULL,  
  correspond = NULL,  
  correspondID = NULL,  
  variant = NULL,  
  output_level = NULL,  
  language = "nb",  
  output_style = "normal",  
  notes = FALSE,  
  quiet = TRUE  
)
```

Arguments

klass	Number/string of the classification ID/number. (use <code>Klass_list()</code> to find this)
date	String for the required date of the classification. Format must be "yyyy-mm-dd". For an interval, provide two dates as a vector. If blank, will default to today's date.
correspond	Number/string of the target class for correspondence table (if a correspondence table is requested).
correspondID	ID number of the correspondence table to retrieve. Use as an alternative to <code>correspond</code> .
variant	The classification variant to fetch (if a variant is wanted).
output_level	Number/string specifying the requested hierarchy level (optional).
language	Two letter string for the requested language output. Default is Bokmål ("nb"). Nynorsk ("nn") and English ("en") also available for some classification.)
output_style	String variable for the output type. Default is "normal". Specify "wide" for a wide formatted table output.
notes	Logical for if notes should be returned as a column. Default FALSE
quiet	Logical for whether to suppress the printing of the API address. Default TRUE.

Value

The function returns a data frame of the specified classification/correspondence table. Output variables include: `code`, `parentCode`, `level`, and `name` for standard lists. For correspondence tables variables include: `sourceCode`, `sourceName`, `targetCode` and `targetName`. For time correspondence tables variables include: `oldCode`, `oldName`, `newCode` and `newName`. For "wide" output, `code` and `name` with level suffixes is specified.

Examples

```
# Get classification for occupation classifications
head(GetKlass(klass = "7"))
# Get classification for occupation classifications in English
head(GetKlass(klass = "7", language = "en"))
```

GetName

Get the name of a classification version

Description

Get the name of a classification version

Usage

```
GetName(version)
```

Arguments

version Version number

Value

string or vector of strings with name of version

Examples

```
GetName("33")
```

GetVersion

Get version number of a class given a date

Description

Get version number of a class given a date

Usage

```
GetVersion(klass = NULL, date = NULL, family = NULL, klassNr = FALSE)
```

Arguments

klass Classification number
date Date for version to be valid
family Family ID number if a list of version number for all classes is desired
klassNr True/False for whether to output classification numbers. Default = FALSE

Value

Number, vector or data frame with version numbers and classification numbers if specified.

Examples

```
GetVersion(7)
```

klassdata	<i>Testdata for klassR package</i>
-----------	------------------------------------

Description

A dataset containing variables for testing of Statistics Norways classification API with the klassR package. Some observations are missing or incorrect for testing and demonstrations.

Usage

```
klassdata
```

Format

A data frame containing 100 rows and 7 variables:

ID Identification number

sex 1/2 variable for sex

education 4-digit number for education standard ISCED97 (level and subject area) NUS (klass = 66) 2015.01.01

kommune 4-digit code for Norwegian municipality (klass = 131). Based on 2015.01.01

kommune2 Numeric variable for Norwegian municipality with dropped leading zero's for testing (klass = 131). Based on 2015.01.01

nace5 5-digit code for industry (NACE). Based on 01.01.2015 standard industry codes (klass = 7)

occupation 4-digit occupation codes using standard for STYRK-08 (klass = 7) 2015.01.01

ListFamily	<i>Classification family list Print a list of all families and the number of classifications in each</i>
------------	--

Description

Classification family list Print a list of all families and the number of classifications in each

Usage

```
ListFamily(family = NULL, codelists = FALSE, language = "nb")
```

Arguments

family Input family ID number to get a list of classifications in that family

codelists True/False for whether to include codelists. Default = FALSE

language Two letter string for the requested language output. Default is Bokmål ("nb"). Nynorsk ("nn") and English ("en").

Value

dataset containing a list of families

Examples

```
ListFamily(family = 1)
```

ListKlass

Classification list Get a full list of all classifications and codelists

Description

Classification list Get a full list of all classifications and codelists

Usage

```
ListKlass(codelists = FALSE, language = "nb")
```

Arguments

`codelists` True/False for whether to include codelists. Default = FALSE

`language` Two letter string for the requested language output. Default is Bokmål ("nb"). Nynorsk ("nn") and English ("en").

Value

A data frame containing a full list of classifications. The data frame includes the classification name, number, family and type.

Examples

```
head(ListKlass(codelists = TRUE))
```

SearchKlass

Search Klass

Description

Search Klass

Usage

```
SearchKlass(query, codelists = FALSE, size = 20)
```


Arguments

query	String with key word to search for
codelists	True/False for whether to include codelists. Default = FALSE
size	The number of results to show. Default = 20.

Value

Data frame of possible classifications that match the query

Examples

```
SearchKlass("occupation")
```

Index

* datasets

klassdata, 7

ApplyClass, 2

CorrespondList, 3

GetFamily, 4

GetClass, 4

GetName, 5

GetVersion, 6

klassdata, 7

ListFamily, 7

ListClass, 8

SearchClass, 8