

Package ‘ncdfCF’

September 13, 2025

Type Package

Title Easy Access to NetCDF Files with CF Metadata Conventions

Version 0.7.0

Description Network Common Data Form ('netCDF') files are widely used for scientific data. Library-level access in R is provided through packages 'RNetCDF' and 'ncdf4'. Package 'ncdfCF' is built on top of 'RNetCDF' and makes the data and its attributes available as a set of R6 classes that are informed by the Climate and Forecasting Metadata Conventions. Access to the data uses standard R subsetting operators and common function forms.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports abind, Cftime (>= 1.7), methods, R6, RNetCDF, stringr

Collate 'AOI.R' 'AOImethod.R' 'CFAuxiliaryLongLat.R' 'CFAxis.R' 'CFAxisCharacter.R' 'CFAxisDiscrete.R' 'CFAxisLatitude.R' 'CFAxisLongitude.R' 'CFAxisNumeric.R' 'CFAxisTime.R' 'CFAxisVertical.R' 'CFBounds.R' 'CFCellMeasure.R' 'CFDataset.R' 'CFGridMapping.R' 'CFLabel.R' 'NCObject.R' 'CFObject.R' 'CFResource.R' 'CFStandardNames.R' 'CFVariable.R' 'CFVariableL3b.R' 'CFVerticalParametricTerm.R' 'NCDimension.R' 'NCGroup.R' 'NCVariable.R' 'makeCFObjects.R' 'ncdfCF-package.R' 'ops.R' 'readCF.R' 'utils.R' 'wkt2.R' 'zzz.R'

Suggests data.table, knitr, rmarkdown, terra, testthat (>= 3.0.0), units

VignetteBuilder knitr

Depends R (>= 4.0)

URL <https://github.com/R-CF/ncdfCF>

BugReports <https://github.com/R-CF/ncdfCF/issues>

Config/testthat/edition 3

Config/Needs/website rmarkdown

NeedsCompilation no

Author Patrick Van Laake [aut, cre, cph]

Maintainer Patrick Van Laake <patrick@vanlaake.net>

Repository CRAN

Date/Publication 2025-09-13 13:20:02 UTC

Contents

aoi	3
as_CF	4
CFAuxiliaryLongLat	5
CFAxis	7
CFAxisCharacter	12
CFAxisDiscrete	15
CFAxisLatitude	18
CFAxisLongitude	20
CFAxisNumeric	22
CFAxisTime	26
CFAxisVertical	29
CFBounds	33
CFCellMeasure	35
CFDataset	37
CFGridMapping	40
CFLabel	42
CFObject	44
CFResource	48
CFStandardNames	49
CFVariable	51
CFVariableL3b	58
CFVerticalParametricTerm	60
dim.AOI	62
dim.CFAxis	63
makeAxis	63
makeCharacterAxis	64
makeDiscreteAxis	65
makeLatitudeAxis	65
makeLongitudeAxis	66
makeTimeAxis	66
makeVerticalAxis	67
names.CFDataset	67
NCDimension	68
NCGroup	70
NCOBJECT	75
NCVariable	77
open_ncdf	79
Ops.CFVariable	80

<i>aoi</i>	3
peek_ncdf	81
str.CFAxis	82
str.CFDataset	82
[.CFVariable	83
[.CFVariableL3b	84
[[.CFDataset	85
Index	87

<i>aoi</i>	<i>Area of Interest</i>
------------	-------------------------

Description

This function constructs the area of interest of an analysis. It consists of an extent and a resolution of longitude and latitude, all in decimal degrees.

The AOI is used to define the subset of data to be extracted from a data variable that has an auxiliary longitude-latitude grid (see the [CFAuxiliaryLongLat](#) class) at a specified resolution. The data variable thus has a primary coordinate system where the horizontal components are not a geographic system of longitude and latitude coordinates.

Usage

```
aoi(lonMin, lonMax, latMin, latMax, resX, resY)
```

Arguments

lonMin, lonMax, latMin, latMax	The minimum and maximum values of the longitude and latitude of the AOI, in decimal degrees. The longitude values must agree with the range of the longitude in the data variable to which this AOI will be applied, e.g. [-180, 180] or [0, 360].
resX, resY	The separation between adjacent grid cell, in the longitude and latitude directions respectively, in decimal degrees. The permitted values lie within the range [0.01 . . . 10]. If resY is missing it will use the value of resX, yielding square grid cells.

Details

Following the CF Metadata Conventions, axis coordinates represent the center of grid cells. So when specifying `aoi(20, 30, -10, 10, 1, 2)`, the south-west grid cell coordinate is at (20.5, -9). If the axes of the longitude-latitude grid have bounds, then the bounds will coincide with the AOI and the `CFVariable$subset()` method that uses the AOI will attach those bounds as attributes to the resulting array.

If no resolution is specified, it will be determined from the separation between adjacent grid cells in both longitude and latitude directions in the middle of the area of interest. If no extent is specified (meaning, none of the values; if some but not all values are specified an error will be thrown),

then the whole extent of the variable is used, extended outwards by the bounds if they are set or half the resolution otherwise. Thus, to get the entire extent of the variable but in a longitude-latitude grid and with a resolution comparable to the resolution at the original Cartesian coordinate system of the variable, simply pass `aoi()` as an argument to `CFVariable$subset()`. Note that any missing arguments are calculated internally and stored in the returned object, but only after the call to `CFVariable$subset()`.

Caching:

In data collections that are composed of multiple data variables in a single netCDF resource, a single auxiliary longitude-latitude grid may be referenced by multiple data variables, such as in **ROMS** data which may have dozens of data variables using a shared grid. When subsetting with an AOI, the instance of this class is cached to improve performance. The successive calls to `CFVariable$subset()` should use the same object returned from a single call to this function for this caching to work properly.

Value

The return value of the function is an R6 object which uses reference semantics. Making changes to the returned object will be visible in all copies made of the object.

Examples

```
(aoi <- aoi(20, 60, -40, -20, 0.5))
```

as_CF

Create a CFVariable instance from an R object

Description

With this function you can convert an R object into a `CFVariable`. This can be an array, matrix or vector of type logical, integer, numeric or character.

Usage

```
as_CF(name, values)
```

Arguments

name	The name of the CFVariable to create.
values	The data of this object. This can be an array, matrix or vector of type logical, integer, numeric or character.

Details

Dimnames on the R object will be converted to instances of a [CFAxis](#) descendant class, depending on their values. If the dimnames along a dimension of the R object can be converted to numeric, then it will be an instance of [CFAxisNumeric](#). If the dimnames are character, a first attempt is made to create a [CFAxisTime](#) (i.e. the dimnames have to represent timestamps), failing that a [CFAxisCharacter](#) will be created. If no dimnames are set, an instance of [CFAxisDiscrete](#) is generated.

The axes of the `CFVariable` are oriented as in the R object. Note that this is different from standard practice in the netCDF community and the portability of saved datasets is thus limited. You can improve this situation by setting the orientation of the axes and by adding attributes.

After creation of the `CFVariable`, it is recommended to set other properties, such as attributes or a coordinate reference system.

Value

An instance of class [CFVariable](#).

CFAuxiliaryLongLat	<i>CF auxiliary longitude-latitude variable</i>
--------------------	---

Description

This class represents the longitude and latitude variables that compose auxiliary coordinate variable axes for X-Y grids that are not longitude-latitude.

The class provides access to the data arrays for longitude and latitude from the netCDF resource, as well as all the details that have been associated with both axes. Additionally, this class can generate the index to extract values on a long-lat grid of the associated X-Y grid data variable using a user-selectable extent and resolution.

Auxiliary longitude-latitude grids are only supported for reading from a netCDF resource. Creating an instance of this class manually therefore has no practical purpose.

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`name` (read-only) The name of the auxiliary lon-lat grid.

`grid_names` (read-only) Read the names of the longitude and latitude grid as a vector of length 2.

`dimids` (read-only) Retrieve the dimension ids used by the longitude and latitude grids.

`aoi` Set or retrieve the AOI for the long-lat grid.

`lon` (read-only) Retrieve the longitude grid.

`lat` (read-only) Retrieve the latitude grid.

`lon_bounds` (read-only) Retrieve the boundary values of the longitude grid.

`lat_bounds` (read-only) Retrieve the boundary values of the latitude grid.

extent (read-only) Retrieve the extent of the longitude and latitude grids, including bounds if they have been set. The extent is reported as a numeric vector of the four elements minimum and maximum longitude and minimum and maximum latitude.

dim (read-only) The dimensions of the longitude and latitude grids.

Methods

Public methods:

- `CFAuxiliaryLongLat$new()`
- `CFAuxiliaryLongLat$print()`
- `CFAuxiliaryLongLat$brief()`
- `CFAuxiliaryLongLat$sample_index()`
- `CFAuxiliaryLongLat$grid_index()`
- `CFAuxiliaryLongLat$clear_cache()`
- `CFAuxiliaryLongLat$detach()`
- `CFAuxiliaryLongLat$clone()`

Method `new()`: Creating a new instance. It should normally not be useful to create an instance of this class other than upon reading a netCDF resource.

Usage:

```
CFAuxiliaryLongLat$new(varLong, varLat, boundsLong = NULL, boundsLat = NULL)
```

Arguments:

`varLong`, `varLat` The [CFVariable](#) instances with the longitude and latitude grid values, respectively.

`boundsLong`, `boundsLat` The [CFBounds](#) instances of the grid cells for the longitude and latitude, respectively, if set. Defaults to NULL.

Method `print()`: Summary of the auxiliary longitude-latitude variable printed to the console.

Usage:

```
CFAuxiliaryLongLat$print()
```

Method `brief()`: Some details of the auxiliary longitude-latitude grid.

Usage:

```
CFAuxiliaryLongLat$brief()
```

Returns: A 2-row data.frame with some details of the grid components.

Method `sample_index()`: Return the indexes into the X (longitude) and Y (latitude) axes of the original data grid of the points closest to the supplied longitudes and latitudes, up to a maximum distance.

Usage:

```
CFAuxiliaryLongLat$sample_index(x, y, maxDist = NULL)
```

Arguments:

`x`, `y` Vectors of longitude and latitude values in decimal degrees, respectively.

maxDist Numeric value in decimal degrees of the maximum distance between the sampling point and the closest grid cell. If omitted (default), the distance is calculated from the nominal resolution of the grids.

Returns: A matrix with two columns X and Y and as many rows as arguments x and y. The X and Y columns give the index into the grid of the sampling points, or c(NA, NA) is no grid point is located within the maxDist distance from the sampling point.

Method `grid_index()`: Compute the indices for the AOI into the data grid.

Usage:

`CFAuxiliaryLongLat$grid_index()`

Returns: An integer matrix with the dimensions of the AOI, where each grid cell gives the linear index value into the longitude and latitude grids.

Method `clear_cache()`: Clears the cache of pre-computed grid index values if an AOI has been set.

Usage:

`CFAuxiliaryLongLat$clear_cache()`

Method `detach()`: Detach the latitude and longitude from an underlying netCDF resource.

Usage:

`CFAuxiliaryLongLat$detach()`

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`CFAuxiliaryLongLat$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

CFAxis

CF axis object

Description

This class is a basic ancestor to all classes that represent CF axes. More useful classes use this class as ancestor.

This super-class does manage the "coordinates" of the axis, i.e. the values along the axis. This could be the values of the axis as stored on file, but it can also be the values from an auxiliary coordinate set, in the form of a [CFLabel](#) instance. The coordinate set to use in display, selection and processing is selectable through methods and fields in this class.

Super class

`ncdfCF::CFObject` -> CFAxis

Active bindings

- `friendlyClassName` (read-only) A nice description of the class.
- `dimid` The netCDF dimension id of this axis. Setting this value to anything other than the correct value will lead to disaster.
- `length` (read-only) The declared length of this axis.
- `orientation` Set or retrieve the orientation of the axis, a single character with a value of "X", "Y", "Z", "T". Setting the orientation of the axis should only be done when the current orientation is unknown. Setting a wrong value may give unexpected errors in processing of data variables.
- `values` (read-only) Retrieve the raw values of the axis. In general you should use the `coordinates` field rather than this one.
- `coordinates` (read-only) Retrieve the coordinate values of the active coordinate set from the axis.
- `bounds` Set or retrieve the bounds of this axis as a [CFBounds](#) object. When setting the bounds, the bounds values must agree with the coordinates of this axis.
- `auxiliary` Set or retrieve auxiliary coordinates for the axis. On assignment, the value must be an instance of [CFLabel](#) or a [CFAxis](#) descendant, which is added to the end of the list of coordinate sets. On retrieval, the active [CFLabel](#) or [CFAxis](#) instance or NULL when the active coordinate set is the primary axis coordinates.
- `coordinate_names` (read-only) Retrieve the names of the coordinate sets defined for the axis, as a character vector. The first element in the vector is the name of the axis and it refers to the values of the coordinates as stored in the netCDF file. Following elements refer to auxiliary coordinates.
- `coordinate_range` (read-only) Retrieve the range of the coordinates of the axis as a vector of two values. The mode of the result depends on the sub-type of the axis.
- `active_coordinates` Set or retrieve the name of the coordinate set to use with the axis for printing to the console as well as for processing methods such as `subset()`.
- `unlimited` Logical to indicate if the axis is unlimited.
- `time` (read-only) Retrieve the [CFTime](#) object associated with the axis. Always returns NULL but [CFAxisTime](#) overrides this field.
- `is_parametric` (read-only) Logical flag that indicates if the axis has dimensional coordinates. Always FALSE for all axes except for [CFAxisVertical](#) which overrides this method.

Methods

Public methods:

- [CFAxis\\$new\(\)](#)
- [CFAxis\\$print\(\)](#)
- [CFAxis\\$brief\(\)](#)
- [CFAxis\\$shard\(\)](#)
- [CFAxis\\$peek\(\)](#)
- [CFAxis\\$detach\(\)](#)
- [CFAxis\\$copy_terms\(\)](#)
- [CFAxis\\$configure_terms\(\)](#)
- [CFAxis\\$identical\(\)](#)

- `CFAxis$can_append()`
- `CFAxis$copy()`
- `CFAxis$copy_with_values()`
- `CFAxis$subset()`
- `CFAxis$indexOf()`
- `CFAxis$write()`

Method new(): Create a new CF axis instance from a dimension and a variable in a netCDF resource. This method is called upon opening a netCDF resource by the `initialize()` method of a descendant class suitable for the type of axis.

Creating a new axis is more easily done with the `makeAxis()` function.

Usage:

```
CFAxis$new(
  var,
  values,
  start = 1L,
  count = NA,
  orientation = "",
  attributes = data.frame()
)
```

Arguments:

`var` The name of the axis when creating a new axis. When reading an axis from file, the `NCVariable` object that describes this instance.

`values` Optional. The values of the axis in a vector. Ignored when argument `var` is a `NCVariable` object.

`start` Optional. Integer index where to start reading axis data from file. The index may be `NA` to start reading data from the start.

`count` Optional. Number of elements to read from file. This may be `NA` to read to the end of the data.

`orientation` Optional. The orientation of the axis: "X", "Y", "Z" "T", or "" (default) when not known or relevant.

`attributes` Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument `var` is an `NCVariable` instance, attributes of the axis will be taken from the netCDF resource.

Returns: A basic `CFAxis` object.

Method print(): Prints a summary of the axis to the console. This method is typically called by the `print()` method of descendant classes.

Usage:

```
CFAxis$print(...)
```

Arguments:

`...` Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Returns: `self`, invisibly.

Method `brief()`: Some details of the axis.

Usage:

`CFAxis$brief()`

Returns: A 1-row `data.frame` with some details of the axis.

Method `shard()`: Very concise information on the axis. The information returned by this function is very concise and most useful when combined with similar information from other axes.

Usage:

`CFAxis$shard()`

Returns: Character string with very basic axis information.

Method `peek()`: Retrieve interesting details of the axis.

Usage:

`CFAxis$peek()`

Returns: A 1-row `data.frame` with details of the axis.

Method `detach()`: Detach the axis from its underlying `netCDF` resource, including any dependent CF objects.

Usage:

`CFAxis$detach()`

Returns: Self, invisibly.

Method `copy_terms()`: Copy the parametric terms of a vertical axis. This method is only useful for `CFAxisVertical` instances having a parametric formulation. This stub is here to make the call to this method succeed with no result for the other descendant classes.

Usage:

`CFAxis$copy_terms(from, original_axes, new_axes)`

Arguments:

`from` A `CFAxisVertical` instance that will receive references to the parametric terms.

`original_axes` List of `CFAxis` instances from the CF object that these parametric terms are copied from.

`new_axes` List of `CFAxis` instances to use with the formula term objects.

Returns: NULL

Method `configure_terms()`: Configure the function terms of a parametric vertical axis. This method is only useful for `CFAxisVertical` instances having a parametric formulation. This stub is here to make the call to this method succeed with no result for the other descendant classes.

Usage:

`CFAxis$configure_terms(axes)`

Arguments:

`axes` List of `CFAxis` instances.

Returns: NULL

Method identical(): Tests if the axis passed to this method is identical to self. This only tests for generic properties - class, length and name - with further assessment done in sub-classes.

Usage:

```
CFAxis$identical(axis)
```

Arguments:

axis The CFAxis instance to test.

Returns: TRUE if the two axes are identical, FALSE if not.

Method can_append(): Tests if the axis passed to this method can be appended to self. This only tests for generic properties - class, mode of the values and name - with further assessment done in sub-classes.

Usage:

```
CFAxis$can_append(axis)
```

Arguments:

axis The CFAxis descendant instance to test.

Returns: TRUE if the passed axis can be appended to self, FALSE if not.

Method copy(): Create a copy of this axis. This method is "virtual" in the sense that it does not do anything other than return NULL. This stub is here to make the call to this method succeed with no result for the CFAxis descendants that do not implement this method.

Usage:

```
CFAxis$copy(name = "")
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: NULL

Method copy_with_values(): Create a copy of this axis but using the supplied values. This method is "virtual" in the sense that it does not do anything other than return NULL. This stub is here to make the call to this method succeed with no result for the CFAxis descendants that do not implement this method.

Usage:

```
CFAxis$copy_with_values(name = "", values)
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

values The values to be used with the copy of this axis.

Returns: NULL

Method subset(): Return an axis spanning a smaller coordinate range. This method is "virtual" in the sense that it does not do anything other than return self. This stub is here to make the call to this method succeed with no result for the CFAxis descendants that do not implement this method.

Usage:

```
CFAxis$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis if the `rng` argument is provided.

rng The range of indices whose values from this axis to include in the returned axis. If the value of the argument is `NULL`, return a copy of the axis.

Returns: `NULL`

Method `indexOf()`: Find indices in the axis domain. Given a vector of numerical, timestamp or categorical coordinates `x`, find their indices in the coordinates of the axis.

This is a virtual method. For more detail, see the corresponding method in descendant classes.

Usage:

```
CFAxis$indexOf(x, method = "constant", rightmost.closed = TRUE)
```

Arguments:

x Vector of numeric, timestamp or categorial coordinates to find axis indices for. The timestamps can be either character, `POSIXct` or `Date` vectors. The type of the vector has to correspond to the type of the axis values.

method Single character value of "constant" or "linear".

rightmost.closed Whether or not to include the upper limit. Default is `TRUE`.

Returns: Numeric vector of the same length as `x`.

Method `write()`: Write the axis to a netCDF file, including its attributes.

Usage:

```
CFAxis$write(nc = NULL)
```

Arguments:

nc The handle of the netCDF file opened for writing or a group in the netCDF file. If `NULL`, write to the file or group where the axis was read from (the file must have been opened for writing).

Returns: `Self`, invisibly.

CFAxisCharacter

CF character axis object

Description

This class represent CF axes that use categorical character labels as coordinate values. Note that this is different from a [CFLabel](#), which is associated with an axis but not an axis itself.

This is an extension to the CF Metadata Conventions. As per CF, axes are required to have numerical values, which is relaxed here.

Super classes

```
ncdfCF::CFObject -> ncdfCF::CFAxis -> CFAxisCharacter
```

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`dimnames` (read-only) The coordinates of the axis as a character vector.

Methods**Public methods:**

- `CFAxisCharacter$new()`
- `CFAxisCharacter$brief()`
- `CFAxisCharacter$copy()`
- `CFAxisCharacter$copy_with_values()`
- `CFAxisCharacter$slice()`
- `CFAxisCharacter$subset()`
- `CFAxisCharacter$identical()`
- `CFAxisCharacter$append()`
- `CFAxisCharacter$indexOf()`

Method `new()`: Create a new instance of this class.

Creating a new character axis is more easily done with the `makeCharacterAxis()` function.

Usage:

```
CFAxisCharacter$new(
  var,
  values,
  start = 1L,
  count = NA,
  attributes = data.frame()
)
```

Arguments:

`var` The name of the axis when creating a new axis. When reading an axis from file, the `NCVariable` object that describes this instance.

`values` Optional. The values of the axis in a vector. These must be character values. Ignored when argument `var` is a `NCVariable` object.

`start` Optional. Integer index where to start reading axis data from file. The index may be `NA` to start reading data from the start.

`count` Optional. Number of elements to read from file. This may be `NA` to read to the end of the data.

`attributes` Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument `var` is an `NCVariable` instance, attributes of the axis will be taken from the `netCDF` resource.

Method `brief()`: Some details of the axis.

Usage:

```
CFAxisCharacter$brief()
```

Returns: A 1-row `data.frame` with some details of the axis.

Method `copy()`: Create a copy of this axis. The copy is completely separate from this axis, meaning that the new axis and all of its components are made from new instances. If this axis is backed by a netCDF resource, the copy will retain the reference to the resource.

Usage:

```
CFAxisCharacter$copy(name = "")
```

Arguments:

`name` The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `copy_with_values()`: Create a copy of this axis but using the supplied values. The attributes are copied to the new axis. Boundary values and auxiliary coordinates are not copied. After this operation the attributes of the newly created axes may not be accurate, except for the "actual_range" attribute. The calling code should set, modify or delete attributes as appropriate.

Usage:

```
CFAxisCharacter$copy_with_values(name = "", values)
```

Arguments:

`name` The name for the new axis. If an empty string is passed, will use the name of this axis.

`values` The values to be used with the copy of this axis.

Returns: The newly created axis.

Method `slice()`: Given a range of domain coordinate values, returns the indices into the axis that fall within the supplied range.

Usage:

```
CFAxisCharacter$slice(rng)
```

Arguments:

`rng` A character vector whose extreme (alphabetic) values indicate the indices of coordinates to return.

Returns: An integer vector of length 2 with the lower and higher indices into the axis that fall within the range of coordinates in argument `rng`. Returns NULL if no values of the axis fall within the range of coordinates.

Method `subset()`: Return an axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the `rng` argument.

Usage:

```
CFAxisCharacter$subset(name = "", rng = NULL)
```

Arguments:

`name` The name for the new axis. If an empty string is passed (default), will use the name of this axis.

`rng` The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisCharacter instance covering the indicated range of indices. If the value of the argument `rng` is NULL, return a copy of this axis as the new axis.

Method identical(): Tests if the axis passed to this method is identical to self.

Usage:

CFAxisCharacter\$identical(axis)

Arguments:

axis The CFAxisCharacter instance to test.

Returns: TRUE if the two axes are identical, FALSE if not.

Method append(): Append a vector of values at the end of the current values of the axis.

Usage:

CFAxisCharacter\$append(from)

Arguments:

from An instance of CFAxisCharacter whose values to append to the values of self.

Returns: A new CFAxisCharacter instance with values from self and the from axis appended.

Method indexOf(): Find indices in the axis domain. Given a vector of character strings x, find their indices in the coordinates of the axis.

Usage:

CFAxisCharacter\$indexOf(x, method = "constant", rightmost.closed = TRUE)

Arguments:

x Vector of character strings to find axis indices for.

method Ignored.

rightmost.closed Ignored.

Returns: Numeric vector of the same length as x. Values of x that are not equal to a coordinate of the axis are returned as NA.

CFAxisDiscrete

CF discrete axis object

Description

This class represent discrete CF axes, i.e. those axes whose coordinate values do not represent a physical property. The coordinate values are ordinal values equal to the index into the axis.

Super classes

`ncdfCF::CFObject -> ncdfCF::CFAxis -> CFAxisDiscrete`

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`dimnames` (read-only) The coordinates of the axis as an integer vector, or labels for every axis element if they have been set.

Methods

Public methods:

- [CFAxisDiscrete\\$new\(\)](#)
- [CFAxisDiscrete\\$print\(\)](#)
- [CFAxisDiscrete\\$brief\(\)](#)
- [CFAxisDiscrete\\$copy\(\)](#)
- [CFAxisDiscrete\\$indexOf\(\)](#)
- [CFAxisDiscrete\\$slice\(\)](#)
- [CFAxisDiscrete\\$subset\(\)](#)
- [CFAxisDiscrete\\$append\(\)](#)
- [CFAxisDiscrete\\$write\(\)](#)

Method new(): Create a new instance of this class. The values of this axis are always a sequence, but the sequence may start with any positive value such that the length of this instance falls within the length of the axis on file, if there is one.

Creating a new discrete axis is more easily done with the [makeDiscreteAxis\(\)](#) function.

Usage:

```
CFAxisDiscrete$new(var, start = 1L, count)
```

Arguments:

var The name of the axis when creating a new axis. When reading an axis from file, the [NCVariable](#) object that describes this instance.

start Optional. Integer value that indicates the starting value of this axis. Defaults to 1L.

count Number of elements in the axis.

Method print(): Summary of the axis printed to the console.

Usage:

```
CFAxisDiscrete$print(...)
```

Arguments:

... Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Returns: self, invisibly.

Method brief(): Some details of the axis.

Usage:

```
CFAxisDiscrete$brief()
```

Returns: A 1-row data.frame with some details of the axis.

Method copy(): Create a copy of this axis. The copy is completely separate from this axis, meaning that both this axis and all of its components are made from new instances.

Usage:

```
CFAxisDiscrete$copy(name = "")
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `indexOf()`: Find indices in the axis domain. Given a vector of numerical values `x`, find their indices in the values of the axis. Outside values will be dropped.

Usage:

```
CFAxisDiscrete$indexOf(x, method = "constant", rightmost.closed = TRUE)
```

Arguments:

`x` Vector of numeric values to find axis indices for.

`method` Ignored.

`rightmost.closed` Ignored.

Returns: Numeric vector of the same length as `x`. Values of `x` outside of the range of the values in the axis are returned as NA.

Method `slice()`: Given a range of coordinate values, returns the indices into the axis that fall within the supplied range. If the axis has auxiliary coordinates selected then these will be used for the identification of the indices to return.

Usage:

```
CFAxisDiscrete$slice(rng)
```

Arguments:

`rng` A vector whose extreme values indicate the indices of coordinates to return. The mode of the vector has to be integer or agree with any auxiliary coordinates selected.

Returns: An integer vector of length 2 with the lower and higher indices into the axis that fall within the range of coordinates in argument `rng`. Returns NULL if no (boundary) values of the axis fall within the range of coordinates.

Method `subset()`: Return an axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the `rng` argument.

Usage:

```
CFAxisDiscrete$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

`rng` The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisDiscrete instance covering the indicated range of indices. If the value of the argument is NULL, return a copy of self as the new axis.

Method `append()`: Append a vector of values at the end of the current values of the axis.

Usage:

```
CFAxisDiscrete$append(from)
```

Arguments:

`from` An instance of CFAxisDiscrete whose length to add to this axis.

Returns: A new CFAxisDiscrete instance with a length that is the sum of the lengths of this axis and the from axis.

Method `write()`: Write the axis to a netCDF file, including its attributes, but only if it has an associated NC variable in the file.

Usage:

```
CFAxisDiscrete$write(nc = NULL)
```

Arguments:

`nc` The handle of the netCDF file opened for writing or a group in the netCDF file. If NULL, write to the file or group where the axis was read from (the file must have been opened for writing). If not NULL, the handle to a netCDF file or a group therein.

Returns: Self, invisibly.

CFAxisLatitude	<i>Latitude CF axis object</i>
----------------	--------------------------------

Description

This class represents a latitude axis. Its values are numeric. This class adds some logic that is specific to latitudes, such as their range, orientation and meaning.

Super classes

```
ncdfCF::CFOBJECT -> ncdfCF::CFAxis -> ncdfCF::CFAxisNumeric -> CFAxisLatitude
```

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

Methods

Public methods:

- `CFAxisLatitude$new()`
- `CFAxisLatitude$copy()`
- `CFAxisLatitude$copy_with_values()`
- `CFAxisLatitude$subset()`
- `CFAxisLatitude$append()`

Method `new()`: Create a new instance of this class.

Creating a new latitude axis is more easily done with the `makeLatitudeAxis()` function.

Usage:

```

CFAxisLatitude$new(
  var,
  values,
  start = 1L,
  count = NA,
  attributes = data.frame()
)

```

Arguments:

var The name of the axis when creating a new axis. When reading an axis from file, the [NCVariable](#) object that describes this instance.

values Optional. The values of the axis in a vector. The values have to be numeric within the range (-90, 90) and monotonic. Ignored when argument **var** is a [NCVariable](#) object.

start Optional. Integer index where to start reading axis data from file. The index may be NA to start reading data from the start.

count Optional. Number of elements to read from file. This may be NA to read to the end of the data.

attributes Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument **var** is an [NCVariable](#) instance, attributes of the axis will be taken from the `netCDF` resource.

Method `copy()`: Create a copy of this axis. The copy is completely separate from `self`, meaning that both `self` and all of its components are made from new instances.

Usage:

```
CFAxisLatitude$copy(name = "")
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `copy_with_values()`: Create a copy of this axis but using the supplied values. The attributes are copied to the new axis. Boundary values and auxiliary coordinates are not copied. After this operation the attributes of the newly created axes may not be accurate, except for the "actual_range" attribute. The calling code should set, modify or delete attributes as appropriate.

Usage:

```
CFAxisLatitude$copy_with_values(name = "", values)
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

values The values to be used with the copy of this axis.

Returns: The newly created axis.

Method `subset()`: Return a latitude axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the `rng` argument.

Usage:

```
CFAxisLatitude$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis. If an empty string is passed (default), will use the name of this axis.

rng The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisLatitude instance covering the indicated range of indices. If the value of the argument **rng** is NULL, return a copy of **self** as the new axis.

Method `append()`: Append a vector of values at the end of the current values of the axis. Boundary values are appended as well but if either this axis or the **from** axis does not have boundary values, neither will the resulting axis.

Usage:

`CFAxisLatitude$append(from)`

Arguments:

from An instance of CFAxisLatitude whose values to append to the values of this axis.

Returns: A new CFAxisLatitude instance with values from this axis and the **from** axis appended.

CFAxisLongitude

Longitude CF axis object

Description

This class represents a longitude axis. Its values are numeric. This class is used for axes that represent longitudes. This class adds some logic that is specific to longitudes, such as their range, orientation and their meaning. (In the near future, it will also support selecting data that crosses the 0-360 degree boundary.)

Super classes

`ncdfCF::CFObject -> ncdfCF::CFAxis -> ncdfCF::CFAxisNumeric -> CFAxisLongitude`

Active bindings

friendlyClassName (read-only) A nice description of the class.

Methods

Public methods:

- `CFAxisLongitude$new()`
- `CFAxisLongitude$copy()`
- `CFAxisLongitude$copy_with_values()`
- `CFAxisLongitude$subset()`
- `CFAxisLongitude$append()`

Method `new()`: Create a new instance of this class.

Creating a new longitude axis is more easily done with the `makeLongitudeAxis()` function.

Usage:

```
CFAxisLongitude$new(
  var,
  values,
  start = 1L,
  count = NA,
  attributes = data.frame()
)
```

Arguments:

`var` The name of the axis when creating a new axis. When reading an axis from file, the `NCVariable` object that describes this instance.

`values` Optional. The values of the axis in a vector. The values have to be numeric with the maximum value no larger than the minimum value + 360, and monotonic. Ignored when argument `var` is a `NCVariable` object.

`start` Optional. Integer index where to start reading axis data from file. The index may be NA to start reading data from the start.

`count` Optional. Number of elements to read from file. This may be NA to read to the end of the data.

`attributes` Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument `var` is an `NCVariable` instance, attributes of the axis will be taken from the `netCDF` resource.

Method `copy()`: Create a copy of this axis. The copy is completely separate from `self`, meaning that both `self` and all of its components are made from new instances.

Usage:

```
CFAxisLongitude$copy(name = "")
```

Arguments:

`name` The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `copy_with_values()`: Create a copy of this axis but using the supplied values. The attributes are copied to the new axis. Boundary values and auxiliary coordinates are not copied.

After this operation the attributes of the newly created axes may not be accurate, except for the "actual_range" attribute. The calling code should set, modify or delete attributes as appropriate.

Usage:

```
CFAxisLongitude$copy_with_values(name = "", values)
```

Arguments:

`name` The name for the new axis. If an empty string is passed, will use the name of this axis.

`values` The values to be used with the copy of this axis.

Returns: The newly created axis.

Method `subset()`: Return a longitude axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the `rng` argument.

Usage:

```
CFAxisLongitude$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis. If an empty string is passed (default), will use the name of this axis.

rng The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisLongitude instance covering the indicated range of indices. If the value of the argument **rng** is NULL, return a copy of **self** as the new axis.

Method `append()`: Append a vector of values at the end of the current values of the axis. Boundary values are appended as well but if either this axis or the **from** axis does not have boundary values, neither will the resulting axis.

Usage:

```
CFAxisLongitude$append(from)
```

Arguments:

from An instance of CFAxisLongitude whose values to append to the values of this axis.

Returns: A new CFAxisLongitude instance with values from this axis and the **from** axis appended.

CFAxisNumeric

Numeric CF axis object

Description

This class represents a numeric axis. Its values are numeric. This class is used for axes with numeric values but without further knowledge of their nature. More specific classes descend from this class.

Super classes

```
ncdfCF::CFObject -> ncdfCF::CFAxis -> CFAxisNumeric
```

Active bindings

friendlyClassName (read-only) A nice description of the class.

dimnames (read-only) The coordinates of the axis as a vector. These are by default the values of the axis, but it could also be a set of auxiliary coordinates, if they have been set.

Methods

Public methods:

- [CFAxisNumeric\\$new\(\)](#)
- [CFAxisNumeric\\$print\(\)](#)
- [CFAxisNumeric\\$brief\(\)](#)
- [CFAxisNumeric\\$range\(\)](#)
- [CFAxisNumeric\\$indexOf\(\)](#)
- [CFAxisNumeric\\$slice\(\)](#)
- [CFAxisNumeric\\$copy\(\)](#)
- [CFAxisNumeric\\$copy_with_values\(\)](#)
- [CFAxisNumeric\\$identical\(\)](#)
- [CFAxisNumeric\\$append\(\)](#)
- [CFAxisNumeric\\$subset\(\)](#)

Method new(): Create a new instance of this class.

Creating a new axis is more easily done with the [makeAxis\(\)](#) function.

Usage:

```
CFAxisNumeric$new(
  var,
  values,
  start = 1L,
  count = NA,
  orientation = "",
  attributes = data.frame()
)
```

Arguments:

var The name of the axis when creating a new axis. When reading an axis from file, the [NCVariable](#) object that describes this instance.

values Optional. The values of the axis in a vector. The values have to be numeric with the maximum value no larger than the minimum value + 360, and monotonic. Ignored when argument **var** is a [NCVariable](#) object.

start Optional. Integer index where to start reading axis data from file. The index may be NA to start reading data from the start.

count Optional. Number of elements to read from file. This may be NA to read to the end of the data.

orientation Optional. The orientation of the axis: "X", "Y", "Z" "T", or "" (default) when not known or relevant.

attributes Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument **var** is an [NCVariable](#) instance, attributes of the axis will be taken from the `netCDF` resource.

Method print(): Summary of the axis printed to the console.

Usage:

```
CFAxisNumeric$print(...)
```

Arguments:

... Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Returns: `self`, invisibly.

Method `brief()`: Some details of the axis.

Usage:

`CFAxisNumeric$brief()`

Returns: A 1-row `data.frame` with some details of the axis.

Method `range()`: Retrieve the range of coordinate values in the axis.

Usage:

`CFAxisNumeric$range()`

Returns: A numeric vector with two elements with the minimum and maximum values in the axis, respectively.

Method `indexOf()`: Retrieve the indices of supplied coordinates on the axis. If the axis has boundary values then the supplied coordinates must fall within the boundaries of an axis coordinate to be considered valid.

Usage:

`CFAxisNumeric$indexOf(x, method = "constant", rightmost.closed = TRUE)`

Arguments:

`x` A numeric vector of coordinates whose indices into the axis to extract.

`method` Extract index values without ("constant", the default) or with ("linear") fractional parts.
`rightmost.closed` Whether or not to include the upper limit. This parameter is ignored for this class, it always is TRUE.

Returns: A vector giving the indices in `x` of valid coordinates provided. Values of `x` outside of the range of the coordinates in the axis are returned as NA. If the axis has boundary values, then values of `x` that do not fall on or between the boundaries of an axis coordinate are returned as NA.

Method `slice()`: Given a range of domain coordinate values, returns the indices into the axis that fall within the supplied range. If the axis has bounds, any coordinate whose boundary values fall entirely or partially within the supplied range will be included in the result.

Usage:

`CFAxisNumeric$slice(rng)`

Arguments:

`rng` A numeric vector whose extreme values indicate the indices of coordinates to return.

Returns: An integer vector of length 2 with the lower and higher indices into the axis that fall within the range of coordinates in argument `rng`. Returns NULL if no (boundary) values of the axis fall within the range of coordinates.

Method `copy()`: Create a copy of this axis. The copy is completely separate from `self`, meaning that both `self` and all of its components are made from new instances.

Usage:

```
CFAxisNumeric$copy(name = "")
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `copy_with_values()`: Create a copy of this axis but using the supplied values. The attributes are copied to the new axis. Boundary values and auxiliary coordinates are not copied. After this operation the attributes of the newly created axes may not be accurate, except for the "actual_range" attribute. The calling code should set, modify or delete attributes as appropriate.

Usage:

```
CFAxisNumeric$copy_with_values(name = "", values)
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

values The values to be used with the copy of this axis.

Returns: The newly created axis.

Method `identical()`: Tests if the axis passed to this method is identical to self.

Usage:

```
CFAxisNumeric$identical(axis)
```

Arguments:

axis The CFAxisNumeric or sub-class instance to test.

Returns: TRUE if the two axes are identical, FALSE if not.

Method `append()`: Append a vector of values at the end of the current values of the axis. Boundary values are appended as well but if either this axis or the from axis does not have boundary values, neither will the resulting axis.

Usage:

```
CFAxisNumeric$append(from)
```

Arguments:

from An instance of CFAxisNumeric whose values to append to the values of this axis.

Returns: A new CFAxisNumeric instance with values from this axis and the from axis appended.

Method `subset()`: Return an axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the rng argument.

Usage:

```
CFAxisNumeric$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis. If an empty string is passed (default), will use the name of this axis.

rng The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisNumeric instance covering the indicated range of indices. If the value of the argument rng is NULL, return a copy of this axis as the new axis.

CFAxisTime

*Time axis object***Description**

This class represents a time axis. The functionality is provided by the CFTime class in the CFtime package.

Super classes

```
ncdfCF::CFObject -> ncdfCF::CFAxis -> CFAxisTime
```

Active bindings

friendlyClassName (read-only) A nice description of the class.

time (read-only) Retrieve the CFTime instance that manages the values of this axis.

dimnames (read-only) The coordinates of the axis as a character vector.

Methods**Public methods:**

- CFAxisTime\$new()
- CFAxisTime\$print()
- CFAxisTime\$brief()
- CFAxisTime\$identical()
- CFAxisTime\$copy()
- CFAxisTime\$copy_with_values()
- CFAxisTime\$append()
- CFAxisTime\$indexOf()
- CFAxisTime\$slice()
- CFAxisTime\$subset()
- CFAxisTime\$write()

Method new(): Create a new instance of this class.

Creating a new time axis is more easily done with the `makeTimeAxis()` function.

Usage:

```
CFAxisTime$new(var, values, start = 1L, count = NA, attributes = data.frame())
```

Arguments:

var The name of the axis when creating a new axis. When reading an axis from file, the `NCVariable` object that describes this instance.

values Either the numeric values of this axis, or an instance of CFTime or CFClimatology with bounds set. If these are numeric values, argument var must be a NCVariable.

start Optional. Integer index where to start reading axis data from file. The index may be NA to start reading data from the start.

count Optional. Number of elements to read from file. This may be NA to read to the end of the data.

attributes Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument `var` is an `NCVariable` instance, attributes of the axis will be taken from the `netCDF` resource.

Method `print()`: Summary of the time axis printed to the console.

Usage:

```
CFAxisTime$print(...)
```

Arguments:

... Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Method `brief()`: Some details of the axis.

Usage:

```
CFAxisTime$brief()
```

Returns: A 1-row `data.frame` with some details of the axis.

Method `identical()`: Tests if the axis passed to this method is identical to `self`.

Usage:

```
CFAxisTime$identical(axis)
```

Arguments:

`axis` The `CFAxisTime` instance to test.

Returns: TRUE if the two axes are identical, FALSE if not.

Method `copy()`: Create a copy of this axis. The copy is completely separate from `self`, meaning that both `self` and all of its components are made from new instances.

Usage:

```
CFAxisTime$copy(name = "")
```

Arguments:

`name` The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `copy_with_values()`: Create a copy of this axis but using the supplied values. The attributes are copied to the new axis. Boundary values and auxiliary coordinates are not copied. After this operation the attributes of the newly created axes may not be accurate, except for the "actual_range" attribute. The calling code should set, modify or delete attributes as appropriate.

Usage:

```
CFAxisTime$copy_with_values(name = "", values)
```

Arguments:

`name` The name for the new axis. If an empty string is passed, will use the name of this axis.

values The values to be used with the copy of this axis. This can be a CTime instance, a vector of numeric values, a vector of character timestamps in ISO8601 or UDUNITS format, or a vector of POSIXct or Date values. If not a CTime instance, the values will be converted into a CTime instance using the definition and calendar of this axis.

Returns: The newly created axis.

Method `append()`: Append a vector of time values at the end of the current values of the axis.

Usage:

```
CFAxisTime$append(from)
```

Arguments:

from An instance of CFAxisTime whose values to append to the values of this axis.

Returns: A new CFAxisTime instance with values from this axis and the from axis appended.

Method `indexOf()`: Retrieve the indices of supplied values on the time axis.

Usage:

```
CFAxisTime$indexOf(x, method = "constant", rightmost.closed = FALSE)
```

Arguments:

x A vector of timestamps whose indices into the time axis to extract.

method Extract index values without ("constant", the default) or with ("linear") fractional parts.

rightmost.closed Whether or not to include the upper limit. Default is FALSE.

Returns: A vector giving the indices in the time axis of valid values in x, or NA if the value is not valid.

Method `slice()`: Retrieve the indices of the time axis falling between two extreme values.

Usage:

```
CFAxisTime$slice(x, rightmost.closed = FALSE)
```

Arguments:

x A vector of two timestamps in between of which all indices into the time axis to extract.

rightmost.closed Whether or not to include the upper limit. Default is FALSE.

Returns: An integer vector giving the indices in the time axis between values in x, or integer(0) if none of the values are valid.

Method `subset()`: Return an axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the rng argument.

Usage:

```
CFAxisTime$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis. If an empty string is passed (default), will use the name of this axis.

rng The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisNumeric instance covering the indicated range of indices. If the value of the argument rng is NULL, return a copy of self as the new axis.

Method `write()`: Write the axis to a netCDF file, including its attributes. If the calendar name is "gregorian", it will be set to the functionally identical calendar "standard" as the former is deprecated.

Usage:

```
CFAxisTime$write(nc = NULL)
```

Arguments:

`nc` The handle of the netCDF file opened for writing or a group in the netCDF file. If NULL, write to the file or group where the axis was read from (the file must have been opened for writing). If not NULL, the handle to a netCDF file or a group therein.

Returns: Self, invisibly.

CFAxisVertical

Vertical CF axis object

Description

This class represents a vertical axis, which may be parametric. A regular vertical axis behaves like any other numeric axis. A parametric vertical axis, on the other hand, is defined through an index value that is contained in the axis coordinates, with additional data variables that hold ancillary "formula terms" with which to calculate dimensional axis coordinates. It is used in atmosphere and ocean data sets.

Parametric vertical axes can only be read from file, not created from scratch.

Super classes

```
ncdfCF::CFObject -> ncdfCF::CFAxis -> ncdfCF::CFAxisNumeric -> CFAxisVertical
```

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`formula_terms` (read-only) A data.frame with the "formula_terms" to calculate the parametric axis values.

`is_parametric` (read-only) Logical flag that indicates if the coordinates of the axis are parametric.

`parametric_coordinates` (read-only) Retrieve the parametric coordinates of this vertical axis as a [CFVariable](#).

`computed_name` (read-only) The name of the computed parameterised coordinates. If the parameterised coordinates have not been computed yet the computed name is an empty string.

`computed_units` (read-only) Return the units of the computed parameterised coordinates, if computed, otherwise return NULL. This will access the standard names table.

Methods

Public methods:

- `CFAxisVertical$new()`
- `CFAxisVertical$detach()`
- `CFAxisVertical$copy()`
- `CFAxisVertical$copy_with_values()`
- `CFAxisVertical$set_parametric_terms()`
- `CFAxisVertical$append()`
- `CFAxisVertical$subset()`
- `CFAxisVertical$subset_parametric_terms()`

Method `new()`: Create a new instance of this class.

Usage:

```
CFAxisVertical$new(
  var,
  values,
  start = 1L,
  count = NA,
  attributes = data.frame()
)
```

Arguments:

`var` The name of the axis when creating a new axis. When reading an axis from file, the `NCVariable` object that describes this instance.

`values` Optional. The values of the axis in a vector. The values have to be numeric and monotonic. Ignored when argument `var` is a `NCVariable` object.

`start` Optional. Integer index where to start reading axis data from file. The index may be `NA` to start reading data from the start.

`count` Optional. Number of elements to read from file. This may be `NA` to read to the end of the data.

`attributes` Optional. A `data.frame` with the attributes of the axis. When an empty `data.frame` (default) and argument `var` is an `NCVariable` instance, attributes of the axis will be taken from the `netCDF` resource.

Method `detach()`: Detach the parametric terms from an underlying `netCDF` resource.

Usage:

```
CFAxisVertical$detach()
```

Returns: Self, invisibly.

Method `copy()`: Create a copy of this axis. The copy is completely separate from this instance, meaning that the copies of both this instance and all of its components are made as new instances.

Usage:

```
CFAxisVertical$copy(name = "")
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

Returns: The newly created axis.

Method `copy_with_values()`: Create a copy of this axis but using the supplied values. The attributes are copied to the new axis. Boundary values, parametric coordinates and auxiliary coordinates are not copied.

After this operation the attributes of the newly created axes may not be accurate, except for the "actual_range" attribute. The calling code should set, modify or delete attributes as appropriate.

Usage:

```
CFAxisVertical$copy_with_values(name = "", values)
```

Arguments:

name The name for the new axis. If an empty string is passed, will use the name of this axis.

values The values to be used with the copy of this axis.

Returns: The newly created axis.

Method `set_parametric_terms()`: Set the parametric terms for this axis. The name and the terms have to fully describe a CF parametric vertical axis.

The terms must also agree with the other axes used by any data variable that refers to this axis. That is not checked here so the calling code must make that assertion.

Usage:

```
CFAxisVertical$set_parametric_terms(sn, terms)
```

Arguments:

sn The "standard_name" of the parametric formulation. See the CF documentation for details.

terms A data.frame with columns term, variable and param containing the terms of the formula to calculate the axis values. Column param has the references to the variables that hold the data for each term.

Method `append()`: Append a vector of values at the end of the current values of the axis. Boundary values are appended as well but if either this axis or the from axis does not have boundary values, neither will the resulting axis.

This method is not recommended for parametric vertical axes. Any parametric terms will be deleted. If appending of parametric axes is required, the calling code should first read out the parametric terms and merge them with the parametric terms of the from axis before setting them back for this axis.

Usage:

```
CFAxisVertical$append(from)
```

Arguments:

from An instance of CFAxisVertical whose values to append to the values of this axis.

Returns: A new CFAxisVertical instance with values from this axis and the from axis appended.

Method `subset()`: Return an axis spanning a smaller coordinate range. This method returns an axis which spans the range of indices given by the rng argument. If this axis has parametric terms, these are not subset here - they should be separately treated once all associated axes in the terms have been subset. That happens automatically in CFVariable methods which call the subset_parametric_terms() method.

Usage:

```
CFAxisVertical$subset(name = "", rng = NULL)
```

Arguments:

name The name for the new axis. If an empty string is passed (default), will use the name of this axis.

rng The range of indices whose values from this axis to include in the returned axis. If the value of the argument is NULL, return a copy of the axis.

Returns: A new CFAxisVertical instance covering the indicated range of indices. If the value of the argument rng is NULL, return a copy of this axis as the new axis.

Method subset_parametric_terms(): Subset the parametric terms of this axis.

Usage:

```
CFAxisVertical$subset_parametric_terms(
  original_axis_names,
  new_axes,
  start,
  count,
  aux = NULL,
  ZT_dim = NULL
)
```

Arguments:

original_axis_names Character vector of names of the axes prior to a modifying operation in the owning data variable

new_axes List of CFAxis instances to use for the subsetting.

start The indices to start reading data from the file, as an integer vector at least as long as the number of axis for the term.

count The number of values to read from the file, as an integer vector at least as long as the number of axis for the term.

aux Optional. List with the parameters for an auxiliary grid transformation. Default is NULL.

ZT_dim Optional. Dimensions of the non-grid axes when an auxiliary grid transformation is specified.

Returns: Self, invisibly. The parametric terms will have been subset in this axis.

References

<https://cfconventions.org/Data/cf-conventions/cf-conventions.html#parametric-vertical-coordinate> <https://www.myroms.org/coordinate>

CFBounds	<i>CF boundary variable</i>
----------	-----------------------------

Description

This class represents the boundaries of an axis or an auxiliary longitude-latitude grid.

The class manages the boundary information for an axis (2 vertices per element) or an auxiliary longitude-latitude grid (4 vertices per element).

Super class

`ncdfCF::CFObject` -> CFBounds

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`length` (read-only) The length of the second dimension of the data, i.e. the number of boundary values.

`vertices` (read-only) The length of the first dimension of the data, i.e. the number of vertices that make up a boundary.

`values` Set or retrieve the boundary values of this object. Upon retrieval, values are read from the netCDF resource, if there is one, upon first access and cached thereafter. Upon setting values, if there is a linked netCDF resource, this object will be detached from it.

Methods

Public methods:

- `CFBounds$new()`
- `CFBounds$print()`
- `CFBounds$range()`
- `CFBounds$copy()`
- `CFBounds$subset()`
- `CFBounds$append()`
- `CFBounds$write()`
- `CFBounds$clone()`

Method `new()`: Create an instance of this class.

Usage:

```
CFBounds$new(
  var,
  values,
  start = NA,
  count = NA,
  attributes = data.frame(),
  owner_dims = 1L
)
```

Arguments:

- var** The name of the boundary variable when creating a new boundary variable. When reading a boundary variable from file, the `NCVariable` object that describes this instance.
- values** Optional. The values of the boundary variable. This must be a numeric matrix whose first dimension has a length equal to the number of vertices for each boundary, and the second dimension is as long as the `CFObject` instances that use these boundary values. Ignored when argument **var** is a `NCVariable` object.
- start** Optional. Vector of indices where to start reading boundary data along the dimensions of the data. The vector must be `NA` to read all data, otherwise it must have a length equal to the dimensionality of the owning object + 1.
- count** Optional. Vector of number of elements to read along each dimension of the boundary data. The vector must be `NA` to read to the end of each dimension, otherwise it must have a length equal to the dimensionality of the owning object + 1.
- attributes** Optional. A `data.frame` with the attributes of the boundary object. When an empty `data.frame` (default) and argument **var** is an `NCVariable` instance, attributes of the bounds object will be taken from the `netCDF` resource.
- owner_dims** Optional, the number of dimensions of the object that these boundary values pertain to. Default is 1.

Returns: A new instance of this class.

Method `print()`: Print a summary of the object to the console.

Usage:

```
CFBounds$print(attributes = TRUE, ...)
```

Arguments:

- attributes** Default `TRUE`, flag to indicate if the attributes of the boundary values should be printed.
- ...** Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Method `range()`: Retrieve the lowest and highest value in the bounds.

Usage:

```
CFBounds$range()
```

Method `copy()`: Create a copy of this bounds object The copy is completely separate from `self`, meaning that both `self` and all of its components are made from new instances.

Usage:

```
CFBounds$copy(name = "")
```

Arguments:

- name** The name for the new bounds object. If an empty string is passed, will use the name of this bounds object.

Returns: The newly created bounds object.

Method `subset()`: Return a boundary variable spanning a smaller coordinate range. This currently only applies to 1-D axes.

This method returns boundary values which span the range of indices given by the `rng` argument.

Usage:

```
CFBounds$subset(rng)
```

Arguments:

`rng` The range of values from this bounds object to include in the returned object.

Returns: A CFBounds instance covering the indicated range of indices.

Method `append()`: Append boundary values at the end of the current values of the boundary variable.

Usage:

```
CFBounds$append(from)
```

Arguments:

`from` An instance of CFBounds whose values to append to the values of this boundary variable.

Returns: A new CFBounds instance with values from this boundary variable and the `from` boundary variable appended. If argument `from` is NULL, return NULL.

Method `write()`: Write the boundary variable to a netCDF file. This method should not be called directly; instead, `CFVariable::save()` will call this method automatically.

Usage:

```
CFBounds$write(h, object_name)
```

Arguments:

`h` The handle to a netCDF file open for writing.

`object_name` The name of the object that uses these boundary values, usually an axis but could also be an auxiliary CV or a parametric Z axis.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFBounds$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

CFCellMeasure

CF cell measure variable

Description

This class represents a CF cell measure variable, the object that indicates the area or volume of every grid cell in referencing data variables.

If a cell measure variable is external to the current file, an instance will still be created for it, but the user must link the external file to this instance before it can be used in analysis.

Active bindings

`measure` (read-only) Retrieve the measure of this instance. Either "area" or "volume".

`name` The name of this instance, which must refer to a NC variable or an external variable.

Methods

Public methods:

- [CFCellMeasure\\$new\(\)](#)
- [CFCellMeasure\\$print\(\)](#)
- [CFCellMeasure\\$data\(\)](#)
- [CFCellMeasure\\$register\(\)](#)
- [CFCellMeasure\\$link\(\)](#)
- [CFCellMeasure\\$detach\(\)](#)
- [CFCellMeasure\\$clone\(\)](#)

Method `new()`: Create an instance of this class.

Usage:

```
CFCellMeasure$new(measure, name, nc_var = NULL, axes = NULL)
```

Arguments:

`measure` The measure of this object. Must be either of "area" or "volume".

`name` The name of the cell measure variable. Ignored if argument `nc_var` is specified.

`nc_var` The netCDF variable that defines this CF cell measure object. NULL for an external variable.

`axes` List of [CFAxis](#) instances that describe the dimensions of the cell measure object. NULL for an external variable.

Returns: An instance of this class.

Method `print()`: Print a summary of the cell measure variable to the console.

Usage:

```
CFCellMeasure$print(...)
```

Arguments:

`...` Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Method `data()`: Retrieve the values of the cell measure variable.

Usage:

```
CFCellMeasure$data()
```

Returns: The values of the cell measure as a [CFVariable](#) instance.

Method `register()`: Register a [CFVariable](#) which is using this cell measure variable. A check is performed on the compatibility between the data variable and this cell measure variable.

Usage:

```
CFCellMeasure$register(var)
```

Arguments:

`var` A [CFVariable](#) instance to link to this instance.

Returns: Self, invisibly.

Method `link()`: Link the cell measure variable to an external netCDF resource. The resource will be opened and the appropriate data variable will be linked to this instance. If the axes or other properties of the external resource are not compatible with this instance, an error will be raised.

Usage:

```
CFCellMeasure$link(resource)
```

Arguments:

`resource` The name of the netCDF resource to open, either a local file name or a remote URI.

Returns: Self, invisibly.

Method `detach()`: Detach the internal data variable from an underlying netCDF resource.

Usage:

```
CFCellMeasure$detach()
```

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFCellMeasure$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

CFDataset

CF data set

Description

This class represents a CF data set, the object that encapsulates a netCDF resource. You should never have to instantiate this class directly; instead, call `open_ncdf()` which will return an instance that has all properties read from the netCDF resource. Class methods can then be called, or the base R functions called with this instance.

The CF data set instance provides access to all the objects in the netCDF resource, organized in groups.

Public fields

`name` The name of the netCDF resource. This is extracted from the URI (file name or URL).

`root` Root of the group hierarchy through which all elements of the netCDF resource are accessed. It is **strongly discouraged** to manipulate the objects in the group hierarchy directly. Use the provided access methods instead.

`file_type` The type of data in the netCDF resource, if identifiable. In terms of the CF Metadata Conventions, this includes discrete sampling geometries (DSG). Other file types that can be identified include L3b files used by NASA and NOAA for satellite imagery (these data sets need special processing), and CMIP5, CMIP6 and CORDEX climate projection data.

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`resource` (read-only) The connection details of the netCDF resource. This is for internal use only.

`uri` (read-only) The connection string to the netCDF resource.

`conventions` (read-only) Returns the conventions that this netCDF resource conforms to.

`var_names` (read-only) Vector of names of variables in this data set.

`axis_names` (read-only) Vector of names of axes in this data set.

Methods**Public methods:**

- `CFDataset$new()`
- `CFDataset$print()`
- `CFDataset$hierarchy()`
- `CFDataset$objects_by_standard_name()`
- `CFDataset$has_subgroups()`
- `CFDataset$find_by_name()`
- `CFDataset$variables()`
- `CFDataset$axes()`
- `CFDataset$attributes()`
- `CFDataset$attribute()`
- `CFDataset$clone()`

Method `new()`: Create an instance of this class.

Usage:

```
CFDataset$new(resource, format)
```

Arguments:

`resource` An instance of `CFResource` that links to the netCDF resource.

`format` Character string with the format of the netCDF resource as reported by the call opening the resource.

Method `print()`: Summary of the data set printed to the console.

Usage:

```
CFDataset$print(...)
```

Arguments:

... Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Method `hierarchy()`: Print the group hierarchy to the console.

Usage:

```
CFDataset$hierarchy()
```

Method `objects_by_standard_name()`: Get objects by `standard_name`. Several conventions define standard vocabularies for physical properties. The standard names from those vocabularies are usually stored as the "standard_name" attribute with variables or axes. This method retrieves all variables or axes that list the specified "standard_name" in its attributes.

Usage:

```
CFDataset$objects_by_standard_name(standard_name)
```

Arguments:

`standard_name` Optional, a character string to search for a specific "standard_name" value in variables and axes.

Returns: If argument `standard_name` is provided, a character vector of variable or axis names. If argument `standard_name` is missing or an empty string, a named list with all "standard_name" attribute values in the the netCDF resource; each list item is named for the variable or axis.

Method `has_subgroups()`: Does the netCDF resource have subgroups? Newer versions of the netcdf library, specifically netcdf4, can organize dimensions and variables in groups. This method will report if the data set is indeed organized with subgroups.

Usage:

```
CFDataset$has_subgroups()
```

Returns: Logical to indicate that the netCDF resource uses subgroups.

Method `find_by_name()`: Find an object by its name. Given the name of a CF data variable or axis, possibly preceded by an absolute group path, return the object to the caller.

Usage:

```
CFDataset$find_by_name(name, scope = "CF")
```

Arguments:

`name` The name of a CF data variable or axis, with an optional absolute group path.

`scope` The scope to look for the name. Either "CF" (default) to search for CF variables or axes, or "NC" to look for groups or NC variables.

Returns: The object with the provided name. If the object is not found, returns NULL.

Method `variables()`: This method lists the CF data variables located in this netCDF resource, including those in subgroups.

Usage:

```
CFDataset$variables()
```

Returns: A list of CFVariable instances.

Method `axes()`: This method lists the axes located in this netCDF resource, including axes in subgroups.

Usage:

```
CFDataset$axes()
```

Returns: A list of CFAxis descendants.

Method `attributes()`: List all the attributes of a group. This method returns a `data.frame` containing all the attributes of the indicated group.

Usage:

```
CFDataset$attributes(group)
```

Arguments:

group The name of the group whose attributes to return. If the argument is missing, the global attributes will be returned.

Returns: A `data.frame` of attributes.

Method `attribute()`: Retrieve global attributes of the data set.

Usage:

```
CFDataset$attribute(att, field = "value")
```

Arguments:

att Vector of character strings of attributes to return.

field The field of the attribute to return values from. This must be "value" (default) or "type".

Returns: If the `field` argument is "type", a character string. If `field` is "value", a single value of the type of the attribute, or a vector when the attribute has multiple values. If no attribute is named with a value of argument `att` NA is returned.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFDataset$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

CFGridMapping

CF grid mapping object

Description

This class contains the details for a coordinate reference system, or grid mapping in CF terms, of a data variable.

When reporting the coordinate reference system to the caller, a character string in WKT2 format is returned, following the OGC standard.

Super class

`ncdfCF::CFObject` -> CFGridMapping

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

Methods

Public methods:

- `CFGridMapping$new()`
- `CFGridMapping$print()`
- `CFGridMapping$brief()`
- `CFGridMapping$wkt2()`
- `CFGridMapping$write()`
- `CFGridMapping$clone()`

Method `new()`: Create a new instance of this class.

Note that when a new grid mapping object is created (as opposed to reading from a netCDF resource), only the `grid_mapping_name` attribute will be set. The caller must set all other parameters through their respective attributes, following the CF Metadata Conventions.

Usage:

```
CFGridMapping$new(var, grid_mapping_name)
```

Arguments:

`var` When creating a new grid mapping object, the name of the object. When reading from a netCDF resource, the netCDF variable that describes this instance.

`grid_mapping_name` Optional. When creating a new grid mapping object, the formal name of the grid mapping, as specified in the CF Metadata Conventions. This value is stored in the new object as attribute "grid_mapping_name". Ignored when argument `var` is a NC object.

Method `print()`: Prints a summary of the grid mapping to the console.

Usage:

```
CFGridMapping$print()
```

Method `brief()`: Retrieve a 1-row data.frame with some information on this grid mapping.

Usage:

```
CFGridMapping$brief()
```

Method `wkt2()`: Retrieve the CRS string for a specific variable.

Usage:

```
CFGridMapping$wkt2(axis_info)
```

Arguments:

`axis_info` A list with information that describes the axes of the CFVariable instance to describe.

Returns: A character string with the CRS in WKT2 format.

Method `write()`: Write the CRS object to a netCDF file.

Usage:

```
CFGridMapping$write(h)
```

Arguments:

`h` Handle to the netCDF file opened for writing.

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFGridMapping$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

<https://docs.ogc.org/is/18-010r11/18-010r11.pdf> <https://cfconventions.org/cf-conventions/cf-conventions.html#appendix-grid-mappings>

CFLabel

CF label object

Description

This class represent CF labels, i.e. a variable of character type that provides a textual label for a discrete or general numeric axis. See also [CFAxisCharacter](#), which is an axis with character labels.

Super class

`ncdfCF::CFObject` -> CFLabel

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`coordinates` Set or retrieve the labels of this object. Upon retrieval, label values are read from the netCDF resource, if there is one, upon first access and cached thereafter. Upon setting values, if there is a linked netCDF resource, this object will be detached from it.

`length` (read-only) The number of labels in the set.

`dimid` (read-only) The netCDF dimension id of this label set. This field should only be accessed if the label set is backed by a netCDF resource.

Methods

Public methods:

- `CFLabel$new()`
- `CFLabel$print()`
- `CFLabel$slice()`
- `CFLabel$subset()`
- `CFLabel$write()`
- `CFLabel$clone()`

Method `new()`: Create a new instance of this class.

Usage:

```
CFLabel$new(var, values = NA, start = NA, count = NA)
```

Arguments:

`var` The [NCVariable](#) instance upon which this CF object is based when read from a netCDF resource, or the name for the object new CF object to be created.

`values` Optional. The labels of the CF object. Ignored when argument `var` is a [NCVariable](#) object.

`start` Optional. Integer index value indicating where to start reading data from the file. The value may be NA (default) to read all data, otherwise it must not be larger than the number of labels. Ignored when argument `var` is not an [NCVariable](#) instance.

`count` Optional. Integer value indicating the number of labels to read from file. The value may be NA to read to the end of the labels, otherwise its value must agree with the corresponding `start` value and the number of labels on file. Ignored when argument `var` is not an [NCVariable](#) instance.

Returns: A [CFLabel](#) instance.

Method `print()`: Prints a summary of the labels to the console.

Usage:

```
CFLabel$print(...)
```

Arguments:

`...` Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Method `slice()`: Given a range of domain coordinate values, returns the indices into the axis that fall within the supplied range.

Usage:

```
CFLabel$slice(rng)
```

Arguments:

`rng` A character vector whose extreme (alphabetic) values indicate the indices of coordinates to return.

Returns: An integer vector of length 2 with the lower and higher indices into the axis that fall within the range of coordinates in argument `rng`. Returns NULL if no values of the axis fall within the range of coordinates.

Method `subset()`: Retrieve a subset of the labels.

Usage:

```
CFLabel$subset(name, rng)
```

Arguments:

`name` The name for the new label set, optional.

`rng` The range of indices whose values from this axis to include in the returned axis.

Returns: A [CFLabel](#) instance, or NULL if the `rng` values are invalid.

Method `write()`: Write the labels to a netCDF file, including its attributes.

Usage:

```
CFLabel$write(nc, dim)
```

Arguments:

nc The handle of the netCDF file opened for writing or a group in the netCDF file. If NULL, write to the file or group where the labels were read from (the file must have been opened for writing). If not NULL, the handle to a netCDF file or a group therein.

dim The dimension to write the labels for. This is the name or dimension id of the object that owns these labels. The dimension must have been written to file before this method is called.

Returns: Self, invisibly.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CFLabel$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

CFObject

CF base object

Description

This class is a basic ancestor to all classes that represent CF objects, specifically data variables and axes. More useful classes use this class as ancestor.

Active bindings

friendlyClassName (read-only) A nice description of the class.

id (read-only) Retrieve the identifier of the CF object.

name Set or retrieve the name of the CF object. The name must be a valid netCDF name: start with a character, use only characters, numbers and the underscore, and be at most 255 characters long.

fullname (read-only) The fully-qualified name of the CF object.

group (read-only) Retrieve the [NCGroup](#) that this object is located in.

attributes (read-only) Retrieve a `data.frame` with the attributes of the CF object.

has_resource (read-only) Flag that indicates if this object has an underlying netCDF resource.

NCvar (read-only) The `NCVariable` object that links to an underlying netCDF resource, or NULL if not linked.

data_type Set or retrieve the data type of the data in the object. Setting the data type to a wrong value can have unpredictable but catastrophic consequences.

ndims (read-only) Retrieve the dimensionality of the data in the array, or the netCDF resource.

array_indices Returns a list with columns "start" and "count" giving the indices for reading the data of this object from a netCDF resource.

Methods

Public methods:

- `CFObjec$new()`
- `CFObjec$detach()`
- `CFObjec$dim()`
- `CFObjec$attribute()`
- `CFObjec$print_attributes()`
- `CFObjec$set_attribute()`
- `CFObjec$append_attribute()`
- `CFObjec$delete_attribute()`
- `CFObjec$write_attributes()`
- `CFObjec$update_coordinates_attribute()`
- `CFObjec$clone()`

Method `new()`: Create a new `CFObjec` instance from a variable in a netCDF resource. This method is called upon opening a netCDF resource. It is rarely, if ever, useful to call this constructor directly. Instead, use the methods from higher-level classes such as [CFVariable](#).

Usage:

```
CFObjec$new(var, values, start = 1L, count = NA, attributes = data.frame())
```

Arguments:

`var` The [NCVariable](#) instance upon which this CF object is based when read from a netCDF resource, or the name for the new CF object to be created.

`values` Optional. The values of the object in an array.

`start` Optional. Vector of indices where to start reading data along the dimensions of the array on file. The vector must be NA to read all data, otherwise it must agree with the dimensions of the array on file. Ignored when argument `var` is not an [NCVariable](#) instance.

`count` Optional. Vector of number of elements to read along each dimension of the array on file. The vector must be NA to read to the end of each dimension, otherwise its value must agree with the corresponding `start` value and the dimension of the array on file. Ignored when argument `var` is not an [NCVariable](#) instance.

`attributes` Optional. A `data.frame` with the attributes of the object. When argument `var` is an [NCVariable](#) instance and this argument is an empty `data.frame` (default), arguments will be read from the resource.

Returns: A `CFObjec` instance.

Method `detach()`: Detach the current object from its underlying netCDF resource. If necessary, data is read from the resource before detaching.

Usage:

```
CFObjec$detach()
```

Method `dim()`: Retrieve the dimensions of the data of this object. This could be for the data on file or for in-memory data.

Usage:

```
CFObjec$dim(dimension)
```

Arguments:

dimension Optional. The index of the dimension to retrieve the length for. If omitted, retrieve the lengths of all dimensions.

Returns: Integer vector with the length of each requested dimension.

Method `attribute()`: Retrieve an attribute of a CF object.

Usage:

```
CFObjec$attribute(att, field = "value")
```

Arguments:

att Single character string of attribute to return.

field The field of the attribute to return values from. This must be "value" (default) or "type".

Returns: If the field argument is "type", a character string. If field is "value", a single value of the type of the attribute, or a vector when the attribute has multiple values. If no attribute is named with a value of argument att NA is returned.

Method `print_attributes()`: Print the attributes of the CF object to the console.

Usage:

```
CFObjec$print_attributes(width = 30L)
```

Arguments:

width The maximum width of each column in the data.frame when printed to the console.

Method `set_attribute()`: Add an attribute. If an attribute name already exists, it will be overwritten.

Usage:

```
CFObjec$set_attribute(name, type, value)
```

Arguments:

name The name of the attribute. The name must begin with a letter and be composed of letters, digits, and underscores, with a maximum length of 255 characters. UTF-8 characters are not supported in attribute names.

type The type of the attribute, as a string value of a netCDF data type.

value The value of the attribute. This can be of any supported type, including a vector or list of values. Matrices, arrays and like compound data structures should be stored as a data variable, not as an attribute and they are thus not allowed. In general, an attribute should be a character value, a numeric value, a logical value, or a short vector or list of any of these. Values passed in a list will be coerced to their common mode.

Returns: Self, invisibly.

Method `append_attribute()`: Append the text value of an attribute. If an attribute name already exists, the value will be appended to the existing value of the attribute. If the attribute name does not exist it will be created. The attribute must be of "NC_CHAR" or "NC_STRING" type; in the latter case having only a single string value.

Usage:

```
CFObjec$append_attribute(name, value, sep = "; ", prepend = FALSE)
```

Arguments:

name The name of the attribute. The name must begin with a letter and be composed of letters, digits, and underscores, with a maximum length of 255 characters. UTF-8 characters are not supported in attribute names.

value The character value of the attribute to append. This must be a character string.

sep The separator to use. Default is "; ".

prepend Logical to flag if the supplied value should be placed before the existing value. Default is FALSE.

Returns: Self, invisibly.

Method delete_attribute(): Delete attributes. If an attribute name is not present this method simply returns.

Usage:

```
CFObjct$delete_attribute(name)
```

Arguments:

name Vector of names of the attributes to delete.

Returns: Self, invisibly.

Method write_attributes(): Write the attributes of this object to a netCDF file.

Usage:

```
CFObjct$write_attributes(nc, nm)
```

Arguments:

nc The handle to the netCDF file opened for writing.

nm The NC variable name or "NC_GLOBAL" to write the attributes to.

Returns: Self, invisibly.

Method update_coordinates_attribute(): Add names of axes or auxiliary coordinates to the "coordinates" attribute, avoiding duplicates and retaining previous values.

Usage:

```
CFObjct$update_coordinates_attribute(crds)
```

Arguments:

crds Vector of axis or auxiliary coordinate names to add to the attribute.

Returns: Self, invisibly.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CFObjct$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

CFResource

NetCDF resource object

Description

This class contains the connection details to a netCDF resource.

There is a single instance of this class for every netCDF resource, owned by the [CFDataset](#) instance. The instance is shared by other objects, specifically [NCGroup](#) instances, for access to the underlying resource for reading of data.

This class should never have to be accessed directly. All access is handled by higher-level methods.

Public fields

`error` Error message, or empty string.

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`handle` (read-only) The handle to the netCDF resource.

`uri` (read-only) The URI of the netCDF resource, either a local filename or the location of an online resource.

Methods

Public methods:

- [CFResource\\$new\(\)](#)
- [CFResource\\$create\(\)](#)
- [CFResource\\$close\(\)](#)
- [CFResource\\$group_handle\(\)](#)
- [CFResource\\$clone\(\)](#)

Method `new()`: Create a connection to a netCDF resource. This is called by [open_ncdf\(\)](#) when opening a netCDF resource or when saving a dataset to file. You should never have to call this directly.

Usage:

```
CFResource$new(uri)
```

Arguments:

`uri` The URI to the netCDF resource.

Returns: An instance of this class.

Method `create()`: Create a new file on disk for the netCDF resource.

Usage:

```
CFResource$create()
```


Returns: Self, invisibly.

Method `close()`: Closing an open netCDF resource. It should rarely be necessary to call this method directly.

Usage:

```
CFResource$close()
```

Method `group_handle()`: Every group in a netCDF file has its own handle, with the "root" group having the handle for the entire netCDF resource. The handle returned by this method is valid only for the named group.

Usage:

```
CFResource$group_handle(group_name)
```

Arguments:

`group_name` The absolute path to the group.

Returns: The handle to the group.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFResource$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

CFStandardNames	<i>CF Standard names table</i>
-----------------	--------------------------------

Description

The CF Metadata Conventions define a large number of standard names for physical parameters, including axes and data variables. This class accesses the standard names table. For each of the entries in the table two properties are provided: the canonical unit and a description. These properties are retrieved when searching for a given name.

Access to this class is through the CF environment. Use the `CF$standard_names$find("name_of_interest")` method to access a particular standard name. It is strongly recommended not to instantiate this class manually as that may introduce problems with accessing the underlying XML file.

The XML table is retrieved from the CF Metadata Conventions web site [here](#) and stored locally in the cache of the `ncdfCF` package. A check is performed periodically for an updated version, which will then be downloaded automatically. The frequency of the update check can be controlled with the `CF.options$cache_stale_days` option.

Active bindings

`is_loaded` (read-only) Flag to determine if the standard names table is available.

Methods

Public methods:

- [CFStandardNames\\$new\(\)](#)
- [CFStandardNames\\$print\(\)](#)
- [CFStandardNames\\$find\(\)](#)
- [CFStandardNames\\$load\(\)](#)
- [CFStandardNames\\$clone\(\)](#)

Method `new()`: Initialize an instance of this class. This is done automatically when the package is loaded.

Usage:

```
CFStandardNames$new()
```

Method `print()`: Print the version number of the standard names table in use, if it is loaded. The table is loaded automatically when it is first used.

Usage:

```
CFStandardNames$print()
```

Method `find()`: Retrieve the information on the specified names.

Usage:

```
CFStandardNames$find(names)
```

Arguments:

`names` A character vector with the names to search the standard names table for.

Returns: If an entry with a value in `names` is found, returns a `data.frame` with with with the canonical units and a description of the name. If no names are found in the table NULL is returned.

Method `load()`: Load the standard names table so that it's contents may be used in display and analysis. Note that the table may be downloaded (4.3MB at version 91) if not available or stale.

Usage:

```
CFStandardNames$load()
```

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFStandardNames$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

<https://cfconventions.org/cf-conventions/cf-conventions.html#standard-name>

CFVariable

*CF data variable***Description**

This class represents a CF data variable, the object that provides access to an array of data.

The CF data variable instance provides access to all the details that have been associated with the data variable, such as axis information, grid mapping parameters, etc.

Super class

`ncdfCF::CFObject` -> CFVariable

Active bindings

`friendlyClassName` (read-only) A nice description of the class.

`axes` (read-only) List of instances of classes descending from `CFAxis` that are the axes of the data object. If there are any scalar axes, they are listed after the axes that associate with the dimensions of the data. (In other words, axes 1..n describe the 1..n data dimensions, while any axes n+1..m are scalar axes.)

`crs` The coordinate reference system of this variable, as an instance of `CFGridMapping`. If this field is NULL, the horizontal component of the axes are in decimal degrees of longitude and latitude.

`cell_measures` (read-only) List of the `CFCellMeasure` objects of this variable, if defined.

`dimids` (read-only) Retrieve the dimension ids used by the NC variable used by this variable.

`dimnames` (read-only) Retrieve dimnames of the data variable.

`auxiliary_names` (read-only) Retrieve the names of the auxiliary longitude and latitude grids as a vector of two character strings, in that order. If no auxiliary grids are defined, returns NULL.

`gridLongLat` Retrieve or set the grid of longitude and latitude values of every grid cell when the main variable grid has a different coordinate system.

`crs_wkt2` (read-only) Retrieve the coordinate reference system description of the variable as a WKT2 string.

Methods**Public methods:**

- `CFVariable$new()`
- `CFVariable$print()`
- `CFVariable$brief()`
- `CFVariable$shard()`
- `CFVariable$peek()`
- `CFVariable$detach()`
- `CFVariable$time()`

- `CFVariable$raw()`
- `CFVariable$array()`
- `CFVariable$subset()`
- `CFVariable$summarise()`
- `CFVariable$profile()`
- `CFVariable$append()`
- `CFVariable$terra()`
- `CFVariable$data.table()`
- `CFVariable$is_coincident()`
- `CFVariable$add_cell_measure()`
- `CFVariable$add_auxiliary_coordinate()`
- `CFVariable$save()`
- `CFVariable$clone()`

Method `new()`: Create an instance of this class.

Usage:

```
CFVariable$new(
  var,
  axes,
  values = values,
  start = NA,
  count = NA,
  attributes = data.frame()
)
```

Arguments:

`var` The [NCVariable](#) instance upon which this CF variable is based when read from a netCDF resource, or the name for the new CF variable to be created.

`axes` List of instances of [CFAxis](#) to use with this variable.

`values` Optional. The values of the variable in an array.

`start` Optional. Vector of indices where to start reading data along the dimensions of the array on file. The vector must be NA to read all data, otherwise it must agree with the dimensions of the array on file. Ignored when argument `var` is not an [NCVariable](#) instance.

`count` Optional. Vector of number of elements to read along each dimension of the array on file. The vector must be NA to read to the end of each dimension, otherwise its value must agree with the corresponding `start` value and the dimension of the array on file. Ignored when argument `var` is not an [NCVariable](#) instance.

`attributes` Optional. A `data.frame` with the attributes of the object. When argument `var` is an [NCVariable](#) instance and this argument is an empty `data.frame` (default), arguments will be read from the resource.

Returns: A [CFVariable](#) instance.

Method `print()`: Print a summary of the data variable to the console.

Usage:

```
CFVariable$print(...)
```

Arguments:

... Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Method `brief()`: Some details of the data variable.

Usage:

`CFVariable$brief()`

Returns: A 1-row `data.frame` with some details of the data variable.

Method `shard()`: The information returned by this method is very concise and most useful when combined with similar information from other variables.

Usage:

`CFVariable$shard()`

Returns: Character string with very basic variable information.

Method `peek()`: Retrieve interesting details of the data variable.

Usage:

`CFVariable$peek()`

Returns: A 1-row `data.frame` with details of the data variable.

Method `detach()`: Detach the various properties of this variable from an underlying `netCDF` resource.

Usage:

`CFVariable$detach()`

Returns: Self, invisibly.

Method `time()`: Return the time object from the axis representing time.

Usage:

`CFVariable$time(want = "time")`

Arguments:

`want` Character string with value "axis" or "time", indicating what is to be returned.

Returns: If `want = "axis"` the [CFAxisTime](#) axis; if `want = "time"` the `CFTIME` instance of the axis, or `NULL` if the variable does not have a "time" axis.

Method `raw()`: Retrieve the data in the object exactly as it was read from a `netCDF` resource or produced by an operation.

Usage:

`CFVariable$raw()`

Returns: An array, matrix or vector with `(dim)names` set.

Method `array()`: Retrieve the data in the object in the form of an R array, with axis ordering Y-X-others and Y values going from the top down.

Usage:

`CFVariable$array()`

Returns: An array or matrix of data in R ordering, or a vector if the data has only a single dimension.

Method `subset()`: This method extracts a subset of values from the array of the variable, with the range along each axis to extract expressed in coordinate values of the domain of each axis.

Usage:

```
CFVariable$subset(..., rightmost.closed = FALSE)
```

Arguments:

`...` One or more arguments of the form `axis = range`. The "axis" part should be the name of an axis or its orientation X, Y, Z or T. The "range" part is a vector of values representing coordinates along the axis where to extract data. Axis designators and names are case-sensitive and can be specified in any order. If values for the range per axis fall outside of the extent of the axis, the range is clipped to the extent of the axis.

`rightmost.closed` Single logical value to indicate if the upper boundary of range in each axis should be included. You must use the argument name when specifying this, like `rightmost.closed = TRUE`, to avoid the argument being treated as an axis name.

Details: The range of values along each axis to be subset is expressed in coordinates of the domain of the axis. Any axes for which no selection is made in the `...` argument are extracted in whole. Coordinates can be specified in a variety of ways that are specific to the nature of the axis. For numeric axes it should (resolve to) be a vector of real values. A range (e.g. `100:200`), a vector (`c(23, 46, 3, 45, 17)`), a sequence (`seq(from = 78, to = 100, by = 2)`), all work. Note, however, that only a single range is generated from the vector so these examples resolve to `(100, 200)`, `(3, 46)`, and `(78, 100)`, respectively. For time axes a vector of character timestamps, POSIXct or Date values must be specified. As with numeric values, only the two extreme values in the vector will be used.

If the range of coordinate values for an axis in argument `...` extends the valid range of the axis, the extracted data will start at the beginning for smaller values and extend to the end for larger values. If the values envelope the valid range the entire axis will be extracted in the result. If the range of coordinate values for any axis are all either smaller or larger than the valid range of the axis then nothing is extracted and NULL is returned.

The extracted data has the same dimensional structure as the data in the variable, with degenerate dimensions dropped. The order of the axes in argument `...` does not reorder the axes in the result; use the `array()` method for this.

As an example, to extract values of a variable for Australia for the year 2020, where the first axis in `x` is the longitude, the second axis is the latitude, both in degrees, and the third (and final) axis is time, the values are extracted by `x$subset(X = c(112, 154), Y = c(-9, -44), T = c("2020-01-01", "2021-01-01"))`. Note that this works equally well for projected coordinate reference systems - the key is that the specification in argument `...` uses the same domain of values as the respective axes in `x` use.

Auxiliary coordinate variables:

A special case exists for variables where the horizontal dimensions (X and Y) are not in longitude and latitude coordinates but in some other coordinate system. In this case the netCDF resource may have so-called *auxiliary coordinate variables* for longitude and latitude that are two grids with the same dimension as the horizontal axes of the data variable where each pixel gives the corresponding value for the longitude and latitude. If the variable has such *auxiliary coordinate variables* then you can specify their names (instead of specifying the names of the

primary planar axes). The resolution of the grid that is produced by this method is automatically calculated. If you want to subset those axes then specify values in decimal degrees; if you want to extract the full extent, specify NA for both axes.

Returns: A CFVariable instance, having the axes and attributes of the variable, or NULL if one or more of the selectors in the ... argument fall entirely outside of the range of the axis. Note that degenerate dimensions (having `length(.) == 1`) are dropped from the data array but the corresponding axis is maintained in the result as a scalar axis.

If `self` is linked to a netCDF resource then the result will be linked to the same netCDF resource as well, except when *auxiliary coordinate variables* have been selected for the planar axes.

Method `summarise()`: Summarise the temporal domain of the data, if present, to a lower resolution, using a user-supplied aggregation function.

Attributes are copied from the input data variable or data array. Note that after a summarisation the attributes may no longer be accurate. This method tries to sanitise attributes but the onus is on the calling code (or yourself as interactive coder). Attributes like `standard_name` and `cell_methods` likely require an update in the output of this method, but the appropriate new values are not known to this method. Use `CFVariable$set_attribute()` on the result of this method to set or update attributes as appropriate.

Usage:

```
CFVariable$summarise(name, fun, period, era = NULL, ...)
```

Arguments:

`name` Character vector with a name for each of the results that `fun` returns. So if `fun` has 2 return values, this should be a vector of length 2. Any missing values are assigned a default name of "result_#" (with '#' being replaced with an ordinal number).

`fun` A function or a symbol or character string naming a function that will be applied to each grouping of data. The function must return an atomic value (such as `sum()` or `mean()`), or a vector of atomic values (such as `range()`). Lists and other objects are not allowed and will throw an error that may be cryptic as there is no way that this method can assert that `fun` behaves properly so an error will pop up somewhere, most probably in unexpected ways. The function may also be user-defined so you could write a wrapper around a function like `lm()` to return values like the intercept or any coefficients from the object returned by calling that function.

`period` The period to summarise to. Must be one of either "day", "dekad", "month", "quarter", "season", "year". A "quarter" is the standard calendar quarter such as January-March, April-June, etc. A "season" is a meteorological season, such as December-February, March-May, etc. (any December data is from the year preceding the January data). The period must be of lower resolution than the resolution of the time axis.

`era` Optional, integer vector of years to summarise over by the specified period. The extreme values of the years will be used. This can also be a list of multiple such vectors. The elements in the list, if used, should have names as these will be used to label the results.

... Additional parameters passed on to `fun`.

Returns: A CFVariable object, or a list thereof with as many CFVariable objects as `fun` returns values.

Method `profile()`: This method extracts profiles of values from the array of the variable, with the location along each axis to extract expressed in coordinate values of each axis.

Usage:

```
CFVariable$profile(..., .names = NULL, .as_table = FALSE)
```

Arguments:

- ... One or more arguments of the form `axis = location`. The "axis" part should be the name of an axis or its orientation X, Y, Z or T. The "location" part is a vector of values representing coordinates along the axis where to profile. A profile will be generated for each of the elements of the "location" vectors in all arguments.
- .names A character vector with names for the results. The names will be used for the resulting CFVariable instances, or as values for the "location" column of the `data.table` if argument `.as_table` is TRUE. If the vector is shorter than the longest vector of locations in the ... argument, a name "location_#" will be used, with the # replaced by the ordinal number of the vector element.
- .as_table Logical to flag if the results should be CFVariable instances (FALSE, default) or a single `data.table` (TRUE). If TRUE, all ... arguments must have the same number of elements, use the same axes and the `data.table` package must be installed.

Details: The coordinates along each axis to be sampled are expressed in values of the domain of the axis. Any axes which are not passed as arguments are extracted in whole to the result. If bounds are set on the axis, the coordinate whose bounds envelop the requested coordinate is selected. Otherwise, the coordinate along the axis closest to the supplied value will be used. If the value for a specified axis falls outside the valid range of that axis, NULL is returned.

A typical case is to extract the temporal profile as a 1D array for a given location. In this case, use arguments for the latitude and longitude on an X-Y-T data variable: `profile(lat = -24, lon = 3)`. Other profiling options are also possible, such as a 2D zonal atmospheric profile at a given longitude for an X-Y-Z data variable: `profile(lon = 34)`.

Multiple profiles can be extracted in one call by supplying vectors for the indicated axes: `profile(lat = c(-24, -23, -2), lon = c(5, 5, 6))`. The vectors need not have the same length, unless `.as_table = TRUE`. With unequal length vectors the result will be a list of CFVariable instances with different dimensionality and/or different axes.

Auxiliary coordinate variables:

A special case exists for variables where the horizontal dimensions (X and Y) are not in longitude and latitude coordinates but in some other coordinate system. In this case the netCDF resource may have so-called *auxiliary coordinate variables*. If the variable has such *auxiliary coordinate variables* then you can specify their names (instead of specifying the names of the primary planar axes).

Returns: If `.as_table = FALSE`, a CFVariable instance, or a list thereof with each having one profile for each of the elements in the "location" vectors of argument ... and named with the respective .names value. If `.as_table = TRUE`, a `data.table` with a row for each element along all profiles, with a ".variable" column using the values from the .names argument.

Method `append()`: Append the data from another CFVariable instance to the current instance, along one of the axes. The operation will only succeed if the axes other than the one to append along have the same coordinates and the coordinates of the axis to append along have to be monotonically increasing or decreasing after appending.

Usage:

```
CFVariable$append(from, along)
```

Arguments:

from The CFVariable instance to append to this data variable.

along The name of the axis to append along. This must be a single character string and the named axis has to be present both in this data variable and in the CFVariable instance in argument from.

Returns: self, invisibly, with the arrays from this data variable and from appended.

Method `terra()`: Convert the data to a `terra::SpatRaster` (3D) or a `terra::SpatRasterDataset` (4D) object. The data will be oriented to North-up. The 3rd dimension in the data will become layers in the resulting `SpatRaster`, any 4th dimension the data sets. The `terra` package needs to be installed for this method to work.

Usage:

```
CFVariable$terra()
```

Returns: A `terra::SpatRaster` or `terra::SpatRasterDataset` instance.

Method `data.table()`: Retrieve the data variable in the object in the form of a `data.table`. The `data.table` package needs to be installed for this method to work.

The attributes associated with this data variable will be mostly lost. If present, attributes 'long_name' and 'units' are attached to the `data.table` as attributes, but all others are lost.

Usage:

```
CFVariable$data.table(var_as_column = FALSE)
```

Arguments:

`var_as_column` Logical to flag if the name of the variable should become a column (TRUE) or be used as the name of the column with the data values (FALSE, default). Including the name of the variable as a column is useful when multiple `data.tables` are merged into one.

Returns: A `data.table` with all data points in individual rows. All axes will become columns. Two attributes are added: `name` indicates the long name of this data variable, `units` indicates the physical unit of the data values.

Method `is_coincident()`: Tests if the other object is coincident with this data variable: identical axes.

Usage:

```
CFVariable$is_coincident(other)
```

Arguments:

`other` A CFVariable instance to compare to this data variable.

Returns: TRUE if the data variables are coincident, FALSE otherwise.

Method `add_cell_measure()`: Add a cell measure variable to this variable.

Usage:

```
CFVariable$add_cell_measure(cm)
```

Arguments:

`cm` An instance of [CFCellMeasure](#).

Returns: Self, invisibly.

Method `add_auxiliary_coordinate()`: Add an auxiliary coordinate to the appropriate axis of this variable. The length of the axis must be the same as the length of the auxiliary labels.

Usage:

```
CFVariable$add_auxiliary_coordinate(aux, axis)
```

Arguments:

`aux` An instance of [CFLabel](#) or [CFAxis](#).

`axis` An instance of [CFAxis](#) that these auxiliary coordinates are for.

Returns: Self, invisibly.

Method `save()`: Save the data object to a netCDF file.

Usage:

```
CFVariable$save(fn, pack = FALSE)
```

Arguments:

`fn` The name of the netCDF file to create.

`pack` Logical to indicate if the data should be packed. Packing is only useful for numeric data; packing is not performed on integer values. Packing is always to the "NC_SHORT" data type, i.e. 16-bits per value.

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFVariable$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

CFVariableL3b

CF data variable for the NASA L3b format

Description

This class represents a CF data variable that provides access to data sets in NASA level-3 binned format, used extensively for satellite imagery.

Super classes

```
ncdfCF::CFObject -> ncdfCF::CFVariable -> CFVariableL3b
```

Methods

Public methods:

- [CFVariableL3b\\$new\(\)](#)
- [CFVariableL3b\\$subset\(\)](#)
- [CFVariableL3b\\$clone\(\)](#)

Method `new()`: Create an instance of this class.

Usage:

```
CFVariableL3b$new(grp, units)
```

Arguments:

`grp` The group that this CF variable lives in. Must be called "/level-3_binned_data".

`units` Vector of two character strings with the variable name and the physical units of the data variable in the netCDF resource.

Returns: An instance of this class.

Method `subset()`: This method extracts a subset of values from the data of the variable, with the range along both axes expressed in decimal degrees.

Usage:

```
CFVariableL3b$subset(..., rightmost.closed = FALSE)
```

Arguments:

`...` One or more arguments of the form `axis = range`. The "axis" part should be the name of axis longitude or latitude or its orientation X or Y. The "range" part is a vector of values representing coordinates along the axis where to extract data. Axis designators and names are case-sensitive and can be specified in any order. If values for the range of an axis fall outside of the extent of the axis, the range is clipped to the extent of the axis.

`rightmost.closed` Single logical value to indicate if the upper boundary of range in each axis should be included.

Details: The range of values along both axes of latitude and longitude is expressed in decimal degrees. Any axes for which no information is provided in the subset argument are extracted in whole. Values can be specified in a variety of ways that should (resolve to) be a vector of real values. A range (e.g. 100:200), a vector (`c(23, 46, 3, 45, 17)`), a sequence (`seq(from = 78, to = 100, by = 2)`), all work. Note, however, that only a single range is generated from the vector so these examples resolve to (100, 200), (3, 46), and (78, 100), respectively.

If the range of values for an axis in argument subset extend the valid range of the axis in x, the extracted slab will start at the beginning for smaller values and extend to the end for larger values. If the values envelope the valid range the entire axis will be extracted in the result. If the range of subset values for any axis are all either smaller or larger than the valid range of the axis in x then nothing is extracted and NULL is returned.

The extracted data has the same dimensional structure as the data in the variable, with degenerate dimensions dropped. The order of the axes in argument subset does not reorder the axes in the result; use the [CFVariable\\$array\(\)](#) method for this.

Returns: A [CFVariable](#) instance, having an array with axes and attributes of the variable, or NULL if one or more of the elements in the `...` argument falls entirely outside of the range of the axis. Note that degenerate dimensions (having `length(.) == 1`) are dropped from the array but the corresponding axis is maintained in the result as a scalar axis.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`CFVariableL3b$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

https://oceancolor.gsfc.nasa.gov/resources/docs/technical/ocean_level-3_binned_data_products.pdf

CFVerticalParametricTerm

Parametric formula term for a vertical CF axis object

Description

This class represents a formula term for a parametric vertical axis.

Super classes

`ncdfCF::CFObject` -> `ncdfCF::CFVariable` -> `CFVerticalParametricTerm`

Active bindings

`has_data` Logical flag that indicates if the instance has an associated data variable. If not, the instance will report `0` as its data.

`values` (read-only) The values of the parametric term. Depending on the definition of the term, this could be a large array or a simple scalar. Specifically, if the term is defined but no data is included in the netCDF resource, this method will return `0`, as per the CF Metadata Conventions.

Methods

Public methods:

- `CFVerticalParametricTerm$new()`
- `CFVerticalParametricTerm$print()`
- `CFVerticalParametricTerm$subset()`
- `CFVerticalParametricTerm$clone()`

Method `new()`: Create an instance of this class.

Usage:

```
CFVerticalParametricTerm$new(
  var,
  axes,
  values = values,
  start = NA,
  count = NA,
  attributes = data.frame()
)
```

Arguments:

var The [NCVariable](#) instance upon which this CF variable is based when read from a netCDF resource, or the name for the new CF variable to be created.

axes A list of [CFAxis](#) descendant instances that describe the axes of the data object.

values Optional. The values of the variable in an array.

start Optional. Vector of indices where to start reading data along the dimensions of the array on file. The vector must be NA to read all data, otherwise it must agree with the dimensions of the array on file. Ignored when argument **var** is not an [NCVariable](#) instance.

count Optional. Vector of number of elements to read along each dimension of the array on file. The vector must be NA to read to the end of each dimension, otherwise its value must agree with the corresponding **start** value and the dimension of the array on file. Ignored when argument **var** is not an [NCVariable](#) instance.

attributes Optional. A `data.frame` with the attributes of the object. When argument **var** is an [NCVariable](#) instance and this argument is an empty `data.frame` (default), arguments will be read from the resource.

Returns: An instance of this class.

Method `print()`: Prints a summary of the parametric formula term to the console.

Usage:

```
CFVerticalParametricTerm$print(...)
```

Arguments:

... Arguments passed on to other functions. Of particular interest is `width =` to indicate a maximum width of attribute columns.

Returns: `self`, invisibly.

Method `subset()`: Subset the indices to read a smaller portion of the data from the netCDF file. The passed indices should be named after the axes that they refer to. There may be more indices than axes and they may be in a different order than the axes of the term.

Usage:

```
CFVerticalParametricTerm$subset(
  original_axis_names,
  new_axes,
  start,
  count,
  aux = NULL,
  ZT_dim = NULL
)
```

Arguments:

`original_axis_names` Character vector of names of the axes prior to a modifying operation in the owning data variable.

`new_axes` List of CFAxis instances to use for the subsetting.

`start` The indices to start reading data from the file, as an integer vector at least as long as the number of axis for the term.

`count` The number of values to read from the file, as an integer vector at least as long as the number of axis for the term.

`aux` Optional. List with the parameters for an auxiliary grid transformation. Default is NULL.

`ZT_dim` Optional. Dimensions of the non-grid axes when an auxiliary grid transformation is specified.

Returns: The new parametric term object.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CFVerticalParametricTerm$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

dim.AOI

The dimensions of the grid of an AOI

Description

This method returns the dimensions of the grid that would be created for the AOI.

Usage

```
## S3 method for class 'AOI'
dim(x)
```

Arguments

`x` An instance of the AOI class.

Value

A vector of two values giving the longitude and latitude dimensions of the grid that would be created for the AOI.

Examples

```
a <- aoi(30, 40, 10, 30, 0.1)
dim(a)
```

dim.CFAxis	<i>Axis length</i>
------------	--------------------

Description

This method returns the lengths of the axes of a variable or axis.

Usage

```
## S3 method for class 'CFAxis'
dim(x)
```

Arguments

x The CFVariable or a descendant of CFAxis.

Value

Vector of axis lengths.

Examples

```
fn <- system.file("extdata", "ERA5land_Rwanda_20160101.nc", package = "ncdfCF")
ds <- open_ncdf(fn)
t2m <- ds[["t2m"]]
dim(t2m)
```

makeAxis	<i>Create an axis</i>
----------	-----------------------

Description

With this method you can create an axis to use with new [CFVariable](#) instances. Depending on the orientation argument and the type of the values argument an instance of a class descending from [CFAxis](#) will be returned.

Usage

```
makeAxis(name, orientation, values, bounds = NULL, attributes = NULL)
```

Arguments

name	Name of the axis.
orientation	The orientation of the axis. Must be one of "X", "Y", "Z", or "T" for longitude, latitude, height or depth, and time axes, respectively. For any other axis, indicate an empty string ""
values	The coordinate values. In the case of an axis with orientation = "T" this must be a CTime or CFClimatology instance.
bounds	The boundary values of the coordinates, or NULL if not available.
attributes	data.frame with the attributes of the axis to create. Depending on which axis is created one or more attributes may be added or amended.

Details

There are several restrictions on the combination of orientation and values arguments. Longitude, latitude and depth axes (orientation of "X", "Y" or "Z") must have numeric values. For a time axis (orientation of "T") the values argument must be an instance of CTime or CFClimatology.

Value

An instance of a class descending from [CFAxis](#).

See Also

[makeLongitudeAxis\(\)](#), [makeLatitudeAxis\(\)](#), [makeTimeAxis\(\)](#), [makeDiscreteAxis\(\)](#)

makeCharacterAxis	<i>Create a character axis</i>
-------------------	--------------------------------

Description

With this method you can create a character axis to use with new [CFVariable](#) instances.

Usage

```
makeCharacterAxis(name, values, attributes = data.frame())
```

Arguments

name	Name of the axis.
values	The character coordinate values of the axis.
attributes	data.frame with the attributes of the axis to create.

Value

A [CFAxisCharacter](#) instance.

makeDiscreteAxis	Create a discrete axis
------------------	------------------------

Description

With this method you can create a discrete axis to use with new [CFVariable](#) instances.

Usage

```
makeDiscreteAxis(name, length)
```

Arguments

name	Name of the axis.
length	The length of the axis.

Value

A [CFAxisDiscrete](#) instance. The values will be a sequence of size length.

makeLatitudeAxis	Create a latitude axis
------------------	------------------------

Description

With this method you can create a latitude axis to use with new [CFVariable](#) instances.

Usage

```
makeLatitudeAxis(name, values, bounds, attributes = NULL)
```

Arguments

name	Name of the axis.
values	The coordinate values.
bounds	The bounds of the coordinate values, or NULL if not available.
attributes	data.frame with the attributes of the axis to create. Attributes "standard_name", "units", "actual_range" and "axis" will be set or updated.

Value

A [CFAxisLatitude](#) instance.

makeLongitudeAxis	<i>Create a longitude axis</i>
-------------------	--------------------------------

Description

With this method you can create a longitude axis to use with new [CFVariable](#) instances.

Usage

```
makeLongitudeAxis(name, values, bounds = NULL, attributes = NULL)
```

Arguments

name	Name of the axis.
values	The coordinate values.
bounds	The bounds of the coordinate values, or NULL if not available.
attributes	data.frame with the attributes of the axis to create. Attributes "standard_name", "units", "actual_range" and "axis" will be set or updated.

Value

A [CFAxisLongitude](#) instance.

makeTimeAxis	<i>Create a time axis</i>
--------------	---------------------------

Description

With this method you can create a time axis to use with new [CFVariable](#) instances.

Usage

```
makeTimeAxis(name, values, attributes = NULL)
```

Arguments

name	Name of the axis.
values	A CFTIME or CFCLIMATOLOGY instance with time values and optionally bounds set.
attributes	data.frame with the attributes of the axis to create. Attributes "standard_name", "units", "calendar", "actual_range" and "axis" will be set or updated.

Value

A [CFAxisTime](#) instance.

makeVerticalAxis	Create a vertical axis
------------------	------------------------

Description

With this method you can create a vertical axis to use with new [CFVariable](#) instances. Note that you should set the "positive" attribute after creating the axis to indicate if values are increasing going upwards (positive = "up") or downwards (positive = "down").

Usage

```
makeVerticalAxis(name, values, bounds, attributes = NULL)
```

Arguments

name	Name of the axis.
values	The coordinate values.
bounds	The bounds of the coordinate values, or NULL if not available.
attributes	data.frame with the attributes of the axis to create. Attributes "actual_range" and "axis" will be set or updated.

Value

A [CFAxisVertical](#) instance.

names.CFdataset	Names or axis values of an CF object
-----------------	--------------------------------------

Description

Retrieve the variable or axis names of an ncdfCF object. The names() function gives the names of the variables in the data set, preceded by the path to the group if the resource uses groups. The return value of the dimnames() function differs depending on the type of object:

- CFdataset, CFVariable: The dimnames are returned as a vector of the names of the axes of the data set or variable, preceded with the path to the group if the resource uses groups. Note that this differs markedly from the base::dimnames() functionality.
- CFAxisNumeric, CFAxisLongitude, CFAxisLatitude, CFAxisVertical: The coordinate values along the axis as a numeric vector.
- CFAxisTime: The coordinate values along the axis as a character vector containing timestamps in ISO8601 format. This could be dates or date-times if time information is available in the axis.
- CFAxisCharacter: The coordinate values along the axis as a character vector.
- CFAxisDiscrete: The index values of the axis, either along the entire axis, or a portion thereof.

Usage

```
## S3 method for class 'CFDataset'
names(x)

groups(x)

## S3 method for class 'CFDataset'
groups(x)
```

Arguments

x An CFObject whose axis names to retrieve. This could be CFDataset, CFVariable, or a class descending from CFAxis.

Value

A vector as described in the Description section.

Examples

```
fn <- system.file("extdata",
  "pr_day_EC-Earth3-CC_ssp245_r1i1p1f1_gr_20230101-20231231_vncdfCF.nc",
  package = "ncdfCF")
ds <- open_ncdf(fn)

# Names of data variables
names(ds)

# CFDataset
dimnames(ds)

# CFVariable
pr <- ds[["pr"]]
dimnames(pr)

# CFAxisNumeric
lon <- ds[["lon"]]
dimnames(lon)

# CFAxisTime
t <- ds[["time"]]
dimnames(t)
```

Description

This class represents an netCDF dimensions. It contains the information on a dimension that is stored in an netCDF file. Consequently, the properties of this class are all read-only. The length of the dimension may change if data is written to an unlimited dimension, but that is managed internally.

This class is not very useful for interactive use. Use the [CFAxis](#) descendent classes instead.

Super class

`ncdfCF::NCOBJECT -> NCDimension`

Active bindings

`length` (read-only) The length of the dimension. If field `unlim = TRUE`, this field indicates the length of the data in this dimension written to file.

`unlim` (read-only) Logical flag to indicate if the dimension is unlimited, i.e. that additional data may be written to file incrementing this dimension.

Methods**Public methods:**

- `NCDimension$new()`
- `NCDimension$print()`
- `NCDimension$write()`
- `NCDimension$clone()`

Method `new()`: Create a new netCDF dimension. This class should not be instantiated directly, create CF objects instead. This class is instantiated when opening a netCDF resource.

Usage:

`NCDimension$new(id, name, length, unlim, group)`

Arguments:

`id` Numeric identifier of the netCDF dimension.

`name` Character string with the name of the netCDF dimension.

`length` Length of the dimension.

`unlim` Is the dimension unlimited?

`group` The group where the dimension is located.

Returns: A NCDimension instance.

Method `print()`: Summary of the NC dimension printed to the console.

Usage:

`NCDimension$print(...)`

Arguments:

`...` Passed on to other methods.

Method `write()`: Write the dimension to a netCDF file.

Usage:

```
NCDimension$write(h)
```

Arguments:

h The handle to the netCDF file to write.

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
NCDimension$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

NCGroup

NetCDF group

Description

This class represents a netCDF group, the object that holds elements like dimensions and variables of a netCDF file. This class also holds references to any CF objects based on the netCDF elements held by the group.

Direct access to groups is usually not necessary. The principal objects held by the group, CF data variables and axes, are accessible via other means. Only for access to the group attributes is a reference to a group required. Changing the properties of a group other than its name may very well invalidate the CF objects or even the netCDF file.

Super class

```
ncdfCF::NCObject -> NCGroup
```

Public fields

resource Access to the underlying netCDF resource. This can be NULL for instances created in memory. Managed internally. Never change the resource as it will very likely lead to problems reading from and writing to file.

parent Parent group of this group, the owning CFDataset for the root group.

subgroups List of child NCGroup instances of this group.

NCvars List of netCDF variables that are located in this group.

NCdims List of netCDF dimensions that are located in this group.

NCudts List of netCDF user-defined types that are located in this group.

CFvars List of CF data variables in this group. There must be a corresponding item in NCvars for each item in this list.

- CFaxes** List of axes of CF data variables in this group. There must be a corresponding item in **NCvars** for each item in this list. Note that the CF data variable(s) that an axis is associated with may be located in a different group. Also, objects that further describe the basic axis definition, such as its bounds, labels, ancillary data, may be located in a different group; all such elements can be accessed directly from the **CFAxis** instances that this list holds.
- CFaux** List of auxiliary coordinates located in this group. These could be **CFLabel** instances or an axis.
- CFlonglat** List of **CFAuxiliaryLongLat** that hold longitude and latitude values for every grid point in the data variable that references them.
- CFmeasures** List of cell measures variables in this group.
- CFcrs** List of grid mappings located in this group.

Active bindings

- friendlyClassName** (read-only) A nice description of the class.
- handle** (read-only) Get the handle to the netCDF resource for the group
- name** Set or retrieve the name of the group. Note that the name is always relative to the location in the hierarchy that the group is in and it should thus not be qualified by backslashes. The name has to be a valid CF name. The name of the root group cannot be changed.
- fullname** (read-only) The fully qualified absolute path of the group.
- root** (read-only) Retrieve the root group.
- data_set** (read-only) Retrieve the **CFDataset** that the group belongs to. If the group is not attached to a **CFDataset**, returns NULL.

Methods

Public methods:

- [NCGroup\\$new\(\)](#)
- [NCGroup\\$print\(\)](#)
- [NCGroup\\$hierarchy\(\)](#)
- [NCGroup\\$find_by_name\(\)](#)
- [NCGroup\\$find_dim_by_id\(\)](#)
- [NCGroup\\$has_name\(\)](#)
- [NCGroup\\$unused\(\)](#)
- [NCGroup\\$add_auxiliary_coordinate\(\)](#)
- [NCGroup\\$add_auxiliary_longlat\(\)](#)
- [NCGroup\\$addCellMeasure\(\)](#)
- [NCGroup\\$fullnames\(\)](#)
- [NCGroup\\$dimensions\(\)](#)
- [NCGroup\\$variables\(\)](#)
- [NCGroup\\$axes\(\)](#)
- [NCGroup\\$grid_mappings\(\)](#)
- [NCGroup\\$clone\(\)](#)

Method `new()`: Create a new instance of this class.

Usage:

```
NCGroup$new(id, name, attributes = data.frame(), parent, resource)
```

Arguments:

`id` The identifier of the group.

`name` The name of the group.

`attributes` Optional, a `data.frame` with group attributes.

`parent` The parent group of this group. the owning [CFDataset](#) for the root group.

`resource` Reference to the [CFResource](#) instance that provides access to the netCDF resource.
For in-memory groups this can be `NULL`.

Method `print()`: Summary of the group printed to the console.

Usage:

```
NCGroup$print(stand_alone = TRUE, ...)
```

Arguments:

`stand_alone` Logical to indicate if the group should be printed as an object separate from other objects (`TRUE`, default), or print as part of an enclosing object (`FALSE`).

`...` Passed on to other methods.

Method `hierarchy()`: Prints the hierarchy of the group and its subgroups to the console, with a summary of contained objects. Usually called from the root group to display the full group hierarchy.

Usage:

```
NCGroup$hierarchy(idx = 1L, total = 1L)
```

Arguments:

`idx, total` Arguments to control indentation. Should both be 1 (the default) when called interactively. The values will be updated during recursion when there are groups below the current group.

Method `find_by_name()`: Find an object by its name. Given the name of an object, possibly preceded by an absolute or relative group path, return the object to the caller. Typically, this method is called programmatically; similar interactive use is provided through the `[[]]` [CFDataset](#) operator.

Usage:

```
NCGroup$find_by_name(name, scope = "CF")
```

Arguments:

`name` The name of an object, with an optional absolute or relative group path from the calling group. The object must either an CF construct (data variable, axis, auxiliary axis, label, or grid mapping) or an NC group, dimension or variable.

`scope` Either "CF" (default) for a CF construct, or "NC" for a netCDF group, dimension or variable.

Returns: The object with the provided name in the requested scope. If the object is not found, returns `NULL`.

Method `find_dim_by_id()`: Find an NC dimension object by its id. Given the id of a dimension, return the [NCDimension](#) object to the caller. The dimension has to be found in the current group or any of its parents.

Usage:

```
NCGroup$find_dim_by_id(id)
```

Arguments:

`id` The id of the dimension.

Returns: The [NCDimension](#) object with an identifier equal to the `id` argument. If the object is not found, returns NULL.

Method `has_name()`: Has a given name been defined in this group already?

Usage:

```
NCGroup$has_name(name, scope = "both")
```

Arguments:

`name` Character string. The name will be searched for, regardless of case.

`scope` Either "CF" for a CF construct, "NC" for a netCDF variable, or "both" (default) to test both scopes.

Returns: TRUE if name is present in the group, FALSE otherwise.

Method `unused()`: Find NC variables that are not referenced by CF objects. For debugging purposes only.

Usage:

```
NCGroup$unused()
```

Returns: List of [NCVariable](#).

Method `add_auxiliary_coordinate()`: Add an auxiliary coordinate variable to the group. This method adds the passed auxiliary coordinate to the group CFAux list.

Usage:

```
NCGroup$add_auxiliary_coordinate(aux)
```

Arguments:

`aux` Instance of [CFLabel](#) or [CFAxis](#).

Returns: self invisibly.

Method `add_auxiliary_longlat()`: Add an auxiliary long-lat variable to the group. This method creates a [CFAuxiliaryLongLat](#) from the arguments and adds it to the group CFlonglat list, but only if the combination of lon, lat isn't already present.

Usage:

```
NCGroup$add_auxiliary_longlat(lon, lat, bndsLong, bndsLat)
```

Arguments:

`lon, lat` Instances of [CFVariable](#), each having a two-dimensional grid of longitude and latitude values.

`bndsLong, bndsLat` Instances of [CFBounds](#) with the 2D bounds of the longitude and latitude grid values, respectively, or NULL when not set.

Returns: self invisibly.

Method addCellMeasure(): Add a cell measure variable to the group.

Usage:

```
NCGroup$addCellMeasure(cm)
```

Arguments:

cm Instance of [CFCellMeasure](#).

Returns: self invisibly.

Method fullnames(): This method lists the fully qualified name of this group, optionally including names in subgroups.

Usage:

```
NCGroup$fullnames(recursive = TRUE)
```

Arguments:

recursive Should subgroups be scanned for names too (default is TRUE)?

Returns: A character vector with group names.

Method dimensions(): List all the dimensions that are visible from this group, possibly including those that are defined in parent groups (by names not defined by any of their child groups in direct lineage to the current group).

Usage:

```
NCGroup$dimensions(scope = "all")
```

Arguments:

scope Character string that indicates if only dimensions in the current group should be reported (local) or visible dimensions in parent groups as well (all, default).

Returns: A vector of [NCDimension](#) objects.

Method variables(): This method lists the CF data variables located in this group, optionally including data variables in subgroups.

Usage:

```
NCGroup$variables(recursive = TRUE)
```

Arguments:

recursive Should subgroups be scanned for CF data variables too (default is TRUE)?

Returns: A list of [CFVariable](#).

Method axes(): This method lists the axes located in this group, optionally including axes in subgroups.

Usage:

```
NCGroup$axes(recursive = TRUE)
```

Arguments:

recursive Should subgroups be scanned for axes too (default is TRUE)?

Returns: A list of [CFAxis](#) descendants.

Method `grid_mappings()`: This method lists the grid mappings located in this group, optionally including grid mappings in subgroups.

Usage:

```
NCGroup$grid_mappings(recursive = TRUE)
```

Arguments:

`recursive` Should subgroups be scanned for grid mappings too (default is TRUE)?

Returns: A list of [CFGridMapping](#) instances.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
NCGroup$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

NCObject

NetCDF base object

Description

This class is a basic ancestor to all classes that represent netCDF objects, specifically groups, dimensions, variables and the user-defined types in a netCDF file. More useful classes use this class as ancestor.

The fields in this class are common among all netCDF objects. In addition, this class manages the attributes for its descendent classes.

Active bindings

`id` (read-only) Retrieve the identifier of the netCDF object.

`name` (read-only) Retrieve the name of the object.

`attributes` (read-only) Read the attributes of the object. When there are no attributes, an empty `data.frame` will be returned.

Methods

Public methods:

- [NCObject\\$new\(\)](#)
- [NCObject\\$print_attributes\(\)](#)
- [NCObject\\$attribute\(\)](#)
- [NCObject\\$write_attributes\(\)](#)
- [NCObject\\$clone\(\)](#)

Method `new()`: Create a new netCDF object. This class should not be instantiated directly, create descendant objects instead.

Usage:

```
NCObject$new(id, name, attributes = data.frame())
```

Arguments:

`id` Numeric identifier of the netCDF object.
`name` Character string with the name of the netCDF object.
`attributes` Optional, `data.frame` with attributes of the object.

Method `print_attributes()`: This function prints the attributes of the netCDF object to the console.

Usage:

```
NCObject$print_attributes(width = 50L)
```

Arguments:

`width` The maximum width of each column in the `data.frame` when printed to the console.

Method `attribute()`: Retrieve an attribute of a NC object.

Usage:

```
NCObject$attribute(att, field = "value")
```

Arguments:

`att` Single character string of attribute to return.
`field` The field of the attribute to return values from. This must be "value" (default) or "type".

Returns: If the `field` argument is "type", a character string. If `field` is "value", a single value of the type of the attribute, or a vector when the attribute has multiple values. If no attribute is named with a value of argument `att` NA is returned.

Method `write_attributes()`: Write the attributes of this object to a netCDF file.

Usage:

```
NCObject$write_attributes(nc, nm)
```

Arguments:

`nc` The handle to the netCDF file opened for writing.
`nm` The NC variable name or "NC_GLOBAL" to write the attributes to.

Returns: Self, invisibly.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
NCObject$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

NCVariable

*NetCDF variable***Description**

This class represents a netCDF variable, the object that holds the properties and data of elements like dimensions and variables of a netCDF file.

Direct access to netCDF variables is usually not necessary. NetCDF variables are linked from CF data variables and axes and all relevant properties are thus made accessible.

Super class

```
ncdfCF::NCObject -> NCVariable
```

Active bindings

group (read-only) NetCDF group where this variable is located.

vtype (read-only) The netCDF data type of this variable. This could be the packed type. Don't check this field but use the appropriate method in the class of the object whose data type you are looking for.

ndims (read-only) Number of dimensions that this variable uses.

dimids (read-only) Vector of dimension identifiers that this NCVariable uses.

netcdf4 (read-only) Additional properties for a netcdf4 resource.

CF Register CF object that uses this netCDF variable, or retrieve the list of registered CF objects.

fullname (read-only) Name of this netCDF variable including the group path from the root group.

Methods**Public methods:**

- `NCVariable$new()`
- `NCVariable$print()`
- `NCVariable$shard()`
- `NCVariable$detach()`
- `NCVariable$get_data()`
- `NCVariable$dimension()`
- `NCVariable$dim()`
- `NCVariable$clone()`

Method new(): Create a new netCDF variable. This class should not be instantiated directly, they are created automatically when opening a netCDF resource.

Usage:

```
NCVariable$new(
  id,
  name,
  group,
  vtype,
  dimids,
  attributes = data.frame(),
  netcdf4 = list()
)
```

Arguments:

id Numeric identifier of the netCDF object.
name Character string with the name of the netCDF object.
group The [NCGroup](#) this variable is located in.
vtype The netCDF data type of the variable.
dimids The identifiers of the dimensions this variable uses.
attributes Optional, data.frame with the attributes of the object.
netcdf4 Optional, netcdf4-specific arguments in the format of RNetCDF.

Returns: An instance of this class.

Method `print()`: Summary of the NC variable printed to the console.

Usage:

```
NCVariable$print(...)
```

Arguments:

... Passed on to other methods.

Method `shard()`: Very concise information on the variable. The information returned by this function is very concise and most useful when combined with similar information from other variables.

Usage:

```
NCVariable$shard()
```

Returns: Character string with very basic variable information.

Method `detach()`: Detach the passed object from this NC variable.

Usage:

```
NCVariable$detach(obj)
```

Arguments:

obj The CFObj instance to detach from this NC variable.

Returns: **obj**, invisibly.

Method `get_data()`: Read (a chunk of) data from the netCDF file. Degenerate dimensions are maintained and data is always returned in its smallest type.

Usage:

```
NCVariable$get_data(start = NA, count = NA)
```

Arguments:

start A vector of indices specifying the element where reading starts along each dimension of the data. When NA, all data are read from the start of the array.

count An integer vector specifying the number of values to read along each dimension of the data. Any NA value in vector count indicates that the corresponding dimension should be read from the start index to the end of the dimension.

Returns: An array with the requested data, or an error object.

Method `dimension()`: Get the [NCDimension](#) object(s) that this variable uses.

Usage:

```
NCVariable$dimension(id)
```

Arguments:

id The index of the dimension. If missing, all dimensions of this variable are returned.

Returns: A [NCDimension](#) object or a list thereof. If no [NCDimensions](#) were found, return NULL.

Method `dim()`: The lengths of the data dimensions of this object.

Usage:

```
NCVariable$dim(dimension)
```

Arguments:

dimension Optional. The index of the dimension to retrieve the length for. If omitted, retrieve the lengths of all dimensions.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
NCVariable$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

open_ncdf

Open a netCDF resource

Description

This function will read the metadata of a netCDF resource and interpret the netCDF dimensions, variables and attributes to generate the corresponding CF objects. The data for the CF variables is not read, please see [CFVariable](#) for methods to read the variable data.

Usage

```
open_ncdf(resource)
```

Arguments

resource The name of the netCDF resource to open, either a local file name or a remote URI.

Value

An CFDataset instance, or an error if the resource was not found or errored upon reading.

Examples

```
fn <- system.file("extdata",
  "pr_day_EC-Earth3-CC_ssp245_r1i1p1f1_gr_20230101-20231231_vncdfCF.nc",
  package = "ncdfCF")
(ds <- open_ncdf(fn))
```

Ops.CFVariable

*Operations on CFVariable objects***Description**

Basic arithmetic, mathematical and logical operations can be applied on the data of [CFVariable](#) objects having a suitable data type, specifically the base R functions from the Ops and Math groups of the S3 [groupGeneric](#) functions.

Usage

```
## S3 method for class 'CFVariable'
Ops(e1, e2)

## S3 method for class 'CFVariable'
Math(x, ...)
```

Arguments

e1, e2	CFVariable objects, or a single numeric value.
x	A CFVariable object.
...	Additional arguments passed on to the math functions.

Details

The functions always return a new CFVariable object. Functions can thus be concatenated to create more complex expressions. The data type of the new object is determined by the base R function; its name is concatenated from the names in the argument object(s).

For the Ops functions with two arguments, if both arguments are a CFVariable object they have to be compatible: same shape, axis coordinate values and coordinate reference system. The resulting CFVariable object will use the same axes as the CFVariable object(s) used as argument.

The attributes of the resulting CFVariable object should be updated to reflect its contents, in particular the "name", "long_name", "standard_name" and "units" attributes. Attributes are not copied over from the CFVariable objects in the arguments.

Value

A new CFVariable object. The object will have the same coordinate space as the CFVariable object used as argument. Arguments are not copied and the new object will only have the "actual_range" attribute set.

Results that are logical (see the examples) are stored using the NC_SHORT data type because netCDF does not have a native logical data type.

Examples

```
fn <- system.file("extdata", "ERA5land_Rwanda_20160101.nc", package = "ncdfCF")
ds <- open_ncdf(fn)

# Temperature data in K
t2m <- ds[["t2m"]]

# Convert to degrees_Celsius
t2mC <- t2m - 273.15
t2mC$name <- "t2m_Celsius"
t2mC$set_attribute("units", "NC_CHAR", "degrees_Celsius")
t2mC

hot <- t2mC > 20
hot$name <- "t2m_Celsius_over_20"
hot$set_attribute("long_name", "NC_CHAR", "Flag to indicate where temperature is 20C or hotter")
hot$set_attribute("units", "NC_CHAR", "1")
hot
```

peek_ncdf

Examine a netCDF resource

Description

This function will read a netCDF resource and return a list of identifying information, including data variables, axes and global attributes. Upon returning the netCDF resource is closed.

Usage

```
peek_ncdf(resource)
```

Arguments

resource	The name of the netCDF resource to open, either a local file name or a remote URI.
----------	--

Details

If you find that you need other information to be included in the result, [open an issue](#).

Value

A list with elements "variables", "axes" and global "attributes", each a data.frame.

Examples

```
fn <- system.file("extdata",
  "pr_day_EC-Earth3-CC_ssp245_r1i1p1f1_gr_20230101-20231231_vncdfCF.nc",
  package = "ncdfCF")
peek_ncdf(fn)
```

str.CFAxis	<i>Compact display of an axis.</i>
------------	------------------------------------

Description

Compact display of an axis.

Usage

```
## S3 method for class 'CFAxis'
str(object, ...)
```

Arguments

- object A CFAxis instance or any descendant.
- ... Ignored.

str.CFDataset	<i>Compact display of a CFDataset</i>
---------------	---------------------------------------

Description

Compact display of a CFDataset

Usage

```
## S3 method for class 'CFDataset'
str(object, ...)
```

Arguments

- object A CFDataset instance.
- ... Ignored.

[.CFVariable	<i>Extract data for a variable</i>
--------------	------------------------------------

Description

Extract data from a CFVariable instance, optionally sub-setting the axes to load only data of interest.

Usage

```
## S3 method for class 'CFVariable'
x[i, j, ..., drop = FALSE]
```

Arguments

x	An CFVariable instance to extract the data of.
i, j, ...	Expressions, one for each axis of x, that select a number of elements along each axis. If any expressions are missing, the entire axis is extracted. The values for the arguments may be an integer vector or a function that returns an integer vector. The range of the values in the vector will be used. See examples, below.
drop	Logical, ignored. Axes are never dropped. Any degenerate dimensions of the array are returned as such, with dimnames and appropriate attributes set.

Details

If all the data of the variable in x is to be extracted, simply use [] (unlike with regular arrays, this is required, otherwise the details of the variable are printed on the console).

The indices into the axes to be subset can be specified in a variety of ways; in practice it should (resolve to) be a vector of integers. A range (e.g. 100:200), an explicit vector (c(23, 46, 3, 45, 17)), a sequence (seq(from = 78, to = 100, by = 2)), all work. Note, however, that only a single range is generated from the vector so these examples resolve to 100:200, 3:46, and 78:100, respectively. It is also possible to use a custom function as an argument.

This method works with "bare" indices into the axes of the array. If you want to use domain values of the axes (e.g. longitude values or timestamps) to extract part of the variable array, use the CFVariable\$subset() method.

Scalar axes should not be included in the indexing as they do not represent a dimension into the data array.

Value

An array with dimnames and other attributes set.

Examples

```
fn <- system.file("extdata",
  "pr_day_EC-Earth3-CC_ssp245_r1i1p1f1_gr_20230101-20231231_vncdfCF.nc",
  package = "ncdfCF")
ds <- open_ncdf(fn)
pr <- ds[["pr"]]

# How are the dimensions organized?
dimnames(pr)

# Precipitation data for March for a single location
x <- pr[5, 12, 61:91]
str(x)

# Summer precipitation over the full spatial extent
summer <- pr[, , 173:263]
str(summer)
```

[.CFVariableL3b

Extract data for a variable

Description

Extract data from a CFVariableL3b instance, optionally sub-setting the axes to load only data of interest.

Usage

```
## S3 method for class 'CFVariableL3b'
x[i, j, ..., drop = FALSE]
```

Arguments

<code>x</code>	An CFVariableL3b instance to extract the data of.
<code>i, j, ...</code>	Expressions, one for each of the two axes of <code>x</code> , that select a number of elements along each axis. <code>i</code> is for the longitude axis, <code>j</code> for the latitude axis, <code>...</code> (additional named arguments) is invalid as there are only two axes to subset from. If either expression is missing, the entire axis is extracted. The values for the arguments may be an integer vector or a function that returns an integer vector. The range of the values in the vector will be used. See examples, below.
<code>drop</code>	Logical, ignored. Axes are never dropped. Any degenerate dimensions of the array are returned as such, with <code>dimnames</code> and appropriate attributes set.

Details

If all the data of the variable in `x` is to be extracted, simply use `[]` (unlike with regular arrays, this is required, otherwise the details of the variable are printed on the console).

The indices into the axes to be subset can be specified in a variety of ways; in practice it should (resolve to) be a vector of integers. A range (e.g. `100:200`), an explicit vector (`c(23, 46, 3, 45, 17)`), a sequence (`seq(from = 78, to = 100, by = 2)`), all work. Note, however, that only a single range is generated from the vector so these examples resolve to `100:200`, `3:46`, and `78:100`, respectively. It is also possible to use a custom function as an argument.

This method works with "bare" indices into the axes of the array. If you want to use domain values of the axes (e.g. longitude values or timestamps) to extract part of the variable array, use the `CFVariableL3b$subset()` method.

Scalar axes should not be included in the indexing as they do not represent a dimension into the data array.

Value

An array with `dimnames` and other attributes set.

Examples

```
fn <- system.file("extdata",
  "pr_day_EC-Earth3-CC_ssp245_r1i1p1f1_gr_20230101-20231231_vncdfCF.nc",
  package = "ncdfCF")
ds <- open_ncdf(fn)
pr <- ds[["pr"]]

# How are the dimensions organized?
dimnames(pr)

# Precipitation data for March for a single location
x <- pr[5, 12, 61:91]
str(x)

# Summer precipitation over the full spatial extent
summer <- pr[, , 173:263]
str(summer)
```

[[.CFDataset

Get a variable or axis object from a data set

Description

This method can be used to retrieve a variable or axis from the data set by name.

Usage

```
## S3 method for class 'CFDataset'
x[[i]]
```

Arguments

- | | |
|----------------|--|
| <code>x</code> | An CFDataset to extract a variable or axis from. |
| <code>i</code> | The name of a variable or axis in <code>x</code> . If data set <code>x</code> has groups, <code>i</code> should be an absolute path to the object to retrieve. |

Details

If the data set has groups, the name `i` of the variable or axis should be fully qualified with the path to the group where the object is located. This fully qualified name can be retrieved with the `names()` and `dimnames()` functions, respectively.

Value

An instance of `CFVariable` or an `CFAxis` descendant class, or `NULL` if the name is not found.

Examples

```
fn <- system.file("extdata", "ERA5land_Rwanda_20160101.nc", package = "ncdfCF")
ds <- open_ncdf(fn)
v1 <- ds$var_names[1]
var <- ds[[v1]]
var
```

Index

[.CFVariable, 83
[.CFVariableL3b, 84
[[, CFDataset-method ([[.CFDataset), 85
[[.CFDataset, 85

aoi, 3
as_CF, 4

bracket_select ([.CFVariable), 83
bracket_select_l3b ([.CFVariableL3b), 84

CFAuxiliaryLongLat, 3, 5, 71, 73
CFAxis, 5, 7, 8, 36, 51, 52, 58, 61, 63, 64, 69, 71, 73, 74
CFAxisCharacter, 5, 12, 42, 64
CFAxisDiscrete, 5, 15, 65
CFAxisLatitude, 18, 65
CFAxisLongitude, 20, 66
CFAxisNumeric, 5, 22
CFAxisTime, 5, 26, 53, 66
CFAxisVertical, 8, 29, 67
CFBounds, 6, 8, 33, 73
CFCellMeasure, 35, 51, 57, 74
CFDataset, 37, 48, 71, 72
CFGridMapping, 40, 51, 75
CFLabel, 7, 8, 12, 42, 58, 71, 73
CFObject, 44
CFResource, 48, 72
CFStandardNames, 49
CFVariable, 4–6, 29, 36, 45, 51, 59, 63–67, 73, 74, 79, 80
CFVariable\$subset(), 4
CFVariableL3b, 58
CFVerticalParametricTerm, 60

dim.AOI, 62
dim.CFAxis, 63
dimnames (names.CFDataset), 67
dimnames(), 86

groupGeneric, 80

groups (names.CFDataset), 67

makeAxis, 63
makeAxis(), 9, 23
makeCharacterAxis, 64
makeCharacterAxis(), 13
makeDiscreteAxis, 65
makeDiscreteAxis(), 16, 64
makeLatitudeAxis, 65
makeLatitudeAxis(), 18, 64
makeLongitudeAxis, 66
makeLongitudeAxis(), 21, 64
makeTimeAxis, 66
makeTimeAxis(), 26, 64
makeVerticalAxis, 67
Math.CFVariable (Ops.CFVariable), 80

names(), 86
names.CFDataset, 67
ncdfCF::CFAxis, 12, 15, 18, 20, 22, 26, 29
ncdfCF::CFAxisNumeric, 18, 20, 29
ncdfCF::CFObject, 7, 12, 15, 18, 20, 22, 26, 29, 33, 40, 42, 51, 58, 60
ncdfCF::CFVariable, 58, 60
ncdfCF::NCObject, 69, 70, 77
NCDimension, 68, 73, 74, 79
NCGroup, 44, 48, 70, 78
NCObject, 75
NCVariable, 9, 13, 16, 19, 21, 23, 26, 30, 34, 43, 45, 52, 61, 73, 77

open_ncdf, 79
open_ncdf(), 37, 48
Ops.CFVariable, 80

peek_ncdf, 81

str.CFAxis, 82
str.CFDataset, 82