

Package ‘ocs4R’

September 16, 2021

Version 0.2-1

Date 2021-09-16

Title Interface to Open Collaboration Services (OCS) REST API

Maintainer Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Depends R (>= 3.3.0), methods

Imports R6, openssl, curl, httr, jsonlite, XML, keyring

Suggests testthat

Description Provides an Interface to Open Collaboration Services 'OCS' (<<https://www.open-collaboration-services.org/>>) REST API.

License MIT + file LICENSE

URL <https://github.com/eblondel/ocs4R>

BugReports <https://github.com/eblondel/ocs4R/issues>

LazyLoad yes

RoxygenNote 7.1.0

NeedsCompilation no

Author Emmanuel Blondel [aut, cre] (<<https://orcid.org/0000-0002-5870-5762>>)

Repository CRAN

Date/Publication 2021-09-16 07:00:05 UTC

R topics documented:

ocs4R	2
ocs4RLogger	2
ocsApiSharingManager	3
ocsApiUserProvisioningManager	4
ocsApiWebdavManager	5
ocsManager	7
ocsRequest	9

Index	11
--------------	-----------

ocs4R

Interface to 'OCS' REST API

Description

Provides an Interface to 'OCS' (<<https://www.open-collaboration-services.org/>>) REST API.

Details

Package: ocs4R
Type: Package
Version: 0.2-1
Date: 2021-09-16
License: MIT
LazyLoad: yes

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

ocs4RLogger

ocs4RLogger

Description

ocs4RLogger

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a simple logger

Abstract Methods

INFO(text) Logger to report information. Used internally

WARN(text) Logger to report warnings. Used internally

ERROR(text) Logger to report errors. Used internally

Note

Logger class used internally by ocs4R

ocsApiSharingManager *ocsApiSharingManager*

Description

ocsApiSharingManager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an ocsManager for the Sharing API

General Methods (inherited from 'ocsManager')

`new(url, user, pwd, logger, keyring_backend)` This method is used to instantiate an ocsApiSharingManager. The user/pwd are mandatory in order to connect to 'ocs'.

The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs).

The keyring_backend can be set to use a different backend for storing the user password with **keyring** (Default value is 'env').

`connect()` A method to connect to 'ocs' and set version/capabilities

`getVersion()` Get the 'ocs' server version

`getCapabilities()` Get the 'ocs' server capabilities

'OCS' Share API methods

`getShares(path, reshares, shared_with_me, state, subfiles, pretty)` Get list of shares as list. To return as data.frame, set pretty = TRUE. The method accepts additional parameters.

`createShare(path, name, shareType, shareWith, publicUpload, password, permissions = NULL, expireDate = NU`

Creates a share for the path (file or folder), given a name. The shareType should be among values 'user', 'group', 'publiclink' or 'federated'. The shareWith is required for shareType 'user' and 'group' and corresponds to the username or groupname. The permissions can be set among values 'read', 'update', 'create', 'delete', 'read-write', 'share', 'all'. By default the permissions will be the default permissions set by the ocs server (by default 'all').

`shareWithUser(path, name, username, permissions, pretty)` Shares a resource (file or folder) with a user given its username handled with argument username. The permissions can be set among values 'read', 'update', 'create', 'delete', 'read-write', 'share', 'all'. By default the permissions will be the default permissions set by the ocs server (by default 'all'). Returns the share properties as list (or as data.frame if pretty is set to TRUE).

`shareWithGroup(path, name, group, permissions, pretty)` Shares a resource (file or folder) with a group given its name handled with argument `group`. The permissions can be set among values `'read'`, `'update'`, `'create'`, `'delete'`, `'read-write'`, `'share'`, `'all'`. By default the permissions will be the default permissions set by the ocs server (by default `'all'`). Returns the share properties as `list` (or `asdata.frame` if `pretty` is set to `TRUE`).

`shareAsPublicLink(path, name, publicUpload, password, permissions, expireDate)` Shares a resource (file or folder) as public link. The function returns the public link generated by ocs.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

ocsApiUserProvisioningManager
ocsApiUserProvisioningManager

Description

ocsApiUserProvisioningManager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an ocsManager for Webdav API

General Methods (inherited from 'ocsManager')

`new(url, user, pwd, logger, keyring_backend)` This method is used to instantiate an ocsApiUserProvisioningManager. The `user/pwd` are mandatory in order to connect to `'ocs'`

The `logger` can be either `NULL`, `"INFO"` (with minimum logs), or `"DEBUG"` (for complete curl http calls logs).

The `keyring_backend` can be set to use a different backend for storing the user password with **keyring** (Default value is `'env'`).

`connect()` A method to connect to `'ocs'` and set version/capabilities

`getVersion()` Get the `'ocs'` server version

`getCapabilities()` Get the `'ocs'` server capabilities

User Provisioning API methods

`addUser(userid, email, password, groups)` Adds a user given a `userid` (required). All other fields (`email`, `password`, `groups`) are optional for the user creation. Returns `TRUE` if the user is added, `FALSE` otherwise.

`getUsers()` Get the list of users. This method returns a vector of class `'character'` giving the user IDs available in the OCS cloud platform.

`getUser(userid, pretty)` Get the user details from its `userid`. If the argument `pretty` is set to `TRUE`, this will return an object of class `data.frame`, otherwise (by default) it returns an object of class `list`.

`editUser(userid, key, value)` Edits a user, identifier by a `userid`. The user property to be edited should be set using its key (eg `display`) and the value to be modified for this key. Returns `TRUE` if the user is edited, `FALSE` otherwise.

`editUserDisplayName(userid, displayName)` Edits a user display name.

`editUserEmail(userid, email)` Edits a user email.

`editUserPassword(userid, password)` Edits a user password.

`editUserQuota(userid, quota)` Edits a user quota.

`enableUser(userid)` Enables a user. Returns `TRUE` if enabled.

`disableUser(userid)` Disables a user. Returns `TRUE` if disabled.

`deleteUser(userid)` Deletes a user. Returns `TRUE` if deleted.

`getUserGroups(userid)` Get user group(s). This method returns a vector of class `'character'` giving the `usergroups` IDs

`codeaddToGroup(userid, groupid)` Adds a user to a group.

`removeFromGroup(userid, groupid)` Removes a user from a group.

`getGroups(search, limit, offset)` Get the list of groups. This method returns a vector of class `'character'` giving the `usergroups` IDs

`getGroup(groupid)` Get the group including member users from its `groupid`.

`addGroup(groupid)` Add group given a `groupid` (required).

`deleteGroup(groupid)` Deletes a group. Returns `TRUE` if deleted.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

ocsApiWebdavManager *ocsApiWebdavManager*

Description

ocsApiWebdavManager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an ocsManager for Webdav API

General Methods (inherited from 'ocsManager')

`new(url, user, pwd, logger, keyring_backend)` This method is used to instantiate an ocsApi-WebdavManager. The user/pwd are mandatory in order to connect to 'ocs'.

The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs).

The `keyring_backend` can be set to use a different backend for storing the user password with **keyring** (Default value is 'env').

`connect()` A method to connect to 'ocs' and set version/capabilities

`getVersion()` Get the 'ocs' server version

`getCapabilities()` Get the 'ocs' server capabilities

WebDAV methods

`getWebdavRoot()` Get the 'ocs' WebDAV root URL

`listFiles(relPath)` WebDAV method to list folders/files given a relative path. The relative path is set to "/" by default, which corresponds to the root of the 'ocs' repository.

`makeCollection(name, relPath)` WebDAV method to make a collection. By default `relPath` is set to "/" (root). The name is the name of the new collection to be created. The function is recursive in the sense that a name can be provided as relative path of a collection tree (eg `newfolder1/newfolder2/newfolder3`), the function will create recursively as many collections are handled in the name.

`uploadFile(filename, relPath, delete_if_existing)` WebDAV method to upload a file. By default `relPath` is set to "/" (root).

`deleteFile(filename, relPath)` WebDAV method to delete a file. By default `relPath` is set to "/" (root).

`getPublicFile(share_token)` Get details of a shared public file given its share token

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

ocsManager

ocsManager

Description

ocsManager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an ocsManager

General Methods

`new(url, user, pwd, logger, keyring_backend)` This method is used to instantiate an ocsManager. The user/pwd are mandatory in order to connect to 'ocs'.

The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs).

The keyring_backend can be set to use a different backend for storing the user password with **keyring** (Default value is 'env').

`connect()` A method to connect to 'ocs' and set version/capabilities

`getVersion()` Get the 'ocs' server version

`getCapabilities()` Get the 'ocs' server capabilities

`getWebdavRoot()` Get the 'ocs' WebDAV root URL

WebDAV methods

`listFiles(relPath)` WebDAV method to list folders/files given a relative path. The relative path is set to "/" by default, which corresponds to the root of the 'ocs' repository.

`makeCollection(name, relPath)` WebDAV method to make a collection. By default relPath is set to "/" (root). The name is the name of the new collection to be created. The function is recursive in the sense that a name can be provided as relative path of a collection tree (eg newfolder1/newfolder2/newfolder3), the function will create recursively as many collections are handled in the name.

`uploadFile(filename, relPath)` WebDAV method to upload a file. By default relPath is set to "/" (root).

'OCS' Share API methods

`getShares(path, reshares, shared_with_me, state, subfiles, pretty)` Get list of shares as list. To return as `data.frame`, set `pretty = TRUE`. The method accepts additional parameters.

`createShare(path, name, shareType, shareWith, publicUpload, password, permissions = NULL, expireDate = NULL)`
Creates a share for the path (file or folder), given a name. The `shareType` should be among values `'user'`, `'group'`, `'publiclink'` or `'federated'`. The `shareWith` is required for `shareType` `'user'` and `'group'` and corresponds to the username or groupname. The permissions can be set among values `'read'`, `'update'`, `'create'`, `'delete'`, `'read-write'`, `'share'`, `'all'`. By default the permissions will be the default permissions set by the ocs server (by default `'all'`).

`shareWithUser(path, name, username, permissions, pretty)` Shares a resource (file or folder) with a user given its username handled with argument `username`. The permissions can be set among values `'read'`, `'update'`, `'create'`, `'delete'`, `'read-write'`, `'share'`, `'all'`. By default the permissions will be the default permissions set by the ocs server (by default `'all'`). Returns the share properties as list (or `asdata.frame` if `pretty` is set to `TRUE`).

`shareWithGroup(path, name, group, permissions, pretty)` Shares a resource (file or folder) with a group given its name handled with argument `group`. The permissions can be set among values `'read'`, `'update'`, `'create'`, `'delete'`, `'read-write'`, `'share'`, `'all'`. By default the permissions will be the default permissions set by the ocs server (by default `'all'`). Returns the share properties as list (or `asdata.frame` if `pretty` is set to `TRUE`).

`shareAsPublicLink(path, name, publicUpload, password, permissions, expireDate)` Shares a resource (file or folder) as public link. The function returns the public link generated by ocs.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
#Not Run:
#Connect to an OCS API
OCS <- ocsManager$new(url = ocs_url, user = ocs_user, pwd = ocs_pwd, logger = "DEBUG")
version <- OCS$getVersion()
caps <- OCS$getCapabilities()

#OCS User Provisioning API
#-----
#users
users <- OCS$getUsers() #get users
user <- OCS$getUser("admin") #get a user
user.df <- OCS$getUser("admin", TRUE) #the same user as data.frame
added <- OCS$addUser("john.doe", password = "ocs4john") #add a user
disabled <- OCS$disableUser("john.doe") #disable a user
enabled <- OCS$enableUser("john.doe") #enable a user
edited <- OCS$editUser("john.doe", key = "display", value = "John Doe") #edit user
#edit some user field
edited2 <- OCS$editUserDisplayName("john.doe", displayName = "John Doe Jr.")
deleted <- OCS$deleteUser("john.doe")
```



```

#groups
admingroups <- OCS$getUserGroups("admin")
groups <- OCS$getGroups()
added <- OCS$addGroup("scientists") #add a new group
sc_group <- OCS$getGroup("scientists") #get group details
added <- OCS$addToGroup("john.doe", "scientists") #add user to group
removed <- OCS$removeFromGroup("john.doe", "scientists") #remove user from group
deleted <- OCS$deleteGroup("scientists")

#OCS Webdav API
#-----
#list files
files <- OCS$listFiles()
subfiles <- OCS$listFiles("Documents")
#make collection
OCS$makeCollection("myfolder")
subfiles <- OCS$listFiles("myfolder")
#upload a file?
filename <- "magic.txt"
file.create(filename); writelines("ocs4R is great", filename)
#we upload the file in 'Documents' folder
OCS$uploadFile(filename, "/Documents")
#check if file is uploaded
OCS$listFiles('Documents')

#OCS Sharing API
#-----
#let's add a user with User provisioning API
added <- OCS$addUser("john.doe", password = "ocs4john") #add a user
#let's share the previously uploaded file with John Doe
OCS$shareWithUser("/Documents", filename, "john.doe")

## End(Not run)

```

 ocsRequest

ocsRequest

Description

ocsRequest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a generic 'ocs' web-service request

Methods

`new(type, url, request, user, logger)` This method is used to instantiate a object for doing an 'ocs' web-service request

`getRequest()` Get the request payload

`getRequestHeaders()` Get the request headers

`getStatus()` Get the request status code

`getResponse()` Get the request response

`getException()` Get the exception (in case of request failure)

`getResult()` Get the result TRUE if the request is successful, FALSE otherwise

Note

Abstract class used internally by **ocs4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Index

- * **api**
 - ocsApiSharingManager, [3](#)
 - ocsApiUserProvisioningManager, [4](#)
 - ocsApiWebdavManager, [5](#)
 - * **logger**
 - ocs4RLogger, [2](#)
 - * **manager**
 - ocsApiSharingManager, [3](#)
 - ocsApiUserProvisioningManager, [4](#)
 - ocsApiWebdavManager, [5](#)
 - ocsManager, [7](#)
 - * **ocs**
 - ocsApiSharingManager, [3](#)
 - ocsApiUserProvisioningManager, [4](#)
 - ocsApiWebdavManager, [5](#)
 - ocsManager, [7](#)
 - ocsRequest, [9](#)
 - * **request**
 - ocsRequest, [9](#)
 - * **sharing**
 - ocsApiSharingManager, [3](#)
 - * **userprovisioning**
 - ocsApiUserProvisioningManager, [4](#)
 - * **webdav**
 - ocsApiWebdavManager, [5](#)
- ocs4R, [2](#)
- ocs4R-package (ocs4R), [2](#)
- ocs4RLogger, [2](#)
- ocsApiSharingManager, [3](#)
- ocsApiUserProvisioningManager, [4](#)
- ocsApiWebdavManager, [5](#)
- ocsManager, [7](#)
- ocsRequest, [9](#)
- R6Class, [2-4](#), [6](#), [7](#), [9](#)