

Package ‘term’

September 27, 2021

Title Create, Manipulate and Query Parameter Terms

Version 0.3.3

Description Creates, manipulates, queries and repairs vectors of parameter terms. Parameter terms are the labels used to reference values in vectors, matrices and arrays. They represent the names in coefficient tables and the column names in 'mcmc' and 'mcmc.list' objects.

License MIT + file LICENSE

URL <https://poissonconsulting.github.io/term/>,
<https://github.com/poissonconsulting/term>

BugReports <https://github.com/poissonconsulting/term/issues>

Depends R (>= 3.4)

Imports chk (>= 0.7.0),
extras,
lifecycle,
purrr,
rlang,
universals,
vctrs

Suggests covr,
testthat (>= 3.0.0)

RdMacros lifecycle

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

R topics documented:

as_term	2
as_term_rcrd	3
chk_term	4
complete_terms	5

consistent_term	6
dims.term	6
dims.term_rcrd	7
is_incomplete_terms	8
is_inconsistent_terms	8
is_term	9
is_term_rcrd	10
NA_term	10
NA_term_rcrd	11
new_term	11
new_term_rcrd	12
normalize_terms	12
npars.term	13
npdims.term	14
nterms.default	14
nterms.term	15
nterms.term_rcrd	16
pars.character	16
pars.default	17
pars.term	18
pars.term_rcrd	18
pars_terms	19
pdims.term	20
pdims.term_rcrd	21
repair_terms	21
scalar_term	22
set_pars.term	23
subset.term	23
subset.term_rcrd	24
term	25
term_rcrd	26
tindex	26
valid_term	27
vld_term	28

Index 30

as_term	<i>Coerce to a Term Vector</i>
---------	--------------------------------

Description

Coerces an R object to a [term-vector\(\)](#).

Usage

```
as_term(x, ...)
```

```
as.term(x, ...)
```

```
## S3 method for class 'character'
```

```
as_term(x, repair = FALSE, normalize = repair, ...)
```

```
## S3 method for class 'numeric'
as_term(x, name = "par", ...)
```

Arguments

x	The object.
...	Unused.
repair	A flag specifying whether to repair terms.
normalize	A flag specifying whether to normalize terms.
name	A string specifying the name of the parameter.

Details

as_term has been **[Soft-deprecated]** for as_term.

Methods (by class)

- character: Coerce character vector to term vector
- numeric: Coerce numeric object to term vector

See Also

[term-vector\(\)](#) and [repair_terms\(\)](#)

Examples

```
as_term(matrix(1:4, 2))
as_term(c("parm3[10]", "parm3[2]", "parm[2,2]", "parm[1,1]"))
```

as_term_rcrd

Coerce to a Term Record

Description

Coerces an R object to a term_rcrd.

Usage

```
as_term_rcrd(x, ...)

## S3 method for class 'character'
as_term_rcrd(x, repair = FALSE, ...)

## S3 method for class 'numeric'
as_term_rcrd(x, name = "par", ...)

## S3 method for class 'term'
as_term_rcrd(x, repair = FALSE, ...)
```

Arguments

x	The object.
...	Unused.
repair	A flag specifying whether to repair terms.
name	A string specifying the name of the parameter.

Methods (by class)

- character: Coerce character vector to term_rcrd
- numeric: Coerce numeric vector to term_rcrd
- term: Coerce term vector to term_rcrd

See Also

[as_term\(\)](#) and [repair_terms\(\)](#)

Examples

```
as_term(matrix(1:4, 2))
as_term(c("parm3[10]", "parm3[2]", "parm[2,2]", "parm[1,1]"))
```

chk_term

Check Term or Term Record

Description

Checks if term using [vld_term\(\)](#) or [vld_term_rcrd\(\)](#).

Usage

```
chk_term(x, validate = "complete", x_name = NULL)
```

```
chk_term_rcrd(x, validate = "complete", x_name = NULL)
```

Arguments

x	The object.
validate	A string specifying the level of the validation. The possible values in order of increasing strictness are 'class', 'valid', 'consistent' and 'complete'.
x_name	A string of the name of object x or NULL.

Value

NULL, invisibly. Called for the side effect of throwing an error if the condition is not met.

Functions

- [chk_term_rcrd](#): Check Term Record

Examples

```
# chk_term
x <- term("x[2]", "x[1]")
chk_term(x)
x <- c("x[2]", "x[1]")
try(chk_term(x, validate = "sorted"))

# chk_term_rcrd
x <- term_rcrd("x[2]", "x[1]")
chk_term_rcrd(x)
x <- c("x[2]", "x[1]")
try(chk_term_rcrd(x, validate = "sorted"))
```

complete_terms	<i>Complete Terms</i>
----------------	-----------------------

Description

Completes an object's terms.

Usage

```
complete_terms(x, ...)
```

```
## S3 method for class 'term'
complete_terms(x, ...)
```

```
## S3 method for class 'term_rcrd'
complete_terms(x, ...)
```

Arguments

x	The object.
...	Unused.

Details

It must not have any invalid or missing (NA) values.

Methods (by class)

- term: Complete Terms for a term Vector
- term_rcrd: Complete Terms for a term_rcrd vector

See Also

[term-vector\(\)](#), [repair_terms\(\)](#) and [is_incomplete_terms\(\)](#).

Examples

```
complete_terms(term("b[3]", "b[1]", "b[2]"))
complete_terms(term("z[2,2]", "z[1,1]"))
## Not run:
complete_terms(term_rcrd("b[3]", "b[1]", "b[2]"))
complete_terms(term_rcrd("z[2,2]", "z[1,1]"))

## End(Not run)
```

consistent_term

Consistent Terms

Description

Test whether the number of dimensions of terms in the same parameter are consistent.

Usage

```
consistent_term(x)
```

Arguments

x The object.

Value

A logical vector indicating whether the number of dimensions is consistent.

See Also

[term-vector\(\)](#) and [npdims\(\)](#)

Examples

```
consistent_term(term("alpha[1]", "alpha[3]", "beta[1,1]", "beta[2,1]"))
consistent_term(term("alpha[1]", NA_term_, "beta[1,1]", "beta[2]"))
```

dims.term

Dimensions

Description

Gets the dimensions of an object.

Usage

```
## S3 method for class 'term'
dims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Details

Unlike `base::dim()`, `dims` returns the length of an atomic vector.

Value

An integer vector of the dimensions.

See Also

[base::dim\(\)](#)

Other dimensions: [ndims\(\)](#), [npdims\(\)](#), [pdims\(\)](#)

Examples

```
dims(term("beta[1,1]"))  
dims(term("beta[1,1]", "beta[1,2]"))
```

dims.term_rcrd

Dimensions

Description

Gets the dimensions of an object.

Usage

```
## S3 method for class 'term_rcrd'  
dims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Details

Unlike `base::dim()`, `dims` returns the length of an atomic vector.

Value

An integer vector of the dimensions.

See Also

[base::dim\(\)](#)

Other dimensions: [ndims\(\)](#), [npdims\(\)](#), [pdims\(\)](#)

Examples

```
dims(term_rcrd("beta[1,1]"))
dims(term_rcrd("beta[1,1]", "beta[1,2]"))
```

is_incomplete_terms *Is Incomplete Terms*

Description

Tests whether a term vector has absent elements. The vector should not require repairing.

Usage

```
is_incomplete_terms(x, ...)
```

Arguments

x	The object.
...	Unused.

Value

A logical scalar indicating whether the object's terms are incomplete.

See Also

[term-vector\(\)](#) and [complete_terms\(\)](#)

Examples

```
is_incomplete_terms(term("b[2]"))
is_incomplete_terms(term("b[2]", "b[1]"))
is_incomplete_terms(term("b[2]", "b[1]", "b[1]"))
```

is_inconsistent_terms *Is Inconsistent Terms*

Description

Tests whether a term vector has inconsistent elements. Returns TRUE if includes missing or invalid terms.

Usage

```
is_inconsistent_terms(x, ...)
```

Arguments

x	The object.
...	Unused.

Value

A logical scalar indicating whether the object's terms are inconsistent.

See Also

[term-vector\(\)](#) and [consistent_term\(\)](#)

Examples

```
is_inconsistent_terms(term("b[2]"))
is_inconsistent_terms(term("b[2]", "b[1]"))
is_inconsistent_terms(term("b[2]", "b[1,1]"))
```

is_term

Is Term

Description

Tests whether an R object inherits from S3 class term.

Usage

```
is_term(x)
```

Arguments

x The object.

Details

It does not test the validity of consistency of the term elements.

Value

A flag indicating whether the test was positive.

See Also

[term-vector\(\)](#), [vld_term\(\)](#), [valid_term\(\)](#) and [consistent_term\(\)](#)

Examples

```
is_term(c("parameter[2]", "parameter[10]"))
is_term(term("parameter[2]", "parameter[10]"))
```

`is_term_rcrd`*Is Term Record*

Description

Tests whether an R object inherits from S3 class `term_rcrd`.

Usage

```
is_term_rcrd(x)
```

Arguments

`x` The object.

Details

It does not test the validity of consistency of the term elements.

Value

A flag indicating whether the test was positive.

See Also

[valid_term\(\)](#) and [consistent_term\(\)](#)

Examples

```
is_term_rcrd(new_term_rcrd())
```

`NA_term_`*Missing Term*

Description

A missing term element.

Usage

```
NA_term_
```

Format

An object of class `term` (inherits from `vctrs_vctr`) of length 1.

See Also

[term-vector\(\)](#)

Examples

```
is_term(NA_term_)
is.na(NA_term_)
```

NA_term_rcrd_	<i>Missing Term</i>
---------------	---------------------

Description

A missing term element of term_rcrd type.

Usage

```
NA_term_rcrd_
```

Format

An object of class term_rcrd (inherits from vctrs_rcrd, vctrs_vctr) of length 1.

See Also

[term-vector\(\)](#)

Examples

```
is_term_rcrd(NA_term_)
is.na(NA_term_)
```

new_term	<i>Construct a New Term Object</i>
----------	------------------------------------

Description

Use this function to quickly construct a [term](#) object from a character vector, without checking the input. Use [term\(\)](#) to repair the input.

Usage

```
new_term(x = character())
```

Arguments

x A character vector.

See Also

[new_term_rcrd\(\)](#)

Examples

```

new_term()
new_term(c("a", "b[1]", "b[2]"))

# Terms are not checked for validity:
new_term("r[")
repair_terms(new_term("r["))

```

new_term_rcrd	<i>Construct a New Term Record Object</i>
---------------	---

Description

Use this function to quickly construct a term_rcrd object.

Usage

```

new_term_rcrd(
  x = data.frame(par = character(), dim = I(list()), stringsAsFactors = FALSE)
)

```

Arguments

x A data frame with columns par and dim.

See Also

[new_term\(\)](#)

Examples

```

new_term_rcrd()
## Not run:
new_term_rcrd(data.frame(
  par = c("x", "x", "y"), dim = I(list(1, 2, c(2,2))),
  stringsAsFactors = FALSE
))

## End(Not run)

```

normalize_terms	<i>Normalize Terms</i>
-----------------	------------------------

Description

Normalizes a term vector.

Usage

```

normalize_terms(x)

```

Arguments

x The object.

Details

If a parameter such as b is a scalar then b[1] is replaced by b but if higher indices are included such as b[2] then b is replaced by b[1].

Value

The normalized term vector.

See Also

[term-vector\(\)](#) and [repair_terms\(\)](#)

Examples

```
normalize_terms(new_term(c("b", "b[3]")))
normalize_terms(new_term(c("b[1]", "a[3]")))
```

npars.term

Number of Parameters

Description

Gets the number of parameters of an object.

The default methods returns the length of [pars\(\)](#) if none are NA, otherwise it returns NA.

Usage

```
## S3 method for class 'term'
npars(x, scalar = NULL, ...)
```

Arguments

x An object.

scalar A flag specifying whether to by default return all parameters (NULL), or only scalar parameters (TRUE) or only non-scalar parameters (FALSE).

... Other arguments passed to methods.

Value

An integer scalar of the number of parameters.

See Also

[pars\(\)](#)

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [nsams\(\)](#), [nsims\(\)](#), [nterms\(\)](#)

Other parameters: [pars\(\)](#), [set_pars\(\)](#)

Examples

```
npars(term("sigma", "alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]"))
```

npdims.term	<i>Number of Dimensions of Each Parameter</i>
-------------	---

Description

The terms argument is [**Defunct**]

Usage

```
## S3 method for class 'term'
npdims(x, terms = FALSE, ...)
```

Arguments

x	An object.
terms	A flag specifying whether to get the number of dimensions for each term element.
...	Other arguments passed to methods.

Value

A named integer vector of the number of dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [pdims\(\)](#)

Examples

```
npdims(term("alpha[1]", "alpha[3]", "beta[1,1]", "beta[2,1]"))
```

nterms.default	<i>Number of Terms</i>
----------------	------------------------

Description

Gets the number of terms of an object.

Usage

```
## Default S3 method:
nterms(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nterms(term("alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]"))
nterms(term("alpha[1]", "alpha[1]", "beta[1,1]", "beta[1,1]"))
```

nterms.term

Number of Terms of a Term

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'term'
nterms(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nterms(term("alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]"))
nterms(term("alpha[1]", "alpha[1]", "beta[1,1]", "beta[1,1]"))
```

nterms.term_rcrd	<i>Number of Terms of a Term Record</i>
------------------	---

Description

Gets the number of terms of an MCMC object.

Usage

```
## S3 method for class 'term_rcrd'
nterms(x, ...)
```

Arguments

x	An object.
...	Other arguments passed to methods.

Value

A integer scalar of the number of terms.

See Also

Other MCMC dimensions: [nchains\(\)](#), [niters\(\)](#), [npars\(\)](#), [nsams\(\)](#), [nsims\(\)](#)

Examples

```
nterms(as_term_rcrd(term("alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]")))
nterms(as_term_rcrd(term("alpha[1]", "alpha[1]", "beta[1,1]", "beta[1,1]")))
```

pars.character	<i>Parameter Names</i>
----------------	------------------------

Description

Gets the parameter names.

Usage

```
## S3 method for class 'character'
pars(x, scalar = NULL, ...)
```

Arguments

x	An object.
scalar	A flag specifying whether to by default return all parameters (NULL), or only scalar parameters (TRUE) or only non-scalar parameters (FALSE).
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

[universals::pars](#)

Other parameters: [pars.default\(\)](#), [pars.term_rcrd\(\)](#), [pars.term\(\)](#), [pars_terms\(\)](#)

Examples

```
pars(c("a", "b[1]", "a[3]"))
```

pars.default	<i>Parameter Names</i>
--------------	------------------------

Description

Gets the parameter names.

Usage

```
## Default S3 method:
pars(x, scalar = NULL, ...)
```

Arguments

x	An object.
scalar	A flag specifying whether to by default return all parameters (NULL), or only scalar parameters (TRUE) or only non-scalar parameters (FALSE).
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

[universals::pars](#)

Other parameters: [pars.character\(\)](#), [pars.term_rcrd\(\)](#), [pars.term\(\)](#), [pars_terms\(\)](#)

Examples

```
pars(matrix(1:4, nrow = 2))
```

pars.term *Parameter Names*

Description

Gets the parameter names.

Usage

```
## S3 method for class 'term'
pars(x, scalar = NULL, terms = FALSE, ...)
```

Arguments

x	An object.
scalar	A flag specifying whether to by default return all parameters (NULL), or only scalar parameters (TRUE) or only non-scalar parameters (FALSE).
terms	A flag specifying whether to return the parameter name for each term element.
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

[universals::pars](#)

Other parameters: [pars.character\(\)](#), [pars.default\(\)](#), [pars.term_rcrd\(\)](#), [pars_terms\(\)](#)

Examples

```
term <- term(
  "alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]",
  "beta[1,2]", "beta[2,2]", "sigma", NA
)
pars(term)
pars(term, scalar = TRUE)
pars(term, scalar = FALSE)
```

pars.term_rcrd *Parameter Names*

Description

Gets the parameter names.

Usage

```
## S3 method for class 'term_rcrd'
pars(x, scalar = NULL, ...)
```

Arguments

x	An object.
scalar	A flag specifying whether to by default return all parameters (NULL), or only scalar parameters (TRUE) or only non-scalar parameters (FALSE).
...	Other arguments passed to methods.

Value

A character vector of the names of the parameters.

See Also

[universals::pars](#)

Other parameters: [pars.character\(\)](#), [pars.default\(\)](#), [pars.term\(\)](#), [pars_terms\(\)](#)

Examples

```
term <- term(
  "alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]",
  "beta[1,2]", "beta[2,2]", "sigma", NA
)
pars(term)
pars(term, scalar = TRUE)
pars(term, scalar = FALSE)
```

pars_terms

Term Parameters

Description

Gets the name of each parameter for each term.

Usage

```
pars_terms(x, scalar = NULL, ...)
```

Arguments

x	A term vector.
scalar	A flag specifying whether to by default return all parameters (NULL), or only scalar parameters (TRUE) or only non-scalar parameters (FALSE).
...	Unused.

Details

The scalar argument is **[Defunct]**

Value

A character vector of the term parameter names.

See Also

Other parameters: [pars.character\(\)](#), [pars.default\(\)](#), [pars.term_rcrd\(\)](#), [pars.term\(\)](#)

Examples

```
term <- term(
  "alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]",
  "beta[1,2]", "beta[2,2]", "sigma", NA
)
pars_terms(term)
```

pdims.term

Parameter Dimensions

Description

Gets the dimensions of each parameter of an object.

Usage

```
## S3 method for class 'term'
pdims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Details

Errors if the parameter dimensions are invalid or inconsistent.

A named list of the dimensions of each parameter can be converted into the equivalent [term-vector\(\)](#) using [term\(\)](#).

Value

A named list of integer vectors of the dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#)

Examples

```
pdims(term("alpha[1]", "alpha[3]", "beta[1,1]", "beta[2,1]"))
```

pdims.term_rcrd *Parameter Dimensions*

Description

Gets the dimensions of each parameter of an object.

Usage

```
## S3 method for class 'term_rcrd'  
pdims(x, ...)
```

Arguments

x An object.
... Other arguments passed to methods.

Details

Errors if the parameter dimensions are inconsistent.

Value

A named list of integer vectors of the dimensions of each parameter.

See Also

Other dimensions: [dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#)

Examples

```
pdims(as_term_rcrd(term("alpha[1]", "alpha[3]", "beta[1,1]", "beta[2,1]")))
```

repair_terms *Repair Terms*

Description

Repairs a terms vector.

Usage

```
repair_terms(x, normalize = TRUE)
```

Arguments

x The object.
normalize A flag specifying whether to normalize terms.

Details

Invalid elements are replaced by missing values and spaces removed.

Value

The repaired term vector.

See Also

[term-vector\(\)](#), [valid_term\(\)](#) and [normalize_terms\(\)](#)

Examples

```
repair_terms(new_term(c("b[3]", "b")))
repair_terms(new_term(c("a[3]", "b[1]")))
repair_terms(new_term(c("a [3]", " b [ 1 ] ")))
repair_terms(new_term(c("a", NA)))
```

 scalar_term

Scalar Term

Description

Test whether each term is a scalar.

Usage

```
scalar_term(x)
```

Arguments

x The object.

Value

A logical vector indicating whether the term is a scalar.

Examples

```
scalar_term(term("alpha[1]", "alpha[3]", "beta[1]", "sigma[3]"))
scalar_term(term("alpha[1]", NA_term_, "beta[1]", "beta[3]"))
```

set_pars.term	<i>Set Parameter Names</i>
---------------	----------------------------

Description

Sets an object's parameter names.

The assignment version `pars<-()` forwards to `set_pars()`.

Usage

```
## S3 method for class 'term'
set_pars(x, value, ...)
```

Arguments

<code>x</code>	An object.
<code>value</code>	A character vector of the new parameter names.
<code>...</code>	Other arguments passed to methods.

Details

`value` must be a unique character vector of the same length as the object's parameters.

Value

The modified object.

See Also

Other parameters: [npars\(\)](#), [pars\(\)](#)

Examples

```
term <- as_term(c("b[2]", "a[1]", "b[3,3]"))
set_pars(term, c("x", "y"))
```

subset.term	<i>Subset Term Vector</i>
-------------	---------------------------

Description

Subsets a term vector.

Usage

```
## S3 method for class 'term'
subset(x, pars = NULL, select = NULL, ...)
```

Arguments

x	The object.
pars	A character vector of parameter names.
select	A character vector of the names of the parameters to include in the subsetted object.
...	Unused.

Details

The select argument is **[Defunct]**.

Value

The modified term vector.

See Also

[term-vector\(\)](#)

Examples

```
term <- term(
  "alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]",
  "beta[1,2]", "beta[2,2]", "sigma"
)
subset(term, "beta")
subset(term, c("alpha", "sigma"))
```

subset.term_rcrd

Subset Term Record

Description

Subsets a term_rcrd.

Usage

```
## S3 method for class 'term_rcrd'
subset(x, pars = NULL, ...)
```

Arguments

x	The object.
pars	A character vector of parameter names.
...	Unused.

Value

The modified term vector.

See Also

[term_rcrd_object\(\)](#)

Examples

```
term_rcrd <- term_rcrd(
  "alpha[1]", "alpha[2]", "beta[1,1]", "beta[2,1]",
  "beta[1,2]", "beta[2,2]", "sigma"
)
## Not run:
subset(term_rcrd, "beta")
subset(term_rcrd, c("alpha", "sigma"))

## End(Not run)
```

term	<i>Create Term Vector</i>
------	---------------------------

Description

Creates a term vector from values. A term vector is an S3 vector of parameter terms of the form p , $q[\#]$ or $r[\#, \#]$ where $\#$ are positive integers. This function checks that all terms are valid but does not require stronger levels of consistency, see `chk_valid()` for details.

Usage

```
term(...)
```

Arguments

... Unnamed values are term values, named values describe the parameter in the name and the dimensionality in the value.

Value

A term vector.

See Also

[dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#) and [pdims\(\)](#)

Other term: [term_rcrd\(\)](#), [tindex\(\)](#)

Examples

```
term()
term("p", "q[1]", "q[2]", "q[3]")
term("q[1]", "q[2]", "q[3]")
combined <- term(par = 2:4, "alpha")
pdims(combined)
term(!!!pdims(combined))

# Invalid terms are rejected:
try(term("r["))
```

```
# Valid terms are repaired
term("r [ 1 ,2 ]")
```

term_rcrd	<i>Create Term Record</i>
-----------	---------------------------

Description

Creates a `term_rcrd` from values. This function checks that all terms are valid but does not require stronger levels of consistency, see `chk_valid()` for details.

Usage

```
term_rcrd(...)
```

Arguments

... Unnamed values are term values, named values describe the parameter in the name and the dimensionality in the value.

Value

A `term_rcrd` vector.

See Also

[dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#) and [pdims\(\)](#)

Other term: [term\(\)](#), [tindex\(\)](#)

Examples

```
term_rcrd()
## Not run:
term_rcrd("p", "q[1]", "q[2]", "q[3]")
term_rcrd("q[1]", "q[2]", "q[3]")

## End(Not run)
```

tindex	<i>Term Index</i>
--------	-------------------

Description

Gets the index for each term of an term or `term_rcrd` object.

Usage

```
tindex(x)
```

Arguments

x The object.

Details

For example the index of `beta[2,1]` is `c(2L,1L)` while the index for `sigma` is `1L`. It is useful for extracting the values of individual terms.

Value

A named list of integer vectors of the index for each term.

See Also

[dims\(\)](#), [ndims\(\)](#), [npdims\(\)](#) and [pdims\(\)](#)

Other term: [term_rcrd\(\)](#), [term\(\)](#)

Examples

```
tindex(term("alpha", "alpha[2]", "beta[1,1]", "beta[2 ,1 ]"))
```

valid_term

Test Valid Terms

Description

Test whether each element in a term or term_rcrd object is valid.

Usage

```
valid_term(x)
```

Arguments

x The object.

Details

Repairing a term vector replaces invalid terms with missing values.

Value

A logical vector indicating whether each term is valid.

See Also

[term-vector\(\)](#) and [repair_terms\(\)](#)

Other valid: [vld_term\(\)](#)

Examples

```
# valid term elements
valid_term(term("a", "a [3]", " b [ 1 ] ", "c[1,300,10]"))
# invalid term elements
valid_term(new_term(c("a b", "a[1]b", "a[0]", "b[1,]", "c[]", "d[1][2]")))
```

vld_term

*Validate Term or Term Record***Description**

Validates the elements of a term or term_rcrd vector. Use [chk_s3_class\(\)](#) to check if an object is a term or term_rcrd.

Usage

```
vld_term(x, validate = "complete")

vld_term_rcrd(x, validate = "complete")
```

Arguments

x	The object.
validate	A string specifying the level of the validation. The possible values in order of increasing strictness are 'class', 'valid', 'consistent' and 'complete'.

Details

Internal validity of a term can be checked on three levels:

- "valid" checks that all terms are of the form x, x[#], x[#,#] etc. where x is an identifier and # are positive integers.
- "consistent" checks that all terms are addressed with the same dimensionality; the terms x[1] and x[2,3] are inconsistent.
- "complete" checks that the values span all possible values across all dimensions; if x[3,4] exist, the vector must contain at least 11 more terms to be consistent (x[1,1] to x[1,4], x[2,1] to x[2,4] and x[3,1] to x[3,3]).

Missing values are ignored as are duplicates and order.

Value

A flag indicating whether the condition was met.

Functions

- [vld_term_rcrd](#): Validate Term Record

See Also

[chk_term\(\)](#)

Other valid: [valid_term\(\)](#)

Other valid: [valid_term\(\)](#)

Examples

```
# vld_term
vld_term(c("x[2]", "x[1]"))
vld_term(term("x[2]", "x[1]"))

# vld_term_rcrd
vld_term_rcrd(c("x[2]", "x[1]"))
vld_term_rcrd(term_rcrd("x[2]", "x[1]"))
```

Index

- * **datasets**
 - NA_term_, 10
 - NA_term_rcrd_, 11
- * **parameters**
 - pars.character, 16
 - pars.default, 17
 - pars.term, 18
 - pars.term_rcrd, 18
 - pars_terms, 19
- * **term**
 - term, 25
 - term_rcrd, 26
 - tindex, 26
- * **valid**
 - valid_term, 27
 - vld_term, 28
- as.term(as_term), 2
- as_term, 2
- as_term(), 4
- as_term_rcrd, 3
- base::dim(), 7
- chk_s3_class(), 28
- chk_term, 4
- chk_term(), 28
- chk_term_rcrd(chk_term), 4
- complete_terms, 5
- complete_terms(), 8
- consistent_term, 6
- consistent_term(), 9, 10
- dims, 14, 20, 21
- dims(), 25–27
- dims.term, 6
- dims.term_rcrd, 7
- is_incomplete_terms, 8
- is_incomplete_terms(), 5
- is_inconsistent_terms, 8
- is_term, 9
- is_term_rcrd, 10
- NA_term_, 10
- NA_term_rcrd_, 11
- nchains, 13, 15, 16
- ndims, 7, 14, 20, 21
- ndims(), 25–27
- new_term, 11
- new_term(), 12
- new_term_rcrd, 12
- new_term_rcrd(), 11
- niters, 13, 15, 16
- normalize_terms, 12
- normalize_terms(), 22
- npars, 15, 16, 23
- npars.term, 13
- npdims, 7, 20, 21
- npdims(), 6, 25–27
- npdims.term, 14
- nsams, 13, 15, 16
- nsims, 13, 15, 16
- nterms, 13
- nterms.default, 14
- nterms.term, 15
- nterms.term_rcrd, 16
- pars, 13, 23
- pars(), 13
- pars.character, 16, 17–20
- pars.default, 17, 17, 18–20
- pars.term, 17, 18, 19, 20
- pars.term_rcrd, 17, 18, 18, 20
- pars_terms, 17–19, 19
- pdims, 7, 14
- pdims(), 25–27
- pdims.term, 20
- pdims.term_rcrd, 21
- repair_terms, 21
- repair_terms(), 3–5, 13, 27
- scalar_term, 22
- set_pars, 13
- set_pars.term, 23
- subset.term, 23
- subset.term_rcrd, 24
- term, 11, 25, 26, 27

`term()`, [11](#), [20](#)
`term-object (term)`, [25](#)
`term-vector (term)`, [25](#)
`term_object (term)`, [25](#)
`term_rcrd`, [25](#), [26](#), [27](#)
`term_rcrd-object (term_rcrd)`, [26](#)
`term_rcrd_object (term_rcrd)`, [26](#)
`term_rcrd_object()`, [25](#)
`term_vector (term)`, [25](#)
`tindex`, [25](#), [26](#), [26](#)

`universals::pars`, [17–19](#)

`valid_term`, [27](#), [28](#)
`valid_term()`, [9](#), [10](#), [22](#)
`vld_term`, [27](#), [28](#)
`vld_term()`, [4](#), [9](#)
`vld_term_rcrd (vld_term)`, [28](#)
`vld_term_rcrd()`, [4](#)