

Package ‘kstMatrix’

December 18, 2025

Type Package

Date 2025-12-18

Version 2.2-0

Title Basic Functions in Knowledge Space Theory Using Matrix Representation

Description Knowledge space theory by Doignon and Falmagne (1999) [doi:10.1007/978-3-642-58625-5](https://doi.org/10.1007/978-3-642-58625-5) is a set- and order-theoretical framework, which proposes mathematical formalisms to operationalize knowledge structures in a particular domain. The 'kstMatrix' package provides basic functionalities to generate, handle, and manipulate knowledge structures and knowledge spaces. Opposed to the 'kst' package, 'kstMatrix' uses matrix representations for knowledge structures. Furthermore, 'kstMatrix' contains several knowledge spaces developed by the research group around Cornelia Dowling through querying experts.

Depends R (>= 4.4.0)

Imports stats, grDevices, sets, pks, tidyr, DiagrammeR, DiagrammeRsvg, rsvg

Suggests knitr, markdown

Maintainer Cord Hockemeyer <cord.hockemeyer@uni-graz.at>

License GPL-3

NeedsCompilation yes

Repository CRAN

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

VignetteBuilder knitr

Author Cord Hockemeyer [aut, cre],
Peter Steiner [aut],
Wai Wong [aut]

Date/Publication 2025-12-18 16:10:02 UTC

Contents

cad	3
fractions	4
kmassess	4
kmassessbayesian	8
kmassesshalfsplit	9
kmassessinformativ	9
kmassessmentsimulation	10
kmassessmultiplicative	12
kmbasis	13
kmbasis.kmsurmisefunction	13
kmbasis.kmsurmisere	14
kmbasis.matrix	14
kmbasisfringe	15
kmbasisneighbourhood	16
kmcolors	17
kmdist	17
kmdoubleequal	18
kmeqreduction	19
kmfamset	19
kmfringe	20
kmgenerate	21
kmgradations	21
kmiita2SR	22
kmiswellgraded	23
kmlearningpaths	24
kmneighbourhood	24
kmnneighbourhood	25
kmnotions	26
kmsetiselement	26
kmSF2basis	27
kmsimulate	28
kmSPACE	29
kmSR2basis	29
kmSRvalidate	30
kmstructure	31
kmsurmisefunction	31
kmsurmisere	32
kmsymmsetdiff	33
kmtrivial	34
kmunionclosure	34
kmvalidate	35
phsg	36
plot	36
readwrite	38
xpl	39

cad	<i>Knowledge spaces on AutoCAD knowledge</i>
-----	--

Description

Bases of knowledge spaces on AutoCAD knowledge obtained from querying experts.

Usage

cad

Format

A list containing seven bases (cad1 to cad6, and cadmaj) in binary matrix form. Each matrix has 28 columns representing the different knowledge items and a varying number of rows containing the basis elements.

Details

Six experts were queried about prerequisite relationships between 28 AutoCAD knowledge items (Dowling, 1991; 1993). A seventh basis represents those prerequisite relationships on which the majority (4 out of 6) of the experts agree (Dowling & Hockemeyer, 1998).

References

- Dowling, C. E. (1991). *Constructing Knowledge Structures from the Judgements of Experts*. Habilitationsschrift, Technische Universität Carolo-Wilhelmina, Braunschweig, Germany.
- Dowling, C. E. (1993). Applying the basis of a knowledge space for controlling the questioning of an expert. *Journal of Mathematical Psychology*, 37, 21–48.
- Dowling, C. E. & Hockemeyer, C. (1998). Computing the intersection of knowledge spaces using only their basis. In Cornelia E. Dowling, Fred S. Roberts, & Peter Theuns, editors, *Recent Progress in Mathematical Psychology*, pp. 133–141. Lawrence Erlbaum Associates Ltd., Mahwah, NJ.

See Also

Other Data: [fractions](#), [phsg](#), [readwrite](#), [xpl](#)

fractions

Knowledge spaces on fractions

Description

Bases of knowledge spaces on fractions obtained from querying experts.

Usage

fractions

Format

A list containing four bases (frac1 to frac3, and fracmaj) in binary matrix form. Each matrix has 77 columns representing the different knowledge items and a varying number of rows containing the basis elements.

Details

Three experts were queried about prerequisite relationships between 77 items on fractions (Baumunk & Dowling, 1997). A forth basis represents those prerequisite relationships on which the majority of the experts agree (Dowling & Hockemeyer, 1998).

References

- Baumunk, K. & Dowling, C. E. (1997). Validity of spaces for assessing knowledge about fractions. *Journal of Mathematical Psychology*, 41, 99–105.
- Dowling, C. E. & Hockemeyer, C. (1998). Computing the intersection of knowledge spaces using only their basis. In Cornelia E. Dowling, Fred S. Roberts, & Peter Theuns, editors, *Recent Progress in Mathematical Psychology*, pp. 133–141. Lawrence Erlbaum Associates Ltd., Mahwah, NJ.

See Also

Other Data: [cad](#), [phsg](#), [readwrite](#), [xpl](#)

kmassess

Perform a probabilistic knowledge assessment

Description

kmassess performs a probabilistic knowledge assessment for a given response vector, knowledge structure, and BLIM parameters.

kmsassess performs a simplified probabilistic knowledge assessment for a given response vector, knowledge structure, and BLIM parameters. It assumes an equal probability distribution over the knowledge structure as starting point and identical beta and eta values for all items.

Usage

```

kmassess(
  r,
  pks,
  questioning,
  update,
  beta,
  eta,
  zeta0,
  zeta1,
  threshold,
  probdev = FALSE
)

kmsassess(
  r,
  ks,
  questioning,
  update,
  beta,
  eta,
  zeta0,
  zeta1,
  threshold,
  probdev = FALSE
)

```

Arguments

<code>r</code>	Response pattern (binary vector)
<code>pks</code>	Probabilistic knowledge structure: a data frame with a probability distribution in the first columns and the structure matrix in the subsequent columns.
<code>questioning</code>	Questioning rule ("halfsplit" or "informative")
<code>update</code>	Update rule ("Bayesian" or "multiplicative")
<code>beta</code>	Careless error probability
<code>eta</code>	Lucky guess probability
<code>zeta0</code>	Update parameter for wrong responses
<code>zeta1</code>	Update parameter for correct responses
<code>threshold</code>	Probability threshold for stopping criterion
<code>probdev</code>	Provide information on the probability development including Hasse diagrams stored in <code>tempdir()</code> . Defaults to FALSE.
<code>ks</code>	Knowledge structure: a binary matrix

Details

kmassess implements the stochastic assessment procedures according to Doignon & Falmagne, 1999, chapter 10.

kmassess stops if the number of questions has reached twice the number of items.

Value

A list with the following elements:

state Diagnosed knowledge state (binary vector)

probs Resulting probability distribution. If probdev is set to TRUE, a list of probability distributions for each step is given instead.

queried Sequence of items used in the assessment (list)

qtime Average time for finding a question

utime Average time for updating the probabilities

A list with the following elements:

state Diagnosed knowledge state (binary vector)

probs Resulting probability distribution. If probdev is set to TRUE, a list of probability distributions for each step is given instead.

queried Sequence of items used in the assessment (list)

qtime Average time for finding a question

utime Average time for updating the probabilities

Background

Doignon & Falmagne (1985, 1999) proposed knowledge space theory originally with adaptive knowledge assessment in mind. The basic idea is to apply prerequisite relationships between items for reducing the number of problems to be posed to a learner in knowledge assessment.

Falmagne & Doignon (1988; Doignon & Falmagne, 1999, chapitre 10) proposed a class of stochastic procedures for such adaptive assessment which take into account that careless errors and lucky guesses may happen during the assessment by estimating a probability distribution over the knowledge structure. Such an assessment consists of three important parts

- Question rule
- Update rule
- Stopping criterion

For the **question rule**, they propose the *halfsplit* and the *informative* rules, implemented in `kmassesshalfsplit` and `kmassessinformative`.

For the **update rule**, they again propose two possibilities there the *multiplicative rule* is a generalisation of the (classical) *Bayesian update rule* implemented here in `kmassessmultiplicative` and `kmassessbayesian`, respectively.

As **stopping criterion**, usually a threshold for the maximal probability for one knowledge state is used. It is strongly recommended to keep this larger than 0.5 in order to have one unequivocal resulting state (see also Hockemeyer, 2002).

Framework of assessment functions within the kstMatrix package::

The founding stones are the four aforementioned functions for finding suitable questions and for updating the probability estimates, respectively. They could also be used in an interactive system, e.g. a Shiny app, for "real" adaptive assessment.

The remaining three assessment functions serve for mere simulation of adaptive assessment. `kmassess` takes, among others, a full response pattern as parameter and takes the responses for the selected questions from this vector. `kmsassess` is a simplified version where the update parameters (beta and eta for Bayesian or `zeta0` and `zeta1` for multiplicative update, respectively) are identical for all items whereas they are item-specific in `kmassess`. Finally, `kmassesssimulation` takes a whole data set, i.e. a collection of response patterns, and does an assessment for each of these patterns. Its result is a data frame which should be suitable for further statistical evaluation, especially if it is called several times with variant parameters (e.g., structures, update parameters, update and question rules).

Both, `kmsassess` and `kmassesssimulation` call `kmassess`.

Problems:

In rare cases `kmassess` may flip forth and back between probability distributions resulting in an endless loop. Therefore, it stops after twice the number of items delivering a NULL result.

References

Doignon, J.-P. & Falmagne, J.-C. (1985). Spaces for the assessment of knowledge. *International Journal of Man-Machine-Studies*, 23, 175-196. doi:10.1016/S00207373(85)800316.

Doignon, J.-P. & Falmagne, J.-C. (1999). *Knowledge Spaces*. Springer Verlag, Berlin. doi:10.1007/9783642586255.

Falmagne, J.-C. & Doignon, J.-P. (1988). A class of stochastic procedures for the assessment of knowledge. *British Journal of Mathematical and Statistical Psychology*, 41, 1-23. doi:10.1111/j.20448317.1988.tb00884.x.

Hoxkemeyer, C. (2002). A comparison of non-deterministic procedures for the adaptive assessment of knowledge. *Psychologische Beiträge*, 44(4), 495-503.

See Also

Other Knowledge assessment: `kmassessbayesian()`, `kmassesshalfsplit()`, `kmassessinformativ()`, `kmassessmentsimulation()`, `kmassessmultiplicative()`

Other Knowledge assessment: `kmassessbayesian()`, `kmassesshalfsplit()`, `kmassessinformativ()`, `kmassessmentsimulation()`, `kmassessmultiplicative()`

Examples

```
kmassess(c(1, 1, 0, 0),
         cbind(as.data.frame(as.matrix(rep(1/9.0, 9), ncol=1)), xpl$space),
         "halfsplit",
         "Bayesian",
         rep(0.12, 4),
         rep(0.1, 4),
         NULL,
         NULL,
```

```

      0.55
    )

kmassess(c(1,1,0,0), xpl$space, "halfsplit", "Bayesian", 0.1, 0.1, NULL, NULL, 0.55)

```

kmassessbayesian

Update probability distribution applying Bayesian update

Description

kmassessbayesian updates a probability distribution over a knowledge structure according to the Bayesian update rule.

Usage

```
kmassessbayesian(probs, ks, beta, eta, question, response)
```

Arguments

probs	Probability distribution over the knowledge structure (vector)
ks	Binary matrix of the knowledge structure
beta	Vector of careless error probabilities
eta	Vector of lucky guess probabilities
question	Item that has been posed
response	Correctness of received response (0 or 1)

Value

Updated probability vector

See Also

Other Knowledge assessment: [kmassess\(\)](#), [kmassesshalfsplit\(\)](#), [kmassessinformativ\(\)](#), [kmassessmentsimulation\(\)](#), [kmassessmultiplicative\(\)](#)

Examples

```

kmassessbayesian(c(0.02, 0.1, 0.07, 0.01, 0.4, 0.17, 0.07, 0.08, 0.08),
  xpl$space,
  rep(0.2,4),
  rep(0.1,4),
  3,
  1
)

```

kmassesshalfsplit	<i>Determine next question for probabilistic knowledge assessment</i>
-------------------	---

Description

kmassesshalfsplit determines the next question in a probabilistic assessment according to the halfsplit rule.

Usage

```
kmassesshalfsplit(probs, ks)
```

Arguments

probs	Probability distribution over the knowledge structure (vector)
ks	Binary matrix of the knowledge structure

Value

Number of the selected question

See Also

Other Knowledge assessment: [kmassess\(\)](#), [kmassessbayesian\(\)](#), [kmassessinformativ\(\)](#), [kmassessmentssimulation\(\)](#), [kmassessmultiplicative\(\)](#)

Examples

```
kmassesshalfsplit(c(0.02, 0.1, 0.07, 0.01, 0.4, 0.17, 0.07, 0.08, 0.08),
  xpl$space)
```

kmassessinformativ	<i>Determine next question for probabilistic knowledge assessment</i>
--------------------	---

Description

kmassessinformativ determines the next question in a probabilistic assessment according to the informative rule.

Usage

```
kmassessinformativ(probs, ks, update, beta, eta, zeta0, zeta1)
```

Arguments

probs	Probability distribution over the knowledge structure (vector)
ks	Binary matrix of the knowledge structure
update	Update rule ("Bayesian" or "multiplicative")
beta	Careless error probabilities (vector)
eta	Lucky guess probabilities (vector)
zeta0	Vector of update parameters for wrong responses
zeta1	Vector of update parameters for correct responses

Value

Number of the selected question

See Also

Other Knowledge assessment: [kmassess\(\)](#), [kmassessbayesian\(\)](#), [kmassesshalfsplit\(\)](#), [kmassessmentsimulation\(\)](#), [kmassessmultiplicative\(\)](#)

Examples

```
kmassessinformativ(c(0.02, 0.1, 0.07, 0.01, 0.4, 0.17, 0.07, 0.08, 0.08),
  xpl$space,
  "Bayesian",
  rep(0.3,4),
  rep(0.2,4),
  NULL,
  NULL
)
```

kmassessmentsimulation

Simulate assessments for a set of response patterns

Description

kmassessmentsimulation does a probabilistic knowledge assessment for each response pattern in a data matrix and stores information about the assessment.

Usage

```
kmassessmentsimulation(  
  respdata,  
  ks,  
  questioning,  
  update,  
  beta,  
  eta,  
  zeta0,  
  zeta1,  
  threshold  
)
```

Arguments

respdata	Data matrix
ks	Knowledge structure
questioning	Question rule
update	Updating rule
beta	Careless error probability
eta	Lucky guess probability
zeta0	Update parameter for wrong responses
zeta1	Update parameter for correct responses
threshold	Stopping criterion

Details

kmassessmentsimulation applies the kmsassess function.

Value

Assessment data as data frame

See Also

Other Knowledge assessment: [kmassess\(\)](#), [kmassessbayesian\(\)](#), [kmassesshalfsplit\(\)](#), [kmassessinformativ\(\)](#), [kmassessmultiplicative\(\)](#)

Examples

```
kmassessmentsimulation(  
  xpl$data,  
  xpl$space,  
  "halfsplit",  
  "multiplicative",  
  NULL,  
  NULL,
```

```

    5,
    5,
    0.55
  )

```

kmassessmultiplicative

Update probability distribution applying multiplicative rule

Description

kmassessmultiplicative updates a probability distribution on a knowledge structure according to the multiplicative rule.

Usage

```
kmassessmultiplicative(probs, ks, zeta0, zeta1, question, response)
```

Arguments

probs	Probability distribution over the knowledge structure (vector)
ks	Binary matrix of the knowledge structure
zeta0	Vector of update parameters for wrong responses
zeta1	Vector of update parameters for correct responses
question	Item that has been posed
response	Correctness of received response (0 or 1)

Value

Updated probability vector

See Also

Other Knowledge assessment: [kmassess\(\)](#), [kmassessbayesian\(\)](#), [kmassesshalfsplit\(\)](#), [kmassessinformativ\(\)](#), [kmassessmentsimulation\(\)](#)

Examples

```

kmassessmultiplicative(c(0.02, 0.1, 0.07, 0.01, 0.4, 0.17, 0.07, 0.08, 0.08),
  xpl$space,
  rep(1.2,4),
  rep(2.1,4),
  3,
  1
)

```

kmbasis	<i>Generic kmbasis() function</i>
---------	-----------------------------------

Description

Generic kmbasis() function

Usage

```
kmbasis(x, ...)
```

Arguments

x	Family of sets or surmise relation in matrix representation
...	Optional additional parameters

Value

Basis for a knowledge space

kmbasis.kmsurmisefunction	<i>Determine the basis for a surmise function</i>
---------------------------	---

Description

Determine the basis for a surmise function

Usage

```
## S3 method for class 'kmsurmisefunction'
kmbasis(x, ...)
```

Arguments

x	Surmise Function
...	Optional/future parameters

Value

Basis

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmSR2basis\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmisefunction\(\)](#), [kmsurmiserelation\(\)](#), [kmunionclosure\(\)](#)

kmbasis.kmsurmiserelation

Determine the basis of a knowledge space from a surmise relation

Description

kmbasis.kmsurmiserelation takes a surmise relation and returns the corresponding basis.

Usage

```
## S3 method for class 'kmsurmiserelation'
kmbasis(x, ...)
```

Arguments

x	Surmise relation
...	Space for additional, optional arameters

Value

Basis

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmSR2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmisefunction\(\)](#), [kmsurmiserelation\(\)](#), [kmunionclosure\(\)](#)

kmbasis.matrix

Compute the basis of a knowledge space

Description

kmbasis.matrix returns a matrix representing the basis of a knowledge space. If x is a knowledge structure or an arbitrary family of sets kmreduction returns the basis of the smallest knowledge space containing x.

Usage

```
## S3 method for class 'matrix'
kmbasis(x, ...)
```

Arguments

x	Binary matrix representing a knowledge space
...	Space or future, optional parameters

Value

Binary matrix representing the basis of the knowledge space.

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmSR2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmsurmisefunction\(\)](#), [kmsurmiserelation\(\)](#), [kmunionclosure\(\)](#)

Examples

```
kmbasis(xpl$space)
```

kmbasisfringe	<i>Compute the fringe of a state within a knowledge structure using its basis</i>
---------------	---

Description

kmbasisfringe computes the fringe of a state within a knowledge structure, i.e. the set of items by which the state differs from its neighbours.

Usage

```
kmbasisfringe(state, basis)
```

```
kmbasisinnerfringe(state, basis)
```

```
kmbasisouterfringe(state, basis)
```

Arguments

state	Binary vector representing a knowledge state
basis	kmbasis object

Value

Binary vector representing the fringe

References

Hockemeyer C (1997). Using the Basis of a Knowledge Space for Determining the Fringe of a Knowledge State. *Journal of Mathematical Psychology*, 41, 275–279.

See Also

Other Fringes & learning paths: [kmbasisneighbourhood\(\)](#), [kmfringe\(\)](#), [kmgradations\(\)](#), [kmlearningpaths\(\)](#), [kmneighbourhood\(\)](#), [kmnneighbourhood\(\)](#)

Examples

```
kmbasisfringe(c(1,0,0,0), xpl$basis)
```

kmbasisneighbourhood	<i>Compute the neighbourhood of a state within a knowledge structure using its basis</i>
----------------------	--

Description

kmbasisneighbourhood computes the neighbourhood of a state within a knowledge structure, i.e. the family of all other states with a symmetric set difference of 1.

Usage

```
kmbasisneighbourhood(state, basis, include = FALSE)
```

Arguments

state	Binary vector representing a knowledge state
basis	kmbasis object
include	Boolean whether the original state should be included in the result (default FALSE)

Value

Matrix containing the neighbouring states, one per row

See Also

Other Fringes & learning paths: [kmbasisfringe\(\)](#), [kmfringe\(\)](#), [kmgradations\(\)](#), [kmlearningpaths\(\)](#), [kmneighbourhood\(\)](#), [kmnneighbourhood\(\)](#)

Examples

```
kmbasisneighbourhood(c(1,1,0,0), xpl$basis)
```

`kmcolors`*Determine a color vector based on probabilities*

Description

`kmcolors` takes a probability vector and a color palette and creates a color vector to be used with `kstMatrix::plot`.

Usage

```
kmcolors(prob, palette = cm.colors)
```

Arguments

<code>prob</code>	Probability vector
<code>palette</code>	Color palette (default = <code>cm.colors</code>)

See Also

Other Plotting knowledge structures: [plot\(\)](#)

Other Utilities: [kmdoubleequal\(\)](#), [kmsetiselement\(\)](#), [kmsymmsetdiff\(\)](#)

`kmdist`*Compute the distance between a data set and a knowledge structure*

Description

`kmdist` returns a named vector with the frequencies of distances between a set of response patterns and a knowledge structure. This vector can be used to compute, e.g., the Discrepancy Index (DI) or the Distance Agreement Coefficient (DA).

Usage

```
kmdist(data, struct)
```

Arguments

<code>data</code>	Binary matrix representing a set of response patterns
<code>struct</code>	Binary matrix representing a knowledge structure

Value

Distance distribution vector

See Also

Other Validating knowledge spaces: [kmSRvalidate\(\)](#), [kmvalidate\(\)](#)

Examples

```
kmdist(xpl$data, xpl$space)
```

kmdoubleequal	<i>Test two double numbers on equity with a certain tolerance</i>
---------------	---

Description

Test two double numbers on equity with a certain tolerance

Usage

```
kmdoubleequal(x, y, tol = sqrt(.Machine$double.eps))
```

Arguments

- | | |
|-----|--------------------------|
| x | First double to compare |
| y | Second double to compare |
| tol | Tolerance optional) |

Value

Boolean for (approximate) equity

See Also

Other Utilities: [kmcolors\(\)](#), [kmsetiselement\(\)](#), [kmsymmsetdiff\(\)](#)

Examples

```
kmdoubleequal(0.5+0.5, 1)
```

kmeqreduction	<i>Reduce a family of knowledge states with respect to item equivalence</i>
---------------	---

Description

kmeqreduction takes a family of knowledge states and returns its reduction to non-equivalent items.

Usage

```
kmeqreduction(x)
```

Arguments

x	Binary matrix
---	---------------

Value

Binary matrix reduced by equivalences

See Also

Other Properties of knowledge structures: [kmiswellgraded\(\)](#), [kmnotions\(\)](#)

Examples

```
kmeqreduction(xpl$space)
```

kmfamset	<i>Convert a binary matrix to a kmfamset object (family of sets)</i>
----------	--

Description

kmfamset returns a kmfamset object after checking that the passed object is a binary matrix with all different rows. If the passed object inherits the kmfamset property, nothing else is changed.

Usage

```
kmfamset(x)
```

Arguments

x	Binary matrix representing a family of sets
---	---

Value

kmfamset object

See Also

Other Constructors: [kmspace\(\)](#), [kmstructure\(\)](#)

Examples

```
m <- as.matrix(c(1,0,0,0,1,0,1,1,1), nrow=3, byrow=TRUE)
kmfamset(m)
```

kmfringe

Compute the fringe of a state within a knowledge structure

Description

kmfringe computes the fringe of a state within a knowledge structure, i.e. the set of items by which the state differs from its neighbours.

Usage

```
kmfringe(state, struct)
```

```
kminnerfringe(state, struct)
```

```
kmouterfringe(state, struct)
```

Arguments

state	Binary vector representing a knowledge state
struct	Binary matrix representing a knowledge structure

Value

Binary vector representing the fringe

See Also

Other Fringes & learning paths: [kmbasisfringe\(\)](#), [kmbasisneighbourhood\(\)](#), [kmgradations\(\)](#), [kmlearningpaths\(\)](#), [kmneighbourhood\(\)](#), [kmnneighbourhood\(\)](#)

Examples

```
kmfringe(c(1,0,0,0), xpl$space)
```

kmgenerate

Generate a knowledge structure from a set of response patterns

Description

kmgenerate returns a matrix representing a knowledge structure generated from data. It uses a simplistic approach: patterns with a frequency above a specified threshold are considered as knowledge states. If the specified threshold is 0 (default) a real threshold is computed as N (number of response patterns) divided by $2^{|Q|}$. Please note that the number of response patterns should be much higher than the size of the power set of the item set Q . A factor of at least 10 is recommended. Currently, the number of items is limited to the number of bits in a C long minus one (i.e. 31 under Windows and 63 otherwise). But we would probably run into memory problems way earlier anyway.

Usage

```
kmgenerate(x, threshold = 0)
```

Arguments

x	Binary matrix representing a data set
threshold	Threshold for taking response patterns as knowledge states (default 0)

Value

Binary matrix representing the generated knowledge structure

See Also

Other Generating knowledge spaces: [kmiita2SR\(\)](#)

Examples

```
kmgenerate(xpl$sim, 15)
```

kmgradations

Determine all gradations between two states

Description

Determine all gradations between two states

Usage

```
kmgradations(structure, from = NULL, to = NULL)
```

Arguments

structure	Knowledge structure
from	Starting state (if NULL (default), it is the empty set)
to	Goal state (if NULL (default), it is the full item set)

Value

A list of gradations where each gradation is a list of states

See Also

Other Fringes & learning paths: [kmbasisfringe\(\)](#), [kmbasisneighbourhood\(\)](#), [kmfringe\(\)](#), [kmlearningpaths\(\)](#), [kmneighbourhood\(\)](#), [kmnneighbourhood\(\)](#)

Examples

```
kmgradations(xpl$space)
```

kmiita2SR

Convert an IITA result into a surmise relation matrix

Description

kmiita2SR takes the result of a `DAKS::iita()` call and delivers the matrix of the computed surmise relation.

Usage

```
kmiita2SR(ii, names = NULL, items = 0)
```

Arguments

ii	iita() result
names	Vector of item names (default NULL)
items	Minimal number of items (default 0)

Value

Surmise relation matrix

The `iita()` function loses information on the item names and uses consecutive numbers instead. The implications part of its result does not give any hint on isolated items, i.e. items which neither have a prerequisite nor are prerequisite of any other item. Therefore, a minimal number of items can be passed to `kmiita2SR()`. If the highest item number within implications is higher, this `items` parameter is ignored.

See Also

Other Generating knowledge spaces: [kmgenerate\(\)](#)

kmiswellgraded	<i>Check for wellgradedness of a knowledge structure</i>
----------------	--

Description

kmiswellgraded returns whether a knowledge structure is wellgraded.

Usage

```
kmiswellgraded(x)
```

Arguments

x	Binary matrix representing a knowledge space
---	--

Value

Logical value specifying whether x is wellgraded

References

Doignon, J.-P. & Falmagne, J.-C. (1999). *Knowledge Spaces*. Springer-Verlag, Berlin.

See Also

Other Properties of knowledge structures: [kmeqreduction\(\)](#), [kmnotions\(\)](#)

Examples

```
kmiswellgraded(xpl$space)
```

kmlearningpaths	<i>Determine all learning paths in a knowledge structure</i>
-----------------	--

Description

Determine all learning paths in a knowledge structure

Usage

```
kmlearningpaths(structure)
```

Arguments

structure	Knowledge structure
-----------	---------------------

Value

A list of learning paths where each learning path is a list of states

See Also

Other Fringes & learning paths: [kmbasisfringe\(\)](#), [kmbasisneighbourhood\(\)](#), [kmfringe\(\)](#), [kmgradations\(\)](#), [kmneighbourhood\(\)](#), [kmnneighbourhood\(\)](#)

Examples

```
kmlearningpaths(xpl$space)
```

kmneighbourhood	<i>Compute the neighbourhood of a state within a knowledge structure</i>
-----------------	--

Description

kmneighbourhood computes the neighbourhood of a state within a knowledge structure, i.e. the family of all other states with a symmetric set difference of 1.

Usage

```
kmneighbourhood(state, struct, include = FALSE)
```

Arguments

state	Binary vector representing a knowledge state
struct	Binary matrix representing a knowledge structure
include	Boolean whether the original state should be included in the result (default FALSE)

Value

Matrix containing the neighbouring states, one per row

See Also

Other Fringes & learning paths: [kmbasisfringe\(\)](#), [kmbasisneighbourhood\(\)](#), [kmfringe\(\)](#), [kmgradations\(\)](#), [kmlearningpaths\(\)](#), [kmnneighbourhood\(\)](#)

Examples

```
kmneighbourhood(c(1,1,0,0), xpl$space)
```

kmneighbourhood	<i>Compute the n-neighbourhod of a state within a knowledge structure</i>
-----------------	---

Description

kmnneighbourhood computes the n-neighbourhood of a state within a knowledge structure, i.e. the family of all other states with a symmetric set difference maximal n.

Usage

```
kmnneighbourhood(state, struct, distance, include = FALSE)
```

Arguments

state	Binary vector representing a knowledge state
struct	Binary matrix representing a knowledge structure
distance	Size of the n-neighbourhood
include	Boolean whether the original state should be included (default FALSE)

Value

Matrix containing the neighbouring states, one per row

See Also

Other Fringes & learning paths: [kmbasisfringe\(\)](#), [kmbasisneighbourhood\(\)](#), [kmfringe\(\)](#), [kmgradations\(\)](#), [kmlearningpaths\(\)](#), [kmneighbourhood\(\)](#)

Examples

```
kmnneighbourhood(c(1,1,0,0), xpl$space, 2)
```

kmnotions

Determine the notions of a knowledge structure

Description

kmnotions returns a matrix representing the notions of a knowledge structure.

Usage

```
kmnotions(x)
```

Arguments

x Binary matrix representing a knowledge structure

Value

Binary matrix representing notions in the knowledge structure

The matrix has a '1' in row 'i' and column 'j' if 'i' and 'j' belong to the same notion (i.e. are equivalent). It is a symmetric matrix with '1's in the main diagonal.

See Also

Other Properties of knowledge structures: [kmeqreduction\(\)](#), [kmiswellgraded\(\)](#)

Examples

```
kmnotions(xpl$space)
```

kmsetiselement

Test if a state is contained in a family of states

Description

Test if a state is contained in a family of states

Usage

```
kmsetiselement(s, f)
```

Arguments

s State
f Family of sets

Value

Boolean is s is contained in f

See Also

Other Utilities: [kmcolors\(\)](#), [kmdoubleequal\(\)](#), [kmsymmsetdiff\(\)](#)

Examples

```
kmsetiselement(c(1,1,1,0), xpl$space)
```

kmSF2basis

Derive a basis from a surmise function

Description

kmSF2basis expects a surmise function data frame and returns the corresponding basis.

Usage

```
kmSF2basis(sf)
```

Arguments

sf Surmise function

Value

Matrix representing the basis.

See Also

Other Different representations for knowledge spaces: [kmSR2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmisefunction\(\)](#), [kmsurmiserelation\(\)](#), [kmunionclosure\(\)](#)

kmsimulate

Simulate a set of response patterns according to the BLIM

Description

kmsimulate returns a data set of n simulated response patterns based on the knowledge structure x given as a binary matrix. The simulation follows the BLIM (Basic Local Independence Model; see Doignon & Falmagne, 1999).

Usage

```
kmsimulate(x, n, beta, eta)
```

Arguments

x	Binary matrix representing a knowledge space
n	Number of simulated response patterns
β	Careless error probability value or vector
η	Lucky guess probability value or vector

Details

The β and η parameters must be either single numerals or vectors with a length identical to the number of rows in the x matrix. A mixture is possible.

The sample function used by kmsimulate might work inaccurately for knowledge structures x with 2^{31} or more states.

Value

Binary matrix representing the simulated data set

References

Doignon, J.-P. & Falmagne, J.-C. (1999). *Knowledge Spaces*. Springer-Verlag, Berlin.

Examples

```
kmsimulate(xpl$space, 50, 0.2, 0.1)
kmsimulate(xpl$space, 50, c(0.2, 0.25, 0.15, 0.2), c(0.1, 0.15, 0.05, 0.1))
kmsimulate(xpl$space, 50, c(0.2, 0.25, 0.15, 0.2), 0)
```

kmspace	<i>Convert a binary matrix to a kmspace object</i>
---------	--

Description

kmspace() returns a kmspace object for a binary matrix.

Usage

```
kmspace(x)
```

Arguments

x Binary matrix representing a family of sets

Value

kmspace object

See Also

Other Constructors: [kmfamset\(\)](#), [kmstructure\(\)](#)

Examples

```
m <- as.matrix(c(1,0,0,0,1,0,1,1,1), nrow=3, byrow=TRUE)
kmspace(m)
```

kmSR2basis	<i>Determine the basis of a knowledge space from a surmise relation</i>
------------	---

Description

kmSR2basis takes a surmise relation and returns the corresponding basis.

Usage

```
kmSR2basis(sr)
```

Arguments

sr Surmise relation

Value

Basis

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmisefunction\(\)](#), [kmsurmiserelation\(\)](#), [kmunionclosure\(\)](#)

`kmSRvalidate`*Validate a surmise relation against a data set*

Description

`kmSRvalidate` returns a list with two elements, Goodman & Kruskal's gamma value and the violational coefficient (VC).

Usage

```
kmSRvalidate(data, sr)
```

Arguments

<code>data</code>	Binary matrix representing a set of response patterns
<code>sr</code>	Binary matrix representing a surmise relation

Value

A list with two elements:

gamma Goodman & Kruskal's gamma index

VC Violational Coefficient

See Also

Other Validating knowledge spaces: [kmdist\(\)](#), [kmvalidate\(\)](#)

Examples

```
kmSRvalidate(xpl$data, xpl$sr)
```

kmstructure	<i>Convert a binary matrix to a kmstructure object</i>
-------------	--

Description

kmstructure() returns a kmstructure object after checking that the passed object is a binary matrix without double rows. The empty set and the full item set are added if missing.

Usage

```
kmstructure(x)
```

Arguments

x Binary matrix representing a family of sets

Value

kmstructure object

See Also

Other Constructors: [kmfamset\(\)](#), [kmspace\(\)](#)

Examples

```
m <- as.matrix(c(1,0,0,0,1,0,1,1,1), nrow=3, byrow=TRUE)
kmstructure(m)
```

kmsurmisefunction	<i>Compute the surmise function for a knowledge space or basis</i>
-------------------	--

Description

kmsurmisefunction returns a data frame representing the surmise function for a knowledge space or basis. The rows of the data frame are ordered by item name.

Usage

```
kmsurmisefunction(x)
```

Arguments

x Binary matrix representing a knowledge space or basis

Value

Data frame representing the surmise unction of x.

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmSR2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmiserelation\(\)](#), [kmunionclosure\(\)](#)

Examples

```
kmsurmisefunction(xpl$space)
```

kmsurmiserelation	<i>Compute the surmise relation of a quasi-ordinal knowledge space</i>
-------------------	--

Description

kmsurmiserelation returns a matrix representing the surmise relation of a quasi-ordinal knowledge space. If x is a general knowledge space, a knowledge structure or an arbitrary family of sets, kmsurmiserelation returns the surmise relation of the smallest quasi-ordinal knowledge space containing x.

Usage

```
kmsurmiserelation(x)
```

Arguments

x Binary matrix representing a quasi-ordinal knowledge space

Value

Binary matrix representing the surmise relation of the corresponding quasi-ordinal knowledge space

Note: The columns of the surmise relation matrix describe the minimal state for the respective item in the quasi-ordinal knowledge space.

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmSR2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmisefunction\(\)](#), [kmunionclosure\(\)](#)

Examples

```
kmsurmiserelation(xpl$space)
```

kmsymmsetdiff	<i>Compute the symmetric set difference between two sets</i>
---------------	--

Description

Compute the symmetric set difference between two sets

Usage

```
kmsymmsetdiff(x, y)
```

```
kmsetdistance(x, y)
```

Arguments

x	Binary vector representing a set
y	Binary vector representing a set

Value

kmsymmsetdiff: Symmetric set difference between 'x' and 'y'

kmsetdistance: Distance between the sets 'x' and 'y', i.e. the cardinality of the symmetric set difference

See Also

Other Utilities: [kmcolors\(\)](#), [kmdoubleequal\(\)](#), [kmsetiselement\(\)](#)

Other Utilities: [kmcolors\(\)](#), [kmdoubleequal\(\)](#), [kmsetiselement\(\)](#)

Examples

```
kmsymmsetdiff(c(1,0,0), c(1,1,0))
```

```
kmsetdistance(c(1,0,0), c(1,1,0))
```

kmtrivial	<i>Create trivial knowledge spaces</i>
-----------	--

Description

These functions create trivial knowledge spaces of a given item number. The minimal space contains just the empty set and the full item set while the maximal space is equal to the power set.

Usage

```
kmminimalspace(noi)
```

```
kmmaximalspace(noi)
```

Arguments

noi	Number of items
-----	-----------------

Details

Please note that the computation time for creating large power sets can grow quite large easily.

Value

A binary matrix representing the respective knowledge space

Examples

```
kmminimalspace(5)
kmmaximalspace(5)
```

kmunionclosure	<i>Close a family of sets under union</i>
----------------	---

Description

kmunionclosure returns a matrix representing a knowledge space. Please note that it may take quite some time for computing larger knowledge spaces.

Usage

```
kmunionclosure(x)
```

Arguments

x	Binary matrix representing a family of sets
---	---

Value

Binary matrix representing the corresponding knowledge space, i.e. the closure of the family under union including the empty set and the full set.

kmunionclosure implements the irredundant algorithm developed by Dowling (1993).

References

Dowling, C. E. (1993). On the irredundant construction of knowledge spaces. *Journal of Mathematical Psychology*, 37, 49–62.

See Also

Other Different representations for knowledge spaces: [kmSF2basis\(\)](#), [kmSR2basis\(\)](#), [kmbasis.kmsurmisefunction\(\)](#), [kmbasis.kmsurmiserelation\(\)](#), [kmbasis.matrix\(\)](#), [kmsurmisefunction\(\)](#), [kmsurmiserelation\(\)](#)

Examples

```
kmunionclosure(xpl$basis)
```

kmvalidate

Validate a knowledge structure against a data set

Description

kmvalidate returns a list with three elements, a named vector (dist) with the frequencies of distances between a set of response patterns and a knowledge structure, the Discrepancy Index (DI), and the Distance Agreement Coefficient (DA).

Usage

```
kmvalidate(data, struct)
```

Arguments

data	Binary matrix representing a set of response patterns
struct	Binary matrix representing a knowledge structure

Value

A list with three elements:

dist Distance distribution vector

DI Discrepancy Index

DA Distance Agreement Coefficient

Warning

The DA computation can take quite some time for larger item sets as the power set has to be computed. For item sets with around 30 items or more, it may even crash the system due to huge memory requests.

See Also

Other Validating knowledge spaces: [kmSRvalidate\(\)](#), [kmdist\(\)](#)

Examples

```
kmvalidate(xpl$data, xpl$space)
```

phsg	<i>Knowledge space on linear functions</i>
------	--

Description

Basis of a small knowledge space and list of items on linear functions used in a manuscript by Steiner et al.

Usage

```
phsg
```

Format

A list containing the basis and the list of items

See Also

Other Data: [cad](#), [fractions](#), [readwrite](#), [xpl](#)

plot	<i>Plot a Hasse diagram</i>
------	-----------------------------

Description

plot takes a matrix representing a family of sets (knowledge states) or a surmise relation and a color vector, and draws a Hasse diagram. If the color vector is NULL the states are drawn in green, the items in the relation are drawn in orange.

Usage

```
## S3 method for class 'kmfamset'
plot(
  x,
  ...,
  horizontal = FALSE,
  colors = NULL,
  keepNames = TRUE,
  itemsep = ",",
  braces = TRUE,
  vertexshape = "oval",
  arrowhead = "none",
  arrowtail = "none",
  edgelabel = FALSE
)

## S3 method for class 'kmneighbourhood'
plot(
  x,
  ...,
  horizontal = FALSE,
  colors = c("#eeee00", "#aaccff", "#bbffbb"),
  keepNames = TRUE,
  itemsep = ",",
  braces = TRUE,
  vertexshape = "oval",
  arrowhead = "none",
  arrowtail = "none",
  edgelabel = FALSE,
  state
)

## S3 method for class 'kmsurmiserection'
plot(
  x,
  ...,
  horizontal = FALSE,
  colors = NULL,
  keepNames = TRUE,
  vertexshape = "circle",
  arrowhead = "none",
  arrowtail = "none"
)
```

Arguments

x	Binary matrix representing a family of sets
...	Optional inherited parameters

horizontal	Boolean defining orientation of the graph, default FALSE
colors	Color value or vector (default NULL).
keepNames	Keep item names (default TRUE)
itemsep	Item separator in sets (default ','; only for families of states)
braces	Put braces around vertices (default TRUE; only for families of states)
vertexshape	Shape of the vertex objects, e.g. circle, oval, box, or none. See Graphviz Node Shapes for a complete list of possible values.
arrowhead	Form of the arrow head, e.g. vee or none (default). See Graphviz Arrow Types for a complete list of possible values. This may be used for vertical graphs although none is the standard there.
arrowtail	Form of the arrow tail, e.g. vee or none (default). See Graphviz Arrow Types for a complete list of possible values. This should be used for horizontal graphs.
edgelabel	Boolean whether to label the edges of the diagram (default FALSE)
state	Knowledge state whose neighbourhood is to be pictured

See Also

Other Plotting knowledge structures: [kmcOLORS\(\)](#)

readwrite	<i>Knowledge spaces on reading and writing abilities</i>
-----------	--

Description

Bases of knowledge spaces on reading/writing abilities obtained from querying experts.

Usage

readwrite

Format

A list containing four bases (rw1 to rw3, and rwmaj) in binary matrix form. Each matrix has 48 columns representing the different knowledge items and a varying number of rows containing the basis elements.

Details

Three experts were queried about prerequisite relationships between 48 items on reading and writing abilities (Dowling, 1991; 1993). A forth basis represents those prerequisite relationships on which the majority of the experts agree (Dowling & Hockemeyer, 1998).

References

- Dowling, C. E. (1991). *Constructing Knowledge Structures from the Judgements of Experts*. Habilitationsschrift, Technische Universität Carolo-Wilhelmina, Braunschweig, Germany.
- Dowling, C. E. (1993). Applying the basis of a knowledge space for controlling the questioning of an expert. *Journal of Mathematical Psychology*, 37, 21–48.
- Dowling, C. E. & Hockemeyer, C. (1998). Computing the intersection of knowledge spaces using only their basis. In Cornelia E. Dowling, Fred S. Roberts, & Peter Theuns, editors, *Recent Progress in Mathematical Psychology*, pp. 133–141. Lawrence Erlbaum Associates Ltd., Mahwah, NJ.

See Also

Other Data: [cad](#), [fractions](#), [phsg](#), [xpl](#)

xpl

Small example knowledge space

Description

Basis and space matrix, surmise relation and surmise function of a small fictional knowledge space, and two data sets (data (7 patterns) and sim (500 patterns)) to be used in examples. The latter was produced from the space with `kmsimulate()` with beta and eta values of 0.1.

Usage

`xpl`

Format

A list containing the basis, the space, the surmise relation, the surmise function, and the two data matrices data and sim.

See Also

Other Data: [cad](#), [fractions](#), [phsg](#), [readwrite](#)

Index

- * **Constructors**
 - kmfamset, 19
 - kmspace, 29
 - kmstructure, 31
 - * **Data**
 - cad, 3
 - fractions, 4
 - phsg, 36
 - readwrite, 38
 - xpl, 39
 - * **Different representations for knowledge spaces**
 - kmbasis.kmsurmisefunction, 13
 - kmbasis.kmsurmiserelation, 14
 - kmbasis.matrix, 14
 - kmSF2basis, 27
 - kmSR2basis, 29
 - kmsurmisefunction, 31
 - kmsurmiserelation, 32
 - kmunionclosure, 34
 - * **Fringes & learning paths**
 - kmbasisfringe, 15
 - kmbasisneighbourhood, 16
 - kmfringe, 20
 - kmgradations, 21
 - kmlearningpaths, 24
 - kmneighbourhood, 24
 - kmneighbourhood, 25
 - * **Generating knowledge spaces**
 - kmgenerate, 21
 - kmiita2SR, 22
 - * **Knowledge assessment**
 - kmassess, 4
 - kmassessbayesian, 8
 - kmassesshalfsplit, 9
 - kmassessinformativ, 9
 - kmassessmentsimulation, 10
 - kmassessmultiplicative, 12
 - * **Plotting knowledge structures**
 - kmcolors, 17
 - plot, 36
 - * **Properties of knowledge structures**
 - kmqreduction, 19
 - kmiswellgraded, 23
 - kmnotions, 26
 - * **Simulating response patterns**
 - kmsimulate, 28
 - * **Trivial knowledge spaces**
 - kmtrivial, 34
 - * **Utilities**
 - kmcolors, 17
 - kmdoubleequal, 18
 - kmsetiselement, 26
 - kmsymmsetdiff, 33
 - * **Validating knowledge spaces**
 - kmdist, 17
 - kmSRvalidate, 30
 - kmvalidate, 35
 - * **datasets**
 - cad, 3
 - fractions, 4
 - phsg, 36
 - readwrite, 38
 - xpl, 39
- Assessment (kmassess), 4
- cad, 3, 4, 36, 39
- fractions, 3, 4, 36, 39
- kmassess, 4, 8–12
- kmassessbayesian, 7, 8, 9–12
- kmassesshalfsplit, 7, 8, 9, 10–12
- kmassessinformativ, 7–9, 9, 11, 12
- kmassessmentsimulation, 7–10, 10, 12
- kmassessmultiplicative, 7–11, 12
- kmbasis, 13
- kmbasis.kmsurmisefunction, 13, 14, 15, 27, 30, 32, 35

kmbasis.kmsurmiserection, [13](#), [14](#), [15](#), [27](#),
[30](#), [32](#), [35](#)
kmbasis.matrix, [13](#), [14](#), [14](#), [27](#), [30](#), [32](#), [35](#)
kmbasisfringe, [15](#), [16](#), [20](#), [22](#), [24](#), [25](#)
kmbasisinnerfringe (kmbasisfringe), [15](#)
kmbasisneighbourhood, [15](#), [16](#), [20](#), [22](#), [24](#), [25](#)
kmbasisouterfringe (kmbasisfringe), [15](#)
kmcOLORS, [17](#), [18](#), [27](#), [33](#), [38](#)
kmdist, [17](#), [30](#), [36](#)
kmdoubleequal, [17](#), [18](#), [27](#), [33](#)
kmeqreduction, [19](#), [23](#), [26](#)
kmfamset, [19](#), [29](#), [31](#)
kmfringe, [15](#), [16](#), [20](#), [22](#), [24](#), [25](#)
kmgenerate, [21](#), [23](#)
kmgradations, [15](#), [16](#), [20](#), [21](#), [24](#), [25](#)
kmiita2SR, [21](#), [22](#)
kminnerfringe (kmfringe), [20](#)
kmiswellgraded, [19](#), [23](#), [26](#)
kmllearningpaths, [15](#), [16](#), [20](#), [22](#), [24](#), [25](#)
kmmaximalspace (kmtrivial), [34](#)
kmminimalspace (kmtrivial), [34](#)
kmneighbourhood, [15](#), [16](#), [20](#), [22](#), [24](#), [24](#), [25](#)
kmnneighbourhood, [15](#), [16](#), [20](#), [22](#), [24](#), [25](#), [25](#)
kmnotions, [19](#), [23](#), [26](#)
kmouterfringe (kmfringe), [20](#)
kmsassess (kmsassess), [4](#)
kmsetdistance (kmsymmsetdiff), [33](#)
kmsetiselement, [17](#), [18](#), [26](#), [33](#)
kmSF2basis, [13–15](#), [27](#), [30](#), [32](#), [35](#)
kmsimulate, [28](#)
kmspace, [20](#), [29](#), [31](#)
kmSR2basis, [13–15](#), [27](#), [29](#), [32](#), [35](#)
kmSRvalidate, [18](#), [30](#), [36](#)
kmstructure, [20](#), [29](#), [31](#)
kmsurmisefunction, [13–15](#), [27](#), [30](#), [31](#), [32](#), [35](#)
kmsurmiserection, [13–15](#), [27](#), [30](#), [32](#), [32](#), [35](#)
kmsymmsetdiff, [17](#), [18](#), [27](#), [33](#)
kmtrivial, [34](#)
kmunionclosure, [13–15](#), [27](#), [30](#), [32](#), [34](#)
kmvalidate, [18](#), [30](#), [35](#)

phsg, [3](#), [4](#), [36](#), [39](#)
plot, [17](#), [36](#)

readwrite, [3](#), [4](#), [36](#), [38](#), [39](#)

xpl, [3](#), [4](#), [36](#), [39](#), [39](#)